
Sage 9.4 Reference Manual: Category Framework

Release 9.4

The Sage Development Team

Aug 24, 2021

CONTENTS

1	The Sage Category Framework	1
1.1	Elements, parents, and categories in Sage: a (draft of) primer	1
1.2	Categories	28
1.3	Axioms	64
1.4	Functors	98
1.5	Implementing a new parent: a (draft of) tutorial	102
2	Maps and Morphisms	105
2.1	Base class for maps	105
2.2	Homsets	114
2.3	Morphisms	122
2.4	Coercion via construction functors	126
3	Individual Categories	155
3.1	Group, ring, etc. actions on objects	155
3.2	Additive groups	158
3.3	Additive magmas	160
3.4	Additive monoids	171
3.5	Additive semigroups	172
3.6	Affine Weyl groups	174
3.7	Algebra ideals	177
3.8	Algebra modules	178
3.9	Algebras	178
3.10	Algebras With Basis	182
3.11	Aperiodic semigroups	187
3.12	Associative algebras	187
3.13	Bialgebras	187
3.14	Bialgebras with basis	189
3.15	Bimodules	193
3.16	Classical Crystals	194
3.17	Coalgebras	198
3.18	Coalgebras with basis	203
3.19	Commutative additive groups	205
3.20	Commutative additive monoids	207
3.21	Commutative additive semigroups	207
3.22	Commutative algebra ideals	208
3.23	Commutative algebras	208
3.24	Commutative ring ideals	209
3.25	Commutative rings	209
3.26	Complete Discrete Valuation Rings (CDVR) and Fields (CDVF)	213

3.27	Complex reflection groups	217
3.28	Common category for Generalized Coxeter Groups or Complex Reflection Groups	219
3.29	Coxeter Group Algebras	237
3.30	Coxeter Groups	240
3.31	Crystals	269
3.32	CW Complexes	293
3.33	Discrete Valuation Rings (DVR) and Fields (DVF)	296
3.34	Distributive Magmas and Additive Magmas	298
3.35	Division rings	299
3.36	Domains	300
3.37	Enumerated sets	301
3.38	Euclidean domains	307
3.39	Fields	309
3.40	Filtered Algebras	314
3.41	Filtered Algebras With Basis	315
3.42	Filtered Modules	322
3.43	Filtered Modules With Basis	324
3.44	Finite Complex Reflection Groups	338
3.45	Finite Coxeter Groups	355
3.46	Finite Crystals	367
3.47	Finite dimensional algebras with basis	367
3.48	Finite dimensional bialgebras with basis	386
3.49	Finite dimensional coalgebras with basis	386
3.50	Finite Dimensional Graded Lie Algebras With Basis	387
3.51	Finite dimensional Hopf algebras with basis	388
3.52	Finite Dimensional Lie Algebras With Basis	389
3.53	Finite dimensional modules with basis	405
3.54	Finite Dimensional Nilpotent Lie Algebras With Basis	413
3.55	Finite dimensional semisimple algebras with basis	414
3.56	Finite Enumerated Sets	416
3.57	Finite fields	422
3.58	Finite groups	423
3.59	Finite lattice posets	425
3.60	Finite monoids	428
3.61	Finite Permutation Groups	432
3.62	Finite posets	436
3.63	Finite semigroups	457
3.64	Finite sets	459
3.65	Finite Weyl Groups	460
3.66	Finitely Generated Lambda bracket Algebras	461
3.67	Finitely Generated Lie Conformal Algebras	462
3.68	Finitely generated magmas	463
3.69	Finitely generated semigroups	464
3.70	Function fields	466
3.71	G-Sets	467
3.72	Gcd domains	467
3.73	Generalized Coxeter Groups	468
3.74	Graded Algebras	469
3.75	Graded algebras with basis	470
3.76	Graded bialgebras	472
3.77	Graded bialgebras with basis	472
3.78	Graded Coalgebras	472
3.79	Graded coalgebras with basis	473
3.80	Graded Hopf algebras	474

3.81	Graded Hopf algebras with basis	474
3.82	Graded Lie Algebras	475
3.83	Graded Lie Algebras With Basis	476
3.84	Graded Lie Conformal Algebras	477
3.85	Graded modules	478
3.86	Graded modules with basis	479
3.87	Graphs	480
3.88	Group Algebras	482
3.89	Groupoid	487
3.90	Groups	487
3.91	Hecke modules	496
3.92	Highest Weight Crystals	497
3.93	Hopf algebras	504
3.94	Hopf algebras with basis	506
3.95	H-trivial semigroups	510
3.96	Infinite Enumerated Sets	511
3.97	Integral domains	512
3.98	J-trivial semigroups	512
3.99	Kac-Moody Algebras	513
3.100	Lambda Bracket Algebras	514
3.101	Lambda Bracket Algebras With Basis	516
3.102	Lattice posets	517
3.103	Left modules	518
3.104	Lie Algebras	519
3.105	Lie Algebras With Basis	529
3.106	Lie Conformal Algebras	531
3.107	Lie Conformal Algebras With Basis	535
3.108	Lie Groups	537
3.109	Loop Crystals	537
3.110	L-trivial semigroups	550
3.111	Magmas	551
3.112	Magmas and Additive Magmas	565
3.113	Non-unital non-associative algebras	567
3.114	Manifolds	570
3.115	Matrix algebras	574
3.116	Metric Spaces	575
3.117	Modular abelian varieties	579
3.118	Modules	580
3.119	Modules With Basis	590
3.120	Monoid algebras	616
3.121	Monoids	616
3.122	Number fields	622
3.123	Objects	624
3.124	Partially ordered monoids	626
3.125	Permutation groups	626
3.126	Pointed sets	627
3.127	Polyhedral subsets of free $\mathbb{Z}\mathbb{Z}$, $\mathbb{Q}\mathbb{Q}$ or $\mathbb{R}\mathbb{R}$ -modules.	627
3.128	Posets	628
3.129	Principal ideal domains	637
3.130	Quotient fields	638
3.131	Quantum Group Representations	644
3.132	Regular Crystals	650
3.133	Regular Supercrystals	658
3.134	Right modules	660

3.135	Ring ideals	660
3.136	Rings	661
3.137	Rngs	670
3.138	R-trivial semigroups	671
3.139	Schemes	671
3.140	Semigroups	672
3.141	Semirngs	684
3.142	Semisimple Algebras	684
3.143	Sets	686
3.144	Sets With a Grading	712
3.145	SetsWithPartialMaps	715
3.146	Shephard Groups	715
3.147	Simplicial Complexes	716
3.148	Simplicial Sets	717
3.149	Super Algebras	724
3.150	Super algebras with basis	726
3.151	Super Hopf algebras with basis	727
3.152	Super Lie Conformal Algebras	727
3.153	Super modules	729
3.154	Super modules with basis	731
3.155	Supercommutative Algebras	733
3.156	Supercrystals	734
3.157	Topological Spaces	739
3.158	Kac-Moody Algebras With Triangular Decomposition Basis	740
3.159	Unique factorization domains	742
3.160	Unital algebras	744
3.161	Vector Bundles	746
3.162	Vector Spaces	747
3.163	Weyl Groups	751
3.164	Technical Categories	760
4	Functorial constructions	763
4.1	Covariant Functorial Constructions	763
4.2	Cartesian Product Functorial Construction	769
4.3	Tensor Product Functorial Construction	771
4.4	Signed Tensor Product Functorial Construction	772
4.5	Dual functorial construction	773
4.6	Group algebras and beyond: the Algebra functorial construction	773
4.7	Subquotient Functorial Construction	780
4.8	Quotients Functorial Construction	780
4.9	Subobjects Functorial Construction	781
4.10	Isomorphic Objects Functorial Construction	781
4.11	Homset categories	782
4.12	Realizations Covariant Functorial Construction	786
4.13	With Realizations Covariant Functorial Construction	788
5	Examples of parents using categories	793
5.1	Examples of algebras with basis	793
5.2	Examples of commutative additive monoids	794
5.3	Examples of commutative additive semigroups	795
5.4	Examples of Coxeter groups	797
5.5	Example of a crystal	797
5.6	Examples of CW complexes	799
5.7	Example of facade set	800

5.8	Examples of finite Coxeter groups	801
5.9	Example of a finite dimensional algebra with basis	803
5.10	Examples of a finite dimensional Lie algebra with basis	804
5.11	Examples of finite enumerated sets	808
5.12	Examples of finite monoids	810
5.13	Examples of finite semigroups	812
5.14	Examples of finite Weyl groups	814
5.15	Examples of graded connected Hopf algebras with basis	816
5.16	Examples of graded modules with basis	818
5.17	Examples of graphs	820
5.18	Examples of Hopf algebras with basis	821
5.19	Examples of infinite enumerated sets	823
5.20	Examples of a Lie algebra	824
5.21	Examples of a Lie algebra with basis	826
5.22	Examples of magmas	827
5.23	Examples of manifolds	828
5.24	Examples of monoids	829
5.25	Examples of posets	831
5.26	Examples of semigroups	833
5.27	Examples of semigroups in cython	838
5.28	Examples of sets	840
5.29	Example of a set with grading	846
5.30	Examples of parents endowed with multiple realizations	847
6	Internals	853
6.1	Specific category classes	853
6.2	Singleton categories	856
6.3	Fast functions for the category framework	859
6.4	Coercion methods for categories	861
6.5	Poor Man's map	861
7	Indices and Tables	863
	Python Module Index	865
	Index	869

THE SAGE CATEGORY FRAMEWORK

1.1 Elements, parents, and categories in Sage: a (draft of) primer

Contents

- *Elements, parents, and categories in Sage: a (draft of) primer*
 - *Abstract*
 - *Introduction: Sage as a library of objects and algorithms*
 - *A bit of help from abstract algebra*
 - *A bit of help from computer science*
 - *Sage categories*
 - *Case study*
 - *Specifying the category of a parent*
 - *Scaling further: functorial constructions, axioms, ...*
 - *Writing a new category*

1.1.1 Abstract

The purpose of categories in Sage is to translate the mathematical concept of categories (category of groups, of vector spaces, ...) into a concrete software engineering design pattern for:

- organizing and promoting generic code
- fostering consistency across the Sage library (naming conventions, doc, tests)
- embedding more mathematical knowledge into the system

This design pattern is largely inspired from Axiom and its followers (Aldor, Fricas, MuPAD, ...). It differs from those by:

- blending in the Magma inspired concept of Parent/Element
- being built on top of (and not into) the standard Python object oriented and class hierarchy mechanism. This did not require changing the language, and could in principle be implemented in any language supporting the creation of new classes dynamically.

The general philosophy is that *Building mathematical information into the system yields more expressive, more conceptual and, at the end, easier to maintain and faster code* (within a programming realm; this would not necessarily apply to specialized libraries like gmp!).

One line pitch for mathematicians

Categories in Sage provide a library of interrelated bookshelves, with each bookshelf containing algorithms, tests, documentation, or some mathematical facts about the objects of a given category (e.g. groups).

One line pitch for programmers

Categories in Sage provide a large hierarchy of abstract classes for mathematical objects. To keep it maintainable, the inheritance information between the classes is not hardcoded but instead reconstructed dynamically from duplication free semantic information.

1.1.2 Introduction: Sage as a library of objects and algorithms

The Sage library, with more than one million lines of code, documentation, and tests, implements:

- Thousands of different kinds of objects (classes):
Integers, polynomials, matrices, groups, number fields, elliptic curves, permutations, morphisms, languages, ... and a few racoons ...
- Tens of thousands methods and functions:
Arithmetic, integer and polynomial factorization, pattern matching on words, ...

Some challenges

- How to organize this library?
One needs some bookshelves to group together related objects and algorithms.
- How to ensure consistency?
Similar objects should behave similarly:

```
sage: Permutations(5).cardinality()
120

sage: GL(2,2).cardinality()
6

sage: A=random_matrix(ZZ,6,3,x=7)
sage: L=LatticePolytope(A.rows())
sage: L.npoints()           # oops!   # random
37
```

- How to ensure robustness?
- How to reduce duplication?
Example: binary powering:

```
sage: m = 3
sage: m^8 == m*m*m*m*m*m*m*m == ((m^2)^2)^2
True
```

```
sage: m=random_matrix(QQ, 4, algorithm='echelonizable', rank=3, upper_bound=60)
sage: m^8 == m*m*m*m*m*m*m*m == ((m^2)^2)^2
True
```

We want to implement binary powering only once, as *generic* code that will apply in all cases.

1.1.3 A bit of help from abstract algebra

The hierarchy of categories

What makes binary powering work in the above examples? In both cases, we have a *set* endowed with a *multiplicative binary operation* which is *associative* and which has a unit element. Such a set is called a *monoid*, and binary powering (to a non-negative power) works generally for any monoid.

Sage knows about monoids:

```
sage: Monoids()
Category of monoids
```

and sure enough, binary powering is defined there:

```
sage: m._pow_int.__module__
'sage.categories.monoids'
```

That's our bookshelf! And it's used in many places:

```
sage: GL(2,ZZ) in Monoids()
True
sage: NN in Monoids()
True
```

For a less trivial bookshelf we can consider euclidean rings: once we know how to do euclidean division in some set R , we can compute gcd's in R generically using the Euclidean algorithm.

We are in fact very lucky: abstract algebra provides us right away with a large and robust set of bookshelves which is the result of centuries of work of mathematicians to identify the important concepts. This includes for example:

```
sage: Sets()
Category of sets

sage: Groups()
Category of groups

sage: Rings()
Category of rings

sage: Fields()
Category of fields
```

(continues on next page)

(continued from previous page)

```
sage: HopfAlgebras(QQ)
Category of hopf algebras over Rational Field
```

Each of the above is called a *category*. It typically specifies what are the operations on the elements, as well as the axioms satisfied by those operations. For example the category of groups specifies that a group is a set endowed with a binary operation (the multiplication) which is associative and admits a unit and inverses.

Each set in Sage knows which bookshelf of generic algorithms it can use, that is to which category it belongs:

```
sage: G = GL(2,ZZ)
sage: G.category()
Category of infinite groups
```

In fact a group is a semigroup, and Sage knows about this:

```
sage: Groups().is_subcategory(Semigroups())
True
sage: G in Semigroups()
True
```

Altogether, our group gets algorithms from a bunch of bookshelves:

```
sage: G.categories()
[Category of infinite groups, Category of groups, Category of monoids,
 ...,
 Category of magmas,
 Category of infinite sets, ...]
```

Those can be viewed graphically:

```
sage: g = Groups().category_graph()
sage: g.set_latex_options(format="dot2tex")
sage: view(g) # not tested
```

In case dot2tex is not available, you can use instead:

```
sage: g.show(vertex_shape=None, figsize=20)
```

Here is an overview of all categories in Sage:

```
sage: g = sage.categories.category.category_graph()
sage: g.set_latex_options(format="dot2tex")
sage: view(g) # not tested
```

Wrap-up: generic algorithms in Sage are organized in a hierarchy of bookshelves modelled upon the usual hierarchy of categories provided by abstract algebra.

Elements, Parents, Categories

Parent

A *parent* is a Python instance modelling a set of mathematical elements together with its additional (algebraic) structure.

Examples include the ring of integers, the group S_3 , the set of prime numbers, the set of linear maps between two given vector spaces, and a given finite semigroup.

These sets are often equipped with additional structure: the set of all integers forms a ring. The main way of encoding this information is specifying which categories a parent belongs to.

It is completely possible to have different Python instances modelling the same set of elements. For example, one might want to consider the ring of integers, or the poset of integers under their standard order, or the poset of integers under divisibility, or the semiring of integers under the operations of maximum and addition. Each of these would be a different instance, belonging to different categories.

For a given model, there should be a unique instance in Sage representing that parent:

```
sage: IntegerRing() is IntegerRing()
True
```

Element

An *element* is a Python instance modelling a mathematical element of a set.

Examples of element include 5 in the integer ring, $x^3 - x$ in the polynomial ring in x over the rationals, $4 + O(3^3)$ in the 3-adics, the transposition (12) in S_3 , and the identity morphism in the set of linear maps from \mathbb{Q}^3 to \mathbb{Q}^3 .

Every element in Sage has a parent. The standard idiom in Sage for creating elements is to create their parent, and then provide enough data to define the element:

```
sage: R = PolynomialRing(ZZ, name='x')
sage: R([1, 2, 3])
3*x^2 + 2*x + 1
```

One can also create elements using various methods on the parent and arithmetic of elements:

```
sage: x = R.gen()
sage: 1 + 2*x + 3*x^2
3*x^2 + 2*x + 1
```

Unlike parents, elements in Sage are not necessarily unique:

```
sage: ZZ(5040) is ZZ(5040)
False
```

Many parents model algebraic structures, and their elements support arithmetic operations. One often further wants to do arithmetic by combining elements from different parents: adding together integers and rationals for example. Sage supports this feature using coercion (see [sage.structure.coerce](#) for more details).

It is possible for a parent to also have simultaneously the structure of an element. Consider for example the monoid of all finite groups, endowed with the Cartesian product operation. Then, every finite group (which is a parent) is also an element of this monoid. This is not yet implemented, and the design details are not yet fixed but experiments are underway in this direction.

Todo: Give a concrete example, typically using `ElementWrapper`.

Category

A *category* is a Python instance modelling a mathematical category.

Examples of categories include the category of finite semigroups, the category of all (Python) objects, the category of \mathbf{Z} -algebras, and the category of Cartesian products of \mathbf{Z} -algebras:

```
sage: FiniteSemigroups()
Category of finite semigroups
sage: Objects()
Category of objects
sage: Algebras(ZZ)
Category of algebras over Integer Ring
sage: Algebras(ZZ).CartesianProducts()
Category of Cartesian products of algebras over Integer Ring
```

Mind the ‘s’ in the names of the categories above; `GroupAlgebra` and `GroupAlgebras` are distinct things.

Every parent belongs to a collection of categories. Moreover, categories are interrelated by the *super categories* relation. For example, the category of rings is a super category of the category of fields, because every field is also a ring.

A category serves two roles:

- to provide a model for the mathematical concept of a category and the associated structures: homsets, morphisms, functorial constructions, axioms.
- to organize and promote generic code, naming conventions, documentation, and tests across similar mathematical structures.

CategoryObject

Objects of a mathematical category are not necessarily parents. `Parent` has a superclass that provides a means of modeling such.

For example, the category of schemes does not have a faithful forgetful functor to the category of sets, so it does not make sense to talk about schemes as parents.

Morphisms, Homsets

As category theorists will expect, *Morphisms* and *Homsets* will play an ever more important role, as support for them will improve.

Much of the mathematical information in Sage is encoded as relations between elements and their parents, parents and their categories, and categories and their super categories:

```
sage: 1.parent()
Integer Ring

sage: ZZ
```

(continues on next page)

(continued from previous page)

Integer Ring

sage: ZZ.category()

Join of Category of euclidean domains
 and Category of infinite enumerated sets
 and Category of metric spaces

sage: ZZ.categories()

[Join of Category of euclidean domains
 and Category of infinite enumerated sets
 and Category of metric spaces,
 Category of euclidean domains, Category of principal ideal domains,
 Category of unique factorization domains, Category of gcd domains,
 Category of integral domains, Category of domains,
 Category of commutative rings, Category of rings, ...
 Category of magmas and additive magmas, ...
 Category of monoids, Category of semigroups,
 Category of commutative magmas, Category of unital magmas, Category of magmas,
 Category of commutative additive groups, ..., Category of additive magmas,
 Category of infinite enumerated sets, Category of enumerated sets,
 Category of infinite sets, Category of metric spaces,
 Category of topological spaces, Category of sets,
 Category of sets with partial maps,
 Category of objects]

sage: g = EuclideanDomains().category_graph()**sage:** g.set_latex_options(format="dot2tex")**sage:** view(g) *# not tested*

1.1.4 A bit of help from computer science

Hierarchy of classes

How are the bookshelves implemented in practice?

Sage uses the classical design paradigm of Object Oriented Programming (OOP). Its fundamental principle is that any object that a program is to manipulate should be modelled by an *instance* of a *class*. The class implements:

- a *data structure*: which describes how the object is stored,
- *methods*: which describe the operations on the object.

The instance itself contains the data for the given object, according to the specified data structure.

Hence, all the objects mentioned above should be instances of some classes. For example, an integer in Sage is an instance of the class `Integer` (and it knows about it!):

sage: i = 12**sage:** type(i)

<type 'sage.rings.integer.Integer'>

Applying an operation is generally done by *calling a method*:

```

sage: i.factor()
2^2 * 3

sage: x = var('x')
sage: p = 6*x^2 + 12*x + 6
sage: type(p)
<type 'sage.symbolic.expression.Expression'>
sage: p.factor()
6*(x + 1)^2

sage: R.<x> = PolynomialRing(QQ, sparse=True)
sage: pQ = R ( p )
sage: type(pQ)
<class 'sage.rings.polynomial.polynomial_ring.PolynomialRing_field_with_category.element_
↳class'>
sage: pQ.factor()
(6) * (x + 1)^2

sage: pZ = ZZ['x'] ( p )
sage: type(pZ)
<type 'sage.rings.polynomial.polynomial_integer_dense_flint.Polynomial_integer_dense_
↳flint'>
sage: pZ.factor()
2 * 3 * (x + 1)^2

```

Factoring integers, expressions, or polynomials are distinct tasks, with completely different algorithms. Yet, from a user (or caller) point of view, all those objects can be manipulated alike. This illustrates the OOP concepts of *polymorphism*, *data abstraction*, and *encapsulation*.

Let us be curious, and see where some methods are defined. This can be done by introspection:

```

sage: i._mul_?? # not tested

```

For plain Python methods, one can also just ask in which module they are implemented:

```

sage: i._pow__.__module__ # not tested (Trac #24275)
'sage.categories.semigroups'

sage: pQ._mul__.__module__
'sage.rings.polynomial.polynomial_element_generic'
sage: pQ._pow__.__module__ # not tested (Trac #24275)
'sage.categories.semigroups'

```

We see that integers and polynomials have each their own multiplication method: the multiplication algorithms are indeed unrelated and deeply tied to their respective datastructures. On the other hand, as we have seen above, they share the same powering method because the set \mathbf{Z} of integers, and the set $\mathbf{Q}[x]$ of polynomials are both semigroups. Namely, the class for integers and the class for polynomials both derive from an *abstract class* for semigroup elements, which factors out the *generic* methods like `_pow_`. This illustrates the use of *hierarchy of classes* to share common code between classes having common behaviour.

OOP design is all about isolating the objects that one wants to model together with their operations, and designing an appropriate hierarchy of classes for organizing the code. As we have seen above, the design of the class hierarchy is easy since it can be modelled upon the hierarchy of categories (bookshelves). Here is for example a piece of the hierarchy of classes for an element of a group of permutations:


```

sage: P = Permutations(4)
sage: m = P.an_element()
sage: for cls in m.__class__.mro(): print(cls)
<class 'sage.combinat.permutation.StandardPermutations_n_with_category.element_class'>
<class 'sage.combinat.permutation.StandardPermutations_n.Element'>
<class 'sage.combinat.permutation.Permutation'>
...
<class 'sage.categories.groups.Groups.element_class'>
<class 'sage.categories.monoids.Monoids.element_class'>
...
<class 'sage.categories.semigroups.Semigroups.element_class'>
...

```

On the top, we see concrete classes that describe the data structure for matrices and provide the operations that are tied to this data structure. Then follow abstract classes that are attached to the hierarchy of categories and provide generic algorithms.

The full hierarchy is best viewed graphically:

```

sage: g = class_graph(m.__class__)
sage: g.set_latex_options(format="dot2tex")
sage: view(g) # not tested

```

Parallel hierarchy of classes for parents

Let us recall that we do not just want to compute with elements of mathematical sets, but with the sets themselves:

```

sage: ZZ.one()
1
sage: R = QQ['x,y']
sage: R.krull_dimension()
2
sage: A = R.quotient( R.ideal(x^2 - 2) )
sage: A.krull_dimension() # todo: not implemented

```

Here are some typical operations that one may want to carry on various kinds of sets:

- The set of permutations of 5, the set of rational points of an elliptic curve: counting, listing, random generation
- A language (set of words): rationality testing, counting elements, generating series
- A finite semigroup: left/right ideals, center, representation theory
- A vector space, an algebra: Cartesian product, tensor product, quotient

Hence, following the OOP fundamental principle, parents should also be modelled by instances of some (hierarchy of) classes. For example, our group G is an instance of the following class:

```

sage: G = GL(2, ZZ)
sage: type(G)
<class 'sage.groups.matrix_gps.linear.LinearMatrixGroup_gap_with_category'>

```

Here is a piece of the hierarchy of classes above it:

```
sage: for cls in G.__class__.mro(): print(cls)
<class 'sage.groups.matrix_gps.linear.LinearMatrixGroup_gap_with_category'>
...
<class 'sage.categories.groups.Groups.parent_class'>
<class 'sage.categories.monoids.Monoids.parent_class'>
<class 'sage.categories.semigroups.Semigroups.parent_class'>
...
```

Note that the hierarchy of abstract classes is again attached to categories and parallel to that we had seen for the elements. This is best viewed graphically:

```
sage: g = class_graph(m.__class__)
sage: g.relabel(lambda x: x.replace("_",r"\_"))
sage: g.set_latex_options(format="dot2tex")
sage: view(g) # not tested
```

Note: This is a progress upon systems like Axiom or MuPAD where a parent is modelled by the class of its elements; this oversimplification leads to confusion between methods on parents and elements, and makes parents special; in particular it prevents potentially interesting constructions like “groups of groups”.

1.1.5 Sage categories

Why this business of categories? And to start with, why don't we just have a good old hierarchy of classes Group, Semigroup, Magma, ... ?

Dynamic hierarchy of classes

As we have just seen, when we manipulate groups, we actually manipulate several kinds of objects:

- groups
- group elements
- morphisms between groups
- and even the category of groups itself!

Thus, on the group bookshelf, we want to put generic code for each of the above. We therefore need three, parallel hierarchies of abstract classes:

- Group, Monoid, Semigroup, Magma, ...
- GroupElement, MonoidElement, SemigroupElement, MagmaElement, ...
- GroupMorphism, SemigroupElement, SemigroupMorphism, MagmaMorphism, ...

(and in fact many more as we will see).

We could implement the above hierarchies as usual:

```
class Group(Monoid):
    # generic methods that apply to all groups

class GroupElement(MonoidElement):
```

(continues on next page)

(continued from previous page)

```
# generic methods that apply to all group elements

class GroupMorphism(MonoidMorphism):
    # generic methods that apply to all group morphisms
```

And indeed that's how it was done in Sage before 2009, and there are still many traces of this. The drawback of this approach is duplication: the fact that a group is a monoid is repeated three times above!

Instead, Sage now uses the following syntax, where the *Groups* bookshelf is structured into units with *nested classes*:

```
class Groups(Category):

    def super_categories(self):
        return [Monoids(), ...]

    class ParentMethods:
        # generic methods that apply to all groups

    class ElementMethods:
        # generic methods that apply to all group elements

    class MorphismMethods:
        # generic methods that apply to all group morphisms (not yet implemented)

    class SubcategoryMethods:
        # generic methods that apply to all subcategories of Groups()
```

With this syntax, the information that a group is a monoid is specified only once, in the `Category.super_categories()` method. And indeed, when the category of inverse unital magmas was introduced, there was a *single point of truth* to update in order to reflect the fact that a group is an inverse unital magma:

```
sage: Groups().super_categories()
[Category of monoids, Category of inverse unital magmas]
```

The price to pay (there is no free lunch) is that some magic is required to construct the actual hierarchy of classes for parents, elements, and morphisms. Namely, `Groups.ElementMethods` should be seen as just a bag of methods, and the actual class `Groups().element_class` is constructed from it by adding the appropriate super classes according to `Groups().super_categories()`:

```
sage: Groups().element_class
<class 'sage.categories.groups.Groups.element_class'>

sage: Groups().element_class.__bases__
(<class 'sage.categories.monoids.Monoids.element_class'>,
 <class 'sage.categories.magmas.Magmas.Unital.Inverse.element_class'>)
```

We now see that the hierarchy of classes for parents and elements is parallel to the hierarchy of categories:

```
sage: Groups().all_super_categories()
[Category of groups,
 Category of monoids,
 Category of semigroups,
 ...]
```

(continues on next page)

(continued from previous page)

```

Category of magmas,
Category of sets,
...]

sage: for cls in Groups().element_class.mro(): print(cls)
<class 'sage.categories.groups.Groups.element_class'>
<class 'sage.categories.monoids.Monoids.element_class'>
<class 'sage.categories.semigroups.Semigroups.element_class'>
...
<class 'sage.categories.magmas.Magmas.element_class'>
...
sage: for cls in Groups().parent_class.mro(): print(cls)
<class 'sage.categories.groups.Groups.parent_class'>
<class 'sage.categories.monoids.Monoids.parent_class'>
<class 'sage.categories.semigroups.Semigroups.parent_class'>
...
<class 'sage.categories.magmas.Magmas.parent_class'>
...

```

Another advantage of building the hierarchy of classes dynamically is that, for parametrized categories, the hierarchy may depend on the parameters. For example an algebra over \mathbf{Q} is a \mathbf{Q} -vector space, but an algebra over \mathbf{Z} is not (it is just a \mathbf{Z} -module)!

Note: At this point this whole infrastructure may feel like overdesigning, right? We felt like this too! But we will see later that, once one gets used to it, this approach scales very naturally.

From a computer science point of view, this infrastructure implements, on top of standard multiple inheritance, a dynamic composition mechanism of mixin classes ([Wikipedia article Mixin](#)), governed by mathematical properties.

For implementation details on how the hierarchy of classes for parents and elements is constructed, see [Category](#).

On the category hierarchy: subcategories and super categories

We have seen above that, for example, the category of sets is a super category of the category of groups. This models the fact that a group can be unambiguously considered as a set by forgetting its group operation. In object-oriented parlance, we want the relation “a group *is a* set”, so that groups can directly inherit code implemented on sets.

Formally, a category $Cs()$ is a *super category* of a category $Ds()$ if Sage considers any object of $Ds()$ to be an object of $Cs()$, up to an implicit application of a canonical functor from $Ds()$ to $Cs()$. This functor is normally an inclusion of categories or a forgetful functor. Reciprocally, $Ds()$ is said to be a *subcategory* of $Cs()$.

Warning: This terminology deviates from the usual mathematical definition of *subcategory* and is subject to change. Indeed, the forgetful functor from the category of groups to the category of sets is not an inclusion of categories, as it is not injective: a given set may admit more than one group structure. See [trac ticket #16183](#) for more details. The name *supercategory* is also used with a different meaning in certain areas of mathematics.

Categories are instances and have operations

Note that categories themselves are naturally modelled by instances because they can have operations of their own. An important one is:

```
sage: Groups().example()
General Linear Group of degree 4 over Rational Field
```

which gives an example of object of the category. Besides illustrating the category, the example provides a minimal template for implementing a new object in the category:

```
sage: S = Semigroups().example(); S
An example of a semigroup: the left zero semigroup
```

Its source code can be obtained by introspection:

```
sage: S?? # not tested
```

This example is also typically used for testing generic methods. See `Category.example()` for more.

Other operations on categories include querying the super categories or the axioms satisfied by the operations of a category:

```
sage: Groups().super_categories()
[Category of monoids, Category of inverse unital magmas]
sage: Groups().axioms()
frozenset({'Associative', 'Inverse', 'Unital'})
```

or constructing the intersection of two categories, or the smallest category containing them:

```
sage: Groups() & FiniteSets()
Category of finite groups
sage: Algebras(QQ) | Groups()
Category of monoids
```

Specifications and generic documentation

Categories do not only contain code but also the specifications of the operations. In particular a list of mandatory and optional methods to be implemented can be found by introspection with:

```
sage: Groups().required_methods()
{'element': {'optional': ['_mul_'], 'required': []},
 'parent': {'optional': [], 'required': ['__contains__']}}
```

Documentation about those methods can be obtained with:

```
sage: G = Groups()
sage: G.element_class._mul_? # not tested
sage: G.parent_class.one? # not tested
```

See also the `abstract_method()` decorator.

Warning: Well, more precisely, that's how things should be, but there is still some work to do in this direction. For example, the inverse operation is not specified above. Also, we are still missing a good programmatic syntax to specify the input and output types of the methods. Finally, in many cases the implementer must provide at least one of two methods, each having a default implementation using the other one (e.g. listing or iterating for a finite enumerated set); there is currently no good programmatic way to specify this.

Generic tests

Another feature that parents and elements receive from categories is generic tests; their purpose is to check (at least to some extent) that the parent satisfies the required mathematical properties (is my semigroup indeed associative?) and is implemented according to the specifications (does the method `an_element` indeed return an element of the parent?):

```
sage: S = FiniteSemigroups().example(alphabet=('a', 'b'))
sage: TestSuite(S).run(verbose = True)
running ._test_an_element() . . . pass
running ._test_associativity() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
    running ._test_elements_eq_reflexive() . . . pass
    running ._test_elements_eq_symmetric() . . . pass
    running ._test_elements_eq_transitive() . . . pass
    running ._test_elements_neq() . . . pass
running ._test_enumerated_set_contains() . . . pass
running ._test_enumerated_set_iter_cardinality() . . . pass
running ._test_enumerated_set_iter_list() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass
```

Tests can be run individually:

```
sage: S._test_associativity()
```

Here is how to access the code of this test:

```
sage: S._test_associativity?? # not tested
```

Here is how to run the test on all elements:

```
sage: L = S.list()
sage: S._test_associativity(elements=L)
```

See `TestSuite` for more information.

Let us see what happens when a test fails. Here we redefine the product of S to something definitely not associative:

```
sage: S.product = lambda x, y: S("("+x.value +y.value+")")
```

And rerun the test:

```
sage: S._test_associativity(elements=L)
Traceback (most recent call last):
...
File ".../sage/categories/semigroups.py", line ..., in _test_associativity
    tester.assertTrue((x * y) * z == x * (y * z))
...
AssertionError: '((aa)a)' != '(a(aa))'
```

We can recover instantly the actual values of x , y , z , that is, a counterexample to the associativity of our broken semigroup, using post mortem introspection with the Python debugger `pdb` (this does not work yet in the notebook):

```
sage: import pdb
sage: pdb.pm() # not tested
> /opt/sage-5.11.rc1/local/lib/python/unittest/case.py(424)assertTrue()
-> raise self.failureException(msg)
(Pdb) u
> /opt/sage-5.11.rc1/local/lib/python2.7/site-packages/sage/categories/semigroups.
-> py(145)_test_associativity()
-> tester.assertTrue((x * y) * z == x * (y * z))
(Pdb) p x, y, z
('a', 'a', 'a')
(Pdb) p (x * y) * z
 '((aa)a)'
(Pdb) p x * (y * z)
 '(a(aa))'
```

Wrap-up

- Categories provide a natural hierarchy of bookshelves to organize not only code, but also specifications and testing tools.
- Everything about, say, algebras with a distinguished basis is gathered in [AlgebrasWithBasis](#) or its super categories. This includes properties and algorithms for elements, parents, morphisms, but also, as we will see, for constructions like Cartesian products or quotients.
- The mathematical relations between elements, parents, and categories translate dynamically into a traditional hierarchy of classes.
- This design enforces robustness and consistency, which is particularly welcome given that Python is an interpreted language without static type checking.

1.1.6 Case study

In this section, we study an existing parent in detail; a good followup is to go through the [sage.categories.tutorial](#) or the thematic tutorial on coercion and categories (“How to implement new algebraic structures in Sage”) to learn how to implement a new one!

We consider the example of finite semigroup provided by the category:

```
sage: S = FiniteSemigroups().example(); S
An example of a finite semigroup: the left regular band generated by ('a', 'b', 'c', 'd')
sage: S? # not tested
```

Where do all the operations on S and its elements come from?

```
sage: x = S('a')
```

`__repr__` is a technical method which comes with the data structure (`ElementWrapper`); since it’s implemented in Cython, we need to use Sage’s introspection tools to recover where it’s implemented:

```
sage: x.__repr__.__module__
sage: sage.misc.sageinspect.sage_getfile(x.__repr__)
'.../sage/structure/element_wrapper.pyx'
```

`__pow_int` is a generic method for all finite semigroups:

```
sage: x.__pow_int.__module__
'sage.categories.semigroups'
```

`__mul__` is a generic method provided by the *Magmas* category (a *magma* is a set with an inner law $*$, not necessarily associative). If the two arguments are in the same parent, it will call the method `__mul__`, and otherwise let the `coercion model` try to discover how to do the multiplication:

```
sage: x.__mul__? # not tested
```

Since it is a speed critical method, it is implemented in Cython in a separate file:

```
sage: x.__mul__.__module__
'sage.categories.coercion_methods'
```

`__mul__` is a default implementation, also provided by the *Magmas* category, that delegates the work to the method `product` of the parent (following the advice: if you do not know what to do, ask your parent); it’s also a speed critical method:

```
sage: x.__mul__? # not tested
sage: x.__mul__.__module__
'sage.categories.coercion_methods'
sage: x.__mul__.__func__ is Magmas.ElementMethods.__mul_parent # py3
True
```

`product` is a mathematical method implemented by the parent:

```
sage: S.product.__module__
'sage.categories.examples.finite_semigroups'
```

`cayley_graph` is a generic method on the parent, provided by the *FiniteSemigroups* category:


```
sage: S.cayley_graph.__module__
'sage.categories.semigroups'
```

`multiplication_table` is a generic method on the parent, provided by the *Magma*s category (it does not require associativity):

```
sage: S.multiplication_table.__module__
'sage.categories.magma'
```

Consider now the implementation of the semigroup:

```
sage: S?? # not tested
```

This implementation specifies a data structure for the parents and the elements, and makes a promise: the implemented parent is a finite semigroup. Then it fulfills the promise by implementing the basic operation `product`. It also implements the optional method `semigroup_generators`. In exchange, *S* and its elements receive generic implementations of all the other operations. *S* may override any of those by more efficient ones. It may typically implement the element method `is_idempotent` to always return `True`.

A (not yet complete) list of mandatory and optional methods to be implemented can be found by introspection with:

```
sage: FiniteSemigroups().required_methods()
{'element': {'optional': ['_mul_'], 'required': []},
 'parent': {'optional': ['semigroup_generators'],
            'required': ['__contains__']}}
```

`product` does not appear in the list because a default implementation is provided in term of the method `_mul_` on elements. Of course, at least one of them should be implemented. On the other hand, a default implementation for `__contains__` is provided by *Parent*.

Documentation about those methods can be obtained with:

```
sage: C = FiniteSemigroups().element_class
sage: C._mul_? # not tested
```

See also the `abstract_method()` decorator.

Here is the code for the finite semigroups category:

```
sage: FiniteSemigroups?? # not tested
```

1.1.7 Specifying the category of a parent

Some parent constructors (not enough!) allow to specify the desired category for the parent. This can typically be used to specify additional properties of the parent that we know to hold a priori. For example, permutation groups are by default in the category of finite permutation groups (no surprise):

```
sage: P = PermutationGroup([(1,2,3)]); P
Permutation Group with generators [(1,2,3)]
sage: P.category()
Category of finite enumerated permutation groups
```

In this case, the group is commutative, so we can specify this:

```

sage: P = PermutationGroup([[ (1,2,3) ]], category=PermutationGroups().Finite().
↳Commutative()); P
Permutation Group with generators [(1,2,3)]
sage: P.category()
Category of finite enumerated commutative permutation groups

```

This feature can even be used, typically in experimental code, to add more structure to existing parents, and in particular to add methods for the parents or the elements, without touching the code base:

```

sage: class Foos(Category):
.....:     def super_categories(self):
.....:         return [PermutationGroups().Finite().Commutative()]
.....:     class ParentMethods:
.....:         def foo(self): print("foo")
.....:     class ElementMethods:
.....:         def bar(self): print("bar")

sage: P = PermutationGroup([[ (1,2,3) ]], category=Foos())
sage: P.foo()
foo
sage: p = P.an_element()
sage: p.bar()
bar

```

In the long run, it would be thinkable to use this idiom to implement forgetful functors; for example the above group could be constructed as a plain set with:

```

sage: P = PermutationGroup([[ (1,2,3) ]], category=Sets()) # todo: not implemented

```

At this stage though, this is still to be explored for robustness and practicality. For now, most parents that accept a category argument only accept a subcategory of the default one.

1.1.8 Scaling further: functorial constructions, axioms, ...

In this section, we explore more advanced features of categories. Along the way, we illustrate that a large hierarchy of categories is desirable to model complicated mathematics, and that scaling to support such a large hierarchy is the driving motivation for the design of the category infrastructure.

Functorial constructions

Sage has support for a certain number of so-called *covariant functorial constructions* which can be used to construct new parents from existing ones while carrying over as much as possible of their algebraic structure. This includes:

- Cartesian products: See `cartesian_product`.
- Tensor products: See `tensor`.
- Subquotients / quotients / subobjects / isomorphic objects: See:
 - `Sets().Subquotients`,
 - `Sets().Quotients`,
 - `Sets().Subobjects`,
 - `Sets().IsomorphicObjects`

- Dual objects: See `Modules().DualObjects`.
- Algebras, as in group algebras, monoid algebras, ...: See: `Sets.ParentMethods.algebra()`.

Let for example A and B be two parents, and let us construct the Cartesian product $A \times B \times B$:

```
sage: A = AlgebrasWithBasis(QQ).example(); A.rename("A")
sage: B = HopfAlgebrasWithBasis(QQ).example(); B.rename("B")
sage: C = cartesian_product([A, B, B]); C
A (+) B (+) B
```

In which category should this new parent be? Since A and B are vector spaces, the result is, as a vector space, the direct sum $A \oplus B \oplus B$, hence the notation. Also, since both A and B are monoids, $A \times B \times B$ is naturally endowed with a monoid structure for pointwise multiplication:

```
sage: C in Monoids()
True
```

the unit being the Cartesian product of the units of the operands:

```
sage: C.one()
B[(0, word: )] + B[(1, ())] + B[(2, ())]
sage: cartesian_product([A.one(), B.one(), B.one()])
B[(0, word: )] + B[(1, ())] + B[(2, ())]
```

The pointwise product can be implemented generically for all magmas (i.e. sets endowed with a multiplicative operation) that are constructed as Cartesian products. It's thus implemented in the `Magmas` category:

```
sage: C.product.__module__
'sage.categories.magmas'
```

More specifically, keeping on using nested classes to structure the code, the product method is put in the nested class `Magmas.CartesianProducts.ParentMethods`:

```
class Magmas(Category):
    class ParentMethods:
        # methods for magmas
    class ElementMethods:
        # methods for elements of magmas
    class CartesianProduct(CartesianProductCategory):
        class ParentMethods:
            # methods for magmas that are constructed as Cartesian products
            def product(self, x, y):
                # ...
        class ElementMethods:
            # ...
```

Note: The support for nested classes in Python is relatively recent. Their intensive use for the category infrastructure did reveal some glitches in their implementation, in particular around class naming and introspection. Sage currently works around the more annoying ones but some remain visible. See e.g. `sage.misc.nested_class_test`.

Let us now look at the categories of C :

```
sage: C.categories()
[Category of finite dimensional Cartesian products of algebras with basis over Rational_
↔Field, ...
Category of Cartesian products of algebras over Rational Field, ...
Category of Cartesian products of semigroups, Category of semigroups, ...
Category of Cartesian products of magmas, ..., Category of magmas, ...
Category of Cartesian products of additive magmas, ..., Category of additive magmas,
Category of Cartesian products of sets, Category of sets, ...]
```

This reveals the parallel hierarchy of categories for Cartesian products of semigroups magmas, ... We are thus glad that Sage uses its knowledge that a monoid is a semigroup to automatically deduce that a Cartesian product of monoids is a Cartesian product of semigroups, and build the hierarchy of classes for parents and elements accordingly.

In general, the Cartesian product of A and B can potentially be an algebra, a coalgebra, a differential module, and be finite dimensional, or graded, or This can only be decided at runtime, by introspection into the properties of A and B ; furthermore, the number of possible combinations (e.g. finite dimensional differential algebra) grows exponentially with the number of properties.

Axioms

First examples

We have seen that Sage is aware of the axioms satisfied by, for example, groups:

```
sage: Groups().axioms()
frozenset({'Associative', 'Inverse', 'Unital'})
```

In fact, the category of groups can be *defined* by stating that a group is a magma, that is a set endowed with an internal binary multiplication, which satisfies the above axioms. Accordingly, we can construct the category of groups from the category of magmas:

```
sage: Magmas().Associative().Unital().Inverse()
Category of groups
```

In general, we can construct new categories in Sage by specifying the axioms that are satisfied by the operations of the super categories. For example, starting from the category of magmas, we can construct all the following categories just by specifying the axioms satisfied by the multiplication:

```
sage: Magmas()
Category of magmas
sage: Magmas().Unital()
Category of unital magmas
```

```
sage: Magmas().Commutative().Unital()
Category of commutative unital magmas
sage: Magmas().Unital().Commutative()
Category of commutative unital magmas
```

```
sage: Magmas().Associative()
Category of semigroups
```

```
sage: Magmas().Associative().Unital()
Category of monoids
```

```
sage: Magmas().Associative().Unital().Commutative()
Category of commutative monoids
```

```
sage: Magmas().Associative().Unital().Inverse()
Category of groups
```

Axioms and categories with axioms

Here, `Associative`, `Unital`, `Commutative` are axioms. In general, any category `Cs` in Sage can declare a new axiom `A`. Then, the *category with axiom* `Cs.A()` models the subcategory of the objects of `Cs` satisfying the axiom `A`. Similarly, for any subcategory `Ds` of `Cs`, `Ds.A()` models the subcategory of the objects of `Ds` satisfying the axiom `A`. In most cases, it's a *full subcategory* (see [Wikipedia article Subcategory](#)).

For example, the category of sets defines the `Finite` axiom, and this axiom is available in the subcategory of groups:

```
sage: Sets().Finite()
Category of finite sets
sage: Groups().Finite()
Category of finite groups
```

The meaning of each axiom is described in the documentation of the corresponding method, which can be obtained as usual by introspection:

```
sage: C = Groups()
sage: C.Finite? # not tested
```

The purpose of categories with axioms is no different from other categories: to provide bookshelves of code, documentation, mathematical knowledge, tests, for their objects. The extra feature is that, when intersecting categories, axioms are automatically combined together:

```
sage: C = Magmas().Associative() & Magmas().Unital().Inverse() & Sets().Finite(); C
Category of finite groups
sage: sorted(C.axioms())
['Associative', 'Finite', 'Inverse', 'Unital']
```

For a more advanced example, Sage knows that a ring is a set C endowed with a multiplication which distributes over addition, such that $(C, +)$ is a commutative additive group and $(C, *)$ is a monoid:

```
sage: C = (CommutativeAdditiveGroups() & Monoids()).Distributive(); C
Category of rings

sage: sorted(C.axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse',
 'AdditiveUnital', 'Associative', 'Distributive', 'Unital']
```

The infrastructure allows for specifying further deduction rules, in order to encode mathematical facts like Wedderburn's theorem:

```
sage: DivisionRings() & Sets().Finite()
Category of finite enumerated fields
```

Note: When an axiom specifies the properties of some operations in Sage, the notations for those operations are tied to this axiom. For example, as we have seen above, we need two distinct axioms for associativity: the axiom “AdditiveAssociative” is about the properties of the addition $+$, whereas the axiom “Associative” is about the properties of the multiplication $*$.

We are touching here an inherent limitation of the current infrastructure. There is indeed no support for providing generic code that is independent of the notations. In particular, the category hierarchy about additive structures (additive monoids, additive groups, ...) is completely duplicated by that for multiplicative structures (monoids, groups, ...).

As far as we know, none of the existing computer algebra systems has a good solution for this problem. The difficulty is that this is not only about a single notation but a bunch of operators and methods: $+$, $-$, `zero`, `summation`, `sum`, ... in one case, $*$, $/$, `one`, `product`, `prod`, `factor`, ... in the other. Sharing something between the two hierarchies of categories would only be useful if one could write generic code that applies in both cases; for that one needs to somehow automatically substitute the right operations in the right spots in the code. That’s kind of what we are doing manually between e.g. `AdditiveMagmas.ParentMethods.addition_table()` and `Magmas.ParentMethods.multiplication_table()`, but doing this systematically is a different beast from what we have been doing so far with just usual inheritance.

Single entry point and name space usage

A nice feature of the notation `Cs.A()` is that, from a single entry point (say the category `Magmas` as above), one can explore a whole range of related categories, typically with the help of introspection to discover which axioms are available, and without having to import new Python modules. This feature will be used in [trac ticket #15741](#) to unclutter the global name space from, for example, the many variants of the category of algebras like:

```
sage: FiniteDimensionalAlgebrasWithBasis(QQ)
Category of finite dimensional algebras with basis over Rational Field
```

There will of course be a deprecation step, but it’s recommended to prefer right away the more flexible notation:

```
sage: Algebras(QQ).WithBasis().FiniteDimensional()
Category of finite dimensional algebras with basis over Rational Field
```

Design discussion

How far should this be pushed? `Fields` should definitely stay, but should `FiniteGroups` or `DivisionRings` be removed from the global namespace? Do we want to further completely deprecate the notation `FiniteGroups()` in favor of `Groups().Finite()`?

On the potential combinatorial explosion of categories with axioms

Even for a very simple category like `Magmas`, there are about 2^5 potential combinations of the axioms! Think about what this becomes for a category with two operations $+$ and $*$:

```
sage: C = (Magmas() & AdditiveMagmas()).Distributive(); C
Category of distributive magmas and additive magmas

sage: C.Associative().AdditiveAssociative().AdditiveCommutative().AdditiveUnital().
↪AdditiveInverse()
```

(continues on next page)

(continued from previous page)

Category of rngs

```
sage: C.Associative().AdditiveAssociative().AdditiveCommutative().AdditiveUnital().
↳Unital()
```

Category of semirings

```
sage: C.Associative().AdditiveAssociative().AdditiveCommutative().AdditiveUnital().
↳AdditiveInverse().Unital()
```

Category of rings

```
sage: Rings().Division()
```

Category of division rings

```
sage: Rings().Division().Commutative()
```

Category of fields

```
sage: Rings().Division().Finite()
```

Category of finite enumerated fields

or for more advanced categories:

```
sage: g = HopfAlgebras(QQ).WithBasis().Graded().Connected().category_graph()
sage: g.set_latex_options(format="dot2tex")
sage: view(g) # not tested
```

Difference between axioms and regressive covariant functorial constructions

Our running examples here will be the axiom `FiniteDimensional` and the regressive covariant functorial construction `Graded`. Let `Cs` be some subcategory of `Modules`, say the category of modules itself:

```
sage: Cs = Modules(QQ)
```

Then, `Cs.FiniteDimensional()` (respectively `Cs.Graded()`) is the subcategory of the objects `O` of `Cs` which are finite dimensional (respectively graded).

Let also `Ds` be a subcategory of `Cs`, say:

```
sage: Ds = Algebras(QQ)
```

A finite dimensional algebra is also a finite dimensional module:

```
sage: Algebras(QQ).FiniteDimensional().is_subcategory( Modules(QQ).FiniteDimensional() )
True
```

Similarly a graded algebra is also a graded module:

```
sage: Algebras(QQ).Graded().is_subcategory( Modules(QQ).Graded() )
True
```

This is the *covariance* property: for `A` an axiom or a covariant functorial construction, if `Ds` is a subcategory of `Cs`, then `Ds.A()` is a subcategory of `Cs.A()`.

What happens if we consider reciprocally an object of `Cs.A()` which is also in `Ds`? A finite dimensional module which is also an algebra is a finite dimensional algebra:

```
sage: Modules(QQ).FiniteDimensional() & Algebras(QQ)
Category of finite dimensional algebras over Rational Field
```

On the other hand, a graded module O which is also an algebra is not necessarily a graded algebra! Indeed, the grading on O may not be compatible with the product on O :

```
sage: Modules(QQ).Graded() & Algebras(QQ)
Join of Category of algebras over Rational Field
and Category of graded vector spaces over Rational Field
```

The relevant difference between `FiniteDimensional` and `Graded` is that `FiniteDimensional` is a statement about the properties of O seen as a module (and thus does not depend on the given category), whereas `Graded` is a statement about the properties of O and all its operations in the given category.

In general, if a category satisfies a given axiom, any subcategory also satisfies that axiom. Another formulation is that, for an axiom A defined in a super category Cs of Ds , $Ds.A()$ is the intersection of the categories Ds and $Cs.A()$:

```
sage: As = Algebras(QQ).FiniteDimensional(); As
Category of finite dimensional algebras over Rational Field
sage: Bs = Algebras(QQ) & Modules(QQ).FiniteDimensional(); As
Category of finite dimensional algebras over Rational Field
sage: As is Bs
True
```

An immediate consequence is that, as we have already noticed, axioms commute:

```
sage: As = Algebras(QQ).FiniteDimensional().WithBasis(); As
Category of finite dimensional algebras with basis over Rational Field
sage: Bs = Algebras(QQ).WithBasis().FiniteDimensional(); Bs
Category of finite dimensional algebras with basis over Rational Field
sage: As is Bs
True
```

On the other hand, axioms do not necessarily commute with functorial constructions, even if the current printout may missuggest so:

```
sage: As = Algebras(QQ).Graded().WithBasis(); As
Category of graded algebras with basis over Rational Field
sage: Bs = Algebras(QQ).WithBasis().Graded(); Bs
Category of graded algebras with basis over Rational Field
sage: As is Bs
False
```

This is because `Bs` is the category of algebras endowed with basis, which are further graded; in particular the basis must respect the grading (i.e. be made of homogeneous elements). On the other hand, `As` is the category of graded algebras, which are further endowed with some basis; that basis need not respect the grading. In fact `As` is really a join category:

```
sage: type(As)
<class 'sage.categories.category.JoinCategory_with_category'>
sage: As._repr_(as_join=True)
'Join of Category of algebras with basis over Rational Field and Category of graded
↪algebras over Rational Field'
```

Todo: Improve the printing of functorial constructions and joins to raise this potentially dangerous ambiguity.

Further reading on axioms

We refer to `sage.categories.category_with_axiom` for how to implement axioms.

Wrap-up

As we have seen, there is a combinatorial explosion of possible classes. Constructing by hand the full class hierarchy would not scale unless one would restrict to a very rigid subset. Even if it was possible to construct automatically the full hierarchy, this would not scale with respect to system resources.

When designing software systems with large hierarchies of abstract classes for business objects, the difficulty is usually to identify a proper set of key concepts. Here we are lucky, as the key concepts have been long identified and are relatively few:

- Operations (+, *, ...)
- Axioms on those operations (associativity, ...)
- Constructions (Cartesian products, ...)

Better, those concepts are sufficiently well known so that a user can reasonably be expected to be familiar with the concepts that are involved for his own needs.

Instead, the difficulty is concentrated in the huge number of possible combinations, an unpredictable large subset of which being potentially of interest; at the same time, only a small – but moving – subset has code naturally attached to it.

This has led to the current design, where one focuses on writing the relatively few classes for which there is actual code or mathematical information, and lets Sage *compose dynamically and lazily* those building blocks to construct the minimal hierarchy of classes needed for the computation at hand. This allows for the infrastructure to scale smoothly as bookshelves are added, extended, or reorganized.

1.1.9 Writing a new category

Each category C **must** be provided with a method `C.super_categories()` and *can* be provided with a method `C._subcategory_hook_(D)`. Also, it may be needed to insert C into the output of the `super_categories()` method of some other category. This determines the position of C in the category graph.

A category *may* provide methods that can be used by all its objects, respectively by all elements of its objects.

Each category *should* come with a good example, in `sage.categories.examples`.

Inserting the new category into the category graph

`C.super_categories()` *must* return a list of categories, namely the *immediate* super categories of C . Of course, if you know that your new category C is an immediate super category of some existing category D , then you should also update the method `D.super_categories` to include C .

The immediate super categories of C *should not* be *join categories*. Furthermore, one always should have:

```
Cs().is_subcategory( Category.join(Cs().super_categories()) )
Cs()._cmp_key > other._cmp_key for other in Cs().super_categories()
```

This is checked by `_test_category()`.

In several cases, the category C is directly provided with a generic implementation of `super_categories`; a typical example is when C implements an axiom or a functorial construction; in such a case, C may implement `C.extra_super_categories()` to complement the super categories discovered by the generic implementation. This method needs not return immediate super categories; instead it's usually best to specify the largest super category providing the desired mathematical information. For example, the category `Magmas.Commutative.Algebras` just states that the algebra of a commutative magma is a commutative magma. This is sufficient to let Sage deduce that it's in fact a commutative algebra.

Methods for objects and elements

Different objects of the same category share some algebraic features, and very often these features can be encoded in a method, in a generic way. For example, for every commutative additive monoid, it makes sense to ask for the sum of a list of elements. Sage's category framework allows to provide a generic implementation for all objects of a category.

If you want to provide your new category with generic methods for objects (or elements of objects), then you simply add a nested class called `ParentMethods` (or `ElementMethods`). The methods of that class will automatically become methods of the objects (or the elements). For instance:

```
sage: P.<x,y> = ZZ[]
sage: P.prod([x,y,2])
2*x*y
sage: P.prod.__module__
'sage.categories.monoids'
sage: P.prod.__func__ is raw_getattr(Monoids().ParentMethods, "prod")
True
```

We recommend to study the code of one example:

```
sage: C = CommutativeAdditiveMonoids()
sage: C?? # not tested
```

On the order of super categories

The generic method `C.all_super_categories()` determines recursively the list of *all* super categories of C .

The order of the categories in this list does influence the inheritance of methods for parents and elements. Namely, if P is an object in the category C and if C_1 and C_2 are both super categories of C defining some method `foo` in `ParentMethods`, then P will use C_1 's version of `foo` if and only if C_1 appears in `C.all_super_categories()` before C_2 .

However this must be considered as an *implementation detail*: if C_1 and C_2 are incomparable categories, then the order in which they appear must be mathematically irrelevant: in particular, the methods `foo` in C_1 and C_2 must have the same semantic. Code should not rely on any specific order, as it is subject to later change. Whenever one of the implementations is preferred in some common subcategory of C_1 and C_2 , for example for efficiency reasons, the ambiguity should be resolved explicitly by defining a method `foo` in this category. See the method `some_elements` in the code of the category `FiniteCoxeterGroups` for an example.

Since [trac ticket #11943](#), `C.all_super_categories()` is computed by the so-called C3 algorithm used by Python to compute Method Resolution Order of new-style classes. Thus the order in `C.all_super_categories()`, `C.parent_class.mro()` and `C.element_class.mro()` are guaranteed to be consistent.

Since [trac ticket #13589](#), the C3 algorithm is put under control of some total order on categories. This order is not necessarily meaningful, but it guarantees that C3 always finds a consistent Method Resolution Order. For background, see [sage.misc.c3_controlled](#). A visible effect is that the order in which categories are specified in `C.super_categories()`, or in a join category, no longer influences the result of `C.all_super_categories()`.

Subcategory hook (advanced optimization feature)

The default implementation of the method `C.is_subcategory(D)` is to look up whether D appears in `C.all_super_categories()`. However, building the list of all the super categories of C is an expensive operation that is sometimes best avoided. For example, if both C and D are categories defined over a base, but the bases differ, then one knows right away that they can not be subcategories of each other.

When such a short-path is known, one can implement a method `_subcategory_hook_`. Then, `C.is_subcategory(D)` first calls `D._subcategory_hook_(C)`. If this returns `Unknown`, then `C.is_subcategory(D)` tries to find D in `C.all_super_categories()`. Otherwise, `C.is_subcategory(D)` returns the result of `D._subcategory_hook_(C)`.

By default, `D._subcategory_hook_(C)` tests whether `issubclass(C.parent_class, D.parent_class)`, which is very often giving the right answer:

```
sage: Rings()._subcategory_hook_(Algebras(QQ))
True
sage: HopfAlgebras(QQ)._subcategory_hook_(Algebras(QQ))
False
sage: Algebras(QQ)._subcategory_hook_(HopfAlgebras(QQ))
True
```

1.2 Categories

AUTHORS:

- David Kohel, William Stein and Nicolas M. Thiery

Every Sage object lies in a category. Categories in Sage are modeled on the mathematical idea of category, and are distinct from Python classes, which are a programming construct.

In most cases, typing `x.category()` returns the category to which `x` belongs. If `C` is a category and `x` is any object, `C(x)` tries to make an object in `C` from `x`. Checking if `x` belongs to `C` is done as usually by `x in C`.

See [Category](#) and [sage.categories.primer](#) for more details.

EXAMPLES:

We create a couple of categories:

```
sage: Sets()
Category of sets
sage: GSets(AbelianGroup([2,4,9]))
Category of G-sets for Multiplicative Abelian group isomorphic to C2 x C4 x C9
sage: Semigroups()
Category of semigroups
sage: VectorSpaces(FiniteField(11))
Category of vector spaces over Finite Field of size 11
sage: Ideals(IntegerRing())
Category of ring ideals in Integer Ring
```

Let's request the category of some objects:

```
sage: V = VectorSpace(RationalField(), 3)
sage: V.category()
Category of finite dimensional vector spaces with basis
over (number fields and quotient fields and metric spaces)

sage: G = SymmetricGroup(9)
sage: G.category()
Join of Category of finite enumerated permutation groups and
Category of finite weyl groups and
Category of well generated finite irreducible complex reflection groups

sage: P = PerfectMatchings(3)
sage: P.category()
Category of finite enumerated sets
```

Let's check some memberships:

```
sage: V in VectorSpaces(QQ)
True
sage: V in VectorSpaces(FiniteField(11))
False
sage: G in Monoids()
True
sage: P in Rings()
False
```

For parametrized categories one can use the following shorthand:

```
sage: V in VectorSpaces
True
sage: G in VectorSpaces
False
```

A parent P is in a category C if $P.category()$ is a subcategory of C .

Note: Any object of a category should be an instance of `CategoryObject`.

For backward compatibility this is not yet enforced:

```
sage: class A:
.....:     def category(self):
.....:         return Fields()
sage: A() in Rings()
True
```

By default, the category of an element x of a parent P is the category of all objects of P (this is dubious and may be deprecated):

```
sage: V = VectorSpace(RationalField(), 3)
sage: v = V.gen(1)
sage: v.category()
Category of elements of Vector space of dimension 3 over Rational Field
```

class `sage.categories.category.Category`($s=None$)

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.sage_object.SageObject`

The base class for modeling mathematical categories, like for example:

- `Groups()`: the category of groups
- `EuclideanDomains()`: the category of euclidean rings
- `VectorSpaces(QQ)`: the category of vector spaces over the field of rationals

See [sage.categories.primer](#) for an introduction to categories in Sage, their relevance, purpose, and usage. The documentation below will focus on their implementation.

Technically, a category is an instance of the class `Category` or some of its subclasses. Some categories, like `VectorSpaces`, are parametrized: `VectorSpaces(QQ)` is one of many instances of the class `VectorSpaces`. On the other hand, `EuclideanDomains()` is the single instance of the class `EuclideanDomains`.

Recall that an algebraic structure (say, the ring $\mathbf{Q}[x]$) is modelled in Sage by an object which is called a parent. This object belongs to certain categories (here `EuclideanDomains()` and `Algebras()`). The elements of the ring are themselves objects.

The class of a category (say `EuclideanDomains`) can define simultaneously:

- Operations on the category itself (what is its super categories? its category of morphisms? its dual category?).
- Generic operations on parents in this category, like the ring $\mathbf{Q}[x]$.
- Generic operations on elements of such parents (e. g., the Euclidean algorithm for computing gcds).
- Generic operations on morphisms of this category.

This is achieved as follows:

```
sage: from sage.categories.all import Category
sage: class EuclideanDomains(Category):
.....:     # operations on the category itself
.....:     def super_categories(self):
.....:         [Rings()]
.....:
.....:     def dummy(self): # TODO: find some good examples
.....:         pass
.....:
.....:     class ParentMethods: # holds the generic operations on parents
.....:         # TODO: find a good example of an operation
.....:         pass
.....:
.....:     class ElementMethods:# holds the generic operations on elements
.....:         def gcd(x,y):
.....:             # Euclid algorithms
.....:             pass
.....:
.....:     class MorphismMethods: # holds the generic operations on morphisms
.....:         # TODO: find a good example of an operation
.....:         pass
.....:
```

Note that the nested class `ParentMethods` is merely a container of operations, and does not inherit from anything. Instead, the hierarchy relation is defined once at the level of the categories, and the actual hierarchy of classes is built in parallel from all the `ParentMethods` nested classes, and stored in the attributes `parent_class`. Then, a parent in a category `C` receives the appropriate operations from all the super categories by usual class inheritance from `C.parent_class`.

Similarly, two other hierarchies of classes, for elements and morphisms respectively, are built from all the `ElementMethods` and `MorphismMethods` nested classes.

EXAMPLES:

We define a hierarchy of four categories `As()`, `Bs()`, `Cs()`, `Ds()` with a diamond inheritance. Think for example:

- `As()`: the category of sets
- `Bs()`: the category of additive groups
- `Cs()`: the category of multiplicative monoids
- `Ds()`: the category of rings

```
sage: from sage.categories.all import Category
sage: from sage.misc.lazy_attribute import lazy_attribute
sage: class As (Category):
.....:     def super_categories(self):
.....:         return []
.....:
.....:     class ParentMethods:
.....:         def fA(self):
.....:             return "A"
.....:         f = fA
```

(continues on next page)

(continued from previous page)

```

sage: class Bs (Category):
.....:     def super_categories(self):
.....:         return [As()]
.....:
.....:     class ParentMethods:
.....:         def fB(self):
.....:             return "B"

sage: class Cs (Category):
.....:     def super_categories(self):
.....:         return [As()]
.....:
.....:     class ParentMethods:
.....:         def fC(self):
.....:             return "C"
.....:         f = fC

sage: class Ds (Category):
.....:     def super_categories(self):
.....:         return [Bs(),Cs()]
.....:
.....:     class ParentMethods:
.....:         def fD(self):
.....:             return "D"

```

Categories should always have unique representation; by [trac ticket #12215](#), this means that it will be kept in cache, but only if there is still some strong reference to it.

We check this before proceeding:

```

sage: import gc
sage: idAs = id(As())
sage: _ = gc.collect()
sage: n == id(As())
False
sage: a = As()
sage: id(As()) == id(As())
True
sage: As().parent_class == As().parent_class
True

```

We construct a parent in the category `Ds()` (that, is an instance of `Ds().parent_class`), and check that it has access to all the methods provided by all the categories, with the appropriate inheritance order:

```

sage: D = Ds().parent_class()
sage: [ D.fA(), D.fB(), D.fC(), D.fD() ]
['A', 'B', 'C', 'D']
sage: D.f()
'C'

```

```

sage: C = Cs().parent_class()
sage: [ C.fA(), C.fC() ]
['A', 'C']

```

(continues on next page)

(continued from previous page)

```
sage: C.f()
'C'
```

Here is the parallel hierarchy of classes which has been built automatically, together with the method resolution order (.mro()):

```
sage: As().parent_class
<class '__main__.As.parent_class'>
sage: As().parent_class.__bases__
(<... 'object'>,)
sage: As().parent_class.mro()
[<class '__main__.As.parent_class'>, <... 'object'>]
```

```
sage: Bs().parent_class
<class '__main__.Bs.parent_class'>
sage: Bs().parent_class.__bases__
(<class '__main__.As.parent_class'>,)
sage: Bs().parent_class.mro()
[<class '__main__.Bs.parent_class'>, <class '__main__.As.parent_class'>, <...
↪ 'object'>]
```

```
sage: Cs().parent_class
<class '__main__.Cs.parent_class'>
sage: Cs().parent_class.__bases__
(<class '__main__.As.parent_class'>,)
sage: Cs().parent_class.__mro__
(<class '__main__.Cs.parent_class'>, <class '__main__.As.parent_class'>, <...
↪ 'object'>)
```

```
sage: Ds().parent_class
<class '__main__.Ds.parent_class'>
sage: Ds().parent_class.__bases__
(<class '__main__.Cs.parent_class'>, <class '__main__.Bs.parent_class'>)
sage: Ds().parent_class.mro()
[<class '__main__.Ds.parent_class'>, <class '__main__.Cs.parent_class'>, <class '__
↪ main__.Bs.parent_class'>, <class '__main__.As.parent_class'>, <... 'object'>]
```

Note that two categories in the same class need not have the same `super_categories`. For example, `Algebras(QQ)` has `VectorSpaces(QQ)` as super category, whereas `Algebras(ZZ)` only has `Modules(ZZ)` as super category. In particular, the constructed parent class and element class will differ (inheriting, or not, methods specific for vector spaces):

```
sage: Algebras(QQ).parent_class is Algebras(ZZ).parent_class
False
sage: issubclass(Algebras(QQ).parent_class, VectorSpaces(QQ).parent_class)
True
```

On the other hand, identical hierarchies of classes are, preferably, built only once (e.g. for categories over a base ring):

```
sage: Algebras(GF(5)).parent_class is Algebras(GF(7)).parent_class
True
```

(continues on next page)

(continued from previous page)

```

sage: F = FractionField(ZZ['t'])
sage: Coalgebras(F).parent_class is Coalgebras(FractionField(F['x'])).parent_class
True

```

We now construct a parent in the usual way:

```

sage: class myparent(Parent):
.....:     def __init__(self):
.....:         Parent.__init__(self, category=Ds())
.....:     def g(self):
.....:         return "myparent"
.....:     class Element(object):
.....:         pass
sage: D = myparent()
sage: D.__class__
<class '__main__.myparent_with_category'>
sage: D.__class__.__bases__
(<class '__main__.myparent'>, <class '__main__.Ds.parent_class'>)
sage: D.__class__.mro()
[<class '__main__.myparent_with_category'>,
<class '__main__.myparent'>,
<type 'sage.structure.parent.Parent'>,
<type 'sage.structure.category_object.CategoryObject'>,
<type 'sage.structure.sage_object.SageObject'>,
<class '__main__.Ds.parent_class'>,
<class '__main__.Cs.parent_class'>,
<class '__main__.Bs.parent_class'>,
<class '__main__.As.parent_class'>,
<... 'object'>]
sage: D.fA()
'A'
sage: D.fB()
'B'
sage: D.fC()
'C'
sage: D.fD()
'D'
sage: D.f()
'C'
sage: D.g()
'myparent'

```

```

sage: D.element_class
<class '__main__.myparent_with_category.element_class'>
sage: D.element_class.mro()
[<class '__main__.myparent_with_category.element_class'>,
<class '...__main__...Element...'>,
<class '__main__.Ds.element_class'>,
<class '__main__.Cs.element_class'>,
<class '__main__.Bs.element_class'>,
<class '__main__.As.element_class'>,
<... 'object'>]

```

`_super_categories()`

The immediate super categories of this category.

This lazy attribute caches the result of the mandatory method `super_categories()` for speed. It also does some mangling (flattening join categories, sorting, ...).

Whenever speed matters, developers are advised to use this lazy attribute rather than calling `super_categories()`.

Note: This attribute is likely to eventually become a tuple. When this happens, we might as well use `Category._sort()`, if not `Category._sort_uniq()`.

EXAMPLES:

```
sage: Rings()._super_categories
[Category of rngs, Category of semirings]
```

`_super_categories_for_classes()`

The super categories of this category used for building classes.

This is a close variant of `_super_categories()` used for constructing the list of the bases for `parent_class()`, `element_class()`, and friends. The purpose is ensure that Python will find a proper Method Resolution Order for those classes. For background, see `sage.misc.c3_controlled`.

See also:

`_cmp_key()`.

Note: This attribute is calculated as a by-product of computing `_all_super_categories()`.

EXAMPLES:

```
sage: Rings()._super_categories_for_classes
[Category of rngs, Category of semirings]
```

`_all_super_categories()`

All the super categories of this category, including this category.

Since [trac ticket #11943](#), the order of super categories is determined by Python's method resolution order C3 algorithm.

See also:

`all_super_categories()`

Note: this attribute is likely to eventually become a tuple.

Note: this sets `_super_categories_for_classes()` as a side effect

EXAMPLES:

```
sage: C = Rings(); C
Category of rings
```

(continues on next page)

(continued from previous page)

```

sage: C._all_super_categories
[Category of rings, Category of rngs, Category of semirings, ...
Category of monoids, ...
Category of commutative additive groups, ...
Category of sets, Category of sets with partial maps,
Category of objects]

```

`_all_super_categories_proper()`

All the proper super categories of this category.

Since [trac ticket #11943](#), the order of super categories is determined by Python's method resolution order C3 algorithm.

See also:

[`all_super_categories\(\)`](#)

Note: this attribute is likely to eventually become a tuple.

EXAMPLES:

```

sage: C = Rings(); C
Category of rings
sage: C._all_super_categories_proper
[Category of rngs, Category of semirings, ...
Category of monoids, ...
Category of commutative additive groups, ...
Category of sets, Category of sets with partial maps,
Category of objects]

```

`_set_of_super_categories()`

The frozen set of all proper super categories of this category.

Note: this is used for speeding up category containment tests.

See also:

[`all_super_categories\(\)`](#)

EXAMPLES:

```

sage: sorted(Groups()._set_of_super_categories, key=str)
[Category of inverse unital magmas,
Category of magmas,
Category of monoids,
Category of objects,
Category of semigroups,
Category of sets,
Category of sets with partial maps,
Category of unital magmas]
sage: sorted(Groups()._set_of_super_categories, key=str)
[Category of inverse unital magmas, Category of magmas, Category of monoids,

```

(continues on next page)

(continued from previous page)

Category of objects, Category of semigroups, Category of sets,
Category of sets with partial maps, Category of unital magmas]

`_make_named_class`(*name*, *method_provider*, *cache=False*, *picklable=True*)

Construction of the parent/element/... class of `self`.

INPUT:

- `name` – a string; the name of the class as an attribute of `self`. E.g. “parent_class”
- `method_provider` – a string; the name of an attribute of `self` that provides methods for the new class (in addition to those coming from the super categories). E.g. “ParentMethods”
- `cache` – a boolean or `ignore_reduction` (default: `False`) (passed down to `dynamic_class`; for internal use only)
- `picklable` – a boolean (default: `True`)

ASSUMPTION:

It is assumed that this method is only called from a lazy attribute whose name coincides with the given name.

OUTPUT:

A dynamic class with bases given by the corresponding named classes of `self`’s `super_categories`, and methods taken from the class `getattr(self, method_provider)`.

Note:

- In this default implementation, the reduction data of the named class makes it depend on `self`. Since the result is going to be stored in a lazy attribute of `self` anyway, we may as well disable the caching in `dynamic_class` (hence the default value `cache=False`).
 - `CategoryWithParameters` overrides this method so that the same parent/element/... classes can be shared between closely related categories.
 - The bases of the named class may also contain the named classes of some indirect super categories, according to `_super_categories_for_classes()`. This is to guarantee that Python will build consistent method resolution orders. For background, see `sage.misc.c3_controlled`.
-

See also:

`CategoryWithParameters._make_named_class()`

EXAMPLES:

```
sage: PC = Rings()._make_named_class("parent_class", "ParentMethods"); PC
<class 'sage.categories.rings.Rings.parent_class'>
sage: type(PC)
<class 'sage.structure.dynamic_class.DynamicMetaClass'>
sage: PC.__bases__
(<class 'sage.categories.rngs.Rngs.parent_class'>,
 <class 'sage.categories.semirings.Semirings.parent_class'>)
```

Note that, by default, the result is not cached:

```
sage: PC is Rings()._make_named_class("parent_class", "ParentMethods")
False
```

Indeed this method is only meant to construct lazy attributes like `parent_class` which already handle this caching:

```
sage: Rings().parent_class
<class 'sage.categories.rings.Rings.parent_class'>
```

Reduction for pickling also assumes the existence of this lazy attribute:

```
sage: PC._reduction
(<built-in function getattr>, (Category of rings, 'parent_class'))
sage: loads(dumps(PC)) is Rings().parent_class
True
```

`_repr_()`

Return the print representation of this category.

EXAMPLES:

```
sage: Sets() # indirect doctest
Category of sets
```

`_repr_object_names()`

Return the name of the objects of this category.

EXAMPLES:

```
sage: FiniteGroups()._repr_object_names()
'finite groups'
sage: AlgebrasWithBasis(QQ)._repr_object_names()
'algebras with basis over Rational Field'
```

`_test_category(**options)`

Run generic tests on this category

See also:

`TestSuite`.

EXAMPLES:

```
sage: Sets()._test_category()
```

Let us now write a couple broken categories:

```
sage: class MyObjects(Category):
....:     pass
sage: MyObjects()._test_category()
Traceback (most recent call last):
...
NotImplementedError: <abstract method super_categories at ...>

sage: class MyObjects(Category):
....:     def super_categories(self):
....:         return tuple()
sage: MyObjects()._test_category()
Traceback (most recent call last):
...
```

(continues on next page)

(continued from previous page)

```

AssertionError: Category of my objects.super_categories() should return a list
sage: class MyObjects(Category):
.....:     def super_categories(self):
.....:         return []
sage: MyObjects()._test_category()
Traceback (most recent call last):
...
AssertionError: Category of my objects is not a subcategory of Objects()

```

`_with_axiom`(*axiom*)

Return the subcategory of the objects of `self` satisfying the given axiom.

INPUT:

- `axiom` – a string, the name of an axiom

EXAMPLES:

```

sage: Sets()._with_axiom("Finite")
Category of finite sets

sage: type(Magmas().Finite().Commutative())
<class 'sage.categories.category.JoinCategory_with_category'>
sage: Magmas().Finite().Commutative().super_categories()
[Category of commutative magmas, Category of finite sets]
sage: Algebras(QQ).WithBasis().Commutative() is Algebras(QQ).Commutative().
↳WithBasis()
True

```

When `axiom` is not defined for `self`, `self` is returned:

```

sage: Sets()._with_axiom("Associative")
Category of sets

```

Warning: This may be changed in the future to raising an error.

`_with_axiom_as_tuple`(*axiom*)

Return a tuple of categories whose join is `self._with_axiom()`.

INPUT:

- `axiom` – a string, the name of an axiom

This is a lazy version of `_with_axiom()` which is used to avoid recursion loops during join calculations.

Note: The order in the result is irrelevant.

EXAMPLES:

```

sage: Sets()._with_axiom_as_tuple('Finite')
(Category of finite sets,)
sage: Magmas()._with_axiom_as_tuple('Finite')

```

(continues on next page)

(continued from previous page)

```
(Category of magmas, Category of finite sets)
sage: Rings().Division()._with_axiom_as_tuple('Finite')
(Category of division rings,
 Category of finite monoids,
 Category of commutative magmas,
 Category of finite additive groups)
sage: HopfAlgebras(QQ)._with_axiom_as_tuple('FiniteDimensional')
(Category of hopf algebras over Rational Field,
 Category of finite dimensional modules over Rational Field)
```

`_without_axioms`(*named=False*)

Return the category without the axioms that have been added to create it.

INPUT:

- `named` – a boolean (default: `False`)

Todo: Improve this explanation.

If `named` is `True`, then this stops at the first category that has an explicit name of its own. See `category_with_axiom.CategoryWithAxiom._without_axioms()`

EXAMPLES:

```
sage: Sets()._without_axioms()
Category of sets
sage: Semigroups()._without_axioms()
Category of magmas
sage: Algebras(QQ).Commutative().WithBasis()._without_axioms()
Category of magmatic algebras over Rational Field
sage: Algebras(QQ).Commutative().WithBasis()._without_axioms(named=True)
Category of algebras over Rational Field
```

`static _sort`(*categories*)

Return the categories after sorting them decreasingly according to their comparison key.

See also:`_cmp_key()`

INPUT:

- `categories` – a list (or iterable) of non-join categories

OUTPUT:

A sorted tuple of categories, possibly with repeats.

Note: The auxiliary function `flatten_categories` used in the test below expects a second argument, which is a type such that instances of that type will be replaced by its super categories. Usually, this type is `JoinCategory`.

EXAMPLES:

```

sage: Category._sort([Sets(), Objects(), Coalgebras(QQ), Monoids(), Sets().
↳Finite()])
(Category of monoids,
 Category of coalgebras over Rational Field,
 Category of finite sets,
 Category of sets,
 Category of objects)
sage: Category._sort([Sets().Finite(), Semigroups().Finite(), Sets().Facade(),
↳Magmas().Commutative()])
(Category of finite semigroups,
 Category of commutative magmas,
 Category of finite sets,
 Category of facade sets)
sage: Category._sort(Category._flatten_categories([Sets().Finite(),
↳Algebras(QQ).WithBasis(), Semigroups().Finite(), Sets().Facade(), Algebras(QQ).
↳Commutative(), Algebras(QQ).Graded().WithBasis()], sage.categories.category.
↳JoinCategory))
(Category of algebras with basis over Rational Field,
 Category of algebras with basis over Rational Field,
 Category of graded algebras over Rational Field,
 Category of commutative algebras over Rational Field,
 Category of finite semigroups,
 Category of finite sets,
 Category of facade sets)

```

static `_sort_uniq(categories)`

Return the categories after sorting them and removing redundant categories.

Redundant categories include duplicates and categories which are super categories of other categories in the input.

INPUT:

- `categories` – a list (or iterable) of categories

OUTPUT: a sorted tuple of mutually incomparable categories

EXAMPLES:

```

sage: Category._sort_uniq([Rings(), Monoids(), Coalgebras(QQ)])
(Category of rings, Category of coalgebras over Rational Field)

```

Note that, in the above example, `Monoids()` does not appear in the result because it is a super category of `Rings()`.

static `__classcall__(*args, **options)`

Input mangling for unique representation.

Let `C = Cs(...)` be a category. Since [trac ticket #12895](#), the class of `C` is a dynamic subclass `Cs_with_category` of `Cs` in order for `C` to inherit code from the `SubcategoryMethods` nested classes of its super categories.

The purpose of this `__classcall__` method is to ensure that reconstructing `C` from its class with `Cs_with_category(...)` actually calls properly `Cs(...)` and gives back `C`.

See also:

[`subcategory_class\(\)`](#)

EXAMPLES:

```
sage: A = Algebras(QQ)
sage: A.__class__
<class 'sage.categories.algebras.Algebras_with_category'>
sage: A is Algebras(QQ)
True
sage: A is A.__class__(QQ)
True
```

`__init__(s=None)`

Initialize this category.

EXAMPLES:

```
sage: class SemiprimitiveRings(Category):
...:     def super_categories(self):
...:         return [Rings()]
...:     class ParentMethods:
...:         def jacobson_radical(self):
...:             return self.ideal(0)
sage: C = SemiprimitiveRings()
sage: C
Category of semiprimitive rings
sage: C.__class__
<class '__main__.SemiprimitiveRings_with_category'>
```

Note: Specifying the name of this category by passing a string is deprecated. If the default name (built from the name of the class) is not adequate, please use `_repr_object_names()` to customize it.

Realizations()

Return the category of realizations of the parent `self` or of objects of the category `self`

INPUT:

- `self` – a parent or a concrete category

Note: this *function* is actually inserted as a *method* in the class `Category` (see `Realizations()`). It is defined here for code locality reasons.

EXAMPLES:

The category of realizations of some algebra:

```
sage: Algebras(QQ).Realizations()
Join of Category of algebras over Rational Field and Category of realizations_
↳ of unital magmas
```

The category of realizations of a given algebra:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.Realizations()
```

(continues on next page)

(continued from previous page)

```

Category of realizations of The subset algebra of {1, 2, 3} over Rational Field
sage: C = GradedHopfAlgebrasWithBasis(QQ).Realizations(); C
Join of Category of graded hopf algebras with basis over Rational Field and
↳Category of realizations of hopf algebras over Rational Field
sage: C.super_categories()
[Category of graded hopf algebras with basis over Rational Field, Category of
↳realizations of hopf algebras over Rational Field]
sage: TestSuite(C).run()

```

See also:

- `Sets().WithRealizations`
- `ClasscallMetaclass`

Todo: Add an optional argument to allow for:

```
sage: Realizations(A, category = Blahs()) # todo: not implemented
```

WithRealizations()

Return the category of parents in self endowed with multiple realizations.

INPUT:

- self – a category

See also:

- The documentation and code (`sage.categories.examples.with_realizations`) of `Sets().WithRealizations().example()` for more on how to use and implement a parent with several realizations.
- Various use cases:
 - `SymmetricFunctions`
 - `QuasiSymmetricFunctions`
 - `NonCommutativeSymmetricFunctions`
 - `SymmetricFunctionsNonCommutingVariables`
 - `DescentAlgebra`
 - `algebras.Moebius`
 - `IwahoriHeckeAlgebra`
 - `ExtendedAffineWeylGroup`
- The `Implementing Algebraic Structures` thematic tutorial.
- `sage.categories.realizations`

Note: this *function* is actually inserted as a *method* in the class `Category` (see `WithRealizations()`). It is defined here for code locality reasons.

EXAMPLES:

```
sage: Sets().WithRealizations()
Category of sets with realizations
```

Parent with realizations

Let us now explain the concept of realizations. A *parent with realizations* is a facade parent (see `Sets.Facade`) admitting multiple concrete realizations where its elements are represented. Consider for example an algebra A which admits several natural bases:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
```

For each such basis B one implements a parent P_B which realizes A with its elements represented by expanding them on the basis B :

```
sage: A.F()
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis
sage: A.Out()
The subset algebra of {1, 2, 3} over Rational Field in the Out basis
sage: A.In()
The subset algebra of {1, 2, 3} over Rational Field in the In basis

sage: A.an_element()
F[{}] + 2*F[{1}] + 3*F[{2}] + F[{1, 2}]
```

If B and B' are two bases, then the change of basis from B to B' is implemented by a canonical coercion between P_B and $P_{B'}$:

```
sage: F = A.F(); In = A.In(); Out = A.Out()
sage: i = In.an_element(); i
In[{}] + 2*In[{1}] + 3*In[{2}] + In[{1, 2}]
sage: F(i)
7*F[{}] + 3*F[{1}] + 4*F[{2}] + F[{1, 2}]
sage: F.coerce_map_from(Out)
Generic morphism:
  From: The subset algebra of {1, 2, 3} over Rational Field in the Out basis
  To:   The subset algebra of {1, 2, 3} over Rational Field in the Fundamental
↪basis
```

allowing for mixed arithmetic:

```
sage: (1 + Out.from_set(1)) * In.from_set(2,3)
Out[{}] + 2*Out[{1}] + 2*Out[{2}] + 2*Out[{3}] + 2*Out[{1, 2}] + 2*Out[{1, 3}]
↪+ 4*Out[{2, 3}] + 4*Out[{1, 2, 3}]
```

In our example, there are three realizations:

```
sage: A.realizations()
[The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis,
The subset algebra of {1, 2, 3} over Rational Field in the In basis,
The subset algebra of {1, 2, 3} over Rational Field in the Out basis]
```

Instead of manually defining the shorthands `F`, `In`, and `Out`, as above one can just do:

```
sage: A.inject_shorthands()
Defining F as shorthand for The subset algebra of {1, 2, 3} over Rational Field_
↳in the Fundamental basis
Defining In as shorthand for The subset algebra of {1, 2, 3} over Rational_
↳Field in the In basis
Defining Out as shorthand for The subset algebra of {1, 2, 3} over Rational_
↳Field in the Out basis
```

Rationale

Besides some goodies described below, the role of A is threefold:

- To provide, as illustrated above, a single entry point for the algebra as a whole: documentation, access to its properties and different realizations, etc.
- To provide a natural location for the initialization of the bases and the coercions between, and other methods that are common to all bases.
- To let other objects refer to A while allowing elements to be represented in any of the realizations.

We now illustrate this second point by defining the polynomial ring with coefficients in A :

```
sage: P = A['x']; P
Univariate Polynomial Ring in x over The subset algebra of {1, 2, 3} over_
↳Rational Field
sage: x = P.gen()
```

In the following examples, the coefficients turn out to be all represented in the F basis:

```
sage: P.one()
F[{}]
sage: (P.an_element() + 1)^2
F[{}]*x^2 + 2*F[{}]*x + F[{}]
```

However we can create a polynomial with mixed coefficients, and compute with it:

```
sage: p = P([1, In[{1}], Out[{2}] ]); p
Out[{2}]*x^2 + In[{1}]*x + F[{}]
sage: p^2
Out[{2}]*x^4
+ (-8*In[{}] + 4*In[{1}] + 8*In[{2}] + 4*In[{3}] - 4*In[{1, 2}] - 2*In[{1, 3}] -
↳ 4*In[{2, 3}] + 2*In[{1, 2, 3}])*x^3
+ (F[{}] + 3*F[{1}] + 2*F[{2}] - 2*F[{1, 2}] - 2*F[{2, 3}] + 2*F[{1, 2, 3}])*x^2
+ (2*F[{}] + 2*F[{1}])*x
+ F[{}]
```

Note how each coefficient involves a single basis which need not be that of the other coefficients. Which basis is used depends on how coercion happened during mixed arithmetic and needs not be deterministic.

One can easily coerce all coefficient to a given basis with:

```
sage: p.map_coefficients(In)
(-4*In[{}] + 2*In[{1}] + 4*In[{2}] + 2*In[{3}] - 2*In[{1, 2}] - In[{1, 3}] -
↳2*In[{2, 3}] + In[{1, 2, 3}])*x^2 + In[{1}]*x + In[{}]
```

Alas, the natural notation for constructing such polynomials does not yet work:

```
sage: In[{1}] * x
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *: 'The subset algebra of {1, 2, 3}
↳ over Rational Field in the In basis' and 'Univariate Polynomial Ring in x
↳ over The subset algebra of {1, 2, 3} over Rational Field'
```

The category of realizations of A

The set of all realizations of A , together with the coercion morphisms is a category (whose class inherits from `Category_realization_of_parent`):

```
sage: A.Realizations()
Category of realizations of The subset algebra of {1, 2, 3} over Rational Field
```

The various parent realizing A belong to this category:

```
sage: A.F() in A.Realizations()
True
```

A itself is in the category of algebras with realizations:

```
sage: A in Algebras(QQ).WithRealizations()
True
```

The (mostly technical) `WithRealizations` categories are the analogs of the `*WithSeveralBases` categories in MuPAD-Combinat. They provide support tools for handling the different realizations and the morphisms between them.

Typically, `VectorSpaces(QQ).FiniteDimensional().WithRealizations()` will eventually be in charge, whenever a coercion $\phi : A \mapsto B$ is registered, to register ϕ^{-1} as coercion $B \mapsto A$ if there is none defined yet. To achieve this, `FiniteDimensionalVectorSpaces` would provide a nested class `WithRealizations` implementing the appropriate logic.

`WithRealizations` is a *regressive covariant functorial construction*. On our example, this simply means that A is automatically in the category of rings with realizations (covariance):

```
sage: A in Rings().WithRealizations()
True
```

and in the category of algebras (regressiveness):

```
sage: A in Algebras(QQ)
True
```

Note: For C a category, `C.WithRealizations()` in fact calls `sage.categories.with_realizations.WithRealizations(C)`. The later is responsible for building the hierarchy

of the categories with realizations in parallel to that of their base categories, optimizing away those categories that do not provide a `WithRealizations` nested class. See [sage.categories.covariant_functorial_construction](#) for the technical details.

Note: Design question: currently `WithRealizations` is a regressive construction. That is `self.WithRealizations()` is a subcategory of `self` by default:

```
sage: Algebras(QQ).WithRealizations().super_categories()
[Category of algebras over Rational Field,
 Category of monoids with realizations,
 Category of additive unital additive magmas with realizations]
```

Is this always desirable? For example, `AlgebrasWithBasis(QQ).WithRealizations()` should certainly be a subcategory of `Algebras(QQ)`, but not of `AlgebrasWithBasis(QQ)`. This is because `AlgebrasWithBasis(QQ)` is specifying something about the concrete realization.

`additional_structure()`

Return whether `self` defines additional structure.

OUTPUT:

- `self` if `self` defines additional structure and `None` otherwise. This default implementation returns `self`.

A category C *defines additional structure* if C -morphisms shall preserve more structure (e.g. operations) than that specified by the super categories of C . For example, the category of magmas defines additional structure, namely the operation `*` that shall be preserved by magma morphisms. On the other hand the category of rings does not define additional structure: a function between two rings that is both a unital magma morphism and a unital additive magma morphism is automatically a ring morphism.

Formally speaking C *defines additional structure*, if C is *not* a full subcategory of the join of its super categories: the morphisms need to preserve more structure, and thus the homsets are smaller.

By default, a category is considered as defining additional structure, unless it is a *category with axiom*.

EXAMPLES:

Here are some typical structure categories, with the additional structure they define:

```
sage: Sets().additional_structure()
Category of sets
sage: Magmas().additional_structure()      # `*`
Category of magmas
sage: AdditiveMagmas().additional_structure() # `+`
Category of additive magmas
sage: LeftModules(ZZ).additional_structure() # left multiplication by scalar
Category of left modules over Integer Ring
sage: Coalgebras(QQ).additional_structure() # coproduct
Category of coalgebras over Rational Field
sage: Crystals().additional_structure()    # crystal operators
Category of crystals
```

On the other hand, the category of semigroups is not a structure category, since its operation `+` is already defined by the category of magmas:

```
sage: Semigroups().additional_structure()
```

Most *categories with axiom* don't define additional structure:

```
sage: Sets().Finite().additional_structure()
sage: Rings().Commutative().additional_structure()
sage: Modules(QQ).FiniteDimensional().additional_structure()
sage: from sage.categories.magmatic_algebras import MagmaticAlgebras
sage: MagmaticAlgebras(QQ).Unital().additional_structure()
```

As of Sage 6.4, the only exceptions are the category of unital magmas or the category of unital additive magmas (both define a unit which shall be preserved by morphisms):

```
sage: Magmas().Unital().additional_structure()
Category of unital magmas
sage: AdditiveMagmas().AdditiveUnital().additional_structure()
Category of additive unital additive magmas
```

Similarly, *functorial construction categories* don't define additional structure, unless the construction is actually defined by their base category. For example, the category of graded modules defines a grading which shall be preserved by morphisms:

```
sage: Modules(ZZ).Graded().additional_structure()
Category of graded modules over Integer Ring
```

On the other hand, the category of graded algebras does not define additional structure; indeed an algebra morphism which is also a module morphism is a graded algebra morphism:

```
sage: Algebras(ZZ).Graded().additional_structure()
```

Similarly, morphisms are requested to preserve the structure given by the following constructions:

```
sage: Sets().Quotients().additional_structure()
Category of quotients of sets
sage: Sets().CartesianProducts().additional_structure()
Category of Cartesian products of sets
sage: Modules(QQ).TensorProducts().additional_structure()
```

This might change, as we are lacking enough data points to guarantee that this was the correct design decision.

Note: In some cases a category defines additional structure, where the structure can be useful to manipulate morphisms but where, in most use cases, we don't want the morphisms to necessarily preserve it. For example, in the context of finite dimensional vector spaces, having a distinguished basis allows for representing morphisms by matrices; yet considering only morphisms that preserve that distinguished basis would be boring.

In such cases, we might want to eventually have two categories, one where the additional structure is preserved, and one where it's not necessarily preserved (we would need to find an idiom for this).

At this point, a choice is to be made each time, according to the main use cases. Some of those choices are yet to be settled. For example, should by default:

- an euclidean domain morphism preserve euclidean division?

```
sage: EuclideanDomains().additional_structure()
Category of euclidean domains
```

- an enumerated set morphism preserve the distinguished enumeration?

```
sage: EnumeratedSets().additional_structure()
```

- a module with basis morphism preserve the distinguished basis?

```
sage: Modules(QQ).WithBasis().additional_structure()
```

See also:

This method together with the methods overloading it provide the basic data to determine, for a given category, the super categories that define some structure (see `structure()`), and to test whether a category is a full subcategory of some other category (see `is_full_subcategory()`). For example, the category of Coxeter groups is not full subcategory of the category of groups since morphisms need to preserve the distinguished generators:

```
sage: CoxeterGroups().is_full_subcategory(Groups())
False
```

The support for modeling full subcategories has been introduced in [trac ticket #16340](#).

`all_super_categories(proper=False)`

Returns the list of all super categories of this category.

INPUT:

- `proper` – a boolean (default: `False`); whether to exclude this category.

Since [trac ticket #11943](#), the order of super categories is determined by Python's method resolution order C3 algorithm.

Note: Whenever speed matters, the developers are advised to use instead the lazy attributes `_all_super_categories()`, `_all_super_categories_proper()`, or `_set_of_super_categories()`, as appropriate. Simply because lazy attributes are much faster than any method.

EXAMPLES:

```
sage: C = Rings(); C
Category of rings
sage: C.all_super_categories()
[Category of rings, Category of rngs, Category of semirings, ...
Category of monoids, ...
Category of commutative additive groups, ...
Category of sets, Category of sets with partial maps,
Category of objects]

sage: C.all_super_categories(proper = True)
[Category of rngs, Category of semirings, ...
Category of monoids, ...
Category of commutative additive groups, ...
```

(continues on next page)

(continued from previous page)

```
Category of sets, Category of sets with partial maps,
Category of objects]
```

```
sage: Sets().all_super_categories()
[Category of sets, Category of sets with partial maps, Category of objects]
sage: Sets().all_super_categories(proper=True)
[Category of sets with partial maps, Category of objects]
sage: Sets().all_super_categories() is Sets()._all_super_categories
True
sage: Sets().all_super_categories(proper=True) is Sets()._all_super_categories_
↳proper
True
```

classmethod an_instance()

Return an instance of this class.

EXAMPLES:

```
sage: Rings.an_instance()
Category of rings
```

Parametrized categories should overload this default implementation to provide appropriate arguments:

```
sage: Algebras.an_instance()
Category of algebras over Rational Field
sage: Bimodules.an_instance()
Category of bimodules over Rational Field on the left and Real Field with 53_
↳bits of precision on the right
sage: AlgebraIdeals.an_instance()
Category of algebra ideals in Univariate Polynomial Ring in x over Rational_
↳Field
```

axioms()

Return the axioms known to be satisfied by all the objects of `self`.

Technically, this is the set of all the axioms `A` such that, if `Cs` is the category defining `A`, then `self` is a subcategory of `Cs().A()`. Any additional axiom `A` would yield a strict subcategory of `self`, at the very least `self & Cs().A()` where `Cs` is the category defining `A`.

EXAMPLES:

```
sage: Monoids().axioms()
frozenset({'Associative', 'Unital'})
sage: (EnumeratedSets().Infinite() & Sets().Facade()).axioms()
frozenset({'Enumerated', 'Facade', 'Infinite'})
```

category()

Return the category of this category. So far, all categories are in the category of objects.

EXAMPLES:

```
sage: Sets().category()
Category of objects
sage: VectorSpaces(QQ).category()
Category of objects
```

category_graph()

Returns the graph of all super categories of this category

EXAMPLES:

```
sage: C = Algebras(QQ)
sage: G = C.category_graph()
sage: G.is_directed_acyclic()
True
```

The girth of a directed acyclic graph is infinite, however, the girth of the underlying undirected graph is 4 in this case:

```
sage: Graph(G).girth()
4
```

element_class()

A common super class for all elements of parents in this category (and its subcategories).

This class contains the methods defined in the nested class `self.ElementMethods` (if it exists), and has as bases the element classes of the super categories of `self`.

See also:

- `parent_class()`, `morphism_class()`
- *Category* for details

EXAMPLES:

```
sage: C = Algebras(QQ).element_class; C
<class 'sage.categories.algebras.Algebras.element_class'>
sage: type(C)
<class 'sage.structure.dynamic_class.DynamicMetaclass'>
```

By [trac ticket #11935](#), some categories share their element classes. For example, the element class of an algebra only depends on the category of the base. A typical example is the category of algebras over a field versus algebras over a non-field:

```
sage: Algebras(GF(5)).element_class is Algebras(GF(3)).element_class
True
sage: Algebras(QQ).element_class is Algebras(ZZ).element_class
False
sage: Algebras(ZZ['t']).element_class is Algebras(ZZ['t', 'x']).element_class
True
```

These classes are constructed with `__slots__ = ()`, so instances may not have a `__dict__`:

```
sage: E = FiniteEnumeratedSets().element_class
sage: E.__dictoffset__
0
```

See also:

`parent_class()`

example(*args, **keywords)

Returns an object in this category. Most of the time, this is a parent.

This serves three purposes:

- Give a typical example to better explain what the category is all about. (and by the way prove that the category is non empty :-))
- Provide a minimal template for implementing other objects in this category
- Provide an object on which to test generic code implemented by the category

For all those applications, the implementation of the object shall be kept to a strict minimum. The object is therefore not meant to be used for other applications; most of the time a full featured version is available elsewhere in Sage, and should be used instead.

Technical note: by default `FooBar(...).example()` is constructed by looking up `sage.categories.examples.foo_bar.Example` and calling it as `Example()`. Extra positional or named parameters are also passed down. For a category over base ring, the base ring is further passed down as an optional argument.

Categories are welcome to override this default implementation.

EXAMPLES:

```
sage: Semigroups().example()
An example of a semigroup: the left zero semigroup

sage: Monoids().Subquotients().example()
NotImplemented
```

`full_super_categories()`

Return the *immediate* full super categories of `self`.

See also:

- `super_categories()`
- `is_full_subcategory()`

Warning: The current implementation selects the full subcategories among the immediate super categories of `self`. This assumes that, if $C \subset B \subset A$ is a chain of categories and C is a full subcategory of A , then C is a full subcategory of B and B is a full subcategory of A .

This assumption is guaranteed to hold with the current model and implementation of full subcategories in Sage. However, mathematically speaking, this is too restrictive. This indeed prevents the complete modelling of situations where any A morphism between elements of C automatically preserves the B structure. See below for an example.

EXAMPLES:

A semigroup morphism between two finite semigroups is a finite semigroup morphism:

```
sage: Semigroups().Finite().full_super_categories()
[Category of semigroups]
```

On the other hand, a semigroup morphism between two monoids is not necessarily a monoid morphism (which must map the unit to the unit):

```
sage: Monoids().super_categories()
[Category of semigroups, Category of unital magmas]
```

(continues on next page)

(continued from previous page)

```
sage: Monoids().full_super_categories()
[Category of unital magmas]
```

Any semigroup morphism between two groups is automatically a monoid morphism (in a group the unit is the unique idempotent, so it has to be mapped to the unit). Yet, due to the limitation of the model advertised above, Sage currently cannot be taught that the category of groups is a full subcategory of the category of semigroups:

```
sage: Groups().full_super_categories() # todo: not implemented
[Category of monoids, Category of semigroups, Category of inverse unital magmas]
sage: Groups().full_super_categories()
[Category of monoids, Category of inverse unital magmas]
```

is_abelian()

Return whether this category is abelian.

An abelian category is a category satisfying:

- It has a zero object;
- It has all pullbacks and pushouts;
- All monomorphisms and epimorphisms are normal.

Equivalently, one can define an increasing sequence of conditions:

- A category is pre-additive if it is enriched over abelian groups (all homsets are abelian groups and composition is bilinear);
- A pre-additive category is additive if every finite set of objects has a biproduct (we can form direct sums and direct products);
- An additive category is pre-abelian if every morphism has both a kernel and a cokernel;
- A pre-abelian category is abelian if every monomorphism is the kernel of some morphism and every epimorphism is the cokernel of some morphism.

EXAMPLES:

```
sage: Modules(ZZ).is_abelian()
True
sage: FreeModules(ZZ).is_abelian()
False
sage: FreeModules(QQ).is_abelian()
True
sage: CommutativeAdditiveGroups().is_abelian()
True
sage: Semigroups().is_abelian()
Traceback (most recent call last):
...
NotImplementedError: is_abelian
```

is_full_subcategory(*other*)

Return whether `self` is a full subcategory of `other`.

A subcategory B of a category A is a *full subcategory* if any A -morphism between two objects of B is also a B -morphism (the reciprocal always holds: any B -morphism between two objects of B is an A -morphism).

This is computed by testing whether `self` is a subcategory of `other` and whether they have the same structure, as determined by `structure()` from the result of `additional_structure()` on the super categories.

Warning: A positive answer is guaranteed to be mathematically correct. A negative answer may mean that Sage has not been taught enough information (or can not yet within the current model) to derive this information. See `full_super_categories()` for a discussion.

See also:

- `is_subcategory()`
- `full_super_categories()`

EXAMPLES:

```
sage: Magmas().Associative().is_full_subcategory(Magmas())
True
sage: Magmas().Unital().is_full_subcategory(Magmas())
False
sage: Rings().is_full_subcategory(Magmas().Unital() & AdditiveMagmas().
↳AdditiveUnital())
True
```

Here are two typical examples of false negatives:

```
sage: Groups().is_full_subcategory(Semigroups())
False
sage: Groups().is_full_subcategory(Semigroups()) # todo: not implemented
True
sage: Fields().is_full_subcategory(Rings())
False
sage: Fields().is_full_subcategory(Rings()) # todo: not implemented
True
```

Todo: The latter is a consequence of `EuclideanDomains` currently being a structure category. Is this what we want?

```
sage: EuclideanDomains().is_full_subcategory(Rings())
False
```

`is_subcategory(c)`

Returns True if `self` is naturally embedded as a subcategory of `c`.

EXAMPLES:

```
sage: AbGrps = CommutativeAdditiveGroups()
sage: Rings().is_subcategory(AbGrps)
True
sage: AbGrps.is_subcategory(Rings())
False
```

The `is_subcategory` function takes into account the base.

```
sage: M3 = VectorSpaces(FiniteField(3))
sage: M9 = VectorSpaces(FiniteField(9, 'a'))
sage: M3.is_subcategory(M9)
False
```

Join categories are properly handled:

```
sage: CatJ = Category.join((CommutativeAdditiveGroups(), Semigroups()))
sage: Rings().is_subcategory(CatJ)
True
```

```
sage: V3 = VectorSpaces(FiniteField(3))
sage: POSet = PartiallyOrderedSets()
sage: PoV3 = Category.join((V3, POSet))
sage: A3 = AlgebrasWithBasis(FiniteField(3))
sage: PoA3 = Category.join((A3, POSet))
sage: PoA3.is_subcategory(PoV3)
True
sage: PoV3.is_subcategory(PoV3)
True
sage: PoV3.is_subcategory(PoA3)
False
```

static `join(categories, as_list=False, ignore_axioms=(), axioms=())`

Return the join of the input categories in the lattice of categories.

At the level of objects and morphisms, this operation corresponds to intersection: the objects and morphisms of a join category are those that belong to all its super categories.

INPUT:

- `categories` – a list (or iterable) of categories
- `as_list` – a boolean (default: `False`); whether the result should be returned as a list
- `axioms` – a tuple of strings; the names of some supplementary axioms

See also:

`__and__()` for a shortcut

EXAMPLES:

```
sage: J = Category.join((Groups(), CommutativeAdditiveMonoids())); J
Join of Category of groups and Category of commutative additive monoids
sage: J.super_categories()
[Category of groups, Category of commutative additive monoids]
sage: J.all_super_categories(proper=True)
[Category of groups, ..., Category of magmas,
 Category of commutative additive monoids, ..., Category of additive magmas,
 Category of sets, ...]
```

As a short hand, one can use:

```
sage: Groups() & CommutativeAdditiveMonoids()
Join of Category of groups and Category of commutative additive monoids
```

This is a commutative and associative operation:

```

sage: Groups() & Posets()
Join of Category of groups and Category of posets
sage: Posets() & Groups()
Join of Category of groups and Category of posets

sage: Groups() & (CommutativeAdditiveMonoids() & Posets())
Join of Category of groups
    and Category of commutative additive monoids
    and Category of posets
sage: (Groups() & CommutativeAdditiveMonoids()) & Posets()
Join of Category of groups
    and Category of commutative additive monoids
    and Category of posets
    
```

The join of a single category is the category itself:

```

sage: Category.join([Monoids()])
Category of monoids
    
```

Similarly, the join of several mutually comparable categories is the smallest one:

```

sage: Category.join((Sets(), Rings(), Monoids()))
Category of rings
    
```

In particular, the unit is the top category *Objects*:

```

sage: Groups() & Objects()
Category of groups
    
```

If the optional parameter `as_list` is `True`, this returns the super categories of the join as a list, without constructing the join category itself:

```

sage: Category.join((Groups(), CommutativeAdditiveMonoids()), as_list=True)
[Category of groups, Category of commutative additive monoids]
sage: Category.join((Sets(), Rings(), Monoids()), as_list=True)
[Category of rings]
sage: Category.join((Modules(ZZ), FiniteFields()), as_list=True)
[Category of finite enumerated fields, Category of modules over Integer Ring]
sage: Category.join([], as_list=True)
[]
sage: Category.join([Groups()], as_list=True)
[Category of groups]
sage: Category.join([Groups() & Posets()], as_list=True)
[Category of groups, Category of posets]
    
```

Support for axiom categories (TODO: put here meaningful examples):

```

sage: Sets().Facade() & Sets().Infinite()
Category of facade infinite sets
sage: Magmas().Infinite() & Sets().Facade()
Category of facade infinite magmas
    
```

(continues on next page)

(continued from previous page)

```

sage: FiniteSets() & Monoids()
Category of finite monoids
sage: Rings().Commutative() & Sets().Finite()
Category of finite commutative rings

```

Note that several of the above examples are actually join categories; they are just nicely displayed:

```

sage: AlgebrasWithBasis(QQ) & FiniteSets().Algebras(QQ)
Join of Category of finite dimensional algebras with basis over Rational Field
and Category of finite set algebras over Rational Field

sage: UniqueFactorizationDomains() & Algebras(QQ)
Join of Category of unique factorization domains
and Category of commutative algebras over Rational Field

```

static meet(*categories*)

Returns the meet of a list of categories

INPUT:

- *categories* - a non empty list (or iterable) of categories

See also:

`__or__()` for a shortcut

EXAMPLES:

```

sage: Category.meet([Algebras(ZZ), Algebras(QQ), Groups()])
Category of monoids

```

That meet of an empty list should be a category which is a subcategory of all categories, which does not make practical sense:

```

sage: Category.meet([])
Traceback (most recent call last):
...
ValueError: The meet of an empty list of categories is not implemented

```

morphism_class()

A common super class for all morphisms between parents in this category (and its subcategories).

This class contains the methods defined in the nested class `self.MorphismMethods` (if it exists), and has as bases the morphism classes of the super categories of `self`.

See also:

- `parent_class()`, `element_class()`
- *Category* for details

EXAMPLES:

```

sage: C = Algebras(QQ).morphism_class; C
<class 'sage.categories.algebras.Algebras.morphism_class'>
sage: type(C)
<class 'sage.structure.dynamic_class.DynamicMetaclass'>

```


or_subcategory(*category=None, join=False*)

Return category or self if category is None.

INPUT:

- *category* – a sub category of self, tuple/list thereof, or None
- *join* – a boolean (default: False)

OUTPUT:

- a category

EXAMPLES:

```
sage: Monoids().or_subcategory(Groups())
Category of groups
sage: Monoids().or_subcategory(None)
Category of monoids
```

If category is a list/tuple, then a join category is returned:

```
sage: Monoids().or_subcategory((CommutativeAdditiveMonoids(), Groups()))
Join of Category of groups and Category of commutative additive monoids
```

If *join* is False, an error is raised if category is not a subcategory of self:

```
sage: Monoids().or_subcategory(EnumeratedSets())
Traceback (most recent call last):
...
ValueError: Subcategory of `Category of monoids` required; got `Category of
↳ enumerated sets`
```

Otherwise, the two categories are joined together:

```
sage: Monoids().or_subcategory(EnumeratedSets(), join=True)
Category of enumerated monoids
```

parent_class()

A common super class for all parents in this category (and its subcategories).

This class contains the methods defined in the nested class `self.ParentMethods` (if it exists), and has as bases the parent classes of the super categories of self.

See also:

- `element_class()`, `morphism_class()`
- `Category` for details

EXAMPLES:

```
sage: C = Algebras(QQ).parent_class; C
<class 'sage.categories.algebras.Algebras.parent_class'>
sage: type(C)
<class 'sage.structure.dynamic_class.DynamicMetaClass'>
```

By [trac ticket #11935](#), some categories share their parent classes. For example, the parent class of an algebra only depends on the category of the base ring. A typical example is the category of algebras over a finite field versus algebras over a non-field:

```

sage: Algebras(GF(7)).parent_class is Algebras(GF(5)).parent_class
True
sage: Algebras(QQ).parent_class is Algebras(ZZ).parent_class
False
sage: Algebras(ZZ['t']).parent_class is Algebras(ZZ['t','x']).parent_class
True

```

See [CategoryWithParameters](#) for an abstract base class for categories that depend on parameters, even though the parent and element classes only depend on the parent or element classes of its super categories. It is used in [Bimodules](#), [Category_over_base](#) and [sage.categories.category.JoinCategory](#).

required_methods()

Returns the methods that are required and optional for parents in this category and their elements.

EXAMPLES:

```

sage: Algebras(QQ).required_methods() # py2
{'element': {'optional': ['_add_', '_mul_'], 'required': ['__nonzero__']},
 'parent': {'optional': ['algebra_generators'], 'required': ['__contains__']}}
sage: Algebras(QQ).required_methods() # py3
{'element': {'optional': ['_add_', '_mul_'], 'required': ['__bool__']},
 'parent': {'optional': ['algebra_generators'], 'required': ['__contains__']}}

```

structure()

Return the structure `self` is endowed with.

This method returns the structure that morphisms in this category shall be preserving. For example, it tells that a ring is a set endowed with a structure of both a unital magma and an additive unital magma which satisfies some further axioms. In other words, a ring morphism is a function that preserves the unital magma and additive unital magma structure.

In practice, this returns the collection of all the super categories of `self` that define some additional structure, as a frozen set.

EXAMPLES:

```

sage: Objects().structure()
frozenset()

sage: def structure(C):
.....:     return Category._sort(C.structure())

sage: structure(Sets())
(Category of sets, Category of sets with partial maps)
sage: structure(Magmas())
(Category of magmas, Category of sets, Category of sets with partial maps)

```

In the following example, we only list the smallest structure categories to get a more readable output:

```

sage: def structure(C):
.....:     return Category._sort_uniq(C.structure())

sage: structure(Magmas())
(Category of magmas,)
sage: structure(Rings())
(Category of unital magmas, Category of additive unital additive magmas)

```

(continues on next page)

(continued from previous page)

```

sage: structure(Fields())
(Category of euclidean domains,)
sage: structure(Algebras(QQ))
(Category of unital magmas,
 Category of right modules over Rational Field,
 Category of left modules over Rational Field)
sage: structure(HopfAlgebras(QQ).Graded().WithBasis().Connected())
(Category of hopf algebras over Rational Field,
 Category of graded modules over Rational Field)

```

This method is used in `is_full_subcategory()` for deciding whether a category is a full subcategory of some other category, and for documentation purposes. It is computed recursively from the result of `additional_structure()` on the super categories of `self`.

`subcategory_class()`

A common superclass for all subcategories of this category (including this one).

This class derives from `D.subcategory_class` for each super category `D` of `self`, and includes all the methods from the nested class `self.SubcategoryMethods`, if it exists.

See also:

- [trac ticket #12895](#)
- `parent_class()`
- `element_class()`
- `_make_named_class()`

EXAMPLES:

```

sage: cls = Rings().subcategory_class; cls
<class 'sage.categories.rings.Rings.subcategory_class'>
sage: type(cls)
<class 'sage.structure.dynamic_class.DynamicMetaclass'>

```

`Rings()` is an instance of this class, as well as all its subcategories:

```

sage: isinstance(Rings(), cls)
True
sage: isinstance(AlgebrasWithBasis(QQ), cls)
True

```

`super_categories()`

Return the *immediate* super categories of `self`.

OUTPUT:

- a duplicate-free list of categories.

Every category should implement this method.

EXAMPLES:

```

sage: Groups().super_categories()
[Category of monoids, Category of inverse unital magmas]

```

(continues on next page)

(continued from previous page)

```
sage: Objects().super_categories()
[]
```

Note: Since [trac ticket #10963](#), the order of the categories in the result is irrelevant. For details, see *On the order of super categories*.

Note: Whenever speed matters, developers are advised to use the lazy attribute `_super_categories()` instead of calling this method.

class `sage.categories.category.CategoryWithParameters`(*s=None*)

Bases: `sage.categories.category.Category`

A parametrized category whose parent/element classes depend only on its super categories.

Many categories in Sage are parametrized, like `C = Algebras(K)` which takes a base ring as parameter. In many cases, however, the operations provided by `C` in the parent class and element class depend only on the super categories of `C`. For example, the vector space operations are provided if and only if `K` is a field, since `VectorSpaces(K)` is a super category of `C` only in that case. In such cases, and as an optimization (see [trac ticket #11935](#)), we want to use the same parent and element class for all fields. This is the purpose of this abstract class.

Currently, `JoinCategory`, `Category_over_base` and `Bimodules` inherit from this class.

EXAMPLES:

```
sage: C1 = Algebras(GF(5))
sage: C2 = Algebras(GF(3))
sage: C3 = Algebras(ZZ)
sage: from sage.categories.category import CategoryWithParameters
sage: isinstance(C1, CategoryWithParameters)
True
sage: C1.parent_class is C2.parent_class
True
sage: C1.parent_class is C3.parent_class
False
```

`Category._make_named_class`(*name, method_provider, cache=False, picklable=True*)

Construction of the parent/element/... class of `self`.

INPUT:

- `name` – a string; the name of the class as an attribute of `self`. E.g. “parent_class”
- `method_provider` – a string; the name of an attribute of `self` that provides methods for the new class (in addition to those coming from the super categories). E.g. “ParentMethods”
- `cache` – a boolean or `ignore_reduction` (default: `False`) (passed down to `dynamic_class`; for internal use only)
- `picklable` – a boolean (default: `True`)

ASSUMPTION:

It is assumed that this method is only called from a lazy attribute whose name coincides with the given name.

OUTPUT:

A dynamic class with bases given by the corresponding named classes of `self`'s `super_categories`, and methods taken from the class `getattr(self,method_provider)`.

Note:

- In this default implementation, the reduction data of the named class makes it depend on `self`. Since the result is going to be stored in a lazy attribute of `self` anyway, we may as well disable the caching in `dynamic_class` (hence the default value `cache=False`).
 - `CategoryWithParameters` overrides this method so that the same parent/element/... classes can be shared between closely related categories.
 - The bases of the named class may also contain the named classes of some indirect super categories, according to `_super_categories_for_classes()`. This is to guarantee that Python will build consistent method resolution orders. For background, see `sage.misc.c3_controlled`.
-

See also:

`CategoryWithParameters._make_named_class()`

EXAMPLES:

```
sage: PC = Rings()._make_named_class("parent_class", "ParentMethods"); PC
<class 'sage.categories.rings.Rings.parent_class'>
sage: type(PC)
<class 'sage.structure.dynamic_class.DynamicMetaClass'>
sage: PC.__bases__
(<class 'sage.categories.rings.Rings.parent_class'>,
 <class 'sage.categories.semiring.Semirings.parent_class'>)
```

Note that, by default, the result is not cached:

```
sage: PC is Rings()._make_named_class("parent_class", "ParentMethods")
False
```

Indeed this method is only meant to construct lazy attributes like `parent_class` which already handle this caching:

```
sage: Rings().parent_class
<class 'sage.categories.rings.Rings.parent_class'>
```

Reduction for pickling also assumes the existence of this lazy attribute:

```
sage: PC._reduction
(<built-in function getattr>, (Category of rings, 'parent_class'))
sage: loads(dumps(PC)) is Rings().parent_class
True
```

class `sage.categories.category.JoinCategory`(*super_categories*, ***kws*)
 Bases: `sage.categories.category.CategoryWithParameters`

A class for joins of several categories. Do not use directly; see `Category.join` instead.

EXAMPLES:

```

sage: from sage.categories.category import JoinCategory
sage: J = JoinCategory((Groups(), CommutativeAdditiveMonoids())); J
Join of Category of groups and Category of commutative additive monoids
sage: J.super_categories()
[Category of groups, Category of commutative additive monoids]
sage: J.all_super_categories(proper=True)
[Category of groups, ..., Category of magmas,
 Category of commutative additive monoids, ..., Category of additive magmas,
 Category of sets, Category of sets with partial maps, Category of objects]

```

By [trac ticket #11935](#), join categories and categories over base rings inherit from *CategoryWithParameters*. This allows for sharing parent and element classes between similar categories. For example, since group algebras belong to a join category and since the underlying implementation is the same for all finite fields, we have:

```

sage: G = SymmetricGroup(10)
sage: A3 = G.algebra(GF(3))
sage: A5 = G.algebra(GF(5))
sage: type(A3.category())
<class 'sage.categories.category.JoinCategory_with_category'>
sage: type(A3) is type(A5)
True

```

`Category._repr_object_names()`

Return the name of the objects of this category.

EXAMPLES:

```

sage: FiniteGroups()._repr_object_names()
'finite groups'
sage: AlgebrasWithBasis(QQ)._repr_object_names()
'algebras with basis over Rational Field'

```

`Category._repr_()`

Return the print representation of this category.

EXAMPLES:

```

sage: Sets() # indirect doctest
Category of sets

```

`Category._without_axioms(named=False)`

Return the category without the axioms that have been added to create it.

INPUT:

- `named` – a boolean (default: `False`)

Todo: Improve this explanation.

If `named` is `True`, then this stops at the first category that has an explicit name of its own. See [category_with_axiom.CategoryWithAxiom._without_axioms\(\)](#)

EXAMPLES:

```

sage: Sets()._without_axioms()
Category of sets
sage: Semigroups()._without_axioms()
Category of magmas
sage: Algebras(QQ).Commutative().WithBasis()._without_axioms()
Category of magmatic algebras over Rational Field
sage: Algebras(QQ).Commutative().WithBasis()._without_axioms(named=True)
Category of algebras over Rational Field

```

additional_structure()

Return None.

Indeed, a join category defines no additional structure.

See also:

Category.additional_structure()

EXAMPLES:

```

sage: Modules(ZZ).additional_structure()

```

is_subcategory(C)

Check whether this join category is subcategory of another category C.

EXAMPLES:

```

sage: Category.join([Rings(), Modules(QQ)]).is_subcategory(Category.join([Rngs(),
↳ Bimodules(QQ, QQ)]))
True

```

super_categories()

Returns the immediate super categories, as per *Category.super_categories()*.

EXAMPLES:

```

sage: from sage.categories.category import JoinCategory
sage: JoinCategory((Semigroups(), FiniteEnumeratedSets())).super_categories()
[Category of semigroups, Category of finite enumerated sets]

```

`sage.categories.category.category_graph(categories=None)`

Return the graph of the categories in Sage.

INPUT:

- `categories` – a list (or iterable) of categories

If `categories` is specified, then the graph contains the mentioned categories together with all their super categories. Otherwise the graph contains (an instance of) each category in `sage.categories.all` (e.g. `Algebras(QQ)` for algebras).

For readability, the names of the category are shortened.

Todo: Further remove the base ring (see also [trac ticket #15801](#)).

EXAMPLES:

```

sage: G = sage.categories.category.category_graph(categories = [Groups()])
sage: G.vertices()
['groups', 'inverse unital magmas', 'magmas', 'monoids', 'objects',
 'semigroups', 'sets', 'sets with partial maps', 'unital magmas']
sage: G.plot()
Graphics object consisting of 20 graphics primitives

sage: sage.categories.category.category_graph().plot()
Graphics object consisting of ... graphics primitives

```

`sage.categories.category.category_sample()`

Return a sample of categories.

It is constructed by looking for all concrete category classes declared in `sage.categories.all`, calling `Category.an_instance()` on those and taking all their super categories.

EXAMPLES:

```

sage: from sage.categories.category import category_sample
sage: sorted(category_sample(), key=str)
[Category of G-sets for Symmetric group of order 8! as a permutation group,
 Category of Hecke modules over Rational Field,
 Category of Lie algebras over Rational Field,
 Category of additive magmas, ...,
 Category of fields, ...,
 Category of graded hopf algebras with basis over Rational Field, ...,
 Category of modular abelian varieties over Rational Field, ...,
 Category of simplicial complexes, ...,
 Category of vector spaces over Rational Field, ...,
 Category of weyl groups, ...

```

`sage.categories.category.is_Category(x)`

Returns True if x is a category.

EXAMPLES:

```

sage: sage.categories.category.is_Category(CommutativeAdditiveSemigroups())
True
sage: sage.categories.category.is_Category(ZZ)
False

```

1.3 Axioms

This documentation covers how to implement axioms and proceeds with an overview of the implementation of the axiom infrastructure. It assumes that the reader is familiar with the *category primer*, and in particular its *section about axioms*.

1.3.1 Implementing axioms

Simple case involving a single predefined axiom

Suppose that one wants to provide code (and documentation, tests, ...) for the objects of some existing category `Cs()` that satisfy some predefined axiom `A`.

The first step is to open the hood and check whether there already exists a class implementing the category `Cs().A()`. For example, taking `Cs=Semigroups` and the `Finite` axiom, there already exists a class for the category of finite semigroups:

```
sage: Semigroups().Finite()
Category of finite semigroups
sage: type(Semigroups().Finite())
<class 'sage.categories.finite_semigroups.FiniteSemigroups_with_category'>
```

In this case, we say that the category of semigroups *implements* the axiom `Finite`, and code about finite semigroups should go in the class `FiniteSemigroups` (or, as usual, in its nested classes `ParentMethods`, `ElementMethods`, and so on).

On the other hand, there is no class for the category of infinite semigroups:

```
sage: Semigroups().Infinite()
Category of infinite semigroups
sage: type(Semigroups().Infinite())
<class 'sage.categories.category.JoinCategory_with_category'>
```

This category is indeed just constructed as the intersection of the categories of semigroups and of infinite sets respectively:

```
sage: Semigroups().Infinite().super_categories()
[Category of semigroups, Category of infinite sets]
```

In this case, one needs to create a new class to implement the axiom `Infinite` for this category. This boils down to adding a nested class `Semigroups.Infinite` inheriting from `CategoryWithAxiom`.

In the following example, we implement a category `Cs`, with a subcategory for the objects satisfying the `Finite` axiom defined in the super category `Sets` (we will see later on how to *define* new axioms):

```
sage: from sage.categories.category_with_axiom import CategoryWithAxiom
sage: class Cs(Category):
....:     def super_categories(self):
....:         return [Sets()]
....:     class Finite(CategoryWithAxiom):
....:         class ParentMethods:
....:             def foo(self):
....:                 print("I am a method on finite C's")
```

```
sage: Cs().Finite()
Category of finite cs
sage: Cs().Finite().super_categories()
[Category of finite sets, Category of cs]
sage: Cs().Finite().all_super_categories()
[Category of finite cs, Category of finite sets,
Category of cs, Category of sets, ...]
```

(continues on next page)

(continued from previous page)

```
sage: Cs().Finite().axioms()
frozenset({'Finite'})
```

Now a parent declared in the category `Cs().Finite()` inherits from all the methods of finite sets and of finite C 's, as desired:

```
sage: P = Parent(category=Cs().Finite())
sage: P.is_finite()           # Provided by Sets.Finite.ParentMethods
True
sage: P.foo()                # Provided by Cs.Finite.ParentMethods
I am a method on finite C's
```

Note:

- This follows the same idiom as for *Covariant Functorial Constructions*.
- From an object oriented point of view, any subcategory `Cs()` of `Sets` inherits a `Finite` method. Usually `Cs` could complement this method by overriding it with a method `Cs.Finite` which would make a super call to `Sets.Finite` and then do extra stuff.

In the above example, `Cs` also wants to complement `Sets.Finite`, though not by doing more stuff, but by providing it with an additional mixin class containing the code for finite `Cs`. To keep the analogy, this mixin class is to be put in `Cs.Finite`.

- By defining the axiom `Finite`, `Sets` fixes the semantic of `Cs.Finite()` for all its subcategories `Cs`: namely “the category of `Cs` which are finite as sets”. Hence, for example, `Modules.Free.Finite` cannot be used to model the category of free modules of finite rank, even though their traditional name “finite free modules” might suggest it.
- It may come as a surprise that we can actually use the same name `Finite` for the mixin class and for the method defining the axiom; indeed, by default a class does not have a binding behavior and would completely override the method. See the section *Defining a new axiom* for details and the rationale behind it.

An alternative would have been to give another name to the mixin class, like `FiniteCategory`. However this would have resulted in more namespace pollution, whereas using `Finite` is already clear, explicit, and easier to remember.

- Under the hood, the category `Cs().Finite()` is aware that it has been constructed from the category `Cs()` by adding the axiom `Finite`:

```
sage: Cs().Finite().base_category()
Category of cs
sage: Cs().Finite()._axiom
'Finite'
```

Over time, the nested class `Cs.Finite` may become large and too cumbersome to keep as a nested subclass of `Cs`. Or the category with axiom may have a name of its own in the literature, like *semigroups* rather than *associative magmas*, or *fields* rather than *commutative division rings*. In this case, the category with axiom can be put elsewhere, typically in a separate file, with just a link from `Cs`:

```
sage: class Cs(Category):
.....:     def super_categories(self):
.....:         return [Sets()]
sage: class FiniteCs(CategoryWithAxiom):
```

(continues on next page)

(continued from previous page)

```

.....:     class ParentMethods:
.....:         def foo(self):
.....:             print("I am a method on finite C's")
sage: Cs.Finite = FiniteCs
sage: Cs().Finite()
Category of finite cs

```

For a real example, see the code of the class *FiniteGroups* and the link to it in *Groups*. Note that the link is implemented using *LazyImport*; this is highly recommended: it makes sure that *FiniteGroups* is imported after *Groups* it depends upon, and makes it explicit that the class *Groups* can be imported and is fully functional without importing *FiniteGroups*.

Note: Some categories with axioms are created upon Sage's startup. In such a case, one needs to pass the `at_startup=True` option to *LazyImport*, in order to quiet the warning about that lazy import being resolved upon startup. See for example `Sets.Finite`.

This is undoubtedly a code smell. Nevertheless, it is preferable to stick to lazy imports, first to resolve the import order properly, and more importantly as a reminder that the category would be best not constructed upon Sage's startup. This is to spur developers to reduce the number of parents (and therefore categories) that are constructed upon startup. Each `at_startup=True` that will be removed will be a measure of progress in this direction.

Note: In principle, due to a limitation of *LazyImport* with nested classes (see [trac ticket #15648](#)), one should pass the option `as_name` to *LazyImport*:

```
Finite = LazyImport('sage.categories.finite_groups', 'FiniteGroups', as_name='Finite')
```

in order to prevent `Groups.Finite` to keep on reimporting `FiniteGroups`.

Given that passing this option introduces some redundancy and is error prone, the axiom infrastructure includes a little workaround which makes the `as_name` unnecessary in this case.

Making the category with axiom directly callable

If desired, a category with axiom can be constructed directly through its class rather than through its base category:

```

sage: Semigroups()
Category of semigroups
sage: Semigroups() is Magmas().Associative()
True

sage: FiniteGroups()
Category of finite groups
sage: FiniteGroups() is Groups().Finite()
True

```

For this notation to work, the class *Semigroups* needs to be aware of the base category class (here, *Magmas*) and of the axiom (here, *Associative*):

```
sage: Semigroups._base_category_class_and_axiom
(<class 'sage.categories.magmas.Magmas'>, 'Associative')
```

(continues on next page)

(continued from previous page)

```
sage: Fields._base_category_class_and_axiom
(<class 'sage.categories.division_rings.DivisionRings'>, 'Commutative')
sage: FiniteGroups._base_category_class_and_axiom
(<class 'sage.categories.groups.Groups'>, 'Finite')
sage: FiniteDimensionalAlgebrasWithBasis._base_category_class_and_axiom
(<class 'sage.categories.algebras_with_basis.AlgebrasWithBasis'>, 'FiniteDimensional')
```

In our example, the attribute `_base_category_class_and_axiom` was set upon calling `Cs().Finite()`, which makes the notation seemingly work:

```
sage: FiniteCs()
Category of finite cs
sage: FiniteCs._base_category_class_and_axiom
(<class '__main__.Cs'>, 'Finite')
sage: FiniteCs._base_category_class_and_axiom_origin
'set by __classget__'
```

But calling `FiniteCs()` right after defining the class would have failed (try it!). In general, one needs to set the attribute explicitly:

```
sage: class FiniteCs(CategoryWithAxiom):
.....:     _base_category_class_and_axiom = (Cs, 'Finite')
.....:     class ParentMethods:
.....:         def foo(self):
.....:             print("I am a method on finite C's")
```

Having to set explicitly this link back from `FiniteCs` to `Cs` introduces redundancy in the code. It would therefore be desirable to have the infrastructure set the link automatically instead (a difficulty is to achieve this while supporting lazy imported categories with axiom).

As a first step, the link is set automatically upon accessing the class from the base category class:

```
sage: Algebras.WithBasis._base_category_class_and_axiom
(<class 'sage.categories.algebras.Algebras'>, 'WithBasis')
sage: Algebras.WithBasis._base_category_class_and_axiom_origin
'set by __classget__'
```

Hence, for whatever this notation is worth, one can currently do:

```
sage: Algebras.WithBasis(QQ)
Category of algebras with basis over Rational Field
```

We don't recommend using syntax like `Algebras.WithBasis(QQ)`, as it may eventually be deprecated.

As a second step, Sage tries some obvious heuristics to deduce the link from the name of the category with axiom (see [base_category_class_and_axiom\(\)](#) for the details). This typically covers the following examples:

```
sage: FiniteCoxeterGroups()
Category of finite coxeter groups
sage: FiniteCoxeterGroups() is CoxeterGroups().Finite()
True
sage: FiniteCoxeterGroups._base_category_class_and_axiom_origin
'deduced by base_category_class_and_axiom'
```

(continues on next page)

(continued from previous page)

```
sage: FiniteDimensionalAlgebrasWithBasis(QQ)
Category of finite dimensional algebras with basis over Rational Field
sage: FiniteDimensionalAlgebrasWithBasis(QQ) is Algebras(QQ).FiniteDimensional().
↳WithBasis()
True
```

If the heuristic succeeds, the result is guaranteed to be correct. If it fails, typically because the category has a name of its own like *Fields*, the attribute `_base_category_class_and_axiom` should be set explicitly. For more examples, see the code of the classes *Semigroups* or *Fields*.

Note: When printing out a category with axiom, the heuristic determines whether a category has a name of its own by checking out how `_base_category_class_and_axiom` was set:

```
sage: Fields._base_category_class_and_axiom_origin
'hardcoded'
```

See `CategoryWithAxiom._without_axioms()`, `CategoryWithAxiom._repr_object_names_static()`.

In our running example `FiniteCs`, Sage failed to deduce automatically the base category class and axiom because the class `Cs` is not in the standard location `sage.categories.cs`.

Design discussion

The above deduction, based on names, is undoubtedly inelegant. But it's safe (either the result is guaranteed to be correct, or an error is raised), it saves on some redundant information, and it is only used for the simple shorthands like `FiniteGroups()` for `Groups().Finite()`. Finally, most if not all of these shorthands are likely to eventually disappear (see [trac ticket #15741](#) and the *related discussion in the primer*).

Defining a new axiom

We describe now how to define a new axiom. The first step is to figure out the largest category where the axiom makes sense. For example `Sets` for `Finite`, `Magnas` for `Associative`, or `Modules` for `FiniteDimensional`. Here we define the axiom `Green` for the category `Cs` and its subcategories:

```
sage: from sage.categories.category_with_axiom import CategoryWithAxiom
sage: class Cs(Category):
.....:     def super_categories(self):
.....:         return [Sets()]
.....:     class SubcategoryMethods:
.....:         def Green(self):
.....:             '<documentation of the axiom Green>'
.....:             return self._with_axiom("Green")
.....:     class Green(CategoryWithAxiom):
.....:         class ParentMethods:
.....:             def foo(self):
.....:                 print("I am a method on green C's")
```

With the current implementation, the name of the axiom must also be added to a global container:

```
sage: all_axioms = sage.categories.category_with_axiom.all_axioms
sage: all_axioms += ("Green",)
```

We can now use the axiom as usual:

```
sage: Cs().Green()
Category of green cs

sage: P = Parent(category=Cs().Green())
sage: P.foo()
I am a method on green C's
```

Compared with our first example, the only newcomer is the method `.Green()` that can be used by any subcategory `Ds()` of `Cs()` to add the axiom `Green`. Note that the expression `Ds().Green` always evaluates to this method, regardless of whether `Ds` has a nested class `Ds.Green` or not (an implementation detail):

```
sage: Cs().Green
<bound method Cs_with_category.Green of Category of cs>
```

Thanks to this feature (implemented in `CategoryWithAxiom.__classget__()`), the user is systematically referred to the documentation of this method when doing introspection on `Ds().Green`:

```
sage: C = Cs()
sage: C.Green? # not tested
sage: Cs().Green.__doc__
'<documentation of the axiom Green>'
```

It is therefore the natural spot for the documentation of the axiom.

Note: The presence of the nested class `Green` in `Cs` is currently mandatory even if it is empty.

Todo: Specify whether or not one should systematically use `@cached_method` in the definition of the axiom. And make sure all the definition of axioms in Sage are consistent in this respect!

Todo: We could possibly define an `@axiom` decorator? This could hide two little implementation details: whether or not to make the method a cached method, and the call to `_with_axiom(...)` under the hood. It could do possibly do some more magic. The gain is not obvious though.

Note: `all_axioms` is only used marginally, for sanity checks and when trying to derive automatically the base category class. The order of the axioms in this tuple also controls the order in which they appear when printing out categories with axioms (see `CategoryWithAxiom._repr_object_names_static()`).

During a Sage session, new axioms should only be added at the *end* of `all_axioms`, as above, so as to not break the cache of `axioms_rank()`. Otherwise, they can be inserted statically anywhere in the tuple. For axioms defined within the Sage library, the name is best inserted by editing directly the definition of `all_axioms` in `sage.categories.category_with_axiom`.

Design note

Let us state again that, unlike what the existence of `all_axioms` might suggest, the definition of an axiom is local to a category and its subcategories. In particular, two independent categories `Cs()` and `Ds()` can very well define axioms with the same name and different semantics. As long as the two hierarchies of subcategories don't intersect, this is not a problem. And if they do intersect naturally (that is if one is likely to create a parent belonging to both categories), this probably means that the categories `Cs` and `Ds` are about related enough areas of mathematics that one should clear the ambiguity by having either the same semantic or different names.

This caveat is no different from that of name clashes in hierarchy of classes involving multiple inheritance.

Todo: Explore ways to get rid of this global `all_axioms` tuple, and/or have automatic registration there, and/or having a `register_axiom(...)` method.

Special case: defining an axiom depending on several categories

In some cases, the largest category where the axiom makes sense is the intersection of two categories. This is typically the case for axioms specifying compatibility conditions between two otherwise unrelated operations, like `Distributive` which specifies a compatibility between `*` and `+`. Ideally, we would want the `Distributive` axiom to be defined by:

```
sage: Magmas() & AdditiveMagmas()
Join of Category of magmas and Category of additive magmas
```

The current infrastructure does not support this perfectly: indeed, defining an axiom for a category `C` requires `C` to have a class of its own; hence a `JoinCategory` as above won't do; we need to implement a new class like `MagmasAndAdditiveMagmas`; furthermore, we cannot yet model the fact that `MagmasAndAdditiveMagmas()` is the intersection of `Magmas()` and `AdditiveMagmas()` rather than a mere subcategory:

```
sage: from sage.categories.magmas_and_additive_magmas import MagmasAndAdditiveMagmas
sage: Magmas() & AdditiveMagmas() is MagmasAndAdditiveMagmas()
False
sage: Magmas() & AdditiveMagmas() # todo: not implemented
Category of magmas and additive magmas
```

Still, there is a workaround to get the natural notations:

```
sage: (Magmas() & AdditiveMagmas()).Distributive()
Category of distributive magmas and additive magmas
sage: (Monoids() & CommutativeAdditiveGroups()).Distributive()
Category of rings
```

The trick is to define `Distributive` as usual in `MagmasAndAdditiveMagmas`, and to add a method `Magmas.SubcategoryMethods.Distributive()` which checks that `self` is a subcategory of both `Magmas()` and `AdditiveMagmas()`, complains if not, and otherwise takes the intersection of `self` with `MagmasAndAdditiveMagmas()` before calling `Distributive`.

The downsides of this workaround are:

- Creation of an otherwise empty class `MagmasAndAdditiveMagmas`.
- Pollution of the namespace of `Magmas()` (and subcategories like `Groups()`) with a method that is irrelevant (but safely complains if called).

- `C._with_axiom('Distributive')` is not strictly equivalent to `C.Distributive()`, which can be unpleasantly surprising:

```
sage: (Monoids() & CommutativeAdditiveGroups()).Distributive()
Category of rings

sage: (Monoids() & CommutativeAdditiveGroups())._with_axiom('Distributive')
Join of Category of monoids and Category of commutative additive groups
```

Todo: Other categories that would be better implemented via an axiom depending on a join category include:

- *Algebras*: defining an associative unital algebra as a ring and a module satisfying the suitable compatibility axiom between inner multiplication and multiplication by scalars (bilinearity). Of course this should be implemented at the level of *MagmaticAlgebras*, if not higher.
- *Bialgebras*: defining a bialgebra as an algebra and coalgebra where the coproduct is a morphism for the product.
- *Bimodules*: defining a bimodule as a left and right module where the two actions commute.

Todo:

- Design and implement an idiom for the definition of an axiom by a join category.
- Or support more advanced joins, through some hook or registration process to specify that a given category *is* the intersection of two (or more) categories.
- Or at least improve the above workaround to avoid the last issue; this possibly could be achieved using a class `Magmas.Distributive` with a bit of `__classcall__` magic.

Handling multiple axioms, arborescence structure of the code

Prelude

Let us consider the category of magmas, together with two of its axioms, namely `Associative` and `Unital`. An associative magma is a *semigroup* and a unital semigroup is a *monoid*. We have also seen that axioms commute:

```
sage: Magmas().Unital()
Category of unital magmas
sage: Magmas().Associative()
Category of semigroups
sage: Magmas().Associative().Unital()
Category of monoids
sage: Magmas().Unital().Associative()
Category of monoids
```

At the level of the classes implementing these categories, the following comes as a general naturalization of the previous section:

```
sage: Magmas.Unital
<class 'sage.categories.magmas.Magmas.Unital'>
sage: Magmas.Associative
```

(continues on next page)

(continued from previous page)

```
<class 'sage.categories.semigroups.Semigroups'>
sage: Magmas.Associative.Unital
<class 'sage.categories.monoids.Monoids'>
```

However, the following may look suspicious at first:

```
sage: Magmas.Unital.Associative
Traceback (most recent call last):
...
AttributeError: type object 'Magmas.Unital' has no attribute 'Associative'
```

The purpose of this section is to explain the design of the code layout and the rationale for this mismatch.

Abstract model

As we have seen in the *Primer*, the objects of a category $C_S()$ can usually satisfy, or not, many different axioms. Out of all combinations of axioms, only a small number are relevant in practice, in the sense that we actually want to provide features for the objects satisfying these axioms.

Therefore, in the context of the category class C_S , we want to provide the system with a collection $(D_S)_{S \in \mathcal{S}}$ where each S is a subset of the axioms and the corresponding D_S is a class for the subcategory of the objects of $C_S()$ satisfying the axioms in S . For example, if $C_S()$ is the category of magmas, the pairs (S, D_S) would include:

```
{Associative}           : Semigroups
{Associative, Unital}   : Monoids
{Associative, Unital, Inverse}: Groups
{Associative, Commutative} : Commutative Semigroups
{Unital, Inverse}       : Loops
```

Then, given a subset T of axioms, we want the system to be able to select automatically the relevant classes $(D_S)_{S \in \mathcal{S}, S \subset T}$, and build from them a category for the objects of C_S satisfying the axioms in T , together with its hierarchy of super categories. If T is in the indexing set \mathcal{S} , then the class of the resulting category is directly D_T :

```
sage: C = Magmas().Unital().Inverse().Associative(); C
Category of groups
sage: type(C)
<class 'sage.categories.groups.Groups_with_category'>
```

Otherwise, we get a join category:

```
sage: C = Magmas().Infinite().Unital().Associative(); C
Category of infinite monoids
sage: type(C)
<class 'sage.categories.category.JoinCategory_with_category'>
sage: C.super_categories()
[Category of monoids, Category of infinite sets]
```

Concrete model as an arborescence of nested classes

We further want the construction to be efficient and amenable to laziness. This led us to the following design decision: the collection $(D_S)_{S \in \mathcal{S}}$ of classes should be structured as an arborescence (or equivalently a *rooted forest*). The root is `Cs`, corresponding to $S = \emptyset$. Any other class D_S should be the child of a single class $D_{S'}$ where S' is obtained from S by removing a single axiom A . Of course, $D_{S'}$ and A are respectively the base category class and axiom of the category with axiom D_S that we have met in the first section.

At this point, we urge the reader to explore the code of `Magmas` and `DistributiveMagmasAndAdditiveMagmas` and see how the arborescence structure on the categories with axioms is reflected by the nesting of category classes.

Discussion of the design

Performance

Thanks to the arborescence structure on subsets of axioms, constructing the hierarchy of categories and computing intersections can be made efficient with, roughly speaking, a linear/quadratic complexity in the size of the involved category hierarchy multiplied by the number of axioms (see Section *Algorithms*). This is to be put in perspective with the manipulation of arbitrary collections of subsets (aka boolean functions) which can easily raise NP-hard problems.

Furthermore, thanks to its locality, the algorithms can be made suitably lazy: in particular, only the involved category classes need to be imported.

Flexibility

This design also brings in quite some flexibility, with the possibility to support features such as defining new axioms depending on other axioms and deduction rules. See below.

Asymmetry

As we have seen at the beginning of this section, this design introduces an asymmetry. It's not so bad in practice, since in most practical cases, we want to work incrementally. It's for example more natural to describe `FiniteFields` as `Fields` with the axiom `Finite` rather than `Magmas` and `AdditiveMagmas` with all (or at least sufficiently many) of the following axioms:

```
sage: sorted(Fields().axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse',
 'AdditiveUnital', 'Associative', 'Commutative', 'Distributive',
 'Division', 'NoZeroDivisors', 'Unital']
```

The main limitation is that the infrastructure currently imposes to be incremental by steps of a single axiom.

In practice, among the roughly 60 categories with axioms that are currently implemented in Sage, most admitted a (rather) natural choice of a base category and single axiom to add. For example, one usually thinks more naturally of a monoid as a semigroup which is unital rather than as a unital magma which is associative. Modeling this asymmetry in the code actually brings a bonus: it is used for printing out categories in a (heuristically) mathematician-friendly way:

```
sage: Magmas().Commutative().Associative()
Category of commutative semigroups
```

Only in a few cases is a choice made that feels mathematically arbitrary. This is essentially in the chain of nested classes `distributive_magmas_and_additive_magmas.DistributiveMagmasAndAdditiveMagmas.AdditiveAssociative.AdditiveCommutative.AdditiveUnital.Associative`.

Placeholder classes

Given that we can only add a single axiom at a time when implementing a `CategoryWithAxiom`, we need to create a few category classes that are just placeholders. For the worst example, see the chain of nested classes `distributive_magmas_and_additive_magmas.DistributiveMagmasAndAdditiveMagmas.AdditiveAssociative.AdditiveCommutative.AdditiveUnital.Associative`.

This is suboptimal, but fits within the scope of the axiom infrastructure which is to reduce a potentially exponential number of placeholder category classes to just a couple.

Note also that, in the above example, it's likely that some of the intermediate classes will grow to non placeholder ones, as people will explore more weaker variants of rings.

Mismatch between the arborescence of nested classes and the hierarchy of categories

The fact that the hierarchy relation between categories is not reflected directly as a relation between the classes may sound suspicious at first! However, as mentioned in the primer, this is actually a big selling point of the axioms infrastructure: by calculating automatically the hierarchy relation between categories with axioms one avoids the nightmare of maintaining it by hand. Instead, only a rather minimal number of links needs to be maintained in the code (one per category with axiom).

Besides, with the flexibility introduced by runtime deduction rules (see below), the hierarchy of categories may depend on the parameters of the categories and not just their class. So it's fine to make it clear from the onset that the two relations do not match.

Evolutivity

At this point, the arborescence structure has to be hardcoded by hand with the annoyances we have seen. This does not preclude, in a future iteration, to design and implement some idiom for categories with axioms that adds several axioms at once to a base category; maybe some variation around:

```
class DistributiveMagmasAndAdditiveMagmas:
    ...

    @category_with_axiom(
        AdditiveAssociative,
        AdditiveCommutative,
        AdditiveUnital,
        AdditiveInverse,
        Associative)
    def _(): return LazyImport('sage.categories.rngs', 'Rngs', at_startup=True)
```

or:

```
register_axiom_category(DistributiveMagmasAndAdditiveMagmas,
                       {AdditiveAssociative,
                        AdditiveCommutative,
                        AdditiveUnital,
```

(continues on next page)

(continued from previous page)

```
AdditiveInverse,
Associative},
'sage.categories.rngs', 'Rngs', at_startup=True)
```

The infrastructure would then be in charge of building the appropriate arborescence under the hood. Or rely on some database (see discussion on [trac ticket #10963](#), in particular at the end of comment 332).

Axioms defined upon other axioms

Sometimes an axiom can only be defined when some other axiom holds. For example, the axiom `NoZeroDivisors` only makes sense if there is a zero, that is if the axiom `AdditiveUnital` holds. Hence, for the category `MagmasAndAdditiveMagmas`, we consider in the abstract model only those subsets of axioms where the presence of `NoZeroDivisors` implies that of `AdditiveUnital`. We also want the axiom to be only available if meaningful:

```
sage: Rings().NoZeroDivisors()
Category of domains
sage: Rings().Commutative().NoZeroDivisors()
Category of integral domains
sage: Semirings().NoZeroDivisors()
Traceback (most recent call last):
...
AttributeError: 'Semirings_with_category' object has no attribute 'NoZeroDivisors'
```

Concretely, this is to be implemented by defining the new axiom in the (`SubcategoryMethods` nested class of the) appropriate category with axiom. For example the axiom `NoZeroDivisors` would be naturally defined in `magmas_and_additive_magmas.MagmasAndAdditiveMagmas.Distributive.AdditiveUnital`.

Note: The axiom `NoZeroDivisors` is currently defined in `Rings`, by simple lack of need for the feature; it should be lifted up as soon as relevant, that is when some code will be available for parents with no zero divisors that are not necessarily rings.

Deduction rules

A similar situation is when an axiom `A` of a category `Cs` implies some other axiom `B`, with the same consequence as above on the subsets of axioms appearing in the abstract model. For example, a division ring necessarily has no zero divisors:

```
sage: 'NoZeroDivisors' in Rings().Division().axioms()
True
sage: 'NoZeroDivisors' in Rings().axioms()
False
```

This deduction rule is implemented by the method `Rings.Division.extra_super_categories()`:

```
sage: Rings().Division().extra_super_categories()
(Category of domains,)
```

In general, this is to be implemented by a method `Cs.A.extra_super_categories` returning a tuple `(Cs().B(),)`, or preferably `(Ds().B(),)` where `Ds` is the category defining the axiom `B`.

This follows the same idiom as for deduction rules about functorial constructions (see `covariant_functorial_construction.CovariantConstructionCategory.extra_super_categories()`). For example, the fact that a Cartesian product of associative magmas (i.e. of semigroups) is an associative magma is implemented in `Semigroups.CartesianProducts.extra_super_categories()`:

```
sage: Magmas().Associative()
Category of semigroups
sage: Magmas().Associative().CartesianProducts().extra_super_categories()
[Category of semigroups]
```

Similarly, the fact that the algebra of a commutative magma is commutative is implemented in `Magmas.Commutative.Algebras.extra_super_categories()`:

```
sage: Magmas().Commutative().Algebras(QQ).extra_super_categories()
[Category of commutative magmas]
```

Warning: In some situations this idiom is inapplicable as it would require to implement two classes for the same category. This is the purpose of the next section.

Special case

In the previous examples, the deduction rule only had an influence on the super categories of the category with axiom being constructed. For example, when constructing `Rings().Division()`, the rule `Rings.Division.extra_super_categories()` simply adds `Rings().NoZeroDivisors()` as a super category thereof.

In some situations this idiom is inapplicable because a class for the category with axiom under construction already exists elsewhere. Take for example Wedderburn's theorem: any finite division ring is commutative, i.e. is a finite field. In other words, `DivisionRings().Finite()` coincides with `Fields().Finite()`:

```
sage: DivisionRings().Finite()
Category of finite enumerated fields
sage: DivisionRings().Finite() is Fields().Finite()
True
```

Therefore we cannot create a class `DivisionRings.Finite` to hold the desired `extra_super_categories` method, because there is already a class for this category with axiom, namely `Fields.Finite`.

A natural idiom would be to have `DivisionRings.Finite` be a link to `Fields.Finite` (locally introducing an undirected cycle in the arborescence of nested classes). It would be a bit tricky to implement though, since one would need to detect, upon constructing `DivisionRings().Finite()`, that `DivisionRings.Finite` is actually `Fields.Finite`, in order to construct appropriately `Fields().Finite()`; and reciprocally, upon computing the super categories of `Fields().Finite()`, to not try to add `DivisionRings().Finite()` as a super category.

Instead the current idiom is to have a method `DivisionRings.Finite_extra_super_categories` which mimics the behavior of the would-be `DivisionRings.Finite.extra_super_categories`:

```
sage: DivisionRings().Finite_extra_super_categories()
(Category of commutative magmas,)
```

This idiom is admittedly rudimentary, but consistent with how mathematical facts specifying non trivial inclusion relations between categories are implemented elsewhere in the various `extra_super_categories` methods of axiom categories and covariant functorial constructions. Besides, it gives a natural spot (the docstring of the method) to document and test the modeling of the mathematical fact. Finally, Wedderburn's theorem is arguably a theorem

about division rings (in the context of division rings, finiteness implies commutativity) and therefore lives naturally in *DivisionRings*.

An alternative would be to implement the category of finite division rings (i.e. finite fields) in a class *DivisionRings.Finite* rather than *Fields.Finite*:

```
sage: from sage.categories.category_with_axiom import CategoryWithAxiom

sage: class MyDivisionRings(Category):
.....:     def super_categories(self):
.....:         return [Rings()]

sage: class MyFields(Category):
.....:     def super_categories(self):
.....:         return [MyDivisionRings()]

sage: class MyFiniteFields(CategoryWithAxiom):
.....:     _base_category_class_and_axiom = (MyDivisionRings, "Finite")
.....:     def extra_super_categories(self): # Wedderburn's theorem
.....:         return [MyFields()]

sage: MyDivisionRings.Finite = MyFiniteFields

sage: MyDivisionRings().Finite()
Category of my finite fields
sage: MyFields().Finite() is MyDivisionRings().Finite()
True
```

In general, if several categories $C_1s()$, $C_2s()$, ... are mapped to the same category when applying some axiom A (that is $C_1s().A() == C_2s().A() == \dots$), then one should be careful to implement this category in a single class Cs . A , and set up methods `extra_super_categories` or `A_extra_super_categories` methods as appropriate. Each such method should return something like $[C_2s()]$ and not $[C_2s().A()]$ for the latter would likely lead to an infinite recursion.

Design discussion

Supporting similar deduction rules will be an important feature in the future, with quite a few occurrences already implemented in upcoming tickets. For the time being though there is a single occurrence of this idiom outside of the tests. So this would be an easy thing to refactor after [trac ticket #10963](#) if a better idiom is found.

Larger synthetic examples

We now consider some larger synthetic examples to check that the machinery works as expected. Let us start with a category defining a bunch of axioms, using `axiom()` for conciseness (don't do it for real axioms; they deserve a full documentation!):

```
sage: from sage.categories.category_singleton import Category_singleton
sage: from sage.categories.category_with_axiom import axiom
sage: import sage.categories.category_with_axiom
sage: all_axioms = sage.categories.category_with_axiom.all_axioms
sage: all_axioms += ("B", "C", "D", "E", "F")
```

(continues on next page)

(continued from previous page)

```

sage: class As(Category_singleton):
.....:     def super_categories(self):
.....:         return [Objects()]
.....:
.....:     class SubcategoryMethods:
.....:         B = axiom("B")
.....:         C = axiom("C")
.....:         D = axiom("D")
.....:         E = axiom("E")
.....:         F = axiom("F")
.....:
.....:     class B(CategoryWithAxiom):
.....:         pass
.....:     class C(CategoryWithAxiom):
.....:         pass
.....:     class D(CategoryWithAxiom):
.....:         pass
.....:     class E(CategoryWithAxiom):
.....:         pass
.....:     class F(CategoryWithAxiom):
.....:         pass

```

Now we construct a subcategory where, by some theorem of William, axioms B and C together are equivalent to E and F together:

```

sage: class A1s(Category_singleton):
.....:     def super_categories(self):
.....:         return [As()]
.....:
.....:     class B(CategoryWithAxiom):
.....:         def C_extra_super_categories(self):
.....:             return [As().E(), As().F()]
.....:
.....:     class E(CategoryWithAxiom):
.....:         def F_extra_super_categories(self):
.....:             return [As().B(), As().C()]

sage: A1s().B().C()
Category of e f a1s

```

The axioms B and C do not show up in the name of the obtained category because, for concision, the printing uses some heuristics to not show axioms that are implied by others. But they are satisfied:

```

sage: sorted(A1s().B().C().axioms())
['B', 'C', 'E', 'F']

```

Note also that this is a join category:

```

sage: type(A1s().B().C())
<class 'sage.categories.category.JoinCategory_with_category'>
sage: A1s().B().C().super_categories()
[Category of e a1s,
 Category of f as,

```

(continues on next page)

(continued from previous page)

```
Category of b a1s,
Category of c a2s]
```

As desired, William's theorem holds:

```
sage: A1s().B().C() is A1s().E().F()
True
```

and propagates appropriately to subcategories:

```
sage: C = A1s().E().F().D().B().C()
sage: C is A1s().B().C().E().F().D() # commutativity
True
sage: C is A1s().E().F().E().F().D() # William's theorem
True
sage: C is A1s().E().E().F().F().D() # commutativity
True
sage: C is A1s().E().F().D() # idempotency
True
sage: C is A1s().D().E().F()
True
```

In this quick variant, we actually implement the category of b c a2s, and choose to do so in A2s.B.C:

```
sage: class A2s(Category_singleton):
.....:     def super_categories(self):
.....:         return [As()]
.....:
.....:     class B(CategoryWithAxiom):
.....:         class C(CategoryWithAxiom):
.....:             def extra_super_categories(self):
.....:                 return [As().E(), As().F()]
.....:
.....:         class E(CategoryWithAxiom):
.....:             def F_extra_super_categories(self):
.....:                 return [As().B(), As().C()]

sage: A2s().B().C()
Category of e f a2s
sage: sorted(A2s().B().C().axioms())
['B', 'C', 'E', 'F']
sage: type(A2s().B().C())
<class '__main__.A2s.B.C_with_category'>
```

As desired, William's theorem and its consequences hold:

```
sage: A2s().B().C() is A2s().E().F()
True
sage: C = A2s().E().F().D().B().C()
sage: C is A2s().B().C().E().F().D() # commutativity
True
sage: C is A2s().E().F().E().F().D() # William's theorem
```

(continues on next page)

(continued from previous page)

```

True
sage: C is A2s().E().E().F().F().D() # commutativity
True
sage: C is A2s().E().F().D()      # idempotency
True
sage: C is A2s().D().E().F()
True

```

Finally, we “accidentally” implement the category of b c a1s, both in A3s.B.C and A3s.E.F:

```

sage: class A3s(Category_singleton):
.....:     def super_categories(self):
.....:         return [As()]
.....:
.....:     class B(CategoryWithAxiom):
.....:         class C(CategoryWithAxiom):
.....:             def extra_super_categories(self):
.....:                 return [As().E(), As().F()]
.....:
.....:     class E(CategoryWithAxiom):
.....:         class F(CategoryWithAxiom):
.....:             def extra_super_categories(self):
.....:                 return [As().B(), As().C()]

```

We can still construct, say:

```

sage: A3s().B()
Category of b a3s
sage: A3s().C()
Category of c a3s

```

However,

```

sage: A3s().B().C() # not tested

```

runs into an infinite recursion loop, as A3s().B().C() wants to have A3s().E().F() as super category and reciprocally.

Todo: The above example violates the specifications (a category should be modelled by at most one class), so it’s appropriate that it fails. Yet, the error message could be usefully complemented by some hint at what the source of the problem is (a category implemented in two distinct classes). Leaving a large enough piece of the backtrace would be useful though, so that one can explore where the issue comes from (e.g. with post mortem debugging).

1.3.2 Specifications

After fixing some vocabulary, we summarize here some specifications about categories and axioms.

The lattice of constructible categories

A mathematical category C is *implemented* if there is a class in Sage modelling it; it is *constructible* if it is either implemented, or is the intersection of *implemented* categories; in the latter case it is modelled by a *JoinCategory*. The comparison of two constructible categories with the *Category.is_subcategory()* method is supposed to model the comparison of the corresponding mathematical categories for inclusion of the objects (see *On the category hierarchy: subcategories and super categories* for details). For example:

```
sage: Fields().is_subcategory(Rings())
True
```

However this modelling may be incomplete. It can happen that a mathematical fact implying that a category A is a subcategory of a category B is not implemented. Still, the comparison should endow the set of constructible categories with a poset structure and in fact a lattice structure.

In this lattice, the join of two categories (*Category.join()*) is supposed to model their intersection. Given that we compare categories for inclusion, it would be more natural to call this operation the *meet*; blames go to me (Nicolas) for originally comparing categories by *amount of structure* rather than by *inclusion*. In practice, the join of two categories may be a strict super category of their intersection; first because this intersection might not be constructible; second because Sage might miss some mathematical information to recover the smallest constructible super category of the intersection.

Axioms

We say that an axiom A is *defined by* a category $Cs()$ if Cs defines an appropriate method $Cs.SubcategoryMethods.A$, with the semantic of the axiom specified in the documentation; for any subcategory $Ds()$, $Ds().A()$ models the subcategory of the objects of $Ds()$ satisfying A . In this case, we say that the axiom A is *defined for* the category $Ds()$. Furthermore, Ds *implements the axiom A* if Ds has a category with axiom as nested class $Ds.A$. The category $Ds()$ *satisfies* the axiom if $Ds()$ is a subcategory of $Cs().A()$ (meaning that all the objects of $Ds()$ are known to satisfy the axiom A).

A digression on the structure of fibers when adding an axiom

Consider the application ϕ_A which maps a category to its category of objects satisfying A . Equivalently, ϕ_A is computing the intersection with the defining category with axiom of A . It follows immediately from the latter that ϕ_A is a regressive endomorphism of the lattice of categories. It restricts to a regressive endomorphism $Cs() \mapsto Cs().A()$ on the lattice of constructible categories.

This endomorphism may have non trivial fibers, as in our favorite example: `DivisionRings()` and `Fields()` are in the same fiber for the axiom `Finite`:

```
sage: DivisionRings().Finite() is Fields().Finite()
True
```

Consider the intersection S of such a fiber of ϕ_A with the upper set I_A of categories that do not satisfy A . The fiber itself is a sublattice. However I_A is not guaranteed to be stable under intersection (though exceptions should be rare). Therefore, there is a priori no guarantee that S would be stable under intersection. Also it's presumably finite, in fact small, but this is not guaranteed either.

Specifications

- Any constructible category C should admit a finite number of larger constructible categories.
- The methods `super_categories`, `extra_super_categories`, and `friends` should always return strict super-categories.
For example, to specify that a finite division ring is a finite field, `DivisionRings.Finite_extra_super_categories` should not return `Fields().Finite()`! It could possibly return `Fields()`; but it's preferable to return the largest category that contains the relevant information, in this case `Magnas().Commutative()`, and to let the infrastructure apply the derivations.
- The base category of a `CategoryWithAxiom` should be an implemented category (i.e. not a `JoinCategory`). This is checked by `CategoryWithAxiom._test_category_with_axiom()`.
- Arborescent structure: Let $Cs()$ be a category, and S be some set of axioms defined in some super categories of $Cs()$ but not satisfied by $Cs()$. Suppose we want to provide a category with axiom for the elements of $Cs()$ satisfying the axioms in S . Then, there should be a single enumeration A_1, A_2, \dots, A_k without repetition of axioms in S such that $Cs.A_1.A_2 \dots A_k$ is an implemented category. Furthermore, every intermediate step $Cs.A_1.A_2 \dots A_i$ with $i \leq k$ should be a category with axiom having A_i as axiom and $Cs.A_1.A_2 \dots A_{i-1}$ as base category class; this base category class should not satisfy A_i . In particular, when some axioms of S can be deduced from previous ones by deduction rules, they should not appear in the enumeration A_1, A_2, \dots, A_k .
- In particular, if $Cs()$ is a category that satisfies some axiom A (e.g. from one of its super categories), then it should not implement that axiom. For example, a category class Cs can never have a nested class $Cs.A.A$. Similarly, applying the specification recursively, a category satisfying A cannot have a nested class $Cs.A_1.A_2.A_3.A$ where A_1, A_2, A_3 are axioms.
- A category can only implement an axiom if this axiom is defined by some super category. The code has not been systematically checked to support having two super categories defining the same axiom (which should of course have the same semantic). You are welcome to try, at your own risk. :-)
- When a category defines an axiom or functorial construction A , this fixes the semantic of A for all the subcategories. In particular, if two categories define A , then these categories should be independent, and either the semantic of A should be the same, or there should be no natural intersection between the two hierarchies of subcategories.
- Any super category of a `CategoryWithParameters` should either be a `CategoryWithParameters` or a `Category_singleton`.
- A `CategoryWithAxiom` having a `Category_singleton` as base category should be a `CategoryWithAxiom_singleton`. This is handled automatically by `CategoryWithAxiom.__init__()` and checked in `CategoryWithAxiom._test_category_with_axiom()`.
- A `CategoryWithAxiom` having a `Category_over_base_ring` as base category should be a `Category_over_base_ring`. This currently has to be handled by hand, using `CategoryWithAxiom_over_base_ring`. This is checked in `CategoryWithAxiom._test_category_with_axiom()`.

Todo: The following specifications would be desirable but are not yet implemented:

- A functorial construction category (`Graded`, `CartesianProducts`, ...) having a `Category_singleton` as base category should be a `CategoryWithAxiom_singleton`.
Nothing difficult to implement, but this will need to rework the current “no subclass of a concrete class” assertion test of `Category_singleton.__classcall__()`.
- Similarly, a covariant functorial construction category having a `Category_over_base_ring` as base category should be a `Category_over_base_ring`.

The following specification might be desirable, or not:

- A join category involving a `Category_over_base_ring` should be a `Category_over_base_ring`. In the mean time, a `base_ring` method is automatically provided for most of those by `Modules.SubcategoryMethods.base_ring()`.

1.3.3 Design goals

As pointed out in the primer, the main design goal of the axioms infrastructure is to subdue the potential combinatorial explosion of the category hierarchy by letting the developer focus on implementing a few bookshelves for which there is actual code or mathematical information, and let Sage *compose dynamically and lazily* these building blocks to construct the minimal hierarchy of classes needed for the computation at hand. This allows for the infrastructure to scale smoothly as bookshelves are added, extended, or reorganized.

Other design goals include:

- Flexibility in the code layout: the category of, say, finite sets can be implemented either within the Sets category (in a nested class `Sets.Finite`), or in a separate file (typically in a class `FiniteSets` in a lazily imported module `sage.categories.finite_sets`).
- Single point of truth: a theorem, like Wedderburn's, should be implemented in a single spot.
- Single entry point: for example, from the entry `Rings`, one can explore a whole range of related categories just by applying axioms and constructions:

```
sage: Rings().Commutative().Finite().NoZeroDivisors()
Category of finite integral domains
sage: Rings().Finite().Division()
Category of finite enumerated fields
```

This will allow for progressively getting rid of all the entries like `GradedHopfAlgebrasWithBasis` which are polluting the global name space.

Note that this is not about precluding the existence of multiple natural ways to construct the same category:

```
sage: Groups().Finite()
Category of finite groups
sage: Monoids().Finite().Inverse()
Category of finite groups
sage: Sets().Finite() & Monoids().Inverse()
Category of finite groups
```

- Concise idioms for the users (adding axioms, ...)
- Concise idioms and well highlighted hierarchy of bookshelves for the developer (especially with code folding)
- Introspection friendly (listing the axioms, recovering the mixins)

Note: The constructor for instances of this class takes as input the base category. Hence, they should in principle be constructed as:

```
sage: FiniteSets(Sets())
Category of finite sets

sage: Sets.Finite(Sets())
Category of finite sets
```

None of these idioms are really practical for the user. So instead, this object is to be constructed using any of the following idioms:

```
sage: Sets()._with_axiom('Finite')
Category of finite sets
sage: FiniteSets()
Category of finite sets
sage: Sets().Finite()
Category of finite sets
```

The later two are implemented using respectively `CategoryWithAxiom.__classcall__()` and `CategoryWithAxiom.__classget__()`.

1.3.4 Upcoming features

Todo:

- Implement compatibility axiom / functorial constructions. For example, one would want to have:

```
A.CartesianProducts() & B.CartesianProducts() = (A&B).CartesianProducts()
```

- Once full subcategories are implemented (see [trac ticket #10668](#)), make the relevant categories with axioms be such. This can be done systematically for, e.g., the axioms `Associative` or `Commutative`, but not for the axiom `Unital`: a semigroup morphism between two monoids need not preserve the unit.

Should all full subcategories be implemented in term of axioms?

1.3.5 Algorithms

Computing joins

The workhorse of the axiom infrastructure is the algorithm for computing the join J of a set C_1, \dots, C_k of categories (see `Category.join()`). Formally, J is defined as the largest constructible category such that $J \subset C_i$ for all i , and $J \subset C.A()$ for every constructible category $C \supset J$ and any axiom A satisfied by J .

The join J is naturally computed as a closure in the lattice of constructible categories: it starts with the C_i 's, gathers the set S of all the axioms satisfied by them, and repeatedly adds each axiom A to those categories that do not yet satisfy A using `Category._with_axiom()`. Due to deduction rules or (extra) super categories, new categories or new axioms may appear in the process. The process stops when each remaining category has been combined with each axiom. In practice, only the smallest categories are kept along the way; this is correct because adding an axiom is covariant: $C.A()$ is a subcategory of $D.A()$ whenever C is a subcategory of D .

As usual in such closure computations, the result does not depend on the order of execution. Furthermore, given that adding an axiom is an idempotent and regressive operation, the process is guaranteed to stop in a number of steps which is bounded by the number of super categories of J . In particular, it is a finite process.

Todo: Detail this a bit. What could typically go wrong is a situation where, for some category $C1$, $C1.A()$ specifies a category $C2$ as super category such that $C2.A()$ specifies $C3$ as super category such that \dots ; this would clearly cause an infinite execution. Note that this situation violates the specifications since $C1.A()$ is supposed to be a subcategory of $C2.A()$, \dots so we would have an infinite increasing chain of constructible categories.

It's reasonable to assume that there is a finite number of axioms defined in the code. There remains to use this assumption to argue that any infinite execution of the algorithm would give rise to such an infinite sequence.

Adding an axiom

Let $Cs()$ be a category and A an axiom defined for this category. To compute $Cs().A()$, there are two cases.

Adding an axiom A to a category $Cs()$ not implementing it

In this case, $Cs().A()$ returns the join of:

- $Cs()$
- $Bs().A()$ for every direct super category $Bs()$ of $Cs()$
- the categories appearing in $Cs().A_extra_super_categories()$

This is a highly recursive process. In fact, as such, it would run right away into an infinite loop! Indeed, the join of $Cs()$ with $Bs().A()$ would trigger the construction of $Cs().A()$ and reciprocally. To avoid this, the `Category.join()` method itself does not use `Category.with_axiom()` to add axioms, but its sister `Category.with_axiom_as_tuple()`; the latter builds a tuple of categories that should be joined together but leaves the computation of the join to its caller, the master join calculation.

Adding an axiom A to a category $Cs()$ implementing it

In this case $Cs().A()$ simply constructs an instance D of $Cs.A$ which models the desired category. The non trivial part is the construction of the super categories of D . Very much like above, this includes:

- $Cs()$
- $Bs().A()$ for every super category $Bs()$ of $Cs()$
- the categories appearing in $D.extra_super_categories()$

This by itself may not be sufficient, due in particular to deduction rules. One may for example discover a new axiom $A1$ satisfied by D , imposing to add $A1$ to all of the above categories. Therefore the super categories are computed as the join of the above categories. Up to one twist: as is, the computation of this join would trigger recursively a recalculation of $Cs().A()$! To avoid this, `Category.join()` is given an optional argument to specify that the axiom A should *not* be applied to $Cs()$.

Sketch of proof of correctness and evaluation of complexity

As we have seen, this is a highly recursive process! In particular, one needs to argue that, as long as the specifications are satisfied, the algorithm won't run in an infinite recursion, in particular in case of deduction rule.

Theorem

Consider the construction of a category C by adding an axiom to a category (or computing of a join). Let H be the hierarchy of implemented categories above C . Let n and m be respectively the number of categories and the number of inheritance edges in H .

Assuming that the specifications are satisfied, the construction of C involves constructing the categories in H exactly once (and no other category), and at most n join calculations. In particular, the time complexity should be, roughly speaking, bounded by n^2 . In particular, it's finite.

Remark

It's actually to be expected that the complexity is more of the order of magnitude of $na + m$, where a is the number of axioms satisfied by C . But this is to be checked in detail, in particular due to the many category inclusion tests involved.

The key argument is that `Category.join` cannot call itself recursively without going through the construction of some implemented category. In turn, the construction of some implemented category C only involves constructing strictly smaller categories, and possibly a direct join calculation whose result is strictly smaller than C . This statement is obvious if C implements the `super_categories` method directly, and easy to check for functorial construction categories. It requires a proof for categories with axioms since there is a recursive join involved.

Lemma

Let C be a category implementing an axiom A . Recall that the construction of $C.A()$ involves a single direct join calculation for computing the super categories. No other direct join calculation occur, and the calculation involves only implemented categories that are strictly smaller than $C.A()$.

Proof

Let D be a category involved in the join calculation for the super categories of $C.A()$, and assume by induction that D is strictly smaller than $C.A()$. A category E newly constructed from D can come from:

- `D.(extra_)super_categories()`

In this case, the specifications impose that E should be strictly smaller than D and therefore strictly smaller than C .

- `D.with_axiom_as_tuple('B')` or `D.B_extra_super_categories()` for some axiom B

In this case, the axiom B is satisfied by some subcategory of $C.A()$, and therefore must be satisfied by $C.A()$ itself. Since adding an axiom is a regressive construction, E must be a subcategory of $C.A()$. If there is equality, then E and $C.A()$ must have the same class, and therefore, E must be directly constructed as $C.A()$. However the join construction explicitly prevents this call.

Note that a call to `D.with_axiom_as_tuple('B')` does not trigger a direct join calculation; but of course, if D implements B , the construction of the implemented category $E = D.B()$ will involve a strictly smaller join calculation.

1.3.6 Conclusion

This is the end of the axioms documentation. Congratulations on having read that far!

1.3.7 Tests

Note: Quite a few categories with axioms are constructed early on during Sage’s startup. Therefore, when playing around with the implementation of the axiom infrastructure, it is easy to break Sage. The following sequence of tests is designed to test the infrastructure from the ground up even in a partially broken Sage. Please don’t remove the imports!

```
class sage.categories.category_with_axiom.Bars(s=None)
    Bases: sage.categories.category_singleton.Category_singleton
```

A toy singleton category, for testing purposes.

See also:

Blahs

Unital_extra_super_categories()

Return extraneous super categories for the unital objects of `self`.

This method specifies that a unital bar is a test object. Thus, the categories of unital bars and of unital test objects coincide.

EXAMPLES:

```
sage: from sage.categories.category_with_axiom import Bars, TestObjects
sage: Bars().Unital_extra_super_categories()
[Category of test objects]
sage: Bars().Unital()
Category of unital test objects
sage: TestObjects().Unital().all_super_categories()
[Category of unital test objects,
Category of unital blahs,
Category of test objects,
Category of bars,
Category of blahs,
Category of sets,
Category of sets with partial maps,
Category of objects]
```

super_categories()

```
class sage.categories.category_with_axiom.Blahs(s=None)
    Bases: sage.categories.category_singleton.Category_singleton
```

A toy singleton category, for testing purposes.

This is the root of a hierarchy of mathematically meaningless categories, used for testing Sage’s category framework:

- *Bars*
- *TestObjects*
- *TestObjectsOverBaseRing*

Blue_extra_super_categories()

Illustrates a current limitation in the way to have an axiom imply another one.

Here, we would want `Blue` to imply `Unital`, and to put the class for the category of unital blue blahs in `Blahs.Unital.Blue` rather than `Blahs.Blue`.

This currently fails because `Blahs` is the category where the axiom `Blue` is defined, and the specifications currently impose that a category defining an axiom should also implement it (here in an category with axiom `Blahs.Blue`). In practice, due to this violation of the specifications, the axiom is lost during the join calculation.

Todo: Decide whether we care about this feature. In such a situation, we are not really defining a new axiom, but just defining an axiom as an alias for a couple others, which might not be that useful.

Todo: Improve the infrastructure to detect and report this violation of the specifications, if this is easy. Otherwise, it's not so bad: when defining an axiom `A` in a category `Cs` the first thing one is supposed to doctest is that `Cs().A()` works. So the problem should not go unnoticed.

class Commutative(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

class Connected(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

class FiniteDimensional(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

class Flying(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

extra_super_categories()

This illustrates a way to have an axiom imply another one.

Here, we want `Flying` to imply `Unital`, and to put the class for the category of unital flying blahs in `Blahs.Flying` rather than `Blahs.Unital.Flying`.

class SubcategoryMethods

Bases: `object`

`Blue()`

`Commutative()`

`Connected()`

`FiniteDimensional()`

`Flying()`

`Unital()`

class Unital(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

class Blue(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

super_categories()

class `sage.categories.category_with_axiom.CategoryWithAxiom`(*base_category*)

Bases: `sage.categories.category.Category`

An abstract class for categories obtained by adding an axiom to a base category.

See the [category primer](#), and in particular its [section about axioms](#) for an introduction to axioms, and [CategoryWithAxiom](#) for how to implement axioms and the documentation of the axiom infrastructure.

static `__classcall__`(*args, **options)

Make `FoosBar(**)` an alias for `Foos(**).with_axiom("Bar")`.

EXAMPLES:

```
sage: FiniteGroups()
Category of finite groups
sage: ModulesWithBasis(ZZ)
Category of modules with basis over Integer Ring
sage: AlgebrasWithBasis(QQ)
Category of algebras with basis over Rational Field
```

This is relevant when e.g. `Foos(**)` does some non trivial transformations:

```
sage: Modules(QQ) is VectorSpaces(QQ)
True
sage: type(Modules(QQ))
<class 'sage.categories.vector_spaces.VectorSpaces_with_category'>

sage: ModulesWithBasis(QQ) is VectorSpaces(QQ).WithBasis()
True
sage: type(ModulesWithBasis(QQ))
<class 'sage.categories.vector_spaces.VectorSpaces.WithBasis_with_category'>
```

static `__classget__`(*base_category*, *base_category_class*)

Implement the binding behavior for categories with axioms.

This method implements a binding behavior on category with axioms so that, when a category `Cs` implements an axiom `A` with a nested class `Cs.A`, the expression `Cs().A` evaluates to the method defining the axiom `A` and not the nested class. See [those design notes](#) for the rationale behind this behavior.

EXAMPLES:

```
sage: Sets().Infinite()
Category of infinite sets
sage: Sets().Infinite
Cached version of <function ...Infinite at ...>
sage: Sets().Infinite.f == Sets.SubcategoryMethods.Infinite.f
True
```

We check that this also works when the class is implemented in a separate file, and lazy imported:

```
sage: Sets().Finite
Cached version of <function ...Finite at ...>
```

There is no binding behavior when accessing `Finite` or `Infinite` from the class of the category instead of the category itself:

```
sage: Sets.Finite
<class 'sage.categories.finite_sets.FiniteSets'>
sage: Sets.Infinite
<class 'sage.categories.sets_cat.Sets.Infinite'>
```

This method also initializes the attribute `_base_category_class_and_axiom` if not already set:

```
sage: Sets.Infinite._base_category_class_and_axiom
(<class 'sage.categories.sets_cat.Sets'>, 'Infinite')
sage: Sets.Infinite._base_category_class_and_axiom_origin
'set by __classget__'
```

`__init__`(*base_category*)

`_repr_object_names`()

The names of the objects of this category, as used by `_repr_`.

See also:

[Category._repr_object_names\(\)](#)

EXAMPLES:

```
sage: FiniteSets()._repr_object_names()
'finite sets'
sage: AlgebrasWithBasis(QQ).FiniteDimensional()._repr_object_names()
'finite dimensional algebras with basis over Rational Field'
sage: Monoids()._repr_object_names()
'monoids'
sage: Semigroups().Unital().Finite()._repr_object_names()
'finite monoids'
sage: Algebras(QQ).Commutative()._repr_object_names()
'commutative algebras over Rational Field'
```

Note: This is implemented by taking `_repr_object_names` from `self._without_axioms(named=True)`, and adding the names of the relevant axioms in appropriate order.

`static _repr_object_names_static`(*category*, *axioms*)

INPUT:

- `base_category` – a category
- `axioms` – a list or iterable of strings

EXAMPLES:

```
sage: from sage.categories.category_with_axiom import CategoryWithAxiom
sage: CategoryWithAxiom._repr_object_names_static(Semigroups(), ["Flying", "Blue
↔"])
'flying blue semigroups'
sage: CategoryWithAxiom._repr_object_names_static(Algebras(QQ), ["Flying",
↔"WithBasis", "Blue"])
'flying blue algebras with basis over Rational Field'
sage: CategoryWithAxiom._repr_object_names_static(Algebras(QQ), ["WithBasis"])
'algebras with basis over Rational Field'
```

(continues on next page)

(continued from previous page)

```

sage: CategoryWithAxiom._repr_object_names_static(Sets().Finite().
↳Subquotients(), ["Finite"])
'subquotients of finite sets'
sage: CategoryWithAxiom._repr_object_names_static(Monoids(), ["Unital"])
'monoids'
sage: CategoryWithAxiom._repr_object_names_static(Algebras(QQ['x']['y']), [
↳"Flying", "WithBasis", "Blue"])
'flying blue algebras with basis over Univariate Polynomial Ring in y over
↳Univariate Polynomial Ring in x over Rational Field'

```

If the axioms is a set or frozen set, then they are first sorted using `canonicalize_axioms()`:

```

sage: CategoryWithAxiom._repr_object_names_static(Semigroups(), set(["Finite",
↳"Commutative", "Facade"]))
'facade finite commutative semigroups'

```

See also:

`_repr_object_names()`

Note: The logic here is shared between `_repr_object_names()` and `category.JoinCategory._repr_object_names()`

`_test_category_with_axiom(options)`**

Run generic tests on this category with axioms.

See also:

`TestSuite`.

This check that an axiom category of a `Category_singleton` is a singleton category, and similarwise for `Category_over_base_ring`.

EXAMPLES:

```

sage: Sets().Finite()._test_category_with_axiom()
sage: Modules(ZZ).FiniteDimensional()._test_category_with_axiom()

```

`_without_axioms(named=False)`

Return the category without the axioms that have been added to create it.

EXAMPLES:

```

sage: Sets().Finite()._without_axioms()
Category of sets
sage: Monoids().Finite()._without_axioms()
Category of magmas

```

This is because:

```

sage: Semigroups().Unital() is Monoids()
True

```

If `named` is `True`, then `_without_axioms` stops at the first category that has an explicit name of its own:

```
sage: Sets().Finite()._without_axioms(named=True)
Category of sets
sage: Monoids().Finite()._without_axioms(named=True)
Category of monoids
```

Technically we test this by checking if the class specifies explicitly the attribute `_base_category_class_and_axiom` by looking up `_base_category_class_and_axiom_origin`.

Some more examples:

```
sage: Algebras(QQ).Commutative()._without_axioms()
Category of magmatic algebras over Rational Field
sage: Algebras(QQ).Commutative()._without_axioms(named=True)
Category of algebras over Rational Field
```

`additional_structure()`

Return the additional structure defined by `self`.

OUTPUT: None

By default, a category with axiom defines no additional structure.

See also:

[*Category.additional_structure\(\)*](#).

EXAMPLES:

```
sage: Sets().Finite().additional_structure()
sage: Monoids().additional_structure()
```

`axioms()`

Return the axioms known to be satisfied by all the objects of `self`.

See also:

[*Category.axioms\(\)*](#)

EXAMPLES:

```
sage: C = Sets.Finite(); C
Category of finite sets
sage: C.axioms()
frozenset({'Finite'})

sage: C = Modules(GF(5)).FiniteDimensional(); C
Category of finite dimensional vector spaces over Finite Field of size 5
sage: sorted(C.axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse',
 'AdditiveUnital', 'Finite', 'FiniteDimensional']

sage: sorted(FiniteMonoids().Algebras(QQ).axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse',
 'AdditiveUnital', 'Associative', 'Distributive',
 'FiniteDimensional', 'Unital', 'WithBasis']

sage: sorted(FiniteMonoids().Algebras(GF(3)).axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse',
 'AdditiveUnital', 'Associative', 'Distributive', 'Finite',
```

(continues on next page)

(continued from previous page)

```
'FiniteDimensional', 'Unital', 'WithBasis']
sage: from sage.categories.magnas_and_additive_magnas import _
↳ MagmasAndAdditiveMagmas
sage: MagmasAndAdditiveMagmas().Distributive().Unital().axioms()
frozenset({'Distributive', 'Unital'})
sage: D = MagmasAndAdditiveMagmas().Distributive()
sage: X = D.AdditiveAssociative().AdditiveCommutative().Associative()
sage: X.Unital().super_categories()[1]
Category of monoids
sage: X.Unital().super_categories()[1] is Monoids()
True
```

base_category()

Return the base category of `self`.

EXAMPLES:

```
sage: C = Sets.Finite(); C
Category of finite sets
sage: C.base_category()
Category of sets
sage: C._without_axioms()
Category of sets
```

extra_super_categories()

Return the extra super categories of a category with axiom.

Default implementation which returns [].

EXAMPLES:

```
sage: FiniteSets().extra_super_categories()
[]
```

super_categories()

Return a list of the (immediate) super categories of `self`, as per *Category.super_categories()*.

This implements the property that if `As` is a subcategory of `Bs`, then the intersection of `As` with `FiniteSets()` is a subcategory of `As` and of the intersection of `Bs` with `FiniteSets()`.

EXAMPLES:

A finite magma is both a magma and a finite set:

```
sage: Magmas().Finite().super_categories()
[Category of magmas, Category of finite sets]
```

Variants:

```
sage: Sets().Finite().super_categories()
[Category of sets]
```

```
sage: Monoids().Finite().super_categories()
[Category of monoids, Category of finite semigroups]
```

EXAMPLES:

```
class sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom, sage.categories.category_types.Category_over_base_ring
```

```
class sage.categories.category_with_axiom.CategoryWithAxiom_singleton(base_category)
    Bases: sage.categories.category_singleton.Category_singleton, sage.categories.category_with_axiom.CategoryWithAxiom
```

```
class sage.categories.category_with_axiom.TestObjects(s=None)
    Bases: sage.categories.category_singleton.Category_singleton
```

A toy singleton category, for testing purposes.

See also:

[Blahs](#)

```
class Commutative(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

class Facade(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

class Finite(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

class FiniteDimensional(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

class FiniteDimensional(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

class Finite(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

class Unital(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

class Commutative(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

class Unital(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom

super_categories()
```

```
class sage.categories.category_with_axiom.TestObjectsOverBaseRing(base, name=None)
    Bases: sage.categories.category_types.Category_over_base_ring
```

A toy singleton category, for testing purposes.

See also:

[Blahs](#)

```
class Commutative(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring

class Facade(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring

class Finite(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring
```

```

class FiniteDimensional(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring
class FiniteDimensional(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring
class Finite(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring
class Unital(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring
class Commutative(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring
class Unital(base_category)
    Bases: sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring
super_categories()

```

```
sage.categories.category_with_axiom.axiom(axiom)
Return a function/method self -> self._with_axiom(axiom).
```

This can be used as a shorthand to define axioms, in particular in the tests below. Usually one will want to attach documentation to an axiom, so the need for such a shorthand in real life might not be that clear, unless we start creating lots of axioms.

In the long run maybe this could evolve into an @axiom decorator.

EXAMPLES:

```

sage: from sage.categories.category_with_axiom import axiom
sage: axiom("Finite")(Semigroups())
Category of finite semigroups

```

Upon assigning the result to a class this becomes a method:

```

sage: class As:
.....:     def _with_axiom(self, axiom): return self, axiom
.....:     Finite = axiom("Finite")
sage: As().Finite()
(<__main__.As ... at ...>, 'Finite')

```

```
sage.categories.category_with_axiom.axiom_of_nested_class(cls, nested_cls)
Given a class and a nested axiom class, return the axiom.
```

EXAMPLES:

This uses some heuristics like checking if the nested_cls carries the name of the axiom, or is built by appending or prepending the name of the axiom to that of the class:

```

sage: from sage.categories.category_with_axiom import TestObjects, axiom_of_nested_
↪class
sage: axiom_of_nested_class(TestObjects, TestObjects.FiniteDimensional)
'FiniteDimensional'
sage: axiom_of_nested_class(TestObjects.FiniteDimensional, TestObjects.
↪FiniteDimensional.Finite)
'Finite'
sage: axiom_of_nested_class(Sets, FiniteSets)
'Finite'

```

(continues on next page)

(continued from previous page)

```
sage: axiom_of_nested_class(Algebras, AlgebrasWithBasis)
'WithBasis'
```

In all other cases, the nested class should provide an attribute `_base_category_class_and_axiom`:

```
sage: Semigroups._base_category_class_and_axiom
(<class 'sage.categories.magmas.Magmas'>, 'Associative')
sage: axiom_of_nested_class(Magmas, Semigroups)
'Associative'
```

`sage.categories.category_with_axiom.base_category_class_and_axiom(cls)`

Try to deduce the base category and the axiom from the name of `cls`.

The heuristic is to try to decompose the name as the concatenation of the name of a category and the name of an axiom, and looking up that category in the standard location (i.e. in `sage.categories.hopf_algebras` for *HopfAlgebras*, and in `sage.categories.sets_cat` as a special case for *Sets*).

If the heuristic succeeds, the result is guaranteed to be correct. Otherwise, an error is raised.

EXAMPLES:

```
sage: from sage.categories.category_with_axiom import base_category_class_and_axiom,
-> CategoryWithAxiom
sage: base_category_class_and_axiom(FiniteSets)
(<class 'sage.categories.sets_cat.Sets'>, 'Finite')
sage: Sets.Finite
<class 'sage.categories.finite_sets.FiniteSets'>
sage: base_category_class_and_axiom(Sets.Finite)
(<class 'sage.categories.sets_cat.Sets'>, 'Finite')

sage: base_category_class_and_axiom(FiniteDimensionalHopfAlgebrasWithBasis)
(<class 'sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis'>,
->'FiniteDimensional')

sage: base_category_class_and_axiom(HopfAlgebrasWithBasis)
(<class 'sage.categories.hopf_algebras.HopfAlgebras'>, 'WithBasis')
```

Along the way, this does some sanity checks:

```
sage: class FacadeSemigroups(CategoryWithAxiom):
.....:     pass
sage: base_category_class_and_axiom(FacadeSemigroups)
Traceback (most recent call last):
...
AssertionError: Missing (lazy import) link for <class 'sage.categories.semigroups.
->Semigroups'> to <class '__main__.FacadeSemigroups'> for axiom Facade?

sage: Semigroups.Facade = FacadeSemigroups
sage: base_category_class_and_axiom(FacadeSemigroups)
(<class 'sage.categories.semigroups.Semigroups'>, 'Facade')
```

Note: In the following example, we could possibly retrieve *Sets* from the class name. However this cannot be implemented robustly until [trac ticket #9107](#) is fixed. Anyway this feature has not been needed so far:

```

sage: Sets.Infinite
<class 'sage.categories.sets_cat.Sets.Infinite'>
sage: base_category_class_and_axiom(Sets.Infinite)
Traceback (most recent call last):
...
TypeError: Could not retrieve the base category class and axiom for <class 'sage.
↳categories.sets_cat.Sets.Infinite'>.
...

```

`sage.categories.category_with_axiom.uncamelcase(s, separator='')`

EXAMPLES:

```

sage: sage.categories.category_with_axiom.uncamelcase("FiniteDimensionalAlgebras")
'finite dimensional algebras'
sage: sage.categories.category_with_axiom.uncamelcase("JTrivialMonoids")
'j trivial monoids'
sage: sage.categories.category_with_axiom.uncamelcase("FiniteDimensionalAlgebras",
↳" _")
'finite_dimensional_algebras'

```

1.4 Functors

AUTHORS:

- David Kohel and William Stein
- David Joyner (2005-12-17): examples
- Robert Bradshaw (2007-06-23): Pyrexify
- Simon King (2010-04-30): more examples, several bug fixes, re-implementation of the default call method, making functors applicable to morphisms (not only to objects)
- Simon King (2010-12): Pickling of functors without losing domain and codomain

`sage.categories.functor.ForgetfulFunctor(domain, codomain)`

Construct the forgetful function from one category to another.

INPUT:

C, D - two categories

OUTPUT:

A functor that returns the corresponding object of D for any element of C, by forgetting the extra structure.

ASSUMPTION:

The category C must be a sub-category of D.

EXAMPLES:

```

sage: rings = Rings()
sage: abgrps = CommutativeAdditiveGroups()
sage: F = ForgetfulFunctor(rings, abgrps)

```

(continues on next page)

(continued from previous page)

```
sage: F
The forgetful functor from Category of rings to Category of commutative additive_
↳groups
```

It would be a mistake to call it in opposite order:

```
sage: F = ForgetfulFunctor(abgrps, rings)
Traceback (most recent call last):
...
ValueError: Forgetful functor not supported for domain Category of commutative_
↳additive groups
```

If both categories are equal, the forgetful functor is the same as the identity functor:

```
sage: ForgetfulFunctor(abgrps, abgrps) == IdentityFunctor(abgrps)
True
```

class sage.categories.functor.ForgetfulFunctor_generic

Bases: [sage.categories.functor.Functor](#)

The forgetful functor, i.e., embedding of a subcategory.

NOTE:

Forgetful functors should be created using [ForgetfulFunctor\(\)](#), since the init method of this class does not check whether the domain is a subcategory of the codomain.

EXAMPLES:

```
sage: F = ForgetfulFunctor(FiniteFields(), Fields()) #indirect doctest
sage: F
The forgetful functor from Category of finite enumerated fields to Category of_
↳fields
sage: F(GF(3))
Finite Field of size 3
```

class sage.categories.functor.Functor

Bases: [sage.structure.sage_object.SageObject](#)

A class for functors between two categories

NOTE:

- In the first place, a functor is given by its domain and codomain, which are both categories.
- When defining a sub-class, the user should not implement a call method. Instead, one should implement three methods, which are composed in the default call method:
 - `_coerce_into_domain(self, x)`: Return an object of `self`'s domain, corresponding to `x`, or raise a `TypeError`.
 - * Default: Raise `TypeError` if `x` is not in `self`'s domain.
 - `_apply_functor(self, x)`: Apply `self` to an object `x` of `self`'s domain.
 - * Default: Conversion into `self`'s codomain.
 - `_apply_functor_to_morphism(self, f)`: Apply `self` to a morphism `f` in `self`'s domain. - Default: Return `self(f.domain()).hom(f, self(f.codomain()))`.

EXAMPLES:

```

sage: rings = Rings()
sage: abgrps = CommutativeAdditiveGroups()
sage: F = ForgetfulFunctor(rings, abgrps)
sage: F.domain()
Category of rings
sage: F.codomain()
Category of commutative additive groups
sage: from sage.categories.functor import is_Functor
sage: is_Functor(F)
True
sage: I = IdentityFunctor(abgrps)
sage: I
The identity functor on Category of commutative additive groups
sage: I.domain()
Category of commutative additive groups
sage: is_Functor(I)
True

```

Note that by default, an instance of the class Functor is coercion from the domain into the codomain. The above subclasses overloaded this behaviour. Here we illustrate the default:

```

sage: from sage.categories.functor import Functor
sage: F = Functor(Rings(), Fields())
sage: F
Functor from Category of rings to Category of fields
sage: F(ZZ)
Rational Field
sage: F(GF(2))
Finite Field of size 2

```

Functors are not only about the objects of a category, but also about their morphisms. We illustrate it, again, with the coercion functor from rings to fields.

```

sage: R1.<x> = ZZ[]
sage: R2.<a,b> = QQ[]
sage: f = R1.hom([a+b], R2)
sage: f
Ring morphism:
  From: Univariate Polynomial Ring in x over Integer Ring
  To:   Multivariate Polynomial Ring in a, b over Rational Field
  Defn: x |--> a + b
sage: F(f)
Ring morphism:
  From: Fraction Field of Univariate Polynomial Ring in x over Integer Ring
  To:   Fraction Field of Multivariate Polynomial Ring in a, b over Rational Field
  Defn: x |--> a + b
sage: F(f)(1/x)
1/(a + b)

```

We can also apply a polynomial ring construction functor to our homomorphism. The result is a homomorphism that is defined on the base ring:

```

sage: F = QQ['t'].construction()[0]
sage: F
Poly[t]
sage: F(f)
Ring morphism:
  From: Univariate Polynomial Ring in t over Univariate Polynomial Ring in x over
↳Integer Ring
  To:   Univariate Polynomial Ring in t over Multivariate Polynomial Ring in a, b
↳over Rational Field
  Defn: Induced from base ring by
        Ring morphism:
          From: Univariate Polynomial Ring in x over Integer Ring
          To:   Multivariate Polynomial Ring in a, b over Rational Field
          Defn: x |--> a + b
sage: p = R1['t']('(-x^2 + x)*t^2 + (x^2 - x)*t - 4*x^2 - x + 1')
sage: F(f)(p)
(-a^2 - 2*a*b - b^2 + a + b)*t^2 + (a^2 + 2*a*b + b^2 - a - b)*t - 4*a^2 - 8*a*b -
↳4*b^2 - a - b + 1

```

codomain()

The codomain of self

EXAMPLES:

```

sage: F = ForgetfulFunctor(FiniteFields(),Fields())
sage: F.codomain()
Category of fields

```

domain()

The domain of self

EXAMPLES:

```

sage: F = ForgetfulFunctor(FiniteFields(),Fields())
sage: F.domain()
Category of finite enumerated fields

```

sage.categories.functor.IdentityFunctor(C)

Construct the identity functor of the given category.

INPUT:

A category, C.

OUTPUT:

The identity functor in C.

EXAMPLES:

```

sage: rings = Rings()
sage: F = IdentityFunctor(rings)
sage: F(ZZ['x','y']) is ZZ['x','y']
True

```

class sage.categories.functor.IdentityFunctor_generic(C)

Bases: *sage.categories.functor.ForgetfulFunctor_generic*

Generic identity functor on any category

NOTE:

This usually is created using `IdentityFunctor()`.

EXAMPLES:

```
sage: F = IdentityFunctor(Fields()) #indirect doctest
sage: F
The identity functor on Category of fields
sage: F(RR) is RR
True
sage: F(ZZ)
Traceback (most recent call last):
...
TypeError: x (=Integer Ring) is not in Category of fields
```

`sage.categories.functor.is_Functor(x)`

Test whether the argument is a functor

NOTE:

There is a deprecation warning when using it from top level. Therefore we import it in our doc test.

EXAMPLES:

```
sage: from sage.categories.functor import is_Functor
sage: F1 = QQ.construction()[0]
sage: F1
FractionField
sage: is_Functor(F1)
True
sage: is_Functor(FractionField)
False
sage: F2 = ForgetfulFunctor(Fields(), Rings())
sage: F2
The forgetful functor from Category of fields to Category of rings
sage: is_Functor(F2)
True
```

1.5 Implementing a new parent: a (draft of) tutorial

The easiest approach for implementing a new parent is to start from a close example in `sage.categories.examples`. Here, we will get through the process of implementing a new finite semigroup, taking as starting point the provided example:

```
sage: S = FiniteSemigroups().example()
sage: S
An example of a finite semigroup: the left regular band generated by ('a', 'b', 'c', 'd')
```

You may lookup the implementation of this example with:

```
sage: S?? # not tested
```

Or by browsing the source code of `sage.categories.examples.finite_semigroups.LeftRegularBand`.

Copy-paste this code into, say, a cell of the notebook, and replace every occurrence of `FiniteSemigroups().example(...)` in the documentation by `LeftRegularBand`. This will be equivalent to:

```
sage: from sage.categories.examples.finite_semigroups import LeftRegularBand
```

Now, try:

```
sage: S = LeftRegularBand(); S
An example of a finite semigroup: the left regular band generated by ('a', 'b', 'c', 'd')
```

and play around with the examples in the documentation of `S` and of *FiniteSemigroups*.

Rename the class to `ShiftSemigroup`, and modify the product to implement the semigroup generated by the given alphabet such that $au = u$ for any u of length 3.

Use `TestSuite` to test the newly implemented semigroup; draw its Cayley graph.

Add another option to the constructor to generalize the construction to any u of length k .

Lookup the Sloane for the sequence of the sizes of those semigroups.

Now implement the commutative monoid of subsets of $\{1, \dots, n\}$ endowed with union as product. What is its category? What are the extra functionalities available there? Implement iteration and cardinality.

TODO: the tutorial should explain there how to reuse the enumerated set of subsets, and endow it with more structure.

MAPS AND MORPHISMS

2.1 Base class for maps

AUTHORS:

- Robert Bradshaw: initial implementation
- Sebastien Besnier (2014-05-5): *FormalCompositeMap* contains a list of Map instead of only two Map. See [trac ticket #16291](#).
- Sebastian Oehms (2019-01-19): *section()* added to *FormalCompositeMap*. See [trac ticket #27081](#).

class `sage.categories.map.FormalCompositeMap`

Bases: `sage.categories.map.Map`

Formal composite maps.

A formal composite map is formed by two maps, so that the codomain of the first map is contained in the domain of the second map.

Note: When calling a composite with additional arguments, these arguments are *only* passed to the second underlying map.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: S.<a> = QQ[]
sage: from sage.categories.morphism import SetMorphism
sage: f = SetMorphism(Hom(R, S, Rings()), lambda p: p[0]*a^p.degree())
sage: g = S.hom([2*x])
sage: f*g
Composite map:
  From: Univariate Polynomial Ring in a over Rational Field
  To:   Univariate Polynomial Ring in a over Rational Field
  Defn: Ring morphism:
        From: Univariate Polynomial Ring in a over Rational Field
        To:   Univariate Polynomial Ring in x over Rational Field
        Defn: a |--> 2*x
  then
  Generic morphism:
  From: Univariate Polynomial Ring in x over Rational Field
  To:   Univariate Polynomial Ring in a over Rational Field
```

(continues on next page)

(continued from previous page)

```

sage: g*f
Composite map:
  From: Univariate Polynomial Ring in x over Rational Field
  To:   Univariate Polynomial Ring in x over Rational Field
  Defn: Generic morphism:
        From: Univariate Polynomial Ring in x over Rational Field
        To:   Univariate Polynomial Ring in a over Rational Field
  then
        Ring morphism:
        From: Univariate Polynomial Ring in a over Rational Field
        To:   Univariate Polynomial Ring in x over Rational Field
        Defn: a |--> 2*x
sage: (f*g)(2*a^2+5)
5*a^2
sage: (g*f)(2*x^2+5)
20*x^2

```

domains()

Iterate over the domains of the factors of this map.

(This is useful in particular to check for loops in coercion maps.)

See also:

[*Map.domains\(\)*](#)

EXAMPLES:

```

sage: f = QQ.coerce_map_from(ZZ)
sage: g = MatrixSpace(QQ, 2, 2).coerce_map_from(QQ)
sage: list((g*f).domains())
[Integer Ring, Rational Field]

```

first()

Return the first map in the formal composition.

If `self` represents $f_n \circ f_{n-1} \circ \dots \circ f_1 \circ f_0$, then `self.first()` returns f_0 . We have `self == self.then() * self.first()`.

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: S.<a> = QQ[]
sage: from sage.categories.morphism import SetMorphism
sage: f = SetMorphism(Hom(R, S, Rings()), lambda p: p[0]*a^p.degree())
sage: g = S.hom([2*x])
sage: fg = f * g
sage: fg.first() == g
True
sage: fg == fg.then() * fg.first()
True

```

is_injective()

Tell whether `self` is injective.

It raises `NotImplementedError` if it can't be determined.

EXAMPLES:

```
sage: V1 = QQ^2
sage: V2 = QQ^3
sage: phi1 = (QQ^1).hom(Matrix([[1, 1]]), V1)
sage: phi2 = V1.hom(Matrix([[1, 2, 3], [4, 5, 6]]), V2)
```

If both constituents are injective, the composition is injective:

```
sage: from sage.categories.map import FormalCompositeMap
sage: c1 = FormalCompositeMap(Hom(QQ^1, V2, phi1.category_for()), phi1, phi2)
sage: c1.is_injective()
True
```

If it cannot be determined whether the composition is injective, an error is raised:

```
sage: psi1 = V2.hom(Matrix([[1, 2], [3, 4], [5, 6]]), V1)
sage: c2 = FormalCompositeMap(Hom(V1, V1, phi2.category_for()), phi2, psi1)
sage: c2.is_injective()
Traceback (most recent call last):
...
NotImplementedError: Not enough information to deduce injectivity.
```

If the first map is surjective and the second map is not injective, then the composition is not injective:

```
sage: psi2 = V1.hom([[1], [1]], QQ^1)
sage: c3 = FormalCompositeMap(Hom(V2, QQ^1, phi2.category_for()), psi2, psi1)
sage: c3.is_injective()
False
```

`is_surjective()`

Tell whether self is surjective.

It raises `NotImplementedError` if it can't be determined.

EXAMPLES:

```
sage: from sage.categories.map import FormalCompositeMap
sage: V3 = QQ^3
sage: V2 = QQ^2
sage: V1 = QQ^1
```

If both maps are surjective, the composition is surjective:

```
sage: phi32 = V3.hom(Matrix([[1, 2], [3, 4], [5, 6]]), V2)
sage: phi21 = V2.hom(Matrix([[1], [1]]), V1)
sage: c_phi = FormalCompositeMap(Hom(V3, V1, phi32.category_for()), phi32,
↳ phi21)
sage: c_phi.is_surjective()
True
```

If the second map is not surjective, the composition is not surjective:

```
sage: FormalCompositeMap(Hom(V3, V1, phi32.category_for()), phi32, V2.
↳ hom(Matrix([[0], [0]]), V1)).is_surjective()
False
```

If the second map is an isomorphism and the first map is not surjective, then the composition is not surjective:

```
sage: FormalCompositeMap(Hom(V2, V1, phi32.category_for()), V2.hom(Matrix([[0], [0]], V1), V1).hom(Matrix([[1]], V1)).is_surjective()
False
```

Otherwise, surjectivity of the composition cannot be determined:

```
sage: FormalCompositeMap(Hom(V2, V1, phi32.category_for()),
.....: V2.hom(Matrix([[1, 1], [1, 1]]), V2),
.....: V2.hom(Matrix([[1], [1]]), V1)).is_surjective()
Traceback (most recent call last):
...
NotImplementedError: Not enough information to deduce surjectivity.
```

section()

Compute a section map from sections of the factors of `self` if they have been implemented.

EXAMPLES:

```
sage: P.<x> = QQ[]
sage: incl = P.coerce_map_from(ZZ)
sage: sect = incl.section(); sect
Composite map:
  From: Univariate Polynomial Ring in x over Rational Field
  To: Integer Ring
  Defn: Generic map:
        From: Univariate Polynomial Ring in x over Rational Field
        To: Rational Field
  then
  Generic map:
  From: Rational Field
  To: Integer Ring
sage: p = x + 5; q = x + 2
sage: sect(p-q)
3
```

the following example has been attached to `_integer_()` of `sage.rings.polynomial.polynomial_element.Polynomial` before (see comment there):

```
sage: k = GF(47)
sage: R.<x> = PolynomialRing(k)
sage: R.coerce_map_from(ZZ).section()
Composite map:
  From: Univariate Polynomial Ring in x over Finite Field of size 47
  To: Integer Ring
  Defn: Generic map:
        From: Univariate Polynomial Ring in x over Finite Field of size 47
        To: Finite Field of size 47
  then
  Lifting map:
  From: Finite Field of size 47
  To: Integer Ring
sage: ZZ(R(45)) # indirect doctest
```

(continues on next page)

(continued from previous page)

```

45
sage: ZZ(3*x + 45) # indirect doctest
Traceback (most recent call last):
...
TypeError: not a constant polynomial

```

then()

Return the tail of the list of maps.

If `self` represents $f_n \circ f_{n-1} \circ \dots \circ f_1 \circ f_0$, then `self.first()` returns $f_n \circ f_{n-1} \circ \dots \circ f_1$. We have `self == self.then() * self.first()`.

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: S.<a> = QQ[]
sage: from sage.categories.morphism import SetMorphism
sage: f = SetMorphism(Hom(R, S, Rings()), lambda p: p[0]*a^p.degree())
sage: g = S.hom([2*x])
sage: (f*g).then() == f
True

sage: f = QQ.coerce_map_from(ZZ)
sage: f = f.extend_domain(ZZ).extend_codomain(QQ)
sage: f.then()
Composite map:
From: Integer Ring
To: Rational Field
Defn: Natural morphism:
From: Integer Ring
To: Rational Field
then
Identity endomorphism of Rational Field

```

class sage.categories.map.Map

Bases: `sage.structure.element.Element`

Basic class for all maps.

Note: The call method is of course not implemented in this base class. This must be done in the sub classes, by overloading `_call_` and possibly also `_call_with_args`.

EXAMPLES:

Usually, instances of this class will not be constructed directly, but for example like this:

```

sage: from sage.categories.morphism import SetMorphism
sage: X.<x> = ZZ[]
sage: Y = ZZ
sage: phi = SetMorphism(Hom(X, Y, Rings()), lambda p: p[0])
sage: phi(x^2+2*x-1)
-1
sage: R.<x,y> = QQ[]

```

(continues on next page)

(continued from previous page)

```
sage: f = R.hom([x+y, x-y], R)
sage: f(x^2+2*x-1)
x^2 + 2*x*y + y^2 + 2*x + 2*y - 1
```

category_for()

Returns the category self is a morphism for.

Note: This is different from the category of maps to which this map belongs *as an object*.

EXAMPLES:

```
sage: from sage.categories.morphism import SetMorphism
sage: X.<x> = ZZ[]
sage: Y = ZZ
sage: phi = SetMorphism(Hom(X, Y, Rings()), lambda p: p[0])
sage: phi.category_for()
Category of rings
sage: phi.category()
Category of homsets of unital magmas and additive unital additive magmas
sage: R.<x,y> = QQ[]
sage: f = R.hom([x+y, x-y], R)
sage: f.category_for()
Join of Category of unique factorization domains
and Category of commutative algebras
over (number fields and quotient fields and metric spaces)
and Category of infinite sets
sage: f.category()
Category of endsets of unital magmas
and right modules over (number fields and quotient fields and metric spaces)
and left modules over (number fields and quotient fields and metric spaces)
```

FIXME: find a better name for this method

codomain**domain****domains()**

Iterate over the domains of the factors of a (composite) map.

This default implementation simply yields the domain of this map.

See also:

[*FormalCompositeMap.domains\(\)*](#)

EXAMPLES:

```
sage: list(QQ.coerce_map_from(ZZ).domains())
[Integer Ring]
```

extend_codomain(new_codomain)

INPUT:

- `self` – a member of $\text{Hom}(X, Y)$
- `new_codomain` – an object Z such that there is a canonical coercion ϕ in $\text{Hom}(Y, Z)$

OUTPUT:

An element of $\text{Hom}(X, Z)$ obtained by composing self with ϕ . If no canonical ϕ exists, a `TypeError` is raised.

EXAMPLES:

```
sage: mor = QQ.coerce_map_from(ZZ)
sage: mor.extend_codomain(RDF)
Composite map:
  From: Integer Ring
  To:   Real Double Field
  Defn: Natural morphism:
        From: Integer Ring
        To:   Rational Field
        then
        Native morphism:
        From: Rational Field
        To:   Real Double Field
sage: mor.extend_codomain(GF(7))
Traceback (most recent call last):
...
TypeError: No coercion from Rational Field to Finite Field of size 7
```

extend_domain(*new_domain*)

INPUT:

- `self` – a member of $\text{Hom}(Y, Z)$
- `new_codomain` – an object X such that there is a canonical coercion ϕ in $\text{Hom}(X, Y)$

OUTPUT:

An element of $\text{Hom}(X, Z)$ obtained by composing self with ϕ . If no canonical ϕ exists, a `TypeError` is raised.

EXAMPLES:

```
sage: mor = CDF.coerce_map_from(RDF)
sage: mor.extend_domain(QQ)
Composite map:
  From: Rational Field
  To:   Complex Double Field
  Defn: Native morphism:
        From: Rational Field
        To:   Real Double Field
        then
        Native morphism:
        From: Real Double Field
        To:   Complex Double Field
sage: mor.extend_domain(ZZ['x'])
Traceback (most recent call last):
...
TypeError: No coercion from Univariate Polynomial Ring in x over Integer Ring
↳to Real Double Field
```

is_surjective()

Tells whether the map is surjective (not implemented in the base class).

parent()

Return the homset containing this map.

Note: The method `_make_weak_references()`, that is used for the maps found by the coercion system, needs to remove the usual strong reference from the coercion map to the homset containing it. As long as the user keeps strong references to domain and codomain of the map, we will be able to reconstruct the homset. However, a strong reference to the coercion map does not prevent the domain from garbage collection!

EXAMPLES:

```
sage: Q = QuadraticField(-5)
sage: phi = CDF._internal_convert_map_from(Q)
sage: print(phi.parent())
Set of field embeddings from Number Field in a with defining polynomial x^2 + 5
↳with a = 2.236067977499790?*I to Complex Double Field
```

We now demonstrate that the reference to the coercion map ϕ does not prevent Q from being garbage collected:

```
sage: import gc
sage: del Q
sage: _ = gc.collect()
sage: phi.parent()
Traceback (most recent call last):
...
ValueError: This map is in an invalid state, the domain has been garbage
↳collected
```

You can still obtain copies of the maps used by the coercion system with strong references:

```
sage: Q = QuadraticField(-5)
sage: phi = CDF.convert_map_from(Q)
sage: print(phi.parent())
Set of field embeddings from Number Field in a with defining polynomial x^2 + 5
↳with a = 2.236067977499790?*I to Complex Double Field
sage: import gc
sage: del Q
sage: _ = gc.collect()
sage: phi.parent()
Set of field embeddings from Number Field in a with defining polynomial x^2 + 5
↳with a = 2.236067977499790?*I to Complex Double Field
```

post_compose(left)

INPUT:

- `self` – a Map in some $\text{Hom}(X, Y, \text{category_right})$
- `left` – a Map in some $\text{Hom}(Y, Z, \text{category_left})$

Returns the composition of `self` followed by `right` as a morphism in $\text{Hom}(X, Z, \text{category})$ where `category` is the meet of `category_left` and `category_right`.

Caveat: see the current restrictions on [Category.meet\(\)](#)

EXAMPLES:


```

sage: from sage.categories.morphism import SetMorphism
sage: X.<x> = ZZ[]
sage: Y = ZZ
sage: Z = QQ
sage: phi_xy = SetMorphism(Hom(X, Y, Rings()), lambda p: p[0])
sage: phi_yz = SetMorphism(Hom(Y, Z, Monoids()), lambda y: QQ(y**2))
sage: phi_xz = phi_xy.post_compose(phi_yz); phi_xz
Composite map:
  From: Univariate Polynomial Ring in x over Integer Ring
  To: Rational Field
  Defn: Generic morphism:
        From: Univariate Polynomial Ring in x over Integer Ring
        To: Integer Ring
  then
        Generic morphism:
        From: Integer Ring
        To: Rational Field
sage: phi_xz.category_for()
Category of monoids

```

pre_compose(right)

INPUT:

- self – a Map in some $\text{Hom}(Y, Z, \text{category_left})$
- left – a Map in some $\text{Hom}(X, Y, \text{category_right})$

Returns the composition of right followed by self as a morphism in $\text{Hom}(X, Z, \text{category})$ where category is the meet of category_left and category_right.

EXAMPLES:

```

sage: from sage.categories.morphism import SetMorphism
sage: X.<x> = ZZ[]
sage: Y = ZZ
sage: Z = QQ
sage: phi_xy = SetMorphism(Hom(X, Y, Rings()), lambda p: p[0])
sage: phi_yz = SetMorphism(Hom(Y, Z, Monoids()), lambda y: QQ(y**2))
sage: phi_xz = phi_yz.pre_compose(phi_xy); phi_xz
Composite map:
  From: Univariate Polynomial Ring in x over Integer Ring
  To: Rational Field
  Defn: Generic morphism:
        From: Univariate Polynomial Ring in x over Integer Ring
        To: Integer Ring
  then
        Generic morphism:
        From: Integer Ring
        To: Rational Field
sage: phi_xz.category_for()
Category of monoids

```

section()

Return a section of self.

Note: By default, it returns `None`. You may override it in subclasses.

class `sage.categories.map.Section`

Bases: `sage.categories.map.Map`

A formal section of a map.

Note: Call methods are not implemented for the base class `Section`.

EXAMPLES:

```
sage: from sage.categories.map import Section
sage: R.<x,y> = ZZ[]
sage: S.<a,b> = QQ[]
sage: f = R.hom([a+b, a-b])
sage: sf = Section(f); sf
Section map:
  From: Multivariate Polynomial Ring in a, b over Rational Field
  To:   Multivariate Polynomial Ring in x, y over Integer Ring
sage: sf(a)
Traceback (most recent call last):
...
NotImplementedError: <type 'sage.categories.map.Section'>
```

inverse()

Return inverse of `self`.

`sage.categories.map.is_Map(x)`

Auxiliary function: Is the argument a map?

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: f = R.hom([x+y, x-y], R)
sage: from sage.categories.map import is_Map
sage: is_Map(f)
True
```

`sage.categories.map.unpickle_map(_class, parent, _dict, _slots)`

Auxiliary function for unpickling a map.

2.2 Homsets

The class `Hom` is the base class used to represent sets of morphisms between objects of a given category. `Hom` objects are usually “weakly” cached upon creation so that they don’t have to be generated over and over but can be garbage collected together with the corresponding objects when these are not strongly ref’ed anymore.

EXAMPLES:

In the following, the `Hom` object is indeed cached:

```
sage: K = GF(17)
sage: H = Hom(ZZ, K)
sage: H
Set of Homomorphisms from Integer Ring to Finite Field of size 17
sage: H is Hom(ZZ, K)
True
```

Nonetheless, garbage collection occurs when the original references are overwritten:

```
sage: for p in prime_range(200):
.....:     K = GF(p)
.....:     H = Hom(ZZ, K)
sage: import gc
sage: _ = gc.collect()
sage: from sage.rings.finite_rings.finite_field_prime_modn import FiniteField_prime_modn
      ↪ as FF
sage: L = [x for x in gc.get_objects() if isinstance(x, FF)]
sage: len(L)
1
sage: L
[Finite Field of size 199]
```

AUTHORS:

- David Kohel and William Stein
- David Joyner (2005-12-17): added examples
- William Stein (2006-01-14): Changed from Homspace to Homset.
- Nicolas M. Thiery (2008-12-): Updated for the new category framework
- Simon King (2011-12): Use a weak cache for homsets
- Simon King (2013-02): added examples

sage.categories.homset.**End**(*X*, *category=None*)
Create the set of endomorphisms of *X* in the category category.

INPUT:

- *X* – anything
- *category* – (optional) category in which to coerce *X*

OUTPUT:

A set of endomorphisms in category

EXAMPLES:

```
sage: V = VectorSpace(QQ, 3)
sage: End(V)
Set of Morphisms (Linear Transformations) from
Vector space of dimension 3 over Rational Field to
Vector space of dimension 3 over Rational Field
```

```
sage: G = AlternatingGroup(3)
sage: S = End(G); S
```

(continues on next page)

(continued from previous page)

```

Set of Morphisms from Alternating group of order 3!/2 as a permutation group to
→Alternating group of order 3!/2 as a permutation group in Category of finite
→enumerated permutation groups
sage: from sage.categories.homset import is_Endset
sage: is_Endset(S)
True
sage: S.domain()
Alternating group of order 3!/2 as a permutation group

```

To avoid creating superfluous categories, a homset in a category $Cs()$ is in the homset category of the lowest full super category $Bs()$ of $Cs()$ that implements $Bs.Homsets$ (or the join thereof if there are several). For example, finite groups form a full subcategory of unital magmas: any unital magma morphism between two finite groups is a finite group morphism. Since finite groups currently implement nothing more than unital magmas about their homsets, we have:

```

sage: G = GL(3,3)
sage: G.category()
Category of finite groups
sage: H = Hom(G,G)
sage: H.homset_category()
Category of finite groups
sage: H.category()
Category of endsets of unital magmas

```

Similarly, a ring morphism just needs to preserve addition, multiplication, zero, and one. Accordingly, and since the category of rings implements nothing specific about its homsets, a ring homset is currently constructed in the category of homsets of unital magmas and unital additive magmas:

```

sage: H = Hom(ZZ,ZZ,Rings())
sage: H.category()
Category of endsets of unital magmas and additive unital additive magmas

```

`sage.categories.homset.Hom(X, Y, category=None, check=True)`
 Create the space of homomorphisms from X to Y in the category `category`.

INPUT:

- X – an object of a category
- Y – an object of a category
- `category` – a category in which the morphisms must be. (default: the meet of the categories of X and Y) Both X and Y must belong to that category.
- `check` – a boolean (default: `True`): whether to check the input, and in particular that X and Y belong to `category`.

OUTPUT: a homset in category

EXAMPLES:

```

sage: V = VectorSpace(QQ,3)
sage: Hom(V, V)
Set of Morphisms (Linear Transformations) from
Vector space of dimension 3 over Rational Field to
Vector space of dimension 3 over Rational Field

```

(continues on next page)

(continued from previous page)

```

sage: G = AlternatingGroup(3)
sage: Hom(G, G)
Set of Morphisms from Alternating group of order 3!/2 as a permutation group to
↳Alternating group of order 3!/2 as a permutation group in Category of finite
↳enumerated permutation groups
sage: Hom(ZZ, QQ, Sets())
Set of Morphisms from Integer Ring to Rational Field in Category of sets

sage: Hom(FreeModule(ZZ,1), FreeModule(QQ,1))
Set of Morphisms from Ambient free module of rank 1 over the principal ideal domain
↳Integer Ring to Vector space of dimension 1 over Rational Field in Category of
↳commutative additive groups
sage: Hom(FreeModule(QQ,1), FreeModule(ZZ,1))
Set of Morphisms from Vector space of dimension 1 over Rational Field to Ambient
↳free module of rank 1 over the principal ideal domain Integer Ring in Category of
↳commutative additive groups

```

Here, we test against a memory leak that has been fixed at [trac ticket #11521](#) by using a weak cache:

```

sage: for p in prime_range(10^3):
.....: K = GF(p)
.....: a = K(0)
sage: import gc
sage: gc.collect()          # random
624
sage: from sage.rings.finite_rings.finite_field_prime_modn import FiniteField_prime_
↳modn as FF
sage: L = [x for x in gc.get_objects() if isinstance(x, FF)]
sage: len(L), L[0]
(1, Finite Field of size 997)

```

To illustrate the choice of the category, we consider the following parents as running examples:

```

sage: X = ZZ; X
Integer Ring
sage: Y = SymmetricGroup(3); Y
Symmetric group of order 3! as a permutation group

```

By default, the smallest category containing both X and Y, is used:

```

sage: Hom(X, Y)
Set of Morphisms from Integer Ring
to Symmetric group of order 3! as a permutation group
in Category of enumerated monoids

```

Otherwise, if category is specified, then category is used, after checking that X and Y are indeed in category:

```

sage: Hom(X, Y, Magmas())
Set of Morphisms from Integer Ring to Symmetric group of order 3! as a permutation
↳group in Category of magmas

sage: Hom(X, Y, Groups())
Traceback (most recent call last):

```

(continues on next page)

(continued from previous page)

```
...
ValueError: Integer Ring is not in Category of groups
```

A parent (or a parent class of a category) may specify how to construct certain homsets by implementing a method `_Hom_(self, codomain, category)`. This method should either construct the requested homset or raise a `TypeError`. This hook is currently mostly used to create homsets in some specific subclass of `Homset` (e.g. `sage.rings.homset.RingHomset`):

```
sage: Hom(QQ, QQ).__class__
<class 'sage.rings.homset.RingHomset_generic_with_category'>
```

Do not call this hook directly to create homsets, as it does not handle unique representation:

```
sage: Hom(QQ, QQ) == QQ._Hom_(QQ, category=QQ.category())
True
sage: Hom(QQ, QQ) is QQ._Hom_(QQ, category=QQ.category())
False
```

Todo:

- Design decision: how much of the homset comes from the category of X and Y , and how much from the specific X and Y . In particular, do we need several parent classes depending on X and Y , or does the difference only lie in the elements (i.e. the morphism), and of course how the parent calls their constructors.
- Specify the protocol for the `_Hom_` hook in case of ambiguity (e.g. if both a parent and some category thereof provide one).

```
class sage.categories.homset.Homset(X, Y, category=None, base=None, check=True)
```

Bases: `sage.structure.parent.Set_generic`

The class for collections of morphisms in a category.

EXAMPLES:

```
sage: H = Hom(QQ^2, QQ^3)
sage: loads(H.dumps()) is H
True
```

Homsets of unique parents are unique as well:

```
sage: H = End(AffineSpace(2, names='x,y'))
sage: loads(dumps(AffineSpace(2, names='x,y'))) is AffineSpace(2, names='x,y')
True
sage: loads(dumps(H)) is H
True
```

Conversely, homsets of non-unique parents are non-unique:

```
sage: H = End(ProductProjectiveSpaces(QQ, [1, 1]))
sage: loads(dumps(ProductProjectiveSpaces(QQ, [1, 1]))) is_
↪ProductProjectiveSpaces(QQ, [1, 1])
False
sage: loads(dumps(ProductProjectiveSpaces(QQ, [1, 1]))) ==_
↪ProductProjectiveSpaces(QQ, [1, 1])
```

(continues on next page)

(continued from previous page)

```
True
sage: loads(dumps(H)) is H
False
sage: loads(dumps(H)) == H
True
```

codomain()

Return the codomain of this homset.

EXAMPLES:

```
sage: P.<t> = ZZ[]
sage: f = P.hom([1/2*t])
sage: f.parent().codomain()
Univariate Polynomial Ring in t over Rational Field
sage: f.codomain() is f.parent().codomain()
True
```

domain()

Return the domain of this homset.

EXAMPLES:

```
sage: P.<t> = ZZ[]
sage: f = P.hom([1/2*t])
sage: f.parent().domain()
Univariate Polynomial Ring in t over Integer Ring
sage: f.domain() is f.parent().domain()
True
```

element_class_set_morphism()

A base class for elements of this homset which are also `SetMorphism`, i.e. implemented by mean of a Python function.

This is currently plain `SetMorphism`, without inheritance from categories.

Todo: Refactor during the upcoming homset cleanup.

EXAMPLES:

```
sage: H = Hom(ZZ, ZZ)
sage: H.element_class_set_morphism
<type 'sage.categories.morphism.SetMorphism'>
```

homset_category()

Return the category that this is a Hom in, i.e., this is typically the category of the domain or codomain object.

EXAMPLES:

```
sage: H = Hom(AlternatingGroup(4), AlternatingGroup(7))
sage: H.homset_category()
Category of finite enumerated permutation groups
```

identity()

The identity map of this homset.

Note: Of course, this only exists for sets of endomorphisms.

EXAMPLES:

```
sage: H = Hom(QQ,QQ)
sage: H.identity()
Identity endomorphism of Rational Field
sage: H = Hom(ZZ,QQ)
sage: H.identity()
Traceback (most recent call last):
...
TypeError: Identity map only defined for endomorphisms. Try natural_map()
↳instead.
sage: H.natural_map()
Natural morphism:
  From: Integer Ring
  To:   Rational Field
```

natural_map()

Return the “natural map” of this homset.

Note: By default, a formal coercion morphism is returned.

EXAMPLES:

```
sage: H = Hom(ZZ['t'],QQ['t'], CommutativeAdditiveGroups())
sage: H.natural_map()
Coercion morphism:
  From: Univariate Polynomial Ring in t over Integer Ring
  To:   Univariate Polynomial Ring in t over Rational Field
sage: H = Hom(QQ['t'],GF(3)['t'])
sage: H.natural_map()
Traceback (most recent call last):
...
TypeError: natural coercion morphism from Univariate Polynomial Ring in t over
↳Rational Field to Univariate Polynomial Ring in t over Finite Field of size 3
↳not defined
```

one()

The identity map of this homset.

Note: Of course, this only exists for sets of endomorphisms.

EXAMPLES:

```
sage: K = GaussianIntegers()
sage: End(K).one()
Identity endomorphism of Gaussian Integers in Number Field in I with defining
↳polynomial x^2 + 1 with I = 1*I
```

(continues on next page)

(continued from previous page)

reversed()

Return the corresponding homset, but with the domain and codomain reversed.

EXAMPLES:

```

sage: H = Hom(ZZ^2, ZZ^3); H
Set of Morphisms from Ambient free module of rank 2 over
the principal ideal domain Integer Ring to Ambient free module
of rank 3 over the principal ideal domain Integer Ring in
Category of finite dimensional modules with basis over (euclidean
domains and infinite enumerated sets and metric spaces)
sage: type(H)
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>
sage: H.reversed()
Set of Morphisms from Ambient free module of rank 3 over
the principal ideal domain Integer Ring to Ambient free module
of rank 2 over the principal ideal domain Integer Ring in
Category of finite dimensional modules with basis over (euclidean
domains and infinite enumerated sets and metric spaces)
sage: type(H.reversed())
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>

```

class `sage.categories.homset.HomsetWithBase`(*X, Y, category=None, check=True, base=None*)

Bases: `sage.categories.homset.Homset`

`sage.categories.homset.end`(*X, f*)

Return $\text{End}(X)$ (*f*), where *f* is data that defines an element of $\text{End}(X)$.

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: phi = end(R, [x + 1])
sage: phi
Ring endomorphism of Univariate Polynomial Ring in x over Rational Field
Defn: x |--> x + 1
sage: phi(x^2 + 5)
x^2 + 2*x + 6

```

`sage.categories.homset.hom`(*X, Y, f*)

Return $\text{Hom}(X, Y)$ (*f*), where *f* is data that defines an element of $\text{Hom}(X, Y)$.

EXAMPLES:

```

sage: phi = hom(QQ['x'], QQ, [2])
sage: phi(x^2 + 3)
7

```

`sage.categories.homset.is_Endset`(*x*)

Return True if *x* is a set of endomorphisms in a category.

EXAMPLES:

```

sage: from sage.categories.homset import is_Endset
sage: P.<t> = ZZ[]

```

(continues on next page)

(continued from previous page)

```

sage: f = P.hom([1/2*t])
sage: is_Endset(f.parent())
False
sage: g = P.hom([2*t])
sage: is_Endset(g.parent())
True

```

`sage.categories.homset.is_Homset(x)`
Return True if `x` is a set of homomorphisms in a category.

EXAMPLES:

```

sage: from sage.categories.homset import is_Homset
sage: P.<t> = ZZ[]
sage: f = P.hom([1/2*t])
sage: is_Homset(f)
False
sage: is_Homset(f.category())
False
sage: is_Homset(f.parent())
True

```

2.3 Morphisms

This module defines the base classes of morphisms between objects of a given category.

EXAMPLES:

Typically, a morphism is defined by the images of the generators of the domain.

```

sage: X.<a, b> = ZZ[]
sage: Y.<c> = ZZ[]
sage: X.hom([c, c^2])
Ring morphism:
  From: Multivariate Polynomial Ring in a, b over Integer Ring
  To:   Univariate Polynomial Ring in c over Integer Ring
  Defn: a |--> c
        b |--> c^2

```

AUTHORS:

- William Stein (2005): initial version
- David Joyner (2005-12-17): added examples
- Robert Bradshaw (2007-06-25): Pyrexification

```

class sage.categories.morphism.CallMorphism
  Bases: sage.categories.morphism.Morphism

```

```

class sage.categories.morphism.FormalCoercionMorphism
  Bases: sage.categories.morphism.Morphism

```

```

class sage.categories.morphism.IdentityMorphism
  Bases: sage.categories.morphism.Morphism

```

is_identity()

Return True if this morphism is the identity morphism.

EXAMPLES:

```
sage: E = End(Partitions(5))
sage: E.identity().is_identity()
True
```

Check that [trac ticket #15478](#) is fixed:

```
sage: K.<z> = GF(4)
sage: phi = End(K)([z^2])
sage: R.<t> = K[]
sage: psi = End(R)(phi)
sage: psi.is_identity()
False
```

is_injective()

Return whether this morphism is injective.

EXAMPLES:

```
sage: Hom(ZZ, ZZ).identity().is_injective()
True
```

is_surjective()

Return whether this morphism is surjective.

EXAMPLES:

```
sage: Hom(ZZ, ZZ).identity().is_surjective()
True
```

section()

Return a section of this morphism.

EXAMPLES:

```
sage: T = Hom(ZZ, ZZ).identity()
sage: T.section() is T
True
```

class sage.categories.morphism.Morphism

Bases: *sage.categories.map.Map*

category()

Return the category of the parent of this morphism.

EXAMPLES:

```
sage: R.<t> = ZZ[]
sage: f = R.hom([t**2])
sage: f.category()
Category of endsets of unital magmas and right modules over
(euclidean domains and infinite enumerated sets and metric spaces)
and left modules over (euclidean domains
```

(continues on next page)

(continued from previous page)

and infinite enumerated sets and metric spaces)

```
sage: K = CyclotomicField(12)
sage: L = CyclotomicField(132)
sage: phi = L._internal_coerce_map_from(K)
sage: phi.category()
Category of homsets of number fields
```

is_endomorphism()

Return True if this morphism is an endomorphism.

EXAMPLES:

```
sage: R.<t> = ZZ[]
sage: f = R.hom([t])
sage: f.is_endomorphism()
True

sage: K = CyclotomicField(12)
sage: L = CyclotomicField(132)
sage: phi = L._internal_coerce_map_from(K)
sage: phi.is_endomorphism()
False
```

is_identity()

Return True if this morphism is the identity morphism.

Note: Implemented only when the domain has a method gens()

EXAMPLES:

```
sage: R.<t> = ZZ[]
sage: f = R.hom([t])
sage: f.is_identity()
True
sage: g = R.hom([t+1])
sage: g.is_identity()
False
```

A morphism between two different spaces cannot be the identity:

```
sage: R2.<t2> = QQ[]
sage: h = R.hom([t2])
sage: h.is_identity()
False
```

pushforward(I)**register_as_coercion()**

Register this morphism as a coercion to Sage's coercion model (see [sage.structure.coerce](#)).

EXAMPLES:

By default, adding polynomials over different variables triggers an error:

```

sage: X.<x> = ZZ[]
sage: Y.<y> = ZZ[]
sage: x^2 + y
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for +: 'Univariate Polynomial Ring in
↪x over Integer Ring' and 'Univariate Polynomial Ring in y over Integer Ring'

```

Let us declare a coercion from $\mathbf{Z}[x]$ to $\mathbf{Z}[z]$:

```

sage: Z.<z> = ZZ[]
sage: phi = Hom(X, Z)(z)
sage: phi(x^2+1)
z^2 + 1
sage: phi.register_as_coercion()

```

Now we can add elements from $\mathbf{Z}[x]$ and $\mathbf{Z}[z]$, because the elements of the former are allowed to be implicitly coerced into the later:

```

sage: x^2 + z
z^2 + z

```

Caveat: the registration of the coercion must be done before any other coercion is registered or discovered:

```

sage: phi = Hom(X, Z)(z^2)
sage: phi.register_as_coercion()
Traceback (most recent call last):
...
AssertionError: coercion from Univariate Polynomial Ring in x over Integer Ring
↪to Univariate Polynomial Ring in z over Integer Ring already registered or
↪discovered

```

register_as_conversion()

Register this morphism as a conversion to Sage's coercion model

(see `sage.structure.coerce`).

EXAMPLES:

Let us declare a conversion from the symmetric group to \mathbf{Z} through the sign map:

```

sage: S = SymmetricGroup(4)
sage: phi = Hom(S, ZZ)(lambda x: ZZ(x.sign()))
sage: x = S.an_element(); x
(2, 3, 4)
sage: phi(x)
1
sage: phi.register_as_conversion()
sage: ZZ(x)
1

```

class sage.categories.morphism.SetMorphism

Bases: `sage.categories.morphism.Morphism`

INPUT:

- `parent` – a Homset

- `function` – a Python function that takes elements of the domain as input and returns elements of the domain.

EXAMPLES:

```
sage: from sage.categories.morphism import SetMorphism
sage: f = SetMorphism(Hom(QQ, ZZ, Sets()), numerator)
sage: f.parent()
Set of Morphisms from Rational Field to Integer Ring in Category of sets
sage: f.domain()
Rational Field
sage: f.codomain()
Integer Ring
sage: TestSuite(f).run()
```

`sage.categories.morphism.is_Morphism(x)`

2.4 Coercion via construction functors

class `sage.categories.pushout.AlgebraicClosureFunctor`

Bases: `sage.categories.pushout.ConstructionFunctor`

Algebraic Closure.

EXAMPLES:

```
sage: F = CDF.construction()[0]
sage: F(QQ)
Algebraic Field
sage: F(RR)
Complex Field with 53 bits of precision
sage: F(F(QQ)) is F(QQ)
True
```

merge(*other*)

Mathematically, Algebraic Closure subsumes Algebraic Extension. However, it seems that people do want to work with algebraic extensions of RR. Therefore, we do not merge with algebraic extension.

class `sage.categories.pushout.AlgebraicExtensionFunctor`(*polys, names, embeddings, structures, cyclotomic=None, prec=None, implementations=None, residue=None, latex_names=None, **kwds*)

Bases: `sage.categories.pushout.ConstructionFunctor`

Algebraic extension (univariate polynomial ring modulo principal ideal).

EXAMPLES:

```
sage: K.<a> = NumberField(x^3+x^2+1)
sage: F = K.construction()[0]
sage: F(ZZ['t'])
Univariate Quotient Polynomial Ring in a over Univariate Polynomial Ring in t over
↳ Integer Ring with modulus a^3 + a^2 + 1
```

Note that, even if a field is algebraically closed, the algebraic extension will be constructed as the quotient of a univariate polynomial ring:

```

sage: F(CC)
Univariate Quotient Polynomial Ring in a over Complex Field with 53 bits of
precision with modulus a^3 + a^2 + 1.0000000000000000
sage: F(RR)
Univariate Quotient Polynomial Ring in a over Real Field with 53 bits of precision
with modulus a^3 + a^2 + 1.0000000000000000

```

Note that the construction functor of a number field applied to the integers returns an order (not necessarily maximal) of that field, similar to the behaviour of `ZZ.extension(...)`:

```

sage: F(ZZ)
Order in Number Field in a with defining polynomial x^3 + x^2 + 1

```

This also holds for non-absolute number fields:

```

sage: K.<a,b> = NumberField([x^3+x^2+1,x^2+x+1])
sage: F = K.construction()[0]
sage: O = F(ZZ); O
Relative Order in Number Field in a with defining polynomial x^3 + x^2 + 1 over its
base field
sage: O.ambient() is K
True

```

Special cases are made for cyclotomic fields and residue fields:

```

sage: C = CyclotomicField(8)
sage: F,R = C.construction()
sage: F
AlgebraicExtensionFunctor
sage: R
Rational Field
sage: F(R)
Cyclotomic Field of order 8 and degree 4
sage: F(ZZ)
Maximal Order in Cyclotomic Field of order 8 and degree 4

```

```

sage: K.<z> = CyclotomicField(7)
sage: P = K.factor(17)[0][0]
sage: k = K.residue_field(P)
sage: F, R = k.construction()
sage: F
AlgebraicExtensionFunctor
sage: R
Cyclotomic Field of order 7 and degree 6
sage: F(R) is k
True
sage: F(ZZ)
Residue field of Integers modulo 17
sage: F(CyclotomicField(49))
Residue field in zbar of Fractional ideal (17)

```

expand()

Decompose the functor F into sub-functors, whose product returns F .

EXAMPLES:

```
sage: P.<x> = QQ[]
sage: K.<a> = NumberField(x^3-5, embedding=0)
sage: L.<b> = K.extension(x^2+a)
sage: F,R = L.construction()
sage: prod(F.expand())(R) == L
True
sage: K = NumberField([x^2-2, x^2-3], 'a')
sage: F, R = K.construction()
sage: F
AlgebraicExtensionFunctor
sage: L = F.expand(); L
[AlgebraicExtensionFunctor, AlgebraicExtensionFunctor]
sage: L[-1](QQ)
Number Field in a1 with defining polynomial x^2 - 3
```

merge(*other*)

Merging with another *AlgebraicExtensionFunctor*.

INPUT:

other – Construction Functor.

OUTPUT:

- If `self==other`, `self` is returned.
- If `self` and `other` are simple extensions and both provide an embedding, then it is tested whether one of the number fields provided by the functors coerces into the other; the functor associated with the target of the coercion is returned. Otherwise, the construction functor associated with the pushout of the codomains of the two embeddings is returned, provided that it is a number field.
- If these two extensions are defined by Conway polynomials over finite fields, merges them into a single extension of degree the lcm of the two degrees.
- Otherwise, `None` is returned.

REMARK:

Algebraic extension with embeddings currently only works when applied to the rational field. This is why we use the admittedly strange rule above for merging.

EXAMPLES:

The following demonstrate coercions for finite fields using Conway or pseudo-Conway polynomials:

```
sage: k = GF(3^2, prefix='z'); a = k.gen()
sage: l = GF(3^3, prefix='z'); b = l.gen()
sage: a + b # indirect doctest
z6^5 + 2*z6^4 + 2*z6^3 + z6^2 + 2*z6 + 1
```

Note that embeddings are compatible in lattices of such finite fields:

```
sage: m = GF(3^5, prefix='z'); c = m.gen()
sage: (a+b)+c == a+(b+c) # indirect doctest
True
sage: from sage.categories.pushout import pushout
sage: n = pushout(k, l)
```

(continues on next page)

(continued from previous page)

```
sage: o = pushout(l, m)
sage: q = pushout(n, o)
sage: q(o(b)) == q(n(b)) # indirect doctest
True
```

Coercion is also available for number fields:

```
sage: P.<x> = QQ[]
sage: L.<b> = NumberField(x^8-x^4+1, embedding=CDF.0)
sage: M1.<c1> = NumberField(x^2+x+1, embedding=b^4-1)
sage: M2.<c2> = NumberField(x^2+1, embedding=-b^6)
sage: M1.coerce_map_from(M2)
sage: M2.coerce_map_from(M1)
sage: c1+c2; parent(c1+c2) #indirect doctest
-b^6 + b^4 - 1
Number Field in b with defining polynomial x^8 - x^4 + 1 with b = -0.
↳2588190451025208? + 0.9659258262890683?*I
sage: pushout(M1['x'],M2['x'])
Univariate Polynomial Ring in x over Number Field in b with defining polynomial
↳x^8 - x^4 + 1 with b = -0.2588190451025208? + 0.9659258262890683?*I
```

In the previous example, the number field L becomes the pushout of M1 and M2 since both are provided with an embedding into L, *and* since L is a number field. If two number fields are embedded into a field that is not a numberfield, no merging occurs:

```
sage: K.<a> = NumberField(x^3-2, embedding=CDF(1/2*I*2^(1/3)*sqrt(3) - 1/2*2^(1/
↳3)))
sage: L.<b> = NumberField(x^6-2, embedding=1.1)
sage: L.coerce_map_from(K)
sage: K.coerce_map_from(L)
sage: pushout(K,L)
Traceback (most recent call last):
...
CoercionException: ('Ambiguous Base Extension', Number Field in a with defining
↳polynomial x^3 - 2 with a = -0.6299605249474365? + 1.091123635971722?*I,
↳Number Field in b with defining polynomial x^6 - 2 with b = 1.122462048309373?
↳)
```

```
class sage.categories.pushout.BlackBoxConstructionFunctor(box)
```

Bases: `sage.categories.pushout.ConstructionFunctor`

Construction functor obtained from any callable object.

EXAMPLES:

```
sage: from sage.categories.pushout import BlackBoxConstructionFunctor
sage: FG = BlackBoxConstructionFunctor(gap)
sage: FS = BlackBoxConstructionFunctor(singular)
sage: FG
BlackBoxConstructionFunctor
sage: FG(ZZ)
Integers
sage: FG(ZZ).parent()
Gap
```

(continues on next page)

(continued from previous page)

```

sage: FS(QQ['t'])
polynomial ring, over a field, global ordering
// coefficients: QQ
// number of vars : 1
//      block 1 : ordering lp
//              : names t
//      block 2 : ordering C
sage: FG == FS
False
sage: FG == loads(dumps(FG))
True

```

class `sage.categories.pushout.CompletionFunctor`(*p, prec, extras=None*)

Bases: `sage.categories.pushout.ConstructionFunctor`

Completion of a ring with respect to a given prime (including infinity).

EXAMPLES:

```

sage: R = Zp(5)
sage: R
5-adic Ring with capped relative precision 20
sage: F1 = R.construction()[0]
sage: F1
Completion[5, prec=20]
sage: F1(ZZ) is R
True
sage: F1(QQ)
5-adic Field with capped relative precision 20
sage: F2 = RR.construction()[0]
sage: F2
Completion[+Infinity, prec=53]
sage: F2(QQ) is RR
True
sage: P.<x> = ZZ[]
sage: Px = P.completion(x) # currently the only implemented completion of P
sage: Px
Power Series Ring in x over Integer Ring
sage: F3 = Px.construction()[0]
sage: F3(GF(3)['x'])
Power Series Ring in x over Finite Field of size 3

```

commutes(*other*)

Completion commutes with fraction fields.

EXAMPLES:

```

sage: F1 = Zp(5).construction()[0]
sage: F2 = QQ.construction()[0]
sage: F1.commutates(F2)
True

```

merge(*other*)

Two Completion functors are merged, if they are equal. If the precisions of both functors coincide, then a Completion functor is returned that results from updating the extras dictionary of `self` by `other`.

extras. Otherwise, if the completion is at infinity then merging does not increase the set precision, and if the completion is at a finite prime, merging does not decrease the capped precision.

EXAMPLES:

```
sage: R1.<a> = Zp(5,prec=20)[]
sage: R2 = Qp(5,prec=40)
sage: R2(1)+a # indirect doctest
(1 + 0(5^20))*a + 1 + 0(5^40)
sage: R3 = RealField(30)
sage: R4 = RealField(50)
sage: R3(1) + R4(1) # indirect doctest
2.00000000
sage: (R3(1) + R4(1)).parent()
Real Field with 30 bits of precision
```

class `sage.categories.pushout.CompositeConstructionFunctor(*args)`

Bases: `sage.categories.pushout.ConstructionFunctor`

A Construction Functor composed by other Construction Functors.

INPUT:

F_1, F_2, \dots : A list of Construction Functors. The result is the composition F_1 followed by F_2 followed by ...

EXAMPLES:

```
sage: from sage.categories.pushout import CompositeConstructionFunctor
sage: F = CompositeConstructionFunctor(QQ.construction()[0], ZZ['x'].
↳ construction()[0], QQ.construction()[0], ZZ['y'].construction()[0])
sage: F
Poly[y](FractionField(Poly[x](FractionField(...))))
sage: F == loads(dumps(F))
True
sage: F == CompositeConstructionFunctor(*F.all)
True
sage: F(GF(2)['t'])
Univariate Polynomial Ring in y over Fraction Field of Univariate Polynomial Ring
↳ in x over Fraction Field of Univariate Polynomial Ring in t over Finite Field of
↳ size 2 (using GF2X)
```

expand()

Return expansion of a CompositeConstructionFunctor.

Note: The product over the list of components, as returned by the `expand()` method, is equal to `self`.

EXAMPLES:

```
sage: from sage.categories.pushout import CompositeConstructionFunctor
sage: F = CompositeConstructionFunctor(QQ.construction()[0], ZZ['x'].
↳ construction()[0], QQ.construction()[0], ZZ['y'].construction()[0])
sage: F
Poly[y](FractionField(Poly[x](FractionField(...))))
sage: prod(F.expand()) == F
True
```

class `sage.categories.pushout.ConstructionFunctor`Bases: `sage.categories.functor.Functor`

Base class for construction functors.

A construction functor is a functorial algebraic construction, such as the construction of a matrix ring over a given ring or the fraction field of a given ring.

In addition to the class `Functor`, construction functors provide rules for combining and merging constructions. This is an important part of Sage's coercion model, namely the pushout of two constructions: When a polynomial p in a variable x with integer coefficients is added to a rational number q , then Sage finds that the parents $\mathbb{Z}\langle x \rangle$ and \mathbb{Q} are obtained from \mathbb{Z} by applying a polynomial ring construction respectively the fraction field construction. Each construction functor has an attribute `rank`, and the rank of the polynomial ring construction is higher than the rank of the fraction field construction. This means that the pushout of \mathbb{Q} and $\mathbb{Z}\langle x \rangle$, and thus a common parent in which p and q can be added, is $\mathbb{Q}\langle x \rangle$, since the construction functor with a lower rank is applied first.

```

sage: F1, R = QQ.construction()
sage: F1
FractionField
sage: R
Integer Ring
sage: F2, R = (ZZ['x']).construction()
sage: F2
Poly[x]
sage: R
Integer Ring
sage: F3 = F2.pushout(F1)
sage: F3
Poly[x](FractionField(...))
sage: F3(R)
Univariate Polynomial Ring in x over Rational Field
sage: from sage.categories.pushout import pushout
sage: P.<x> = ZZ[]
sage: pushout(QQ,P)
Univariate Polynomial Ring in x over Rational Field
sage: ((x+1) + 1/2).parent()
Univariate Polynomial Ring in x over Rational Field

```

When composing two construction functors, they are sometimes merged into one, as is the case in the Quotient construction:

```

sage: Q15, R = (ZZ.quo(15*ZZ)).construction()
sage: Q15
QuotientFunctor
sage: Q35, R = (ZZ.quo(35*ZZ)).construction()
sage: Q35
QuotientFunctor
sage: Q15.merge(Q35)
QuotientFunctor
sage: Q15.merge(Q35)(ZZ)
Ring of integers modulo 5

```

Functors can not only be applied to objects, but also to morphisms in the respective categories. For example:

```

sage: P.<x,y> = ZZ[]
sage: F = P.construction()[0]; F
MPoly[x,y]
sage: A.<a,b> = GF(5)[]
sage: f = A.hom([a+b,a-b],A)
sage: F(A)
Multivariate Polynomial Ring in x, y over Multivariate Polynomial Ring in a, b over
↳Finite Field of size 5
sage: F(f)
Ring endomorphism of Multivariate Polynomial Ring in x, y over Multivariate
↳Polynomial Ring in a, b over Finite Field of size 5
  Defn: Induced from base ring by
        Ring endomorphism of Multivariate Polynomial Ring in a, b over Finite Field
↳of size 5
          Defn: a |--> a + b
                b |--> a - b
sage: F(f)(F(A)(x)*a)
(a + b)*x

```

common_base(*other_functor*, *self_bases*, *other_bases*)

This function is called by [pushout\(\)](#) when no common parent is found in the construction tower.

Note: The main use is for multivariate construction functors, which use this function to implement recursion for [pushout\(\)](#).

INPUT:

- *other_functor* – a construction functor.
- *self_bases* – the arguments passed to this functor.
- *other_bases* – the arguments passed to the functor *other_functor*.

OUTPUT:

Nothing, since a [CoercionException](#) is raised.

Note: Overload this function in derived class, see e.e. [MultivariateConstructionFunctor](#).

commutes(*other*)

Determine whether *self* commutes with another construction functor.

Note: By default, `False` is returned in all cases (even if the two functors are the same, since in this case [merge\(\)](#) will apply anyway). So far there is no construction functor that overloads this method. Anyway, this method only becomes relevant if two construction functors have the same rank.

EXAMPLES:

```

sage: F = QQ.construction()[0]
sage: P = ZZ['t'].construction()[0]
sage: F.commutates(P)
False

```

(continues on next page)

(continued from previous page)

```

sage: P.commutates(F)
False
sage: F.commutates(F)
False

```

expand()

Decompose `self` into a list of construction functors.

Note: The default is to return the list only containing `self`.

EXAMPLES:

```

sage: F = QQ.construction()[0]
sage: F.expand()
[FractionField]
sage: Q = ZZ.quo(2).construction()[0]
sage: Q.expand()
[QuotientFunctor]
sage: P = ZZ['t'].construction()[0]
sage: FP = F*P
sage: FP.expand()
[FractionField, Poly[t]]

```

merge(*other*)

Merge `self` with another construction functor, or return `None`.

Note: The default is to merge only if the two functors coincide. But this may be overloaded for subclasses, such as the quotient functor.

EXAMPLES:

```

sage: F = QQ.construction()[0]
sage: P = ZZ['t'].construction()[0]
sage: F.merge(F)
FractionField
sage: F.merge(P)
sage: P.merge(F)
sage: P.merge(P)
Poly[t]

```

pushout(*other*)

Composition of two construction functors, ordered by their ranks.

Note:

- This method seems not to be used in the coercion model.
 - By default, the functor with smaller rank is applied first.
-

class `sage.categories.pushout.FractionField`

Bases: `sage.categories.pushout.ConstructionFunctor`

Construction functor for fraction fields.

EXAMPLES:

```

sage: F = QQ.construction()[0]
sage: F
FractionField
sage: F.domain()
Category of integral domains
sage: F.codomain()
Category of fields
sage: F(GF(5)) is GF(5)
True
sage: F(ZZ['t'])
Fraction Field of Univariate Polynomial Ring in t over Integer Ring
sage: P.<x,y> = QQ[]
sage: f = P.hom([x+2*y,3*x-y],P)
sage: F(f)
Ring endomorphism of Fraction Field of Multivariate Polynomial Ring in x, y over
↪Rational Field
  Defn: x |--> x + 2*y
        y |--> 3*x - y
sage: F(f)(1/x)
1/(x + 2*y)
sage: F == loads(dumps(F))
True

```

class `sage.categories.pushout.IdentityConstructionFunctor`

Bases: `sage.categories.pushout.ConstructionFunctor`

A construction functor that is the identity functor.

class `sage.categories.pushout.InfinitePolynomialFunctor`(*gens, order, implementation*)

Bases: `sage.categories.pushout.ConstructionFunctor`

A Construction Functor for Infinite Polynomial Rings (see `infinite_polynomial_ring`).

AUTHOR:

– Simon King

This construction functor is used to provide uniqueness of infinite polynomial rings as parent structures. As usual, the construction functor allows for constructing pushouts.

Another purpose is to avoid name conflicts of variables of the to-be-constructed infinite polynomial ring with variables of the base ring, and moreover to keep the internal structure of an Infinite Polynomial Ring as simple as possible: If variables v_1, \dots, v_n of the given base ring generate an *ordered* sub-monoid of the monomials of the ambient Infinite Polynomial Ring, then they are removed from the base ring and merged with the generators of the ambient ring. However, if the orders don't match, an error is raised, since there was a name conflict without merging.

EXAMPLES:

```

sage: A.<a,b> = InfinitePolynomialRing(ZZ['t'])
sage: A.construction()
[InfPoly{[a,b], "lex", "dense"},
 Univariate Polynomial Ring in t over Integer Ring]
sage: type(_[0])

```

(continues on next page)

(continued from previous page)

```
<class 'sage.categories.pushout.InfinitePolynomialFunctor'>
sage: B.<x,y,a_3,a_1> = PolynomialRing(QQ, order='lex')
sage: B.construction()
(MPoly[x,y,a_3,a_1], Rational Field)
sage: A.construction()[0]*B.construction()[0]
InfPoly{[a,b], "lex", "dense"}(MPoly[x,y](...))
```

Apparently the variables a_1, a_3 of the polynomial ring are merged with the variables a_0, a_1, a_2, \dots of the infinite polynomial ring; indeed, they form an ordered sub-structure. However, if the polynomial ring was given a different ordering, merging would not be allowed, resulting in a name conflict:

```
sage: A.construction()[0]*PolynomialRing(QQ,names=['x','y','a_3','a_1']).
↪construction()[0]
Traceback (most recent call last):
...
CoercionException: Incompatible term orders lex, degrevlex
```

In an infinite polynomial ring with generator a_* , the variable a_3 will always be greater than the variable a_1 . Hence, the orders are incompatible in the next example as well:

```
sage: A.construction()[0]*PolynomialRing(QQ,names=['x','y','a_1','a_3'], order='lex
↪').construction()[0]
Traceback (most recent call last):
...
CoercionException: Overlapping variables (('a', 'b'), ['a_1', 'a_3']) are
↪incompatible
```

Another requirement is that after merging the order of the remaining variables must be unique. This is not the case in the following example, since it is not clear whether the variables x, y should be greater or smaller than the variables b_* :

```
sage: A.construction()[0]*PolynomialRing(QQ,names=['a_3','a_1','x','y'], order='lex
↪').construction()[0]
Traceback (most recent call last):
...
CoercionException: Overlapping variables (('a', 'b'), ['a_3', 'a_1']) are
↪incompatible
```

Since the construction functors are actually used to construct infinite polynomial rings, the following result is no surprise:

```
sage: C.<a,b> = InfinitePolynomialRing(B); C
Infinite polynomial ring in a, b over Multivariate Polynomial Ring in x, y over
↪Rational Field
```

There is also an overlap in the next example:

```
sage: X.<w,x,y> = InfinitePolynomialRing(ZZ)
sage: Y.<x,y,z> = InfinitePolynomialRing(QQ)
```

X and Y have an overlapping generators x_*, y_* . Since the default lexicographic order is used in both rings, it gives rise to isomorphic sub-monoids in both X and Y . They are merged in the pushout, which also yields a common parent for doing arithmetic:


```

sage: P = sage.categories.pushout.pushout(Y,X); P
Infinite polynomial ring in w, x, y, z over Rational Field
sage: w[2]+z[3]
w_2 + z_3
sage: _.parent() is P
True

```

expand()

Decompose the functor F into sub-functors, whose product returns F .

EXAMPLES:

```

sage: F = InfinitePolynomialRing(QQ, ['x','y'],order='degrevlex').
↳construction()[0]; F
InfPoly{[x,y], "degrevlex", "dense"}
sage: F.expand()
[InfPoly{[y], "degrevlex", "dense"}, InfPoly{[x], "degrevlex", "dense"}]
sage: F = InfinitePolynomialRing(QQ, ['x','y','z'],order='degrevlex').
↳construction()[0]; F
InfPoly{[x,y,z], "degrevlex", "dense"}
sage: F.expand()
[InfPoly{[z], "degrevlex", "dense"},
 InfPoly{[y], "degrevlex", "dense"},
 InfPoly{[x], "degrevlex", "dense"}]
sage: prod(F.expand())==F
True

```

merge(*other*)

Merge two construction functors of infinite polynomial rings, regardless of monomial order and implementation.

The purpose is to have a pushout (and thus, arithmetic) even in cases when the parents are isomorphic as rings, but not as ordered rings.

EXAMPLES:

```

sage: X.<x,y> = InfinitePolynomialRing(QQ,implementation='sparse')
sage: Y.<x,y> = InfinitePolynomialRing(QQ,order='degrevlex')
sage: X.construction()
[InfPoly{[x,y], "lex", "sparse"}, Rational Field]
sage: Y.construction()
[InfPoly{[x,y], "degrevlex", "dense"}, Rational Field]
sage: Y.construction()[0].merge(Y.construction()[0])
InfPoly{[x,y], "degrevlex", "dense"}
sage: y[3] + X(x[2])
x_2 + y_3
sage: _.parent().construction()
[InfPoly{[x,y], "degrevlex", "dense"}, Rational Field]

```

class sage.categories.pushout.**LaurentPolynomialFunctor**(*var*, *multi_variate=False*)

Bases: *sage.categories.pushout.ConstructionFunctor*

Construction functor for Laurent polynomial rings.

EXAMPLES:

```

sage: L.<t> = LaurentPolynomialRing(ZZ)
sage: F = L.construction()[0]
sage: F
LaurentPolynomialFunctor
sage: F(QQ)
Univariate Laurent Polynomial Ring in t over Rational Field
sage: K.<x> = LaurentPolynomialRing(ZZ)
sage: F(K)
Univariate Laurent Polynomial Ring in t over Univariate Laurent Polynomial Ring in
↳x over Integer Ring
sage: P.<x,y> = ZZ[]
sage: f = P.hom([x+2*y, 3*x-y], P)
sage: F(f)
Ring endomorphism of Univariate Laurent Polynomial Ring in t over Multivariate
↳Polynomial Ring in x, y over Integer Ring
Defn: Induced from base ring by
      Ring endomorphism of Multivariate Polynomial Ring in x, y over Integer Ring
      Defn: x |--> x + 2*y
            y |--> 3*x - y
sage: F(f)(x*F(P).gen()^-2+y*F(P).gen()^3)
(x + 2*y)*t^-2 + (3*x - y)*t^3

```

merge(*other*)

Two Laurent polynomial construction functors merge if the variable names coincide.

The result is multivariate if one of the arguments is multivariate.

EXAMPLES:

```

sage: from sage.categories.pushout import LaurentPolynomialFunctor
sage: F1 = LaurentPolynomialFunctor('t')
sage: F2 = LaurentPolynomialFunctor('t', multi_variate=True)
sage: F1.merge(F2)
LaurentPolynomialFunctor
sage: F1.merge(F2)(LaurentPolynomialRing(GF(2), 'a'))
Multivariate Laurent Polynomial Ring in a, t over Finite Field of size 2
sage: F1.merge(F1)(LaurentPolynomialRing(GF(2), 'a'))
Univariate Laurent Polynomial Ring in t over Univariate Laurent Polynomial Ring
↳in a over Finite Field of size 2

```

class `sage.categories.pushout.MatrixFunctor`(*nrows*, *ncols*, *is_sparse=False*)

Bases: `sage.categories.pushout.ConstructionFunctor`

A construction functor for matrices over rings.

EXAMPLES:

```

sage: MS = MatrixSpace(ZZ, 2, 3)
sage: F = MS.construction()[0]; F
MatrixFunctor
sage: MS = MatrixSpace(ZZ, 2)
sage: F = MS.construction()[0]; F
MatrixFunctor
sage: P.<x,y> = QQ[]
sage: R = F(P); R

```

(continues on next page)

(continued from previous page)

```

Full MatrixSpace of 2 by 2 dense matrices over Multivariate Polynomial Ring in x, y
↳over Rational Field
sage: f = P.hom([x+y,x-y],P); F(f)
Ring endomorphism of Full MatrixSpace of 2 by 2 dense matrices over Multivariate
↳Polynomial Ring in x, y over Rational Field
Defn: Induced from base ring by
      Ring endomorphism of Multivariate Polynomial Ring in x, y over Rational
↳Field
Defn: x |--> x + y
      y |--> x - y
sage: M = R([x,y,x*y,x+y])
sage: F(f)(M)
[  x + y    x - y]
[x^2 - y^2    2*x]

```

merge(*other*)

Merging is only happening if both functors are matrix functors of the same dimension.

The result is sparse if and only if both given functors are sparse.

EXAMPLES:

```

sage: F1 = MatrixSpace(ZZ,2,2).construction()[0]
sage: F2 = MatrixSpace(ZZ,2,3).construction()[0]
sage: F3 = MatrixSpace(ZZ,2,2,sparse=True).construction()[0]
sage: F1.merge(F2)
sage: F1.merge(F3)
MatrixFunctor
sage: F13 = F1.merge(F3)
sage: F13.is_sparse
False
sage: F1.is_sparse
False
sage: F3.is_sparse
True
sage: F3.merge(F3).is_sparse
True

```

class sage.categories.pushout.**MultiPolynomialFunctor**(*vars, term_order*)

Bases: [sage.categories.pushout.ConstructionFunctor](#)

A constructor for multivariate polynomial rings.

EXAMPLES:

```

sage: P.<x,y> = ZZ[]
sage: F = P.construction()[0]; F
MPoly[x,y]
sage: A.<a,b> = GF(5)[]
sage: F(A)
Multivariate Polynomial Ring in x, y over Multivariate Polynomial Ring in a, b over
↳Finite Field of size 5
sage: f = A.hom([a+b,a-b],A)
sage: F(f)

```

(continues on next page)

(continued from previous page)

```

Ring endomorphism of Multivariate Polynomial Ring in x, y over Multivariate_
↳Polynomial Ring in a, b over Finite Field of size 5
  Defn: Induced from base ring by
        Ring endomorphism of Multivariate Polynomial Ring in a, b over Finite Field_
↳of size 5
      Defn: a |--> a + b
            b |--> a - b
sage: F(f)(F(A)(x)*a)
(a + b)*x

```

expand()

Decompose self into a list of construction functors.

EXAMPLES:

```

sage: F = QQ['x,y,z,t'].construction()[0]; F
MPoly[x,y,z,t]
sage: F.expand()
[MPoly[t], MPoly[z], MPoly[y], MPoly[x]]

```

Now an actual use case:

```

sage: R.<x,y,z> = ZZ[]
sage: S.<z,t> = QQ[]
sage: x+t
x + t
sage: parent(x+t)
Multivariate Polynomial Ring in x, y, z, t over Rational Field
sage: T.<y,s> = QQ[]
sage: x + s
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for +: 'Multivariate Polynomial Ring_
↳in x, y, z over Integer Ring' and 'Multivariate Polynomial Ring in y, s over_
↳Rational Field'
sage: R = PolynomialRing(ZZ, 'x', 500)
sage: S = PolynomialRing(GF(5), 'x', 200)
sage: R.gen(0) + S.gen(0)
2*x0

```

merge(*other*)

Merge self with another construction functor, or return None.

EXAMPLES:

```

sage: F = sage.categories.pushout.MultiPolynomialFunctor(['x','y'], None)
sage: G = sage.categories.pushout.MultiPolynomialFunctor(['t'], None)
sage: F.merge(G) is None
True
sage: F.merge(F)
MPoly[x,y]

```

class sage.categories.pushout.MultivariateConstructionFunctorBases: *sage.categories.pushout.ConstructionFunctor*

An abstract base class for functors that take multiple inputs (e.g. Cartesian products).

common_base(*other_functor*, *self_bases*, *other_bases*)

This function is called by *pushout()* when no common parent is found in the construction tower.

INPUT:

- *other_functor* – a construction functor.
- *self_bases* – the arguments passed to this functor.
- *other_bases* – the arguments passed to the functor *other_functor*.

OUTPUT:

A parent.

If no common base is found a `sage.structure.coerce_exceptions.CoercionException` is raised.

Note: Overload this function in derived class, see e.g. *MultivariateConstructionFunctor*.

class `sage.categories.pushout.PermutationGroupFunctor`(*gens*, *domain*)

Bases: `sage.categories.pushout.ConstructionFunctor`

EXAMPLES:

```
sage: from sage.categories.pushout import PermutationGroupFunctor
sage: PF = PermutationGroupFunctor([PermutationGroupElement([(1,2)])], [(1,2)]); PF
PermutationGroupFunctor[(1,2)]
```

gens()

EXAMPLES:

```
sage: P1 = PermutationGroup([(1,2)])
sage: PF, P = P1.construction()
sage: PF.gens()
[(1,2)]
```

merge(*other*)

Merge self with another construction functor, or return None.

EXAMPLES:

```
sage: P1 = PermutationGroup([(1,2)])
sage: PF1, P = P1.construction()
sage: P2 = PermutationGroup([(1,3)])
sage: PF2, P = P2.construction()
sage: PF1.merge(PF2)
PermutationGroupFunctor[(1,2), (1,3)]
```

class `sage.categories.pushout.PolynomialFunctor`(*var*, *multi_variate=False*, *sparse=False*)

Bases: `sage.categories.pushout.ConstructionFunctor`

Construction functor for univariate polynomial rings.

EXAMPLES:

```

sage: P = ZZ['t'].construction()[0]
sage: P(GF(3))
Univariate Polynomial Ring in t over Finite Field of size 3
sage: P == loads(dumps(P))
True
sage: R.<x,y> = GF(5)[]
sage: f = R.hom([x+2*y, 3*x-y], R)
sage: P(f)((x+y)*P(R).0)
(-x + y)*t

```

By [trac ticket #9944](#), the construction functor distinguishes sparse and dense polynomial rings. Before, the following example failed:

```

sage: R.<x> = PolynomialRing(GF(5), sparse=True)
sage: F,B = R.construction()
sage: F(B) is R
True
sage: S.<x> = PolynomialRing(ZZ)
sage: R.has_coerce_map_from(S)
False
sage: S.has_coerce_map_from(R)
False
sage: S.0 + R.0
2*x
sage: (S.0 + R.0).parent()
Univariate Polynomial Ring in x over Finite Field of size 5
sage: (S.0 + R.0).parent().is_sparse()
False

```

`merge`(*other*)

Merge self with another construction functor, or return None.

Note: Internally, the merging is delegated to the merging of multipolynomial construction functors. But in effect, this does the same as the default implementation, that returns None unless the to-be-merged functors coincide.

EXAMPLES:

```

sage: P = ZZ['x'].construction()[0]
sage: Q = ZZ['y', 'x'].construction()[0]
sage: P.merge(Q)
sage: P.merge(P) is P
True

```

class `sage.categories.pushout.QuotientFunctor`(*I*, *names=None*, *as_field=False*, *domain=None*, *codomain=None*, ***kwds*)

Bases: `sage.categories.pushout.ConstructionFunctor`

Construction functor for quotient rings.

Note: The functor keeps track of variable names. Optionally, it may keep track of additional properties of the quotient, such as its category or its implementation.

EXAMPLES:

```
sage: P.<x,y> = ZZ[]
sage: Q = P.quo([x^2+y^2]*P)
sage: F = Q.construction()[0]
sage: F(QQ['x','y'])
Quotient of Multivariate Polynomial Ring in x, y over Rational Field by the ideal
↳(x^2 + y^2)
sage: F(QQ['x','y']) == QQ['x','y'].quo([x^2+y^2]*QQ['x','y'])
True
sage: F(QQ['x','y','z'])
Traceback (most recent call last):
...
CoercionException: Cannot apply this quotient functor to Multivariate Polynomial
↳Ring in x, y, z over Rational Field
sage: F(QQ['y','z'])
Traceback (most recent call last):
...
TypeError: Could not find a mapping of the passed element to this ring.
```

merge(*other*)

Two quotient functors with coinciding names are merged by taking the gcd of their moduli, the meet of their domains, and the join of their codomains.

In particular, if one of the functors being merged knows that the quotient is going to be a field, then the merged functor will return fields as well.

EXAMPLES:

```
sage: P.<x> = QQ[]
sage: Q1 = P.quo([(x^2+1)^2*(x^2-3)])
sage: Q2 = P.quo([(x^2+1)^2*(x^5+3)])
sage: from sage.categories.pushout import pushout
sage: pushout(Q1,Q2) # indirect doctest
Univariate Quotient Polynomial Ring in xbar over Rational Field with modulus x^
↳4 + 2*x^2 + 1
```

The following was fixed in [trac ticket #8800](#):

```
sage: pushout(GF(5), Integers(5))
Finite Field of size 5
```

class `sage.categories.pushout.SubspaceFunctor`(*basis*)

Bases: `sage.categories.pushout.ConstructionFunctor`

Constructing a subspace of an ambient free module, given by a basis.

Note: This construction functor keeps track of the basis. It can only be applied to free modules into which this basis coerces.

EXAMPLES:

```
sage: M = ZZ^3
sage: S = M.submodule([(1,2,3),(4,5,6)]); S
```

(continues on next page)

(continued from previous page)

```

Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1 2 3]
[0 3 6]
sage: F = S.construction()[0]
sage: F(GF(2)^3)
Vector space of degree 3 and dimension 2 over Finite Field of size 2
User basis matrix:
[1 0 1]
[0 1 0]

```

merge(*other*)

Two Subspace Functors are merged into a construction functor of the sum of two subspaces.

EXAMPLES:

```

sage: M = GF(5)^3
sage: S1 = M.submodule([(1,2,3),(4,5,6)])
sage: S2 = M.submodule([(2,2,3)])
sage: F1 = S1.construction()[0]
sage: F2 = S2.construction()[0]
sage: F1.merge(F2)
SubspaceFunctor
sage: F1.merge(F2)(GF(5)^3) == S1+S2
True
sage: F1.merge(F2)(GF(5)['t']^3)
Free module of degree 3 and rank 3 over Univariate Polynomial Ring in t over
↳Finite Field of size 5
User basis matrix:
[1 0 0]
[0 1 0]
[0 0 1]

```

class `sage.categories.pushout.VectorFunctor`(*n*, *is_sparse=False*, *inner_product_matrix=None*)

Bases: `sage.categories.pushout.ConstructionFunctor`

A construction functor for free modules over commutative rings.

EXAMPLES:

```

sage: F = (ZZ^3).construction()[0]
sage: F
VectorFunctor
sage: F(GF(2)['t'])
Ambient free module of rank 3 over the principal ideal domain Univariate Polynomial
↳Ring in t over Finite Field of size 2 (using GF2X)

```

merge(*other*)

Two constructors of free modules merge, if the module ranks and the inner products coincide. If both have explicitly given inner product matrices, they must coincide as well.

EXAMPLES:

Two modules without explicitly given inner product allow coercion:


```

sage: M1 = QQ^3
sage: P.<t> = ZZ[]
sage: M2 = FreeModule(P, 3)
sage: M1([1, 1/2, 1/3]) + M2([t, t^2+t, 3])      # indirect doctest
(t + 1, t^2 + t + 1/2, 10/3)

```

If only one summand has an explicit inner product, the result will be provided with it:

```

sage: M3 = FreeModule(P, 3, inner_product_matrix = Matrix(3, 3, range(9)))
sage: M1([1, 1/2, 1/3]) + M3([t, t^2+t, 3])
(t + 1, t^2 + t + 1/2, 10/3)
sage: (M1([1, 1/2, 1/3]) + M3([t, t^2+t, 3])).parent().inner_product_matrix()
[0 1 2]
[3 4 5]
[6 7 8]

```

If both summands have an explicit inner product (even if it is the standard inner product), then the products must coincide. The only difference between M1 and M4 in the following example is the fact that the default inner product was *explicitly* requested for M4. It is therefore not possible to coerce with a different inner product:

```

sage: M4 = FreeModule(QQ, 3, inner_product_matrix = Matrix(3, 3, 1))
sage: M4 == M1
True
sage: M4.inner_product_matrix() == M1.inner_product_matrix()
True
sage: M4([1, 1/2, 1/3]) + M3([t, t^2+t, 3])      # indirect doctest
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for +: 'Ambient quadratic space of
↳ dimension 3 over Rational Field
Inner product matrix:
[1 0 0]
[0 1 0]
[0 0 1]' and 'Ambient free quadratic module of rank 3 over the integral domain
↳ Univariate Polynomial Ring in t over Integer Ring
Inner product matrix:
[0 1 2]
[3 4 5]
[6 7 8]'

```

`sage.categories.pushout.construction_tower(R)`

An auxiliary function that is used in `pushout()` and `pushout_lattice()`.

INPUT:

An object

OUTPUT:

A constructive description of the object from scratch, by a list of pairs of a construction functor and an object to which the construction functor is to be applied. The first pair is formed by None and the given object.

EXAMPLES:

```

sage: from sage.categories.pushout import construction_tower
sage: construction_tower(MatrixSpace(FractionField(QQ['t']),2))
[(None, Full MatrixSpace of 2 by 2 dense matrices over Fraction Field of Univariate
↪Polynomial Ring in t over Rational Field), (MatrixFunctor, Fraction Field of
↪Univariate Polynomial Ring in t over Rational Field), (FractionField, Univariate
↪Polynomial Ring in t over Rational Field), (Poly[t], Rational Field),
↪(FractionField, Integer Ring)]

```

`sage.categories.pushout.expand_tower(tower)`

An auxiliary function that is used in `pushout()`.

INPUT:

A construction tower as returned by `construction_tower()`.

OUTPUT:

A new construction tower with all the construction functors expanded.

EXAMPLES:

```

sage: from sage.categories.pushout import construction_tower, expand_tower
sage: construction_tower(QQ['x,y,z'])
[(None, Multivariate Polynomial Ring in x, y, z over Rational Field),
 (MPoly[x,y,z], Rational Field),
 (FractionField, Integer Ring)]
sage: expand_tower(construction_tower(QQ['x,y,z']))
[(None, Multivariate Polynomial Ring in x, y, z over Rational Field),
 (MPoly[z], Univariate Polynomial Ring in y over Univariate Polynomial Ring in x
↪over Rational Field),
 (MPoly[y], Univariate Polynomial Ring in x over Rational Field),
 (MPoly[x], Rational Field),
 (FractionField, Integer Ring)]

```

`sage.categories.pushout.pushout(R, S)`

Given a pair of objects R and S , try to construct a reasonable object Y and return maps such that canonically $R \leftarrow Y \rightarrow S$.

ALGORITHM:

This incorporates the idea of functors discussed at Sage Days 4. Every object R can be viewed as an initial object and a series of functors (e.g. polynomial, quotient, extension, completion, vector/matrix, etc.). Call the series of increasingly simple objects (with the associated functors) the “tower” of R . The construction method is used to create the tower.

Given two objects R and S , try to find a common initial object Z . If the towers of R and S meet, let Z be their join. Otherwise, see if the top of one coerces naturally into the other.

Now we have an initial object and two ordered lists of functors to apply. We wish to merge these in an unambiguous order, popping elements off the top of one or the other tower as we apply them to Z .

- If the functors are of distinct types, there is an absolute ordering given by the rank attribute. Use this.
- Otherwise:
 - If the tops are equal, we (try to) merge them.
 - If exactly one occurs lower in the other tower, we may unambiguously apply the other (hoping for a later merge).
 - If the tops commute, we can apply either first.

- Otherwise fail due to ambiguity.

The algorithm assumes by default that when a construction F is applied to an object X , the object $F(X)$ admits a coercion map from X . However, the algorithm can also handle the case where $F(X)$ has a coercion map *to* X instead. In this case, the attribute `coercion_reversed` of the class implementing F should be set to `True`.

EXAMPLES:

Here our “towers” are $R = \text{Complete}_7(\text{Frac}(\mathbf{Z}))$ and $\text{Frac}(\text{Poly}_x(\mathbf{Z}))$, which give us $\text{Frac}(\text{Poly}_x(\text{Complete}_7(\text{Frac}(\mathbf{Z}))))$:

```
sage: from sage.categories.pushout import pushout
sage: pushout(Qp(7), Frac(ZZ['x']))
Fraction Field of Univariate Polynomial Ring in x over 7-adic Field with capped
↪relative precision 20
```

Note we get the same thing with

```
sage: pushout(Zp(7), Frac(QQ['x']))
Fraction Field of Univariate Polynomial Ring in x over 7-adic Field with capped
↪relative precision 20
sage: pushout(Zp(7)['x'], Frac(QQ['x']))
Fraction Field of Univariate Polynomial Ring in x over 7-adic Field with capped
↪relative precision 20
```

Note that polynomial variable ordering must be unambiguously determined.

```
sage: pushout(ZZ['x,y,z'], QQ['w,z,t'])
Traceback (most recent call last):
...
CoercionException: ('Ambiguous Base Extension', Multivariate Polynomial Ring in x,
↪y, z over Integer Ring, Multivariate Polynomial Ring in w, z, t over Rational
↪Field)
sage: pushout(ZZ['x,y,z'], QQ['w,x,z,t'])
Multivariate Polynomial Ring in w, x, y, z, t over Rational Field
```

Some other examples:

```
sage: pushout(Zp(7)['y'], Frac(QQ['t'])['x,y,z'])
Multivariate Polynomial Ring in x, y, z over Fraction Field of Univariate
↪Polynomial Ring in t over 7-adic Field with capped relative precision 20
sage: pushout(ZZ['x,y,z'], Frac(ZZ['x'])['y'])
Multivariate Polynomial Ring in y, z over Fraction Field of Univariate Polynomial
↪Ring in x over Integer Ring
sage: pushout(MatrixSpace(RDF, 2, 2), Frac(ZZ['x']))
Full MatrixSpace of 2 by 2 dense matrices over Fraction Field of Univariate
↪Polynomial Ring in x over Real Double Field
sage: pushout(ZZ, MatrixSpace(ZZ[['x']], 3, 3))
Full MatrixSpace of 3 by 3 dense matrices over Power Series Ring in x over Integer
↪Ring
sage: pushout(QQ['x,y'], ZZ[['x']])
Univariate Polynomial Ring in y over Power Series Ring in x over Rational Field
sage: pushout(Frac(ZZ['x']), QQ[['x']])
Laurent Series Ring in x over Rational Field
```

A construction with `coercion_reversed = True` (currently only the *SubspaceFunctor* construction) is only

applied if it leads to a valid coercion:

```

sage: A = ZZ^2
sage: V = span([[1, 2]], QQ)
sage: P = sage.categories.pushout.pushout(A, V)
sage: P
Vector space of dimension 2 over Rational Field
sage: P.has_coerce_map_from(A)
True

sage: V = (QQ^3).span([[1, 2, 3/4]])
sage: A = ZZ^3
sage: pushout(A, V)
Vector space of dimension 3 over Rational Field
sage: B = A.span([[0, 0, 2/3]])
sage: pushout(B, V)
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 2 0]
[0 0 1]

```

Some more tests with `coercion_reversed = True`:

```

sage: from sage.categories.pushout import ConstructionFunctor
sage: class EvenPolynomialRing(type(QQ['x'])):
.....:     def __init__(self, base, var):
.....:         super(EvenPolynomialRing, self).__init__(base, var)
.....:         self.register_embedding(base[var])
.....:     def __repr__(self):
.....:         return "Even Power " + super(EvenPolynomialRing, self).__repr__()
.....:     def construction(self):
.....:         return EvenPolynomialFunctor(), self.base()[self.variable_name()]
.....:     def _coerce_map_from_(self, R):
.....:         return self.base().has_coerce_map_from(R)
sage: class EvenPolynomialFunctor(ConstructionFunctor):
.....:     rank = 10
.....:     coercion_reversed = True
.....:     def __init__(self):
.....:         ConstructionFunctor.__init__(self, Rings(), Rings())
.....:     def _apply_functor(self, R):
.....:         return EvenPolynomialRing(R.base(), R.variable_name())
sage: pushout(EvenPolynomialRing(QQ, 'x'), ZZ)
Even Power Univariate Polynomial Ring in x over Rational Field
sage: pushout(EvenPolynomialRing(QQ, 'x'), QQ)
Even Power Univariate Polynomial Ring in x over Rational Field
sage: pushout(EvenPolynomialRing(QQ, 'x'), RR)
Even Power Univariate Polynomial Ring in x over Real Field with 53 bits of precision

sage: pushout(EvenPolynomialRing(QQ, 'x'), ZZ['x'])
Univariate Polynomial Ring in x over Rational Field
sage: pushout(EvenPolynomialRing(QQ, 'x'), QQ['x'])
Univariate Polynomial Ring in x over Rational Field
sage: pushout(EvenPolynomialRing(QQ, 'x'), RR['x'])
Univariate Polynomial Ring in x over Real Field with 53 bits of precision

```

(continues on next page)

(continued from previous page)

```

sage: pushout(EvenPolynomialRing(QQ, 'x'), EvenPolynomialRing(QQ, 'x'))
Even Power Univariate Polynomial Ring in x over Rational Field
sage: pushout(EvenPolynomialRing(QQ, 'x'), EvenPolynomialRing(RR, 'x'))
Even Power Univariate Polynomial Ring in x over Real Field with 53 bits of precision

sage: pushout(EvenPolynomialRing(QQ, 'x')^2, RR^2)
Ambient free module of rank 2 over the principal ideal domain Even Power Univariate_
↳Polynomial Ring in x over Real Field with 53 bits of precision
sage: pushout(EvenPolynomialRing(QQ, 'x')^2, RR['x']^2)
Ambient free module of rank 2 over the principal ideal domain Univariate Polynomial_
↳Ring in x over Real Field with 53 bits of precision

```

Some more tests related to univariate/multivariate constructions. We consider a generalization of polynomial rings, where in addition to the coefficient ring C we also specify an additive monoid E for the exponents of the indeterminate. In particular, the elements of such a parent are given by

$$\sum_{i=0}^I c_i X^{e_i}$$

with $c_i \in C$ and $e_i \in E$. We define

```

sage: class GPolynomialRing(Parent):
.....:     def __init__(self, coefficients, var, exponents):
.....:         self.coefficients = coefficients
.....:         self.var = var
.....:         self.exponents = exponents
.....:         super(GPolynomialRing, self).__init__(category=Rings())
.....:     def _repr_(self):
.....:         return 'Generalized Polynomial Ring in %s^(%s) over %s' % (
.....:             self.var, self.exponents, self.coefficients)
.....:     def construction(self):
.....:         return GPolynomialFuncor(self.var, self.exponents), self.coefficients
.....:     def _coerce_map_from_(self, R):
.....:         return self.coefficients.has_coerce_map_from(R)

```

and

```

sage: class GPolynomialFuncor(ConstructionFuncor):
.....:     rank = 10
.....:     def __init__(self, var, exponents):
.....:         self.var = var
.....:         self.exponents = exponents
.....:         ConstructionFuncor.__init__(self, Rings(), Rings())
.....:     def _repr_(self):
.....:         return 'GPoly[%s^(%s)]' % (self.var, self.exponents)
.....:     def _apply_funcor(self, coefficients):
.....:         return GPolynomialRing(coefficients, self.var, self.exponents)
.....:     def merge(self, other):
.....:         if isinstance(other, GPolynomialFuncor) and self.var == other.var:
.....:             exponents = pushout(self.exponents, other.exponents)
.....:             return GPolynomialFuncor(self.var, exponents)

```

We can construct a parent now in two different ways:

```

sage: GPolynomialRing(QQ, 'X', ZZ)
Generalized Polynomial Ring in X^(Integer Ring) over Rational Field
sage: GP_ZZ = GPolynomialFunctor('X', ZZ); GP_ZZ
GPoly[X^(Integer Ring)]
sage: GP_ZZ(QQ)
Generalized Polynomial Ring in X^(Integer Ring) over Rational Field

```

Since the construction

```

sage: GP_ZZ(QQ).construction()
(GPoly[X^(Integer Ring)], Rational Field)

```

uses the coefficient ring, we have the usual coercion with respect to this parameter:

```

sage: pushout(GP_ZZ(ZZ), GP_ZZ(QQ))
Generalized Polynomial Ring in X^(Integer Ring) over Rational Field
sage: pushout(GP_ZZ(ZZ['t']), GP_ZZ(QQ))
Generalized Polynomial Ring in X^(Integer Ring) over Univariate Polynomial Ring in t
↪ t over Rational Field
sage: pushout(GP_ZZ(ZZ['a,b']), GP_ZZ(ZZ['b,c']))
Generalized Polynomial Ring in X^(Integer Ring)
over Multivariate Polynomial Ring in a, b, c over Integer Ring
sage: pushout(GP_ZZ(ZZ['a,b']), GP_ZZ(QQ['b,c']))
Generalized Polynomial Ring in X^(Integer Ring)
over Multivariate Polynomial Ring in a, b, c over Rational Field
sage: pushout(GP_ZZ(ZZ['a,b']), GP_ZZ(ZZ['c,d']))
Traceback (most recent call last):
...
CoercionException: ('Ambiguous Base Extension', ...)

```

```

sage: GP_QQ = GPolynomialFunctor('X', QQ)
sage: pushout(GP_ZZ(ZZ), GP_QQ(ZZ))
Generalized Polynomial Ring in X^(Rational Field) over Integer Ring
sage: pushout(GP_QQ(ZZ), GP_ZZ(ZZ))
Generalized Polynomial Ring in X^(Rational Field) over Integer Ring

```

```

sage: GP_ZZt = GPolynomialFunctor('X', ZZ['t'])
sage: pushout(GP_ZZt(ZZ), GP_QQ(ZZ))
Generalized Polynomial Ring in X^(Univariate Polynomial Ring in t
over Rational Field) over Integer Ring

```

```

sage: pushout(GP_ZZ(ZZ), GP_QQ(QQ))
Generalized Polynomial Ring in X^(Rational Field) over Rational Field
sage: pushout(GP_ZZ(QQ), GP_QQ(ZZ))
Generalized Polynomial Ring in X^(Rational Field) over Rational Field
sage: pushout(GP_ZZt(QQ), GP_QQ(ZZ))
Generalized Polynomial Ring in X^(Univariate Polynomial Ring in t
over Rational Field) over Rational Field
sage: pushout(GP_ZZt(ZZ), GP_QQ(QQ))
Generalized Polynomial Ring in X^(Univariate Polynomial Ring in t
over Rational Field) over Rational Field
sage: pushout(GP_ZZt(ZZ['a,b']), GP_QQ(ZZ['c,d']))

```

(continues on next page)

(continued from previous page)

```

Traceback (most recent call last):
...
CoercionException: ('Ambiguous Base Extension', ...)
sage: pushout(GP_ZZt(ZZ['a,b']), GP_QQ(ZZ['b,c']))
Generalized Polynomial Ring in X^(Univariate Polynomial Ring in t over Rational
↪Field)
over Multivariate Polynomial Ring in a, b, c over Integer Ring

```

Some tests with Cartesian products:

```

sage: from sage.sets.cartesian_product import CartesianProduct
sage: A = CartesianProduct((ZZ['x'], QQ['y'], QQ['z']), Sets().CartesianProducts())
sage: B = CartesianProduct((ZZ['x'], ZZ['y'], ZZ['t']['z']), Sets().
↪CartesianProducts())
sage: A.construction()
(The cartesian_product functorial construction,
(Univariate Polynomial Ring in x over Integer Ring,
Univariate Polynomial Ring in y over Rational Field,
Univariate Polynomial Ring in z over Rational Field))
sage: pushout(A, B)
The Cartesian product of
(Univariate Polynomial Ring in x over Integer Ring,
Univariate Polynomial Ring in y over Rational Field,
Univariate Polynomial Ring in z over Univariate Polynomial Ring in t over
↪Rational Field)
sage: pushout(ZZ, cartesian_product([ZZ, QQ]))
Traceback (most recent call last):
...
CoercionException: 'NoneType' object is not iterable

```

```

sage: from sage.categories.pushout import PolynomialFunctor
sage: from sage.sets.cartesian_product import CartesianProduct
sage: class CartesianProductPoly(CartesianProduct):
....:     def __init__(self, polynomial_rings):
....:         sort = sorted(polynomial_rings, key=lambda P: P.variable_name())
....:         super(CartesianProductPoly, self).__init__(sort, Sets().
↪CartesianProducts())
....:     def vars(self):
....:         return tuple(P.variable_name() for P in self.cartesian_factors())
....:     def _pushout_(self, other):
....:         if isinstance(other, CartesianProductPoly):
....:             s_vars = self.vars()
....:             o_vars = other.vars()
....:             if s_vars == o_vars:
....:                 return
....:             return pushout(CartesianProductPoly(
....:                 self.cartesian_factors() +
....:                 tuple(f for f in other.cartesian_factors()
....:                     if f.variable_name() not in s_vars)),
....:                 CartesianProductPoly(
....:                     other.cartesian_factors() +
....:                     tuple(f for f in self.cartesian_factors()

```

(continues on next page)

(continued from previous page)

```

.....:             if f.variable_name() not in o_vars)))
.....:         C = other.construction()
.....:         if C is None:
.....:             return
.....:         elif isinstance(C[0], PolynomialFunctor):
.....:             return pushout(self, CartesianProductPoly((other,)))

```

```

sage: pushout(CartesianProductPoly((ZZ['x'],)),
.....:         CartesianProductPoly((ZZ['y'],)))
The Cartesian product of
(Univariate Polynomial Ring in x over Integer Ring,
 Univariate Polynomial Ring in y over Integer Ring)
sage: pushout(CartesianProductPoly((ZZ['x'], ZZ['y'])),
.....:         CartesianProductPoly((ZZ['x'], ZZ['z'])))
The Cartesian product of
(Univariate Polynomial Ring in x over Integer Ring,
 Univariate Polynomial Ring in y over Integer Ring,
 Univariate Polynomial Ring in z over Integer Ring)
sage: pushout(CartesianProductPoly((QQ['a,b']['x'], QQ['y'])),
.....:         CartesianProductPoly((ZZ['b,c']['x'], SR['z'])))
The Cartesian product of
(Univariate Polynomial Ring in x over
 Multivariate Polynomial Ring in a, b, c over Rational Field,
 Univariate Polynomial Ring in y over Rational Field,
 Univariate Polynomial Ring in z over Symbolic Ring)

```

```

sage: pushout(CartesianProductPoly((ZZ['x'],)), ZZ['y'])
The Cartesian product of
(Univariate Polynomial Ring in x over Integer Ring,
 Univariate Polynomial Ring in y over Integer Ring)
sage: pushout(QQ['b,c']['y'], CartesianProductPoly((ZZ['a,b']['x'],)))
The Cartesian product of
(Univariate Polynomial Ring in x over
 Multivariate Polynomial Ring in a, b over Integer Ring,
 Univariate Polynomial Ring in y over
 Multivariate Polynomial Ring in b, c over Rational Field)

```

```

sage: pushout(CartesianProductPoly((ZZ['x'],)), ZZ)
Traceback (most recent call last):
...
CoercionException: No common base ("join") found for
The cartesian_product functorial construction(...) and None(Integer Ring):
(Multivariate) functors are incompatible.

```

AUTHORS:

- Robert Bradshaw
- Peter Bruin
- Simon King
- Daniel Krenn

- David Roe

`sage.categories.pushout.pushout_lattice(R, S)`

Given a pair of objects R and S , try to construct a reasonable object Y and return maps such that canonically $R \leftarrow Y \rightarrow S$.

ALGORITHM:

This is based on the model that arose from much discussion at Sage Days 4. Going up the tower of constructions of R and S (e.g. the reals come from the rationals come from the integers), try to find a common parent, and then try to fill in a lattice with these two towers as sides with the top as the common ancestor and the bottom will be the desired ring.

See the code for a specific worked-out example.

EXAMPLES:

```
sage: from sage.categories.pushout import pushout_lattice
sage: A, B = pushout_lattice(Qp(7), Frac(ZZ['x']))
sage: A.codomain()
Fraction Field of Univariate Polynomial Ring in x over 7-adic Field with capped_
↪relative precision 20
sage: A.codomain() is B.codomain()
True
sage: A, B = pushout_lattice(ZZ, MatrixSpace(ZZ[['x']], 3, 3))
sage: B
Identity endomorphism of Full MatrixSpace of 3 by 3 dense matrices over Power_
↪Series Ring in x over Integer Ring
```

AUTHOR:

- Robert Bradshaw

`sage.categories.pushout.type_to_parent(P)`

An auxiliary function that is used in `pushout()`.

INPUT:

A type

OUTPUT:

A Sage parent structure corresponding to the given type

INDIVIDUAL CATEGORIES

3.1 Group, ring, etc. actions on objects

The terminology and notation used is suggestive of groups acting on sets, but this framework can be used for modules, algebras, etc.

A group action $G \times S \rightarrow S$ is a functor from G to Sets.

Warning: An *Action* object only keeps a weak reference to the underlying set which is acted upon. This decision was made in [trac ticket #715](#) in order to allow garbage collection within the coercion framework (this is where actions are mainly used) and avoid memory leaks.

```
sage: from sage.categories.action import Action
sage: class P: pass
sage: A = Action(P(),P())
sage: import gc
sage: _ = gc.collect()
sage: A
<repr(<sage.categories.action.Action at 0x...>) failed: RuntimeError: This action_
↳acted on a set that became garbage collected>
```

To avoid garbage collection of the underlying set, it is sufficient to create a strong reference to it before the action is created.

```
sage: _ = gc.collect()
sage: from sage.categories.action import Action
sage: class P: pass
sage: q = P()
sage: A = Action(P(),q)
sage: gc.collect()
0
sage: A
Left action by <__main__.P ... at ...> on <__main__.P ... at ...>
```

AUTHOR:

- Robert Bradshaw: initial version

```
class sage.categories.action.Action
    Bases: sage.categories.functor.Functor
    The action of G on S.
```

INPUT:

- G – a parent or Python type
- S – a parent or Python type
- `is_left` – (boolean, default: `True`) whether elements of G are on the left
- `op` – (default: `None`) operation. This is not used by *Action* itself, but other classes may use it

G

`act(g, x)`

This is a consistent interface for acting on x by g , regardless of whether it's a left or right action.

If needed, g and x are converted to the correct parent.

EXAMPLES:

```
sage: R.<x> = ZZ []
sage: from sage.structure.coerce_actions import IntegerMulAction
sage: A = IntegerMulAction(ZZ, R, True) # Left action
sage: A.act(5, x)
5*x
sage: A.act(int(5), x)
5*x
sage: A = IntegerMulAction(ZZ, R, False) # Right action
sage: A.act(5, x)
5*x
sage: A.act(int(5), x)
5*x
```

`actor()`

`codomain()`

`domain()`

`is_left()`

`left_domain()`

`op`

`operation()`

`right_domain()`

class `sage.categories.action.ActionEndomorphism`

Bases: `sage.categories.morphism.Morphism`

The endomorphism defined by the action of one element.

EXAMPLES:

```
sage: A = ZZ['x'].get_action(QQ, self_on_left=False, op=operator.mul)
sage: A
Left scalar multiplication by Rational Field on Univariate Polynomial
Ring in x over Integer Ring
sage: A(1/2)
Action of 1/2 on Univariate Polynomial Ring in x over Integer Ring
under Left scalar multiplication by Rational Field on Univariate
Polynomial Ring in x over Integer Ring.
```

class `sage.categories.action.InverseAction`Bases: `sage.categories.action.Action`

An action that acts as the inverse of the given action.

EXAMPLES:

```

sage: V = QQ^3
sage: v = V((1, 2, 3))
sage: cm = get_coercion_model()

sage: a = cm.get_action(V, QQ, operator.mul)
sage: a
Right scalar multiplication by Rational Field on Vector space of dimension 3 over
↳Rational Field
sage: ~a
Right inverse action by Rational Field on Vector space of dimension 3 over Rational
↳Field
sage: (~a)(v, 1/3)
(3, 6, 9)

sage: b = cm.get_action(QQ, V, operator.mul)
sage: b
Left scalar multiplication by Rational Field on Vector space of dimension 3 over
↳Rational Field
sage: ~b
Left inverse action by Rational Field on Vector space of dimension 3 over Rational
↳Field
sage: (~b)(1/3, v)
(3, 6, 9)

sage: c = cm.get_action(ZZ, list, operator.mul)
sage: c
Left action by Integer Ring on <... 'list'>
sage: ~c
Traceback (most recent call last):
...
TypeError: no inverse defined for Left action by Integer Ring on <... 'list'>

```

`codomain()`**class** `sage.categories.action.PrecomposedAction`Bases: `sage.categories.action.Action`

A precomposed action first applies given maps, and then applying an action to the return values of the maps.

EXAMPLES:

We demonstrate that an example discussed on [trac ticket #14711](#) did not become a problem:

```

sage: E = ModularSymbols(11).2
sage: s = E.modular_symbol_rep()
sage: del E, s
sage: import gc
sage: _ = gc.collect()
sage: E = ModularSymbols(11).2
sage: v = E.manin_symbol_rep()

```

(continues on next page)

(continued from previous page)

```

sage: c,x = v[0]
sage: y = x.modular_symbol_rep()
sage: coercion_model.get_action(QQ, parent(y), op=operator.mul)
Left scalar multiplication by Rational Field on Abelian Group of all Formal Finite_
↔Sums over Rational Field
with precomposition on right by Coercion map:
  From: Abelian Group of all Formal Finite Sums over Integer Ring
  To:   Abelian Group of all Formal Finite Sums over Rational Field

```

codomain()**domain()****left_precomposition**

The left map to precompose with, or None if there is no left precomposition map.

right_precomposition

The right map to precompose with, or None if there is no right precomposition map.

3.2 Additive groups

class `sage.categories.additive_groups.AdditiveGroups`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of additive groups.

An *additive group* is a set with an internal binary operation $+$ which is associative, admits a zero, and where every element can be negated.

EXAMPLES:

```

sage: from sage.categories.additive_groups import AdditiveGroups
sage: from sage.categories.additive_monoids import AdditiveMonoids
sage: AdditiveGroups()
Category of additive groups
sage: AdditiveGroups().super_categories()
[Category of additive inverse additive unital additive magmas,
 Category of additive monoids]
sage: AdditiveGroups().all_super_categories()
[Category of additive groups,
 Category of additive inverse additive unital additive magmas,
 Category of additive monoids,
 Category of additive unital additive magmas,
 Category of additive semigroups,
 Category of additive magmas,
 Category of sets,
 Category of sets with partial maps,
 Category of objects]

sage: AdditiveGroups().axioms()
frozenset({'AdditiveAssociative', 'AdditiveInverse', 'AdditiveUnital'})
sage: AdditiveGroups() is AdditiveMonoids().AdditiveInverse()
True

```

AdditiveCommutativealias of `sage.categories.commutative_additive_groups.CommutativeAdditiveGroups`**class Algebras**(*category*, *args)Bases: `sage.categories.algebra_functor.AlgebrasCategory`**class ParentMethods**

Bases: object

group()

Return the underlying group of the group algebra.

EXAMPLES:

```

sage: GroupAlgebras(QQ).example(GL(3, GF(11))).group()
General Linear Group of degree 3 over Finite Field of size 11
sage: SymmetricGroup(10).algebra(QQ).group()
Symmetric group of order 10! as a permutation group

```

class Finite(*base_category*)Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`**class Algebras**(*category*, *args)Bases: `sage.categories.algebra_functor.AlgebrasCategory`**class ParentMethods**

Bases: object

extra_super_categories()

Implement Maschke's theorem.

In characteristic 0 all finite group algebras are semisimple.

EXAMPLES:

```

sage: FiniteGroups().Algebras(QQ).is_subcategory(Algebras(QQ).
↳Semisimple())
True
sage: FiniteGroups().Algebras(FiniteField(7)).is_
↳subcategory(Algebras(FiniteField(7)).Semisimple())
False
sage: FiniteGroups().Algebras(ZZ).is_subcategory(Algebras(ZZ).
↳Semisimple())
False
sage: FiniteGroups().Algebras(Fields()).is_
↳subcategory(Algebras(Fields()).Semisimple())
False

sage: Cat = CommutativeAdditiveGroups().Finite()
sage: Cat.Algebras(QQ).is_subcategory(Algebras(QQ).Semisimple())
True
sage: Cat.Algebras(GF(7)).is_subcategory(Algebras(GF(7)).Semisimple())
False
sage: Cat.Algebras(ZZ).is_subcategory(Algebras(ZZ).Semisimple())
False
sage: Cat.Algebras(Fields()).is_subcategory(Algebras(Fields()).
↳Semisimple())
False

```

3.3 Additive magmas

class `sage.categories.additive_magmas.AdditiveMagmas(s=None)`
 Bases: `sage.categories.category_singleton.Category_singleton`

The category of additive magmas.

An additive magma is a set endowed with a binary operation $+$.

EXAMPLES:

```
sage: AdditiveMagmas()
Category of additive magmas
sage: AdditiveMagmas().super_categories()
[Category of sets]
sage: AdditiveMagmas().all_super_categories()
[Category of additive magmas, Category of sets, Category of sets with partial maps, ↪
↪Category of objects]
```

The following axioms are defined by this category:

```
sage: AdditiveMagmas().AdditiveAssociative()
Category of additive semigroups
sage: AdditiveMagmas().AdditiveUnital()
Category of additive unital additive magmas
sage: AdditiveMagmas().AdditiveCommutative()
Category of additive commutative additive magmas
sage: AdditiveMagmas().AdditiveUnital().AdditiveInverse()
Category of additive inverse additive unital additive magmas
sage: AdditiveMagmas().AdditiveAssociative().AdditiveCommutative()
Category of commutative additive semigroups
sage: AdditiveMagmas().AdditiveAssociative().AdditiveCommutative().AdditiveUnital()
Category of commutative additive monoids
sage: AdditiveMagmas().AdditiveAssociative().AdditiveCommutative().AdditiveUnital().
↪AdditiveInverse()
Category of commutative additive groups
```

AdditiveAssociative

alias of `sage.categories.additive_semigroups.AdditiveSemigroups`

class `AdditiveCommutative(base_category)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

class `Algebras(category, *args)`

Bases: `sage.categories.algebra_functor.AlgebrasCategory`

extra_super_categories()

Implement the fact that the algebra of a commutative additive magmas is commutative.

EXAMPLES:

```
sage: AdditiveMagmas().AdditiveCommutative().Algebras(QQ).extra_super_
↪categories()
[Category of commutative magmas]

sage: AdditiveMagmas().AdditiveCommutative().Algebras(QQ).super_
↪categories()
```

(continues on next page)

(continued from previous page)

```
[Category of additive magma algebras over Rational Field,
Category of commutative magmas]
```

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

extra_super_categories()

Implement the fact that a Cartesian product of commutative additive magmas is a commutative additive magma.

EXAMPLES:

```
sage: C = AdditiveMagmas().AdditiveCommutative().CartesianProducts()
sage: C.extra_super_categories()
[Category of additive commutative additive magmas]
sage: C.axioms()
frozenset({'AdditiveCommutative'})
```

class AdditiveUnital(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

class AdditiveInverse(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

class ElementMethods

Bases: object

extra_super_categories()

Implement the fact that a Cartesian product of additive magmas with inverses is an additive magma with inverse.

EXAMPLES:

```
sage: C = AdditiveMagmas().AdditiveUnital().AdditiveInverse().
->CartesianProducts()
sage: C.extra_super_categories()
[Category of additive inverse additive unital additive magmas]
sage: sorted(C.axioms())
['AdditiveInverse', 'AdditiveUnital']
```

class Algebras(*category, *args*)

Bases: *sage.categories.algebra_functor.AlgebrasCategory*

class ParentMethods

Bases: object

one_basis()

Return the zero of this additive magma, which index the one of this algebra, as per *AlgebrasWithBasis.ParentMethods.one_basis()*.

EXAMPLES:

```
sage: S = CommutativeAdditiveMonoids().example(); S
An example of a commutative monoid: the free commutative monoid,
->generated by ('a', 'b', 'c', 'd')
```

(continues on next page)

(continued from previous page)

```

sage: A = S.algebra(ZZ)
sage: A.one_basis()
0
sage: A.one()
B[0]
sage: A(3)
3*B[0]

```

extra_super_categories()

EXAMPLES:

```

sage: C = AdditiveMagmas().AdditiveUnital().Algebras(QQ)
sage: C.extra_super_categories()
[Category of unital magmas]

sage: C.super_categories()
[Category of unital algebras with basis over Rational Field, Category of
↪additive magma algebras over Rational Field]

```

class CartesianProducts(category, *args)Bases: *sage.categories.cartesian_product.CartesianProductsCategory***class ParentMethods**

Bases: object

zero()

Returns the zero of this group

EXAMPLES:

```

sage: GF(8, 'x').cartesian_product(GF(5)).zero()
(0, 0)

```

extra_super_categories()

Implement the fact that a Cartesian product of unital additive magmas is a unital additive magma.

EXAMPLES:

```

sage: C = AdditiveMagmas().AdditiveUnital().CartesianProducts()
sage: C.extra_super_categories()
[Category of additive unital additive magmas]
sage: C.axioms()
frozenset({'AdditiveUnital'})

```

class ElementMethods

Bases: object

class Homsets(category, *args)Bases: *sage.categories.homsets.HomsetsCategory***class ParentMethods**

Bases: object

zero()

EXAMPLES:

```

sage: R = QQ['x']
sage: H = Hom(ZZ, R, AdditiveMagmas().AdditiveUnital())
sage: f = H.zero()
sage: f
Generic morphism:
  From: Integer Ring
  To:  Univariate Polynomial Ring in x over Rational Field
sage: f(3)
0
sage: f(3) is R.zero()
True

```

extra_super_categories()

Implement the fact that a homset between two unital additive magmas is a unital additive magma.

EXAMPLES:

```

sage: AdditiveMagmas().AdditiveUnital().Homsets().extra_super_
↳categories()
[Category of additive unital additive magmas]
sage: AdditiveMagmas().AdditiveUnital().Homsets().super_categories()
[Category of additive unital additive magmas, Category of homsets]

```

class ParentMethods

Bases: object

is_empty()

Return whether this set is empty.

Since this set is an additive magma it has a zero element and hence is not empty. This method thus always returns False.

EXAMPLES:

```

sage: A = AdditiveAbelianGroup([3,3])
sage: A in AdditiveMagmas()
True
sage: A.is_empty()
False

sage: B = CommutativeAdditiveMonoids().example()
sage: B.is_empty()
False

```

zero()

Return the zero of this additive magma, that is the unique neutral element for +.

The default implementation is to coerce 0 into self.

It is recommended to override this method because the coercion from the integers:

- is not always meaningful (except for 0), and
- often uses self.zero() otherwise.

EXAMPLES:

```

sage: S = CommutativeAdditiveMonoids().example()
sage: S.zero()
0

```

class SubcategoryMethods

Bases: object

AdditiveInverse()

Return the full subcategory of the additive inverse objects of self.

An inverse *additive magma* is a unital additive magma such that every element admits both an additive inverse on the left and on the right. Such an additive magma is also called an *additive loop*.

See also:

[Wikipedia article Inverse_element](#), [Wikipedia article Quasigroup](#)

EXAMPLES:

```
sage: AdditiveMagmas().AdditiveUnital().AdditiveInverse()
Category of additive inverse additive unital additive magmas
sage: from sage.categories.additive_monoids import AdditiveMonoids
sage: AdditiveMonoids().AdditiveInverse()
Category of additive groups
```

class WithRealizations(category, *args)Bases: *sage.categories.with_realizations.WithRealizationsCategory***class ParentMethods**

Bases: object

zero()

Return the zero of this unital additive magma.

This default implementation returns the zero of the realization of self given by *a_realization()*.

EXAMPLES:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.zero.__module__
'sage.categories.additive_magmas'
sage: A.zero()
0
```

additional_structure()

Return whether self is a structure category.

See also:

Category.additional_structure()

The category of unital additive magmas defines the zero as additional structure, and this zero shall be preserved by morphisms.

EXAMPLES:

```
sage: AdditiveMagmas().AdditiveUnital().additional_structure()
Category of additive unital additive magmas
```

class Algebras(category, *args)Bases: *sage.categories.algebra_functor.AlgebrasCategory*

class ParentMethods

Bases: object

algebra_generators()

The generators of this algebra, as per *MagmaticAlgebras.ParentMethods.algebra_generators()*.

They correspond to the generators of the additive semigroup.

EXAMPLES:

```
sage: S = CommutativeAdditiveSemigroups().example(); S
An example of a commutative semigroup: the free commutative semigroup
↳ generated by ('a', 'b', 'c', 'd')
sage: A = S.algebra(QQ)
sage: A.algebra_generators()
Finite family {0: B[a], 1: B[b], 2: B[c], 3: B[d]}
```

Todo: This doctest does not actually test this method, but rather the method of the same name for *AdditiveSemigroups*. Find a better doctest!

product_on_basis(g1, g2)

Product, on basis elements, as per *MagmaticAlgebras.WithBasis.ParentMethods.product_on_basis()*.

The product of two basis elements is induced by the addition of the corresponding elements of the group.

EXAMPLES:

```
sage: S = CommutativeAdditiveSemigroups().example(); S
An example of a commutative semigroup: the free commutative semigroup
↳ generated by ('a', 'b', 'c', 'd')
sage: A = S.algebra(QQ)
sage: a,b,c,d = A.algebra_generators()
sage: a * d * b
B[a + b + d]
```

Todo: This doctest does not actually test this method, but rather the method of the same name for *AdditiveSemigroups*. Find a better doctest!

extra_super_categories()

EXAMPLES:

```
sage: AdditiveMagmas().Algebras(QQ).extra_super_categories()
[Category of magmatic algebras with basis over Rational Field]

sage: AdditiveMagmas().Algebras(QQ).super_categories()
[Category of magmatic algebras with basis over Rational Field, Category of
↳ set algebras over Rational Field]
```

class CartesianProducts(category, *args)Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

class ElementMethods

Bases: object

extra_super_categories()

Implement the fact that a Cartesian product of additive magmas is an additive magma.

EXAMPLES:

```
sage: C = AdditiveMagmas().CartesianProducts()
sage: C.extra_super_categories()
[Category of additive magmas]
sage: C.super_categories()
[Category of additive magmas, Category of Cartesian products of sets]
sage: C.axioms()
frozenset()
```

class ElementMethods

Bases: object

class Homsets(category, *args)Bases: *sage.categories.homsets.HomsetsCategory***extra_super_categories()**

Implement the fact that a homset between two magmas is a magma.

EXAMPLES:

```
sage: AdditiveMagmas().Homsets().extra_super_categories()
[Category of additive magmas]
sage: AdditiveMagmas().Homsets().super_categories()
[Category of additive magmas, Category of homsets]
```

class ParentMethods

Bases: object

addition_table(names='letters', elements=None)

Return a table describing the addition operation.

Note: The order of the elements in the row and column headings is equal to the order given by the table's `column_keys()` method. The association can also be retrieved with the `translation()` method.

INPUT:

- `names` – the type of names used:
 - 'letters' - lowercase ASCII letters are used for a base 26 representation of the elements' positions in the list given by `column_keys()`, padded to a common width with leading 'a's.
 - 'digits' - base 10 representation of the elements' positions in the list given by `column_keys()`, padded to a common width with leading zeros.
 - 'elements' - the string representations of the elements themselves.
 - a list - a list of strings, where the length of the list equals the number of elements.
- `elements` – (default: `None`) A list of elements of the additive magma, in forms that can be coerced into the structure, eg. their string representations. This may be used to impose an alternate ordering on the elements, perhaps when this is used in the context of a particular structure. The default is to use whatever ordering the `S.list` method returns. Or the `elements` can be a subset which is closed under the operation. In particular, this can be used when the base set is infinite.

OUTPUT:

The addition table as an object of the class `OperationTable` which defines several methods for manipulating and displaying the table. See the documentation there for full details to supplement the documentation here.

EXAMPLES:

All that is required is that an algebraic structure has an addition defined. The default is to represent elements as lowercase ASCII letters.

```
sage: R=IntegerModRing(5)
sage: R.addition_table()
+ a b c d e
+-----
a| a b c d e
b| b c d e a
c| c d e a b
d| d e a b c
e| e a b c d
```

The `names` argument allows displaying the elements in different ways. Requesting `elements` will use the representation of the elements of the set. Requesting `digits` will include leading zeros as padding.

```
sage: R=IntegerModRing(11)
sage: P=R.addition_table(names='elements')
sage: P
+ 0 1 2 3 4 5 6 7 8 9 10
+-----
0| 0 1 2 3 4 5 6 7 8 9 10
1| 1 2 3 4 5 6 7 8 9 10 0
2| 2 3 4 5 6 7 8 9 10 0 1
3| 3 4 5 6 7 8 9 10 0 1 2
4| 4 5 6 7 8 9 10 0 1 2 3
5| 5 6 7 8 9 10 0 1 2 3 4
6| 6 7 8 9 10 0 1 2 3 4 5
7| 7 8 9 10 0 1 2 3 4 5 6
8| 8 9 10 0 1 2 3 4 5 6 7
9| 9 10 0 1 2 3 4 5 6 7 8
10| 10 0 1 2 3 4 5 6 7 8 9

sage: T=R.addition_table(names='digits')
sage: T
+ 00 01 02 03 04 05 06 07 08 09 10
+-----
00| 00 01 02 03 04 05 06 07 08 09 10
01| 01 02 03 04 05 06 07 08 09 10 00
02| 02 03 04 05 06 07 08 09 10 00 01
03| 03 04 05 06 07 08 09 10 00 01 02
04| 04 05 06 07 08 09 10 00 01 02 03
05| 05 06 07 08 09 10 00 01 02 03 04
06| 06 07 08 09 10 00 01 02 03 04 05
07| 07 08 09 10 00 01 02 03 04 05 06
08| 08 09 10 00 01 02 03 04 05 06 07
09| 09 10 00 01 02 03 04 05 06 07 08
10| 10 00 01 02 03 04 05 06 07 08 09
```

Specifying the elements in an alternative order can provide more insight into how the operation behaves.

```
sage: S=IntegerModRing(7)
sage: elts = [0, 3, 6, 2, 5, 1, 4]
sage: S.addition_table(elements=elts)
+  a b c d e f g
  +-----+
a| a b c d e f g
b| b c d e f g a
c| c d e f g a b
d| d e f g a b c
e| e f g a b c d
f| f g a b c d e
g| g a b c d e f
```

The `elements` argument can be used to provide a subset of the elements of the structure. The subset must be closed under the operation. Elements need only be in a form that can be coerced into the set. The `names` argument can also be used to request that the elements be represented with their usual string representation.

```
sage: T=IntegerModRing(12)
sage: elts=[0, 3, 6, 9]
sage: T.addition_table(names='elements', elements=elts)
+  0 3 6 9
  +-----+
0| 0 3 6 9
3| 3 6 9 0
6| 6 9 0 3
9| 9 0 3 6
```

The table returned can be manipulated in various ways. See the documentation for `OperationTable` for more comprehensive documentation.

```
sage: R=IntegerModRing(3)
sage: T=R.addition_table()
sage: T.column_keys()
(0, 1, 2)
sage: sorted(T.translation().items())
[('a', 0), ('b', 1), ('c', 2)]
sage: T.change_names(['x', 'y', 'z'])
sage: sorted(T.translation().items())
[('x', 0), ('y', 1), ('z', 2)]
sage: T
+  x y z
  +-----+
x| x y z
y| y z x
z| z x y
```

summation(x, y)

Return the sum of x and y .

The binary addition operator of this additive magma.

INPUT:

- x, y – elements of this additive magma

EXAMPLES:

```
sage: S = CommutativeAdditiveSemigroups().example()
sage: (a,b,c,d) = S.additive_semigroup_generators()
sage: S.summation(a, b)
a + b
```

A parent in `AdditiveMagmas()` must either implement `summation()` in the parent class or `_add_` in the element class. By default, the addition method on elements `x._add_(y)` calls `S.summation(x, y)`, and reciprocally.

As a bonus effect, `S.summation` by itself models the binary function from `S` to `S`:

```
sage: bin = S.summation
sage: bin(a,b)
a + b
```

Here, `S.summation` is just a bound method. Whenever possible, it is recommended to enrich `S.summation` with extra mathematical structure. Lazy attributes can come handy for this.

Todo: Add an example.

`summation_from_element_class_add(x, y)`

Return the sum of x and y .

The binary addition operator of this additive magma.

INPUT:

- x, y – elements of this additive magma

EXAMPLES:

```
sage: S = CommutativeAdditiveSemigroups().example()
sage: (a,b,c,d) = S.additive_semigroup_generators()
sage: S.summation(a, b)
a + b
```

A parent in `AdditiveMagmas()` must either implement `summation()` in the parent class or `_add_` in the element class. By default, the addition method on elements `x._add_(y)` calls `S.summation(x, y)`, and reciprocally.

As a bonus effect, `S.summation` by itself models the binary function from `S` to `S`:

```
sage: bin = S.summation
sage: bin(a,b)
a + b
```

Here, `S.summation` is just a bound method. Whenever possible, it is recommended to enrich `S.summation` with extra mathematical structure. Lazy attributes can come handy for this.

Todo: Add an example.

class `SubcategoryMethods`

Bases: `object`

AdditiveAssociative()

Return the full subcategory of the additive associative objects of `self`.

An *additive magma* M is *associative* if, for all $x, y, z \in M$,

$$x + (y + z) = (x + y) + z$$

See also:

[Wikipedia article Associative_property](#)

EXAMPLES:

```
sage: AdditiveMagmas().AdditiveAssociative()
Category of additive semigroups
```

AdditiveCommutative()

Return the full subcategory of the commutative objects of `self`.

An *additive magma* M is *commutative* if, for all $x, y \in M$,

$$x + y = y + x$$

See also:

[Wikipedia article Commutative_property](#)

EXAMPLES:

```
sage: AdditiveMagmas().AdditiveCommutative()
Category of additive commutative additive magmas
sage: AdditiveMagmas().AdditiveAssociative().AdditiveUnital().
↪AdditiveCommutative()
Category of commutative additive monoids
sage: _ is CommutativeAdditiveMonoids()
True
```

AdditiveUnital()

Return the subcategory of the unital objects of `self`.

An *additive magma* M is *unital* if it admits an element 0 , called *neutral element*, such that for all $x \in M$,

$$0 + x = x + 0 = x$$

This element is necessarily unique, and should be provided as `M.zero()`.

See also:

[Wikipedia article Unital_magma#unital](#)

EXAMPLES:

```
sage: AdditiveMagmas().AdditiveUnital()
Category of additive unital additive magmas
sage: from sage.categories.additive_semigroups import AdditiveSemigroups
sage: AdditiveSemigroups().AdditiveUnital()
Category of additive monoids
sage: CommutativeAdditiveMonoids().AdditiveUnital()
Category of commutative additive monoids
```

super_categories()

EXAMPLES:

```
sage: AdditiveMagmas().super_categories()
[Category of sets]
```

3.4 Additive monoids

class `sage.categories.additive_monoids.AdditiveMonoids`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of additive monoids.

An *additive monoid* is a unital *additive semigroup*, that is a set endowed with a binary operation $+$ which is associative and admits a zero (see [Wikipedia article Monoid](#)).

EXAMPLES:

```
sage: from sage.categories.additive_monoids import AdditiveMonoids
sage: C = AdditiveMonoids(); C
Category of additive monoids
sage: C.super_categories()
[Category of additive unital additive magmas, Category of additive semigroups]
sage: sorted(C.axioms())
['AdditiveAssociative', 'AdditiveUnital']
sage: from sage.categories.additive_semigroups import AdditiveSemigroups
sage: C is AdditiveSemigroups().AdditiveUnital()
True
```

AdditiveCommutative

alias of `sage.categories.commutative_additive_monoids.CommutativeAdditiveMonoids`

AdditiveInverse

alias of `sage.categories.additive_groups.AdditiveGroups`

class `Homsets`(*category*, **args*)

Bases: `sage.categories.homsets.HomsetsCategory`

extra_super_categories()

Implement the fact that a homset between two monoids is associative.

EXAMPLES:

```
sage: from sage.categories.additive_monoids import AdditiveMonoids
sage: AdditiveMonoids().Homsets().extra_super_categories()
[Category of additive semigroups]
sage: AdditiveMonoids().Homsets().super_categories()
[Category of homsets of additive unital additive magmas, Category of
↪ additive monoids]
```

Todo: This could be deduced from `AdditiveSemigroups.Homsets.extra_super_categories()`. See comment in `Objects.SubcategoryMethods.Homsets()`.

class ParentMethods

Bases: object

sum(args)

Return the sum of the elements in args, as an element of self.

INPUT:

- args – a list (or iterable) of elements of self

EXAMPLES:

```
sage: S = CommutativeAdditiveMonoids().example()
sage: (a,b,c,d) = S.additive_semigroup_generators()
sage: S.sum((a,b,a,c,a,b))
3*a + 2*b + c
sage: S.sum(())
0
sage: S.sum().parent() == S
True
```

3.5 Additive semigroups

class sage.categories.additive_semigroups.**AdditiveSemigroups**(base_category)Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

The category of additive semigroups.

An *additive semigroup* is an associative *additive magma*, that is a set endowed with an operation $+$ which is associative.

EXAMPLES:

```
sage: from sage.categories.additive_semigroups import AdditiveSemigroups
sage: C = AdditiveSemigroups(); C
Category of additive semigroups
sage: C.super_categories()
[Category of additive magmas]
sage: C.all_super_categories()
[Category of additive semigroups,
Category of additive magmas,
Category of sets,
Category of sets with partial maps,
Category of objects]

sage: C.axioms()
frozenset({'AdditiveAssociative'})
sage: C is AdditiveMagmas().AdditiveAssociative()
True
```

AdditiveCommutativealias of *sage.categories.commutative_additive_semigroups.CommutativeAdditiveSemigroups***AdditiveUnital**alias of *sage.categories.additive_monoids.AdditiveMonoids*

class Algebras(category, *args)

Bases: *sage.categories.algebra_functor.AlgebrasCategory*

class ParentMethods

Bases: object

algebra_generators()

Return the generators of this algebra, as per *MagmaticAlgebras.ParentMethods.algebra_generators()*.

They correspond to the generators of the additive semigroup.

EXAMPLES:

```
sage: S = CommutativeAdditiveSemigroups().example(); S
An example of a commutative semigroup: the free commutative semigroup
↳ generated by ('a', 'b', 'c', 'd')
sage: A = S.algebra(QQ)
sage: A.algebra_generators()
Finite family {0: B[a], 1: B[b], 2: B[c], 3: B[d]}
```

product_on_basis(g1, g2)

Product, on basis elements, as per *MagmaticAlgebras.WithBasis.ParentMethods.product_on_basis()*.

The product of two basis elements is induced by the addition of the corresponding elements of the group.

EXAMPLES:

```
sage: S = CommutativeAdditiveSemigroups().example(); S
An example of a commutative semigroup: the free commutative semigroup
↳ generated by ('a', 'b', 'c', 'd')
sage: A = S.algebra(QQ)
sage: a,b,c,d = A.algebra_generators()
sage: b * d * c
B[b + c + d]
```

extra_super_categories()

EXAMPLES:

```
sage: from sage.categories.additive_semigroups import AdditiveSemigroups
sage: AdditiveSemigroups().Algebras(QQ).extra_super_categories()
[Category of semigroups]
sage: CommutativeAdditiveSemigroups().Algebras(QQ).super_categories()
[Category of additive semigroup algebras over Rational Field,
Category of additive commutative additive magma algebras over Rational
↳Field]
```

class CartesianProducts(category, *args)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

extra_super_categories()

Implement the fact that a Cartesian product of additive semigroups is an additive semigroup.

EXAMPLES:

```
sage: from sage.categories.additive_semigroups import AdditiveSemigroups
sage: C = AdditiveSemigroups().CartesianProducts()
sage: C.extra_super_categories()
[Category of additive semigroups]
sage: C.axioms()
frozenset({'AdditiveAssociative'})
```

class Homsets(*category, *args*)

Bases: *sage.categories.homsets.HomsetsCategory*

extra_super_categories()

Implement the fact that a homset between two semigroups is a semigroup.

EXAMPLES:

```
sage: from sage.categories.additive_semigroups import AdditiveSemigroups
sage: AdditiveSemigroups().Homsets().extra_super_categories()
[Category of additive semigroups]
sage: AdditiveSemigroups().Homsets().super_categories()
[Category of homsets of additive magmas, Category of additive semigroups]
```

class ParentMethods

Bases: object

3.6 Affine Weyl groups

class *sage.categories.affine_weyl_groups.AffineWeylGroups*(*s=None*)

Bases: *sage.categories.category_singleton.Category_singleton*

The category of affine Weyl groups

Todo: add a description of this category

See also:

- [Wikipedia article Affine_weyl_group](#)
- *WeylGroups*, *WeylGroup*

EXAMPLES:

```
sage: C = AffineWeylGroups(); C
Category of affine weyl groups
sage: C.super_categories()
[Category of infinite weyl groups]

sage: C.example()
NotImplemented
sage: W = WeylGroup(["A", 4, 1]); W
Weyl Group of type ['A', 4, 1] (as a matrix group acting on the root space)
sage: W.category()
Category of irreducible affine weyl groups
```

class ElementMethods

Bases: object

affine_grassmannian_to_core()Bijection between affine Grassmannian elements of type $A_k^{(1)}$ and $(k + 1)$ -cores.

INPUT:

- `self` – an affine Grassmannian element of some affine Weyl group of type $A_k^{(1)}$

Recall that an element w of an affine Weyl group is affine Grassmannian if all its all reduced words end in 0, see `is_affine_grassmannian()`.

OUTPUT:

- a $(k + 1)$ -core

See also:[`affine_grassmannian_to_partition\(\)`](#)

EXAMPLES:

```
sage: W = WeylGroup(['A', 2, 1])
sage: w = W.from_reduced_word([0, 2, 1, 0])
sage: la = w.affine_grassmannian_to_core(); la
[4, 2]
sage: type(la)
<class 'sage.combinat.core.Cores_length_with_category.element_class'>
sage: la.to_grassmannian() == w
True

sage: w = W.from_reduced_word([0, 2, 1])
sage: w.affine_grassmannian_to_core()
Traceback (most recent call last):
...
ValueError: this only works on type 'A' affine Grassmannian elements
```

affine_grassmannian_to_partition()Bijection between affine Grassmannian elements of type $A_k^{(1)}$ and k -bounded partitions.

INPUT:

- `self` is affine Grassmannian element of the affine Weyl group of type $A_k^{(1)}$ (i.e. all reduced words end in 0)

OUTPUT:

- k -bounded partition

See also:[`affine_grassmannian_to_core\(\)`](#)

EXAMPLES:

```
sage: k = 2
sage: W = WeylGroup(['A', k, 1])
sage: w = W.from_reduced_word([0, 2, 1, 0])
sage: la = w.affine_grassmannian_to_partition(); la
[2, 2]
sage: la.from_kbounded_to_grassmannian(k) == w
True
```

is_affine_grassmannian()Test whether `self` is affine Grassmannian.

An element of an affine Weyl group is *affine Grassmannian* if any of the following equivalent properties holds:

- all reduced words for `self` end with 0.
- `self` is the identity, or 0 is its single right descent.
- `self` is a minimal coset representative for $W / c1 W$.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3, 1])
sage: w = W.from_reduced_word([2, 1, 0])
sage: w.is_affine_grassmannian()
True
sage: w = W.from_reduced_word([2, 0])
sage: w.is_affine_grassmannian()
False
sage: W.one().is_affine_grassmannian()
True
```

class ParentMethods

Bases: object

`affine_grassmannian_elements_of_given_length(k)`

Return the affine Grassmannian elements of length k .

This is returned as a finite enumerated set.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3, 1])
sage: [x.reduced_word() for x in W.affine_grassmannian_elements_of_given_
↪length(3)]
[[2, 1, 0], [3, 1, 0], [2, 3, 0]]
```

See also:

[*AffineWeylGroups.ElementMethods.is_affine_grassmannian\(\)*](#)

`special_node()`

Return the distinguished special node of the underlying Dynkin diagram.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3, 1])
sage: W.special_node()
0
```

`additional_structure()`

Return None.

Indeed, the category of affine Weyl groups defines no additional structure: affine Weyl groups are a special class of Weyl groups.

See also:

[*Category.additional_structure\(\)*](#)

Todo: Should this category be a `CategoryWithAxiom`?

EXAMPLES:


```
sage: AffineWeylGroups().additional_structure()
```

super_categories()

EXAMPLES:

```
sage: AffineWeylGroups().super_categories()
[Category of infinite weyl groups]
```

3.7 Algebra ideals

class sage.categories.algebra_ideals.**AlgebraIdeals**(A)

Bases: *sage.categories.category_types.Category_ideal*

The category of two-sided ideals in a fixed algebra *A*.

EXAMPLES:

```
sage: AlgebraIdeals(QQ['a'])
Category of algebra ideals in Univariate Polynomial Ring in a over Rational Field
```

Todo:

- Add support for non commutative rings (this is currently not supported by the subcategory *AlgebraModules*).
- Make `AlgebraIdeals(R)`, return `CommutativeAlgebraIdeals(R)` when *R* is commutative.
- If useful, implement `AlgebraLeftIdeals` and `AlgebraRightIdeals` of which `AlgebraIdeals` would be a subcategory.

algebra()

EXAMPLES:

```
sage: AlgebraIdeals(QQ['x']).algebra()
Univariate Polynomial Ring in x over Rational Field
```

super_categories()

The category of algebra modules should be a super category of this category.

However, since algebra modules are currently only available over commutative rings, we have to omit it if our ring is non-commutative.

EXAMPLES:

```
sage: AlgebraIdeals(QQ['x']).super_categories()
[Category of algebra modules over Univariate Polynomial Ring in x over Rational_
↪Field]
sage: C = AlgebraIdeals(FreeAlgebra(QQ, 2, 'a,b'))
sage: C.super_categories()
[]
```

3.8 Algebra modules

class `sage.categories.algebra_modules.AlgebraModules(A)`
 Bases: `sage.categories.category_types.Category_module`

The category of modules over a fixed algebra A .

EXAMPLES:

```
sage: AlgebraModules(QQ['a'])
Category of algebra modules over Univariate Polynomial Ring in a over Rational Field
sage: AlgebraModules(QQ['a']).super_categories()
[Category of modules over Univariate Polynomial Ring in a over Rational Field]
```

Note: as of now, A is required to be commutative, ensuring that the categories of left and right modules are isomorphic. Feedback and use cases for potential generalizations to the non commutative case are welcome.

algebra()

EXAMPLES:

```
sage: AlgebraModules(QQ['x']).algebra()
Univariate Polynomial Ring in x over Rational Field
```

classmethod `an_instance()`

Returns an instance of this class

EXAMPLES:

```
sage: AlgebraModules.an_instance()
Category of algebra modules over Univariate Polynomial Ring in x over Rational
↪Field
```

super_categories()

EXAMPLES:

```
sage: AlgebraModules(QQ['x']).super_categories()
[Category of modules over Univariate Polynomial Ring in x over Rational Field]
```

3.9 Algebras

AUTHORS:

- David Kohel & William Stein (2005): initial revision
- Nicolas M. Thiery (2008-2011): rewrote for the category framework

class `sage.categories.algebras.Algebras(base_category)`
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

The category of associative and unital algebras over a given base ring.

An associative and unital algebra over a ring R is a module over R which is itself a ring.

Warning: *Algebras* will be eventually be replaced by *magmatic_algebras.MagmaticAlgebras* for consistency with e.g. Wikipedia article [Algebras](#) which assumes neither associativity nor the existence of a unit (see [trac ticket #15043](#)).

Todo: Should R be a commutative ring?

EXAMPLES:

```
sage: Algebras(ZZ)
Category of algebras over Integer Ring
sage: sorted(Algebras(ZZ).super_categories(), key=str)
[Category of associative algebras over Integer Ring,
Category of rings,
Category of unital algebras over Integer Ring]
```

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

The category of algebras constructed as Cartesian products of algebras

This construction gives the direct product of algebras. See discussion on:

- http://groups.google.fr/group/sage-devel/browse_thread/thread/35a72b1d0a2fc77a/348f42ae77a66d16#348f42ae77a66d16
- Wikipedia article [Direct product](#)

extra_super_categories()

A Cartesian product of algebras is endowed with a natural algebra structure.

EXAMPLES:

```
sage: C = Algebras(QQ).CartesianProducts()
sage: C.extra_super_categories()
[Category of algebras over Rational Field]
sage: sorted(C.super_categories(), key=str)
[Category of Cartesian products of distributive magmas and additive magmas,
Category of Cartesian products of monoids,
Category of Cartesian products of vector spaces over Rational Field,
Category of algebras over Rational Field]
```

Commutative

alias of *sage.categories.commutative_algebras.CommutativeAlgebras*

class DualObjects(*category, *args*)

Bases: *sage.categories.dual.DualObjectsCategory*

extra_super_categories()

Return the dual category

EXAMPLES:

The category of algebras over the Rational Field is dual to the category of coalgebras over the same field:

```

sage: C = Algebras(QQ)
sage: C.dual()
Category of duals of algebras over Rational Field
sage: C.dual().extra_super_categories()
[Category of coalgebras over Rational Field]

```

Warning: This is only correct in certain cases (finite dimension, ...). See [trac ticket #15647](#).

class ElementMethods

Bases: object

Filtered

alias of *sage.categories.filtered_algebras.FilteredAlgebras*

Graded

alias of *sage.categories.graded_algebras.GradedAlgebras*

class Quotients(*category, *args*)

Bases: *sage.categories.quotients.QuotientsCategory*

class ParentMethods

Bases: object

algebra_generators()

Return algebra generators for *self*.

This implementation retracts the algebra generators from the ambient algebra.

EXAMPLES:

```

sage: A = FiniteDimensionalAlgebrasWithBasis(QQ).example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: S = A.semisimple_quotient()
sage: S.algebra_generators()
Finite family {'x': B['x'], 'y': B['y'], 'a': 0, 'b': 0}

```

Todo: this could possibly remove the elements that retract to zero.

Semisimple

alias of *sage.categories.semisimple_algebras.SemisimpleAlgebras*

class SubcategoryMethods

Bases: object

Semisimple()

Return the subcategory of semisimple objects of *self*.

Note: This mimics the syntax of axioms for a smooth transition if *Semisimple* becomes one.

EXAMPLES:

```

sage: Algebras(QQ).Semisimple()
Category of semisimple algebras over Rational Field
sage: Algebras(QQ).WithBasis().FiniteDimensional().Semisimple()
Category of finite dimensional semisimple algebras with basis over Rational
↪Field

```

Supercommutative()

Return the full subcategory of the supercommutative objects of self.

This is shorthand for creating the corresponding super category.

EXAMPLES:

```

sage: Algebras(ZZ).Supercommutative()
Category of supercommutative algebras over Integer Ring
sage: Algebras(ZZ).WithBasis().Supercommutative()
Category of supercommutative super algebras with basis over Integer Ring

sage: Cat = Algebras(ZZ).Supercommutative()
sage: Cat is Algebras(ZZ).Super().Supercommutative()
True

```

Super

alias of *sage.categories.super_algebras.SuperAlgebras*

class TensorProducts(category, *args)

Bases: *sage.categories.tensor.TensorProductsCategory*

class ElementMethods

Bases: object

class ParentMethods

Bases: object

extra_super_categories()

EXAMPLES:

```

sage: Algebras(QQ).TensorProducts().extra_super_categories()
[Category of algebras over Rational Field]
sage: Algebras(QQ).TensorProducts().super_categories()
[Category of algebras over Rational Field,
Category of tensor products of vector spaces over Rational Field]

```

Meaning: a tensor product of algebras is an algebra

WithBasis

alias of *sage.categories.algebras_with_basis.AlgebrasWithBasis*

3.10 Algebras With Basis

class `sage.categories.algebras_with_basis.AlgebrasWithBasis`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of algebras with a distinguished basis.

EXAMPLES:

```
sage: C = AlgebrasWithBasis(QQ); C
Category of algebras with basis over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of algebras over Rational Field,
 Category of unital algebras with basis over Rational Field]
```

We construct a typical parent in this category, and do some computations with it:

```
sage: A = C.example(); A
An example of an algebra with basis: the free algebra on the generators ('a', 'b',
↪ 'c') over Rational Field

sage: A.category()
Category of algebras with basis over Rational Field

sage: A.one_basis()
word:
sage: A.one()
B[word: ]

sage: A.base_ring()
Rational Field
sage: A.basis().keys()
Finite words over {'a', 'b', 'c'}

sage: (a,b,c) = A.algebra_generators()
sage: a^3, b^2
(B[word: aaa], B[word: bb])
sage: a*c*b
B[word: acb]

sage: A.product
<bound method FreeAlgebraWithCategory._product_from_product_on_basis_multiply of
An example of an algebra with basis: the free algebra on the generators ('a', 'b',
↪ 'c') over Rational Field>
sage: A.product(a*b,b)
B[word: abb]

sage: TestSuite(A).run(verbose=True)
running ._test_additive_associativity() . . . pass
running ._test_an_element() . . . pass
running ._test_associativity() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_characteristic() . . . pass
```

(continues on next page)

(continued from previous page)

```

running ._test_construction() . . . pass
running ._test_distributivity() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_nonzero_equal() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_one() . . . pass
running ._test_pickling() . . . pass
running ._test_prod() . . . pass
running ._test_some_elements() . . . pass
running ._test_zero() . . . pass
sage: A.__class__
<class 'sage.categories.examples.algebras_with_basis.FreeAlgebra_with_category'>
sage: A.element_class
<class 'sage.categories.examples.algebras_with_basis.FreeAlgebra_with_category.
↪element_class'>

```

Please see the source code of A (with $A??$) for how to implement other algebras with basis.

class CartesianProducts(*category*, *args)

Bases: [sage.categories.cartesian_product.CartesianProductsCategory](#)

The category of algebras with basis, constructed as Cartesian products of algebras with basis.

Note: this construction give the direct products of algebras with basis. See comment in [Algebras.CartesianProducts](#)

class ParentMethods

Bases: object

one()

one_from_cartesian_product_of_one_basis()

Returns the one of this Cartesian product of algebras, as per [Monoids.ParentMethods.one](#)

It is constructed as the Cartesian product of the ones of the summands, using their `one_basis()` methods.

This implementation does not require multiplication by scalars nor calling `cartesian_product`. This might help keeping things as lazy as possible upon initialization.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example(); A
```

```
An example of an algebra with basis: the free algebra on the generators (
↪ 'a', 'b', 'c') over Rational Field
```

(continues on next page)

(continued from previous page)

```

sage: A.one_basis()
word:

sage: B = cartesian_product((A, A, A))
sage: B.one_from_cartesian_product_of_one_basis()
B[(0, word: )] + B[(1, word: )] + B[(2, word: )]
sage: B.one()
B[(0, word: )] + B[(1, word: )] + B[(2, word: )]

sage: cartesian_product([SymmetricGroupAlgebra(QQ, 3),
↳SymmetricGroupAlgebra(QQ, 4)]).one()
B[(0, [1, 2, 3])] + B[(1, [1, 2, 3, 4])]

```

extra_super_categories()

A Cartesian product of algebras with basis is endowed with a natural algebra with basis structure.

EXAMPLES:

```

sage: AlgebrasWithBasis(QQ).CartesianProducts().extra_super_categories()
[Category of algebras with basis over Rational Field]
sage: AlgebrasWithBasis(QQ).CartesianProducts().super_categories()
[Category of algebras with basis over Rational Field,
Category of Cartesian products of algebras over Rational Field,
Category of Cartesian products of vector spaces with basis over Rational
↳Field]

```

class ElementMethods

Bases: object

Filtered

alias of *sage.categories.filtered_algebras_with_basis.FilteredAlgebrasWithBasis*

FiniteDimensional

alias of *sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis*

Graded

alias of *sage.categories.graded_algebras_with_basis.GradedAlgebrasWithBasis*

class ParentMethods

Bases: object

hochschild_complex(*M*)

Return the Hochschild complex of *self* with coefficients in *M*.

See also:

[HochschildComplex](#)

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: A = algebras.DifferentialWeyl(R)
sage: H = A.hochschild_complex(A)

sage: SGA = SymmetricGroupAlgebra(QQ, 3)

```

(continues on next page)

(continued from previous page)

```
sage: T = SGA.trivial_representation()
sage: H = SGA.hochschild_complex(T)
```

one()

Return the multiplicative unit element.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example()
sage: A.one_basis()
word:
sage: A.one()
B[word: ]
```

Superalias of `sage.categories.super_algebras_with_basis.SuperAlgebrasWithBasis`**class TensorProducts**(*category, *args*)Bases: `sage.categories.tensor.TensorProductsCategory`

The category of algebras with basis constructed by tensor product of algebras with basis

class ElementMethods

Bases: object

Implements operations on elements of tensor products of algebras with basis

class ParentMethods

Bases: object

implements operations on tensor products of algebras with basis

one_basis()Returns the index of the one of this tensor product of algebras, as per `AlgebrasWithBasis.ParentMethods.one_basis`It is the tuple whose operands are the indices of the ones of the operands, as returned by their `one_basis()` methods.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example(); A
An example of an algebra with basis: the free algebra on the generators (
↳ 'a', 'b', 'c') over Rational Field
sage: A.one_basis()
word:
sage: B = tensor((A, A, A))
sage: B.one_basis()
(word: , word: , word: )
sage: B.one()
B[word: ] # B[word: ] # B[word: ]
```

product_on_basis(*t1, t2*)The product of the algebra on the basis, as per `AlgebrasWithBasis.ParentMethods.product_on_basis`.

EXAMPLES:

```

sage: A = AlgebrasWithBasis(QQ).example(); A
An example of an algebra with basis: the free algebra on the generators (
↳ 'a', 'b', 'c') over Rational Field
sage: (a,b,c) = A.algebra_generators()

sage: x = tensor( (a, b, c) ); x
B[word: a] # B[word: b] # B[word: c]
sage: y = tensor( (c, b, a) ); y
B[word: c] # B[word: b] # B[word: a]
sage: x*y
B[word: ac] # B[word: bb] # B[word: ca]

sage: x = tensor( ((a+2*b), c) ) ; x
B[word: a] # B[word: c] + 2*B[word: b] # B[word: c]
sage: y = tensor( (c, a) ) + 1; y
B[word: ] # B[word: ] + B[word: c] # B[word: a]
sage: x*y
B[word: a] # B[word: c] + B[word: ac] # B[word: ca] + 2*B[word: b] #
↳ B[word: c] + 2*B[word: bc] # B[word: ca]

```

TODO: optimize this implementation!

extra_super_categories()

EXAMPLES:

```

sage: AlgebrasWithBasis(QQ).TensorProducts().extra_super_categories()
[Category of algebras with basis over Rational Field]
sage: AlgebrasWithBasis(QQ).TensorProducts().super_categories()
[Category of algebras with basis over Rational Field,
Category of tensor products of algebras over Rational Field,
Category of tensor products of vector spaces with basis over Rational
↳ Field]

```

example(alphabet=('a', 'b', 'c'))

Return an example of algebra with basis.

EXAMPLES:

```

sage: AlgebrasWithBasis(QQ).example()
An example of an algebra with basis: the free algebra on the generators ('a', 'b
↳ ', 'c') over Rational Field

```

An other set of generators can be specified as optional argument:

```

sage: AlgebrasWithBasis(QQ).example((1,2,3))
An example of an algebra with basis: the free algebra on the generators (1, 2,
↳ 3) over Rational Field

```

3.11 Aperiodic semigroups

class `sage.categories.aperiodic_semigroups.AperiodicSemigroups`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

extra_super_categories()

Implement the fact that an aperiodic semigroup is H -trivial.

EXAMPLES:

```
sage: Semigroups().Aperiodic().extra_super_categories()
[Category of h trivial semigroups]
```

3.12 Associative algebras

class `sage.categories.associative_algebras.AssociativeAlgebras`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

The category of associative algebras over a given base ring.

An associative algebra over a ring R is a module over R which is also a not necessarily unital ring.

Warning: Until [trac ticket #15043](#) is implemented, *Algebras* is the category of associative unital algebras; thus, unlike the name suggests, *AssociativeAlgebras* is not a subcategory of *Algebras* but of *MagmaticAlgebras*.

EXAMPLES:

```
sage: from sage.categories.associative_algebras import AssociativeAlgebras
sage: C = AssociativeAlgebras(ZZ); C
Category of associative algebras over Integer Ring
```

Unital

alias of `sage.categories.algebras.Algebras`

3.13 Bialgebras

class `sage.categories.bialgebras.Bialgebras`(*base*, *name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of bialgebras

EXAMPLES:

```
sage: Bialgebras(ZZ)
Category of bialgebras over Integer Ring
sage: Bialgebras(ZZ).super_categories()
[Category of algebras over Integer Ring, Category of coalgebras over Integer Ring]
```

class `ElementMethods`

Bases: `object`

is_grouplike()

Return whether `self` is a grouplike element.

EXAMPLES:

```
sage: s = SymmetricFunctions(QQ).schur()
sage: s([5]).is_grouplike()
False
sage: s([]).is_grouplike()
True
```

is_primitive()

Return whether `self` is a primitive element.

EXAMPLES:

```
sage: s = SymmetricFunctions(QQ).schur()
sage: s([5]).is_primitive()
False
sage: p = SymmetricFunctions(QQ).powersum()
sage: p([5]).is_primitive()
True
```

class Super(*base_category*)

Bases: *sage.categories.super_modules.SuperModulesCategory*

WithBasis

alias of *sage.categories.bialgebras_with_basis.BialgebrasWithBasis*

additional_structure()

Return None.

Indeed, the category of bialgebras defines no additional structure: a morphism of coalgebras and of algebras between two bialgebras is a bialgebra morphism.

See also:

Category.additional_structure()

Todo: This category should be a `CategoryWithAxiom`.

EXAMPLES:

```
sage: Bialgebras(QQ).additional_structure()
```

super_categories()

EXAMPLES:

```
sage: Bialgebras(QQ).super_categories()
[Category of algebras over Rational Field, Category of coalgebras over Rational_
↪Field]
```

3.14 Bialgebras with basis

class `sage.categories.bialgebras_with_basis.BialgebrasWithBasis`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of bialgebras with a distinguished basis.

EXAMPLES:

```
sage: C = BialgebrasWithBasis(QQ); C
Category of bialgebras with basis over Rational Field

sage: sorted(C.super_categories(), key=str)
[Category of algebras with basis over Rational Field,
Category of bialgebras over Rational Field,
Category of coalgebras with basis over Rational Field]
```

class `ElementMethods`

Bases: `object`

adams_operator(*n*)

Compute the *n*-th convolution power of the identity morphism `Id` on `self`.

INPUT:

- *n* – a nonnegative integer

OUTPUT:

- the image of `self` under the convolution power Id^{*n}

Note: In the literature, this is also called a Hopf power or Sweedler power, cf. [AL2015].

See also:

`sage.categories.bialgebras.ElementMethods.convolution_product()`

Todo: Remove dependency on `modules_with_basis` methods.

EXAMPLES:

```
sage: h = SymmetricFunctions(QQ).h()
sage: h[5].adams_operator(2)
2*h[3, 2] + 2*h[4, 1] + 2*h[5]
sage: h[5].plethysm(2*h[1])
2*h[3, 2] + 2*h[4, 1] + 2*h[5]
sage: h[[]].adams_operator(0)
h[]
sage: h[[]].adams_operator(1)
h[]
sage: h[3,2].adams_operator(0)
0
sage: h[3,2].adams_operator(1)
h[3, 2]
```

```

sage: S = NonCommutativeSymmetricFunctions(QQ).S()
sage: S[4].adams_operator(5)
5*S[1, 1, 1, 1] + 10*S[1, 1, 2] + 10*S[1, 2, 1] + 10*S[1, 3] + 10*S[2, 1, ↵
↵1] + 10*S[2, 2] + 10*S[3, 1] + 5*S[4]

```

```

sage: m = SymmetricFunctionsNonCommutingVariables(QQ).m()
sage: m[[1,3],[2]].adams_operator(-2)
3*m{{1}, {2, 3}} + 3*m{{1, 2}, {3}} + 6*m{{1, 2, 3}} - 2*m{{1, 3}, {2}}

```

convolution_product(*maps)

Return the image of `self` under the convolution product (map) of the maps.

Let A and B be bialgebras over a commutative ring R . Given maps $f_i : A \rightarrow B$ for $1 \leq i < n$, define the convolution product

$$(f_1 * f_2 * \cdots * f_n) := \mu^{(n-1)} \circ (f_1 \otimes f_2 \otimes \cdots \otimes f_n) \circ \Delta^{(n-1)},$$

where $\Delta^{(k)} := (\Delta \otimes \text{Id}^{\otimes(k-1)}) \circ \Delta^{(k-1)}$, with $\Delta^{(1)} = \Delta$ (the ordinary coproduct in A) and $\Delta^{(0)} = \text{Id}$; and with $\mu^{(k)} := \mu \circ (\mu^{(k-1)} \otimes \text{Id})$ and $\mu^{(1)} = \mu$ (the ordinary product in B). See [Swe1969].

(In the literature, one finds, e.g., $\Delta^{(2)}$ for what we denote above as $\Delta^{(1)}$. See [KMN2012].)

INPUT:

- `maps` – any number $n \geq 0$ of linear maps f_1, f_2, \dots, f_n on `self.parent()`; or a single list or tuple of such maps

OUTPUT:

- the convolution product of `maps` applied to `self`

AUTHORS:

- Amy Pang - 12 June 2015 - Sage Days 65

Todo: Remove dependency on `modules_with_basis` methods.

EXAMPLES:

We compute convolution products of the identity and antipode maps on Schur functions:

```

sage: Id = lambda x: x
sage: Antipode = lambda x: x.antipode()
sage: s = SymmetricFunctions(QQ).schur()
sage: s[3].convolution_product(Id, Id)
2*s[2, 1] + 4*s[3]
sage: s[3,2].convolution_product(Id) == s[3,2]
True

```

The method accepts multiple arguments, or a single argument consisting of a list of maps:

```

sage: s[3,2].convolution_product(Id, Id)
2*s[2, 1, 1, 1] + 6*s[2, 2, 1] + 6*s[3, 1, 1] + 12*s[3, 2] + 6*s[4, 1] + ↵
↵2*s[5]
sage: s[3,2].convolution_product([Id, Id])
2*s[2, 1, 1, 1] + 6*s[2, 2, 1] + 6*s[3, 1, 1] + 12*s[3, 2] + 6*s[4, 1] + ↵
↵2*s[5]

```

We test the defining property of the antipode morphism; namely, that the antipode is the inverse of the identity map in the convolution algebra whose identity element is the composition of the counit and unit:

```
sage: s[3,2].convolution_product() == s[3,2].convolution_product(Antipode, ↵
↵ Id) == s[3,2].convolution_product(Id, Antipode)
True
```

```
sage: Psi = NonCommutativeSymmetricFunctions(QQ).Psi()
sage: Psi[2,1].convolution_product(Id, Id, Id)
3*Psi[1, 2] + 6*Psi[2, 1]
sage: (Psi[5,1] - Psi[1,5]).convolution_product(Id, Id, Id)
-3*Psi[1, 5] + 3*Psi[5, 1]
```

```
sage: G = SymmetricGroup(3)
sage: QG = GroupAlgebra(G,QQ)
sage: x = QG.sum_of_terms([(p,p.length()) for p in Permutations(3)]); x
[1, 3, 2] + [2, 1, 3] + 2*[2, 3, 1] + 2*[3, 1, 2] + 3*[3, 2, 1]
sage: x.convolution_product(Id, Id)
5*[1, 2, 3] + 2*[2, 3, 1] + 2*[3, 1, 2]
sage: x.convolution_product(Id, Id, Id)
4*[1, 2, 3] + [1, 3, 2] + [2, 1, 3] + 3*[3, 2, 1]
sage: x.convolution_product([Id]*6)
9*[1, 2, 3]
```

class ParentMethods

Bases: object

convolution_product(*maps)

Return the convolution product (a map) of the given maps.

Let A and B be bialgebras over a commutative ring R . Given maps $f_i : A \rightarrow B$ for $1 \leq i < n$, define the convolution product

$$(f_1 * f_2 * \cdots * f_n) := \mu^{(n-1)} \circ (f_1 \otimes f_2 \otimes \cdots \otimes f_n) \circ \Delta^{(n-1)},$$

where $\Delta^{(k)} := (\Delta \otimes \text{Id}^{\otimes (k-1)}) \circ \Delta^{(k-1)}$, with $\Delta^{(1)} = \Delta$ (the ordinary coproduct in A) and $\Delta^{(0)} = \text{Id}$; and with $\mu^{(k)} := \mu \circ (\mu^{(k-1)} \otimes \text{Id})$ and $\mu^{(1)} = \mu$ (the ordinary product in B). See [Swe1969].

(In the literature, one finds, e.g., $\Delta^{(2)}$ for what we denote above as $\Delta^{(1)}$. See [KMN2012].)

INPUT:

- maps – any number $n \geq 0$ of linear maps f_1, f_2, \dots, f_n on self; or a single list or tuple of such maps

OUTPUT:

- the new map $f_1 * f_2 * \cdots * f_n$ representing their convolution product

See also:

sage.categories.bialgebras.ElementMethods.convolution_product()

AUTHORS:

- Aaron Lauve - 12 June 2015 - Sage Days 65

Todo: Remove dependency on modules_with_basis methods.

EXAMPLES:

We construct some maps: the identity, the antipode and projection onto the homogeneous component of degree 2:

```

sage: Id = lambda x: x
sage: Antipode = lambda x: x.antipode()
sage: Proj2 = lambda x: x.parent().sum_of_terms([(m, c) for (m, c) in x if
↪ m.size() == 2])

```

Compute the convolution product of the identity with itself and with the projection Proj2 on the Hopf algebra of non-commutative symmetric functions:

```

sage: R = NonCommutativeSymmetricFunctions(QQ).ribbon()
sage: T = R.convolution_product([Id, Id])
sage: [T(R(comp)) for comp in Compositions(3)]
[4*R[1, 1, 1] + R[1, 2] + R[2, 1],
 2*R[1, 1, 1] + 4*R[1, 2] + 2*R[2, 1] + 2*R[3],
 2*R[1, 1, 1] + 2*R[1, 2] + 4*R[2, 1] + 2*R[3],
 R[1, 2] + R[2, 1] + 4*R[3]]
sage: T = R.convolution_product(Proj2, Id)
sage: [T(R([i])) for i in range(1, 5)]
[0, R[2], R[2, 1] + R[3], R[2, 2] + R[4]]

```

Compute the convolution product of no maps on the Hopf algebra of symmetric functions in non-commuting variables. This is the composition of the counit with the unit:

```

sage: m = SymmetricFunctionsNonCommutingVariables(QQ).m()
sage: T = m.convolution_product()
sage: [T(m(lam)) for lam in SetPartitions(0).list() + SetPartitions(2).
↪ list()]
[m{}, 0, 0]

```

Compute the convolution product of the projection Proj2 with the identity on the Hopf algebra of symmetric functions in non-commuting variables:

```

sage: T = m.convolution_product(Proj2, Id)
sage: [T(m(lam)) for lam in SetPartitions(3)]
[0,
 m{{1, 2}, {3}} + m{{1, 2, 3}},
 m{{1, 2}, {3}} + m{{1, 2, 3}},
 m{{1, 2}, {3}} + m{{1, 2, 3}},
 3*m{{1}, {2}, {3}} + 3*m{{1}, {2, 3}} + 3*m{{1, 3}, {2}}]

```

Compute the convolution product of the antipode with itself and the identity map on group algebra of the symmetric group:

```

sage: G = SymmetricGroup(3)
sage: QG = GroupAlgebra(G, QQ)
sage: x = QG.sum_of_terms([(p, p.number_of_peaks() + p.number_of_
↪ inversions()) for p in Permutations(3)]); x
2*[1, 3, 2] + [2, 1, 3] + 3*[2, 3, 1] + 2*[3, 1, 2] + 3*[3, 2, 1]
sage: T = QG.convolution_product(Antipode, Antipode, Id)
sage: T(x)
2*[1, 3, 2] + [2, 1, 3] + 2*[2, 3, 1] + 3*[3, 1, 2] + 3*[3, 2, 1]

```


3.15 Bimodules

class `sage.categories.bimodules.Bimodules`(*left_base*, *right_base*, *name=None*)

Bases: `sage.categories.category.CategoryWithParameters`

The category of (R, S) -bimodules

For R and S rings, a (R, S) -bimodule X is a left R -module and right S -module such that the left and right actions commute: $r * (x * s) = (r * x) * s$.

EXAMPLES:

```
sage: Bimodules(QQ, ZZ)
Category of bimodules over Rational Field on the left and Integer Ring on the right
sage: Bimodules(QQ, ZZ).super_categories()
[Category of left modules over Rational Field, Category of right modules over
↪Integer Ring]
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

additional_structure()

Return `None`.

Indeed, the category of bimodules defines no additional structure: a left and right module morphism between two bimodules is a bimodule morphism.

See also:

`Category.additional_structure()`

Todo: Should this category be a `CategoryWithAxiom`?

EXAMPLES:

```
sage: Bimodules(QQ, ZZ).additional_structure()
```

classmethod `an_instance()`

Return an instance of this class.

EXAMPLES:

```
sage: Bimodules.an_instance()
Category of bimodules over Rational Field on the left and Real Field with 53
↪bits of precision on the right
```

left_base_ring()

Return the left base ring over which elements of this category are defined.

EXAMPLES:

```
sage: Bimodules(QQ, ZZ).left_base_ring()
Rational Field
```

right_base_ring()

Return the right base ring over which elements of this category are defined.

EXAMPLES:

```
sage: Bimodules(QQ, ZZ).right_base_ring()
Integer Ring
```

super_categories()

EXAMPLES:

```
sage: Bimodules(QQ, ZZ).super_categories()
[Category of left modules over Rational Field, Category of right modules over
Integer Ring]
```

3.16 Classical Crystals

class sage.categories.classical_crystals.**ClassicalCrystals**(*s=None*)

Bases: *sage.categories.category_singleton.Category_singleton*

The category of classical crystals, that is crystals of finite Cartan type.

EXAMPLES:

```
sage: C = ClassicalCrystals()
sage: C
Category of classical crystals
sage: C.super_categories()
[Category of regular crystals,
Category of finite crystals,
Category of highest weight crystals]
sage: C.example()
Highest weight crystal of type A_3 of highest weight omega_1
```

class ElementMethods

Bases: object

lusztig_involution()

Return the Lusztig involution on the classical highest weight crystal *self*.

The Lusztig involution on a finite-dimensional highest weight crystal $B(\lambda)$ of highest weight λ maps the highest weight vector to the lowest weight vector and the Kashiwara operator f_i to e_{i^*} , where i^* is defined as $\alpha_{i^*} = -w_0(\alpha_i)$. Here w_0 is the longest element of the Weyl group acting on the i -th simple root α_i .

EXAMPLES:

```
sage: B = crystals.Tableaux(['A', 3], shape=[2, 1])
sage: b = B(rows=[[1, 2], [4]])
sage: b.lusztig_involution()
[[1, 4], [3]]
sage: b.to_tableau().schuetzenberger_involution(n=4)
[[1, 4], [3]]
```

```
sage: all(b.lusztig_involution().to_tableau() == b.to_tableau().
schuetzenberger_involution(n=4) for b in B)
```

(continues on next page)

(continued from previous page)

```

True

sage: B = crystals.Tableaux(['D',4],shape=[1])
sage: [[b,b.lusztig_involution()] for b in B]
[[[1], [-1]], [[2], [-2]], [[3], [-3]], [[4], [-4]], [[-4],
→4],
[4]], [[-3], [3]], [[-2], [2]], [[-1], [1]]]

sage: B = crystals.Tableaux(['D',3],shape=[1])
sage: [[b,b.lusztig_involution()] for b in B]
[[[1], [-1]], [[2], [-2]], [[3], [3]], [[-3], [-3]],
[[-2], [2]], [[-1], [1]]]

sage: C = CartanType(['E',6])
sage: La = C.root_system().weight_lattice().fundamental_weights()
sage: T = crystals.HighestWeight(La[1])
sage: t = T[3]; t
[(-4, 2, 5)]
sage: t.lusztig_involution()
[(-2, -3, 4)]

```

class ParentMethods

Bases: object

cardinality()

Returns the number of elements of the crystal, using Weyl's dimension formula on each connected component.

EXAMPLES:

```

sage: C = ClassicalCrystals().example(5)
sage: C.cardinality()
6

```

character(*R=None*)

Returns the character of this crystal.

INPUT:

- *R* – a [WeylCharacterRing](#) (default: the default [WeylCharacterRing](#) for this Cartan type)

Returns the character of `self` as an element of *R*.

EXAMPLES:

```

sage: C = crystals.Tableaux("A2", shape=[2,1])
sage: chi = C.character(); chi
A2(2,1,0)

sage: T = crystals.TensorProduct(C,C)
sage: chiT = T.character(); chiT
A2(2,2,2) + 2*A2(3,2,1) + A2(3,3,0) + A2(4,1,1) + A2(4,2,0)
sage: chiT == chi^2
True

```

One may specify an alternate [WeylCharacterRing](#):

```
sage: R = WeylCharacterRing("A2", style="coroots")
sage: chiT = T.character(R); chiT
A2(0,0) + 2*A2(1,1) + A2(0,3) + A2(3,0) + A2(2,2)
sage: chiT in R
True
```

It should have the same Cartan type and use the same realization of the weight lattice as `self`:

```
sage: R = WeylCharacterRing("A3", style="coroots")
sage: T.character(R)
Traceback (most recent call last):
...
ValueError: Weyl character ring does not have the right Cartan type
```

`demazure_character`($w, f=None$)

Return the Demazure character associated to w .

INPUT:

- w – an element of the ambient weight lattice realization of the crystal, or a reduced word, or an element in the associated Weyl group

OPTIONAL:

- f – a function from the crystal to a module

This is currently only supported for crystals whose underlying weight space is the ambient space.

The Demazure character is obtained by applying the Demazure operator D_w (see [sage.categories.regular_crystals.RegularCrystals.ParentMethods.demazure_operator\(\)](#)) to the highest weight element of the classical crystal. The simple Demazure operators D_i (see [sage.categories.regular_crystals.RegularCrystals.ElementMethods.demazure_operator_simple\(\)](#)) do not braid on the level of crystals, but on the level of characters they do. That is why it makes sense to input w either as a weight, a reduced word, or as an element of the underlying Weyl group.

EXAMPLES:

```
sage: T = crystals.Tableaux(['A',2], shape = [2,1])
sage: e = T.weight_lattice_realization().basis()
sage: weight = e[0] + 2*e[2]
sage: weight.reduced_word()
[2, 1]
sage: T.demazure_character(weight)
x1^2*x2 + x1*x2^2 + x1^2*x3 + x1*x2*x3 + x1*x3^2

sage: T = crystals.Tableaux(['A',3], shape=[2,1])
sage: T.demazure_character([1,2,3])
x1^2*x2 + x1*x2^2 + x1^2*x3 + x1*x2*x3 + x2^2*x3
sage: W = WeylGroup(['A',3])
sage: w = W.from_reduced_word([1,2,3])
sage: T.demazure_character(w)
x1^2*x2 + x1*x2^2 + x1^2*x3 + x1*x2*x3 + x2^2*x3

sage: T = crystals.Tableaux(['B',2], shape = [2])
sage: e = T.weight_lattice_realization().basis()
sage: weight = -2*e[1]
sage: T.demazure_character(weight)
x1^2 + x1*x2 + x2^2 + x1 + x2 + x1/x2 + 1/x2 + 1/x2^2 + 1
```

(continues on next page)

(continued from previous page)

```

sage: T = crystals.Tableaux("B2", shape=[1/2, 1/2])
sage: b2=WeylCharacterRing("B2", base_ring=QQ).ambient()
sage: T.demazure_character([1, 2], f=lambda x: b2(x.weight()))
b2(-1/2, 1/2) + b2(1/2, -1/2) + b2(1/2, 1/2)

```

REFERENCES:

- [De1974]
- [Ma2009]

class TensorProducts(*category, *args*)Bases: *sage.categories.tensor.TensorProductsCategory*

The category of classical crystals constructed by tensor product of classical crystals.

extra_super_categories()

EXAMPLES:

```

sage: ClassicalCrystals().TensorProducts().extra_super_categories()
[Category of classical crystals]

```

additional_structure()

Return None.

Indeed, the category of classical crystals defines no additional structure: it only states that its objects are $U_q(\mathfrak{g})$ -crystals, where \mathfrak{g} is of finite type.**See also:***Category.additional_structure()*

EXAMPLES:

```

sage: ClassicalCrystals().additional_structure()

```

example(*n=3*)Returns an example of highest weight crystals, as per *Category.example()*.

EXAMPLES:

```

sage: B = ClassicalCrystals().example(); B
Highest weight crystal of type A_3 of highest weight omega_1

```

super_categories()

EXAMPLES:

```

sage: ClassicalCrystals().super_categories()
[Category of regular crystals,
 Category of finite crystals,
 Category of highest weight crystals]

```

3.17 Coalgebras

class `sage.categories.coalgebras.Coalgebras`(*base, name=None*)
 Bases: `sage.categories.category_types.Category_over_base_ring`

The category of coalgebras

EXAMPLES:

```
sage: Coalgebras(QQ)
Category of coalgebras over Rational Field
sage: Coalgebras(QQ).super_categories()
[Category of vector spaces over Rational Field]
```

class `Cocommutative`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

Category of cocommutative coalgebras.

class `DualObjects`(*category, *args*)
 Bases: `sage.categories.dual.DualObjectsCategory`

extra_super_categories()

Return the dual category.

EXAMPLES:

The category of coalgebras over the Rational Field is dual to the category of algebras over the same field:

```
sage: C = Coalgebras(QQ)
sage: C.dual()
Category of duals of coalgebras over Rational Field
sage: C.dual().super_categories() # indirect doctest
[Category of algebras over Rational Field,
 Category of duals of vector spaces over Rational Field]
```

Warning: This is only correct in certain cases (finite dimension, ...). See [trac ticket #15647](#).

class `ElementMethods`

Bases: `object`

coproduct()

Return the coproduct of self.

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis:
the group algebra of the Dihedral group of order 6 as a permutation group_
over Rational Field
sage: [a,b] = A.algebra_generators()
sage: a, a.coproduct()
(B[(1,2,3)], B[(1,2,3)] # B[(1,2,3)])
sage: b, b.coproduct()
(B[(1,3)], B[(1,3)] # B[(1,3)])
```

counit()

Return the counit of self.

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis:
  the group algebra of the Dihedral group of order 6 as a permutation group
↳over Rational Field
sage: [a,b] = A.algebra_generators()
sage: a, a.counit()
(B[(1,2,3)], 1)
sage: b, b.counit()
(B[(1,3)], 1)
```

class Filtered(*base_category*)

Bases: *sage.categories.filtered_modules.FilteredModulesCategory*

Category of filtered coalgebras.

Graded

alias of *sage.categories.graded_coalgebras.GradedCoalgebras*

class ParentMethods

Bases: object

coproduct(*x*)

Return the coproduct of *x*.

Eventually, there will be a default implementation, delegating to the overloading mechanism and forcing the conversion back

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis:
  the group algebra of the Dihedral group of order 6 as a permutation group
↳over Rational Field
sage: [a,b] = A.algebra_generators()
sage: a, A.coproduct(a)
(B[(1,2,3)], B[(1,2,3)] # B[(1,2,3)])
sage: b, A.coproduct(b)
(B[(1,3)], B[(1,3)] # B[(1,3)])
```

counit(*x*)

Return the counit of *x*.

Eventually, there will be a default implementation, delegating to the overloading mechanism and forcing the conversion back

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis:
  the group algebra of the Dihedral group of order 6 as a permutation group
↳over Rational Field
sage: [a,b] = A.algebra_generators()
sage: a, A.counit(a)
```

(continues on next page)

(continued from previous page)

```
(B[(1,2,3)], 1)
sage: b, A.counit(b)
(B[(1,3)], 1)
```

TODO: implement some tests of the axioms of coalgebras, bialgebras and Hopf algebras using the counit.

class Realizations(*category, *args*)

Bases: *sage.categories.realizations.RealizationsCategory*

class ParentMethods

Bases: object

coproduct_by_coercion(*x*)

Return the coproduct by coercion if `coproduct_by_basis` is not implemented.

EXAMPLES:

```
sage: Sym = SymmetricFunctions(QQ)
sage: m = Sym.monomial()
sage: f = m[2,1]
sage: f.coproduct.__module__
'sage.categories.coalgebras'
sage: m.coproduct_on_basis
NotImplemented
sage: m.coproduct == m.coproduct_by_coercion
True
sage: f.coproduct()
m[] # m[2, 1] + m[1] # m[2] + m[2] # m[1] + m[2, 1] # m[]
```

```
sage: N = NonCommutativeSymmetricFunctions(QQ)
sage: R = N.ribbon()
sage: R.coproduct_by_coercion.__module__
'sage.categories.coalgebras'
sage: R.coproduct_on_basis
NotImplemented
sage: R.coproduct == R.coproduct_by_coercion
True
sage: R[1].coproduct()
R[] # R[1] + R[1] # R[]
```

counit_by_coercion(*x*)

Return the counit of *x* if `counit_by_basis` is not implemented.

EXAMPLES:

```
sage: sp = SymmetricFunctions(QQ).sp()
sage: sp.an_element()
2*sp[] + 2*sp[1] + 3*sp[2]
sage: sp.counit(sp.an_element())
2

sage: o = SymmetricFunctions(QQ).o()
sage: o.an_element()
2*o[] + 2*o[1] + 3*o[2]
```

(continues on next page)

(continued from previous page)

```
sage: o.counit(o.an_element())
-1
```

class SubcategoryMethods

Bases: object

Cocommutative()Return the full subcategory of the cocommutative objects of `self`.A coalgebra C is said to be *cocommutative* if

$$\Delta(c) = \sum_{(c)} c_{(1)} \otimes c_{(2)} = \sum_{(c)} c_{(2)} \otimes c_{(1)}$$

in Sweedler's notation for all $c \in C$.

EXAMPLES:

```
sage: C1 = Coalgebras(ZZ).Cocommutative().WithBasis(); C1
Category of cocommutative coalgebras with basis over Integer Ring
sage: C2 = Coalgebras(ZZ).WithBasis().Cocommutative()
sage: C1 is C2
True
sage: BialgebrasWithBasis(QQ).Cocommutative()
Category of cocommutative bialgebras with basis over Rational Field
```

class Super(*base_category*)Bases: *sage.categories.super_modules.SuperModulesCategory***class SubcategoryMethods**

Bases: object

Supercocommutative()Return the full subcategory of the supercocommutative objects of `self`.

EXAMPLES:

```
sage: Coalgebras(ZZ).WithBasis().Super().Supercocommutative()
Category of supercocommutative super coalgebras with basis over Integer_
↳Ring
sage: BialgebrasWithBasis(QQ).Super().Supercocommutative()
Join of Category of super algebras with basis over Rational Field
and Category of super bialgebras over Rational Field
and Category of super coalgebras with basis over Rational Field
and Category of supercocommutative super coalgebras over Rational Field
```

class Supercocommutative(*base_category*)Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring*

Category of supercocommutative coalgebras.

extra_super_categories()

EXAMPLES:

```
sage: Coalgebras(ZZ).Super().extra_super_categories()
[Category of graded coalgebras over Integer Ring]
sage: Coalgebras(ZZ).Super().super_categories()
```

(continues on next page)

(continued from previous page)

```
[Category of graded coalgebras over Integer Ring,
Category of super modules over Integer Ring]
```

Compare this with the situation for bialgebras:

```
sage: Bialgebras(ZZ).Super().extra_super_categories()
[]
sage: Bialgebras(ZZ).Super().super_categories()
[Category of super algebras over Integer Ring,
Category of super coalgebras over Integer Ring]
```

The category of bialgebras does not occur in these results, since super bialgebras are not bialgebras.

class TensorProducts(*category, *args*)

Bases: *sage.categories.tensor.TensorProductsCategory*

class ElementMethods

Bases: object

class ParentMethods

Bases: object

extra_super_categories()

EXAMPLES:

```
sage: Coalgebras(QQ).TensorProducts().extra_super_categories()
[Category of coalgebras over Rational Field]
sage: Coalgebras(QQ).TensorProducts().super_categories()
[Category of tensor products of vector spaces over Rational Field,
Category of coalgebras over Rational Field]
```

Meaning: a tensor product of coalgebras is a coalgebra

WithBasis

alias of *sage.categories.coalgebras_with_basis.CoalgebrasWithBasis*

class WithRealizations(*category, *args*)

Bases: *sage.categories.with_realizations.WithRealizationsCategory*

class ParentMethods

Bases: object

coproduct(*x*)

Return the coproduct of *x*.

EXAMPLES:

```
sage: N = NonCommutativeSymmetricFunctions(QQ)
sage: S = N.complete()
sage: N.coproduct.__module__
'sage.categories.coalgebras'
sage: N.coproduct(S[2])
S[] # S[2] + S[1] # S[1] + S[2] # S[]
```

counit(*x*)

Return the counit of *x*.

EXAMPLES:

```

sage: Sym = SymmetricFunctions(QQ)
sage: s = Sym.schur()
sage: f = s[2,1]
sage: f.counit.__module__
'sage.categories.coalgebras'
sage: f.counit()
0

```

```

sage: N = NonCommutativeSymmetricFunctions(QQ)
sage: N.counit.__module__
'sage.categories.coalgebras'
sage: N.counit(N.one())
1
sage: x = N.an_element(); x
2*S[] + 2*S[1] + 3*S[1, 1]
sage: N.counit(x)
2

```

super_categories()

EXAMPLES:

```

sage: Coalgebras(QQ).super_categories()
[Category of vector spaces over Rational Field]

```

3.18 Coalgebras with basis

class `sage.categories.coalgebras_with_basis.CoalgebrasWithBasis`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of coalgebras with a distinguished basis.

EXAMPLES:

```

sage: CoalgebrasWithBasis(ZZ)
Category of coalgebras with basis over Integer Ring
sage: sorted(CoalgebrasWithBasis(ZZ).super_categories(), key=str)
[Category of coalgebras over Integer Ring,
 Category of modules with basis over Integer Ring]

```

class `ElementMethods`

Bases: `object`

coproduct_iterated(*n=1*)

Apply *n* coproducts to self.

Todo: Remove dependency on `modules_with_basis` methods.

EXAMPLES:

```

sage: Psi = NonCommutativeSymmetricFunctions(QQ).Psi()
sage: Psi[2,2].coproduct_iterated(0)

```

(continues on next page)

(continued from previous page)

```

Psi[2, 2]
sage: Psi[2,2].coproduct_iterated(2)
Psi[] # Psi[] # Psi[2, 2] + 2*Psi[] # Psi[2] # Psi[2]
+ Psi[] # Psi[2, 2] # Psi[] + 2*Psi[2] # Psi[] # Psi[2]
+ 2*Psi[2] # Psi[2] # Psi[] + Psi[2, 2] # Psi[] # Psi[]

```

class Filtered(*base_category*)

Bases: *sage.categories.filtered_modules.FilteredModulesCategory*

Category of filtered coalgebras.

Graded

alias of *sage.categories.graded_coalgebras_with_basis.GradedCoalgebrasWithBasis*

class ParentMethods

Bases: object

coproduct()

If *coproduct_on_basis()* is available, construct the coproduct morphism from *self* to *self* \otimes *self* by extending it by linearity. Otherwise, use *coproduct_by_coercion()*, if available.

EXAMPLES:

```

sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis: the group algebra of the Dihedral_
↳group of order 6 as a permutation group over Rational Field
sage: [a,b] = A.algebra_generators()
sage: a, A.coproduct(a)
(B[(1,2,3)], B[(1,2,3)] # B[(1,2,3)])
sage: b, A.coproduct(b)
(B[(1,3)], B[(1,3)] # B[(1,3)])

```

coproduct_on_basis(*i*)

The coproduct of the algebra on the basis (optional).

INPUT:

- *i* – the indices of an element of the basis of *self*

Returns the coproduct of the corresponding basis elements. If implemented, the coproduct of the algebra is defined from it by linearity.

EXAMPLES:

```

sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis: the group algebra of the Dihedral_
↳group of order 6 as a permutation group over Rational Field
sage: (a, b) = A._group.gens()
sage: A.coproduct_on_basis(a)
B[(1,2,3)] # B[(1,2,3)]

```

count()

If *count_on_basis()* is available, construct the counit morphism from *self* to *self* \otimes *self* by extending it by linearity.

EXAMPLES:

```

sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis: the group algebra of the Dihedral_
↳group of order 6 as a permutation group over Rational Field
sage: [a,b] = A.algebra_generators()
sage: a, A.counit(a)
(B[(1,2,3)], 1)
sage: b, A.counit(b)
(B[(1,3)], 1)

```

counit_on_basis(*i*)

The counit of the algebra on the basis (optional).

INPUT:

- *i* – the indices of an element of the basis of self

Returns the counit of the corresponding basis elements If implemented, the counit of the algebra is defined from it by linearity.

EXAMPLES:

```

sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis: the group algebra of the Dihedral_
↳group of order 6 as a permutation group over Rational Field
sage: (a, b) = A._group.gens()
sage: A.counit_on_basis(a)
1

```

class Super(*base_category*)

Bases: *sage.categories.super_modules.SuperModulesCategory*

extra_super_categories()

EXAMPLES:

```

sage: C = Coalgebras(ZZ).WithBasis().Super()
sage: sorted(C.super_categories(), key=str) # indirect doctest
[Category of graded coalgebras with basis over Integer Ring,
Category of super coalgebras over Integer Ring,
Category of super modules with basis over Integer Ring]

```

3.19 Commutative additive groups

class sage.categories.commutative_additive_groups.CommutativeAdditiveGroups(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*, *sage.categories.category_types.AbelianCategory*

The category of abelian groups, i.e. additive abelian monoids where each element has an inverse.

EXAMPLES:

```

sage: C = CommutativeAdditiveGroups(); C
Category of commutative additive groups
sage: C.super_categories()
[Category of additive groups, Category of commutative additive monoids]
sage: sorted(C.axioms())

```

(continues on next page)

(continued from previous page)

```
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse', 'AdditiveUnital']
sage: C is CommutativeAdditiveMonoids().AdditiveInverse()
True
sage: from sage.categories.additive_groups import AdditiveGroups
sage: C is AdditiveGroups().AdditiveCommutative()
True
```

Note: This category is currently empty. It's left there for backward compatibility and because it is likely to grow in the future.

class `Algebras`(*category*, **args*)

Bases: `sage.categories.algebra_functor.AlgebrasCategory`

class `CartesianProducts`(*category*, **args*)

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

class `ElementMethods`

Bases: `object`

additive_order()

Return the additive order of this element.

EXAMPLES:

```
sage: G = cartesian_product([Zmod(3), Zmod(6), Zmod(5)])
sage: G((1,1,1)).additive_order()
30
sage: any((i * G((1,1,1))).is_zero() for i in range(1,30))
False
sage: 30 * G((1,1,1))
(0, 0, 0)

sage: G = cartesian_product([ZZ, ZZ])
sage: G((0,0)).additive_order()
1
sage: G((0,1)).additive_order()
+Infinity

sage: K = GF(9)
sage: H = cartesian_product([cartesian_product([Zmod(2), Zmod(9)]), K])
sage: z = H((1,2), K.gen())
sage: z.additive_order()
18
```

3.20 Commutative additive monoids

class `sage.categories.commutative_additive_monoids.CommutativeAdditiveMonoids`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of commutative additive monoids, that is abelian additive semigroups with a unit

EXAMPLES:

```
sage: C = CommutativeAdditiveMonoids(); C
Category of commutative additive monoids
sage: C.super_categories()
[Category of additive monoids, Category of commutative additive semigroups]
sage: sorted(C.axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveUnital']
sage: C is AdditiveMagmas().AdditiveAssociative().AdditiveCommutative().
↪AdditiveUnital()
True
```

Note: This category is currently empty and only serves as a place holder to make `C.example()` work.

3.21 Commutative additive semigroups

class `sage.categories.commutative_additive_semigroups.CommutativeAdditiveSemigroups`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of additive abelian semigroups, i.e. sets with an associative and abelian operation +.

EXAMPLES:

```
sage: C = CommutativeAdditiveSemigroups(); C
Category of commutative additive semigroups
sage: C.example()
An example of a commutative semigroup: the free commutative semigroup generated by (
↪'a', 'b', 'c', 'd')

sage: sorted(C.super_categories(), key=str)
[Category of additive commutative additive magmas,
 Category of additive semigroups]
sage: sorted(C.axioms())
['AdditiveAssociative', 'AdditiveCommutative']
sage: C is AdditiveMagmas().AdditiveAssociative().AdditiveCommutative()
True
```

Note: This category is currently empty and only serves as a place holder to make `C.example()` work.

3.22 Commutative algebra ideals

class `sage.categories.commutative_algebra_ideals.CommutativeAlgebraIdeals(A)`

Bases: `sage.categories.category_types.Category_ideal`

The category of ideals in a fixed commutative algebra A .

EXAMPLES:

```
sage: C = CommutativeAlgebraIdeals(QQ['x'])
sage: C
Category of commutative algebra ideals in Univariate Polynomial Ring in x over
↳Rational Field
```

algebra()

EXAMPLES:

```
sage: CommutativeAlgebraIdeals(QQ['x']).algebra()
Univariate Polynomial Ring in x over Rational Field
```

super_categories()

EXAMPLES:

```
sage: CommutativeAlgebraIdeals(QQ['x']).super_categories()
[Category of algebra ideals in Univariate Polynomial Ring in x over Rational
↳Field]
```

3.23 Commutative algebras

class `sage.categories.commutative_algebras.CommutativeAlgebras(base_category)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

The category of commutative algebras with unit over a given base ring.

EXAMPLES:

```
sage: M = CommutativeAlgebras(GF(19))
sage: M
Category of commutative algebras over Finite Field of size 19
sage: CommutativeAlgebras(QQ).super_categories()
[Category of algebras over Rational Field, Category of commutative rings]
```

This is just a shortcut for:

```
sage: Algebras(QQ).Commutative()
Category of commutative algebras over Rational Field
```


3.24 Commutative ring ideals

class `sage.categories.commutative_ring_ideals.CommutativeRingIdeals(R)`

Bases: `sage.categories.category_types.Category_ideal`

The category of ideals in a fixed commutative ring.

EXAMPLES:

```
sage: C = CommutativeRingIdeals(IntegerRing())
sage: C
Category of commutative ring ideals in Integer Ring
```

super_categories()

EXAMPLES:

```
sage: CommutativeRingIdeals(ZZ).super_categories()
[Category of ring ideals in Integer Ring]
```

3.25 Commutative rings

class `sage.categories.commutative_rings.CommutativeRings(base_category)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of commutative rings

commutative rings with unity, i.e. rings with commutative `*` and a multiplicative identity

EXAMPLES:

```
sage: C = CommutativeRings(); C
Category of commutative rings
sage: C.super_categories()
[Category of rings, Category of commutative monoids]
```

class `CartesianProducts(category, *args)`

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

extra_super_categories()

Let Sage know that Cartesian products of commutative rings is a commutative ring.

EXAMPLES:

```
sage: CommutativeRings().Commutative().CartesianProducts().extra_super_
↪categories()
[Category of commutative rings]
sage: cartesian_product([ZZ, Zmod(34), QQ, GF(5)]) in CommutativeRings()
True
```

class `ElementMethods`

Bases: `object`

class `Finite(base_category)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

Check that Sage knows that Cartesian products of finite commutative rings is a finite commutative ring.

EXAMPLES:

```
sage: cartesian_product([Zmod(34), GF(5)]) in Rings().Commutative().Finite()
True
```

class ParentMethods

Bases: object

cyclotomic_cosets(q , *cosets=None*)

Return the (multiplicative) orbits of q in the ring.

Let R be a finite commutative ring. The group of invertible elements R^* in R gives rise to a group action on R by multiplication. An orbit of the subgroup generated by an invertible element q is called a q -cyclotomic coset (since in a finite ring, each invertible element is a root of unity).

These cosets arise in the theory of minimal polynomials of finite fields, duadic codes and combinatorial designs. Fix a primitive element z of $GF(q^k)$. The minimal polynomial of z^s over $GF(q)$ is given by

$$M_s(x) = \prod_{i \in C_s} (x - z^i),$$

where C_s is the q -cyclotomic coset mod n containing s , $n = q^k - 1$.

Note: When $R = \mathbf{Z}/n\mathbf{Z}$ the smallest element of each coset is sometimes called a *coset leader*. This function returns sorted lists so that the coset leader will always be the first element of the coset.

INPUT:

- q – an invertible element of the ring
- *cosets* – an optional lists of elements of `self`. If provided, the function only return the list of cosets that contain some element from *cosets*.

OUTPUT:

A list of lists.

EXAMPLES:

```
sage: Zmod(11).cyclotomic_cosets(2)
[[0], [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]]
sage: Zmod(15).cyclotomic_cosets(2)
[[0], [1, 2, 4, 8], [3, 6, 9, 12], [5, 10], [7, 11, 13, 14]]
```

Since the group of invertible elements of a finite field is cyclic, the set of squares is a particular case of cyclotomic coset:

```
sage: K = GF(25, 'z')
sage: a = K.multiplicative_generator()
sage: K.cyclotomic_cosets(a**2, cosets=[1])
[[1, 2, 3, 4, z + 1, z + 3,
  2*z + 1, 2*z + 2, 3*z + 3,
  3*z + 4, 4*z + 2, 4*z + 4]]
sage: sorted(b for b in K if not b.is_zero() and b.is_square())
[1, 2, 3, 4, z + 1, z + 3,
  2*z + 1, 2*z + 2, 3*z + 3,
  3*z + 4, 4*z + 2, 4*z + 4]
```

We compute some examples of minimal polynomials:

```
sage: K = GF(27, 'z')
sage: a = K.multiplicative_generator()
sage: R.<X> = PolynomialRing(K, 'X')
sage: a.minimal_polynomial('X')
X^3 + 2*X + 1
sage: cyc3 = Zmod(26).cyclotomic_cosets(3,cosets=[1]); cyc3
[[1, 3, 9]]
sage: prod(X - a**i for i in cyc3[0])
X^3 + 2*X + 1

sage: (a**7).minimal_polynomial('X')
X^3 + X^2 + 2*X + 1
sage: cyc7 = Zmod(26).cyclotomic_cosets(3,cosets=[7]); cyc7
[[7, 11, 21]]
sage: prod(X - a**i for i in cyc7[0])
X^3 + X^2 + 2*X + 1
```

Cyclotomic cosets of fields are useful in combinatorial design theory to provide so called difference families (see [Wikipedia article Difference_set](#) and [difference_family](#)). This is illustrated on the following examples:

```
sage: K = GF(5)
sage: a = K.multiplicative_generator()
sage: H = K.cyclotomic_cosets(a**2, cosets=[1,2]); H
[[1, 4], [2, 3]]
sage: sorted(x-y for D in H for x in D for y in D if x != y)
[1, 2, 3, 4]

sage: K = GF(37)
sage: a = K.multiplicative_generator()
sage: H = K.cyclotomic_cosets(a**4, cosets=[1]); H
[[1, 7, 9, 10, 12, 16, 26, 33, 34]]
sage: sorted(x-y for D in H for x in D for y in D if x != y)
[1, 1, 2, 2, 3, 3, 4, 4, 5, 5, ..., 33, 34, 34, 35, 35, 36, 36]
```

The method `cyclotomic_cosets` works on any finite commutative ring:

```
sage: R = cartesian_product([GF(7), Zmod(14)])
sage: a = R((3,5))
sage: R.cyclotomic_cosets((3,5), [(1,1)])
[[ (1, 1), (2, 11), (3, 5), (4, 9), (5, 3), (6, 13) ]]
```

class ParentMethods

Bases: object

over(*base=None, gen=None, gens=None, name=None, names=None*)

Return this ring, considered as an extension of *base*.

INPUT:

- *base* – a commutative ring or a morphism or `None` (default: `None`); the base of this extension or its defining morphism
- *gen* – a generator of this extension (over its base) or `None` (default: `None`);
- *gens* – a list of generators of this extension (over its base) or `None` (default: `None`);
- *name* – a variable name or `None` (default: `None`)

- `names` – a list or a tuple of variable names or `None` (default: `None`)

EXAMPLES:

We construct an extension of finite fields:

```
sage: F = GF(5^2)
sage: k = GF(5^4)
sage: z4 = k.gen()

sage: K = k.over(F)
sage: K
Field in z4 with defining polynomial x^2 + (4*z2 + 3)*x + z2 over its base
```

If not explicitly given, the default generator of the top ring (here `k`) is used and the same name is kept:

```
sage: K.gen()
z4
sage: K(z4)
z4
```

However, it is possible to specify another generator and/or another name. For example:

```
sage: Ka = k.over(F, name='a')
sage: Ka
Field in a with defining polynomial x^2 + (4*z2 + 3)*x + z2 over its base
sage: Ka.gen()
a
sage: Ka(z4)
a

sage: Kb = k.over(F, gen=-z4+1, name='b')
sage: Kb
Field in b with defining polynomial x^2 + z2*x + 4 over its base
sage: Kb.gen()
b
sage: Kb(-z4+1)
b
```

Note that the shortcut `K.<a>` is also available:

```
sage: KKa.<a> = k.over(F)
sage: KKa is Ka
True
```

Building an extension on top of another extension is allowed:

```
sage: L = GF(5^12).over(K)
sage: L
Field in z12 with defining polynomial x^3 + (1 + (4*z2 + 2)*z4)*x^2 + (2 +
↪ 2*z4)*x - z4 over its base
sage: L.base_ring()
Field in z4 with defining polynomial x^2 + (4*z2 + 3)*x + z2 over its base
```

The successive bases of an extension are accessible via the method `sage.rings.ring_extension.RingExtension_generic.bases()`:

```
sage: L.bases()
[Field in z12 with defining polynomial x^3 + (1 + (4*z2 + 2)*z4)*x^2 + (2 +
↪2*z4)*x - z4 over its base,
Field in z4 with defining polynomial x^2 + (4*z2 + 3)*x + z2 over its base,
Finite Field in z2 of size 5^2]
```

When base is omitted, the canonical base of the ring is used:

```
sage: S.<x> = QQ[]
sage: E = S.over()
sage: E
Univariate Polynomial Ring in x over Rational Field over its base
sage: E.base_ring()
Rational Field
```

Here is an example where base is a defining morphism:

```
sage: k.<a> = QQ.extension(x^2 - 2)
sage: l.<b> = QQ.extension(x^4 - 2)
sage: f = k.hom([b^2])
sage: L = l.over(f)
sage: L
Field in b with defining polynomial x^2 - a over its base
sage: L.base_ring()
Number Field in a with defining polynomial x^2 - 2
```

Similarly, one can create a tower of extensions:

```
sage: K = k.over()
sage: L = l.over(Hom(K,l)(f))
sage: L
Field in b with defining polynomial x^2 - a over its base
sage: L.base_ring()
Field in a with defining polynomial x^2 - 2 over its base
sage: L.bases()
[Field in b with defining polynomial x^2 - a over its base,
Field in a with defining polynomial x^2 - 2 over its base,
Rational Field]
```

3.26 Complete Discrete Valuation Rings (CDVR) and Fields (CDVF)

```
class sage.categories.complete_discrete_valuation.CompleteDiscreteValuationFields(s=None)
    Bases: sage.categories.category_singleton.Category_singleton
```

The category of complete discrete valuation fields

EXAMPLES:

```
sage: Zp(7) in CompleteDiscreteValuationFields()
False
sage: QQ in CompleteDiscreteValuationFields()
False
```

(continues on next page)

(continued from previous page)

```

sage: LaurentSeriesRing(QQ, 'u') in CompleteDiscreteValuationFields()
True
sage: Qp(7) in CompleteDiscreteValuationFields()
True
sage: TestSuite(CompleteDiscreteValuationFields()).run()

```

class ElementMethods

Bases: object

denominator()

Return the denominator of this element normalized as a power of the uniformizer

EXAMPLES:

```

sage: K = Qp(7)
sage: x = K(1/21)
sage: x.denominator()
7 + 0(7^21)

sage: x = K(7)
sage: x.denominator()
1 + 0(7^20)

```

Note that the denominator lives in the ring of integers:

```

sage: x.denominator().parent()
7-adic Ring with capped relative precision 20

```

When the denominator is indistinguishable from 0 and the precision on the input is $O(p^n)$, the return value is 1 if n is nonnegative and $p^{-(n)}$ otherwise:

```

sage: x = K(0, 5); x
0(7^5)
sage: x.denominator()
1 + 0(7^20)

sage: x = K(0, -5); x
0(7^-5)
sage: x.denominator()
7^5 + 0(7^25)

```

numerator()Return the numerator of this element, normalized in such a way that $x = x.numerator()/x.denominator()$ always holds true.

EXAMPLES:

```

sage: K = Qp(7, 5)
sage: x = K(1/21)
sage: x.numerator()
5 + 4*7 + 4*7^2 + 4*7^3 + 4*7^4 + 0(7^5)

sage: x == x.numerator() / x.denominator()
True

```

Note that the numerator lives in the ring of integers:

```
sage: x.numerator().parent()
7-adic Ring with capped relative precision 5
```

valuation()

Return the valuation of this element.

EXAMPLES:

```
sage: K = Qp(7)
sage: x = K(7); x
7 + 0(7^21)
sage: x.valuation()
1
```

super_categories()

EXAMPLES:

```
sage: CompleteDiscreteValuationFields().super_categories()
[Category of discrete valuation fields]
```

class sage.categories.complete_discrete_valuation.CompleteDiscreteValuationRings(*s=None*)

Bases: *sage.categories.category_singleton.Category_singleton*

The category of complete discrete valuation rings

EXAMPLES:

```
sage: Zp(7) in CompleteDiscreteValuationRings()
True
sage: QQ in CompleteDiscreteValuationRings()
False
sage: QQ[['u']] in CompleteDiscreteValuationRings()
True
sage: Qp(7) in CompleteDiscreteValuationRings()
False
sage: TestSuite(CompleteDiscreteValuationRings()).run()
```

class ElementMethods

Bases: object

denominator()

Return the denominator of this element normalized as a power of the uniformizer

EXAMPLES:

```
sage: K = Qp(7)
sage: x = K(1/21)
sage: x.denominator()
7 + 0(7^21)

sage: x = K(7)
sage: x.denominator()
1 + 0(7^20)
```

Note that the denominator lives in the ring of integers:

```
sage: x.denominator().parent()
7-adic Ring with capped relative precision 20
```

When the denominator is indistinguishable from 0 and the precision on the input is $O(p^n)$, the return value is 1 if n is nonnegative and $p^{(-n)}$ otherwise:

```
sage: x = K(0,5); x
0(7^5)
sage: x.denominator()
1 + 0(7^20)

sage: x = K(0,-5); x
0(7^-5)
sage: x.denominator()
7^5 + 0(7^25)
```

lift_to_precision(*absprec=None*)

Return another element of the same parent with absolute precision at least *absprec*, congruent to this element modulo the precision of this element.

INPUT:

- *absprec* – an integer or None (default: None), the absolute precision of the result. If None, lifts to the maximum precision allowed.

Note: If setting *absprec* that high would violate the precision cap, raises a precision error. Note that the new digits will not necessarily be zero.

EXAMPLES:

```
sage: R = ZpCA(17)
sage: R(-1,2).lift_to_precision(10)
16 + 16*17 + 0(17^10)
sage: R(1,15).lift_to_precision(10)
1 + 0(17^15)
sage: R(1,15).lift_to_precision(30)
Traceback (most recent call last):
...
PrecisionError: precision higher than allowed by the precision cap
sage: R(-1,2).lift_to_precision().precision_absolute() == R.precision_cap()
True

sage: R = Zp(5); c = R(17,3); c.lift_to_precision(8)
2 + 3*5 + 0(5^8)
sage: c.lift_to_precision().precision_relative() == R.precision_cap()
True
```

numerator()

Return the numerator of this element, normalized in such a way that $x = x.numerator()/x.denominator()$ always holds true.

EXAMPLES:

```
sage: K = Qp(7, 5)
sage: x = K(1/21)
```

(continues on next page)

(continued from previous page)

```
sage: x.numerator()
5 + 4*7 + 4*7^2 + 4*7^3 + 4*7^4 + 0(7^5)

sage: x == x.numerator() / x.denominator()
True
```

Note that the numerator lives in the ring of integers:

```
sage: x.numerator().parent()
7-adic Ring with capped relative precision 5
```

valuation()

Return the valuation of this element.

EXAMPLES:

```
sage: R = Zp(7)
sage: x = R(7); x
7 + 0(7^21)
sage: x.valuation()
1
```

super_categories()

EXAMPLES:

```
sage: CompleteDiscreteValuationRings().super_categories()
[Category of discrete valuation rings]
```

3.27 Complex reflection groups

class `sage.categories.complex_reflection_groups.ComplexReflectionGroups`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of complex reflection groups.

Let V be a complex vector space. A *complex reflection* is an element of $GL(V)$ fixing an hyperplane pointwise and acting by multiplication by a root of unity on a complementary line.

A *complex reflection group* is a group W that is (isomorphic to) a subgroup of some general linear group $GL(V)$ generated by a distinguished set of complex reflections.

The dimension of V is the *rank* of W .

For a comprehensive treatment of complex reflection groups and many definitions and theorems used here, we refer to [LT2009]. See also [Wikipedia article Reflection_group](#).

See also:

`ReflectionGroup()` for usage examples of this category.

EXAMPLES:

```
sage: from sage.categories.complex_reflection_groups import ComplexReflectionGroups
sage: ComplexReflectionGroups()
Category of complex reflection groups
```

(continues on next page)

(continued from previous page)

```

sage: ComplexReflectionGroups().super_categories()
[Category of complex reflection or generalized coxeter groups]
sage: ComplexReflectionGroups().all_super_categories()
[Category of complex reflection groups,
Category of complex reflection or generalized coxeter groups,
Category of groups,
Category of monoids,
Category of finitely generated semigroups,
Category of semigroups,
Category of finitely generated magmas,
Category of inverse unital magmas,
Category of unital magmas,
Category of magmas,
Category of enumerated sets,
Category of sets,
Category of sets with partial maps,
Category of objects]

```

An example of a reflection group:

```

sage: W = ComplexReflectionGroups().example(); W
5-colored permutations of size 3

```

W is in the category of complex reflection groups:

```

sage: W in ComplexReflectionGroups()
True

```

Finite

alias of `sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups`

class ParentMethods

Bases: object

rank()

Return the rank of self.

The rank of self is the dimension of the smallest faithful reflection representation of self.

EXAMPLES:

```

sage: W = CoxeterGroups().example(); W
The symmetric group on {0, ..., 3}
sage: W.rank()
3

```

additional_structure()

Return None.

Indeed, all the structure complex reflection groups have in addition to groups (simple reflections, ...) is already defined in the super category.

See also:

`Category.additional_structure()`

EXAMPLES:

```
sage: from sage.categories.complex_reflection_groups import ↵
↵ComplexReflectionGroups
sage: ComplexReflectionGroups().additional_structure()
```

example()

Return an example of a complex reflection group.

EXAMPLES:

```
sage: from sage.categories.complex_reflection_groups import ↵
↵ComplexReflectionGroups
sage: ComplexReflectionGroups().example()
5-colored permutations of size 3
```

super_categories()

Return the super categories of self.

EXAMPLES:

```
sage: from sage.categories.complex_reflection_groups import ↵
↵ComplexReflectionGroups
sage: ComplexReflectionGroups().super_categories()
[Category of complex reflection or generalized coxeter groups]
```

3.28 Common category for Generalized Coxeter Groups or Complex Reflection Groups

class `sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups`

Bases: `sage.categories.category_singleton.Category_singleton`

The category of complex reflection groups or generalized Coxeter groups.

Finite Coxeter groups can be defined equivalently as groups generated by reflections, or by presentations. Over the last decades, the theory has been generalized in both directions, leading to the study of (finite) complex reflection groups on the one hand, and (finite) generalized Coxeter groups on the other hand. Many of the features remain similar, yet, in the current state of the art, there is no general theory covering both directions.

This is reflected by the name of this category which is about factoring out the common code, tests, and declarations.

A group in this category has:

- A distinguished finite set of generators $(s_i)_I$, called *simple reflections*. The set I is called the *index set*. The name “reflection” is somewhat of an abuse as they can have higher order; still, they are all of finite order: $s_i^k = 1$ for some k .
- A collection of *distinguished reflections* which are the conjugates of the simple reflections. For complex reflection groups, they are in one-to-one correspondence with the reflection hyperplanes and share the same index set.
- A collection of *reflections* which are the conjugates of all the non trivial powers of the simple reflections.

The usual notions of reduced words, length, irreducibility, etc can be canonically defined from the above.

The following methods must be implemented:

- `ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods.index_set()`
- `ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods.simple_reflection()`

Optionally one can define analog methods for distinguished reflections and reflections (see below).

At least one of the following methods must be implemented:

- `ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods.apply_simple_reflection()`
- `ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods.apply_simple_reflection_left()`
- `ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods.apply_simple_reflection_right()`
- `ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods._mul_()`

It's recommended to implement either `_mul_` or both `apply_simple_reflection_left` and `apply_simple_reflection_right`.

See also:

- `complex_reflection_groups.ComplexReflectionGroups`
- `generalized_coxeter_groups.GeneralizedCoxeterGroups`

EXAMPLES:

```
sage: from sage.categories.complex_reflection_or_generalized_coxeter_groups import_
↳ComplexReflectionOrGeneralizedCoxeterGroups
sage: C = ComplexReflectionOrGeneralizedCoxeterGroups(); C
Category of complex reflection or generalized coxeter groups
sage: C.super_categories()
[Category of finitely generated enumerated groups]

sage: C.required_methods()
{'element': {'optional': ['reflection_length'],
                  'required': []},
 'parent': {'optional': ['distinguished_reflection', 'hyperplane_index_set',
                        'irreducible_components',
                        'reflection', 'reflection_index_set'],
            'required': ['__contains__', 'index_set']}}
```

class ElementMethods

Bases: object

apply_conjugation_by_simple_reflection(*i*)

Conjugate self by the *i*-th simple reflection.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3])
sage: w = W.from_reduced_word([3, 1, 2, 1])
sage: w.apply_conjugation_by_simple_reflection(1).reduced_word()
[3, 2]
```

apply_reflections(*word*, *side*='right', *word_type*='all')

Return the result of the (left/right) multiplication of self by word.

INPUT:

- `word` – a sequence of indices of reflections
- `side` – (default: `'right'`) indicates multiplying from left or right
- `word_type` – (optional, default: `'all'`): either `'simple'`, `'distinguished'`, or `'all'`

EXAMPLES:

```

sage: W = ReflectionGroup((1,1,3))           # optional - gap3
sage: W.one().apply_reflections([1])        # optional - gap3
(1,4)(2,3)(5,6)
sage: W.one().apply_reflections([2])        # optional - gap3
(1,3)(2,5)(4,6)
sage: W.one().apply_reflections([2,1])      # optional - gap3
(1,2,6)(3,4,5)

sage: W = CoxeterGroups().example()
sage: w = W.an_element(); w
(1, 2, 3, 0)
sage: w.apply_reflections([0,1], word_type='simple')
(2, 3, 1, 0)
sage: w
(1, 2, 3, 0)
sage: w.apply_reflections([0,1], side='left', word_type='simple')
(0, 1, 3, 2)

sage: W = WeylGroup("A3", prefix='s')
sage: w = W.an_element(); w
s1*s2*s3
sage: AS = W.domain()
sage: r1 = AS.roots()[4]
sage: r1
(0, 1, 0, -1)
sage: r2 = AS.roots()[5]
sage: r2
(0, 0, 1, -1)
sage: w.apply_reflections([r1, r2], word_type='all')
s1

sage: W = ReflectionGroup((1,1,3))           # optional - gap3
sage: W.one().apply_reflections([1], word_type='distinguished') #_
↳optional - gap3
(1,4)(2,3)(5,6)
sage: W.one().apply_reflections([2], word_type='distinguished') #_
↳optional - gap3
(1,3)(2,5)(4,6)
sage: W.one().apply_reflections([3], word_type='distinguished') #_
↳optional - gap3
(1,5)(2,4)(3,6)
sage: W.one().apply_reflections([2,1], word_type='distinguished') #_
↳optional - gap3
(1,2,6)(3,4,5)

```

(continues on next page)

(continued from previous page)

```

sage: W = ReflectionGroup((1,1,3), hyperplane_index_set=['A','B','C']); W
↪# optional - gap3
Irreducible real reflection group of rank 2 and type A2
sage: W.one().apply_reflections(['A'], word_type='distinguished') #_
↪optional - gap3
(1,4)(2,3)(5,6)

```

apply_simple_reflection(*i*, *side*='right')

Return self multiplied by the simple reflection s[i].

INPUT:

- *i* – an element of the index set
- *side* – (default: "right") "left" or "right"

This default implementation simply calls `apply_simple_reflection_left()` or `apply_simple_reflection_right()`.

EXAMPLES:

```

sage: W = CoxeterGroups().example()
sage: w = W.an_element(); w
(1, 2, 3, 0)
sage: w.apply_simple_reflection(0, side = "left")
(0, 2, 3, 1)
sage: w.apply_simple_reflection(1, side = "left")
(2, 1, 3, 0)
sage: w.apply_simple_reflection(2, side = "left")
(1, 3, 2, 0)

sage: w.apply_simple_reflection(0, side = "right")
(2, 1, 3, 0)
sage: w.apply_simple_reflection(1, side = "right")
(1, 3, 2, 0)
sage: w.apply_simple_reflection(2, side = "right")
(1, 2, 0, 3)

```

By default, side is "right":

```

sage: w.apply_simple_reflection(0)
(2, 1, 3, 0)

```

Some tests with a complex reflection group:

```

sage: from sage.categories.complex_reflection_groups import _
↪ComplexReflectionGroups
sage: W = ComplexReflectionGroups().example(); W
5-colored permutations of size 3
sage: w = W.an_element(); w
[[1, 0, 0], [3, 1, 2]]
sage: w.apply_simple_reflection(1, side="left")
[[0, 1, 0], [1, 3, 2]]
sage: w.apply_simple_reflection(2, side="left")
[[1, 0, 0], [3, 2, 1]]
sage: w.apply_simple_reflection(3, side="left")

```

(continues on next page)

(continued from previous page)

```

[[1, 0, 1], [3, 1, 2]]
sage: w.apply_simple_reflection(1, side="right")
[[1, 0, 0], [3, 2, 1]]
sage: w.apply_simple_reflection(2, side="right")
[[1, 0, 0], [2, 1, 3]]
sage: w.apply_simple_reflection(3, side="right")
[[2, 0, 0], [3, 1, 2]]

```

apply_simple_reflection_left(*i*)

Return `self` multiplied by the simple reflection `s[i]` on the left.

This low level method is used intensively. Coxeter groups are encouraged to override this straightforward implementation whenever a faster approach exists.

EXAMPLES:

```

sage: W = CoxeterGroups().example()
sage: w = W.an_element(); w
(1, 2, 3, 0)
sage: w.apply_simple_reflection_left(0)
(0, 2, 3, 1)
sage: w.apply_simple_reflection_left(1)
(2, 1, 3, 0)
sage: w.apply_simple_reflection_left(2)
(1, 3, 2, 0)

```

EXAMPLES:

```

sage: from sage.categories.complex_reflection_groups import _
↳ComplexReflectionGroups
sage: W = ComplexReflectionGroups().example()
sage: w = W.an_element(); w
[[1, 0, 0], [3, 1, 2]]
sage: w.apply_simple_reflection_left(1)
[[0, 1, 0], [1, 3, 2]]
sage: w.apply_simple_reflection_left(2)
[[1, 0, 0], [3, 2, 1]]
sage: w.apply_simple_reflection_left(3)
[[1, 0, 1], [3, 1, 2]]

```

apply_simple_reflection_right(*i*)

Return `self` multiplied by the simple reflection `s[i]` on the right.

This low level method is used intensively. Coxeter groups are encouraged to override this straightforward implementation whenever a faster approach exists.

EXAMPLES:

```

sage: W=CoxeterGroups().example()
sage: w = W.an_element(); w
(1, 2, 3, 0)
sage: w.apply_simple_reflection_right(0)
(2, 1, 3, 0)
sage: w.apply_simple_reflection_right(1)

```

(continues on next page)

(continued from previous page)

```

(1, 3, 2, 0)
sage: w.apply_simple_reflection_right(2)
(1, 2, 0, 3)

sage: from sage.categories.complex_reflection_groups import _
↳ComplexReflectionGroups
sage: W = ComplexReflectionGroups().example()
sage: w = W.an_element(); w
[[1, 0, 0], [3, 1, 2]]
sage: w.apply_simple_reflection_right(1)
[[1, 0, 0], [3, 2, 1]]
sage: w.apply_simple_reflection_right(2)
[[1, 0, 0], [2, 1, 3]]
sage: w.apply_simple_reflection_right(3)
[[2, 0, 0], [3, 1, 2]]

```

apply_simple_reflections(*word*, *side*='right', *type*='simple')

Return the result of the (left/right) multiplication of *self* by *word*.

INPUT:

- *word* – a sequence of indices of simple reflections
- *side* – (default: 'right') indicates multiplying from left or right

This is a specialized implementation of [apply_reflections\(\)](#) for the simple reflections. The rationale for its existence are:

- It can take advantage of `apply_simple_reflection`, which often is less expensive than computing a product.
- It reduced burden on implementations that would want to provide an optimized version of this method.

EXAMPLES:

```

sage: W = CoxeterGroups().example()
sage: w = W.an_element(); w
(1, 2, 3, 0)
sage: w.apply_simple_reflections([0,1])
(2, 3, 1, 0)
sage: w
(1, 2, 3, 0)
sage: w.apply_simple_reflections([0,1],side='left')
(0, 1, 3, 2)

```

inverse()

Return the inverse of *self*.

EXAMPLES:

```

sage: W = WeylGroup(['B',7])
sage: w = W.an_element()
sage: u = w.inverse()
sage: u == ~w
True
sage: u * w == w * u
True
sage: u * w

```

(continues on next page)

(continued from previous page)

```
[1 0 0 0 0 0 0]
[0 1 0 0 0 0 0]
[0 0 1 0 0 0 0]
[0 0 0 1 0 0 0]
[0 0 0 0 1 0 0]
[0 0 0 0 0 1 0]
[0 0 0 0 0 0 1]
```

is_reflection()Return whether `self` is a reflection.

EXAMPLES:

```
sage: W = ReflectionGroup((1,1,4)) # optional - gap3
sage: [t.is_reflection() for t in W.reflections()] # optional - gap3
[True, True, True, True, True]
sage: len([t for t in W.reflections() if t.is_reflection()]) # optional -
→ gap3
6

sage: W = ReflectionGroup((2,1,3)) # optional - gap3
sage: [t.is_reflection() for t in W.reflections()] # optional - gap3
[True, True, True, True, True, True, True, True, True]
sage: len([t for t in W.reflections() if t.is_reflection()]) # optional -
→ gap3
9
```

reflection_length()Return the reflection length of `self`.This is the minimal length of a factorization of `self` into reflections.

EXAMPLES:

```
sage: W = ReflectionGroup((1,1,2)) # optional - gap3
sage: sorted([t.reflection_length() for t in W]) # optional - gap3
[0, 1]

sage: W = ReflectionGroup((2,1,2)) # optional - gap3
sage: sorted([t.reflection_length() for t in W]) # optional - gap3
[0, 1, 1, 1, 1, 2, 2, 2]

sage: W = ReflectionGroup((3,1,2)) # optional - gap3
sage: sorted([t.reflection_length() for t in W]) # optional - gap3
[0, 1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2]

sage: W = ReflectionGroup((2,2,2)) # optional - gap3
sage: sorted([t.reflection_length() for t in W]) # optional - gap3
[0, 1, 1, 2]
```

class Irreducible(*base_category*)Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`**class ParentMethods**Bases: `object`

irreducible_components()

Return a list containing all irreducible components of `self` as finite reflection groups.

EXAMPLES:

```
sage: W = ColoredPermutations(4, 3)
sage: W.irreducible_components()
[4-colored permutations of size 3]
```

class ParentMethods

Bases: object

distinguished_reflection(*i*)

Return the *i*-th distinguished reflection of `self`.

INPUT:

- *i* – an element of the index set of the distinguished reflections.

See also:

- `distinguished_reflections()`
- `hyperplane_index_set()`

EXAMPLES:

```
sage: W = ReflectionGroup((1,1,4), hyperplane_index_set=('a','b','c','d','e
↳','f')) # optional - gap3
sage: for i in W.hyperplane_index_set(): # optional -
↳gap3
.....:     print('%s %s'%(i, W.distinguished_reflection(i))) # optional -
↳gap3
a (1,7)(2,4)(5,6)(8,10)(11,12)
b (1,4)(2,8)(3,5)(7,10)(9,11)
c (2,5)(3,9)(4,6)(8,11)(10,12)
d (1,8)(2,7)(3,6)(4,10)(9,12)
e (1,6)(2,9)(3,8)(5,11)(7,12)
f (1,11)(3,10)(4,9)(5,7)(6,12)
```

distinguished_reflections()

Return a finite family containing the distinguished reflections of `self`, indexed by `hyperplane_index_set()`.

A *distinguished reflection* is a conjugate of a simple reflection. For a Coxeter group, reflections and distinguished reflections coincide. For a Complex reflection groups this is a reflection acting on the complement of the fixed hyperplane H as $\exp(2\pi i/n)$, where n is the order of the reflection subgroup fixing H .

See also:

- `distinguished_reflection()`
- `hyperplane_index_set()`

EXAMPLES:

```
sage: W = ReflectionGroup((1,1,3)) # optional - gap3
sage: distinguished_reflections = W.distinguished_reflections() # optional -
↳ gap3
sage: for index in sorted(distinguished_reflections.keys()): #
↳ optional - gap3
```

(continues on next page)

(continued from previous page)

```

.....:     print('%s %s'%(index, distinguished_reflections[index])) #_
↳optional - gap3
1 (1,4)(2,3)(5,6)
2 (1,3)(2,5)(4,6)
3 (1,5)(2,4)(3,6)

sage: W = ReflectionGroup((1,1,3),hyperplane_index_set=['a','b','c']) #_
↳optional - gap3
sage: distinguished_reflections = W.distinguished_reflections() # optional -
↳ gap3
sage: for index in sorted(distinguished_reflections.keys()): #_
↳optional - gap3
.....:     print('%s %s'%(index, distinguished_reflections[index])) #_
↳optional - gap3
a (1,4)(2,3)(5,6)
b (1,3)(2,5)(4,6)
c (1,5)(2,4)(3,6)

sage: W = ReflectionGroup((3,1,1)) # optional - gap3
sage: distinguished_reflections = W.distinguished_reflections() # optional -
↳ gap3
sage: for index in sorted(distinguished_reflections.keys()): #_
↳optional - gap3
.....:     print('%s %s'%(index, distinguished_reflections[index])) #_
↳optional - gap3
1 (1,2,3)

sage: W = ReflectionGroup((1,1,3), (3,1,2)) # optional - gap3
sage: distinguished_reflections = W.distinguished_reflections() # optional -
↳ gap3
sage: for index in sorted(distinguished_reflections.keys()): # optional -
↳ gap3
.....:     print('%s %s'%(index, distinguished_reflections[index])) #_
↳optional - gap3
1 (1,6)(2,5)(7,8)
2 (1,5)(2,7)(6,8)
3 (3,9,15)(4,10,16)(12,17,23)(14,18,24)(20,25,29)(21,22,26)(27,28,30)
4 (3,11)(4,12)(9,13)(10,14)(15,19)(16,20)(17,21)(18,22)(23,27)(24,28)(25,
↳26)(29,30)
5 (1,7)(2,6)(5,8)
6 (3,19)(4,25)(9,11)(10,17)(12,28)(13,15)(14,30)(16,18)(20,27)(21,29)(22,
↳23)(24,26)
7 (4,21,27)(10,22,28)(11,13,19)(12,14,20)(16,26,30)(17,18,25)(23,24,29)
8 (3,13)(4,24)(9,19)(10,29)(11,15)(12,26)(14,21)(16,23)(17,30)(18,27)(20,
↳22)(25,28)

```

from_reduced_word(word, word_type='simple')

Return an element of self from its (reduced) word.

INPUT:

- word – a list (or iterable) of elements of the index set of self (resp. of the distinguished or of all reflections)
- word_type – (optional, default: 'simple'): either 'simple', 'distinguished', or 'all'

If `word` is $[i_1, i_2, \dots, i_k]$, then this returns the corresponding product of simple reflections $s_{i_1} s_{i_2} \cdots s_{i_k}$.

If `word_type` is 'distinguished' (resp. 'all'), then the product of the distinguished reflections (resp. all reflections) is returned.

Note: The main use case is for constructing elements from reduced words, hence the name of this method. However, the input word need *not* be reduced.

See also:

- `index_set()`
- `reflection_index_set()`
- `hyperplane_index_set()`
- `apply_simple_reflections()`
- `reduced_word()`
- `_test_reduced_word()`

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: W
The symmetric group on {0, ..., 3}
sage: s = W.simple_reflections()
sage: W.from_reduced_word([0,2,0,1])
(0, 3, 1, 2)
sage: W.from_reduced_word((0,2,0,1))
(0, 3, 1, 2)
sage: s[0]*s[2]*s[0]*s[1]
(0, 3, 1, 2)
```

We now experiment with the different values for `word_type` for the colored symmetric group:

```
sage: W = ColoredPermutations(1,4)
sage: W.from_reduced_word([1,2,1,2,1,2])
[[0, 0, 0, 0], [1, 2, 3, 4]]

sage: W.from_reduced_word([1, 2, 3]).reduced_word()
[1, 2, 3]

sage: W = WeylGroup("A3", prefix='s')
sage: AS = W.domain()
sage: r1 = AS.roots()[4]
sage: r1
(0, 1, 0, -1)
sage: r2 = AS.roots()[5]
sage: r2
(0, 0, 1, -1)
sage: W.from_reduced_word([r1, r2], word_type='all')
s3*s2

sage: W = WeylGroup("G2", prefix='s')
sage: W.from_reduced_word(W.domain().positive_roots(), word_type='all')
s1*s2
```

(continues on next page)

(continued from previous page)

```

sage: W = ReflectionGroup((1,1,4))           # optional - gap3
sage: W.from_reduced_word([1,2,3], word_type='all').reduced_word() #_
↳ optional - gap3
[1, 2, 3]

sage: W.from_reduced_word([1,2,3], word_type='all').reduced_word_in_
↳ reflections() # optional - gap3
[1, 2, 3]

sage: W.from_reduced_word([1,2,3]).reduced_word_in_reflections() #_
↳ optional - gap3
[1, 2, 3]

```

group_generators()

Return the simple reflections of `self`, as distinguished group generators.

See also:

- `simple_reflections()`
- `Groups.ParentMethods.group_generators()`
- `Semigroups.ParentMethods.semigroup_generators()`

EXAMPLES:

```

sage: D10 = FiniteCoxeterGroups().example(10)
sage: D10.group_generators()
Finite family {1: (1,), 2: (2,)}
sage: SymmetricGroup(5).group_generators()
Finite family {1: (1,2), 2: (2,3), 3: (3,4), 4: (4,5)}

sage: W = ColoredPermutations(3,2)
sage: W.group_generators()
Finite family {1: [[0, 0],
                  [2, 1]],
              2: [[0, 1],
                  [1, 2]]}

```

The simple reflections are also semigroup generators, even for an infinite group:

```

sage: W = WeylGroup(["A", 2, 1])
sage: W.semigroup_generators()
Finite family {0: [-1  1  1]
                  [ 0  1  0]
                  [ 0  0  1],
              1: [ 1  0  0]
                  [ 1 -1  1]
                  [ 0  0  1],
              2: [ 1  0  0]
                  [ 0  1  0]
                  [ 1  1 -1]}

```

hyperplane_index_set()

Return the index set of the distinguished reflections of `self`.

This is also the index set of the reflection hyperplanes of `self`, hence the name. This name is slightly abusive since the concept of reflection hyperplanes is not defined for all generalized Coxeter groups. However for all practical purposes this is only used for complex reflection groups, and there this is the desirable name.

See also:

- `distinguished_reflection()`
- `distinguished_reflections()`

EXAMPLES:

```
sage: W = ReflectionGroup((1,1,4)) # optional - gap3
sage: W.hyperplane_index_set() # optional - gap3
(1, 2, 3, 4, 5, 6)
sage: W = ReflectionGroup((1,1,4), hyperplane_index_set=[1,3,'asdf',7,9,
↪11]) # optional - gap3
sage: W.hyperplane_index_set() # optional - gap3
(1, 3, 'asdf', 7, 9, 11)
sage: W = ReflectionGroup((1,1,4), hyperplane_index_set=('a','b','c','d','e
↪','f')) # optional - gap3
sage: W.hyperplane_index_set() # optional - gap3
('a', 'b', 'c', 'd', 'e', 'f')
```

index_set()

Return the index set of (the simple reflections of) `self`, as a list (or iterable).

See also:

- `simple_reflection()`
- `simple_reflections()`

EXAMPLES:

```
sage: W = CoxeterGroups().Finite().example(); W
The 5-th dihedral group of order 10
sage: W.index_set()
(1, 2)

sage: W = ColoredPermutations(1, 4)
sage: W.index_set()
(1, 2, 3)
sage: W = ReflectionGroup((1,1,4), index_set=[1,3,'asdf']) # optional -
↪gap3
sage: W.index_set() # optional - gap3
(1, 3, 'asdf')
sage: W = ReflectionGroup((1,1,4), index_set=('a','b','c')) # optional -
↪gap3
sage: W.index_set() # optional - gap3
('a', 'b', 'c')
```

irreducible_component_index_sets()

Return a list containing the index sets of the irreducible components of `self` as finite reflection groups.

EXAMPLES:

```

sage: W = ReflectionGroup([1,1,3], [3,1,3], 4); W      # optional - gap3
Reducible complex reflection group of rank 7 and type A2 x G(3,1,3) x ST4
sage: sorted(W.irreducible_component_index_sets())    # optional - gap3
[[1, 2], [3, 4, 5], [6, 7]]

```

ALGORITHM:

Take the connected components of the graph on the index set with edges (i, j) , where $s[i]$ and $s[j]$ do not commute.

irreducible_components()

Return the irreducible components of `self` as finite reflection groups.

EXAMPLES:

```

sage: W = ReflectionGroup([1,1,3], [3,1,3], 4)      # optional - gap3
sage: W.irreducible_components()                    # optional - gap3
[Irreducible real reflection group of rank 2 and type A2,
 Irreducible complex reflection group of rank 3 and type G(3,1,3),
 Irreducible complex reflection group of rank 2 and type ST4]

```

is_irreducible()

Return True if `self` is irreducible.

EXAMPLES:

```

sage: W = ColoredPermutations(1,3); W
1-colored permutations of size 3
sage: W.is_irreducible()
True

sage: W = ReflectionGroup((1,1,3),(2,1,3)); W      # optional - gap3
Reducible real reflection group of rank 5 and type A2 x B3
sage: W.is_irreducible()                          # optional - gap3
False

```

is_reducible()

Return True if `self` is not irreducible.

EXAMPLES:

```

sage: W = ColoredPermutations(1,3); W
1-colored permutations of size 3
sage: W.is_reducible()
False

sage: W = ReflectionGroup((1,1,3), (2,1,3)); W    # optional - gap3
Reducible real reflection group of rank 5 and type A2 x B3
sage: W.is_reducible()                          # optional - gap3
True

```

number_of_irreducible_components()

Return the number of irreducible components of `self`.

EXAMPLES:

```

sage: SymmetricGroup(3).number_of_irreducible_components()
1

sage: ColoredPermutations(1,3).number_of_irreducible_components()
1

sage: ReflectionGroup((1,1,3),(2,1,3)).number_of_irreducible_components()
↪ # optional - gap3
2

```

number_of_simple_reflections()

Return the number of simple reflections of `self`.

EXAMPLES:

```

sage: W = ColoredPermutations(1,3)
sage: W.number_of_simple_reflections()
2

sage: W = ColoredPermutations(2,3)
sage: W.number_of_simple_reflections()
3

sage: W = ColoredPermutations(4,3)
sage: W.number_of_simple_reflections()
3

sage: W = ReflectionGroup((4,2,3)) # optional - gap3
sage: W.number_of_simple_reflections() # optional - gap3
4

```

reflection(*i*)

Return the i -th reflection of `self`.

For i in $1, \dots, N$, this gives the i -th reflection of `self`.

See also:

- `reflections_index_set()`
- `reflections()`

EXAMPLES:

```

sage: W = ReflectionGroup((1,1,4)) # optional - gap3
sage: for i in W.reflection_index_set(): # optional - gap3
.....:     print('%s %s'%(i, W.reflection(i))) # optional - gap3
1 (1,7)(2,4)(5,6)(8,10)(11,12)
2 (1,4)(2,8)(3,5)(7,10)(9,11)
3 (2,5)(3,9)(4,6)(8,11)(10,12)
4 (1,8)(2,7)(3,6)(4,10)(9,12)
5 (1,6)(2,9)(3,8)(5,11)(7,12)
6 (1,11)(3,10)(4,9)(5,7)(6,12)

```

reflection_index_set()

Return the index set of the reflections of `self`.

See also:

- `reflection()`
- `reflections()`

EXAMPLES:

```

sage: W = ReflectionGroup((1,1,4)) # optional - gap3
sage: W.reflection_index_set() # optional - gap3
(1, 2, 3, 4, 5, 6)
sage: W = ReflectionGroup((1,1,4), reflection_index_set=[1,3,'asdf',7,9,
↪11]) # optional - gap3
sage: W.reflection_index_set() # optional - gap3
(1, 3, 'asdf', 7, 9, 11)
sage: W = ReflectionGroup((1,1,4), reflection_index_set=('a','b','c','d','e
↪','f')) # optional - gap3
sage: W.reflection_index_set() # optional - gap3
('a', 'b', 'c', 'd', 'e', 'f')

```

reflections()

Return a finite family containing the reflections of `self`, indexed by `reflection_index_set()`.

See also:

- `reflection()`
- `reflection_index_set()`

EXAMPLES:

```

sage: W = ReflectionGroup((1,1,3)) # optional - gap3
sage: reflections = W.reflections() # optional - gap3
sage: for index in sorted(reflections.keys()): # optional - gap3
.....:     print('%s %s'%(index, reflections[index])) # optional - gap3
1 (1,4)(2,3)(5,6)
2 (1,3)(2,5)(4,6)
3 (1,5)(2,4)(3,6)

sage: W = ReflectionGroup((1,1,3),reflection_index_set=['a','b','c']) #_
↪optional - gap3
sage: reflections = W.reflections() # optional - gap3
sage: for index in sorted(reflections.keys()): # optional - gap3
.....:     print('%s %s'%(index, reflections[index])) # optional - gap3
a (1,4)(2,3)(5,6)
b (1,3)(2,5)(4,6)
c (1,5)(2,4)(3,6)

sage: W = ReflectionGroup((3,1,1)) # optional - gap3
sage: reflections = W.reflections() # optional - gap3
sage: for index in sorted(reflections.keys()): # optional - gap3
.....:     print('%s %s'%(index, reflections[index])) # optional - gap3
1 (1,2,3)
2 (1,3,2)

sage: W = ReflectionGroup((1,1,3), (3,1,2)) # optional - gap3
sage: reflections = W.reflections() # optional - gap3
sage: for index in sorted(reflections.keys()): # optional - gap3
.....:     print('%s %s'%(index, reflections[index])) # optional - gap3
1 (1,6)(2,5)(7,8)
2 (1,5)(2,7)(6,8)
3 (3,9,15)(4,10,16)(12,17,23)(14,18,24)(20,25,29)(21,22,26)(27,28,30)

```

(continues on next page)

(continued from previous page)

```

4 (3, 11)(4, 12)(9, 13)(10, 14)(15, 19)(16, 20)(17, 21)(18, 22)(23, 27)(24, 28)(25,
  ↪26)(29, 30)
5 (1, 7)(2, 6)(5, 8)
6 (3, 19)(4, 25)(9, 11)(10, 17)(12, 28)(13, 15)(14, 30)(16, 18)(20, 27)(21, 29)(22,
  ↪23)(24, 26)
7 (4, 21, 27)(10, 22, 28)(11, 13, 19)(12, 14, 20)(16, 26, 30)(17, 18, 25)(23, 24, 29)
8 (3, 13)(4, 24)(9, 19)(10, 29)(11, 15)(12, 26)(14, 21)(16, 23)(17, 30)(18, 27)(20,
  ↪22)(25, 28)
9 (3, 15, 9)(4, 16, 10)(12, 23, 17)(14, 24, 18)(20, 29, 25)(21, 26, 22)(27, 30, 28)
10 (4, 27, 21)(10, 28, 22)(11, 19, 13)(12, 20, 14)(16, 30, 26)(17, 25, 18)(23, 29, 24)

```

semigroup_generators()

Return the simple reflections of `self`, as distinguished group generators.

See also:

- `simple_reflections()`
- `Groups.ParentMethods.group_generators()`
- `Semigroups.ParentMethods.semigroup_generators()`

EXAMPLES:

```

sage: D10 = FiniteCoxeterGroups().example(10)
sage: D10.group_generators()
Finite family {1: (1,), 2: (2,)}
sage: SymmetricGroup(5).group_generators()
Finite family {1: (1,2), 2: (2,3), 3: (3,4), 4: (4,5)}

sage: W = ColoredPermutations(3,2)
sage: W.group_generators()
Finite family {1: [[0, 0],
                  [2, 1]],
               2: [[0, 1],
                  [1, 2]]}

```

The simple reflections are also semigroup generators, even for an infinite group:

```

sage: W = WeylGroup(["A", 2, 1])
sage: W.semigroup_generators()
Finite family {0: [-1 1 1]
                  [ 0 1 0]
                  [ 0 0 1],
               1: [ 1 0 0]
                  [ 1 -1 1]
                  [ 0 0 1],
               2: [ 1 0 0]
                  [ 0 1 0]
                  [ 1 1 -1]}

```

simple_reflection(*i*)

Return the i -th simple reflection s_i of `self`.

INPUT:

- i – an element from the index set

See also:

- `index_set()`
- `simple_reflections()`

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: W
The symmetric group on {0, ..., 3}
sage: W.simple_reflection(1)
(0, 2, 1, 3)
sage: s = W.simple_reflections()
sage: s[1]
(0, 2, 1, 3)

sage: W = ReflectionGroup((1,1,4), index_set=[1,3,'asdf']) # optional ->
->gap3
sage: for i in W.index_set(): # optional - gap3
....:     print('%s %s'%(i, W.simple_reflection(i))) # optional - gap3
1 (1,7)(2,4)(5,6)(8,10)(11,12)
3 (1,4)(2,8)(3,5)(7,10)(9,11)
asdf (2,5)(3,9)(4,6)(8,11)(10,12)
```

`simple_reflection_orders()`

Return the orders of the simple reflections.

EXAMPLES:

```
sage: W = WeylGroup(['B',3])
sage: W.simple_reflection_orders()
[2, 2, 2]
sage: W = CoxeterGroup(['C',4])
sage: W.simple_reflection_orders()
[2, 2, 2, 2]
sage: SymmetricGroup(5).simple_reflection_orders()
[2, 2, 2, 2]
sage: C = ColoredPermutations(4, 3)
sage: C.simple_reflection_orders()
[2, 2, 4]
```

`simple_reflections()`

Return the simple reflections $(s_i)_{i \in I}$ of `self` as a family indexed by `index_set()`.

See also:

- `simple_reflection()`
- `index_set()`

EXAMPLES:

For the symmetric group, we recognize the simple transpositions:

```
sage: W = SymmetricGroup(4); W
Symmetric group of order 4! as a permutation group
sage: s = W.simple_reflections()
sage: s
Finite family {1: (1,2), 2: (2,3), 3: (3,4)}
sage: s[1]
```

(continues on next page)

(continued from previous page)

```
(1,2)
sage: s[2]
(2,3)
sage: s[3]
(3,4)
```

Here are the simple reflections for a colored symmetric group and a reflection group:

```
sage: W = ColoredPermutations(1,3)
sage: W.simple_reflections()
Finite family {1: [[0, 0, 0], [2, 1, 3]], 2: [[0, 0, 0], [1, 3, 2]]}

sage: W = ReflectionGroup((1,1,3), index_set=['a','b']) # optional - gap3
sage: W.simple_reflections() # optional - gap3
Finite family {'a': (1,4)(2,3)(5,6), 'b': (1,3)(2,5)(4,6)}
```

This default implementation uses `index_set()` and `simple_reflection()`.

`some_elements()`

Implement `Sets.ParentMethods.some_elements()` by returning some typical elements of `self`.

The result is currently composed of the simple reflections together with the unit and the result of `an_element()`.

EXAMPLES:

```
sage: W = WeylGroup(['A',3])
sage: W.some_elements()
[
[0 1 0 0] [1 0 0 0] [1 0 0 0] [1 0 0 0] [0 0 0 1]
[1 0 0 0] [0 0 1 0] [0 1 0 0] [0 1 0 0] [1 0 0 0]
[0 0 1 0] [0 1 0 0] [0 0 0 1] [0 0 1 0] [0 1 0 0]
[0 0 0 1], [0 0 0 1], [0 0 1 0], [0 0 0 1], [0 0 1 0]
]

sage: W = ColoredPermutations(1,4)
sage: W.some_elements()
[[[0, 0, 0, 0], [2, 1, 3, 4]],
 [[0, 0, 0, 0], [1, 3, 2, 4]],
 [[0, 0, 0, 0], [1, 2, 4, 3]],
 [[0, 0, 0, 0], [1, 2, 3, 4]],
 [[0, 0, 0, 0], [4, 1, 2, 3]]]
```

class `SubcategoryMethods`

Bases: `object`

`Irreducible()`

Return the full subcategory of irreducible objects of `self`.

A complex reflection group, or generalized coxeter group is *reducible* if its simple reflections can be split in two sets X and Y such that the elements of X commute with that of Y . In particular, the group is then direct product of $\langle X \rangle$ and $\langle Y \rangle$. It's *irreducible* otherwise.

EXAMPLES:

```

sage: from sage.categories.complex_reflection_groups import_
↳ComplexReflectionGroups
sage: ComplexReflectionGroups().Irreducible()
Category of irreducible complex reflection groups
sage: CoxeterGroups().Irreducible()
Category of irreducible coxeter groups

```

super_categories()

Return the super categories of self.

EXAMPLES:

```

sage: from sage.categories.complex_reflection_groups import_
↳ComplexReflectionGroups
sage: ComplexReflectionGroups().super_categories()
[Category of complex reflection or generalized coxeter groups]

```

3.29 Coxeter Group Algebras

class `sage.categories.coxeter_group_algebras.CoxeterGroupAlgebras`(*category*, **args*)

Bases: `sage.categories.algebra_functor.AlgebrasCategory`

class ParentMethods

Bases: object

demazure_lusztig_eigenvectors(*q1*, *q2*)

Return the family of eigenvectors for the Cherednik operators.

INPUT:

- `self` – a finite Coxeter group W
- `q1`, `q2` – two elements of the ground ring K

The affine Hecke algebra $H_{q_1, q_2}(\bar{W})$ acts on the group algebra of W through the Demazure-Lusztig operators T_i . Its Cherednik operators Y^λ can be simultaneously diagonalized as long as q_1/q_2 is not a small root of unity [HST2008].

This method returns the family of joint eigenvectors, indexed by W .

See also:

- `demazure_lusztig_operators()`
- `sage.combinat.root_system.hecke_algebra_representation.CherednikOperatorsEigenvectors`

EXAMPLES:

```

sage: W = WeylGroup(["B", 2])
sage: W.element_class._repr_=lambda x: "".join(str(i) for i in x.reduced_
↳word())
sage: K = QQ['q1, q2'].fraction_field()
sage: q1, q2 = K.gens()
sage: KW = W.algebra(K)
sage: E = KW.demazure_lusztig_eigenvectors(q1, q2)
sage: E.keys()
Weyl Group of type ['B', 2] (as a matrix group acting on the ambient space)
sage: w = W.an_element()

```

(continues on next page)

(continued from previous page)

```
sage: E[w]
(q2/(-q1+q2))*2121 + ((-q2)/(-q1+q2))*121 - 212 + 12
```

demazure_lusztig_operator_on_basis(*w*, *i*, *q1*, *q2*, *side='right'*)

Return the result of applying the *i*-th Demazure Lusztig operator on *w*.

INPUT:

- *w* – an element of the Coxeter group
- *i* – an element of the index set
- *q1*, *q2* – two elements of the ground ring
- *bar* – a boolean (default False)

See `demazure_lusztig_operators()` for details.

EXAMPLES:

```
sage: W = WeylGroup(["B", 3])
sage: W.element_class._repr_ = lambda x: "".join(str(i) for i in x.reduced_
->word())
sage: K = QQ['q1,q2']
sage: q1, q2 = K.gens()
sage: KW = W.algebra(K)
sage: w = W.an_element()
sage: KW.demazure_lusztig_operator_on_basis(w, 0, q1, q2)
(-q2)*323123 + (q1+q2)*123
sage: KW.demazure_lusztig_operator_on_basis(w, 1, q1, q2)
q1*1231
sage: KW.demazure_lusztig_operator_on_basis(w, 2, q1, q2)
q1*1232
sage: KW.demazure_lusztig_operator_on_basis(w, 3, q1, q2)
(q1+q2)*123 + (-q2)*12
```

At $q_1 = 1$ and $q_2 = 0$ we recover the action of the isobaric divided differences π_i :

```
sage: KW.demazure_lusztig_operator_on_basis(w, 0, 1, 0)
123
sage: KW.demazure_lusztig_operator_on_basis(w, 1, 1, 0)
1231
sage: KW.demazure_lusztig_operator_on_basis(w, 2, 1, 0)
1232
sage: KW.demazure_lusztig_operator_on_basis(w, 3, 1, 0)
123
```

At $q_1 = 1$ and $q_2 = -1$ we recover the action of the simple reflection s_i :

```
sage: KW.demazure_lusztig_operator_on_basis(w, 0, 1, -1)
323123
sage: KW.demazure_lusztig_operator_on_basis(w, 1, 1, -1)
1231
sage: KW.demazure_lusztig_operator_on_basis(w, 2, 1, -1)
1232
sage: KW.demazure_lusztig_operator_on_basis(w, 3, 1, -1)
12
```

demazure_lusztig_operators($q1, q2, side='right', affine=True$)

Return the Demazure Lusztig operators acting on `self`.

INPUT:

- $q1, q2$ – two elements of the ground ring K
- `side` – "left" or "right" (default: "right"); which side to act upon
- `affine` – a boolean (default: True)

The Demazure-Lusztig operator T_i is the linear map $R \rightarrow R$ obtained by interpolating between the simple projection π_i (see `CoxeterGroups.ElementMethods.simple_projection()`) and the simple reflection s_i so that T_i has eigenvalues q_1 and q_2 :

$$(q_1 + q_2)\pi_i - q_2s_i.$$

The Demazure-Lusztig operators give the usual representation of the operators T_i of the q_1, q_2 Hecke algebra associated to the Coxeter group.

For a finite Coxeter group, and if `affine=True`, the Demazure-Lusztig operators T_1, \dots, T_n are completed by T_0 to implement the level 0 action of the affine Hecke algebra.

EXAMPLES:

```
sage: W = WeylGroup(["B", 3])
sage: W.element_class._repr_ = lambda x: "".join(str(i) for i in x.reduced_
↪word())
sage: K = QQ['q1, q2']
sage: q1, q2 = K.gens()
sage: KW = W.algebra(K)
sage: T = KW.demazure_lusztig_operators(q1, q2, affine=True)
sage: x = KW.monomial(W.an_element()); x
123
sage: T[0](x)
(-q2)*323123 + (q1+q2)*123
sage: T[1](x)
q1*1231
sage: T[2](x)
q1*1232
sage: T[3](x)
(q1+q2)*123 + (-q2)*12
sage: T._test_relations()
```

Note: For a finite Weyl group W , the level 0 action of the affine Weyl group \tilde{W} only depends on the Coxeter diagram of the affinization, not its Dynkin diagram. Hence it is possible to explore all cases using only untwisted affinizations.

3.30 Coxeter Groups

class `sage.categories.coxeter_groups.CoxeterGroups`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of Coxeter groups.

A *Coxeter group* is a group W with a distinguished (finite) family of involutions $(s_i)_{i \in I}$, called the *simple reflections*, subject to relations of the form $(s_i s_j)^{m_{i,j}} = 1$.

I is the *index set* of W and $|I|$ is the *rank* of W .

See [Wikipedia article Coxeter_group](#) for details.

EXAMPLES:

```
sage: C = CoxeterGroups(); C
Category of coxeter groups
sage: C.super_categories()
[Category of generalized coxeter groups]

sage: W = C.example(); W
The symmetric group on {0, ..., 3}

sage: W.simple_reflections()
Finite family {0: (1, 0, 2, 3), 1: (0, 2, 1, 3), 2: (0, 1, 3, 2)}
```

Here are some further examples:

```
sage: FiniteCoxeterGroups().example()
The 5-th dihedral group of order 10
sage: FiniteWeylGroups().example()
The symmetric group on {0, ..., 3}
sage: WeylGroup(["B", 3])
Weyl Group of type ['B', 3] (as a matrix group acting on the ambient space)

sage: S4 = SymmetricGroup(4); S4
Symmetric group of order 4! as a permutation group
sage: S4 in CoxeterGroups().Finite()
True
```

Those will eventually be also in this category:

```
sage: DihedralGroup(5)
Dihedral group of order 10 as a permutation group
```

Todo: add a demo of usual computations on Coxeter groups.

See also:

- `sage.combinat.root_system`
- [WeylGroups](#)
- [GeneralizedCoxeterGroups](#)

Warning: It is assumed that morphisms in this category preserve the distinguished choice of simple reflections. In particular, subobjects in this category are parabolic subgroups. In this sense, this category might be better named `Coxeter Systems`. In the long run we might want to have two distinct categories, one for Coxeter groups (with morphisms being just group morphisms) and one for Coxeter systems:

```
sage: CoxeterGroups().is_full_subcategory(Groups())
False
sage: from sage.categories.generalized_coxeter_groups import _
      ↪ GeneralizedCoxeterGroups
sage: CoxeterGroups().is_full_subcategory(GeneralizedCoxeterGroups())
True
```

Algebras

alias of `sage.categories.coxeter_group_algebras.CoxeterGroupAlgebras`

class ElementMethods

Bases: object

absolute_covers()

Return the list of covers of `self` in absolute order.

See also:

[`absolute_length\(\)`](#)

EXAMPLES:

```
sage: W = WeylGroup(["A", 3])
sage: s = W.simple_reflections()
sage: w0 = s[1]
sage: w1 = s[1]*s[2]*s[3]
sage: w0.absolute_covers()
[
 [0 0 1 0]  [0 1 0 0]  [0 1 0 0]  [0 0 0 1]  [0 1 0 0]
 [1 0 0 0]  [1 0 0 0]  [0 0 1 0]  [1 0 0 0]  [0 0 0 1]
 [0 1 0 0]  [0 0 0 1]  [1 0 0 0]  [0 0 1 0]  [0 0 1 0]
 [0 0 0 1], [0 0 1 0], [0 0 0 1], [0 1 0 0], [1 0 0 0]
]
```

absolute_le(*other*)

Return whether `self` is smaller than `other` in the absolute order.

A general reflection is an element of the form ws_iw^{-1} , where s_i is a simple reflection. The absolute order is defined analogously to the weak order but using general reflections rather than just simple reflections.

This partial order can be used to define noncrossing partitions associated with this Coxeter group.

See also:

[`absolute_length\(\)`](#)

EXAMPLES:

```
sage: W = WeylGroup(["A", 3])
sage: s = W.simple_reflections()
sage: w0 = s[1]
```

(continues on next page)

(continued from previous page)

```

sage: w1 = s[1]*s[2]*s[3]
sage: w0.absolute_le(w1)
True
sage: w1.absolute_le(w0)
False
sage: w1.absolute_le(w1)
True

```

absolute_length()

Return the absolute length of `self`.

The absolute length is the length of the shortest expression of the element as a product of reflections.

For permutations in the symmetric groups, the absolute length is the size minus the number of its disjoint cycles.

See also:

[absolute_le\(\)](#)

EXAMPLES:

```

sage: W = WeylGroup(["A", 3])
sage: s = W.simple_reflections()
sage: (s[1]*s[2]*s[3]).absolute_length()
3

sage: W = SymmetricGroup(4)
sage: s = W.simple_reflections()
sage: (s[3]*s[2]*s[1]).absolute_length()
3

```

apply_demazure_product(*element*, *side*='right', *length_increasing*=True)

Returns the Demazure or 0-Hecke product of `self` with another Coxeter group element.

See [CoxeterGroups.ParentMethods.simple_projections\(\)](#).

INPUT:

- **element** – either an element of the same Coxeter group as `self` or a tuple or a list (such as a reduced word) of elements from the index set of the Coxeter group.
- **side** – ‘left’ or ‘right’ (default: ‘right’); the side of `self` on which the element should be applied. If `side` is ‘left’ then the operation is applied on the left.
- **length_increasing** – a boolean (default True) whether to act length increasingly or decreasingly

EXAMPLES:

```

sage: W = WeylGroup(['C', 4], prefix="s")
sage: v = W.from_reduced_word([1, 2, 3, 4, 3, 1])
sage: v.apply_demazure_product([1, 3, 4, 3, 3])
s4*s1*s2*s3*s4*s3*s1
sage: v.apply_demazure_product([1, 3, 4, 3], side='left')
s3*s4*s1*s2*s3*s4*s2*s3*s1
sage: v.apply_demazure_product((1, 3, 4, 3), side='left')
s3*s4*s1*s2*s3*s4*s2*s3*s1
sage: v.apply_demazure_product(v)
s2*s3*s4*s1*s2*s3*s4*s2*s3*s2*s1

```

apply_simple_projection(*i*, *side*='right', *length_increasing*=True)

INPUT:

- *i* - an element of the index set of the Coxeter group
- *side* - 'left' or 'right' (default: 'right')
- *length_increasing* - a boolean (default: True) specifying the direction of the projection

Returns the result of the application of the simple projection π_i (resp. $\bar{\pi}_i$) on *self*.

See `CoxeterGroups.ParentMethods.simple_projections()` for the definition of the simple projections.

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: w = W.an_element()
sage: w
(1, 2, 3, 0)
sage: w.apply_simple_projection(2)
(1, 2, 3, 0)
sage: w.apply_simple_projection(2, length_increasing=False)
(1, 2, 0, 3)
sage: W = WeylGroup(['C', 4], prefix="s")
sage: v = W.from_reduced_word([1, 2, 3, 4, 3, 1])
sage: v
s1*s2*s3*s4*s3*s1
sage: v.apply_simple_projection(2)
s1*s2*s3*s4*s3*s1*s2
sage: v.apply_simple_projection(2, side='left')
s1*s2*s3*s4*s3*s1
sage: v.apply_simple_projection(1, length_increasing = False)
s1*s2*s3*s4*s3
```

binary_factorizations(*predicate*=The constant function (...) -> True)

Return the set of all the factorizations $self = uv$ such that $l(self) = l(u) + l(v)$.

Iterating through this set is Constant Amortized Time (counting arithmetic operations in the Coxeter group as constant time) complexity, and memory linear in the length of *self*.

One can pass as optional argument a predicate *p* such that $p(u)$ implies $p(u')$ for any *u* left factor of *self* and *u'* left factor of *u*. Then this returns only the factorizations $self = uv$ such *p(u)* holds.

EXAMPLES:

We construct the set of all factorizations of the maximal element of the group:

```
sage: W = WeylGroup(['A', 3])
sage: s = W.simple_reflections()
sage: w0 = W.from_reduced_word([1, 2, 3, 1, 2, 1])
sage: w0.binary_factorizations().cardinality()
24
```

The same number of factorizations, by bounded length:

```
sage: [w0.binary_factorizations(lambda u: u.length() <= l).cardinality()
↪ for l in [-1, 0, 1, 2, 3, 4, 5, 6]]
[0, 1, 4, 9, 15, 20, 23, 24]
```

The number of factorizations of the elements just below the maximal element:

```
sage: [(s[i]*w0).binary_factorizations().cardinality() for i in [1,2,3]]
[12, 12, 12]
sage: w0.binary_factorizations(lambda u: False).cardinality()
0
```

bruhat_le(*other*)

Bruhat comparison

INPUT:

- *other* – an element of the same Coxeter group

OUTPUT: a boolean

Returns whether `self <= other` in the Bruhat order.

EXAMPLES:

```
sage: W = WeylGroup(["A", 3])
sage: u = W.from_reduced_word([1, 2, 1])
sage: v = W.from_reduced_word([1, 2, 3, 2, 1])
sage: u.bruhat_le(u)
True
sage: u.bruhat_le(v)
True
sage: v.bruhat_le(u)
False
sage: v.bruhat_le(v)
True
sage: s = W.simple_reflections()
sage: s[1].bruhat_le(W.one())
False
```

The implementation uses the equivalent condition that any reduced word for `other` contains a reduced word for `self` as subword. See Stembridge, A short derivation of the Möbius function for the Bruhat order. *J. Algebraic Combin.* 25 (2007), no. 2, 141–148, Proposition 1.1.

Complexity: $O(l * c)$, where l is the minimum of the lengths of u and of v , and c is the cost of the low level methods `first_descent()`, `has_descent()`, `apply_simple_reflection()`, etc. Those are typically $O(n)$, where n is the rank of the Coxeter group.

bruhat_lower_covers()Returns all elements that `self` covers in (strong) Bruhat order.

If $w = \text{self}$ has a descent at i , then the elements that w covers are exactly $\{ws_i, u_1s_i, u_2s_i, \dots, u_js_i\}$, where the u_k are elements that ws_i covers that also do not have a descent at i .

EXAMPLES:

```
sage: W = WeylGroup(["A", 3])
sage: w = W.from_reduced_word([3, 2, 3])
sage: print([v.reduced_word() for v in w.bruhat_lower_covers()])
[[3, 2], [2, 3]]

sage: W = WeylGroup(["A", 3])
sage: print([v.reduced_word() for v in W.simple_reflection(1).bruhat_lower_
->covers()])
[[]]
```

(continues on next page)

(continued from previous page)

```

sage: print([v.reduced_word() for v in W.one().bruhat_lower_covers()])
[]
sage: W = WeylGroup(["B", 4, 1])
sage: w = W.from_reduced_word([0, 2])
sage: print([v.reduced_word() for v in w.bruhat_lower_covers()])
[[2], [0]]
sage: W = WeylGroup("A3", prefix="s", implementation="permutation")
sage: [s1, s2, s3]=W.simple_reflections()
sage: (s1*s2*s3*s1).bruhat_lower_covers()
[s2*s1*s3, s1*s2*s1, s1*s2*s3]

```

We now show how to construct the Bruhat poset:

```

sage: W = WeylGroup(["A", 3])
sage: covers = tuple([u, v] for v in W for u in v.bruhat_lower_covers() )
sage: P = Poset((W, covers), cover_relations = True)
sage: P.show()

```

Alternatively, one can just use:

```

sage: P = W.bruhat_poset()

```

The algorithm is taken from Stembridge's 'coxeter/weyl' package for Maple.

bruhat_lower_covers_reflections()

Returns all 2-tuples of lower_covers and reflections (v, r) where v is covered by self and r is the reflection such that self = v r.

ALGORITHM:

See [bruhat_lower_covers\(\)](#)

EXAMPLES:

```

sage: W = WeylGroup(['A', 3], prefix="s")
sage: w = W.from_reduced_word([3, 1, 2, 1])
sage: w.bruhat_lower_covers_reflections()
[(s1*s2*s1, s1*s2*s3*s2*s1), (s3*s2*s1, s2), (s3*s1*s2, s1)]

```

bruhat_upper_covers()

Returns all elements that cover self in (strong) Bruhat order.

The algorithm works recursively, using the 'inverse' of the method described for lower covers [bruhat_lower_covers\(\)](#). Namely, it runs through all i in the index set. Let w equal self. If w has no right descent i , then ws_i is a cover; if w has a descent at i , then $u_j s_i$ is a cover of w where u_j is a cover of ws_i .

EXAMPLES:

```

sage: W = WeylGroup(['A', 3, 1], prefix="s")
sage: w = W.from_reduced_word([1, 2, 1])
sage: w.bruhat_upper_covers()
[s1*s2*s1*s0, s1*s2*s0*s1, s0*s1*s2*s1, s3*s1*s2*s1, s2*s3*s1*s2,
↪s1*s2*s3*s1]
sage: W = WeylGroup(['A', 3])

```

(continues on next page)

(continued from previous page)

```

sage: w = W.long_element()
sage: w.bruhat_upper_covers()
[]

sage: W = WeylGroup(['A', 3])
sage: w = W.from_reduced_word([1, 2, 1])
sage: S = [v for v in W if w in v.bruhat_lower_covers()]
sage: C = w.bruhat_upper_covers()
sage: set(S) == set(C)
True

```

bruhat_upper_covers_reflections()

Returns all 2-tuples of covers and reflections (v, r) where v covers `self` and r is the reflection such that `self = v r`.

ALGORITHM:

See `bruhat_upper_covers()`

EXAMPLES:

```

sage: W = WeylGroup(['A', 4], prefix="s")
sage: w = W.from_reduced_word([3, 1, 2, 1])
sage: w.bruhat_upper_covers_reflections()
[(s1*s2*s3*s2*s1, s3), (s2*s3*s1*s2*s1, s2*s3*s2), (s3*s4*s1*s2*s1, s4),
 ↪(s4*s3*s1*s2*s1, s1*s2*s3*s4*s3*s2*s1)]

```

canonical_matrix()

Return the matrix of `self` in the canonical faithful representation.

This is an n -dimension real faithful essential representation, where n is the number of generators of the Coxeter group. Note that this is not always the most natural matrix representation, for instance in type A_n .

EXAMPLES:

```

sage: W = WeylGroup(["A", 3])
sage: s = W.simple_reflections()
sage: (s[1]*s[2]*s[3]).canonical_matrix()
[ 0  0 -1]
[ 1  0 -1]
[ 0  1 -1]

```

coset_representative(*index_set*, *side*='right')

INPUT:

- `index_set` - a subset (or iterable) of the nodes of the Dynkin diagram
- `side` - 'left' or 'right'

Returns the unique shortest element of the Coxeter group W which is in the same left (resp. right) coset as `self`, with respect to the parabolic subgroup W_I .

EXAMPLES:

```

sage: W = CoxeterGroups().example(5)
sage: s = W.simple_reflections()
sage: w = s[2]*s[1]*s[3]

```

(continues on next page)

(continued from previous page)

```

sage: w.coset_representative([]).reduced_word()
[2, 3, 1]
sage: w.coset_representative([1]).reduced_word()
[2, 3]
sage: w.coset_representative([1,2]).reduced_word()
[2, 3]
sage: w.coset_representative([1,3]                ).reduced_word()
[2]
sage: w.coset_representative([2,3]                ).reduced_word()
[2, 1]
sage: w.coset_representative([1,2,3]              ).reduced_word()
[]
sage: w.coset_representative([], side='left').reduced_word()
[2, 3, 1]
sage: w.coset_representative([1], side='left').reduced_word()
[2, 3, 1]
sage: w.coset_representative([1,2], side='left').reduced_word()
[3]
sage: w.coset_representative([1,3], side='left').reduced_word()
[2, 3, 1]
sage: w.coset_representative([2,3], side='left').reduced_word()
[1]
sage: w.coset_representative([1,2,3], side='left').reduced_word()
[]

```

cover_reflections(*side='right'*)

Return the set of reflections t such that $\text{self} \cdot t$ covers self .

If side is 'left', $t \cdot \text{self}$ covers self .

EXAMPLES:

```

sage: W = WeylGroup(['A',4], prefix="s")
sage: w = W.from_reduced_word([3,1,2,1])
sage: w.cover_reflections()
[s3, s2*s3*s2, s4, s1*s2*s3*s4*s3*s2*s1]
sage: w.cover_reflections(side='left')
[s4, s2, s1*s2*s1, s3*s4*s3]

```

coxeter_sorting_word(*c*)

Return the c -sorting word of self .

For a Coxeter element c and an element w , the c -sorting word of w is the lexicographic minimal reduced expression of w in the infinite word c^∞ .

INPUT:

- c – a Coxeter element.

OUTPUT:

the c -sorting word of self as a list of integers.

EXAMPLES:

```

sage: W = CoxeterGroups().example()
sage: c = W.from_reduced_word([0,2,1])

```

(continues on next page)

(continued from previous page)

```
sage: w = W.from_reduced_word([1,2,1,0,1])
sage: w.coxeter_sorting_word(c)
[2, 1, 2, 0, 1]
```

deodhar_factor_element(*w*, *index_set*)

Returns Deodhar's Bruhat order factoring element.

INPUT:

- *w* is an element of the same Coxeter group W as `self`
- *index_set* is a subset of Dynkin nodes defining a parabolic subgroup W' of W

It is assumed that $v = \text{self}$ and w are minimum length coset representatives for W/W' such that $v \leq w$ in Bruhat order.

OUTPUT:

Deodhar's element $f(v, w)$ is the unique element of W' such that, for all v' and w' in W' , $vv' \leq ww'$ in W if and only if $v' \leq f(v, w) * w'$ in W' where $*$ is the Demazure product.

EXAMPLES:

```
sage: W = WeylGroup(['A', 5], prefix="s")
sage: v = W.from_reduced_word([5])
sage: w = W.from_reduced_word([4, 5, 2, 3, 1, 2])
sage: v.deodhar_factor_element(w, [1, 3, 4])
s3*s1
sage: W = WeylGroup(['C', 2])
sage: w = W.from_reduced_word([2, 1])
sage: w.deodhar_factor_element(W.from_reduced_word([2]), [1])
Traceback (most recent call last):
...
ValueError: [2, 1] is not of minimum length in its coset for the parabolic_
↪subgroup with index set [1]
```

REFERENCES:

- [Deo1987a]

deodhar_lift_down(*w*, *index_set*)

Letting $v = \text{self}$, given a Bruhat relation $v W' \geq w W'$ among cosets with respect to the subgroup W' given by the Dynkin node subset *index_set*, returns the Bruhat-maximum lift x of wW' such that $v \geq x$.

INPUT:

- *w* is an element of the same Coxeter group W as `self`.
- *index_set* is a subset of Dynkin nodes defining a parabolic subgroup W' .

OUTPUT:

The unique Bruhat-maximum element x in W such that $x W' = w W'$ and $v \geq x$.

See also:

[sage.categories.coxeter_groups.CoxeterGroups.ElementMethods.deodhar_lift_up\(\)](#)

EXAMPLES:

```
sage: W = WeylGroup(['A', 3], prefix="s")
sage: v = W.from_reduced_word([1, 2, 3, 2])
```

(continues on next page)

(continued from previous page)

```
sage: w = W.from_reduced_word([3,2])
sage: v.deodhar_lift_down(w, [3])
s2*s3*s2
```

deodhar_lift_up(*w, index_set*)

Letting $v = \text{self}$, given a Bruhat relation $v W' \leq w W'$ among cosets with respect to the subgroup W' given by the Dynkin node subset *index_set*, returns the Bruhat-minimum lift x of wW' such that $v \leq x$.

INPUT:

- *w* is an element of the same Coxeter group W as *self*.
- *index_set* is a subset of Dynkin nodes defining a parabolic subgroup W' .

OUTPUT:

The unique Bruhat-minimum element x in W such that $x W' = w W'$ and $v \leq x$.

See also:

[sage.categories.coxeter_groups.CoxeterGroups.ElementMethods.deodhar_lift_down\(\)](#)

EXAMPLES:

```
sage: W = WeylGroup(['A',3],prefix="s")
sage: v = W.from_reduced_word([1,2,3])
sage: w = W.from_reduced_word([1,3,2])
sage: v.deodhar_lift_up(w, [3])
s1*s2*s3*s2
```

descents(*side='right', index_set=None, positive=False*)

INPUT:

- *index_set* - a subset (as a list or iterable) of the nodes of the Dynkin diagram; (default: all of them)
- *side* - 'left' or 'right' (default: 'right')
- *positive* - a boolean (default: False)

Returns the descents of *self*, as a list of elements of the *index_set*.

The *index_set* option can be used to restrict to the parabolic subgroup indexed by *index_set*.

If *positive* is True, then returns the non-descents instead

Todo: find a better name for *positive*: complement? non_descent?

Caveat: the return type may change to some other iterable (tuple, ...) in the future. Please use keyword arguments also, as the order of the arguments may change as well.

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: s = W.simple_reflections()
sage: w = s[0]*s[1]
sage: w.descents()
[1]
sage: w = s[0]*s[2]
sage: w.descents()
[0, 2]
```

Todo: side, index_set, positive

first_descent (*side='right', index_set=None, positive=False*)

Return the first left (resp. right) descent of self, as an element of `index_set`, or None if there is none.

See `descents()` for a description of the options.

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: s = W.simple_reflections()
sage: w = s[2]*s[0]
sage: w.first_descent()
0
sage: w = s[0]*s[2]
sage: w.first_descent()
0
sage: w = s[0]*s[1]
sage: w.first_descent()
1
```

has_descent (*i, side='right', positive=False*)

Returns whether `i` is a (left/right) descent of self.

See `descents()` for a description of the options.

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: s = W.simple_reflections()
sage: w = s[0] * s[1] * s[2]
sage: w.has_descent(2)
True
sage: [ w.has_descent(i)           for i in [0,1,2] ]
[False, False, True]
sage: [ w.has_descent(i, side='left') for i in [0,1,2] ]
[True, False, False]
sage: [ w.has_descent(i, positive=True) for i in [0,1,2] ]
[True, True, False]
```

This default implementation delegates the work to `has_left_descent()` and `has_right_descent()`.

has_full_support ()

Return whether self has full support.

An element is said to have full support if its support contains all simple reflections.

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: w = W.from_reduced_word([1,2,1])
sage: w.has_full_support()
False
sage: w = W.from_reduced_word([1,2,1,0,1])
```

(continues on next page)

(continued from previous page)

```
sage: w.has_full_support()
True
```

has_left_descent(*i*)

Returns whether *i* is a left descent of self.

This default implementation uses that a left descent of *w* is a right descent of w^{-1} .

EXAMPLES:

```
sage: W = CoxeterGroups().example(); W
The symmetric group on {0, ..., 3}
sage: w = W.an_element(); w
(1, 2, 3, 0)
sage: w.has_left_descent(0)
True
sage: w.has_left_descent(1)
False
sage: w.has_left_descent(2)
False
```

has_right_descent(*i*)

Returns whether *i* is a right descent of self.

EXAMPLES:

```
sage: W = CoxeterGroups().example(); W
The symmetric group on {0, ..., 3}
sage: w = W.an_element(); w
(1, 2, 3, 0)
sage: w.has_right_descent(0)
False
sage: w.has_right_descent(1)
False
sage: w.has_right_descent(2)
True
```

inversions_as_reflections()

Returns the set of reflections *r* such that $\text{self } r < \text{self}$.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3], prefix="s")
sage: w = W.from_reduced_word([3, 1, 2, 1])
sage: w.inversions_as_reflections()
[s1, s1*s2*s1, s2, s1*s2*s3*s2*s1]
```

is_coxeter_sortable(*c*, *sorting_word=None*)

Return whether *self* is *c*-sortable.

Given a Coxeter element *c*, an element *w* is *c*-sortable if its *c*-sorting word decomposes into a sequence of weakly decreasing subwords of *c*.

INPUT:

- *c* – a Coxeter element.

- `sorting_word` – sorting word (default: None) used to not recompute the `c`-sorting word if already computed.

OUTPUT:

is self `c`-sortable

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: c = W.from_reduced_word([0,2,1])
sage: w = W.from_reduced_word([1,2,1,0,1])
sage: w.coxeter_sorting_word(c)
[2, 1, 2, 0, 1]
sage: w.is_coxeter_sortable(c)
False
sage: w = W.from_reduced_word([0,2,1,0,2])
sage: w.coxeter_sorting_word(c)
[2, 0, 1, 2, 0]
sage: w.is_coxeter_sortable(c)
True
sage: W = CoxeterGroup(['A',3])
sage: c = W.from_reduced_word([1,2,3])
sage: len([w for w in W if w.is_coxeter_sortable(c)]) # number of c-
↳ sortable elements in A_3 (Catalan number)
14
```

is_grassmannian(*side='right'*)

Return whether `self` is Grassmannian.

INPUT:

- `side` – “left” or “right” (default: “right”)

An element is Grassmannian if it has at most one descent on the right (resp. on the left).

EXAMPLES:

```
sage: W = CoxeterGroups().example(); W
The symmetric group on {0, ..., 3}
sage: s = W.simple_reflections()
sage: W.one().is_grassmannian()
True
sage: s[1].is_grassmannian()
True
sage: (s[1]*s[2]).is_grassmannian()
True
sage: (s[0]*s[1]).is_grassmannian()
True
sage: (s[1]*s[2]*s[1]).is_grassmannian()
False

sage: (s[0]*s[2]*s[1]).is_grassmannian(side="left")
False
sage: (s[0]*s[2]*s[1]).is_grassmannian(side="right")
True
sage: (s[0]*s[2]*s[1]).is_grassmannian()
True
```

left_inversions_as_reflections()

Returns the set of reflections r such that $r \text{ self} < \text{self}$.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3], prefix="s")
sage: w = W.from_reduced_word([3, 1, 2, 1])
sage: w.left_inversions_as_reflections()
[s1, s3, s1*s2*s3*s2*s1, s2*s3*s2]
```

length()

Return the length of `self`.

This is the minimal length of a product of simple reflections giving `self`.

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: s1 = W.simple_reflection(1)
sage: s2 = W.simple_reflection(2)
sage: s1.length()
1
sage: (s1*s2).length()
2
sage: W = CoxeterGroups().example()
sage: s = W.simple_reflections()
sage: w = s[0]*s[1]*s[0]
sage: w.length()
3
sage: W = CoxeterGroups().example()
sage: sum((x^w.length() for w in W) - expand(prod(sum(x^i for i in
↳ range(j+1)) for j in range(4)))) # This is scandalously slow!!!
0
```

See also:

[reduced_word\(\)](#)

Todo: Should use `reduced_word_iterator` (or `reverse_iterator`)

lower_cover_reflections(side='right')

Returns the reflections t such that `self` covers `self t`.

If `side` is 'left', `self` covers `t self`.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3], prefix="s")
sage: w = W.from_reduced_word([3, 1, 2, 1])
sage: w.lower_cover_reflections()
[s1*s2*s3*s2*s1, s2, s1]
sage: w.lower_cover_reflections(side='left')
[s2*s3*s2, s3, s1]
```

lower_covers(side='right', index_set=None)

Return all elements that `self` covers in weak order.

INPUT:

- `side` – ‘left’ or ‘right’ (default: ‘right’)
- `index_set` – a list of indices or None

OUTPUT: a list

EXAMPLES:

```
sage: W = WeylGroup(['A', 3])
sage: w = W.from_reduced_word([3, 2, 1])
sage: [x.reduced_word() for x in w.lower_covers()]
[[3, 2]]
```

To obtain covers for left weak order, set the option `side` to ‘left’:

```
sage: [x.reduced_word() for x in w.lower_covers(side='left')]
[[2, 1]]
sage: w = W.from_reduced_word([3, 2, 3, 1])
sage: [x.reduced_word() for x in w.lower_covers()]
[[2, 3, 2], [3, 2, 1]]
```

Covers w.r.t. a parabolic subgroup are obtained with the option `index_set`:

```
sage: [x.reduced_word() for x in w.lower_covers(index_set = [1, 2])]
[[2, 3, 2]]
sage: [x.reduced_word() for x in w.lower_covers(side='left')]
[[3, 2, 1], [2, 3, 1]]
```

min_demazure_product_greater(*element*)

Find the unique Bruhat-minimum element u such that $v \leq w * u$ where v is `self`, w is `element` and $*$ is the Demazure product.

INPUT:

- `element` is either an element of the same Coxeter group as `self` or a list (such as a reduced word) of elements from the index set of the Coxeter group.

EXAMPLES:

```
sage: W = WeylGroup(['A', 4], prefix="s")
sage: v = W.from_reduced_word([2, 3, 4, 1, 2])
sage: u = W.from_reduced_word([2, 3, 2, 1])
sage: v.min_demazure_product_greater(u)
s4*s2
sage: v.min_demazure_product_greater([2, 3, 2, 1])
s4*s2
sage: v.min_demazure_product_greater((2, 3, 2, 1))
s4*s2
```

reduced_word()

Return a reduced word for `self`.

This is a word $[i_1, i_2, \dots, i_k]$ of minimal length such that $s_{i_1} s_{i_2} \cdots s_{i_k} = \text{self}$, where the s_i are the simple reflections.

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: s = W.simple_reflections()
```

(continues on next page)

(continued from previous page)

```

sage: w = s[0]*s[1]*s[2]
sage: w.reduced_word()
[0, 1, 2]
sage: w = s[0]*s[2]
sage: w.reduced_word()
[2, 0]

```

See also:

- [reduced_words\(\)](#), [reduced_word_reverse_iterator\(\)](#),
- [length\(\)](#), [reduced_word_graph\(\)](#)

reduced_word_graph()

Return the reduced word graph of `self`.

The reduced word graph of an element w in a Coxeter group is the graph whose vertices are the reduced words for w (see [reduced_word\(\)](#) for a definition of this term), and which has an m -colored edge between two reduced words x and y whenever x and y differ by exactly one length- m braid move (with $m \geq 2$).

This graph is always connected (a theorem due to Tits) and has no multiple edges.

EXAMPLES:

```

sage: W = WeylGroup(['A', 3], prefix='s')
sage: w0 = W.long_element()
sage: G = w0.reduced_word_graph()
sage: G.num_verts()
16
sage: len(w0.reduced_words())
16
sage: G.num_edges()
18
sage: len([e for e in G.edges() if e[2] == 2])
10
sage: len([e for e in G.edges() if e[2] == 3])
8

```

See also:

[reduced_words\(\)](#), [reduced_word_reverse_iterator\(\)](#), [length\(\)](#), [reduced_word\(\)](#)

reduced_word_reverse_iterator()

Return a reverse iterator on a reduced word for `self`.

EXAMPLES:

```

sage: W = CoxeterGroups().example()
sage: s = W.simple_reflections()
sage: sigma = s[0]*s[1]*s[2]
sage: rI=sigma.reduced_word_reverse_iterator()
sage: [i for i in rI]
[2, 1, 0]
sage: s[0]*s[1]*s[2]==sigma
True
sage: sigma.length()
3

```

See also:

`reduced_word()`

Default implementation: recursively remove the first right descent until the identity is reached (see `first_descent()` and `apply_simple_reflection()`).

reduced_words()

Return all reduced words for self.

See `reduced_word()` for the definition of a reduced word.

The algorithm uses the Matsumoto property that any two reduced expressions are related by braid relations, see Theorem 3.3.1(ii) in [BB2005].

See also:

`braid_orbit()`

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: s = W.simple_reflections()
sage: w = s[0] * s[2]
sage: sorted(w.reduced_words())
[[0, 2], [2, 0]]

sage: W = WeylGroup(['E', 6])
sage: w = W.from_reduced_word([2, 3, 4, 2])
sage: sorted(w.reduced_words())
[[2, 3, 4, 2], [3, 2, 4, 2], [3, 4, 2, 4]]

sage: W = ReflectionGroup(['A', 3], index_set=["AA", "BB", 5]) # optional -j
↳gap3
sage: w = W.long_element() # optional -j
↳gap3
sage: w.reduced_words() # optional -j
↳gap3
[['AA', 5, 'BB', 5, 'AA', 'BB'],
 ['AA', 'BB', 5, 'BB', 'AA', 'BB'],
 [5, 'BB', 'AA', 5, 'BB', 5],
 ['BB', 5, 'AA', 'BB', 5, 'AA'],
 [5, 'BB', 5, 'AA', 'BB', 5],
 ['BB', 5, 'AA', 'BB', 'AA', 5],
 [5, 'AA', 'BB', 'AA', 5, 'BB'],
 ['BB', 'AA', 5, 'BB', 5, 'AA'],
 ['AA', 'BB', 'AA', 5, 'BB', 'AA'],
 [5, 'BB', 'AA', 'BB', 5, 'BB'],
 ['BB', 'AA', 5, 'BB', 'AA', 5],
 [5, 'AA', 'BB', 5, 'AA', 'BB'],
 ['AA', 'BB', 5, 'AA', 'BB', 'AA'],
 ['BB', 5, 'BB', 'AA', 'BB', 5],
 ['AA', 5, 'BB', 'AA', 5, 'BB'],
 ['BB', 'AA', 'BB', 5, 'BB', 'AA']]
```

Todo: The result should be full featured finite enumerated set (e.g., counting can be done much faster)

than iterating).

See also:

reduced_word(), *reduced_word_reverse_iterator()*, *length()*, *reduced_word_graph()*

reflection_length()

Return the reflection length of *self*.

The reflection length is the length of the shortest expression of the element as a product of reflections.

See also:

absolute_length()

EXAMPLES:

```
sage: W = WeylGroup(['A', 3])
sage: s = W.simple_reflections()
sage: (s[1]*s[2]*s[3]).reflection_length()
3

sage: W = SymmetricGroup(4)
sage: s = W.simple_reflections()
sage: (s[3]*s[2]*s[3]).reflection_length()
1
```

support()

Return the support of *self*, that is the simple reflections that appear in the reduced expressions of *self*.

OUTPUT:

The support of *self* as a set of integers

EXAMPLES:

```
sage: W = CoxeterGroups().example()
sage: w = W.from_reduced_word([1, 2, 1])
sage: w.support()
{1, 2}
```

upper_covers(*side='right', index_set=None*)

Return all elements that cover *self* in weak order.

INPUT:

- *side* – ‘left’ or ‘right’ (default: ‘right’)
- *index_set* – a list of indices or None

OUTPUT: a list

EXAMPLES:

```
sage: W = WeylGroup(['A', 3])
sage: w = W.from_reduced_word([2, 3])
sage: [x.reduced_word() for x in w.upper_covers()]
[[2, 3, 1], [2, 3, 2]]
```

To obtain covers for left weak order, set the option *side* to ‘left’:

```
sage: [x.reduced_word() for x in w.upper_covers(side='left')]
[[1, 2, 3], [2, 3, 2]]
```

Covers w.r.t. a parabolic subgroup are obtained with the option `index_set`:

```
sage: [x.reduced_word() for x in w.upper_covers(index_set = [1])]
[[2, 3, 1]]
sage: [x.reduced_word() for x in w.upper_covers(side='left', index_set =
↳ [1])]
[[1, 2, 3]]
```

weak_covers(*side='right', index_set=None, positive=False*)

Return all elements that `self` covers in weak order.

INPUT:

- `side` – ‘left’ or ‘right’ (default: ‘right’)
- `positive` – a boolean (default: False)
- `index_set` – a list of indices or None

OUTPUT: a list

EXAMPLES:

```
sage: W = WeylGroup(['A', 3])
sage: w = W.from_reduced_word([3, 2, 1])
sage: [x.reduced_word() for x in w.weak_covers()]
[[3, 2]]
```

To obtain instead elements that cover `self`, set `positive=True`:

```
sage: [x.reduced_word() for x in w.weak_covers(positive=True)]
[[3, 1, 2, 1], [2, 3, 2, 1]]
```

To obtain covers for left weak order, set the option `side` to ‘left’:

```
sage: [x.reduced_word() for x in w.weak_covers(side='left')]
[[2, 1]]
sage: w = W.from_reduced_word([3, 2, 3, 1])
sage: [x.reduced_word() for x in w.weak_covers()]
[[2, 3, 2], [3, 2, 1]]
sage: [x.reduced_word() for x in w.weak_covers(side='left')]
[[3, 2, 1], [2, 3, 1]]
```

Covers w.r.t. a parabolic subgroup are obtained with the option `index_set`:

```
sage: [x.reduced_word() for x in w.weak_covers(index_set = [1, 2])]
[[2, 3, 2]]
```

weak_le(*other, side='right'*)

comparison in weak order

INPUT:

- `other` – an element of the same Coxeter group
- `side` – ‘left’ or ‘right’ (default: ‘right’)

OUTPUT: a boolean

Returns whether `self` \leq `other` in left (resp. right) weak order, that is if ‘`v`’ can be obtained from ‘`v`’ by length increasing multiplication by simple reflections on the left (resp. right).

EXAMPLES:

```
sage: W = WeylGroup(["A", 3])
sage: u = W.from_reduced_word([1, 2])
sage: v = W.from_reduced_word([1, 2, 3, 2])
sage: u.weak_le(u)
True
sage: u.weak_le(v)
True
sage: v.weak_le(u)
False
sage: v.weak_le(v)
True
```

Comparison for left weak order is achieved with the option `side`:

```
sage: u.weak_le(v, side='left')
False
```

The implementation uses the equivalent condition that any reduced word for u is a right (resp. left) prefix of some reduced word for v .

Complexity: $O(l * c)$, where l is the minimum of the lengths of u and of v , and c is the cost of the low level methods `first_descent()`, `has_descent()`, `apply_simple_reflection()`, etc. Those are typically $O(n)$, where n is the rank of the Coxeter group.

We now run consistency tests with permutations:

```
sage: W = WeylGroup(["A", 3])
sage: P4 = Permutations(4)
sage: def P4toW(w): return W.from_reduced_word(w.reduced_word())
sage: for u in P4: # long time (5s on sage.math, 2011)
.....:     for v in P4:
.....:         assert u.permutohedron_lequal(v) == P4toW(u).weak_le(P4toW(v))
.....:         assert u.permutohedron_lequal(v, side='left') == P4toW(u).
↳weak_le(P4toW(v), side='left')
```

Finite

alias of `sage.categories.finite_coxeter_groups.FiniteCoxeterGroups`

class ParentMethods

Bases: object

`braid_group_as_finitely_presented_group()`

Return the associated braid group.

EXAMPLES:

```
sage: W = CoxeterGroup(['A', 2])
sage: W.braid_group_as_finitely_presented_group()
Finitely presented group < S1, S2 | S1*S2*S1*S2^-1*S1^-1*S2^-1 >

sage: W = WeylGroup(['B', 2])
sage: W.braid_group_as_finitely_presented_group()
Finitely presented group < S1, S2 | (S1*S2)^2*(S1^-1*S2^-1)^2 >
```

(continues on next page)

(continued from previous page)

```

sage: W = ReflectionGroup(['B',3], index_set=["AA","BB",5]) # optional -
↳gap3
sage: W.braid_group_as_finitely_presented_group()           # optional -
↳gap3
Finitely presented group < SAA, SBB, S5 |
  SAA*SBB*SAA*SBB^-1*SAA^-1*SBB^-1, SAA*S5*SAA^-1*S5^-1,
  (SBB*S5)^2*(SBB^-1*S5^-1)^2 >

```

braid_orbit(word)

Return the braid orbit of a word word of indices.

The input word does not need to be a reduced expression of an element.

INPUT:

- word: a list (or iterable) of indices in `self.index_set()`

OUTPUT: a list of all lists that can be obtained from word by replacements of braid relations

See `braid_relations()` for the definition of braid relations.

EXAMPLES:

```

sage: W = CoxeterGroups().example()
sage: s = W.simple_reflections()
sage: w = s[0] * s[1] * s[2] * s[1]
sage: word = w.reduced_word(); word
[0, 1, 2, 1]

sage: sorted(W.braid_orbit(word))
[[0, 1, 2, 1], [0, 2, 1, 2], [2, 0, 1, 2]]

sage: sorted(W.braid_orbit([2,1,1,2,1]))
[[1, 2, 1, 1, 2], [2, 1, 1, 2, 1], [2, 1, 2, 1, 2], [2, 2, 1, 2, 2]]

sage: W = ReflectionGroup(['A',3], index_set=["AA","BB",5]) # optional -
↳gap3
sage: w = W.long_element() # optional -
↳gap3
sage: W.braid_orbit(w.reduced_word()) # optional -
↳gap3
[['AA', 5, 'BB', 5, 'AA', 'BB'],
 ['AA', 'BB', 5, 'BB', 'AA', 'BB'],
 [5, 'BB', 'AA', 5, 'BB', 5],
 ['BB', 5, 'AA', 'BB', 5, 'AA'],
 [5, 'BB', 5, 'AA', 'BB', 5],
 ['BB', 5, 'AA', 'BB', 'AA', 5],
 [5, 'AA', 'BB', 'AA', 5, 'BB'],
 ['BB', 'AA', 5, 'BB', 5, 'AA'],
 ['AA', 'BB', 'AA', 5, 'BB', 'AA'],
 [5, 'BB', 'AA', 'BB', 5, 'BB'],
 ['BB', 'AA', 5, 'BB', 'AA', 5],
 [5, 'AA', 'BB', 5, 'AA', 'BB'],
 ['AA', 'BB', 5, 'AA', 'BB', 'AA'],
 ['BB', 5, 'BB', 'AA', 'BB', 5],

```

(continues on next page)

(continued from previous page)

```
['AA', 5, 'BB', 'AA', 5, 'BB'],
['BB', 'AA', 'BB', 5, 'BB', 'AA']]
```

Todo: The result should be full featured finite enumerated set (e.g., counting can be done much faster than iterating).

See also:

`reduced_words()`

braid_relations()

Return the braid relations of `self` as a list of reduced words of the braid relations.

EXAMPLES:

```
sage: W = WeylGroup(["A", 2])
sage: W.braid_relations()
[[[1, 2, 1], [2, 1, 2]]]

sage: W = WeylGroup(["B", 3])
sage: W.braid_relations()
[[[1, 2, 1], [2, 1, 2]], [[1, 3], [3, 1]], [[2, 3, 2, 3], [3, 2, 3, 2]]]
```

bruhat_graph(*x=None, y=None, edge_labels=False*)

Return the Bruhat graph as a directed graph, with an edge $u \rightarrow v$ if and only if $u < v$ in the Bruhat order, and $u = r \cdot v$.

The Bruhat graph $\Gamma(x, y)$, defined if $x \leq y$ in the Bruhat order, has as its vertices the Bruhat interval $\{t \mid x \leq t \leq y\}$, and as its edges are the pairs (u, v) such that $u = r \cdot v$ where r is a reflection, that is, a conjugate of a simple reflection.

REFERENCES:

Carrell, The Bruhat graph of a Coxeter group, a conjecture of Deodhar, and rational smoothness of Schubert varieties. Algebraic groups and their generalizations: classical methods (University Park, PA, 1991), 53–61, Proc. Sympos. Pure Math., 56, Part 1, Amer. Math. Soc., Providence, RI, 1994.

EXAMPLES:

```
sage: W = CoxeterGroup(["H", 3])
sage: G = W.bruhat_graph(); G
Digraph on 120 vertices

sage: W = CoxeterGroup(["A", 2, 1])
sage: s1, s2, s3 = W.simple_reflections()
sage: W.bruhat_graph(s1, s1*s3*s2*s3)
Digraph on 6 vertices

sage: W.bruhat_graph(s1, s3*s2*s3)
Digraph on 0 vertices

sage: W = WeylGroup("A3", prefix="s")
sage: s1, s2, s3 = W.simple_reflections()
sage: G = W.bruhat_graph(s1*s3, s1*s2*s3*s2*s1); G
Digraph on 10 vertices
```

Check that the graph has the correct number of edges (see [trac ticket #17744](#)):

```
sage: len(G.edges())
16
```

bruhat_interval(*x*, *y*)

Return the list of *t* such that $x \leq t \leq y$.

EXAMPLES:

```
sage: W = WeylGroup("A3", prefix="s")
sage: [s1,s2,s3] = W.simple_reflections()
sage: W.bruhat_interval(s2,s1*s3*s2*s1*s3)
[s1*s2*s3*s2*s1, s2*s3*s2*s1, s3*s1*s2*s1, s1*s2*s3*s1,
s1*s2*s3*s2, s3*s2*s1, s2*s3*s1, s2*s3*s2, s1*s2*s1,
s3*s1*s2, s1*s2*s3, s2*s1, s3*s2, s2*s3, s1*s2, s2]

sage: W = WeylGroup(['A',2,1], prefix="s")
sage: [s0,s1,s2] = W.simple_reflections()
sage: W.bruhat_interval(1,s0*s1*s2)
[s0*s1*s2, s1*s2, s0*s2, s0*s1, s2, s1, s0, 1]
```

bruhat_interval_poset(*x*, *y*, *facade=False*)

Return the poset of the Bruhat interval between *x* and *y* in Bruhat order.

EXAMPLES:

```
sage: W = WeylGroup("A3", prefix="s")
sage: s1,s2,s3 = W.simple_reflections()
sage: W.bruhat_interval_poset(s2, s1*s3*s2*s1*s3)
Finite poset containing 16 elements

sage: W = WeylGroup(['A',2,1], prefix="s")
sage: s0,s1,s2 = W.simple_reflections()
sage: W.bruhat_interval_poset(1, s0*s1*s2)
Finite poset containing 8 elements
```

canonical_representation()

Return the canonical faithful representation of *self*.

EXAMPLES:

```
sage: W = WeylGroup("A3")
sage: W.canonical_representation()
Finite Coxeter group over Integer Ring with Coxeter matrix:
[1 3 2]
[3 1 3]
[2 3 1]
```

coxeter_diagram()

Return the Coxeter diagram of *self*.

EXAMPLES:

```
sage: W = CoxeterGroup(['H',3], implementation="reflection")
sage: G = W.coxeter_diagram(); G
```

(continues on next page)

(continued from previous page)

```

Graph on 3 vertices
sage: G.edges()
[(1, 2, 3), (2, 3, 5)]
sage: CoxeterGroup(G) is W
True
sage: G = Graph([(0, 1, 3), (1, 2, oo)])
sage: W = CoxeterGroup(G)
sage: W.coxeter_diagram() == G
True
sage: CoxeterGroup(W.coxeter_diagram()) is W
True

```

coxeter_element()

Return a Coxeter element.

The result is the product of the simple reflections, in some order.

Note: This implementation is shared with well generated complex reflection groups. It would be nicer to put it in some joint super category; however, in the current state of the art, there is none where it is clear that this is the right construction for obtaining a Coxeter element.

In this context, this is an element having a regular eigenvector (a vector not contained in any reflection hyperplane of `self`).

EXAMPLES:

```

sage: CoxeterGroup(['A', 4]).coxeter_element().reduced_word()
[1, 2, 3, 4]
sage: CoxeterGroup(['B', 4]).coxeter_element().reduced_word()
[1, 2, 3, 4]
sage: CoxeterGroup(['D', 4]).coxeter_element().reduced_word()
[1, 2, 4, 3]
sage: CoxeterGroup(['F', 4]).coxeter_element().reduced_word()
[1, 2, 3, 4]
sage: CoxeterGroup(['E', 8]).coxeter_element().reduced_word()
[1, 3, 2, 4, 5, 6, 7, 8]
sage: CoxeterGroup(['H', 3]).coxeter_element().reduced_word()
[1, 2, 3]

```

This method is also used for well generated finite complex reflection groups:

```

sage: W = ReflectionGroup((1,1,4))           # optional - gap3
sage: W.coxeter_element().reduced_word()    # optional - gap3
[1, 2, 3]

sage: W = ReflectionGroup((2,1,4))           # optional - gap3
sage: W.coxeter_element().reduced_word()    # optional - gap3
[1, 2, 3, 4]

sage: W = ReflectionGroup((4,1,4))           # optional - gap3
sage: W.coxeter_element().reduced_word()    # optional - gap3
[1, 2, 3, 4]

```

(continues on next page)

(continued from previous page)

```

sage: W = ReflectionGroup((4,4,4))           # optional - gap3
sage: W.coxeter_element().reduced_word()    # optional - gap3
[1, 2, 3, 4]

```

coxeter_matrix()Return the Coxeter matrix associated to `self`.

EXAMPLES:

```

sage: G = WeylGroup(['A', 3])
sage: G.coxeter_matrix()
[1 3 2]
[3 1 3]
[2 3 1]

```

coxeter_type()Return the Coxeter type of `self`.

EXAMPLES:

```

sage: W = CoxeterGroup(['H', 3])
sage: W.coxeter_type()
Coxeter type of ['H', 3]

```

demazure_product(Q)Return the Demazure product of the list `Q` in `self`.

INPUT:

- `Q` is a list of elements from the index set of `self`.

This returns the Coxeter group element that represents the composition of 0-Hecke or Demazure operators.

See `CoxeterGroups.ParentMethods.simple_projections()`.

EXAMPLES:

```

sage: W = WeylGroup(['A', 2])
sage: w = W.demazure_product([2, 2, 1])
sage: w.reduced_word()
[2, 1]

sage: w = W.demazure_product([2, 1, 2, 1, 2])
sage: w.reduced_word()
[1, 2, 1]

sage: W = WeylGroup(['B', 2])
sage: w = W.demazure_product([2, 1, 2, 1, 2])
sage: w.reduced_word()
[2, 1, 2, 1]

```

elements_of_length(n)Return all elements of length `n`.

EXAMPLES:


```

sage: A = AffinePermutationGroup(['A',2,1])
sage: [len(list(A.elements_of_length(i))) for i in [0..5]]
[1, 3, 6, 9, 12, 15]

sage: W = CoxeterGroup(['H',3])
sage: [len(list(W.elements_of_length(i))) for i in range(4)]
[1, 3, 5, 7]

sage: W = CoxeterGroup(['A',2])
sage: [len(list(W.elements_of_length(i))) for i in range(6)]
[1, 2, 2, 1, 0, 0]

```

fully_commutative_elements()

Return the set of fully commutative elements in this Coxeter group.

See also:

[FullyCommutativeElements](#)

EXAMPLES:

```

sage: CoxeterGroup(['A', 3]).fully_commutative_elements()
Fully commutative elements of Finite Coxeter group over Integer Ring with
->Coxeter matrix:
[1 3 2]
[3 1 3]
[2 3 1]

```

grassmannian_elements(side='right')

Return the left or right Grassmannian elements of `self` as an enumerated set.

INPUT:

- `side` – (default: "right") "left" or "right"

EXAMPLES:

```

sage: S = CoxeterGroups().example()
sage: G = S.grassmannian_elements()
sage: G.cardinality()
12
sage: G.list()
[(0, 1, 2, 3), (1, 0, 2, 3), (0, 2, 1, 3), (0, 1, 3, 2),
 (2, 0, 1, 3), (1, 2, 0, 3), (0, 3, 1, 2), (0, 2, 3, 1),
 (3, 0, 1, 2), (1, 3, 0, 2), (1, 2, 3, 0), (2, 3, 0, 1)]
sage: sorted(tuple(w.descents()) for w in G)
[(), (0,), (0,), (0,), (1,), (1,), (1,), (1,), (1,), (2,), (2,), (2,)]
sage: G = S.grassmannian_elements(side = "left")
sage: G.cardinality()
12
sage: sorted(tuple(w.descents(side = "left")) for w in G)
[(), (0,), (0,), (0,), (1,), (1,), (1,), (1,), (1,), (2,), (2,), (2,)]

```

index_set()

Return the index set of `self`.

EXAMPLES:

```

sage: W = CoxeterGroup([[1,3],[3,1]])
sage: W.index_set()
(1, 2)
sage: W = CoxeterGroup([[1,3],[3,1]], index_set=['x', 'y'])
sage: W.index_set()
('x', 'y')
sage: W = CoxeterGroup(['H',3])
sage: W.index_set()
(1, 2, 3)

```

random_element_of_length(*n*)

Return a random element of length *n* in `self`.

Starts at the identity, then chooses an upper cover at random.

Not very uniform: actually constructs a uniformly random reduced word of length *n*. Thus we most likely get elements with lots of reduced words!

EXAMPLES:

```

sage: A = AffinePermutationGroup(['A', 7, 1])
sage: p = A.random_element_of_length(10)
sage: p in A
True
sage: p.length() == 10
True

sage: W = CoxeterGroup(['A', 4])
sage: p = W.random_element_of_length(5)
sage: p in W
True
sage: p.length() == 5
True

```

sign_representation(*base_ring=None, side='twosided'*)

Return the sign representation of `self` over `base_ring`.

INPUT:

- `base_ring` – (optional) the base ring; the default is \mathbf{Z}
- `side` – ignored

EXAMPLES:

```

sage: W = WeylGroup(["A", 1, 1])
sage: W.sign_representation()
Sign representation of Weyl Group of type ['A', 1, 1] (as a matrix group_
↪ acting on the root space) over Integer Ring

```

simple_projection(*i, side='right, length_increasing=True*)

Return the simple projection π_i (or $\bar{\pi}_i$ if `length_increasing` is `False`).

INPUT:

- `i` – an element of the index set of `self`

See `simple_projections()` for the options and for the definition of the simple projections.

EXAMPLES:

```

sage: W = CoxeterGroups().example()
sage: W
The symmetric group on {0, ..., 3}
sage: s = W.simple_reflections()
sage: sigma = W.an_element()
sage: sigma
(1, 2, 3, 0)
sage: u0 = W.simple_projection(0)
sage: d0 = W.simple_projection(0,length_increasing=False)
sage: sigma.length()
3
sage: pi=sigma*s[0]
sage: pi.length()
4
sage: u0(sigma)
(2, 1, 3, 0)
sage: pi
(2, 1, 3, 0)
sage: u0(pi)
(2, 1, 3, 0)
sage: d0(sigma)
(1, 2, 3, 0)
sage: d0(pi)
(1, 2, 3, 0)

```

simple_projections(*side='right', length_increasing=True*)

Return the family of simple projections, also known as 0-Hecke or Demazure operators.

INPUT:

- `self` – a Coxeter group W
- `side` – ‘left’ or ‘right’ (default: ‘right’)
- `length_increasing` – a boolean (default: True) specifying whether the operator increases or decreases length

Returns the simple projections of W , as a family.

To each simple reflection s_i of W , corresponds a *simple projection* π_i from W to W defined by:

$$\pi_i(w) = ws_i \text{ if } i \text{ is not a descent of } w \quad \pi_i(w) = w \text{ otherwise.}$$

The simple projections $(\pi_i)_{i \in I}$ move elements down the right permutohedron, toward the maximal element. They satisfy the same braid relations as the simple reflections, but are idempotents $\pi_i^2 = \pi$ not involutions $s_i^2 = 1$. As such, the simple projections generate the 0-Hecke monoid.

By symmetry, one can also define the projections $(\bar{\pi}_i)_{i \in I}$ (when the option `length_increasing` is False):

$$\bar{\pi}_i(w) = ws_i \text{ if } i \text{ is a descent of } w \quad \bar{\pi}_i(w) = w \text{ otherwise.}$$

as well as the analogues acting on the left (when the option `side` is ‘left’).

EXAMPLES:

```

sage: W = CoxeterGroups().example(); W
The symmetric group on {0, ..., 3}
sage: s = W.simple_reflections()
sage: sigma = W.an_element(); sigma
(1, 2, 3, 0)
sage: pi = W.simple_projections(); pi
Finite family {0: <function ...<lambda> at ...>, 1: <function ...<lambda>_
↪at ...>, 2: <function ...<lambda> ...>}

```

(continues on next page)

(continued from previous page)

```
sage: pi[1](sigma)
(1, 3, 2, 0)
sage: W.simple_projection(1)(sigma)
(1, 3, 2, 0)
```

standard_coxeter_elements()Return all standard Coxeter elements in `self`.This is the set of all elements in `self` obtained from any product of the simple reflections in `self`.**Note:**

- `self` is assumed to be well-generated.
- This works even beyond real reflection groups, but the conjugacy class is not unique and we only obtain one such class.

EXAMPLES:

```
sage: W = ReflectionGroup(4) # optional - gap3
sage: sorted(W.standard_coxeter_elements()) # optional - gap3
[(1, 7, 6, 12, 23, 20) (2, 8, 17, 24, 9, 5) (3, 16, 10, 19, 15, 21) (4, 14, 11, 22, 18, 13),
 (1, 10, 4, 12, 21, 22) (2, 11, 19, 24, 13, 3) (5, 15, 7, 17, 16, 23) (6, 18, 8, 20, 14, 9)]
```

weak_order_ideal(*predicate*, *side*='right', *category*=None)

Return a weak order ideal defined by a predicate

INPUT:

- `predicate`: a predicate on the elements of `self` defining an weak order ideal in `self`
- `side`: “left” or “right” (default: “right”)

OUTPUT: an enumerated set

EXAMPLES:

```
sage: D6 = FiniteCoxeterGroups().example(5)
sage: I = D6.weak_order_ideal(predicate = lambda w: w.length() <= 3)
sage: I.cardinality()
7
sage: list(I)
[(), (1,), (2,), (1, 2), (2, 1), (1, 2, 1), (2, 1, 2)]
```

We now consider an infinite Coxeter group:

```
sage: W = WeylGroup(["A", 1, 1])
sage: I = W.weak_order_ideal(predicate = lambda w: w.length() <= 2)
sage: list(iter(I))
[
 [1 0] [-1 2] [ 1 0] [ 3 -2] [-1 2]
 [0 1], [ 0 1], [ 2 -1], [ 2 -1], [-2 3]
]
```

Even when the result is finite, some features of *FiniteEnumeratedSets* are not available:

```
sage: I.cardinality() # todo: not implemented
5
sage: list(I) # todo: not implemented
```

unless this finiteness is explicitly specified:

```
sage: I = W.weak_order_ideal(predicate = lambda w: w.length() <= 2,
.....:                          category = FiniteEnumeratedSets())
sage: I.cardinality()
5
sage: list(I)
[
 [1 0] [-1 2] [ 1 0] [ 3 -2] [-1 2]
 [0 1], [ 0 1], [ 2 -1], [ 2 -1], [-2 3]
]
```

Background

The weak order is returned as a `RecursivelyEnumeratedSet_forest`. This is achieved by assigning to each element u_1 of the ideal a single ancestor $u = u_1 s_i$, where i is the smallest descent of u .

This allows for iterating through the elements in roughly Constant Amortized Time and constant memory (taking the operations and size of the generated objects as constants).

`additional_structure()`

Return None.

Indeed, all the structure Coxeter groups have in addition to groups (simple reflections, ...) is already defined in the super category.

See also:

`Category.additional_structure()`

EXAMPLES:

```
sage: CoxeterGroups().additional_structure()
```

`super_categories()`

EXAMPLES:

```
sage: CoxeterGroups().super_categories()
[Category of generalized coxeter groups]
```

3.31 Crystals

class `sage.categories.crystals.CrystalHomset(X, Y, category=None)`

Bases: `sage.categories.homset.Homset`

The set of crystal morphisms from one crystal to another.

An $U_q(\mathfrak{g})$ I -crystal morphism $\Psi : B \rightarrow C$ is a map $\Psi : B \cup \{0\} \rightarrow C \cup \{0\}$ such that:

- $\Psi(0) = 0$.
- If $b \in B$ and $\Psi(b) \in C$, then $\text{wt}(\Psi(b)) = \text{wt}(b)$, $\varepsilon_i(\Psi(b)) = \varepsilon_i(b)$, and $\varphi_i(\Psi(b)) = \varphi_i(b)$ for all $i \in I$.
- If $b, b' \in B$, $\Psi(b), \Psi(b') \in C$ and $f_i b = b'$, then $f_i \Psi(b) = \Psi(b')$ and $\Psi(b) = e_i \Psi(b')$ for all $i \in I$.

If the Cartan type is unambiguous, it is suppressed from the notation.

We can also generalize the definition of a crystal morphism by considering a map of σ of the (now possibly different) Dynkin diagrams corresponding to B and C along with scaling factors $\gamma_i \in \mathbf{Z}$ for $i \in I$. Let σ_i denote the orbit of i under σ . We write objects for B as X with corresponding objects of C as \widehat{X} . Then a *virtual* crystal morphism Ψ is a map such that the following holds:

- $\Psi(0) = 0$.
- If $b \in B$ and $\Psi(b) \in C$, then for all $j \in \sigma_i$:

$$\varepsilon_i(b) = \frac{1}{\gamma_j} \widehat{\varepsilon}_j(\Psi(b)), \quad \varphi_i(b) = \frac{1}{\gamma_j} \widehat{\varphi}_j(\Psi(b)), \quad \text{wt}(\Psi(b)) = \sum_i c_i \sum_{j \in \sigma_i} \gamma_j \widehat{\Lambda}_j,$$

where $\text{wt}(b) = \sum_i c_i \Lambda_i$.

- If $b, b' \in B$, $\Psi(b), \Psi(b') \in C$ and $f_i b = b'$, then independent of the ordering of σ_i we have:

$$\Psi(b') = e_i \Psi(b) = \prod_{j \in \sigma_i} \widehat{e}_j^{\gamma_j} \Psi(b), \quad \Psi(b') = f_i \Psi(b) = \prod_{j \in \sigma_i} \widehat{f}_j^{\gamma_j} \Psi(b).$$

If $\gamma_i = 1$ for all $i \in I$ and the Dynkin diagrams are the same, then we call Ψ a *twisted* crystal morphism.

INPUT:

- X – the domain
- Y – the codomain
- category – (optional) the category of the crystal morphisms

See also:

For the construction of an element of the homset, see [CrystalMorphismByGenerators](#) and [crystal_morphism\(\)](#).

EXAMPLES:

We begin with the natural embedding of $B(2\Lambda_1)$ into $B(\Lambda_1) \otimes B(\Lambda_1)$ in type A_1 :

```
sage: B = crystals.Tableaux(['A', 1], shape=[2])
sage: F = crystals.Tableaux(['A', 1], shape=[1])
sage: T = crystals.TensorProduct(F, F)
sage: v = T.highest_weight_vectors()[0]; v
[[[1]], [[1]]]
sage: H = Hom(B, T)
sage: psi = H([v])
sage: b = B.highest_weight_vector(); b
[[1, 1]]
sage: psi(b)
[[[1]], [[1]]]
sage: b.f(1)
[[1, 2]]
sage: psi(b.f(1))
[[[1]], [[2]]]
```

We now look at the decomposition of $B(\Lambda_1) \otimes B(\Lambda_1)$ into $B(2\Lambda_1) \oplus B(0)$:

```

sage: B0 = crystals.Tableaux(['A', 1], shape=[])
sage: D = crystals.DirectSum([B, B0])
sage: H = Hom(T, D)
sage: psi = H(D.module_generators)
sage: psi
['A', 1] Crystal morphism:
  From: Full tensor product of the crystals
    [The crystal of tableaux of type ['A', 1] and shape(s) [[1]],
    The crystal of tableaux of type ['A', 1] and shape(s) [[1]]]
  To: Direct sum of the crystals Family
    (The crystal of tableaux of type ['A', 1] and shape(s) [[2]],
    The crystal of tableaux of type ['A', 1] and shape(s) [[]])
  Defn: [[[]], [[]]] |--> [[1, 1]]
        [[2]], [[]]] |--> []
sage: psi.is_isomorphism()
True

```

We can always construct the trivial morphism which sends everything to 0:

```

sage: Binfinity = crystals.infinity.Tableaux(['B', 2])
sage: B = crystals.Tableaux(['B', 2], shape=[1])
sage: H = Hom(Binfinity, B)
sage: psi = H(lambda x: None)
sage: psi(Binfinity.highest_weight_vector())

```

For Kirillov-Reshetikhin crystals, we consider the map to the corresponding classical crystal:

```

sage: K = crystals.KirillovReshetikhin(['D', 4, 1], 2, 1)
sage: B = K.classical_decomposition()
sage: H = Hom(K, B)
sage: psi = H(lambda x: x.lift(), cartan_type=['D', 4])
sage: L = [psi(mg) for mg in K.module_generators]; L
[[], [[1], [2]]]
sage: all(x.parent() == B for x in L)
True

```

Next we consider a type D_4 crystal morphism where we twist by $3 \leftrightarrow 4$:

```

sage: B = crystals.Tableaux(['D', 4], shape=[1])
sage: H = Hom(B, B)
sage: d = {1:1, 2:2, 3:4, 4:3}
sage: psi = H(B.module_generators, automorphism=d)
sage: b = B.highest_weight_vector()
sage: b.f_string([1, 2, 3])
[[4]]
sage: b.f_string([1, 2, 4])
[[-4]]
sage: psi(b.f_string([1, 2, 3]))
[[-4]]
sage: psi(b.f_string([1, 2, 4]))
[[4]]

```

We construct the natural virtual embedding of a type B_3 into a type D_4 crystal:

```

sage: B = crystals.Tableaux(['B',3], shape=[1])
sage: C = crystals.Tableaux(['D',4], shape=[2])
sage: H = Hom(B, C)
sage: psi = H(C.module_generators)
sage: psi
['B', 3] -> ['D', 4] Virtual Crystal morphism:
  From: The crystal of tableaux of type ['B', 3] and shape(s) [[1]]
  To:   The crystal of tableaux of type ['D', 4] and shape(s) [[2]]
  Defn: [[1]] |--> [[1, 1]]
sage: for b in B: print("{} |--> {}".format(b, psi(b)))
[[1]] |--> [[1, 1]]
[[2]] |--> [[2, 2]]
[[3]] |--> [[3, 3]]
[[0]] |--> [[3, -3]]
[[-3]] |--> [[-3, -3]]
[[-2]] |--> [[-2, -2]]
[[-1]] |--> [[-1, -1]]

```

Elementalias of *CrystalMorphismByGenerators*

class sage.categories.crystals.**CrystalMorphism**(parent, cartan_type=None, virtualization=None, scaling_factors=None)

Bases: *sage.categories.morphism.Morphism*

A crystal morphism.

INPUT:

- parent – a homset
- cartan_type – (optional) a Cartan type; the default is the Cartan type of the domain
- virtualization – (optional) a dictionary whose keys are in the index set of the domain and whose values are lists of entries in the index set of the codomain
- scaling_factors – (optional) a dictionary whose keys are in the index set of the domain and whose values are scaling factors for the weight, ε and φ

cartan_type()

Return the Cartan type of self.

EXAMPLES:

```

sage: B = crystals.Tableaux(['A',2], shape=[2,1])
sage: psi = Hom(B, B).an_element()
sage: psi.cartan_type()
['A', 2]

```

is_injective()

Return if self is an injective crystal morphism.

EXAMPLES:

```

sage: B = crystals.Tableaux(['A',2], shape=[2,1])
sage: psi = Hom(B, B).an_element()
sage: psi.is_injective()
False

```


is_surjective()

Check if self is a surjective crystal morphism.

EXAMPLES:

```
sage: B = crystals.Tableaux(['C',2], shape=[1,1])
sage: C = crystals.Tableaux(['C',2], ([2,1], [1,1]))
sage: psi = B.crystal_morphism(C.module_generators[1:], codomain=C)
sage: psi.is_surjective()
False
sage: im_gens = [None, B.module_generators[0]]
sage: psi = C.crystal_morphism(im_gens, codomain=B)
sage: psi.is_surjective()
True

sage: C = crystals.Tableaux(['A',2], shape=[2,1])
sage: B = crystals.infinity.Tableaux(['A',2])
sage: La = RootSystem(['A',2]).weight_lattice().fundamental_weights()
sage: W = crystals.elementary.T(['A',2], La[1]+La[2])
sage: T = W.tensor(B)
sage: mg = T(W.module_generators[0], B.module_generators[0])
sage: psi = Hom(C,T)([mg])
sage: psi.is_surjective()
False
```

scaling_factors()

Return the scaling factors γ_i .

EXAMPLES:

```
sage: B = crystals.Tableaux(['B',3], shape=[1])
sage: C = crystals.Tableaux(['D',4], shape=[2])
sage: psi = B.crystal_morphism(C.module_generators)
sage: psi.scaling_factors()
Finite family {1: 2, 2: 2, 3: 1}
```

virtualization()

Return the virtualization sets σ_i .

EXAMPLES:

```
sage: B = crystals.Tableaux(['B',3], shape=[1])
sage: C = crystals.Tableaux(['D',4], shape=[2])
sage: psi = B.crystal_morphism(C.module_generators)
sage: psi.virtualization()
Finite family {1: (1,), 2: (2,), 3: (3, 4)}
```

class sage.categories.crystals.**CrystalMorphismByGenerators**(parent, on_gens, cartan_type=None, virtualization=None, scaling_factors=None, gens=None, check=True)

Bases: *sage.categories.crystals.CrystalMorphism*

A crystal morphism defined by a set of generators which create a virtual crystal inside the codomain.

INPUT:

- parent – a homset

- `on_gens` – a function or list that determines the image of the generators (if given a list, then this uses the order of the generators of the domain) of the domain under `self`
- `cartan_type` – (optional) a Cartan type; the default is the Cartan type of the domain
- `virtualization` – (optional) a dictionary whose keys are in the index set of the domain and whose values are lists of entries in the index set of the codomain
- `scaling_factors` – (optional) a dictionary whose keys are in the index set of the domain and whose values are scaling factors for the weight, ε and φ
- `gens` – (optional) a finite list of generators to define the morphism; the default is to use the highest weight vectors of the crystal
- `check` – (default: True) check if the crystal morphism is valid

See also:

`sage.categories.crystals.Crystals.ParentMethods.crystal_morphism()`

im_gens()

Return the image of the generators of `self` as a tuple.

EXAMPLES:

```
sage: B = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: F = crystals.Tableaux(['A', 2], shape=[1])
sage: T = crystals.TensorProduct(F, F, F)
sage: H = Hom(T, B)
sage: b = B.highest_weight_vector()
sage: psi = H((None, b, b, None), generators=T.highest_weight_vectors())
sage: psi.im_gens()
(None, [[1, 1], [2]], [[1, 1], [2]], None)
```

image()

Return the image of `self` in the codomain as a Subcrystal.

Warning: This assumes that `self` is a strict crystal morphism.

EXAMPLES:

```
sage: B = crystals.Tableaux(['B', 3], shape=[1])
sage: C = crystals.Tableaux(['D', 4], shape=[2])
sage: H = Hom(B, C)
sage: psi = H(C.module_generators)
sage: psi.image()
Virtual crystal of The crystal of tableaux of type ['D', 4] and shape(s) [[2]]
↳ of type ['B', 3]
```

to_module_generator(x)

Return a generator `mg` and a path of e_i and f_i operations to `mg`.

OUTPUT:

A tuple consisting of:

- a module generator,
- a list of 'e' and 'f' to denote which operation, and

- a list of matching indices.

EXAMPLES:

```
sage: B = crystals.elementary.Elementary(['A',2], 2)
sage: psi = B.crystal_morphism(B.module_generators)
sage: psi.to_module_generator(B(4))
(0, ['f', 'f', 'f', 'f'], [2, 2, 2, 2])
sage: psi.to_module_generator(B(-2))
(0, ['e', 'e'], [2, 2])
```

class `sage.categories.crystals.Crystals`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of crystals.

See `sage.combinat.crystals.crystals` for an introduction to crystals.

EXAMPLES:

```
sage: C = Crystals()
sage: C
Category of crystals
sage: C.super_categories()
[Category of... enumerated sets]
sage: C.example()
Highest weight crystal of type A_3 of highest weight omega_1
```

Parents in this category should implement the following methods:

- either an attribute `_cartan_type` or a method `cartan_type`
- `module_generators`: a list (or container) of distinct elements which generate the crystal using f_i

Furthermore, their elements `x` should implement the following methods:

- `x.e(i)` (returning $e_i(x)$)
- `x.f(i)` (returning $f_i(x)$)
- `x.epsilon(i)` (returning $\varepsilon_i(x)$)
- `x.phi(i)` (returning $\varphi_i(x)$)

EXAMPLES:

```
sage: from sage.misc.abstract_method import abstract_methods_of_class
sage: abstract_methods_of_class(Crystals().element_class)
{'optional': [], 'required': ['e', 'epsilon', 'f', 'phi', 'weight']}
```

class `ElementMethods`

Bases: `object`

`Epsilon()`

EXAMPLES:

```
sage: C = crystals.Letters(['A',5])
sage: C(0).Epsilon()
(0, 0, 0, 0, 0)
sage: C(1).Epsilon()
```

(continues on next page)

(continued from previous page)

```
(0, 0, 0, 0, 0, 0)
sage: C(2).Epsilon()
(1, 0, 0, 0, 0, 0)
```

Phi()

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C(0).Phi()
(0, 0, 0, 0, 0, 0)
sage: C(1).Phi()
(1, 0, 0, 0, 0, 0)
sage: C(2).Phi()
(1, 1, 0, 0, 0, 0)
```

all_paths_to_highest_weight(*index_set=None*)Iterate over all paths to the highest weight from `self` with respect to *index_set*.

INPUT:

- `index_set` – (optional) a subset of the index set of `self`

EXAMPLES:

```
sage: B = crystals.infinity.Tableaux("A2")
sage: b0 = B.highest_weight_vector()
sage: b = b0.f_string([1, 2, 1, 2])
sage: L = b.all_paths_to_highest_weight()
sage: list(L)
[[2, 1, 2, 1], [2, 2, 1, 1]]

sage: Y = crystals.infinity.GeneralizedYoungWalls(3)
sage: y0 = Y.highest_weight_vector()
sage: y = y0.f_string([0, 1, 2, 3, 2, 1, 0])
sage: list(y.all_paths_to_highest_weight())
[[0, 1, 2, 3, 2, 1, 0],
 [0, 1, 3, 2, 2, 1, 0],
 [0, 3, 1, 2, 2, 1, 0],
 [0, 3, 2, 1, 1, 0, 2],
 [0, 3, 2, 1, 1, 2, 0]]

sage: B = crystals.Tableaux("A3", shape=[4,2,1])
sage: b0 = B.highest_weight_vector()
sage: b = b0.f_string([1, 1, 2, 3])
sage: list(b.all_paths_to_highest_weight())
[[1, 3, 2, 1], [3, 1, 2, 1], [3, 2, 1, 1]]
```

cartan_type()Returns the Cartan type associated to `self`

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C(1).cartan_type()
['A', 5]
```

e(i)

Return e_i of `self` if it exists or `None` otherwise.

This method should be implemented by the element class of the crystal.

EXAMPLES:

```
sage: C = Crystals().example(5)
sage: x = C[2]; x
3
sage: x.e(1), x.e(2), x.e(3)
(None, 2, None)
```

e_string(list)

Applies $e_{i_r} \cdots e_{i_1}$ to `self` for `list` as $[i_1, \dots, i_r]$

EXAMPLES:

```
sage: C = crystals.Letters(['A', 3])
sage: b = C(3)
sage: b.e_string([2, 1])
1
sage: b.e_string([1, 2])
```

epsilon(i)

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C(1).epsilon(1)
0
sage: C(2).epsilon(1)
1
```

f(i)

Return f_i of `self` if it exists or `None` otherwise.

This method should be implemented by the element class of the crystal.

EXAMPLES:

```
sage: C = Crystals().example(5)
sage: x = C[1]; x
2
sage: x.f(1), x.f(2), x.f(3)
(None, 3, None)
```

f_string(list)

Applies $f_{i_r} \cdots f_{i_1}$ to `self` for `list` as $[i_1, \dots, i_r]$

EXAMPLES:

```
sage: C = crystals.Letters(['A', 3])
sage: b = C(1)
sage: b.f_string([1, 2])
3
sage: b.f_string([2, 1])
```

index_set()

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C(1).index_set()
(1, 2, 3, 4, 5)
```

is_highest_weight(*index_set=None*)

Returns True if *self* is a highest weight. Specifying the option *index_set* to be a subset *I* of the index set of the underlying crystal, finds all highest weight vectors for arrows in *I*.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C(1).is_highest_weight()
True
sage: C(2).is_highest_weight()
False
sage: C(2).is_highest_weight(index_set = [2,3,4,5])
True
```

is_lowest_weight(*index_set=None*)

Returns True if *self* is a lowest weight. Specifying the option *index_set* to be a subset *I* of the index set of the underlying crystal, finds all lowest weight vectors for arrows in *I*.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C(1).is_lowest_weight()
False
sage: C(6).is_lowest_weight()
True
sage: C(4).is_lowest_weight(index_set = [1,3])
True
```

phi(*i*)

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C(1).phi(1)
1
sage: C(2).phi(1)
0
```

phi_minus_epsilon(*i*)

Return $\varphi_i - \varepsilon_i$ of *self*.

There are sometimes better implementations using the weight for this. It is used for reflections along a string.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C(1).phi_minus_epsilon(1)
1
```

s(*i*)Return the reflection of `self` along its *i*-string.

EXAMPLES:

```

sage: C = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: b = C(rows=[[1, 1], [3]])
sage: b.s(1)
[[2, 2], [3]]
sage: b = C(rows=[[1, 2], [3]])
sage: b.s(2)
[[1, 2], [3]]
sage: T = crystals.Tableaux(['A', 2], shape=[4])
sage: t = T(rows=[[1, 2, 2, 2]])
sage: t.s(1)
[[1, 1, 1, 2]]

```

subcrystal(*index_set=None, max_depth=inf, direction='both', contained=None, cartan_type=None, category=None*)

Construct the subcrystal generated by `self` using e_i and/or f_i for all *i* in `index_set`.

INPUT:

- `index_set` – (default: `None`) the index set; if `None` then use the index set of the crystal
- `max_depth` – (default: infinity) the maximum depth to build
- `direction` – (default: `'both'`) the direction to build the subcrystal; it can be one of the following:
 - `'both'` - using both e_i and f_i
 - `'upper'` - using e_i
 - `'lower'` - using f_i
- `contained` – (optional) a set (or function) defining the containment in the subcrystal
- `cartan_type` – (optional) specify the Cartan type of the subcrystal
- `category` – (optional) specify the category of the subcrystal

See also:

- [*Crystals.ParentMethods.subcrystal\(\)*](#)

EXAMPLES:

```

sage: C = crystals.KirillovReshetikhin(['A', 3, 1], 1, 2)
sage: elt = C(1, 4)
sage: list(elt.subcrystal(index_set=[1, 3]))
[[[1, 4]], [[2, 4]], [[1, 3]], [[2, 3]]]
sage: list(elt.subcrystal(index_set=[1, 3], max_depth=1))
[[[1, 4]], [[2, 4]], [[1, 3]]]
sage: list(elt.subcrystal(index_set=[1, 3], direction='upper'))
[[[1, 4]], [[1, 3]]]
sage: list(elt.subcrystal(index_set=[1, 3], direction='lower'))
[[[1, 4]], [[2, 4]]]

```

tensor(**elts*)Return the tensor product of `self` with the crystal elements `elts`.

EXAMPLES:

```

sage: C = crystals.Letters(['A', 3])
sage: B = crystals.infinity.Tableaux(['A', 3])
sage: c = C[0]

```

(continues on next page)

(continued from previous page)

```

sage: b = B.highest_weight_vector()
sage: t = c.tensor(c, b)
sage: ascii_art(t)
      1 1 1
1 # 1 # 2 2
      3
sage: tensor([c, c, b]) == t
True
sage: ascii_art(tensor([b, b, c]))
  1 1 1   1 1 1
  2 2   # 2 2   # 1
  3       3

```

to_highest_weight(*index_set=None*)

Return the highest weight element u and a list $[i_1, \dots, i_k]$ such that $\text{self} = f_{i_1} \dots f_{i_k} u$, where i_1, \dots, i_k are elements in *index_set*. By default the index set is assumed to be the full index set of self.

EXAMPLES:

```

sage: T = crystals.Tableaux(['A', 3], shape = [1])
sage: t = T(rows = [[3]])
sage: t.to_highest_weight()
[[[1]], [2, 1]]
sage: T = crystals.Tableaux(['A', 3], shape = [2, 1])
sage: t = T(rows = [[1, 2], [4]])
sage: t.to_highest_weight()
[[[1, 1], [2]], [1, 3, 2]]
sage: t.to_highest_weight(index_set = [3])
[[[1, 2], [3]], [3]]
sage: K = crystals.KirillovReshetikhin(['A', 3, 1], 2, 1)
sage: t = K(rows=[[2], [3]]); t.to_highest_weight(index_set=[1])
[[[1], [3]], [1]]
sage: t.to_highest_weight()
Traceback (most recent call last):
...
ValueError: This is not a highest weight crystals!

```

to_lowest_weight(*index_set=None*)

Return the lowest weight element u and a list $[i_1, \dots, i_k]$ such that $\text{self} = e_{i_1} \dots e_{i_k} u$, where i_1, \dots, i_k are elements in *index_set*. By default the index set is assumed to be the full index set of self.

EXAMPLES:

```

sage: T = crystals.Tableaux(['A', 3], shape = [1])
sage: t = T(rows = [[3]])
sage: t.to_lowest_weight()
[[[4]], [3]]
sage: T = crystals.Tableaux(['A', 3], shape = [2, 1])
sage: t = T(rows = [[1, 2], [4]])
sage: t.to_lowest_weight()
[[[3, 4], [4]], [1, 2, 2, 3]]
sage: t.to_lowest_weight(index_set = [3])
[[[1, 2], [4]], []]

```

(continues on next page)

(continued from previous page)

```

sage: K = crystals.KirillovReshetikhin(['A',3,1],2,1)
sage: t = K.module_generator(); t
[[1], [2]]
sage: t.to_lowest_weight(index_set=[1,2,3])
[[[3], [4]], [2, 1, 3, 2]]
sage: t.to_lowest_weight()
Traceback (most recent call last):
...
ValueError: This is not a highest weight crystals!

```

weight()

Return the weight of this crystal element.

This method should be implemented by the element class of the crystal.

EXAMPLES:

```

sage: C = crystals.Letters(['A',5])
sage: C(1).weight()
(1, 0, 0, 0, 0, 0)

```

Finite

alias of *sage.categories.finite_crystals.FiniteCrystals*

class MorphismMethods

Bases: object

is_embedding()

Check if self is an injective crystal morphism.

EXAMPLES:

```

sage: B = crystals.Tableaux(['C',2], shape=[1,1])
sage: C = crystals.Tableaux(['C',2], ([2,1], [1,1]))
sage: psi = B.crystal_morphism(C.module_generators[1:], codomain=C)
sage: psi.is_embedding()
True

sage: C = crystals.Tableaux(['A',2], shape=[2,1])
sage: B = crystals.infinity.Tableaux(['A',2])
sage: La = RootSystem(['A',2]).weight_lattice().fundamental_weights()
sage: W = crystals.elementary.T(['A',2], La[1]+La[2])
sage: T = W.tensor(B)
sage: mg = T(W.module_generators[0], B.module_generators[0])
sage: psi = Hom(C,T)([mg])
sage: psi.is_embedding()
True

```

is_isomorphism()

Check if self is a crystal isomorphism.

EXAMPLES:

```

sage: B = crystals.Tableaux(['C',2], shape=[1,1])
sage: C = crystals.Tableaux(['C',2], ([2,1], [1,1]))

```

(continues on next page)

(continued from previous page)

```
sage: psi = B.crystal_morphism(C.module_generators[1:], codomain=C)
sage: psi.is_isomorphism()
False
```

is_strict()

Check if `self` is a strict crystal morphism.

EXAMPLES:

```
sage: B = crystals.Tableaux(['C', 2], shape=[1, 1])
sage: C = crystals.Tableaux(['C', 2], ([2, 1], [1, 1]))
sage: psi = B.crystal_morphism(C.module_generators[1:], codomain=C)
sage: psi.is_strict()
True
```

class ParentMethods

Bases: object

Lambda()

Returns the fundamental weights in the weight lattice realization for the root system associated with the crystal

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C.Lambda()
Finite family {1: (1, 0, 0, 0, 0), 2: (1, 1, 0, 0, 0), 3: (1, 1, 1, 0,
↪ 0, 0), 4: (1, 1, 1, 1, 0), 5: (1, 1, 1, 1, 1, 0)}
```

an_element()

Returns an element of `self`

```
sage: C = crystals.Letters(['A', 5]) sage: C.an_element() 1
```

cartan_type()

Returns the Cartan type of the crystal

EXAMPLES:

```
sage: C = crystals.Letters(['A', 2])
sage: C.cartan_type()
['A', 2]
```

connected_components()

Return the connected components of `self` as subcrystals.

EXAMPLES:

```
sage: B = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: C = crystals.Letters(['A', 2])
sage: T = crystals.TensorProduct(B, C)
sage: T.connected_components()
[Subcrystal of Full tensor product of the crystals
 [The crystal of tableaux of type ['A', 2] and shape(s) [[2, 1]],
  The crystal of letters for type ['A', 2]],
Subcrystal of Full tensor product of the crystals
 [The crystal of tableaux of type ['A', 2] and shape(s) [[2, 1]],
```

(continues on next page)

(continued from previous page)

```
The crystal of letters for type ['A', 2]],
Subcrystal of Full tensor product of the crystals
[The crystal of tableaux of type ['A', 2] and shape(s) [[2, 1]],
The crystal of letters for type ['A', 2]]]
```

connected_components_generators()

Return a tuple of generators for each of the connected components of `self`.

EXAMPLES:

```
sage: B = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: C = crystals.Letters(['A', 2])
sage: T = crystals.TensorProduct(B, C)
sage: T.connected_components_generators()
[[[1, 1], [2]], 1], [[1, 2], [2]], 1], [[1, 2], [3]], 1]]
```

crystal_morphism(*on_gens*, *codomain=None*, *cartan_type=None*, *index_set=None*, *generators=None*, *automorphism=None*, *virtualization=None*, *scaling_factors=None*, *category=None*, *check=True*)

Construct a crystal morphism from `self` to another crystal codomain.

INPUT:

- `on_gens` – a function or list that determines the image of the generators (if given a list, then this uses the order of the generators of the domain) of `self` under the crystal morphism
- `codomain` – (default: `self`) the codomain of the morphism
- `cartan_type` – (optional) the Cartan type of the morphism; the default is the Cartan type of `self`
- `index_set` – (optional) the index set of the morphism; the default is the index set of the Cartan type
- `generators` – (optional) the generators to define the morphism; the default is the generators of `self`
- `automorphism` – (optional) the automorphism to perform the twisting
- `virtualization` – (optional) a dictionary whose keys are in the index set of the domain and whose values are lists of entries in the index set of the codomain; the default is the identity dictionary
- `scaling_factors` – (optional) a dictionary whose keys are in the index set of the domain and whose values are scaling factors for the weight, ε and φ ; the default are all scaling factors to be one
- `category` – (optional) the category for the crystal morphism; the default is the category of [Crystals](#).
- `check` – (default: `True`) check if the crystal morphism is valid

See also:

For more examples, see [sage.categories.crystals.CrystalHomset](#).

EXAMPLES:

We construct the natural embedding of a crystal using tableaux into the tensor product of single boxes via the reading word:

```
sage: B = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: F = crystals.Tableaux(['A', 2], shape=[1])
sage: T = crystals.TensorProduct(F, F, F)
sage: mg = T.highest_weight_vectors()[2]; mg
[[1]], [[2]], [[1]]
sage: psi = B.crystal_morphism([mg], codomain=T); psi
```

(continues on next page)

(continued from previous page)

```

['A', 2] Crystal morphism:
  From: The crystal of tableaux of type ['A', 2] and shape(s) [[2, 1]]
  To:   Full tensor product of the crystals
        [The crystal of tableaux of type ['A', 2] and shape(s) [[1]],
         The crystal of tableaux of type ['A', 2] and shape(s) [[1]],
         The crystal of tableaux of type ['A', 2] and shape(s) [[1]]]
  Defn: [[1, 1], [2]] |--> [[[1]], [[2]], [[1]]]
sage: b = B.module_generators[0]
sage: b.pp()
  1  1
  2
sage: psi(b)
[[[1]], [[2]], [[1]]]
sage: psi(b.f(2))
[[[1]], [[3]], [[1]]]
sage: psi(b.f_string([2,1,1]))
[[[2]], [[3]], [[2]]]
sage: lw = b.to_lowest_weight()[0]
sage: lw.pp()
  2  3
  3
sage: psi(lw)
[[[3]], [[3]], [[2]]]
sage: psi(lw) == mg.to_lowest_weight()[0]
True

```

We now take the other isomorphic highest weight component in the tensor product:

```

sage: mg = T.highest_weight_vectors()[1]; mg
[[[2]], [[1]], [[1]]]
sage: psi = B.crystal_morphism([mg], codomain=T)
sage: psi(lw)
[[[3]], [[2]], [[3]]]

```

We construct a crystal morphism of classical crystals using a Kirillov-Reshetikhin crystal:

```

sage: B = crystals.Tableaux(['D', 4], shape=[1,1])
sage: K = crystals.KirillovReshetikhin(['D',4,1], 2,2)
sage: K.module_generators
[[], [[1], [2]], [[1, 1], [2, 2]]]
sage: v = K.module_generators[1]
sage: psi = B.crystal_morphism([v], codomain=K, category=FiniteCrystals())
sage: psi
['D', 4] -> ['D', 4, 1] Virtual Crystal morphism:
  From: The crystal of tableaux of type ['D', 4] and shape(s) [[1, 1]]
  To:   Kirillov-Reshetikhin crystal of type ['D', 4, 1] with (r,s)=(2,2)
  Defn: [[1], [2]] |--> [[1], [2]]
sage: b = B.module_generators[0]
sage: psi(b)
[[1], [2]]
sage: psi(b.to_lowest_weight()[0])
[[-2], [-1]]

```

We can define crystal morphisms using a different set of generators. For example, we construct an example using the lowest weight vector:

```
sage: B = crystals.Tableaux(['A', 2], shape=[1])
sage: La = RootSystem(['A', 2]).weight_lattice().fundamental_weights()
sage: T = crystals.elementary.T(['A', 2], La[2])
sage: Bp = T.tensor(B)
sage: C = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: x = C.module_generators[0].f_string([1, 2])
sage: psi = Bp.crystal_morphism([x], generators=Bp.lowest_weight_vectors())
sage: psi(Bp.highest_weight_vector())
[[1, 1], [2]]
```

We can also use a dictionary to specify the generators and their images:

```
sage: psi = Bp.crystal_morphism({Bp.lowest_weight_vectors()[0]: x})
sage: psi(Bp.highest_weight_vector())
[[1, 1], [2]]
```

We construct a twisted crystal morphism induced from the diagram automorphism of type $A_3^{(1)}$:

```
sage: La = RootSystem(['A', 3, 1]).weight_lattice(extended=True).fundamental_
↳weights()
sage: B0 = crystals.GeneralizedYoungWalls(3, La[0])
sage: B1 = crystals.GeneralizedYoungWalls(3, La[1])
sage: phi = B0.crystal_morphism(B1.module_generators, automorphism={0:1, 1:
↳1:2, 2:3, 3:0})
sage: phi
['A', 3, 1] Twisted Crystal morphism:
  From: Highest weight crystal of generalized Young walls of Cartan type ['A
↳', 3, 1] and highest weight Lambda[0]
  To:   Highest weight crystal of generalized Young walls of Cartan type ['A
↳', 3, 1] and highest weight Lambda[1]
  Defn: [] |--> []
sage: x = B0.module_generators[0].f_string([0, 1, 2, 3]); x
[[0, 3], [1], [2]]
sage: phi(x)
[[], [1, 0], [2], [3]]
```

We construct a virtual crystal morphism from type G_2 into type D_4 :

```
sage: D = crystals.Tableaux(['D', 4], shape=[1, 1])
sage: G = crystals.Tableaux(['G', 2], shape=[1])
sage: psi = G.crystal_morphism(D.module_generators,
.....:                               virtualization={1:[2], 2:[1, 3, 4]},
.....:                               scaling_factors={1:1, 2:1})
sage: for x in G:
.....:     ascii_art(x, psi(x), sep=' |--> ')
.....:     print("")
          1
1  |-->  2

          1
2  |-->  3
```

(continues on next page)

(continued from previous page)

```

      2
3  |--> -3

      3
0  |--> -3

      3
-3 |--> -2

      -3
-2 |--> -1

      -2
-1 |--> -1

```

digraph(*subset=None, index_set=None*)

Return the **DiGraph** associated to *self*.

INPUT:

- *subset* – (optional) a subset of vertices for which the digraph should be constructed
- *index_set* – (optional) the index set to draw arrows

EXAMPLES:

```

sage: C = Crystals().example(5)
sage: C.digraph()
Digraph on 6 vertices

```

The edges of the crystal graph are by default colored using blue for edge 1, red for edge 2, and green for edge 3:

```

sage: C = Crystals().example(3)
sage: G = C.digraph()
sage: view(G) # optional - dot2tex graphviz, not tested (opens external_
↪window)

```

One may also overwrite the colors:

```

sage: C = Crystals().example(3)
sage: G = C.digraph()
sage: G.set_latex_options(color_by_label = {1:"red", 2:"purple", 3:"blue"})
sage: view(G) # optional - dot2tex graphviz, not tested (opens external_
↪window)

```

Or one may add colors to yet unspecified edges:

```

sage: C = Crystals().example(4)
sage: G = C.digraph()
sage: C.cartan_type()._index_set_coloring[4]="purple"
sage: view(G) # optional - dot2tex graphviz, not tested (opens external_
↪window)

```

Here is an example of how to take the top part up to a given depth of an infinite dimensional crystal:

```

sage: C = CartanType(['C',2,1])
sage: La = C.root_system().weight_lattice().fundamental_weights()
sage: T = crystals.HighestWeight(La[0])
sage: S = T.subcrystal(max_depth=3)
sage: G = T.digraph(subset=S); G
Digraph on 5 vertices
sage: sorted(G.vertices(), key=str)
[(-Lambda[0] + 2*Lambda[1] - delta,),
 (1/2*Lambda[0] + Lambda[1] - Lambda[2] - 1/2*delta, -1/2*Lambda[0] +
 ↪Lambda[1] - 1/2*delta),
 (1/2*Lambda[0] - Lambda[1] + Lambda[2] - 1/2*delta, -1/2*Lambda[0] +
 ↪Lambda[1] - 1/2*delta),
 (Lambda[0] - 2*Lambda[1] + 2*Lambda[2] - delta,),
 (Lambda[0],)]

```

Here is a way to construct a picture of a Demazure crystal using the subset option:

```

sage: B = crystals.Tableaux(['A',2], shape=[2,1])
sage: t = B.highest_weight_vector()
sage: D = B.demazure_subcrystal(t, [2,1])
sage: list(D)
[[[1, 1], [2]], [[1, 2], [2]], [[1, 1], [3]],
 [[1, 3], [2]], [[1, 3], [3]]]
sage: view(D) # optional - dot2tex graphviz, not tested (opens external_
↪window)

```

We can also choose to display particular arrows using the `index_set` option:

```

sage: C = crystals.KirillovReshetikhin(['D',4,1], 2, 1)
sage: G = C.digraph(index_set=[1,3])
sage: len(G.edges())
20
sage: view(G) # optional - dot2tex graphviz, not tested (opens external_
↪window)

```

Todo: Add more tests.

`direct_sum(X)`

Return the direct sum of `self` with `X`.

EXAMPLES:

```

sage: B = crystals.Tableaux(['A',2], shape=[2,1])
sage: C = crystals.Letters(['A',2])
sage: B.direct_sum(C)
Direct sum of the crystals Family
(The crystal of tableaux of type ['A', 2] and shape(s) [[2, 1]],
 The crystal of letters for type ['A', 2])

```

As a shorthand, we can use `+`:

```

sage: B + C
Direct sum of the crystals Family

```

(continues on next page)

(continued from previous page)

```
(The crystal of tableaux of type ['A', 2] and shape(s) [[2, 1]],
The crystal of letters for type ['A', 2])
```

dot_tex()

Return a dot_tex string representation of self.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 2])
sage: C.dot_tex()
'digraph G { \n node [ shape=plaintext ];\n N_0 [ label = " ", texlbl = "
↪$1$" ];\n N_1 [ label = " ", texlbl = "$2$" ];\n N_2 [ label = " ",
↪texlbl = "$3$" ];\n N_0 -> N_1 [ label = " ", texlbl = "1" ];\n N_1 ->
↪N_2 [ label = " ", texlbl = "2" ];\n}'
```

index_set()

Returns the index set of the Dynkin diagram underlying the crystal

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C.index_set()
(1, 2, 3, 4, 5)
```

is_connected()

Return True if self is a connected crystal.

EXAMPLES:

```
sage: B = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: C = crystals.Letters(['A', 2])
sage: T = crystals.TensorProduct(B, C)
sage: B.is_connected()
True
sage: T.is_connected()
False
```

latex(options)**

Returns the crystal graph as a latex string. This can be exported to a file with self.latex_file('filename').

EXAMPLES:

```
sage: T = crystals.Tableaux(['A', 2], shape=[1])
sage: T._latex_()
'...tikzpicture...'
sage: view(T) # optional - dot2tex graphviz, not tested (opens external_
↪window)
```

One can for example also color the edges using the following options:

```
sage: T = crystals.Tableaux(['A', 2], shape=[1])
sage: T._latex_(color_by_label={0:"black", 1:"red", 2:"blue"})
'...tikzpicture...'
```

latex_file(filename)

Export a file, suitable for pdflatex, to 'filename'.

This requires a proper installation of `dot2tex` in sage-python. For more information see the documentation for `self.latex()`.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: fn = tmp_filename(ext='.tex')
sage: C.latex_file(fn)
```

metapost(*filename*, *thicklines=False*, *labels=True*, *scaling_factor=1.0*, *tallness=1.0*)

Use `C.metapost("filename.mp",[options])`, where options can be:

`thicklines = True` (for thicker edges) `labels = False` (to suppress labeling of the vertices) `scaling_factor=value`, where `value` is a floating point number, 1.0 by default. Increasing or decreasing the scaling factor changes the size of the image. `tallness=1.0`. Increasing makes the image taller without increasing the width.

Root operators `e(1)` or `f(1)` move along red lines, `e(2)` or `f(2)` along green. The highest weight is in the lower left. Vertices with the same weight are kept close together. The concise labels on the nodes are strings introduced by Berenstein and Zelevinsky and Littelmann; see Littelmann's paper *Cones, Crystals, Patterns*, sections 5 and 6.

For Cartan types B2 or C2, the pattern has the form

a2 a3 a4 a1

where $c*a2 = a3 = 2*a4 = 0$ and $a1=0$, with $c=2$ for B2, $c=1$ for C2. Applying `e(2)` $a1$ times, `e(1)` $a2$ times, `e(2)` $a3$ times, `e(1)` $a4$ times returns to the highest weight. (Observe that Littelmann writes the roots in opposite of the usual order, so our `e(1)` is his `e(2)` for these Cartan types.) For type A2, the pattern has the form

a3 a2 a1

where applying `e(1)` $a1$ times, `e(2)` $a2$ times then `e(3)` $a1$ times returns to the highest weight. These data determine the vertex and may be translated into a Gelfand-Tsetlin pattern or tableau.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 2])
sage: C.metapost(tmp_filename())
```

```
sage: C = crystals.Letters(['A', 5])
sage: C.metapost(tmp_filename())
Traceback (most recent call last):
...
NotImplementedError
```

number_of_connected_components()

Return the number of connected components of `self`.

EXAMPLES:

```
sage: B = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: C = crystals.Letters(['A', 2])
sage: T = crystals.TensorProduct(B, C)
sage: T.number_of_connected_components()
3
```

plot(**options)

Return the plot of `self` as a directed graph.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: print(C.plot())
Graphics object consisting of 17 graphics primitives
```

plot3d(**options)

Return the 3-dimensional plot of `self` as a directed graph.

EXAMPLES:

```
sage: C = crystals.KirillovReshetikhin(['A', 3, 1], 2, 1)
sage: print(C.plot3d())
Graphics3d Object
```

subcrystal(*index_set=None, generators=None, max_depth=inf, direction='both', contained=None, virtualization=None, scaling_factors=None, cartan_type=None, category=None*)

Construct the subcrystal from generators using e_i and/or f_i for all i in `index_set`.

INPUT:

- `index_set` – (default: None) the index set; if None then use the index set of the crystal
- `generators` – (default: None) the list of generators; if None then use the module generators of the crystal
- `max_depth` – (default: infinity) the maximum depth to build
- `direction` – (default: 'both') the direction to build the subcrystal; it can be one of the following:
 - 'both' - using both e_i and f_i
 - 'upper' - using e_i
 - 'lower' - using f_i
- `contained` – (optional) a set or function defining the containment in the subcrystal
- `virtualization, scaling_factors` – (optional) dictionaries whose key i corresponds to the sets σ_i and γ_i respectively used to define virtual crystals; see `VirtualCrystal`
- `cartan_type` – (optional) specify the Cartan type of the subcrystal
- `category` – (optional) specify the category of the subcrystal

EXAMPLES:

```
sage: C = crystals.KirillovReshetikhin(['A', 3, 1], 1, 2)
sage: S = list(C.subcrystal(index_set=[1, 2])); S
[[[1, 1]], [[1, 2]], [[2, 2]], [[1, 3]], [[2, 3]], [[3, 3]]]
sage: C.cardinality()
10
sage: len(S)
6
sage: list(C.subcrystal(index_set=[1, 3], generators=[C(1, 4)]))
[[[1, 4]], [[2, 4]], [[1, 3]], [[2, 3]]]
sage: list(C.subcrystal(index_set=[1, 3], generators=[C(1, 4)], max_depth=1))
[[[1, 4]], [[2, 4]], [[1, 3]]]
sage: list(C.subcrystal(index_set=[1, 3], generators=[C(1, 4)], direction=
↪ 'upper'))
[[[1, 4]], [[1, 3]]]
sage: list(C.subcrystal(index_set=[1, 3], generators=[C(1, 4)], direction=
↪ 'lower'))
[[[1, 4]], [[2, 4]]]
```

(continues on next page)

(continued from previous page)

```

sage: G = C.subcrystal(index_set=[1,2,3]).digraph()
sage: GA = crystals.Tableaux('A3', shape=[2]).digraph()
sage: G.is_isomorphic(GA, edge_labels=True)
True

```

We construct the subcrystal which contains the necessary data to construct the corresponding dual equivalence graph:

```

sage: C = crystals.Tableaux(['A',5], shape=[3,3])
sage: is_wt0 = lambda x: all(x.epsilon(i) == x.phi(i) for i in x.parent().
↪ index_set())
sage: def check(x):
.....:     if is_wt0(x):
.....:         return True
.....:     for i in x.parent().index_set()[:-1]:
.....:         L = [x.e(i), x.e_string([i,i+1]), x.f(i), x.f_string([i,i+1])]
.....:         if any(y is not None and is_wt0(y) for y in L):
.....:             return True
.....:     return False
sage: wt0 = [x for x in C if is_wt0(x)]
sage: S = C.subcrystal(contained=check, generators=wt0)
sage: S.module_generators[0]
[[1, 3, 5], [2, 4, 6]]
sage: S.module_generators[0].e(2).e(3).f(2).f(3)
[[1, 2, 5], [3, 4, 6]]

```

An example of a type B_2 virtual crystal inside of a type A_3 ambient crystal:

```

sage: A = crystals.Tableaux(['A',3], shape=[2,1,1])
sage: S = A.subcrystal(virtualization={1:[1,3], 2:[2]},
.....:                 scaling_factors={1:1,2:1}, cartan_type=['B',2])
sage: B = crystals.Tableaux(['B',2], shape=[1])
sage: S.digraph().is_isomorphic(B.digraph(), edge_labels=True)
True

```

tensor(*crystals, **options)

Return the tensor product of self with the crystals B.

EXAMPLES:

```

sage: C = crystals.Letters(['A', 3])
sage: B = crystals.infinity.Tableaux(['A', 3])
sage: T = C.tensor(C, B); T
Full tensor product of the crystals
[The crystal of letters for type ['A', 3],
 The crystal of letters for type ['A', 3],
 The infinity crystal of tableaux of type ['A', 3]]
sage: tensor([C, C, B]) is T
True

sage: C = crystals.Letters(['A',2])
sage: T = C.tensor(C, C, generators=[[C(2),C(1),C(1)],[C(1),C(2),C(1)]]); T

```

(continues on next page)

(continued from previous page)

```
The tensor product of the crystals
[The crystal of letters for type ['A', 2],
 The crystal of letters for type ['A', 2],
 The crystal of letters for type ['A', 2]]
sage: T.module_generators
([2, 1, 1], [1, 2, 1])
```

weight_lattice_realization()

Return the weight lattice realization used to express weights in `self`.

This default implementation uses the ambient space of the root system for (non relabelled) finite types and the weight lattice otherwise. This is a legacy from when ambient spaces were partially implemented, and may be changed in the future.

For affine types, this returns the extended weight lattice by default.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C.weight_lattice_realization()
Ambient space of the Root system of type ['A', 5]
sage: K = crystals.KirillovReshetikhin(['A',2,1], 1, 1)
sage: K.weight_lattice_realization()
Weight lattice of the Root system of type ['A', 2, 1]
```

class SubcategoryMethods

Bases: `object`

Methods for all subcategories.

TensorProducts()

Return the full subcategory of objects of `self` constructed as tensor products.

See also:

- [*tensor.TensorProductsCategory*](#)
- [*RegressiveCovariantFunctorialConstruction*](#).

EXAMPLES:

```
sage: HighestWeightCrystals().TensorProducts()
Category of tensor products of highest weight crystals
```

class TensorProducts(category, *args)

Bases: [*sage.categories.tensor.TensorProductsCategory*](#)

The category of crystals constructed by tensor product of crystals.

extra_super_categories()

EXAMPLES:

```
sage: Crystals().TensorProducts().extra_super_categories()
[Category of crystals]
```

example(choice='highwt', **kws)

Returns an example of a crystal, as per [*Category.example\(\)*](#).

INPUT:

- `choice` – str [default: ‘highwt’]. Can be either ‘highwt’ for the highest weight crystal of type A, or ‘naive’ for an example of a broken crystal.
- `**kwds` – keyword arguments passed onto the constructor for the chosen crystal.

EXAMPLES:

```
sage: Crystals().example(choice='highwt', n=5)
Highest weight crystal of type A_5 of highest weight omega_1
sage: Crystals().example(choice='naive')
A broken crystal, defined by digraph, of dimension five.
```

super_categories()

EXAMPLES:

```
sage: Crystals().super_categories()
[Category of enumerated sets]
```

3.32 CW Complexes

class `sage.categories.cw_complexes.CWComplexes`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of CW complexes.

A CW complex is a Closure-finite cell complex in the Weak topology.

REFERENCES:

- [Wikipedia article CW_complex](#)

Note: The notion of “finite” is that the number of cells is finite.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: C = CWComplexes(); C
Category of CW complexes
```

Compact_extra_super_categories()

Return extraneous super categories for `CWComplexes().Compact()`.

A compact CW complex is finite, see Proposition A.1 in [Hat2002].

Todo: Fix the name of finite CW complexes.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: CWComplexes().Compact() # indirect doctest
Category of finite finite dimensional CW complexes
sage: CWComplexes().Compact() is CWComplexes().Finite()
True
```

class Connected(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

The category of connected CW complexes.

class ElementMethods

Bases: object

dimension()

Return the dimension of self.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: X = CWComplexes().example()
sage: X.an_element().dimension()
2
```

class Finite(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

Category of finite CW complexes.

A finite CW complex is a CW complex with a finite number of cells.

class ParentMethods

Bases: object

dimension()

Return the dimension of self.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: X = CWComplexes().example()
sage: X.dimension()
2
```

extra_super_categories()

Return the extra super categories of self.

A finite CW complex is a compact finite-dimensional CW complex.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: C = CWComplexes().Finite()
sage: C.extra_super_categories()
[Category of finite dimensional CW complexes,
Category of compact topological spaces]
```

class FiniteDimensional(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

Category of finite dimensional CW complexes.

class ParentMethods

Bases: object

cells()

Return the cells of self.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: X = CWComplexes().example()
sage: C = X.cells()
sage: sorted((d, C[d]) for d in C.keys())
[(0, (0-cell v,)),
 (1, (0-cell e1, 0-cell e2)),
 (2, (2-cell f,))]
```

dimension()

Return the dimension of self.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: X = CWComplexes().example()
sage: X.dimension()
2
```

class SubcategoryMethods

Bases: object

Connected()

Return the full subcategory of the connected objects of self.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: CWComplexes().Connected()
Category of connected CW complexes
```

FiniteDimensional()

Return the full subcategory of the finite dimensional objects of self.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: C = CWComplexes().FiniteDimensional(); C
Category of finite dimensional CW complexes
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: CWComplexes().super_categories()
[Category of topological spaces]
```

3.33 Discrete Valuation Rings (DVR) and Fields (DVF)

class `sage.categories.discrete_valuation.DiscreteValuationFields`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of discrete valuation fields

EXAMPLES:

```
sage: Qp(7) in DiscreteValuationFields()
True
sage: TestSuite(DiscreteValuationFields()).run()
```

class `ElementMethods`

Bases: `object`

valuation()

Return the valuation of this element.

EXAMPLES:

```
sage: x = Qp(5)(50)
sage: x.valuation()
2
```

class `ParentMethods`

Bases: `object`

residue_field()

Return the residue field of the ring of integers of this discrete valuation field.

EXAMPLES:

```
sage: Qp(5).residue_field()
Finite Field of size 5

sage: K.<u> = LaurentSeriesRing(QQ)
sage: K.residue_field()
Rational Field
```

uniformizer()

Return a uniformizer of this ring.

EXAMPLES:

```
sage: Qp(5).uniformizer()
5 + 0(5^21)
```

super_categories()

EXAMPLES:

```
sage: DiscreteValuationFields().super_categories()
[Category of fields]
```

class `sage.categories.discrete_valuation.DiscreteValuationRings`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of discrete valuation rings

EXAMPLES:

```
sage: GF(7)[['x']] in DiscreteValuationRings()
True
sage: TestSuite(DiscreteValuationRings()).run()
```

class ElementMethods

Bases: object

euclidean_degree()

Return the Euclidean degree of this element.

gcd(*other*)

Return the greatest common divisor of self and other, normalized so that it is a power of the distinguished uniformizer.

is_unit()

Return True if self is invertible.

EXAMPLES:

```
sage: x = Zp(5)(50)
sage: x.is_unit()
False

sage: x = Zp(7)(50)
sage: x.is_unit()
True
```

lcm(*other*)

Return the least common multiple of self and other, normalized so that it is a power of the distinguished uniformizer.

quo_rem(*other*)

Return the quotient and remainder for Euclidean division of self by other.

valuation()

Return the valuation of this element.

EXAMPLES:

```
sage: x = Zp(5)(50)
sage: x.valuation()
2
```

class ParentMethods

Bases: object

residue_field()

Return the residue field of this ring.

EXAMPLES:

```
sage: Zp(5).residue_field()
Finite Field of size 5

sage: K.<u> = QQ[[]]
sage: K.residue_field()
Rational Field
```

uniformizer()

Return a uniformizer of this ring.

EXAMPLES:

```
sage: Zp(5).uniformizer()
5 + 0(5^21)

sage: K.<u> = QQ[[]]
sage: K.uniformizer()
u
```

super_categories()

EXAMPLES:

```
sage: DiscreteValuationRings().super_categories()
[Category of euclidean domains]
```

3.34 Distributive Magmas and Additive Magmas

class `sage.categories.distributive_magmas_and_additive_magmas.DistributiveMagmasAndAdditiveMagmas`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of sets $(S, +, *)$ with $*$ distributing on $+$.

This is similar to a ring, but $+$ and $*$ are only required to be (additive) magmas.

EXAMPLES:

```
sage: from sage.categories.distributive_magmas_and_additive_magmas import _
↪DistributiveMagmasAndAdditiveMagmas
sage: C = DistributiveMagmasAndAdditiveMagmas(); C
Category of distributive magmas and additive magmas
sage: C.super_categories()
[Category of magmas and additive magmas]
```

class `AdditiveAssociative`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

class `AdditiveCommutative`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

class `AdditiveUnital`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

class `Associative`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

AdditiveInverse

alias of `sage.categories.rngs.Rngs`

Unital

alias of `sage.categories.semirings.Semirings`

class `CartesianProducts`(*category*, *args)

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

extra_super_categories()

Implement the fact that a Cartesian product of magmas distributing over additive magmas is a magma distributing over an additive magma.

EXAMPLES:

```
sage: C = (Magmas() & AdditiveMagmas()).Distributive().CartesianProducts()
sage: C.extra_super_categories()
[Category of distributive magmas and additive magmas]
sage: C.axioms()
frozenset({'Distributive'})
```

class ParentMethods

Bases: object

3.35 Division rings

class sage.categories.division_rings.DivisionRings(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

The category of division rings

A division ring (or skew field) is a not necessarily commutative ring where all non-zero elements have multiplicative inverses

EXAMPLES:

```
sage: DivisionRings()
Category of division rings
sage: DivisionRings().super_categories()
[Category of domains]
```

Commutative

alias of *sage.categories.fields.Fields*

class ElementMethods

Bases: object

Finite_extra_super_categories()

Return extraneous super categories for *DivisionRings().Finite()*.

EXAMPLES:

Any field is a division ring:

```
sage: Fields().is_subcategory(DivisionRings())
True
```

This methods specifies that, by Weddeburn theorem, the reciprocal holds in the finite case: a finite division ring is commutative and thus a field:

```
sage: DivisionRings().Finite_extra_super_categories()
(Category of commutative magmas,)
sage: DivisionRings().Finite()
Category of finite enumerated fields
```

Warning: This is not implemented in `DivisionRings.Finite.extra_super_categories` because the categories of finite division rings and of finite fields coincide. See the section *Deduction rules* in the documentation of axioms.

class ParentMethods

Bases: object

extra_super_categories()

Return the *Domains* category.

This method specifies that a division ring has no zero divisors, i.e. is a domain.

See also:

The *Deduction rules* section in the documentation of axioms

EXAMPLES:

```
sage: DivisionRings().extra_super_categories()
(Category of domains,)
sage: "NoZeroDivisors" in DivisionRings().axioms()
True
```

3.36 Domains

class `sage.categories.domains.Domains`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of domains

A domain (or non-commutative integral domain), is a ring, not necessarily commutative, with no nonzero zero divisors.

EXAMPLES:

```
sage: C = Domains(); C
Category of domains
sage: C.super_categories()
[Category of rings]
sage: C is Rings().NoZeroDivisors()
True
```

Commutative

alias of `sage.categories.integral_domains.IntegralDomains`

class ElementMethods

Bases: object

class ParentMethods

Bases: object

super_categories()

EXAMPLES:

```
sage: Domains().super_categories()
[Category of rings]
```

3.37 Enumerated sets

class `sage.categories.enumerated_sets.EnumeratedSets`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of enumerated sets

An *enumerated set* is a *finite* or *countable* set or multiset S together with a canonical enumeration of its elements; conceptually, this is very similar to an immutable list. The main difference lies in the names and the return type of the methods, and of course the fact that the list of elements is not supposed to be expanded in memory. Whenever possible one should use one of the two sub-categories `FiniteEnumeratedSets` or `InfiniteEnumeratedSets`.

The purpose of this category is threefold:

- to fix a common interface for all these sets;
- to provide a bunch of default implementations;
- to provide consistency tests.

The standard methods for an enumerated set S are:

- `S.cardinality()`: the number of elements of the set. This is the equivalent for `len` on a list except that the return value is specified to be a Sage `Integer` or `infinity`, instead of a Python `int`.
- `iter(S)`: an iterator for the elements of the set;
- `S.list()`: the list of the elements of the set, when possible; raises a `NotImplementedError` if the list is predictably too large to be expanded in memory.
- `S.unrank(n)`: the n -th element of the set when n is a sage `Integer`. This is the equivalent for `l[n]` on a list.
- `S.rank(e)`: the position of the element e in the set; This is equivalent to `l.index(e)` for a list except that the return value is specified to be a Sage `Integer`, instead of a Python `int`.
- `S.first()`: the first object of the set; it is equivalent to `S.unrank(0)`.
- `S.next(e)`: the object of the set which follows e ; It is equivalent to `S.unrank(S.rank(e)+1)`.
- `S.random_element()`: a random generator for an element of the set. Unless otherwise stated, and for finite enumerated sets, the probability is uniform.

For examples and tests see:

- `FiniteEnumeratedSets().example()`
- `InfiniteEnumeratedSets().example()`

EXAMPLES:

```
sage: EnumeratedSets()
Category of enumerated sets
sage: EnumeratedSets().super_categories()
[Category of sets]
sage: EnumeratedSets().all_super_categories()
[Category of enumerated sets, Category of sets, Category of sets with partial maps, ↪
↪Category of objects]
```

class `CartesianProducts`(*category*, **args*)

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

class ParentMethods

Bases: object

first()

Return the first element.

EXAMPLES:

```
sage: cartesian_product([ZZ]*10).first()
(0, 0, 0, 0, 0, 0, 0, 0, 0, 0)
```

class ElementMethods

Bases: object

rank()

Return the rank of self in its parent.

See also *EnumeratedSets.ElementMethods.rank()*

EXAMPLES:

```
sage: F = FiniteSemigroups().example(('a', 'b', 'c'))
sage: L = list(F)
sage: L[7].rank()
7
sage: all(x.rank() == i for i, x in enumerate(L))
True
```

Finitealias of *sage.categories.finite_enumerated_sets.FiniteEnumeratedSets***Infinite**alias of *sage.categories.infinite_enumerated_sets.InfiniteEnumeratedSets***class ParentMethods**

Bases: object

first()

The “first” element of self.

self.first() returns the first element of the set self. This is a generic implementation from the category EnumeratedSets() which can be used when the method `__iter__` is provided.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: C.first() # indirect doctest
1
```

is_empty()

Return whether this set is empty.

EXAMPLES:

```
sage: F = FiniteEnumeratedSet([1, 2, 3])
sage: F.is_empty()
False
sage: F = FiniteEnumeratedSet([])
sage: F.is_empty()
True
```

iterator_range(*start=None, stop=None, step=None*)

Iterate over the range of elements of *self* starting at *start*, ending at *stop*, and stepping by *step*.

See also:

`unrank()`, `unrank_range()`

EXAMPLES:

```
sage: P = Partitions()
sage: list(P.iterator_range(stop=5))
[[], [1], [2], [1, 1], [3]]
sage: list(P.iterator_range(0, 5))
[[], [1], [2], [1, 1], [3]]
sage: list(P.iterator_range(3, 5))
[[1, 1], [3]]
sage: list(P.iterator_range(3, 10))
[[1, 1], [3], [2, 1], [1, 1, 1], [4], [3, 1], [2, 2]]
sage: list(P.iterator_range(3, 10, 2))
[[1, 1], [2, 1], [4], [2, 2]]
sage: it = P.iterator_range(3)
sage: [next(it) for x in range(10)]
[[1, 1],
 [3], [2, 1], [1, 1, 1],
 [4], [3, 1], [2, 2], [2, 1, 1], [1, 1, 1, 1],
 [5]]
sage: it = P.iterator_range(3, step=2)
sage: [next(it) for x in range(5)]
[[1, 1],
 [2, 1],
 [4], [2, 2], [1, 1, 1, 1]]
sage: next(P.iterator_range(stop=-3))
Traceback (most recent call last):
...
NotImplementedError: cannot list an infinite set
sage: next(P.iterator_range(start=-3))
Traceback (most recent call last):
...
NotImplementedError: cannot list an infinite set
```

list()

Return a list of the elements of *self*.

The elements of set *x* are created and cached on the first call of `x.list()`. Then each call of `x.list()` returns a new list from the cached result. Thus in looping, it may be better to do `for e in x:`, not `for e in x.list():`.

If *x* is not known to be finite, then an exception is raised.

EXAMPLES:

```
sage: (GF(3)^2).list()
[(0, 0), (1, 0), (2, 0), (0, 1), (1, 1), (2, 1), (0, 2), (1, 2), (2, 2)]
sage: R = Integers(11)
sage: R.list()
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
sage: l = R.list(); l
```

(continues on next page)

(continued from previous page)

```
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
sage: l.remove(0); l
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
sage: R.list()
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

map(*f*, *name=None*)Return the image $\{f(x)|x \in \text{self}\}$ of this enumerated set by *f*, as an enumerated set.*f* is supposed to be injective.

EXAMPLES:

```
sage: R = Compositions(4).map(attrcall('partial_sums')); R
Image of Compositions of 4 by *.partial_sums()
sage: R.cardinality()
8
sage: R.list()
[[1, 2, 3, 4], [1, 2, 4], [1, 3, 4], [1, 4], [2, 3, 4], [2, 4], [3, 4], [4]]
sage: [ r for r in R ]
[[1, 2, 3, 4], [1, 2, 4], [1, 3, 4], [1, 4], [2, 3, 4], [2, 4], [3, 4], [4]]
```

Warning: If the function is not injective, then there may be repeated elements:

```
sage: P = Compositions(4)
sage: P.list()
[[1, 1, 1, 1], [1, 1, 2], [1, 2, 1], [1, 3], [2, 1, 1], [2, 2], [3, 1], ...
↪ [4]]
sage: P.map(attrcall('major_index')).list()
[6, 3, 4, 1, 5, 2, 3, 0]
```

Warning: `MapCombinatorialClass` needs to be refactored to use categories:

```
sage: R.category() # todo: not implemented
Category of enumerated sets
sage: TestSuite(R).run(skip=['_test_an_element', '_test_category', '_test_
↪some_elements'])
```

next(*obj*)The “next” element after *obj* in *self*.*self*.next(*e*) returns the element of the set *self* which follows *e*. This is a generic implementation from the category `EnumeratedSets()` which can be used when the method `__iter__` is provided.Remark: this is the default (brute force) implementation of the category `EnumeratedSets()`. Its complexity is $O(r)$, where *r* is the rank of *obj*.

EXAMPLES:

```
sage: C = InfiniteEnumeratedSets().example()
sage: C._next_from_iterator(10) # indirect doctest
11
```


TODO: specify the behavior when `obj` is not in `self`.

`random_element()`

Return a random element in `self`.

Unless otherwise stated, and for finite enumerated sets, the probability is uniform.

This is a generic implementation from the category `EnumeratedSets()`. It raise a `NotImplementedError` since one does not know whether the set is finite.

EXAMPLES:

```
sage: class broken(UniqueRepresentation, Parent):
.....: def __init__(self):
.....:     Parent.__init__(self, category = EnumeratedSets())
sage: broken().random_element()
Traceback (most recent call last):
...
NotImplementedError: unknown cardinality
```

`rank(x)`

The rank of an element of `self`

`self.rank(x)` returns the rank of x , that is its position in the enumeration of `self`. This is an integer between 0 and $n-1$ where n is the cardinality of `self`, or `None` if x is not in `self`.

This is the default (brute force) implementation from the category `EnumeratedSets()` which can be used when the method `__iter__` is provided. Its complexity is $O(r)$, where r is the rank of `obj`. For infinite enumerated sets, this won't terminate when x is not in `self`

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: list(C)
[1, 2, 3]
sage: C.rank(3) # indirect doctest
2
sage: C.rank(5) # indirect doctest
```

`some_elements()`

Return some elements in `self`.

See `TestSuite` for a typical use case.

This is a generic implementation from the category `EnumeratedSets()` which can be used when the method `__iter__` is provided. It returns an iterator for up to the first 100 elements of `self`

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: list(C.some_elements()) # indirect doctest
[1, 2, 3]
```

`unrank(r)`

The r -th element of `self`

`self.unrank(r)` returns the r -th element of `self`, where r is an integer between 0 and $n-1$ where n is the cardinality of `self`.

This is the default (brute force) implementation from the category `EnumeratedSets()` which can be used when the method `__iter__` is provided. Its complexity is $O(r)$, where r is the rank of `obj`.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: C.unrank(2) # indirect doctest
3
sage: C._unrank_from_iterator(5)
Traceback (most recent call last):
...
ValueError: the value must be between 0 and 2 inclusive
```

unrank_range(*start=None, stop=None, step=None*)

Return the range of elements of *self* starting at *start*, ending at *stop*, and stepping by *step*.

See also:

`unrank()`, `iterator_range()`

EXAMPLES:

```
sage: P = Partitions()
sage: P.unrank_range(stop=5)
[[], [1], [2], [1, 1], [3]]
sage: P.unrank_range(0, 5)
[[], [1], [2], [1, 1], [3]]
sage: P.unrank_range(3, 5)
[[1, 1], [3]]
sage: P.unrank_range(3, 10)
[[1, 1], [3], [2, 1], [1, 1, 1], [4], [3, 1], [2, 2]]
sage: P.unrank_range(3, 10, 2)
[[1, 1], [2, 1], [4], [2, 2]]
sage: P.unrank_range(3)
Traceback (most recent call last):
...
NotImplementedError: cannot list an infinite set
sage: P.unrank_range(stop=-3)
Traceback (most recent call last):
...
NotImplementedError: cannot list an infinite set
sage: P.unrank_range(start=-3)
Traceback (most recent call last):
...
NotImplementedError: cannot list an infinite set
```

additional_structure()

Return None.

Indeed, morphisms of enumerated sets are not required to preserve the enumeration.

See also:

`Category.additional_structure()`

EXAMPLES:

```
sage: EnumeratedSets().additional_structure()
```

super_categories()

EXAMPLES:

```
sage: EnumeratedSets().super_categories()
[Category of sets]
```

3.38 Euclidean domains

AUTHORS:

- Teresa Gomez-Diaz (2008): initial version
- Julian Rueth (2013-09-13): added euclidean degree, quotient remainder, and their tests

class `sage.categories.euclidean_domains.EuclideanDomains`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of constructive euclidean domains, i.e., one can divide producing a quotient and a remainder where the remainder is either zero or its `ElementMethods.euclidean_degree()` is smaller than the divisor.

EXAMPLES:

```
sage: EuclideanDomains()
Category of euclidean domains
sage: EuclideanDomains().super_categories()
[Category of principal ideal domains]
```

class `ElementMethods`

Bases: `object`

euclidean_degree()

Return the degree of this element as an element of an Euclidean domain, i.e., for elements a, b the euclidean degree f satisfies the usual properties:

1. if b is not zero, then there are elements q and r such that $a = bq + r$ with $r = 0$ or $f(r) < f(b)$
2. if a, b are not zero, then $f(a) \leq f(ab)$

Note: The name `euclidean_degree` was chosen because the euclidean function has different names in different contexts, e.g., absolute value for integers, degree for polynomials.

OUTPUT:

For non-zero elements, a natural number. For the zero element, this might raise an exception or produce some other output, depending on the implementation.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: x.euclidean_degree()
1
sage: ZZ.one().euclidean_degree()
1
```

gcd(*other*)

Return the greatest common divisor of this element and `other`.

INPUT:

- `other` – an element in the same ring as `self`

ALGORITHM:

Algorithm 3.2.1 in [Coh1993].

EXAMPLES:

```
sage: R.<x> = PolynomialRing(QQ, sparse=True)
sage: EuclideanDomains().element_class.gcd(x, x+1)
-1
```

quo_rem(*other*)

Return the quotient and remainder of the division of this element by the non-zero element *other*.

INPUT:

- *other* – an element in the same euclidean domain

OUTPUT:

a pair of elements

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: x.quo_rem(x)
(1, 0)
```

class ParentMethods

Bases: object

gcd_free_basis(*elts*)

Compute a set of coprime elements that can be used to express the elements of *elts*.

INPUT:

- *elts* - A sequence of elements of *self*.

OUTPUT:

A GCD-free basis (also called a coprime base) of *elts*; that is, a set of pairwise relatively prime elements of *self* such that any element of *elts* can be written as a product of elements of the set.

ALGORITHM:

Naive implementation of the algorithm described in Section 4.8 of Bach & Shallit [BS1996].

EXAMPLES:

```
sage: ZZ.gcd_free_basis([1])
[]
sage: ZZ.gcd_free_basis([4, 30, 14, 49])
[2, 15, 7]

sage: Pol.<x> = QQ[]
sage: sorted(Pol.gcd_free_basis([
.....:      (x+1)^3*(x+2)^3*(x+3), (x+1)*(x+2)*(x+3),
.....:      (x+1)*(x+2)*(x+4)]))
[x + 3, x + 4, x^2 + 3*x + 2]
```

is_euclidean_domain()

Return True, since this is an object of the category of Euclidean domains.

EXAMPLES:

```
sage: Parent(QQ, category=EuclideanDomains()).is_euclidean_domain()
True
```

super_categories()

EXAMPLES:

```
sage: EuclideanDomains().super_categories()
[Category of principal ideal domains]
```

3.39 Fields

class `sage.categories.fields.Fields`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of (commutative) fields, i.e. commutative rings where all non-zero elements have multiplicative inverses

EXAMPLES:

```
sage: K = Fields()
sage: K
Category of fields
sage: Fields().super_categories()
[Category of euclidean domains, Category of division rings]

sage: K(IntegerRing())
Rational Field
sage: K(PolynomialRing(GF(3), 'x'))
Fraction Field of Univariate Polynomial Ring in x over
Finite Field of size 3
sage: K(RealField())
Real Field with 53 bits of precision
```

class `ElementMethods`

Bases: `object`

euclidean_degree()

Return the degree of this element as an element of an Euclidean domain.

In a field, this returns 0 for all but the zero element (for which it is undefined).

EXAMPLES:

```
sage: QQ.one().euclidean_degree()
0
```

factor()

Return a factorization of `self`.

Since `self` is either a unit or zero, this function is trivial.

EXAMPLES:

```

sage: x = GF(7)(5)
sage: x.factor()
5
sage: RR(0).factor()
Traceback (most recent call last):
...
ArithmeticError: factorization of 0.0000000000000000 is not defined

```

gcd(*other*)

Greatest common divisor.

Note: Since we are in a field and the greatest common divisor is only determined up to a unit, it is correct to either return zero or one. Note that fraction fields of unique factorization domains provide a more sophisticated gcd.

EXAMPLES:

```

sage: K = GF(5)
sage: K(2).gcd(K(1))
1
sage: K(0).gcd(K(0))
0
sage: all(x.gcd(y) == (0 if x == 0 and y == 0 else 1) for x in K for y in K)
True

```

For field of characteristic zero, the gcd of integers is considered as if they were elements of the integer ring:

```

sage: gcd(15.0, 12.0)
3.0000000000000000

```

But for other floating point numbers, the gcd is just 0.0 or 1.0:

```

sage: gcd(3.2, 2.18)
1.0000000000000000

sage: gcd(0.0, 0.0)
0.0000000000000000

```

AUTHOR:

- Simon King (2011-02) – [trac ticket #10771](#)
- Vincent Delecroix (2015) – [trac ticket #17671](#)

inverse_of_unit()

Return the inverse of this element.

EXAMPLES:

```

sage: NumberField(x^7+2, 'a')(2).inverse_of_unit()
1/2

```

Trying to invert the zero element typically raises a `ZeroDivisionError`:

```
sage: QQ(0).inverse_of_unit()
Traceback (most recent call last):
...
ZeroDivisionError: rational division by zero
```

To catch that exception in a way that also works for non-units in more general rings, use something like:

```
sage: try:
.....:     QQ(0).inverse_of_unit()
.....: except ArithmeticError:
.....:     pass
```

Also note that some “fields” allow one to invert the zero element:

```
sage: RR(0).inverse_of_unit()
+infinity
```

is_unit()

Returns True if `self` has a multiplicative inverse.

EXAMPLES:

```
sage: QQ(2).is_unit()
True
sage: QQ(0).is_unit()
False
```

lcm(*other*)

Least common multiple.

Note: Since we are in a field and the least common multiple is only determined up to a unit, it is correct to either return zero or one. Note that fraction fields of unique factorization domains provide a more sophisticated lcm.

EXAMPLES:

```
sage: GF(2)(1).lcm(GF(2)(0))
0
sage: GF(2)(1).lcm(GF(2)(1))
1
```

For field of characteristic zero, the lcm of integers is considered as if they were elements of the integer ring:

```
sage: lcm(15.0, 12.0)
60.00000000000000
```

But for others floating point numbers, it is just 0.0 or 1.0:

```
sage: lcm(3.2, 2.18)
1.0000000000000000
```

(continues on next page)

(continued from previous page)

```
sage: lcm(0.0, 0.0)
0.0000000000000000
```

AUTHOR:

- Simon King (2011-02) – [trac ticket #10771](#)
- Vincent Delecroix (2015) – [trac ticket #17671](#)

quo_rem(*other*)Return the quotient with remainder of the division of this element by *other*.

INPUT:

- *other* – an element of the field

EXAMPLES:

```
sage: f, g = QQ(1), QQ(2)
sage: f. quo_rem(g)
(1/2, 0)
```

xgcd(*other*)Compute the extended gcd of *self* and *other*.

INPUT:

- *other* – an element with the same parent as *self*

OUTPUT:

A tuple (*r*, *s*, *t*) of elements in the parent of *self* such that $r = s * self + t * other$. Since the computations are done over a field, *r* is zero if *self* and *other* are zero, and one otherwise.

AUTHORS:

- Julian Rueth (2012-10-19): moved here from `sage.structure.element.FieldElement`

EXAMPLES:

```
sage: K = GF(5)
sage: K(2).xgcd(K(1))
(1, 3, 0)
sage: K(0).xgcd(K(4))
(1, 0, 4)
sage: K(1).xgcd(K(1))
(1, 1, 0)
sage: GF(5)(0).xgcd(GF(5)(0))
(0, 0, 0)
```

The `xgcd` of non-zero floating point numbers will be a triple of floating points. But if the input are two integral floating points the result is a floating point version of the standard gcd on \mathbf{Z} :

```
sage: xgcd(12.0, 8.0)
(4.000000000000000, 1.000000000000000, -1.000000000000000)

sage: xgcd(3.1, 2.98714)
(1.000000000000000, 0.322580645161290, 0.000000000000000)

sage: xgcd(0.0, 1.1)
(1.000000000000000, 0.000000000000000, 0.909090909090909)
```

Finitealias of `sage.categories.finite_fields.FiniteFields`

class ParentMethods

Bases: object

fraction_field()Returns the *fraction field* of `self`, which is `self`.

EXAMPLES:

```
sage: QQ.fraction_field() is QQ
True
```

is_field(*proof=True*)Returns True as `self` is a field.

EXAMPLES:

```
sage: QQ.is_field()
True
sage: Parent(QQ, category=Fields()).is_field()
True
```

is_integrally_closed()Return True, as per `IntegralDomain.is_integrally_closed()`: for every field F , F is its own field of fractions, hence every element of F is integral over F .

EXAMPLES:

```
sage: QQ.is_integrally_closed()
True
sage: QQbar.is_integrally_closed()
True
sage: Z5 = GF(5); Z5
Finite Field of size 5
sage: Z5.is_integrally_closed()
True
```

is_perfect()Return whether this field is perfect, i.e., its characteristic is $p = 0$ or every element has a p -th root.

EXAMPLES:

```
sage: QQ.is_perfect()
True
sage: GF(2).is_perfect()
True
sage: FunctionField(GF(2), 'x').is_perfect()
False
```

vector_space(*args, **kws)

Gives an isomorphism of this field with a vector space over a subfield.

This method is an alias for `free_module`, which may have more documentation.

INPUT:

- `base` – a subfield or morphism into this field (defaults to the base field)
- `basis` – a basis of the field as a vector space over the subfield; if not given, one is chosen automatically
- `map` – whether to return maps from and to the vector space

OUTPUT:

- `V` – a vector space over `base`
- `from_V` – an isomorphism from `V` to this field
- `to_V` – the inverse isomorphism from this field to `V`

EXAMPLES:

```
sage: K.<a> = Qq(125)
sage: V, fr, to = K.vector_space()
sage: v = V([1,2,3])
sage: fr(v, 7)
(3*a^2 + 2*a + 1) + 0(5^7)
```

`extra_super_categories()`

EXAMPLES:

```
sage: Fields().extra_super_categories()
[Category of euclidean domains]
```

3.40 Filtered Algebras

`class sage.categories.filtered_algebras.FilteredAlgebras`(*base_category*)

Bases: `sage.categories.filtered_modules.FilteredModulesCategory`

The category of filtered algebras.

An algebra A over a commutative ring R is *filtered* if A is endowed with a structure of a filtered R -module (whose underlying R -module structure is identical with that of the R -algebra A) such that the indexing set I (typically $I = \mathbf{N}$) is also an additive abelian monoid, the unity 1 of A belongs to F_0 , and we have $F_i \cdot F_j \subseteq F_{i+j}$ for all $i, j \in I$.

EXAMPLES:

```
sage: Algebras(ZZ).Filtered()
Category of filtered algebras over Integer Ring
sage: Algebras(ZZ).Filtered().super_categories()
[Category of algebras over Integer Ring,
 Category of filtered modules over Integer Ring]
```

REFERENCES:

- [Wikipedia article Filtered_algebra](#)

`class ParentMethods`

Bases: `object`

`graded_algebra()`

Return the associated graded algebra to `self`.

Todo: Implement a version of the associated graded algebra which does not require `self` to have a distinguished basis.

EXAMPLES:

```

sage: A = AlgebrasWithBasis(ZZ).Filtered().example()
sage: A.graded_algebra()
Graded Algebra of An example of a filtered algebra with basis:
the universal enveloping algebra of
Lie algebra of RR^3 with cross product over Integer Ring

```

3.41 Filtered Algebras With Basis

A filtered algebra with basis over a commutative ring R is a filtered algebra over R endowed with the structure of a filtered module with basis (with the same underlying filtered-module structure). See [FilteredAlgebras](#) and [FilteredModulesWithBasis](#) for these two notions.

class `sage.categories.filtered_algebras_with_basis.FilteredAlgebrasWithBasis`(*base_category*)
 Bases: `sage.categories.filtered_modules.FilteredModulesCategory`

The category of filtered algebras with a distinguished homogeneous basis.

A filtered algebra with basis over a commutative ring R is a filtered algebra over R endowed with the structure of a filtered module with basis (with the same underlying filtered-module structure). See [FilteredAlgebras](#) and [FilteredModulesWithBasis](#) for these two notions.

EXAMPLES:

```

sage: C = AlgebrasWithBasis(ZZ).Filtered(); C
Category of filtered algebras with basis over Integer Ring
sage: sorted(C.super_categories(), key=str)
[Category of algebras with basis over Integer Ring,
Category of filtered algebras over Integer Ring,
Category of filtered modules with basis over Integer Ring]

```

class `ElementMethods`

Bases: object

class `ParentMethods`

Bases: object

from_graded_conversion()

Return the inverse of the canonical R -module isomorphism $A \rightarrow \text{gr } A$ induced by the basis of A (where $A =$). This inverse is an isomorphism $\text{gr } A \rightarrow A$.

This is an isomorphism of R -modules, not of algebras. See the class documentation [AssociatedGradedAlgebra](#).

See also:

[to_graded_conversion\(\)](#)

EXAMPLES:

```

sage: A = Algebras(QQ).WithBasis().Filtered().example()
sage: p = A.an_element() + A.algebra_generators()['x'] + 2; p
U['x']^2*U['y']^2*U['z']^3 + 3*U['x'] + 3*U['y'] + 3
sage: q = A.to_graded_conversion()(p)
sage: A.from_graded_conversion()(q) == p
True

```

(continues on next page)

(continued from previous page)

```
sage: q.parent() is A.graded_algebra()
True
```

graded_algebra()

Return the associated graded algebra to self.

See [AssociatedGradedAlgebra](#) for the definition and the properties of this.

If the filtered algebra self with basis is called A , then this method returns $\text{gr } A$. The method [to_graded_conversion\(\)](#) returns the canonical R -module isomorphism $A \rightarrow \text{gr } A$ induced by the basis of A , and the method [from_graded_conversion\(\)](#) returns the inverse of this isomorphism. The method [projection\(\)](#) projects elements of A onto $\text{gr } A$ according to their place in the filtration on A .

Warning: When not overridden, this method returns the default implementation of an associated graded algebra – namely, `AssociatedGradedAlgebra(self)`, where `AssociatedGradedAlgebra` is `AssociatedGradedAlgebra`. But many instances of `FilteredAlgebrasWithBasis` override this method, as the associated graded algebra often is (isomorphic) to a simpler object (for instance, the associated graded algebra of a graded algebra can be identified with the graded algebra itself). Generic code that uses associated graded algebras (such as the code of the [induced_graded_map\(\)](#) method below) should make sure to only communicate with them via the [to_graded_conversion\(\)](#), [from_graded_conversion\(\)](#), and [projection\(\)](#) methods (in particular, do not expect there to be a conversion from self to `self.graded_algebra()`; this currently does not work for Clifford algebras). Similarly, when overriding [graded_algebra\(\)](#), make sure to accordingly redefine these three methods, unless their definitions below still apply to your case (this will happen whenever the basis of your [graded_algebra\(\)](#) has the same indexing set as self, and the partition of this indexing set according to degree is the same as for self).

Todo: Maybe the thing about the conversion from self to `self.graded_algebra()` on the Clifford at least could be made to work? (I would still warn the user against ASSUMING that it must work – as there is probably no way to guarantee it in all cases, and we shouldn't require users to mess with element constructors.)

EXAMPLES:

```
sage: A = AlgebrasWithBasis(ZZ).Filtered().example()
sage: A.graded_algebra()
Graded Algebra of An example of a filtered algebra with basis:
the universal enveloping algebra of
Lie algebra of RR^3 with cross product over Integer Ring
```

induced_graded_map(other, f)

Return the graded linear map between the associated graded algebras of self and other canonically induced by the filtration-preserving map $f : \text{self} \rightarrow \text{other}$.

Let A and B be two filtered algebras with basis, and let $(F_i)_{i \in I}$ and $(G_i)_{i \in I}$ be their filtrations. Let $f : A \rightarrow B$ be a linear map which preserves the filtration (i.e., satisfies $f(F_i) \subseteq G_i$ for all $i \in I$). Then, there is a canonically defined graded linear map $\text{gr } f : \text{gr } A \rightarrow \text{gr } B$ which satisfies

$$(\text{gr } f)(p_i(a)) = p_i(f(a)) \quad \text{for all } i \in I \text{ and } a \in F_i,$$

where the p_i on the left hand side is the canonical projection from F_i onto the i -th graded component of $\text{gr } A$, while the p_i on the right hand side is the canonical projection from G_i onto the i -th graded component of $\text{gr } B$.

INPUT:

- `other` – a filtered algebra with basis
- `f` – a filtration-preserving linear map from `self` to `other` (can be given as a morphism or as a function)

OUTPUT:

The graded linear map $\text{gr } f$.

EXAMPLES:

Example 1.

We start with the universal enveloping algebra of the Lie algebra \mathbb{R}^3 (with the cross product serving as Lie bracket):

```
sage: A = AlgebrasWithBasis(QQ).Filtered().example(); A
An example of a filtered algebra with basis: the
universal enveloping algebra of Lie algebra of RR^3
with cross product over Rational Field
sage: M = A.indices(); M
Free abelian monoid indexed by {'x', 'y', 'z'}
sage: x,y,z = [A.basis()[M.gens()[i]] for i in "xyz"]
```

Let us define a stupid filtered map from A to itself:

```
sage: def map_on_basis(m):
.....:     d = m.dict()
.....:     i = d.get('x', 0); j = d.get('y', 0); k = d.get('z', 0)
.....:     g = (y ** (i+j)) * (z ** k)
.....:     if i > 0:
.....:         g += i * (x ** (i-1)) * (y ** j) * (z ** k)
.....:     return g
sage: f = A.module_morphism(on_basis=map_on_basis,
.....:                       codomain=A)
sage: f(x)
U['y'] + 1
sage: f(x*y*z)
U['y']^2*U['z'] + U['y']*U['z']
sage: f(x*x*y*z)
U['y']^3*U['z'] + 2*U['x']*U['y']*U['z']
sage: f(A.one())
1
sage: f(y*z)
U['y']*U['z']
```

(There is nothing here that is peculiar to this universal enveloping algebra; we are only using its module structure, and we could just as well be using a polynomial algebra in its stead.)

We now compute $\text{gr } f$

```
sage: grA = A.graded_algebra(); grA
Graded Algebra of An example of a filtered algebra with
basis: the universal enveloping algebra of Lie algebra
```

(continues on next page)

(continued from previous page)

```

of RR^3 with cross product over Rational Field
sage: xx, yy, zz = [A.to_graded_conversion()(i) for i in [x, y, z]]
sage: xx+yy*zz
bar(U['y']*U['z']) + bar(U['x'])
sage: grf = A.induced_graded_map(A, f); grf
Generic endomorphism of Graded Algebra of An example
of a filtered algebra with basis: the universal
enveloping algebra of Lie algebra of RR^3 with cross
product over Rational Field
sage: grf(xx)
bar(U['y'])
sage: grf(xx*yy*zz)
bar(U['y']^2*U['z'])
sage: grf(xx*xx*yy*zz)
bar(U['y']^3*U['z'])
sage: grf(grA.one())
bar(1)
sage: grf(yy*zz)
bar(U['y']*U['z'])
sage: grf(yy*zz-2*yy)
bar(U['y']*U['z']) - 2*bar(U['y'])

```

Example 2.

We shall now construct $gr f$ for a different map f out of the same A ; the new map f will lead into a graded algebra already, namely into the algebra of symmetric functions:

```

sage: h = SymmetricFunctions(QQ).h()
sage: def map_on_basis(m): # redefining map_on_basis
.....:     d = m.dict()
.....:     i = d.get('x', 0); j = d.get('y', 0); k = d.get('z', 0)
.....:     g = (h[1] ** i) * (h[2] ** (floor(j/2))) * (h[3] ** (floor(k/3)))
.....:     g += i * (h[1] ** (i+j+k))
.....:     return g
sage: f = A.module_morphism(on_basis=map_on_basis,
.....:                       codomain=h) # redefining f
sage: f(x)
2*h[1]
sage: f(y)
h[]
sage: f(z)
h[]
sage: f(y**2)
h[2]
sage: f(x**2)
3*h[1, 1]
sage: f(x*y*z)
h[1] + h[1, 1, 1]
sage: f(x*x*y*y*z)
2*h[1, 1, 1, 1, 1] + h[2, 1, 1]
sage: f(A.one())
h[]

```

The algebra `h` of symmetric functions in the h -basis is already graded, so its associated graded algebra is implemented as itself:

```
sage: grh = h.graded_algebra(); grh is h
True
sage: grf = A.induced_graded_map(h, f); grf
Generic morphism:
  From: Graded Algebra of An example of a filtered
        algebra with basis: the universal enveloping
        algebra of Lie algebra of RR^3 with cross
        product over Rational Field
  To:   Symmetric Functions over Rational Field
        in the homogeneous basis
sage: grf(xx)
2*h[1]
sage: grf(yy)
0
sage: grf(zz)
0
sage: grf(yy**2)
h[2]
sage: grf(xx**2)
3*h[1, 1]
sage: grf(xx*yy*zz)
h[1, 1, 1]
sage: grf(xx*xx*yy*yy*zz)
2*h[1, 1, 1, 1, 1]
sage: grf(grA.one())
h[]
```

Example 3.

After having had a graded algebra as the codomain, let us try to have one as the domain instead. Our new `f` will go from `h` to `A`:

```
sage: def map_on_basis(lam): # redefining map_on_basis
.....:     return x ** (sum(lam)) + y ** (len(lam))
sage: f = h.module_morphism(on_basis=map_on_basis,
.....:                       codomain=A) # redefining f
sage: f(h[1])
U['x'] + U['y']
sage: f(h[2])
U['x']^2 + U['y']
sage: f(h[1, 1])
U['x']^2 + U['y']^2
sage: f(h[2, 2])
U['x']^4 + U['y']^2
sage: f(h[3, 2, 1])
U['x']^6 + U['y']^3
sage: f(h.one())
2
sage: grf = h.induced_graded_map(A, f); grf
Generic morphism:
  From: Symmetric Functions over Rational Field
```

(continues on next page)

(continued from previous page)

```

in the homogeneous basis
To: Graded Algebra of An example of a filtered
    algebra with basis: the universal enveloping
    algebra of Lie algebra of  $\mathbb{R}^3$  with cross
    product over Rational Field
sage: grf(h[1])
bar(U['x']) + bar(U['y'])
sage: grf(h[2])
bar(U['x']^2)
sage: grf(h[1, 1])
bar(U['x']^2) + bar(U['y']^2)
sage: grf(h[2, 2])
bar(U['x']^4)
sage: grf(h[3, 2, 1])
bar(U['x']^6)
sage: grf(h.one())
2*bar(1)

```

Example 4.

The construct $gr\ f$ also makes sense when f is a filtration-preserving map between graded algebras.

```

sage: def map_on_basis(lam): # redefining map_on_basis
.....:     return h[lam] + h[len(lam)]
sage: f = h.module_morphism(on_basis=map_on_basis,
.....:                       codomain=h) # redefining f
sage: f(h[1])
2*h[1]
sage: f(h[2])
h[1] + h[2]
sage: f(h[1, 1])
h[1, 1] + h[2]
sage: f(h[2, 1])
h[2] + h[2, 1]
sage: f(h.one())
2*h[]
sage: grf = h.induced_graded_map(h, f); grf
Generic endomorphism of Symmetric Functions over Rational
Field in the homogeneous basis
sage: grf(h[1])
2*h[1]
sage: grf(h[2])
h[2]
sage: grf(h[1, 1])
h[1, 1] + h[2]
sage: grf(h[2, 1])
h[2, 1]
sage: grf(h.one())
2*h[]

```

Example 5.

For another example, let us compute $gr\ f$ for a map f between two Clifford algebras:


```

sage: Q = QuadraticForm(ZZ, 2, [1,2,3])
sage: B = CliffordAlgebra(Q, names=['u', 'v']); B
The Clifford algebra of the Quadratic form in 2
variables over Integer Ring with coefficients:
[ 1 2 ]
[ * 3 ]
sage: m = Matrix(ZZ, [[1, 2], [1, -1]])
sage: f = B.lift_module_morphism(m, names=['x', 'y'])
sage: A = f.domain(); A
The Clifford algebra of the Quadratic form in 2
variables over Integer Ring with coefficients:
[ 6 0 ]
[ * 3 ]
sage: x, y = A.gens()
sage: f(x)
u + v
sage: f(y)
2*u - v
sage: f(x**2)
6
sage: f(x*y)
-3*u*v + 3
sage: grA = A.graded_algebra(); grA
The exterior algebra of rank 2 over Integer Ring
sage: A.to_graded_conversion()(x)
x
sage: A.to_graded_conversion()(y)
y
sage: A.to_graded_conversion()(x*y)
x*y
sage: u = A.to_graded_conversion()(x*y+1); u
x*y + 1
sage: A.from_graded_conversion()(u)
x*y + 1
sage: A.projection(2)(x*y+1)
x*y
sage: A.projection(1)(x+2*y-2)
x + 2*y
sage: grf = A.induced_graded_map(B, f); grf
Generic morphism:
From: The exterior algebra of rank 2 over Integer Ring
To: The exterior algebra of rank 2 over Integer Ring
sage: grf(A.to_graded_conversion()(x))
u + v
sage: grf(A.to_graded_conversion()(y))
2*u - v
sage: grf(A.to_graded_conversion()(x**2))
6
sage: grf(A.to_graded_conversion()(x*y))
-3*u*v
sage: grf(grA.one())
1

```

projection(*i*)

Return the i -th projection $p_i : F_i \rightarrow G_i$ (in the notations of the class documentation `AssociatedGradedAlgebra`, where $A =$).

This method actually does not return the map p_i itself, but an extension of p_i to the whole R -module A . This extension is the composition of the R -module isomorphism $A \rightarrow \text{gr } A$ with the canonical projection of the graded R -module $\text{gr } A$ onto its i -th graded component G_i . The codomain of this map is $\text{gr } A$, although its actual image is G_i . The map p_i is obtained from this map by restricting its domain to F_i and its image to G_i .

EXAMPLES:

```
sage: A = Algebras(QQ).WithBasis().Filtered().example()
sage: p = A.an_element() + A.algebra_generators()['x'] + 2; p
U['x']^2*U['y']^2*U['z']^3 + 3*U['x'] + 3*U['y'] + 3
sage: q = A.projection(7)(p); q
bar(U['x']^2*U['y']^2*U['z']^3)
sage: q.parent() is A.graded_algebra()
True
sage: A.projection(8)(p)
0
```

to_graded_conversion()

Return the canonical R -module isomorphism $A \rightarrow \text{gr } A$ induced by the basis of A (where $A =$).

This is an isomorphism of R -modules, not of algebras. See the class documentation `AssociatedGradedAlgebra`.

See also:

[`from_graded_conversion\(\)`](#)

EXAMPLES:

```
sage: A = Algebras(QQ).WithBasis().Filtered().example()
sage: p = A.an_element() + A.algebra_generators()['x'] + 2; p
U['x']^2*U['y']^2*U['z']^3 + 3*U['x'] + 3*U['y'] + 3
sage: q = A.to_graded_conversion()(p); q
bar(U['x']^2*U['y']^2*U['z']^3) + 3*bar(U['x'])
+ 3*bar(U['y']) + 3*bar(1)
sage: q.parent() is A.graded_algebra()
True
```

3.42 Filtered Modules

A *filtered module* over a ring R with a totally ordered indexing set I (typically $I = \mathbf{N}$) is an R -module M equipped with a family $(F_i)_{i \in I}$ of R -submodules satisfying $F_i \subseteq F_j$ for all $i, j \in I$ having $i \leq j$, and $M = \bigcup_{i \in I} F_i$. This family is called a *filtration* of the given module M .

Todo: Implement a notion for decreasing filtrations: where $F_j \subseteq F_i$ when $i \leq j$.

Todo: Implement filtrations for all concrete categories.

Todo: Implement `gr` as a functor.

class `sage.categories.filtered_modules.FilteredModules`(*base_category*)

Bases: `sage.categories.filtered_modules.FilteredModulesCategory`

The category of filtered modules over a given ring R .

A *filtered module* over a ring R with a totally ordered indexing set I (typically $I = \mathbf{N}$) is an R -module M equipped with a family $(F_i)_{i \in I}$ of R -submodules satisfying $F_i \subseteq F_j$ for all $i, j \in I$ having $i \leq j$, and $M = \bigcup_{i \in I} F_i$. This family is called a *filtration* of the given module M .

EXAMPLES:

```
sage: Modules(ZZ).Filtered()
Category of filtered modules over Integer Ring
sage: Modules(ZZ).Filtered().super_categories()
[Category of modules over Integer Ring]
```

REFERENCES:

- [Wikipedia article Filtration_\(mathematics\)](#)

class `Connected`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

class `SubcategoryMethods`

Bases: `object`

Connected()

Return the full subcategory of the connected objects of `self`.

A filtered R -module M with filtration (F_0, F_1, F_2, \dots) (indexed by \mathbf{N}) is said to be *connected* if F_0 is isomorphic to R .

EXAMPLES:

```
sage: Modules(ZZ).Filtered().Connected()
Category of filtered connected modules over Integer Ring
sage: Coalgebras(QQ).Filtered().Connected()
Category of filtered connected coalgebras over Rational Field
sage: AlgebrasWithBasis(QQ).Filtered().Connected()
Category of filtered connected algebras with basis over Rational Field
```

extra_super_categories()

Add `VectorSpaces` to the super categories of `self` if the base ring is a field.

EXAMPLES:

```
sage: Modules(QQ).Filtered().is_subcategory(VectorSpaces(QQ))
True
sage: Modules(ZZ).Filtered().extra_super_categories()
[]
```

This makes sure that `Modules(QQ).Filtered()` returns an instance of `FilteredModules` and not a join category of an instance of this class and of `VectorSpaces(QQ)`:

```
sage: type(Modules(QQ).Filtered())
<class 'sage.categories.vector_spaces.VectorSpaces.Filtered_with_category'>
```

Todo: Get rid of this workaround once there is a more systematic approach for the alias `Modules(QQ)` \rightarrow `VectorSpaces(QQ)`. Probably the latter should be a category with axiom, and covariant constructions should play well with axioms.

class `sage.categories.filtered_modules.FilteredModulesCategory`(*base_category*)

Bases: `sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory`,
`sage.categories.category_types.Category_over_base_ring`

EXAMPLES:

```
sage: C = Algebras(QQ).Filtered()
sage: C
Category of filtered algebras over Rational Field
sage: C.base_category()
Category of algebras over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of algebras over Rational Field,
Category of filtered vector spaces over Rational Field]

sage: AlgebrasWithBasis(QQ).Filtered().base_ring()
Rational Field
sage: HopfAlgebrasWithBasis(QQ).Filtered().base_ring()
Rational Field
```

3.43 Filtered Modules With Basis

A *filtered module with basis* over a ring R means (for the purpose of this code) a filtered R -module M with filtration $(F_i)_{i \in I}$ (typically $I = \mathbf{N}$) endowed with a basis $(b_j)_{j \in J}$ of M and a partition $J = \bigsqcup_{i \in I} J_i$ of the set J (it is allowed that some J_i are empty) such that for every $n \in I$, the subfamily $(b_j)_{j \in U_n}$, where $U_n = \bigcup_{i \leq n} J_i$, is a basis of the R -submodule F_n .

For every $i \in I$, the R -submodule of M spanned by $(b_j)_{j \in J_i}$ is called the *i -th graded component* (aka the *i -th homogeneous component*) of the filtered module with basis M ; the elements of this submodule are referred to as *homogeneous elements of degree i* .

See the class documentation `FilteredModulesWithBasis` for further details.

class `sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis`(*base_category*)

Bases: `sage.categories.filtered_modules.FilteredModulesCategory`

The category of filtered modules with a distinguished basis.

A *filtered module with basis* over a ring R means (for the purpose of this code) a filtered R -module M with filtration $(F_i)_{i \in I}$ (typically $I = \mathbf{N}$) endowed with a basis $(b_j)_{j \in J}$ of M and a partition $J = \bigsqcup_{i \in I} J_i$ of the set J (it is allowed that some J_i are empty) such that for every $n \in I$, the subfamily $(b_j)_{j \in U_n}$, where $U_n = \bigcup_{i \leq n} J_i$, is a basis of the R -submodule F_n .

For every $i \in I$, the R -submodule of M spanned by $(b_j)_{j \in J_i}$ is called the *i -th graded component* (aka the *i -th homogeneous component*) of the filtered module with basis M ; the elements of this submodule are referred to as *homogeneous elements of degree i* . The R -module M is the direct sum of its i -th graded components over all $i \in I$, and thus becomes a graded R -module with basis. Conversely, any graded R -module with basis canonically becomes a filtered R -module with basis (by defining $F_n = \bigoplus_{i \leq n} G_i$ where G_i is the i -th graded component, and defining J_i as the indexing set of the basis of the i -th graded component). Hence, the notion of a filtered R -module with basis is equivalent to the notion of a graded R -module with basis.

However, the *category* of filtered R -modules with basis is not the category of graded R -modules with basis. Indeed, the *morphisms* of filtered R -modules with basis are defined to be morphisms of R -modules which send each F_n of the domain to the corresponding F_n of the target; in contrast, the morphisms of graded R -modules with basis must preserve each homogeneous component. Also, the notion of a filtered algebra with basis differs from that of a graded algebra with basis.

Note: Currently, to make use of the functionality of this class, an instance of `FilteredModulesWithBasis` should fulfill the contract of a `CombinatorialFreeModule` (most likely by inheriting from it). It should also have the indexing set J encoded as its `_indices` attribute, and `_indices.subset(size=i)` should yield the subset J_i (as an iterable). If the latter conditions are not satisfied, then `basis()` must be overridden.

Note: One should implement a `degree_on_basis` method in the parent class in order to fully utilize the methods of this category. This might become a required abstract method in the future.

EXAMPLES:

```
sage: C = ModulesWithBasis(ZZ).Filtered(); C
Category of filtered modules with basis over Integer Ring
sage: sorted(C.super_categories(), key=str)
[Category of filtered modules over Integer Ring,
 Category of modules with basis over Integer Ring]
sage: C is ModulesWithBasis(ZZ).Filtered()
True
```

class ElementMethods

Bases: object

degree()

The degree of a nonzero homogeneous element `self` in the filtered module.

Note: This raises an error if the element is not homogeneous. To compute the maximum of the degrees of the homogeneous summands of a (not necessarily homogeneous) element, use `maximal_degree()` instead.

EXAMPLES:

```
sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: x = A(Partition((3,2,1)))
sage: y = A(Partition((4,4,1)))
sage: z = A(Partition((2,2,2)))
sage: x.degree()
6
sage: (x + 2*z).degree()
6
sage: (y - x).degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous
```

An example in a graded algebra:

```

sage: S = NonCommutativeSymmetricFunctions(QQ).S()
sage: (x, y) = (S[2], S[3])
sage: x.homogeneous_degree()
2
sage: (x^3 + 4*y^2).homogeneous_degree()
6
sage: ((1 + x)^3).homogeneous_degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous

```

Let us now test a filtered algebra (but remember that the notion of homogeneity now depends on the choice of a basis):

```

sage: A = AlgebrasWithBasis(QQ).Filtered().example()
sage: x,y,z = A.algebra_generators()
sage: (x*y).homogeneous_degree()
2
sage: (y*x).homogeneous_degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous
sage: A.one().homogeneous_degree()
0

```

degree_on_basis(*m*)

Return the degree of the basis element indexed by *m* in self.

EXAMPLES:

```

sage: A = GradedModulesWithBasis(QQ).example()
sage: A.degree_on_basis(Partition((2,1)))
3
sage: A.degree_on_basis(Partition((4,2,1,1,1,1)))
10

```

homogeneous_component(*n*)

Return the homogeneous component of degree *n* of the element self.

Let m be an element of a filtered R -module M with basis. Then, m can be uniquely written in the form $m = \sum_{i \in I} m_i$, where each m_i is a homogeneous element of degree i . For $n \in I$, we define the homogeneous component of degree n of the element m to be m_n .

EXAMPLES:

```

sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: x = A.an_element(); x
2*P[] + 2*P[1] + 3*P[2]
sage: x.homogeneous_component(-1)
0
sage: x.homogeneous_component(0)
2*P[]
sage: x.homogeneous_component(1)
2*P[1]
sage: x.homogeneous_component(2)

```

(continues on next page)

(continued from previous page)

```

3*P[2]
sage: x.homogeneous_component(3)
0

sage: A = ModulesWithBasis(ZZ).Graded().example()
sage: x = A.an_element(); x
2*P[] + 2*P[1] + 3*P[2]
sage: x.homogeneous_component(-1)
0
sage: x.homogeneous_component(0)
2*P[]
sage: x.homogeneous_component(1)
2*P[1]
sage: x.homogeneous_component(2)
3*P[2]
sage: x.homogeneous_component(3)
0

sage: A = AlgebrasWithBasis(ZZ).Filtered().example()
sage: G = A.algebra_generators()
sage: g = A.an_element() - 2 * G['x'] * G['y']; g
U['x']^2*U['y']^2*U['z']^3 - 2*U['x']*U['y']
+ 2*U['x'] + 3*U['y'] + 1
sage: g.homogeneous_component(-1)
0
sage: g.homogeneous_component(0)
1
sage: g.homogeneous_component(2)
-2*U['x']*U['y']
sage: g.homogeneous_component(5)
0
sage: g.homogeneous_component(7)
U['x']^2*U['y']^2*U['z']^3
sage: g.homogeneous_component(8)
0

```

homogeneous_degree()

The degree of a nonzero homogeneous element `self` in the filtered module.

Note: This raises an error if the element is not homogeneous. To compute the maximum of the degrees of the homogeneous summands of a (not necessarily homogeneous) element, use `maximal_degree()` instead.

EXAMPLES:

```

sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: x = A(Partition((3,2,1)))
sage: y = A(Partition((4,4,1)))
sage: z = A(Partition((2,2,2)))
sage: x.degree()
6

```

(continues on next page)

(continued from previous page)

```

sage: (x + 2*z).degree()
6
sage: (y - x).degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous

```

An example in a graded algebra:

```

sage: S = NonCommutativeSymmetricFunctions(QQ).S()
sage: (x, y) = (S[2], S[3])
sage: x.homogeneous_degree()
2
sage: (x^3 + 4*y^2).homogeneous_degree()
6
sage: ((1 + x)^3).homogeneous_degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous

```

Let us now test a filtered algebra (but remember that the notion of homogeneity now depends on the choice of a basis):

```

sage: A = AlgebrasWithBasis(QQ).Filtered().example()
sage: x,y,z = A.algebra_generators()
sage: (x*y).homogeneous_degree()
2
sage: (y*x).homogeneous_degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous
sage: A.one().homogeneous_degree()
0

```

`is_homogeneous()`

Return whether the element `self` is homogeneous.

EXAMPLES:

```

sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: x=A(Partition((3,2,1)))
sage: y=A(Partition((4,4,1)))
sage: z=A(Partition((2,2,2)))
sage: (3*x).is_homogeneous()
True
sage: (x - y).is_homogeneous()
False
sage: (x+2*z).is_homogeneous()
True

```

Here is an example with a graded algebra:


```

sage: S = NonCommutativeSymmetricFunctions(QQ).S()
sage: (x, y) = (S[2], S[3])
sage: (3*x).is_homogeneous()
True
sage: (x^3 - y^2).is_homogeneous()
True
sage: ((x + y)^2).is_homogeneous()
False

```

Let us now test a filtered algebra (but remember that the notion of homogeneity now depends on the choice of a basis, or at least on a definition of homogeneous components):

```

sage: A = AlgebrasWithBasis(QQ).Filtered().example()
sage: x,y,z = A.algebra_generators()
sage: (x*y).is_homogeneous()
True
sage: (y*x).is_homogeneous()
False
sage: A.one().is_homogeneous()
True
sage: A.zero().is_homogeneous()
True
sage: (A.one()+x).is_homogeneous()
False

```

maximal_degree()

The maximum of the degrees of the homogeneous components of `self`.

This is also the smallest i such that `self` belongs to F_i . Hence, it does not depend on the basis of the parent of `self`.

See also:

[*homogeneous_degree\(\)*](#)

EXAMPLES:

```

sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: x = A(Partition((3,2,1)))
sage: y = A(Partition((4,4,1)))
sage: z = A(Partition((2,2,2)))
sage: x.maximal_degree()
6
sage: (x + 2*z).maximal_degree()
6
sage: (y - x).maximal_degree()
9
sage: (3*z).maximal_degree()
6

```

Now, we test this on a graded algebra:

```

sage: S = NonCommutativeSymmetricFunctions(QQ).S()
sage: (x, y) = (S[2], S[3])
sage: x.maximal_degree()

```

(continues on next page)

(continued from previous page)

```

2
sage: (x^3 + 4*y^2).maximal_degree()
6
sage: ((1 + x)^3).maximal_degree()
6

```

Let us now test a filtered algebra:

```

sage: A = AlgebrasWithBasis(QQ).Filtered().example()
sage: x,y,z = A.algebra_generators()
sage: (x*y).maximal_degree()
2
sage: (y*x).maximal_degree()
2
sage: A.one().maximal_degree()
0
sage: A.zero().maximal_degree()
Traceback (most recent call last):
...
ValueError: the zero element does not have a well-defined degree
sage: (A.one()+x).maximal_degree()
1

```

truncate(*n*)

Return the sum of the homogeneous components of degree strictly less than *n* of *self*.

See [homogeneous_component\(\)](#) for the notion of a homogeneous component.

EXAMPLES:

```

sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: x = A.an_element(); x
2*P[] + 2*P[1] + 3*P[2]
sage: x.truncate(0)
0
sage: x.truncate(1)
2*P[]
sage: x.truncate(2)
2*P[] + 2*P[1]
sage: x.truncate(3)
2*P[] + 2*P[1] + 3*P[2]

sage: A = ModulesWithBasis(ZZ).Graded().example()
sage: x = A.an_element(); x
2*P[] + 2*P[1] + 3*P[2]
sage: x.truncate(0)
0
sage: x.truncate(1)
2*P[]
sage: x.truncate(2)
2*P[] + 2*P[1]
sage: x.truncate(3)
2*P[] + 2*P[1] + 3*P[2]

```

(continues on next page)

(continued from previous page)

```

sage: A = AlgebrasWithBasis(ZZ).Filtered().example()
sage: G = A.algebra_generators()
sage: g = A.an_element() - 2 * G['x'] * G['y']; g
U['x']^2*U['y']^2*U['z']^3 - 2*U['x']*U['y']
+ 2*U['x'] + 3*U['y'] + 1
sage: g.truncate(-1)
0
sage: g.truncate(0)
0
sage: g.truncate(2)
2*U['x'] + 3*U['y'] + 1
sage: g.truncate(3)
-2*U['x']*U['y'] + 2*U['x'] + 3*U['y'] + 1
sage: g.truncate(5)
-2*U['x']*U['y'] + 2*U['x'] + 3*U['y'] + 1
sage: g.truncate(7)
-2*U['x']*U['y'] + 2*U['x'] + 3*U['y'] + 1
sage: g.truncate(8)
U['x']^2*U['y']^2*U['z']^3 - 2*U['x']*U['y']
+ 2*U['x'] + 3*U['y'] + 1

```

class ParentMethods

Bases: object

basis(*d=None*)Return the basis for (the *d*-th homogeneous component of) *self*.

INPUT:

- *d* – (optional, default None) nonnegative integer or None

OUTPUT:

If *d* is None, returns the basis of the module. Otherwise, returns the basis of the homogeneous component of degree *d* (i.e., the subfamily of the basis of the whole module which consists only of the basis vectors lying in $F_d \setminus \bigcup_{i < d} F_i$).

The basis is always returned as a family.

EXAMPLES:

```

sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: A.basis(4)
Lazy family (Term map from Partitions to An example of a
filtered module with basis: the free module on partitions
over Integer Ring(i))_{i in Partitions of the integer 4}

```

Without arguments, the full basis is returned:

```

sage: A.basis()
Lazy family (Term map from Partitions to An example of a
filtered module with basis: the free module on partitions
over Integer Ring(i))_{i in Partitions}
sage: A.basis()
Lazy family (Term map from Partitions to An example of a

```

(continues on next page)

(continued from previous page)

```
filtered module with basis: the free module on partitions
over Integer Ring(i))_{i in Partitions}
```

Checking this method on a filtered algebra. Note that this will typically raise a `NotImplementedError` when this feature is not implemented.

```
sage: A = AlgebrasWithBasis(ZZ).Filtered().example()
sage: A.basis(4)
Traceback (most recent call last):
...
NotImplementedError: infinite set
```

Without arguments, the full basis is returned:

```
sage: A.basis()
Lazy family (Term map from Free abelian monoid indexed by
{'x', 'y', 'z'} to An example of a filtered algebra with
basis: the universal enveloping algebra of Lie algebra
of RR^3 with cross product over Integer Ring(i))_{i in
Free abelian monoid indexed by {'x', 'y', 'z'}}
```

An example with a graded algebra:

```
sage: E.<x,y> = ExteriorAlgebra(QQ)
sage: E.basis()
Lazy family (Term map from Subsets of {0, 1} to
The exterior algebra of rank 2 over Rational Field(i))_{i in
Subsets of {0, 1}}
```

`from_graded_conversion()`

Return the inverse of the canonical R -module isomorphism $A \rightarrow \text{gr } A$ induced by the basis of A (where $A =$). This inverse is an isomorphism $\text{gr } A \rightarrow A$.

This is an isomorphism of R -modules. See the class documentation `AssociatedGradedAlgebra`.

See also:

`to_graded_conversion()`

EXAMPLES:

```
sage: A = Modules(QQ).WithBasis().Filtered().example()
sage: p = -2 * A.an_element(); p
-4*P[] - 4*P[1] - 6*P[2]
sage: q = A.to_graded_conversion()(p); q
-4*Bbar[[]] - 4*Bbar[[1]] - 6*Bbar[[2]]
sage: A.from_graded_conversion()(q) == p
True
sage: q.parent() is A.graded_algebra()
True
```

`graded_algebra()`

Return the associated graded module to self.

See `AssociatedGradedAlgebra` for the definition and the properties of this.

If the filtered module `self` with basis is called A , then this method returns $\text{gr } A$. The method `to_graded_conversion()` returns the canonical R -module isomorphism $A \rightarrow \text{gr } A$ induced by the basis of A , and the method `from_graded_conversion()` returns the inverse of this isomorphism. The method `projection()` projects elements of A onto $\text{gr } A$ according to their place in the filtration on A .

Warning: When not overridden, this method returns the default implementation of an associated graded module – namely, `AssociatedGradedAlgebra(self)`, where `AssociatedGradedAlgebra` is `AssociatedGradedAlgebra`. But some instances of `FilteredModulesWithBasis` override this method, as the associated graded module often is (isomorphic) to a simpler object (for instance, the associated graded module of a graded module can be identified with the graded module itself). Generic code that uses associated graded modules (such as the code of the `induced_graded_map()` method below) should make sure to only communicate with them via the `to_graded_conversion()`, `from_graded_conversion()` and `projection()` methods (in particular, do not expect there to be a conversion from `self` to `self.graded_algebra()`; this currently does not work for Clifford algebras). Similarly, when overriding `graded_algebra()`, make sure to accordingly redefine these three methods, unless their definitions below still apply to your case (this will happen whenever the basis of your `graded_algebra()` has the same indexing set as `self`, and the partition of this indexing set according to degree is the same as for `self`).

EXAMPLES:

```
sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: A.graded_algebra()
Graded Module of An example of a filtered module with basis:
the free module on partitions over Integer Ring
```

homogeneous_component(d)

Return the d -th homogeneous component of `self`.

EXAMPLES:

```
sage: A = GradedModulesWithBasis(ZZ).example()
sage: A.homogeneous_component(4)
Degree 4 homogeneous component of An example of a graded module
with basis: the free module on partitions over Integer Ring
```

homogeneous_component_basis(d)

Return a basis for the d -th homogeneous component of `self`.

EXAMPLES:

```
sage: A = GradedModulesWithBasis(ZZ).example()
sage: A.homogeneous_component_basis(4)
Lazy family (Term map from Partitions to An example of a graded module with
↪basis:
        the free module on partitions over Integer Ring(i))_{i in
↪Partitions of the integer 4}

sage: cat = GradedModulesWithBasis(ZZ)
sage: C = CombinatorialFreeModule(ZZ, ['a', 'b'], category=cat)
sage: C.degree_on_basis = lambda x: 1 if x == 'a' else 2
```

(continues on next page)

(continued from previous page)

```

sage: C.homogeneous_component_basis(1)
Finite family {'a': B['a']}
sage: C.homogeneous_component_basis(2)
Finite family {'b': B['b']}

```

induced_graded_map(*other, f*)

Return the graded linear map between the associated graded modules of **self** and **other** canonically induced by the filtration-preserving map $f : \mathbf{self} \rightarrow \mathbf{other}$.

Let A and B be two filtered modules with basis, and let $(F_i)_{i \in I}$ and $(G_i)_{i \in I}$ be their filtrations. Let $f : A \rightarrow B$ be a linear map which preserves the filtration (i.e., satisfies $f(F_i) \subseteq G_i$ for all $i \in I$). Then, there is a canonically defined graded linear map $\text{gr } f : \text{gr } A \rightarrow \text{gr } B$ which satisfies

$$(\text{gr } f)(p_i(a)) = p_i(f(a)) \quad \text{for all } i \in I \text{ and } a \in F_i,$$

where the p_i on the left hand side is the canonical projection from F_i onto the i -th graded component of $\text{gr } A$, while the p_i on the right hand side is the canonical projection from G_i onto the i -th graded component of $\text{gr } B$.

INPUT:

- **other** – a filtered algebra with basis
- **f** – a filtration-preserving linear map from **self** to **other** (can be given as a morphism or as a function)

OUTPUT:

The graded linear map $\text{gr } f$.

EXAMPLES:

Example 1.

We start with the free \mathbb{Q} -module with basis the set of all partitions:

```

sage: A = Modules(QQ).WithBasis().Filtered().example(); A
An example of a filtered module with basis: the free module
on partitions over Rational Field
sage: M = A.indices(); M
Partitions
sage: p1, p2, p21, p321 = [A.basis()[Partition(i)] for i in [[1], [2], [2,
↪1], [3,2,1]]]

```

Let us define a map from **A** to itself which acts on the basis by sending every partition λ to the sum of the conjugates of all partitions μ for which λ/μ is a horizontal strip:

```

sage: def map_on_basis(lam):
.....:     return A.sum_of_monomials([Partition(mu).conjugate() for k in_
↪range(sum(lam) + 1)
.....:                                     for mu in lam.remove_horizontal_border_
↪strip(k)])
sage: f = A.module_morphism(on_basis=map_on_basis,
.....:                       codomain=A)
sage: f(p1)
P[] + P[1]
sage: f(p2)
P[] + P[1] + P[1, 1]
sage: f(p21)

```

(continues on next page)

(continued from previous page)

```

P[1] + P[1, 1] + P[2] + P[2, 1]
sage: f(p21 - p1)
-P[] + P[1, 1] + P[2] + P[2, 1]
sage: f(p321)
P[2, 1] + P[2, 1, 1] + P[2, 2] + P[2, 2, 1]
+ P[3, 1] + P[3, 1, 1] + P[3, 2] + P[3, 2, 1]

```

We now compute $gr f$

```

sage: grA = A.graded_algebra(); grA
Graded Module of An example of a filtered module with basis:
the free module on partitions over Rational Field
sage: pp1, pp2, pp21, pp321 = [A.to_graded_conversion()(i) for i in [p1, p2,
↪ p21, p321]]
sage: pp2 + 4 * pp21
Bbar[[2]] + 4*Bbar[[2, 1]]
sage: grf = A.induced_graded_map(A, f); grf
Generic endomorphism of Graded Module of An example of a
filtered module with basis:
the free module on partitions over Rational Field
sage: grf(pp1)
Bbar[[1]]
sage: grf(pp2 + 4 * pp21)
Bbar[[1, 1]] + 4*Bbar[[2, 1]]

```

Example 2.

We shall now construct $gr f$ for a different map f out of the same A ; the new map f will lead into a graded algebra already, namely into the algebra of symmetric functions:

```

sage: h = SymmetricFunctions(QQ).h()
sage: def map_on_basis(lam): # redefining map_on_basis
....:     return h.sum_of_monomials([Partition(mu).conjugate() for k in
↪ range(sum(lam) + 1)
....:                                     for mu in lam.remove_horizontal_border_
↪ strip(k)])
sage: f = A.module_morphism(on_basis=map_on_basis,
....:                       codomain=h) # redefining f
sage: f(p1)
h[] + h[1]
sage: f(p2)
h[] + h[1] + h[1, 1]
sage: f(A.zero())
0
sage: f(p2 - 3*p1)
-2*h[] - 2*h[1] + h[1, 1]

```

The algebra h of symmetric functions in the h -basis is already graded, so its associated graded algebra is implemented as itself:

```

sage: grh = h.graded_algebra(); grh is h
True
sage: grf = A.induced_graded_map(h, f); grf

```

(continues on next page)

(continued from previous page)

```

Generic morphism:
  From: Graded Module of An example of a filtered
        module with basis: the free module on partitions
        over Rational Field
  To:   Symmetric Functions over Rational Field
        in the homogeneous basis
sage: grf(pp1)
h[1]
sage: grf(pp2)
h[1, 1]
sage: grf(pp321)
h[3, 2, 1]
sage: grf(pp2 - 3*pp1)
-3*h[1] + h[1, 1]
sage: grf(pp21)
h[2, 1]
sage: grf(grA.zero())
0

```

Example 3.

After having had a graded module as the codomain, let us try to have one as the domain instead. Our new f will go from h to A :

```

sage: def map_on_basis(lam): # redefining map_on_basis
.....:     return A.sum_of_monomials([Partition(mu).conjugate() for k in_
↳range(sum(lam) + 1)
.....:                                     for mu in lam.remove_horizontal_border_
↳strip(k)])
sage: f = h.module_morphism(on_basis=map_on_basis,
.....:                       codomain=A) # redefining f
sage: f(h[1])
P[] + P[1]
sage: f(h[2])
P[] + P[1] + P[1, 1]
sage: f(h[1, 1])
P[1] + P[2]
sage: f(h[2, 2])
P[1, 1] + P[2, 1] + P[2, 2]
sage: f(h[3, 2, 1])
P[2, 1] + P[2, 1, 1] + P[2, 2] + P[2, 2, 1]
+ P[3, 1] + P[3, 1, 1] + P[3, 2] + P[3, 2, 1]
sage: f(h.one())
P[]
sage: grf = h.induced_graded_map(A, f); grf
Generic morphism:
  From: Symmetric Functions over Rational Field
        in the homogeneous basis
  To:   Graded Module of An example of a filtered
        module with basis: the free module on partitions
        over Rational Field
sage: grf(h[1])
Bbar[[1]]

```

(continues on next page)

(continued from previous page)

```

sage: grf(h[2])
Bbar[[1, 1]]
sage: grf(h[1, 1])
Bbar[[2]]
sage: grf(h[2, 2])
Bbar[[2, 2]]
sage: grf(h[3, 2, 1])
Bbar[[3, 2, 1]]
sage: grf(h.one())
Bbar[[]]

```

Example 4.

The construct $\text{gr } f$ also makes sense when f is a filtration-preserving map between graded modules.

```

sage: def map_on_basis(lam): # redefining map_on_basis
.....:     return h.sum_of_monomials([Partition(mu).conjugate() for k in_
↳range(sum(lam) + 1)
.....:                                     for mu in lam.remove_horizontal_border_
↳strip(k)])
sage: f = h.module_morphism(on_basis=map_on_basis,
.....:                       codomain=h) # redefining f
sage: f(h[1])
h[] + h[1]
sage: f(h[2])
h[] + h[1] + h[1, 1]
sage: f(h[1, 1])
h[1] + h[2]
sage: f(h[2, 1])
h[1] + h[1, 1] + h[2] + h[2, 1]
sage: f(h.one())
h[]
sage: grf = h.induced_graded_map(h, f); grf
Generic endomorphism of Symmetric Functions over Rational
Field in the homogeneous basis
sage: grf(h[1])
h[1]
sage: grf(h[2])
h[1, 1]
sage: grf(h[1, 1])
h[2]
sage: grf(h[2, 1])
h[2, 1]
sage: grf(h.one())
h[]

```

projection(i)

Return the i -th projection $p_i : F_i \rightarrow G_i$ (in the notations of the class documentation `AssociatedGradedAlgebra`, where $A =$).

This method actually does not return the map p_i itself, but an extension of p_i to the whole R -module A . This extension is the composition of the R -module isomorphism $A \rightarrow \text{gr } A$ with the canonical projection of the graded R -module $\text{gr } A$ onto its i -th graded component G_i . The codomain of this map is $\text{gr } A$, although its actual image is G_i . The map p_i is obtained from this map by restricting its

domain to F_i and its image to G_i .

EXAMPLES:

```
sage: A = Modules(ZZ).WithBasis().Filtered().example()
sage: p = -2 * A.an_element(); p
-4*P[] - 4*P[1] - 6*P[2]
sage: q = A.projection(2)(p); q
-6*Bbar[[2]]
sage: q.parent() is A.graded_algebra()
True
sage: A.projection(3)(p)
0
```

to_graded_conversion()

Return the canonical R -module isomorphism $A \rightarrow \text{gr } A$ induced by the basis of A (where $A =$).

This is an isomorphism of R -modules. See the class documentation `AssociatedGradedAlgebra`.

See also:

[*from_graded_conversion\(\)*](#)

EXAMPLES:

```
sage: A = Modules(QQ).WithBasis().Filtered().example()
sage: p = -2 * A.an_element(); p
-4*P[] - 4*P[1] - 6*P[2]
sage: q = A.to_graded_conversion()(p); q
-4*Bbar[[[]]] - 4*Bbar[[[1]]] - 6*Bbar[[[2]]]
sage: q.parent() is A.graded_algebra()
True
```

3.44 Finite Complex Reflection Groups

class `sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of finite complex reflection groups.

See `ComplexReflectionGroups` for the definition of complex reflection group. In the finite case, most of the information about the group can be recovered from its *degrees* and *codegrees*, and to a lesser extent to the explicit realization as subgroup of $GL(V)$. Hence the most important optional methods to implement are:

- `ComplexReflectionGroups.Finite.ParentMethods.degrees()`,
- `ComplexReflectionGroups.Finite.ParentMethods.codegrees()`,
- `ComplexReflectionGroups.Finite.ElementMethods.to_matrix()`.

Finite complex reflection groups are completely classified. In particular, if the group is irreducible, then it's uniquely determined by its degrees and codegrees and whether it's reflection representation is *primitive* or not (see [LT2009] Chapter 2.1 for the definition of primitive).

See also:

[Wikipedia article Complex_reflection_groups](#)

EXAMPLES:

```

sage: from sage.categories.complex_reflection_groups import ComplexReflectionGroups
sage: ComplexReflectionGroups().Finite()
Category of finite complex reflection groups
sage: ComplexReflectionGroups().Finite().super_categories()
[Category of complex reflection groups,
 Category of finite groups,
 Category of finite finitely generated semigroups]

```

An example of a finite reflection group:

```

sage: W = ComplexReflectionGroups().Finite().example(); W          # optional - gap3
Reducible real reflection group of rank 4 and type A2 x B2

sage: W.reflections()                                           # optional - gap3
Finite family {1: (1,8)(2,5)(9,12), 2: (1,5)(2,9)(8,12),
              3: (3,10)(4,7)(11,14), 4: (3,6)(4,11)(10,13),
              5: (1,9)(2,8)(5,12), 6: (4,14)(6,13)(7,11),
              7: (3,13)(6,10)(7,14)}

```

W is in the category of complex reflection groups:

```

sage: W in ComplexReflectionGroups().Finite()                   # optional - gap3
True

```

class ElementMethods

Bases: object

character_value()

Return the value at self of the character of the reflection representation given by `to_matrix()`.

EXAMPLES:

```

sage: W = ColoredPermutations(1,3); W
1-colored permutations of size 3
sage: [t.character_value() for t in W]
[3, 1, 1, 0, 0, 1]

```

Note that this could be a different (faithful) representation than that given by the corresponding root system:

```

sage: W = ReflectionGroup((1,1,3)); W          # optional - gap3
Irreducible real reflection group of rank 2 and type A2
sage: [t.character_value() for t in W]         # optional - gap3
[2, 0, 0, -1, -1, 0]

sage: W = ColoredPermutations(2,2); W
2-colored permutations of size 2
sage: [t.character_value() for t in W]
[2, 0, 0, -2, 0, 0, 0, 0]

sage: W = ColoredPermutations(3,1); W
3-colored permutations of size 1
sage: [t.character_value() for t in W]
[1, zeta3, -zeta3 - 1]

```

reflection_length(*in_unitary_group=False*)

Return the reflection length of `self`.

This is the minimal numbers of reflections needed to obtain `self`.

INPUT:

- `in_unitary_group` – (default: `False`) if `True`, the reflection length is computed in the unitary group which is the dimension of the move space of `self`

EXAMPLES:

```
sage: W = ReflectionGroup((1,1,3))           # optional - gap3
sage: sorted([t.reflection_length() for t in W]) # optional - gap3
[0, 1, 1, 1, 2, 2]

sage: W = ReflectionGroup((2,1,2))           # optional - gap3
sage: sorted([t.reflection_length() for t in W]) # optional - gap3
[0, 1, 1, 1, 1, 2, 2, 2]

sage: W = ReflectionGroup((2,2,2))           # optional - gap3
sage: sorted([t.reflection_length() for t in W]) # optional - gap3
[0, 1, 1, 2]

sage: W = ReflectionGroup((3,1,2))           # optional - gap3
sage: sorted([t.reflection_length() for t in W]) # optional - gap3
[0, 1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2]
```

to_matrix()

Return the matrix presentation of `self` acting on a vector space V .

EXAMPLES:

```
sage: W = ReflectionGroup((1,1,3))           # optional - gap3
sage: [t.to_matrix() for t in W]             # optional - gap3
[
[1 0] [ 1 1] [-1 0] [-1 -1] [ 0 1] [ 0 -1]
[0 1], [ 0 -1], [ 1 1], [ 1 0], [-1 -1], [-1 0]
]

sage: W = ColoredPermutations(1,3)
sage: [t.to_matrix() for t in W]
[
[1 0 0] [1 0 0] [0 1 0] [0 0 1] [0 1 0] [0 0 1]
[0 1 0] [0 0 1] [1 0 0] [1 0 0] [0 0 1] [0 1 0]
[0 0 1], [0 1 0], [0 0 1], [0 1 0], [1 0 0], [1 0 0]
]
]
```

A different representation is given by the colored permutations:

```
sage: W = ColoredPermutations(3, 1)
sage: [t.to_matrix() for t in W]
[[1], [zeta3], [-zeta3 - 1]]
```

class Irreducible(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

class ParentMethods

Bases: `object`

absolute_order_ideal(*gens=None, in_unitary_group=True, return_lengths=False*)

Return all elements in `self` below given elements in the absolute order of `self`.

This order is defined by

$$\omega \leq_R \tau \Leftrightarrow \ell_R(\omega) + \ell_R(\omega^{-1}\tau) = \ell_R(\tau),$$

where ℓ_R denotes the reflection length.

This is, if `in_unitary_group` is `False`, then

$$\ell_R(w) = \min\{\ell : w = r_1 \cdots r_\ell, r_i \in R\},$$

and otherwise

$$\ell_R(w) = \dim \operatorname{im}(w - 1).$$

Note: If `gens` are not given, `self` is assumed to be well-generated.

INPUT:

- `gens` – (default: `None`) if one or more elements are given, the order ideal in the absolute order generated by `gens` is returned. Otherwise, the standard Coxeter element is used as unique maximal element.
- `in_unitary_group` (default: `True`) determines the length function used to compute the order. For real groups, both possible orders coincide, and for complex non-real groups, the order in the unitary group is much faster to compute.
- `return_lengths` (default: `False`) whether or not to also return the lengths of the elements.

EXAMPLES:

```
sage: W = ReflectionGroup((1,1,3)) # optional -gap3
↳gap3

sage: sorted( w.reduced_word() for w in W.absolute_order_ideal() ) # optional -gap3
↳optional -gap3
[[], [1], [1, 2], [1, 2, 1], [2]]

sage: sorted( w.reduced_word() for w in W.absolute_order_ideal(W.from_
↳reduced_word([2,1])) ) # optional -gap3
[[], [1], [1, 2, 1], [2], [2, 1]]

sage: sorted( w.reduced_word() for w in W.absolute_order_ideal(W.from_
↳reduced_word([2])) ) # optional -gap3
[[], [2]]

sage: W = CoxeterGroup(['A', 3])
sage: len(list(W.absolute_order_ideal()))
14

sage: W = CoxeterGroup(['A', 2])
sage: for (w, l) in W.absolute_order_ideal(return_lengths=True):
.....:     print(w.reduced_word(), l)
[1, 2] 2
[1, 2, 1] 1
```

(continues on next page)

(continued from previous page)

```
[2] 1
[1] 1
[] 0
```

absolute_poset(*in_unitary_group=False*)Return the poset induced by the absolute order of `self` as a finite lattice.

INPUT:

- `in_unitary_group` – (default: `False`) if `False`, the relation is given by $\sigma \leq \tau$ if $l_R(\sigma) + l_R(\sigma^{-1}\tau) = l_R(\tau)$. If `True`, the relation is given by $\sigma \leq \tau$ if $\dim(\text{Fix}(\sigma)) + \dim(\text{Fix}(\sigma^{-1}\tau)) = \dim(\text{Fix}(\tau))$

See also:[*noncrossing_partition_lattice\(\)*](#)

EXAMPLES:

```
sage: P = ReflectionGroup((1,1,3)).absolute_poset(); P      # optional ->
->gap3
Finite poset containing 6 elements

sage: sorted(w.reduced_word() for w in P)                  # optional ->
->gap3
[[], [1], [1, 2], [1, 2, 1], [2], [2, 1]]

sage: W = ReflectionGroup(4); W                            # optional ->
->gap3
Irreducible complex reflection group of rank 2 and type ST4
sage: W.absolute_poset()                                  # optional ->
->gap3
Finite poset containing 24 elements
```

coxeter_number()

Return the Coxeter number of an irreducible reflection group.

This is defined as $\frac{N+N^*}{n}$ where N is the number of reflections, N^* is the number of reflection hyperplanes, and n is the rank of `self`.

EXAMPLES:

```
sage: W = ReflectionGroup(31)                             # optional - gap3
sage: W.coxeter_number()                                  # optional - gap3
30
```

elements_below_coxeter_element(*c=None*)

Deprecated method.

Superseded by [*absolute_order_ideal\(\)*](#)**generalized_noncrossing_partitions**(*m, c=None, positive=False*)Return the set of all chains of length m in the noncrossing partition lattice of `self`, see [*noncrossing_partition_lattice\(\)*](#).**Note:** `self` is assumed to be well-generated.

INPUT:

- `c` – (default: `None`) if an element `c` in `self` is given, it is used as the maximal element in the interval
- `positive` – (default: `False`) if `True`, only those generalized noncrossing partitions of full support are returned

EXAMPLES:

```

sage: W = ReflectionGroup((1,1,3)) # optional -
↳gap3

sage: sorted([w.reduced_word() for w in chain] # optional -
↳gap3
.....:     for chain in W.generalized_noncrossing_partitions(2)) #
↳optional - gap3
[[[], [], [1, 2]],
 [ [], [1], [2]],
 [ [], [1, 2], []],
 [ [], [1, 2, 1], [1]],
 [ [], [2], [1, 2, 1]],
 [ [1], [], [2]],
 [ [1], [2], []],
 [ [1, 2], [], []],
 [ [1, 2, 1], [], [1]],
 [ [1, 2, 1], [1], []],
 [ [2], [], [1, 2, 1]],
 [ [2], [1, 2, 1], []]]

sage: sorted([w.reduced_word() for w in chain] # optional -
↳gap3
.....:     for chain in W.generalized_noncrossing_partitions(2,
↳positive=True)) # optional - gap3
[[[], [1, 2], []],
 [ [], [1, 2, 1], [1]],
 [ [1], [2], []],
 [ [1, 2], [], []],
 [ [1, 2, 1], [], [1]],
 [ [1, 2, 1], [1], []],
 [ [2], [1, 2, 1], []]]

```

noncrossing_partition_lattice(`c=None, L=None, in_unitary_group=True`)

Return the interval $[1, c]$ in the absolute order of `self` as a finite lattice.

See also:

[`absolute_order_ideal\(\)`](#)

INPUT:

- `c` – (default: `None`) if an element `c` in `self` is given, it is used as the maximal element in the interval
- `L` – (default: `None`) if a subset `L` (must be hashable!) of `self` is given, it is used as the underlying set (only cover relations are checked).
- `in_unitary_group` – (default: `False`) if `False`, the relation is given by $\sigma \leq \tau$ if $l_R(\sigma) + l_R(\sigma^{-1}\tau) = l_R(\tau)$; if `True`, the relation is given by $\sigma \leq \tau$ if $\dim(\text{Fix}(\sigma)) + \dim(\text{Fix}(\sigma^{-1}\tau)) = \dim(\text{Fix}(\tau))$

Note: If `L` is given, the parameter `c` is ignored.

EXAMPLES:

```

sage: W = SymmetricGroup(4)
sage: W.noncrossing_partition_lattice()
Finite lattice containing 14 elements

sage: W = WeylGroup(['G', 2])
sage: W.noncrossing_partition_lattice()
Finite lattice containing 8 elements

sage: W = ReflectionGroup((1,1,3)) # optional -
↳gap3

sage: sorted( w.reduced_word() for w in W.noncrossing_partition_
↳lattice() ) # optional - gap3
[[], [1], [1, 2], [1, 2, 1], [2]]

sage: sorted( w.reduced_word() for w in W.noncrossing_partition_
↳lattice(W.from_reduced_word([2,1])) ) # optional - gap3
[[], [1], [1, 2, 1], [2], [2, 1]]

sage: sorted( w.reduced_word() for w in W.noncrossing_partition_
↳lattice(W.from_reduced_word([2])) ) # optional - gap3
[[], [2]]

```

example()

Return an example of an irreducible complex reflection group.

EXAMPLES:

```

sage: from sage.categories.complex_reflection_groups import_
↳ComplexReflectionGroups
sage: ComplexReflectionGroups().Finite().Irreducible().example() #
↳optional - gap3
Irreducible complex reflection group of rank 3 and type G(4,2,3)

```

class ParentMethods

Bases: object

base_change_matrix()

Return the base change from the standard basis of the vector space of `self` to the basis given by the independent roots of `self`.

Todo: For non-well-generated groups there is a conflict with construction of the matrix for an element.

EXAMPLES:

```

sage: W = ReflectionGroup((1,1,3)) # optional -
↳gap3
sage: W.base_change_matrix() # optional -
↳gap3
[1 0]
[0 1]

```

(continues on next page)

(continued from previous page)

```

sage: W = ReflectionGroup(23) # optional - ↵
↪ gap3
sage: W.base_change_matrix() # optional - ↵
↪ gap3
[1 0 0]
[0 1 0]
[0 0 1]

sage: W = ReflectionGroup((3,1,2)) # optional - ↵
↪ gap3
sage: W.base_change_matrix() # optional - ↵
↪ gap3
[1 0]
[1 1]

sage: W = ReflectionGroup((4,2,2)) # optional - ↵
↪ gap3
sage: W.base_change_matrix() # optional - ↵
↪ gap3
[ 1 0]
[E(4) 1]

```

cardinality()Return the cardinality of `self`.It is given by the product of the degrees of `self`.

EXAMPLES:

```

sage: W = ColoredPermutations(1,3)
sage: W.cardinality()
6
sage: W = ColoredPermutations(2,3)
sage: W.cardinality()
48
sage: W = ColoredPermutations(4,3)
sage: W.cardinality()
384
sage: W = ReflectionGroup((4,2,3)) # optional - gap3
sage: W.cardinality() # optional - gap3
192

```

codedegrees()Return the codegrees of `self`.

OUTPUT: a tuple of Sage integers

EXAMPLES:

```

sage: W = ColoredPermutations(1,4)
sage: W.codedegrees()
(2, 1, 0)

sage: W = ColoredPermutations(3,3)

```

(continues on next page)

(continued from previous page)

```

sage: W.codegrees()
(6, 3, 0)

sage: W = ReflectionGroup(31)           # optional - gap3
sage: W.codegrees()                     # optional - gap3
(28, 16, 12, 0)

```

degrees()

Return the degrees of `self`.

OUTPUT: a tuple of Sage integers

EXAMPLES:

```

sage: W = ColoredPermutations(1,4)
sage: W.degrees()
(2, 3, 4)

sage: W = ColoredPermutations(3,3)
sage: W.degrees()
(3, 6, 9)

sage: W = ReflectionGroup(31)           # optional - gap3
sage: W.degrees()                       # optional - gap3
(8, 12, 20, 24)

```

is_real()

Return whether `self` is real.

A complex reflection group is *real* if it is isomorphic to a reflection group in $GL(V)$ over a real vector space V . Equivalently its character table has real entries.

This implementation uses the following statement: an irreducible complex reflection group is real if and only if 2 is a degree of `self` with multiplicity one. Hence, in general we just need to compare the number of occurrences of 2 as degree of `self` and the number of irreducible components.

EXAMPLES:

```

sage: W = ColoredPermutations(1,3)
sage: W.is_real()
True

sage: W = ColoredPermutations(4,3)
sage: W.is_real()
False

```

Todo: Add an example of non real finite complex reflection group that is generated by order 2 reflections.

is_well_generated()

Return whether `self` is well-generated.

A finite complex reflection group is *well generated* if the number of its simple reflections coincides with its rank.

See also:

`ComplexReflectionGroups.Finite.WellGenerated()`

Note:

- All finite real reflection groups are well generated.
- The complex reflection groups of type $G(r, 1, n)$ and of type $G(r, r, n)$ are well generated.
- The complex reflection groups of type $G(r, p, n)$ with $1 < p < r$ are *not* well generated.
- The direct product of two well generated finite complex reflection group is still well generated.

EXAMPLES:

```
sage: W = ColoredPermutations(1,3)
sage: W.is_well_generated()
True

sage: W = ColoredPermutations(4,3)
sage: W.is_well_generated()
True

sage: W = ReflectionGroup((4,2,3))           # optional - gap3
sage: W.is_well_generated()                 # optional - gap3
False

sage: W = ReflectionGroup((4,4,3))           # optional - gap3
sage: W.is_well_generated()                 # optional - gap3
True
```

number_of_reflection_hyperplanes()

Return the number of reflection hyperplanes of `self`.

This is also the number of distinguished reflections. For real groups, this coincides with the number of reflections.

This implementation uses that it is given by the sum of the codegrees of `self` plus its rank.

See also:

[`number_of_reflections\(\)`](#)

EXAMPLES:

```
sage: W = ColoredPermutations(1,3)
sage: W.number_of_reflection_hyperplanes()
3
sage: W = ColoredPermutations(2,3)
sage: W.number_of_reflection_hyperplanes()
9
sage: W = ColoredPermutations(4,3)
sage: W.number_of_reflection_hyperplanes()
15
sage: W = ReflectionGroup((4,2,3))           # optional - gap3
sage: W.number_of_reflection_hyperplanes()   # optional - gap3
15
```

number_of_reflections()

Return the number of reflections of `self`.

For real groups, this coincides with the number of reflection hyperplanes.

This implementation uses that it is given by the sum of the degrees of `self` minus its rank.

See also:

[`number_of_reflection_hyperplanes\(\)`](#)

EXAMPLES:

```
sage: [SymmetricGroup(i).number_of_reflections() for i in range(int(8))]
[0, 0, 1, 3, 6, 10, 15, 21]

sage: W = ColoredPermutations(1,3)
sage: W.number_of_reflections()
3
sage: W = ColoredPermutations(2,3)
sage: W.number_of_reflections()
9
sage: W = ColoredPermutations(4,3)
sage: W.number_of_reflections()
21
sage: W = ReflectionGroup((4,2,3))           # optional - gap3
sage: W.number_of_reflections()             # optional - gap3
15
```

rank()

Return the rank of `self`.

The rank of `self` is the dimension of the smallest faithful reflection representation of `self`.

This default implementation uses that the rank is the number of [`degrees\(\)`](#).

See also:

`ComplexReflectionGroups.rank()`

EXAMPLES:

```
sage: W = ColoredPermutations(1,3)
sage: W.rank()
2
sage: W = ColoredPermutations(2,3)
sage: W.rank()
3
sage: W = ColoredPermutations(4,3)
sage: W.rank()
3
sage: W = ReflectionGroup((4,2,3))           # optional - gap3
sage: W.rank()                               # optional - gap3
3
```

class SubcategoryMethods

Bases: `object`

WellGenerated()

Return the full subcategory of well-generated objects of `self`.

A finite complex generated group is *well generated* if it is isomorphic to a subgroup of the general linear group GL_n generated by n reflections.

See also:

`ComplexReflectionGroups.Finite.ParentMethods.is_well_generated()`

EXAMPLES:

```
sage: from sage.categories.complex_reflection_groups import _
      ↪ComplexReflectionGroups
sage: C = ComplexReflectionGroups().Finite().WellGenerated(); C
Category of well generated finite complex reflection groups
```

Here is an example of a finite well-generated complex reflection group:

```
sage: W = C.example(); W                               # optional - gap3
Reducible complex reflection group of rank 4 and type A2 x G(3,1,2)
```

All finite Coxeter groups are well generated:

```
sage: CoxeterGroups().Finite().is_subcategory(C)
True
sage: SymmetricGroup(3) in C
True
```

Note: The category of well generated finite complex reflection groups is currently implemented as an axiom. See discussion on [trac ticket #11187](#). This may be a bit of overkill. Still it's nice to have a full subcategory.

class WellGenerated(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

class Irreducible(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of finite irreducible well-generated finite complex reflection groups.

class ParentMethods

Bases: object

catalan_number(*positive=False, polynomial=False*)

Return the Catalan number associated to `self`.

It is defined by

$$\prod_{i=1}^n \frac{d_i + h}{d_i},$$

where d_1, \dots, d_n are the degrees and where h is the Coxeter number. See [Ar2006] for further information.

INPUT:

- `positive` – optional boolean (default `False`) if `True`, return instead the positive Catalan number
- `polynomial` – optional boolean (default `False`) if `True`, return instead the q -analogue as a polynomial in q

Note:

- For the symmetric group S_n , it reduces to the Catalan number $\frac{1}{n+1} \binom{2n}{n}$.
- The Catalan numbers for $G(r, 1, n)$ all coincide for $r > 1$.

EXAMPLES:

```
sage: [ColoredPermutations(1,n).catalan_number() for n in [3,4,5]]
[5, 14, 42]

sage: [ColoredPermutations(2,n).catalan_number() for n in [3,4,5]]
[20, 70, 252]

sage: [ReflectionGroup((2,2,n)).catalan_number() for n in [3,4,5]] #_
↳optional - gap3
[14, 50, 182]
```

coxeter_number()

Return the Coxeter number of a well-generated, irreducible reflection group. This is defined to be the order of a regular element in `self`, and is equal to the highest degree of `self`.

See also:

`ComplexReflectionGroups.Finite.Irreducible()`

Note: This method overwrites the more general method for complex reflection groups since the expression given here is quicker to compute.

EXAMPLES:

```
sage: W = ColoredPermutations(1,3)
sage: W.coxeter_number()
3

sage: W = ColoredPermutations(4,3)
sage: W.coxeter_number()
12

sage: W = ReflectionGroup((4,4,3)) # optional - gap3
sage: W.coxeter_number() # optional - gap3
8
```

fuss_catalan_number(*m*, *positive=False*, *polynomial=False*)

Return the *m*-th Fuss-Catalan number associated to `self`.

This is defined by

$$\prod_{i=1}^n \frac{d_i + mh}{d_i},$$

where d_1, \dots, d_n are the degrees and h is the Coxeter number.

INPUT:

- `positive` – optional boolean (default `False`) if `True`, return instead the positive Fuss-Catalan number

- `polynomial` – optional boolean (default `False`) if `True`, return instead the q -analogue as a polynomial in q
- See [Ar2006] for further information.

Note:

- For the symmetric group S_n , it reduces to the Fuss-Catalan number $\frac{1}{mn+1} \binom{(m+1)n}{n}$.
- The Fuss-Catalan numbers for $G(r, 1, n)$ all coincide for $r > 1$.

EXAMPLES:

```

sage: W = ColoredPermutations(1,3)
sage: [W.fuss_catalan_number(i) for i in [1,2,3]]
[5, 12, 22]

sage: W = ColoredPermutations(1,4)
sage: [W.fuss_catalan_number(i) for i in [1,2,3]]
[14, 55, 140]

sage: W = ColoredPermutations(1,5)
sage: [W.fuss_catalan_number(i) for i in [1,2,3]]
[42, 273, 969]

sage: W = ColoredPermutations(2,2)
sage: [W.fuss_catalan_number(i) for i in [1,2,3]]
[6, 15, 28]

sage: W = ColoredPermutations(2,3)
sage: [W.fuss_catalan_number(i) for i in [1,2,3]]
[20, 84, 220]

sage: W = ColoredPermutations(2,4)
sage: [W.fuss_catalan_number(i) for i in [1,2,3]]
[70, 495, 1820]

```

number_of_reflections_of_full_support()

Return the number of reflections with full support.

EXAMPLES:

```

sage: W = Permutations(4)
sage: W.number_of_reflections_of_full_support()
1

sage: W = ColoredPermutations(1,4)
sage: W.number_of_reflections_of_full_support()
1

sage: W = CoxeterGroup("B3")
sage: W.number_of_reflections_of_full_support()
3

sage: W = ColoredPermutations(3,3)
sage: W.number_of_reflections_of_full_support()

```

(continues on next page)

(continued from previous page)

3

rational_catalan_number(p , *polynomial=False*)Return the p -th rational Catalan number associated to `self`.

It is defined by

$$\prod_{i=1}^n \frac{p + (p(d_i - 1) \bmod h)}{d_i},$$

where d_1, \dots, d_n are the degrees and h is the Coxeter number. See [STW2016] for this formula.

INPUT:

- `polynomial` – optional boolean (default `False`) if `True`, return instead the q -analogue as a polynomial in q

EXAMPLES:

```
sage: W = ColoredPermutations(1,3)
sage: [W.rational_catalan_number(p) for p in [5,7,8]]
[7, 12, 15]

sage: W = ColoredPermutations(2,2)
sage: [W.rational_catalan_number(p) for p in [7,9,11]]
[10, 15, 21]
```

example()

Return an example of an irreducible well-generated complex reflection group.

EXAMPLES:

```
sage: from sage.categories.complex_reflection_groups import _
      ↪ ComplexReflectionGroups
sage: ComplexReflectionGroups().Finite().WellGenerated().Irreducible().
      ↪ example()
4-colored permutations of size 3
```

class ParentMethodsBases: `object`**coxeter_element()**

Return a Coxeter element.

The result is the product of the simple reflections, in some order.

Note: This implementation is shared with well generated complex reflection groups. It would be nicer to put it in some joint super category; however, in the current state of the art, there is none where it is clear that this is the right construction for obtaining a Coxeter element.

In this context, this is an element having a regular eigenvector (a vector not contained in any reflection hyperplane of `self`).

EXAMPLES:


```

sage: CoxeterGroup(['A', 4]).coxeter_element().reduced_word()
[1, 2, 3, 4]
sage: CoxeterGroup(['B', 4]).coxeter_element().reduced_word()
[1, 2, 3, 4]
sage: CoxeterGroup(['D', 4]).coxeter_element().reduced_word()
[1, 2, 4, 3]
sage: CoxeterGroup(['F', 4]).coxeter_element().reduced_word()
[1, 2, 3, 4]
sage: CoxeterGroup(['E', 8]).coxeter_element().reduced_word()
[1, 3, 2, 4, 5, 6, 7, 8]
sage: CoxeterGroup(['H', 3]).coxeter_element().reduced_word()
[1, 2, 3]

```

This method is also used for well generated finite complex reflection groups:

```

sage: W = ReflectionGroup((1,1,4))           # optional - gap3
sage: W.coxeter_element().reduced_word()    # optional - gap3
[1, 2, 3]

sage: W = ReflectionGroup((2,1,4))           # optional - gap3
sage: W.coxeter_element().reduced_word()    # optional - gap3
[1, 2, 3, 4]

sage: W = ReflectionGroup((4,1,4))           # optional - gap3
sage: W.coxeter_element().reduced_word()    # optional - gap3
[1, 2, 3, 4]

sage: W = ReflectionGroup((4,4,4))           # optional - gap3
sage: W.coxeter_element().reduced_word()    # optional - gap3
[1, 2, 3, 4]

```

coxeter_elements()

Return the (unique) conjugacy class in `self` containing all Coxeter elements.

A Coxeter element is an element that has an eigenvalue $e^{2\pi i/h}$ where h is the Coxeter number.

In case of finite Coxeter groups, these are exactly the elements that are conjugate to one (or, equivalently, all) standard Coxeter element, this is, to an element that is the product of the simple generators in some order.

See also:

`standard_coxeter_elements()`

EXAMPLES:

```

sage: W = ReflectionGroup((1,1,3))           # optional - gap3
sage: sorted(c.reduced_word() for c in W.coxeter_elements()) #_
↳ optional - gap3
[[1, 2], [2, 1]]

sage: W = ReflectionGroup((1,1,4))           # optional - gap3
sage: sorted(c.reduced_word() for c in W.coxeter_elements()) #_
↳ optional - gap3
[[1, 2, 1, 3, 2], [1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 1, 3, 2, 1], [3,
↳ 2, 1]]

```

is_well_generated()

Return True as self is well-generated.

EXAMPLES:

```
sage: W = ReflectionGroup((3,1,2))      # optional - gap3
sage: W.is_well_generated()            # optional - gap3
True
```

standard_coxeter_elements()

Return all standard Coxeter elements in self.

This is the set of all elements in self obtained from any product of the simple reflections in self.

Note:

- self is assumed to be well-generated.
- This works even beyond real reflection groups, but the conjugacy class is not unique and we only obtain one such class.

EXAMPLES:

```
sage: W = ReflectionGroup(4)            # optional - gap3
sage: sorted(W.standard_coxeter_elements()) # optional - gap3
[(1, 7, 6, 12, 23, 20) (2, 8, 17, 24, 9, 5) (3, 16, 10, 19, 15, 21) (4, 14, 11, 22, 18, 13),
 (1, 10, 4, 12, 21, 22) (2, 11, 19, 24, 13, 3) (5, 15, 7, 17, 16, 23) (6, 18, 8, 20, 14, 9)]
```

example()

Return an example of a well-generated complex reflection group.

EXAMPLES:

```
sage: from sage.categories.complex_reflection_groups import _
↪ComplexReflectionGroups
sage: ComplexReflectionGroups().Finite().WellGenerated().example() #_
↪optional - gap3
Reducible complex reflection group of rank 4 and type A2 x G(3,1,2)
```

example()

Return an example of a complex reflection group.

EXAMPLES:

```
sage: from sage.categories.complex_reflection_groups import _
↪ComplexReflectionGroups
sage: ComplexReflectionGroups().Finite().example() # optional - gap3
Reducible real reflection group of rank 4 and type A2 x B2
```

3.45 Finite Coxeter Groups

class `sage.categories.finite_coxeter_groups.FiniteCoxeterGroups`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of finite Coxeter groups.

EXAMPLES:

```
sage: CoxeterGroups.Finite()
Category of finite coxeter groups
sage: FiniteCoxeterGroups().super_categories()
[Category of finite generalized coxeter groups,
 Category of coxeter groups]

sage: G = CoxeterGroups().Finite().example()
sage: G.cayley_graph(side = "right").plot()
Graphics object consisting of 40 graphics primitives
```

Here are some further examples:

```
sage: WeylGroups().Finite().example()
The symmetric group on {0, ..., 3}

sage: WeylGroup(["B", 3])
Weyl Group of type ['B', 3] (as a matrix group acting on the ambient space)
```

Those other examples will eventually be also in this category:

```
sage: SymmetricGroup(4)
Symmetric group of order 4! as a permutation group
sage: DihedralGroup(5)
Dihedral group of order 10 as a permutation group
```

class `ElementMethods`

Bases: `object`

bruhat_upper_covers()

Returns all the elements that cover `self` in Bruhat order.

EXAMPLES:

```
sage: W = WeylGroup(["A", 4])
sage: w = W.from_reduced_word([3, 2])
sage: print([v.reduced_word() for v in w.bruhat_upper_covers()])
[[4, 3, 2], [3, 4, 2], [2, 3, 2], [3, 1, 2], [3, 2, 1]]

sage: W = WeylGroup(["B", 6])
sage: w = W.from_reduced_word([1, 2, 1, 4, 5])
sage: C = w.bruhat_upper_covers()
sage: len(C)
9
sage: print([v.reduced_word() for v in C])
[[6, 4, 5, 1, 2, 1], [4, 5, 6, 1, 2, 1], [3, 4, 5, 1, 2, 1], [2, 3, 4, 5, 1,
↪ 2],
```

(continues on next page)

(continued from previous page)

```
[1, 2, 3, 4, 5, 1], [4, 5, 4, 1, 2, 1], [4, 5, 3, 1, 2, 1], [4, 5, 2, 3, 1, ↵
↵2],
[4, 5, 1, 2, 3, 1]]
sage: ww = W.from_reduced_word([5,6,5])
sage: CC = ww.bruhat_upper_covers()
sage: print([v.reduced_word() for v in CC])
[[6, 5, 6, 5], [4, 5, 6, 5], [5, 6, 4, 5], [5, 6, 5, 4], [5, 6, 5, 3], [5, ↵
↵6, 5, 2],
[5, 6, 5, 1]]
```

Recursive algorithm: write w for self. If i is a non-descent of w , then the covers of w are exactly $\{ws_i, u_1s_i, u_2s_i, \dots, u_js_i\}$, where the u_k are those covers of ws_i that have a descent at i .

covered_reflections_subgroup()

Return the subgroup of W generated by the conjugates by w of the simple reflections indexed by right descents of w .

This is used to compute the shard intersection order on W .

EXAMPLES:

```
sage: W = CoxeterGroup(['A',3], base_ring=ZZ)
sage: len(W.long_element().covered_reflections_subgroup())
24
sage: s = W.simple_reflection(1)
sage: Gs = s.covered_reflections_subgroup()
sage: len(Gs)
2
sage: s in [u.lift() for u in Gs]
True
sage: len(W.one().covered_reflections_subgroup())
1
```

coxeter_knuth_graph()

Return the Coxeter-Knuth graph of type A .

The Coxeter-Knuth graph of type A is generated by the Coxeter-Knuth relations which are given by $aa + 1a \sim a + 1aa + 1$, $abc \sim acb$ if $b < a < c$ and $abc \sim bac$ if $a < c < b$.

EXAMPLES:

```
sage: W = WeylGroup(['A',4], prefix='s')
sage: w = W.from_reduced_word([1,2,1,3,2])
sage: D = w.coxeter_knuth_graph()
sage: D.vertices()
[(1, 2, 1, 3, 2),
(1, 2, 3, 1, 2),
(2, 1, 2, 3, 2),
(2, 1, 3, 2, 3),
(2, 3, 1, 2, 3)]
sage: D.edges()
[((1, 2, 1, 3, 2), (1, 2, 3, 1, 2), None),
((1, 2, 1, 3, 2), (2, 1, 2, 3, 2), None),
((2, 1, 2, 3, 2), (2, 1, 3, 2, 3), None),
((2, 1, 3, 2, 3), (2, 3, 1, 2, 3), None)]
```

(continues on next page)

(continued from previous page)

```

sage: w = W.from_reduced_word([1,3])
sage: D = w.coxeter_knuth_graph()
sage: D.vertices()
[(1, 3), (3, 1)]
sage: D.edges()
[]

```

coxeter_knuth_neighbor(*w*)

Return the Coxeter-Knuth (oriented) neighbors of the reduced word *w* of `self`.

INPUT:

- *w* – reduced word of `self`

The Coxeter-Knuth relations are given by $aa + 1a \sim a + 1aa + 1$, $abc \sim acb$ if $b < a < c$ and $abc \sim bac$ if $a < c < b$. This method returns all neighbors of *w* under the Coxeter-Knuth relations oriented from left to right.

EXAMPLES:

```

sage: W = WeylGroup(['A',4], prefix='s')
sage: word = [1,2,1,3,2]
sage: w = W.from_reduced_word(word)
sage: w.coxeter_knuth_neighbor(word)
{(1, 2, 3, 1, 2), (2, 1, 2, 3, 2)}

sage: word = [1,2,1,3,2,4,3]
sage: w = W.from_reduced_word(word)
sage: w.coxeter_knuth_neighbor(word)
{(1, 2, 1, 3, 4, 2, 3), (1, 2, 3, 1, 2, 4, 3), (2, 1, 2, 3, 2, 4, 3)}

```

is_coxeter_element()

Return whether this is a Coxeter element.

This is, whether `self` has an eigenvalue $e^{2\pi i/h}$ where *h* is the Coxeter number.

See also:

`coxeter_elements()`

EXAMPLES:

```

sage: W = CoxeterGroup(['A',2])
sage: c = prod(W.gens())
sage: c.is_coxeter_element()
True
sage: W.one().is_coxeter_element()
False

sage: W = WeylGroup(['G', 2])
sage: c = prod(W.gens())
sage: c.is_coxeter_element()
True
sage: W.one().is_coxeter_element()
False

```

class ParentMethods

Bases: object

Ambiguity resolution: the implementation of `some_elements` is preferable to that of `FiniteGroups`. The same holds for `__iter__`, although a breadth first search would be more natural; at least this maintains backward compatibility after [trac ticket #13589](#).

bhz_poset()

Return the Bergeron-Hohlweg-Zabrocki partial order on the Coxeter group.

This is a partial order on the elements of a finite Coxeter group W , which is distinct from the Bruhat order, the weak order and the shard intersection order. It was defined in [BHZ2005].

This partial order is not a lattice, as there is no unique maximal element. It can be succinctly defined as follows.

Let u and v be two elements of the Coxeter group W . Let $S(u)$ be the support of u . Then $u \leq v$ if and only if $v_{S(u)} = u$ (here $v = v^I v_I$ denotes the usual parabolic decomposition with respect to the standard parabolic subgroup W_I).

See also:[bruhat_poset\(\)](#), [shard_poset\(\)](#), [weak_poset\(\)](#)

EXAMPLES:

```
sage: W = CoxeterGroup(['A',3], base_ring=ZZ)
sage: P = W.bhz_poset(); P
Finite poset containing 24 elements
sage: P.relations_number()
103
sage: P.chain_polynomial()
34*q^4 + 90*q^3 + 79*q^2 + 24*q + 1
sage: len(P.maximal_elements())
13
```

bruhat_poset(facade=False)

Return the Bruhat poset of self.

See also:[bhz_poset\(\)](#), [shard_poset\(\)](#), [weak_poset\(\)](#)

EXAMPLES:

```
sage: W = WeylGroup(["A", 2])
sage: P = W.bruhat_poset()
sage: P
Finite poset containing 6 elements
sage: P.show()
```

Here are some typical operations on this poset:

```
sage: W = WeylGroup(["A", 3])
sage: P = W.bruhat_poset()
sage: u = W.from_reduced_word([3,1])
sage: v = W.from_reduced_word([3,2,1,2,3])
sage: P(u) <= P(v)
True
```

(continues on next page)

(continued from previous page)

```
sage: len(P.interval(P(u), P(v)))
10
sage: P.is_join_semilattice()
False
```

By default, the elements of P are aware that they belong to P :

```
sage: P.an_element().parent()
Finite poset containing 24 elements
```

If instead one wants the elements to be plain elements of the Coxeter group, one can use the facade option:

```
sage: P = W.bruhat_poset(facade = True)
sage: P.an_element().parent()
Weyl Group of type ['A', 3] (as a matrix group acting on the ambient space)
```

See also:

`Poset()` for more on posets and facade posets.

Todo:

- Use the symmetric group in the examples (for nicer output), and print the edges for a stronger test.
- The constructed poset should be lazy, in order to handle large / infinite Coxeter groups.

cambrian_lattice(c , $on_roots=False$)

Return the c -Cambrian lattice on delta sequences.

See [arXiv 1503.00710](#) and [arXiv math/0611106](#).

Delta sequences are certain 2-colored minimal factorizations of c into reflections.

INPUT:

- c – a standard Coxeter element in `self` (as a tuple, or as an element of `self`)
- `on_roots` (optional, default `False`) – if `on_roots` is `True`, the lattice is realized on roots rather than on reflections. In order for this to work, the ElementMethod `reflection_to_root` must be available.

EXAMPLES:

```
sage: CoxeterGroup(["A", 2]).cambrian_lattice((1,2))
Finite lattice containing 5 elements

sage: CoxeterGroup(["B", 2]).cambrian_lattice((1,2))
Finite lattice containing 6 elements

sage: CoxeterGroup(["G", 2]).cambrian_lattice((1,2))
Finite lattice containing 8 elements
```

codegrees()

Return the codegrees of the Coxeter group.

These are just the degrees minus 2.

EXAMPLES:

```

sage: CoxeterGroup(['A', 4]).codegrees()
(0, 1, 2, 3)
sage: CoxeterGroup(['B', 4]).codegrees()
(0, 2, 4, 6)
sage: CoxeterGroup(['D', 4]).codegrees()
(0, 2, 2, 4)
sage: CoxeterGroup(['F', 4]).codegrees()
(0, 4, 6, 10)
sage: CoxeterGroup(['E', 8]).codegrees()
(0, 6, 10, 12, 16, 18, 22, 28)
sage: CoxeterGroup(['H', 3]).codegrees()
(0, 4, 8)

sage: WeylGroup(["A",3], ["A",3], ["B",2]).codegrees()
(0, 1, 2, 0, 1, 2, 0, 2)

```

degrees()

Return the degrees of the Coxeter group.

The output is an increasing list of integers.

EXAMPLES:

```

sage: CoxeterGroup(['A', 4]).degrees()
(2, 3, 4, 5)
sage: CoxeterGroup(['B', 4]).degrees()
(2, 4, 6, 8)
sage: CoxeterGroup(['D', 4]).degrees()
(2, 4, 4, 6)
sage: CoxeterGroup(['F', 4]).degrees()
(2, 6, 8, 12)
sage: CoxeterGroup(['E', 8]).degrees()
(2, 8, 12, 14, 18, 20, 24, 30)
sage: CoxeterGroup(['H', 3]).degrees()
(2, 6, 10)

sage: WeylGroup(["A",3], ["A",3], ["B",2]).degrees()
(2, 3, 4, 2, 3, 4, 2, 4)

```

inversion_sequence(*word*)

Return the inversion sequence corresponding to the *word* in indices of simple generators of *self*.

If *word* corresponds to $[w_0, w_1, \dots, w_k]$, the output is $[w_0, w_0w_1w_0, \dots, w_0w_1 \cdots w_k \cdots w_1w_0]$.

INPUT:

- *word* – a word in the indices of the simple generators of *self*.

EXAMPLES:

```

sage: CoxeterGroup(["A", 2]).inversion_sequence([1,2,1])
[
[-1  1]  [ 0 -1]  [ 1  0]
[ 0  1], [-1  0], [ 1 -1]
]

sage: [t.reduced_word() for t in CoxeterGroup(["A",3]).inversion_
sequence([2,1,3,2,1,3])]

```

(continues on next page)

(continued from previous page)

```
[[2], [1, 2, 1], [2, 3, 2], [1, 2, 3, 2, 1], [3], [1]]
```

is_real()

Return True since `self` is a real reflection group.

EXAMPLES:

```
sage: CoxeterGroup(['F', 4]).is_real()
True
sage: CoxeterGroup(['H', 4]).is_real()
True
```

long_element(*index_set=None, as_word=False*)

Return the longest element of `self`, or of the parabolic subgroup corresponding to the given `index_set`.

INPUT:

- `index_set` – a subset (as a list or iterable) of the nodes of the Dynkin diagram; (default: all of them)
- `as_word` – boolean (default False). If True, then return instead a reduced decomposition of the longest element.

Should this method be called `maximal_element`? `longest_element`?

EXAMPLES:

```
sage: D10 = FiniteCoxeterGroups().example(10)
sage: D10.long_element()
(1, 2, 1, 2, 1, 2, 1, 2, 1, 2)
sage: D10.long_element([1])
(1,)
sage: D10.long_element([2])
(2,)
sage: D10.long_element([])
()

sage: D7 = FiniteCoxeterGroups().example(7)
sage: D7.long_element()
(1, 2, 1, 2, 1, 2, 1)
```

One can require instead a reduced word for `w0`:

```
sage: A3 = CoxeterGroup(['A', 3])
sage: A3.long_element(as_word=True)
[1, 2, 1, 3, 2, 1]
```

m_cambrian_lattice(*c, m=1, on_roots=False*)

Return the m -Cambrian lattice on m -delta sequences.

See [arXiv 1503.00710](https://arxiv.org/abs/1503.00710) and [arXiv math/0611106](https://arxiv.org/abs/math/0611106).

The m -delta sequences are certain m -colored minimal factorizations of c into reflections.

INPUT:

- c – a Coxeter element of `self` (as a tuple, or as an element of `self`)
- m – a positive integer (optional, default 1)

- `on_roots` (optional, default `False`) – if `on_roots` is `True`, the lattice is realized on roots rather than on reflections. In order for this to work, the ElementMethod `reflection_to_root` must be available.

EXAMPLES:

```
sage: CoxeterGroup(["A",2]).m_cambrian_lattice((1,2))
Finite lattice containing 5 elements

sage: CoxeterGroup(["A",2]).m_cambrian_lattice((1,2),2)
Finite lattice containing 12 elements
```

permutahedron(*point=None, base_ring=None*)

Return the permutahedron of `self`,

This is the convex hull of the point `point` in the weight basis under the action of `self` on the underlying vector space V .

See also:

`permutahedron()`

INPUT:

- `point` – optional, a point given by its coordinates in the weight basis (default is $(1, 1, 1, \dots)$)
- `base_ring` – optional, the base ring of the polytope

Note: The result is expressed in the root basis coordinates.

Note: If function is too slow, switching the base ring to `RDF` will almost certainly speed things up.

EXAMPLES:

```
sage: W = CoxeterGroup(['H',3], base_ring=RDF)
sage: W.permutahedron()
doctest:warning
...
UserWarning: This polyhedron data is numerically complicated; cdd could not
↳convert between the inexact V and H representation without loss of data.↳
↳The resulting object might show inconsistencies.
A 3-dimensional polyhedron in RDF^3 defined as the convex hull of 120↳
↳vertices

sage: W = CoxeterGroup(['I',7])
sage: W.permutahedron()
A 2-dimensional polyhedron in AA^2 defined as the convex hull of 14 vertices
sage: W.permutahedron(base_ring=RDF)
A 2-dimensional polyhedron in RDF^2 defined as the convex hull of 14↳
↳vertices

sage: W = ReflectionGroup(['A',3]) # optional -↳
↳gap3
sage: W.permutahedron() # optional -↳
↳gap3
A 3-dimensional polyhedron in QQ^3 defined as the convex hull
of 24 vertices
```


(continues on next page)

(continued from previous page)

```

sage: W = ReflectionGroup(['A',3],['B',2])           # optional -
↳gap3
sage: W.permutahedron()                             # optional -
↳gap3
A 5-dimensional polyhedron in QQ^5 defined as the convex hull of 192
↳vertices

```

**reflections_from_w0()**

Return the reflections of `self` using the inversion set of `w_0`.

EXAMPLES:

```

sage: WeylGroup(['A',2]).reflections_from_w0()
[
[0 1 0] [0 0 1] [1 0 0]
[1 0 0] [0 1 0] [0 0 1]
[0 0 1], [1 0 0], [0 1 0]
]

sage: WeylGroup(['A',3]).reflections_from_w0()
[
[0 1 0 0] [0 0 1 0] [1 0 0 0] [0 0 0 1] [1 0 0 0] [1 0 0 0]
[1 0 0 0] [0 1 0 0] [0 0 1 0] [0 1 0 0] [0 0 0 1] [0 1 0 0]
[0 0 1 0] [1 0 0 0] [0 1 0 0] [0 0 1 0] [0 0 1 0] [0 0 0 1]
[0 0 0 1], [0 0 0 1], [0 0 0 1], [1 0 0 0], [0 1 0 0], [0 0 1 0]
]

```

shard_poset(side='right')

Return the shard intersection order attached to W .

This is a lattice structure on W , introduced in [Rea2009]. It contains the noncrossing partition lattice, as the induced lattice on the subset of c -sortable elements.

The partial order is given by simultaneous inclusion of inversion sets and subgroups attached to every element.

The precise description used here can be found in [STW2018].

Another implementation for the symmetric groups is available as `shard_poset()`.

See also:

[bhz_poset\(\)](#), [bruhat_poset\(\)](#), [weak_poset\(\)](#)

EXAMPLES:

```
sage: W = CoxeterGroup(['A', 3], base_ring=ZZ)
sage: SH = W.shard_poset(); SH
Finite lattice containing 24 elements
sage: SH.is_graded()
True
sage: SH.characteristic_polynomial()
q^3 - 11*q^2 + 23*q - 13
sage: SH.f_polynomial()
34*q^3 + 22*q^2 + q
```

w0()

Return the longest element of self.

This attribute is deprecated, use [long_element\(\)](#) instead.

EXAMPLES:

```
sage: D8 = FiniteCoxeterGroups().example(8)
sage: D8.w0
(1, 2, 1, 2, 1, 2, 1, 2)
sage: D3 = FiniteCoxeterGroups().example(3)
sage: D3.w0
(1, 2, 1)
```

weak_lattice(*side='right', facade=False*)

INPUT:

- *side* – “left”, “right”, or “twosided” (default: “right”)
- *facade* – a boolean (default: False)

Returns the left (resp. right) poset for weak order. In this poset, u is smaller than v if some reduced word of u is a right (resp. left) factor of some reduced word of v .

See also:

[bhz_poset\(\)](#), [bruhat_poset\(\)](#), [shard_poset\(\)](#)

EXAMPLES:

```
sage: W = WeylGroup(["A", 2])
sage: P = W.weak_poset()
sage: P
Finite lattice containing 6 elements
sage: P.show()
```

This poset is in fact a lattice:

```
sage: W = WeylGroup(["B", 3])
sage: P = W.weak_poset(side = "left")
sage: P.is_lattice()
True
```

so this method has an alias [weak_lattice\(\)](#):

```
sage: W.weak_lattice(side = "left") is W.weak_poset(side = "left")
True
```

As a bonus feature, one can create the left-right weak poset:

```
sage: W = WeylGroup(["A", 2])
sage: P = W.weak_poset(side = "twosided")
sage: P.show()
sage: len(P.hasse_diagram().edges())
8
```

This is the transitive closure of the union of left and right order. In this poset, u is smaller than v if some reduced word of u is a factor of some reduced word of v . Note that this is not a lattice:

```
sage: P.is_lattice()
False
```

By default, the elements of P are aware of that they belong to P :

```
sage: P.an_element().parent()
Finite poset containing 6 elements
```

If instead one wants the elements to be plain elements of the Coxeter group, one can use the facade option:

```
sage: P = W.weak_poset(facade = True)
sage: P.an_element().parent()
Weyl Group of type ['A', 2] (as a matrix group acting on the ambient space)
```

See also:

[Poset\(\)](#) for more on posets and facade posets.

Todo:

- Use the symmetric group in the examples (for nicer output), and print the edges for a stronger test.
- The constructed poset should be lazy, in order to handle large / infinite Coxeter groups.

weak_poset(*side='right', facade=False*)

INPUT:

- *side* – “left”, “right”, or “twosided” (default: “right”)
- *facade* – a boolean (default: False)

Returns the left (resp. right) poset for weak order. In this poset, u is smaller than v if some reduced word of u is a right (resp. left) factor of some reduced word of v .

See also:

[bhz_poset\(\)](#), [bruhat_poset\(\)](#), [shard_poset\(\)](#)

EXAMPLES:

```
sage: W = WeylGroup(["A", 2])
sage: P = W.weak_poset()
sage: P
Finite lattice containing 6 elements
sage: P.show()
```

This poset is in fact a lattice:

```
sage: W = WeylGroup(["B", 3])
sage: P = W.weak_poset(side = "left")
sage: P.is_lattice()
True
```

so this method has an alias `weak_lattice()`:

```
sage: W.weak_lattice(side = "left") is W.weak_poset(side = "left")
True
```

As a bonus feature, one can create the left-right weak poset:

```
sage: W = WeylGroup(["A", 2])
sage: P = W.weak_poset(side = "twosided")
sage: P.show()
sage: len(P.hasse_diagram().edges())
8
```

This is the transitive closure of the union of left and right order. In this poset, u is smaller than v if some reduced word of u is a factor of some reduced word of v . Note that this is not a lattice:

```
sage: P.is_lattice()
False
```

By default, the elements of P are aware of that they belong to P :

```
sage: P.an_element().parent()
Finite poset containing 6 elements
```

If instead one wants the elements to be plain elements of the Coxeter group, one can use the facade option:

```
sage: P = W.weak_poset(facade = True)
sage: P.an_element().parent()
Weyl Group of type ['A', 2] (as a matrix group acting on the ambient space)
```

See also:

`Poset()` for more on posets and facade posets.

Todo:

- Use the symmetric group in the examples (for nicer output), and print the edges for a stronger test.
- The constructed poset should be lazy, in order to handle large / infinite Coxeter groups.

`extra_super_categories()`

EXAMPLES:

```
sage: CoxeterGroups().Finite().super_categories()
[Category of finite generalized coxeter groups,
 Category of coxeter groups]
```

3.46 Finite Crystals

class `sage.categories.finite_crystals.FiniteCrystals`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of finite crystals.

EXAMPLES:

```
sage: C = FiniteCrystals()
sage: C
Category of finite crystals
sage: C.super_categories()
[Category of crystals, Category of finite enumerated sets]
sage: C.example()
Highest weight crystal of type A_3 of highest weight omega_1
```

class `TensorProducts`(*category, *args*)

Bases: `sage.categories.tensor.TensorProductsCategory`

The category of finite crystals constructed by tensor product of finite crystals.

extra_super_categories()

EXAMPLES:

```
sage: FiniteCrystals().TensorProducts().extra_super_categories()
[Category of finite crystals]
```

example(*n=3*)

Returns an example of highest weight crystals, as per `Category.example()`.

EXAMPLES:

```
sage: B = FiniteCrystals().example(); B
Highest weight crystal of type A_3 of highest weight omega_1
```

extra_super_categories()

EXAMPLES:

```
sage: FiniteCrystals().extra_super_categories()
[Category of finite enumerated sets]
```

3.47 Finite dimensional algebras with basis

Todo: Quotients of polynomial rings.

Quotients in general.

Matrix rings.

REFERENCES:

- [CR1962]

class `sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of finite dimensional algebras with a distinguished basis.

EXAMPLES:

```
sage: C = FiniteDimensionalAlgebrasWithBasis(QQ); C
Category of finite dimensional algebras with basis over Rational Field
sage: C.super_categories()
[Category of algebras with basis over Rational Field,
 Category of finite dimensional magmatic algebras with basis over Rational Field]
sage: C.example()
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
```

class `Cellular`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

Cellular algebras.

Let R be a commutative ring. A R -algebra A is a *cellular algebra* if it has a *cell datum*, which is a tuple (Λ, i, M, C) , where Λ is finite poset with order \geq , if $\mu \in \Lambda$ then $T(\mu)$ is a finite set and

$$C: \prod_{\mu \in \Lambda} T(\mu) \times T(\mu) \longrightarrow A; (\mu, s, t) \mapsto c_{st}^{\mu} \text{ is an injective map}$$

such that the following holds:

- The set $\{c_{st}^{\mu} \mid \mu \in \Lambda, s, t \in T(\mu)\}$ is a basis of A .
- If $a \in A$ and $\mu \in \Lambda, s, t \in T(\mu)$ then:

$$ac_{st}^{\mu} = \sum_{u \in T(\mu)} r_a(s, u) c_{ut}^{\mu} \pmod{A^{>\mu}},$$

where $A^{>\mu}$ is spanned by

$$\{c_{ab}^{\nu} \mid \nu > \mu \text{ and } a, b \in T(\nu)\}.$$

Moreover, the scalar $r_a(s, u)$ depends only on a, s and u and, in particular, is independent of t .

- The map $\iota: A \longrightarrow A; c_{st}^{\mu} \mapsto c_{ts}^{\mu}$ is an algebra anti-isomorphism.

A *cellular basis* for A is any basis of the form $\{c_{st}^{\mu} \mid \mu \in \Lambda, s, t \in T(\mu)\}$.

Note that in particular, the scalars $r_a(u, s)$ in the second condition do not depend on t .

REFERENCES:

- [GrLe1996]
- [KX1998]
- [Mat1999]
- Wikipedia article [Cellular algebra](#)
- <http://webusers.imj-prg.fr/~bernhard.keller/ictp2006/lecturenotes/xi.pdf>

class `ElementMethods`

Bases: object

cellular_involution()

Return the cellular involution on `self`.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 4)
sage: elt = S([3,1,2,4])
sage: ci = elt.cellular_involution(); ci
7/48*[1, 3, 2, 4] + 49/48*[2, 3, 1, 4]
- 1/48*[3, 1, 2, 4] - 7/48*[3, 2, 1, 4]
sage: ci.cellular_involution()
[3, 1, 2, 4]
```

class ParentMethods

Bases: object

cell_module(*mu*, *kws*)**

Return the cell module indexed by `mu`.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: S.cell_module(Partition([2,1]))
Cell module indexed by [2, 1] of Cellular basis of
Symmetric group algebra of order 3 over Rational Field
```

cell_module_indices(*mu*)

Return the indices of the cell module of `self` indexed by `mu`.

This is the finite set $M(\lambda)$.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: S.cell_module_indices([2,1])
Standard tableaux of shape [2, 1]
```

cell_poset()

Return the cell poset of `self`.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 4)
sage: S.cell_poset()
Finite poset containing 5 elements
```

cells()

Return the cells of `self`.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: dict(S.cells())
{[1, 1, 1]: Standard tableaux of shape [1, 1, 1],
 [2, 1]: Standard tableaux of shape [2, 1],
 [3]: Standard tableaux of shape [3]}
```

cellular_basis()

Return the cellular basis of `self`.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: S.cellular_basis()
Cellular basis of Symmetric group algebra of order 3
over Rational Field
```

cellular_involution(x)

Return the cellular involution of x in `self`.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: for b in S.basis(): b, S.cellular_involution(b)
([1, 2, 3], [1, 2, 3])
([1, 3, 2], 49/48*[1, 3, 2] + 7/48*[2, 3, 1]
 - 7/48*[3, 1, 2] - 1/48*[3, 2, 1])
([2, 1, 3], [2, 1, 3])
([2, 3, 1], -7/48*[1, 3, 2] - 1/48*[2, 3, 1]
 + 49/48*[3, 1, 2] + 7/48*[3, 2, 1])
([3, 1, 2], 7/48*[1, 3, 2] + 49/48*[2, 3, 1]
 - 1/48*[3, 1, 2] - 7/48*[3, 2, 1])
([3, 2, 1], -1/48*[1, 3, 2] - 7/48*[2, 3, 1]
 + 7/48*[3, 1, 2] + 49/48*[3, 2, 1])
```

simple_module_parameterization()

Return a parameterization of the simple modules of `self`.

The set of simple modules are parameterized by $\lambda \in \Lambda$ such that the cell module bilinear form $\Phi_\lambda \neq 0$.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 4)
sage: S.simple_module_parameterization()
([4], [3, 1], [2, 2], [2, 1, 1], [1, 1, 1, 1])
```

class TensorProducts(*category*, *args)

Bases: [sage.categories.tensor.TensorProductsCategory](#)

The category of cellular algebras constructed by tensor product of cellular algebras.

class ParentMethods

Bases: object

cell_module_indices(mu)

Return the indices of the cell module of `self` indexed by μ .

This is the finite set $M(\lambda)$.

EXAMPLES:

```
sage: S2 = SymmetricGroupAlgebra(QQ, 2)
sage: S3 = SymmetricGroupAlgebra(QQ, 3)
sage: T = S2.tensor(S3)
sage: T.cell_module_indices([[1,1], [2,1]])
The Cartesian product of (Standard tableaux of shape [1, 1],
                          Standard tableaux of shape [2, 1])
```

cell_poset()

Return the cell poset of self.

EXAMPLES:

```
sage: S2 = SymmetricGroupAlgebra(QQ, 2)
sage: S3 = SymmetricGroupAlgebra(QQ, 3)
sage: T = S2.tensor(S3)
sage: T.cell_poset()
Finite poset containing 6 elements
```

cellular_involution()

Return the image of the cellular involution of the basis element indexed by i.

EXAMPLES:

```
sage: S2 = SymmetricGroupAlgebra(QQ, 2)
sage: S3 = SymmetricGroupAlgebra(QQ, 3)
sage: T = S2.tensor(S3)
sage: for b in T.basis(): b, T.cellular_involution(b)
([1, 2] # [1, 2, 3], [1, 2] # [1, 2, 3])
([1, 2] # [1, 3, 2],
 49/48*[1, 2] # [1, 3, 2] + 7/48*[1, 2] # [2, 3, 1]
 - 7/48*[1, 2] # [3, 1, 2] - 1/48*[1, 2] # [3, 2, 1])
([1, 2] # [2, 1, 3], [1, 2] # [2, 1, 3])
([1, 2] # [2, 3, 1],
 -7/48*[1, 2] # [1, 3, 2] - 1/48*[1, 2] # [2, 3, 1]
 + 49/48*[1, 2] # [3, 1, 2] + 7/48*[1, 2] # [3, 2, 1])
([1, 2] # [3, 1, 2],
 7/48*[1, 2] # [1, 3, 2] + 49/48*[1, 2] # [2, 3, 1]
 - 1/48*[1, 2] # [3, 1, 2] - 7/48*[1, 2] # [3, 2, 1])
([1, 2] # [3, 2, 1],
 -1/48*[1, 2] # [1, 3, 2] - 7/48*[1, 2] # [2, 3, 1]
 + 7/48*[1, 2] # [3, 1, 2] + 49/48*[1, 2] # [3, 2, 1])
([2, 1] # [1, 2, 3], [2, 1] # [1, 2, 3])
([2, 1] # [1, 3, 2],
 49/48*[2, 1] # [1, 3, 2] + 7/48*[2, 1] # [2, 3, 1]
 - 7/48*[2, 1] # [3, 1, 2] - 1/48*[2, 1] # [3, 2, 1])
([2, 1] # [2, 1, 3], [2, 1] # [2, 1, 3])
([2, 1] # [2, 3, 1],
 -7/48*[2, 1] # [1, 3, 2] - 1/48*[2, 1] # [2, 3, 1]
 + 49/48*[2, 1] # [3, 1, 2] + 7/48*[2, 1] # [3, 2, 1])
([2, 1] # [3, 1, 2],
 7/48*[2, 1] # [1, 3, 2] + 49/48*[2, 1] # [2, 3, 1]
 - 1/48*[2, 1] # [3, 1, 2] - 7/48*[2, 1] # [3, 2, 1])
([2, 1] # [3, 2, 1],
 -1/48*[2, 1] # [1, 3, 2] - 7/48*[2, 1] # [2, 3, 1]
 + 7/48*[2, 1] # [3, 1, 2] + 49/48*[2, 1] # [3, 2, 1])
```

extra_super_categories()

Tensor products of cellular algebras are cellular.

EXAMPLES:

```
sage: cat = Algebras(QQ).FiniteDimensional().WithBasis()
sage: cat.Cellular().TensorProducts().extra_super_categories()
[Category of finite dimensional cellular algebras with basis
over Rational Field]
```

class ElementMethods

Bases: object

on_left_matrix(*base_ring=None, action=<built-in function mul>, side='left'*)Return the matrix of the action of `self` on the algebra.

INPUT:

- `base_ring` – the base ring for the matrix to be constructed
- `action` – a bivariate function (default: `operator.mul()`)
- `side` – ‘left’ or ‘right’ (default: ‘left’)

EXAMPLES:

```
sage: QS3 = SymmetricGroupAlgebra(QQ, 3)
sage: a = QS3([2,1,3])
sage: a.to_matrix(side='left')
[0 0 1 0 0 0]
[0 0 0 0 1 0]
[1 0 0 0 0 0]
[0 0 0 0 0 1]
[0 1 0 0 0 0]
[0 0 0 1 0 0]
sage: a.to_matrix(side='right')
[0 0 1 0 0 0]
[0 0 0 1 0 0]
[1 0 0 0 0 0]
[0 1 0 0 0 0]
[0 0 0 0 0 1]
[0 0 0 0 1 0]
sage: a.to_matrix(base_ring=RDF, side="left")
[0.0 0.0 1.0 0.0 0.0 0.0]
[0.0 0.0 0.0 0.0 1.0 0.0]
[1.0 0.0 0.0 0.0 0.0 0.0]
[0.0 0.0 0.0 0.0 0.0 1.0]
[0.0 1.0 0.0 0.0 0.0 0.0]
[0.0 0.0 0.0 1.0 0.0 0.0]
```

AUTHORS: Mike Hansen, ...

to_matrix(*base_ring=None, action=<built-in function mul>, side='left'*)Return the matrix of the action of `self` on the algebra.

INPUT:

- `base_ring` – the base ring for the matrix to be constructed
- `action` – a bivariate function (default: `operator.mul()`)
- `side` – ‘left’ or ‘right’ (default: ‘left’)

EXAMPLES:

```
sage: QS3 = SymmetricGroupAlgebra(QQ, 3)
sage: a = QS3([2,1,3])
sage: a.to_matrix(side='left')
```

(continues on next page)

(continued from previous page)

```

[0 0 1 0 0 0]
[0 0 0 0 1 0]
[1 0 0 0 0 0]
[0 0 0 0 0 1]
[0 1 0 0 0 0]
[0 0 0 1 0 0]
sage: a.to_matrix(side='right')
[0 0 1 0 0 0]
[0 0 0 1 0 0]
[1 0 0 0 0 0]
[0 1 0 0 0 0]
[0 0 0 0 0 1]
[0 0 0 0 1 0]
sage: a.to_matrix(base_ring=RDF, side="left")
[0.0 0.0 1.0 0.0 0.0 0.0]
[0.0 0.0 0.0 0.0 1.0 0.0]
[1.0 0.0 0.0 0.0 0.0 0.0]
[0.0 0.0 0.0 0.0 0.0 1.0]
[0.0 1.0 0.0 0.0 0.0 0.0]
[0.0 0.0 0.0 0.0 1.0 0.0]

```

AUTHORS: Mike Hansen, ...

class ParentMethods

Bases: object

cartan_invariants_matrix()

Return the Cartan invariants matrix of the algebra.

OUTPUT: a matrix of non negative integers

Let A be this finite dimensional algebra and $(S_i)_{i \in I}$ be representatives of the right simple modules of A . Note that their adjoints S_i^* are representatives of the left simple modules.

Let $(P_i^L)_{i \in I}$ and $(P_i^R)_{i \in I}$ be respectively representatives of the corresponding indecomposable projective left and right modules of A . In particular, we assume that the indexing is consistent so that $S_i^* = \text{top } P_i^L$ and $S_i = \text{top } P_i^R$.

The *Cartan invariant matrix* $(C_{i,j})_{i,j \in I}$ is a matrix of non negative integers that encodes much of the representation theory of A ; namely:

- $C_{i,j}$ counts how many times $S_i^* \otimes S_j$ appears as composition factor of A seen as a bimodule over itself;
- $C_{i,j} = \dim \text{Hom}_A(P_j^R, P_i^R)$;
- $C_{i,j}$ counts how many times S_j appears as composition factor of P_i^R ;
- $C_{i,j} = \dim \text{Hom}_A(P_i^L, P_j^L)$;
- $C_{i,j}$ counts how many times S_i^* appears as composition factor of P_j^L .

In the commutative case, the Cartan invariant matrix is diagonal. In the context of solving systems of multivariate polynomial equations of dimension zero, A is the quotient of the polynomial ring by the ideal generated by the equations, the simple modules correspond to the roots, and the numbers $C_{i,i}$ give the multiplicities of those roots.

Note: For simplicity, the current implementation assumes that the index set I is of the form $\{0, \dots, n-1\}$. Better indexations will be possible in the future.

ALGORITHM:

The Cartan invariant matrix of A is computed from the dimension of the summands of its Peirce decomposition.

See also:

- `peirce_decomposition()`
- `isotypic_projective_modules()`

EXAMPLES:

For a semisimple algebra, in particular for group algebras in characteristic zero, the Cartan invariants matrix is the identity:

```
sage: A3 = SymmetricGroup(3).algebra(QQ)
sage: A3.cartan_invariants_matrix()
[1 0 0]
[0 1 0]
[0 0 1]
```

For the path algebra of a quiver, the Cartan invariants matrix counts the number of paths between two vertices:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example()
sage: A.cartan_invariants_matrix()
[1 2]
[0 1]
```

In the commutative case, the Cartan invariant matrix is diagonal:

```
sage: Z12 = Monoids().Finite().example(); Z12
An example of a finite multiplicative monoid: the integers modulo 12
sage: A = Z12.algebra(QQ)
sage: A.cartan_invariants_matrix()
[1 0 0 0 0 0 0 0 0 0]
[0 1 0 0 0 0 0 0 0 0]
[0 0 2 0 0 0 0 0 0 0]
[0 0 0 1 0 0 0 0 0 0]
[0 0 0 0 2 0 0 0 0 0]
[0 0 0 0 0 1 0 0 0 0]
[0 0 0 0 0 0 1 0 0 0]
[0 0 0 0 0 0 0 2 0 0]
[0 0 0 0 0 0 0 0 2 0]
[0 0 0 0 0 0 0 0 0 1]
```

With the algebra of the 0-Hecke monoid:

```
sage: from sage.monoids.hecke_monoid import HeckeMonoid
sage: A = HeckeMonoid(SymmetricGroup(4)).algebra(QQ)
sage: A.cartan_invariants_matrix()
[1 0 0 0 0 0 0 0]
[0 2 1 0 1 1 0 0]
[0 1 1 0 1 0 0 0]
[0 0 0 1 0 1 1 0]
[0 1 1 0 1 0 0 0]
[0 1 0 1 0 2 1 0]
```

(continues on next page)

(continued from previous page)

```
[0 0 0 1 0 1 1 0]
[0 0 0 0 0 0 0 1]
```

center()

Return the center of self.

See also:[center_basis\(\)](#)

EXAMPLES:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: center = A.center(); center
Center of An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: center in Algebras(QQ).WithBasis().FiniteDimensional().Commutative()
True
sage: center.dimension()
1
sage: center.basis()
Finite family {0: B[0]}
sage: center.ambient() is A
True
sage: [c.lift() for c in center.basis()]
[x + y]
```

The center of a semisimple algebra is semisimple:

```
sage: DihedralGroup(6).algebra(QQ).center() in Algebras(QQ).Semisimple()
True
```

Todo:

- Pickling by construction, as `A.center()`?
- Lazy evaluation of `_repr_`

center_basis()

Return a basis of the center of self.

OUTPUT:

- a list of elements of self.

See also:[center\(\)](#)

EXAMPLES:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
```

(continues on next page)

(continued from previous page)

```
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: A.center_basis()
(x + y,)
```

idempotent_lift(x)

Lift an idempotent of the semisimple quotient into an idempotent of `self`.

Let A be this finite dimensional algebra and π be the projection $A \rightarrow \overline{A}$ on its semisimple quotient. Let \overline{x} be an idempotent of \overline{A} , and x any lift thereof in A . This returns an idempotent e of A such that $\pi(e) = \overline{x}$ and e is a polynomial in x .

INPUT:

- x – an element of A that projects on an idempotent \overline{x} of the semisimple quotient of A . Alternatively one may give as input the idempotent \overline{x} , in which case some lift thereof will be taken for x .

OUTPUT: the idempotent e of `self`

ALGORITHM:

Iterate the formula $1 - (1 - x^2)^2$ until having an idempotent.

See [CR1962] for correctness and termination proofs.

EXAMPLES:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example()
sage: S = A.semisimple_quotient()
sage: A.idempotent_lift(S.basis()['x'])
x
sage: A.idempotent_lift(A.basis()['y'])
y
```

Todo: Add some non trivial example

is_commutative()

Return whether `self` is a commutative algebra.

EXAMPLES:

```
sage: S4 = SymmetricGroupAlgebra(QQ, 4)
sage: S4.is_commutative()
False
sage: S2 = SymmetricGroupAlgebra(QQ, 2)
sage: S2.is_commutative()
True
```

is_identity_decomposition_into_orthogonal_idempotents(l)

Return whether l is a decomposition of the identity into orthogonal idempotents.

INPUT:

- l – a list or iterable of elements of `self`

EXAMPLES:

```
sage: A = FiniteDimensionalAlgebrasWithBasis(QQ).example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
```

(continues on next page)

(continued from previous page)

(containing the arrows $a:x \rightarrow y$ and $b:x \rightarrow y$) over Rational Field

```
sage: x,y,a,b = A.algebra_generators(); x,y,a,b
(x, y, a, b)
```

```
sage: A.is_identity_decomposition_into_orthogonal_idempotents([A.one()])
True
```

```
sage: A.is_identity_decomposition_into_orthogonal_idempotents([x,y])
True
```

```
sage: A.is_identity_decomposition_into_orthogonal_idempotents([x+a, y-a])
True
```

Here the idempotents do not sum up to 1:

```
sage: A.is_identity_decomposition_into_orthogonal_idempotents([x])
False
```

Here $1+x$ and $-x$ are neither idempotent nor orthogonal:

```
sage: A.is_identity_decomposition_into_orthogonal_idempotents([1+x, -x])
False
```

With the algebra of the 0-Hecke monoid:

```
sage: from sage.monoids.hecke_monoid import HeckeMonoid
sage: A = HeckeMonoid(SymmetricGroup(4)).algebra(QQ)
sage: idempotents = A.orthogonal_idempotents_central_mod_radical()
sage: A.is_identity_decomposition_into_orthogonal_idempotents(idempotents)
True
```

Here are some more counterexamples:

1. Some orthogonal elements summing to 1 but not being idempotent:

```
sage: class PQAlgebra(CombinatorialFreeModule):
...:     def __init__(self, F, p):
...:         # Construct the quotient algebra F[x] / p,
...:         # where p is a univariate polynomial.
...:         R = parent(p); x = R.gen()
...:         I = R.ideal(p)
...:         self._xbar = R.quotient(I).gen()
...:         basis_keys = [self._xbar**i for i in range(p.degree())]
...:         CombinatorialFreeModule.__init__(self, F, basis_keys,
...:                                         category=Algebras(F).FiniteDimensional().
↳WithBasis())
...:         def x(self):
...:             return self(self._xbar)
...:         def one(self):
...:             return self.basis()[self.base_ring().one()]
...:         def product_on_basis(self, w1, w2):
...:             return self.from_vector(vector(w1*w2))
sage: R.<x> = PolynomialRing(QQ)
sage: A = PQAlgebra(QQ, x**3 - x**2 + x + 1); y = A.x()
sage: a, b = y, 1-y
```

(continues on next page)

(continued from previous page)

```
sage: A.is_identity_decomposition_into_orthogonal_idempotents((a, b))
False
```

For comparison:

```
sage: A = PQAAlgebra(QQ, x**2 - x); y = A.x()
sage: a, b = y, 1-y
sage: A.is_identity_decomposition_into_orthogonal_idempotents((a, b))
True
sage: A.is_identity_decomposition_into_orthogonal_idempotents((a, A.
↪zero(), b))
True
sage: A = PQAAlgebra(QQ, x**3 - x**2 + x - 1); y = A.x()
sage: a = (y**2 + 1) / 2
sage: b = 1 - a
sage: A.is_identity_decomposition_into_orthogonal_idempotents((a, b))
True
```

2. Some idempotents summing to 1 but not orthogonal:

```
sage: R.<x> = PolynomialRing(GF(2))
sage: A = PQAAlgebra(GF(2), x)
sage: a = A.one()
sage: A.is_identity_decomposition_into_orthogonal_idempotents((a,))
True
sage: A.is_identity_decomposition_into_orthogonal_idempotents((a, a, a))
False
```

3. Some orthogonal idempotents not summing to the identity:

```
sage: A.is_identity_decomposition_into_orthogonal_idempotents((a, a))
False
sage: A.is_identity_decomposition_into_orthogonal_idempotents(())
False
```

isotypic_projective_modules(*side='left'*)

Return the isotypic projective side self-modules.

Let P_i be representatives of the indecomposable projective side-modules of this finite dimensional algebra A , and S_i be the associated simple modules.

The regular side representation of A can be decomposed as a direct sum $A = \bigoplus_i Q_i$ where each Q_i is an isotypic projective module; namely Q_i is the direct sum of $\dim S_i$ copies of the indecomposable projective module P_i . This decomposition is not unique.

The isotypic projective modules are constructed as $Q_i = e_i A$, where the $(e_i)_i$ is the decomposition of the identity into orthogonal idempotents obtained by lifting the central orthogonal idempotents of the semisimple quotient of A .

INPUT:

- *side* – ‘left’ or ‘right’ (default: ‘left’)

OUTPUT: a list of subspaces of *self*.

EXAMPLES:

```

sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: Q = A.isotypic_projective_modules(side="left"); Q
[Free module generated by {0} over Rational Field,
 Free module generated by {0, 1, 2} over Rational Field]
sage: [[x.lift() for x in Qi.basis()]
.....: for Qi in Q]
[[x],
 [y, a, b]]

```

We check that the sum of the dimensions of the isotypic projective modules is the dimension of `self`:

```

sage: sum([Qi.dimension() for Qi in Q]) == A.dimension()
True

```

See also:

- [orthogonal_idempotents_central_mod_radical\(\)](#)
- [peirce_decomposition\(\)](#)

`orthogonal_idempotents_central_mod_radical()`

Return a family of orthogonal idempotents of `self` that project on the central orthogonal idempotents of the semisimple quotient.

OUTPUT:

- a list of orthogonal idempotents obtained by lifting the central orthogonal idempotents of the semisimple quotient.

ALGORITHM:

The orthogonal idempotents of A are obtained by lifting the central orthogonal idempotents of the semisimple quotient \bar{A} .

Namely, let (\bar{f}_i) be the central orthogonal idempotents of the semisimple quotient of A . We recursively construct orthogonal idempotents of A by the following procedure: assuming $(f_i)_{i < n}$ is a set of already constructed orthogonal idempotent, we construct f_k by idempotent lifting of $(1 - f)g(1 - f)$, where g is any lift of \bar{e}_k and $f = \sum_{i < k} f_i$.

See [CR1962] for correctness and termination proofs.

See also:

- `Algebras.SemiSimple.FiniteDimensional.WithBasis.ParentMethods.central_orthogonal_idempotents()`
- [idempotent_lift\(\)](#)

EXAMPLES:

```

sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: A.orthogonal_idempotents_central_mod_radical()
(x, y)

```

```

sage: Z12 = Monoids().Finite().example(); Z12
An example of a finite multiplicative monoid: the integers modulo 12
sage: A = Z12.algebra(QQ)
sage: idempotents = A.orthogonal_idempotents_central_mod_radical()
sage: sorted(idempotents, key=str) # py2
[-1/2*B[8] + 1/2*B[4],
 -B[0] + 1/2*B[8] + 1/2*B[4],
 -B[0] + 1/2*B[9] + 1/2*B[3],
 1/2*B[9] - 1/2*B[3],
 1/4*B[1] + 1/2*B[3] + 1/4*B[5] - 1/4*B[7] - 1/2*B[9] - 1/4*B[11],
 1/4*B[1] + 1/4*B[11] - 1/4*B[5] - 1/4*B[7],
 1/4*B[1] - 1/2*B[4] - 1/4*B[5] + 1/4*B[7] + 1/2*B[8] - 1/4*B[11],
 B[0],
 B[0] + 1/4*B[1] - 1/2*B[3] - 1/2*B[4] + 1/4*B[5] + 1/4*B[7] - 1/2*B[8] - 1/
↪2*B[9] + 1/4*B[11]]
sage: sorted(idempotents, key=str) # py3
[-B[0] + 1/2*B[4] + 1/2*B[8],
 1/2*B[4] - 1/2*B[8],
 1/2*B[9] + 1/2*B[3] - B[0],
 1/2*B[9] - 1/2*B[3],
 1/4*B[1] + 1/4*B[11] - 1/4*B[5] - 1/4*B[7],
 1/4*B[1] - 1/2*B[9] + 1/4*B[5] - 1/4*B[7] + 1/2*B[3] - 1/4*B[11],
 1/4*B[1] - 1/2*B[9] - 1/2*B[3] + 1/4*B[11] + 1/4*B[5] + 1/4*B[7] + B[0] -
↪1/2*B[4] - 1/2*B[8],
 1/4*B[1] - 1/4*B[5] + 1/4*B[7] - 1/4*B[11] - 1/2*B[4] + 1/2*B[8],
 B[0]]
sage: sum(idempotents) == 1
True
sage: all(e*e == e for e in idempotents)
True
sage: all(e*f == 0 and f*e == 0 for e in idempotents for f in idempotents
↪if e != f)
True

```

This is best tested with:

```

sage: A.is_identity_decomposition_into_orthogonal_idempotents(idempotents)
True

```

We construct orthogonal idempotents for the algebra of the 0-Hecke monoid:

```

sage: from sage.monoids.hecke_monoid import HeckeMonoid
sage: A = HeckeMonoid(SymmetricGroup(4)).algebra(QQ)
sage: idempotents = A.orthogonal_idempotents_central_mod_radical()
sage: A.is_identity_decomposition_into_orthogonal_idempotents(idempotents)
True

```

peirce_decomposition(*idempotents=None, check=True*)

Return a Peirce decomposition of *self*.

Let $(e_i)_i$ be a collection of orthogonal idempotents of A with sum 1. The *Peirce decomposition* of A is the decomposition of A into the direct sum of the subspaces $e_i A e_j$.

With the default collection of orthogonal idempotents, one has

$$\dim e_i A e_j = C_{i,j} \dim S_i \dim S_j$$

where $(S_i)_i$ are the simple modules of A and $(C_{i,j})_{i,j}$ is the Cartan invariants matrix.

INPUT:

- `idempotents` – a list of orthogonal idempotents $(e_i)_{i=0,\dots,n}$ of the algebra that sum to 1 (default: the idempotents returned by `orthogonal_idempotents_central_mod_radical()`)
- `check` – (default: True) whether to check that the idempotents are indeed orthogonal and idempotent and sum to 1

OUTPUT:

A list of lists l such that $l[i][j]$ is the subspace $e_i A e_j$.

See also:

- `orthogonal_idempotents_central_mod_radical()`
- `cartan_invariants_matrix()`

EXAMPLES:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: A.orthogonal_idempotents_central_mod_radical()
(x, y)
sage: decomposition = A.peirce_decomposition(); decomposition
[[Free module generated by {0} over Rational Field,
  Free module generated by {0, 1} over Rational Field],
 [Free module generated by {} over Rational Field,
  Free module generated by {0} over Rational Field]]
sage: [ [x.lift() for x in decomposition[i][j].basis()]
.....:   for j in range(2)]
.....:   for i in range(2)]
[[[x], [a, b]],
 [[], [y]]]
```

We recover that the group algebra of the symmetric group S_4 is a block matrix algebra:

```
sage: A = SymmetricGroup(4).algebra(QQ)
sage: decomposition = A.peirce_decomposition() # long time
sage: [[decomposition[i][j].dimension() # long time (4s)
.....:   for j in range(len(decomposition))]
.....:   for i in range(len(decomposition))]
[[9, 0, 0, 0, 0],
 [0, 9, 0, 0, 0],
 [0, 0, 4, 0, 0],
 [0, 0, 0, 1, 0],
 [0, 0, 0, 0, 1]]
```

The dimension of each block is d^2 , where d is the dimension of the corresponding simple module of S_4 . The latter are given by:

```
sage: [p.standard_tableaux().cardinality() for p in Partitions(4)]
[1, 3, 2, 3, 1]
```

peirce_summand(*ei, ej*)

Return the Peirce decomposition summand $e_i A e_j$.

INPUT:

- *self* – an algebra A
- *ei, ej* – two idempotents of A

OUTPUT: $e_i A e_j$, as a subspace of A .

See also:

- [peirce_decomposition\(\)](#)
- [principal_ideal\(\)](#)

EXAMPLES:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example()
sage: idemp = A.orthogonal_idempotents_central_mod_radical()
sage: A.peirce_summand(idemp[0], idemp[1])
Free module generated by {0, 1} over Rational Field
sage: A.peirce_summand(idemp[1], idemp[0])
Free module generated by {} over Rational Field
```

We recover the 2×2 block of $\mathbb{Q}[S_4]$ corresponding to the unique simple module of dimension 2 of the symmetric group S_4 :

```
sage: A4 = SymmetricGroup(4).algebra(QQ)
sage: e = A4.central_orthogonal_idempotents()[2]
sage: A4.peirce_summand(e, e)
Free module generated by {0, 1, 2, 3} over Rational Field
```

principal_ideal(*a, side='left'*)

Construct the side principal ideal generated by a .

EXAMPLES:

In order to highlight the difference between left and right principal ideals, our first example deals with a non commutative algebra:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: x, y, a, b = A.basis()
```

In this algebra, multiplication on the right by x annihilates all basis elements but x :

```
sage: x*x, y*x, a*x, b*x
(x, 0, 0, 0)
```

so the left ideal generated by x is one-dimensional:

```
sage: Ax = A.principal_ideal(x, side='left'); Ax
Free module generated by {0} over Rational Field
sage: [B.lift() for B in Ax.basis()]
[x]
```

Multiplication on the left by x annihilates only x and fixes the other basis elements:

```
sage: x*x, x*y, x*a, x*b
(x, 0, a, b)
```

so the right ideal generated by x is 3-dimensional:

```
sage: xA = A.principal_ideal(x, side='right'); xA
Free module generated by {0, 1, 2} over Rational Field
sage: [B.lift() for B in xA.basis()]
[x, a, b]
```

See also:

- [peirce_summand\(\)](#)

radical()

Return the Jacobson radical of self.

This uses [radical_basis\(\)](#), whose default implementation handles algebras over fields of characteristic zero or fields of characteristic p in which we can compute $x^{1/p}$.

See also:

[radical_basis\(\)](#), [semisimple_quotient\(\)](#)

EXAMPLES:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: radical = A.radical(); radical
Radical of An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
```

The radical is an ideal of A , and thus a finite dimensional non unital associative algebra:

```
sage: from sage.categories.associative_algebras import AssociativeAlgebras
sage: radical in AssociativeAlgebras(QQ).WithBasis().FiniteDimensional()
True
sage: radical in Algebras(QQ)
False

sage: radical.dimension()
2
sage: radical.basis()
Finite family {0: B[0], 1: B[1]}
sage: radical.ambient() is A
True
sage: [c.lift() for c in radical.basis()]
[a, b]
```

Todo:

- Tell Sage that the radical is in fact an ideal;
- Pickling by construction, as [A.center\(\)](#);
- Lazy evaluation of `_repr_`.

radical_basis()

Return a basis of the Jacobson radical of this algebra.

Note: This implementation handles algebras over fields of characteristic zero (using Dixon's lemma) or fields of characteristic p in which we can compute $x^{1/p}$ [FR1985], [Eb1989].

OUTPUT:

- a list of elements of self.

See also:

radical(), *Algebras.Semisimple*

EXAMPLES:

```
sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: A.radical_basis()
(a, b)
```

We construct the group algebra of the Klein Four-Group over the rationals:

```
sage: A = KleinFourGroup().algebra(QQ)
```

This algebra belongs to the category of finite dimensional algebras over the rationals:

```
sage: A in Algebras(QQ).FiniteDimensional().WithBasis()
True
```

Since the field has characteristic 0, Maschke's Theorem tells us that the group algebra is semisimple. So its radical is the zero ideal:

```
sage: A in Algebras(QQ).Semisimple()
True
sage: A.radical_basis()
()
```

Let's work instead over a field of characteristic 2:

```
sage: A = KleinFourGroup().algebra(GF(2))
sage: A in Algebras(GF(2)).Semisimple()
False
sage: A.radical_basis()
(( ) + (1,2)(3,4), (3,4) + (1,2)(3,4), (1,2) + (1,2)(3,4))
```

We now implement the algebra $A = K[x]/(x^p - 1)$, where K is a finite field of characteristic p , and check its radical; alas, we currently need to wrap A to make it a proper *ModulesWithBasis*:

```
sage: class AnAlgebra(CombinatorialFreeModule):
.....:     def __init__(self, F):
.....:         R.<x> = PolynomialRing(F)
.....:         I = R.ideal(x**F.characteristic()-F.one())
```

(continues on next page)

(continued from previous page)

```

.....:         self._xbar = R.quotient(I).gen()
.....:         basis_keys = [self._xbar**i for i in range(F.
↳characteristic())]
.....:         CombinatorialFreeModule.__init__(self, F, basis_keys,
.....:             category=Algebras(F).FiniteDimensional().WithBasis())
.....:     def one(self):
.....:         return self.basis()[self.base_ring().one()]
.....:     def product_on_basis(self, w1, w2):
.....:         return self.from_vector(vector(w1*w2))
sage: AnAlgebra(GF(3)).radical_basis()
(B[1] + 2*B[xbar^2], B[xbar] + 2*B[xbar^2])
sage: AnAlgebra(GF(16,'a')).radical_basis()
(B[1] + B[xbar],)
sage: AnAlgebra(GF(49,'a')).radical_basis()
(B[1] + 6*B[xbar^6], B[xbar] + 6*B[xbar^6], B[xbar^2] + 6*B[xbar^6],
B[xbar^3] + 6*B[xbar^6], B[xbar^4] + 6*B[xbar^6], B[xbar^5] + 6*B[xbar^6])

```

semisimple_quotient()

Return the semisimple quotient of `self`.

This is the quotient of `self` by its radical.

See also:

[`radical\(\)`](#)

EXAMPLES:

```

sage: A = Algebras(QQ).FiniteDimensional().WithBasis().example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: a,b,x,y = sorted(A.basis())
sage: S = A.semisimple_quotient(); S
Semisimple quotient of An example of a finite dimensional algebra with
↳basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: S in Algebras(QQ).Semisimple()
True
sage: S.basis()
Finite family {'x': B['x'], 'y': B['y']}
sage: xs,ys = sorted(S.basis())
sage: (xs + ys) * xs
B['x']

```

Sanity check: the semisimple quotient of the n -th descent algebra of the symmetric group is of dimension the number of partitions of n :

```

sage: [ DescentAlgebra(QQ,n).B().semisimple_quotient().dimension()
.....:     for n in range(6) ]
[1, 1, 2, 3, 5, 7]
sage: [Partitions(n).cardinality() for n in range(10)]
[1, 1, 2, 3, 5, 7, 11, 15, 22, 30]

```

Todo:

- Pickling by construction, as `A.semisimple_quotient()`?
- Lazy evaluation of `_repr_`

class SubcategoryMethods

Bases: object

Cellular()Return the full subcategory of the cellular objects of `self`.**See also:**[Wikipedia article Cellular_algebra](#)**EXAMPLES:**

```
sage: Algebras(QQ).FiniteDimensional().WithBasis().Cellular()
Category of finite dimensional cellular algebras with basis
over Rational Field
```

3.48 Finite dimensional bialgebras with basis

`sage.categories.finite_dimensional_bialgebras_with_basis.FiniteDimensionalBialgebrasWithBasis(base_ring)`

The category of finite dimensional bialgebras with a distinguished basis

EXAMPLES:

```
sage: C = FiniteDimensionalBialgebrasWithBasis(QQ); C
Category of finite dimensional bialgebras with basis over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of bialgebras with basis over Rational Field,
 Category of finite dimensional algebras with basis over Rational Field]
sage: C is Bialgebras(QQ).WithBasis().FiniteDimensional()
True
```

3.49 Finite dimensional coalgebras with basis

`sage.categories.finite_dimensional_coalgebras_with_basis.FiniteDimensionalCoalgebrasWithBasis(base_ring)`

The category of finite dimensional coalgebras with a distinguished basis

EXAMPLES:

```
sage: C = FiniteDimensionalCoalgebrasWithBasis(QQ); C
Category of finite dimensional coalgebras with basis over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of coalgebras with basis over Rational Field,
 Category of finite dimensional modules with basis over Rational Field]
sage: C is Coalgebras(QQ).WithBasis().FiniteDimensional()
True
```

3.50 Finite Dimensional Graded Lie Algebras With Basis

AUTHORS:

- Eero Hakavuori (2018-08-16): initial version

class `sage.categories.finite_dimensional_graded_lie_algebras_with_basis.FiniteDimensionalGradedLieAlgebrasWithBasis`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

Category of finite dimensional graded Lie algebras with a basis.

A grading of a Lie algebra \mathfrak{g} is a direct sum decomposition $\mathfrak{g} = \bigoplus_i V_i$ such that $[V_i, V_j] \subset V_{i+j}$.

EXAMPLES:

```
sage: C = LieAlgebras(ZZ).WithBasis().FiniteDimensional().Graded(); C
Category of finite dimensional graded lie algebras with basis over Integer Ring
sage: C.super_categories()
[Category of graded lie algebras with basis over Integer Ring,
 Category of finite dimensional lie algebras with basis over Integer Ring]

sage: C is LieAlgebras(ZZ).WithBasis().FiniteDimensional().Graded()
True
```

class `ParentMethods`

Bases: `object`

homogeneous_component_as_submodule(*d*)

Return the *d*-th homogeneous component of `self` as a submodule.

EXAMPLES:

```
sage: C = LieAlgebras(QQ).WithBasis().Graded()
sage: C = C.FiniteDimensional().Stratified().Nilpotent()
sage: L = LieAlgebra(QQ, {'x','y': {'z': 1}},
.....:                  nilpotent=True, category=C)
sage: L.homogeneous_component_as_submodule(2)
Sparse vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[0 0 1]
```

class `Stratified(base_category)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

Category of finite dimensional stratified Lie algebras with a basis.

A stratified Lie algebra is a graded Lie algebra that is generated as a Lie algebra by its homogeneous component of degree 1. That is to say, for a graded Lie algebra $L = \bigoplus_{k=1}^M L_k$, we have $L_{k+1} = [L_1, L_k]$.

EXAMPLES:

```
sage: C = LieAlgebras(QQ).WithBasis().Graded().Stratified().FiniteDimensional()
sage: C
Category of finite dimensional stratified lie algebras with basis over Rational
Field
```

A finite-dimensional stratified Lie algebra is nilpotent:

```
sage: C is C.Nilpotent()
True
```

class ParentMethods

Bases: object

degree_on_basis(m)

Return the degree of the basis element indexed by m.

If the degrees of the basis elements are not defined, they will be computed. By assumption the stratification $L_1 \oplus \cdots \oplus L_s$ of `self` is such that each component L_k is spanned by some subset of the basis.

The degree of a basis element X is therefore the largest index k such that $X \in L_k \oplus \cdots \oplus L_s$. The space $L_k \oplus \cdots \oplus L_s$ is by assumption the k -th term of the lower central series.

EXAMPLES:

```
sage: C = LieAlgebras(QQ).WithBasis().Graded()
sage: C = C.FiniteDimensional().Stratified().Nilpotent()
sage: sc = {'X','Y': {'Z': 1}}
sage: L.<X,Y,Z> = LieAlgebra(QQ, sc, nilpotent=True, category=C)
sage: L.degree_on_basis(X.leading_support())
1
sage: X.degree()
1
sage: Y.degree()
1
sage: L[X, Y]
Z
sage: Z.degree()
2
```

3.51 Finite dimensional Hopf algebras with basis

class sage.categories.finite_dimensional_hopf_algebras_with_basis.FiniteDimensionalHopfAlgebrasWithBasisBases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

The category of finite dimensional Hopf algebras with a distinguished basis.

EXAMPLES:

```
sage: FiniteDimensionalHopfAlgebrasWithBasis(QQ) # fixme: Hopf should be capitalized
Category of finite dimensional hopf algebras with basis over Rational Field
sage: FiniteDimensionalHopfAlgebrasWithBasis(QQ).super_categories()
[Category of hopf algebras with basis over Rational Field,
Category of finite dimensional algebras with basis over Rational Field]
```

class ElementMethods

Bases: object

class ParentMethods

Bases: object

3.52 Finite Dimensional Lie Algebras With Basis

AUTHORS:

- Travis Scrimshaw (07-15-2013): Initial implementation

class `sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis()`
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

Category of finite dimensional Lie algebras with a basis.

Todo: Many of these tests should use non-abelian Lie algebras and need to be added after [trac ticket #16820](#).

class `ElementMethods`

Bases: `object`

adjoint_matrix()

Return the matrix of the adjoint action of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.an_element().adjoint_matrix()
[0 0 0]
[0 0 0]
[0 0 0]
```

```
sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: x.adjoint_matrix()
[0 0]
[1 0]
sage: y.adjoint_matrix()
[-1 0]
[ 0 0]
```

to_vector(*order=None*)

Return the vector in `g.module()` corresponding to the element `self` of `g` (where `g` is the parent of `self`).

Implement this if you implement `g.module()`. See `sage.categories.lie_algebras.LieAlgebras.module()` for how this is to be done.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.an_element().to_vector()
(0, 0, 0)

sage: D = DescentAlgebra(QQ, 4).D()
sage: L = LieAlgebra(associative=D)
sage: L.an_element().to_vector()
(1, 1, 1, 1, 1, 1, 1, 1)
```

Nilpotent

alias of `sage.categories.finite_dimensional_nilpotent_lie_algebras_with_basis.FiniteDimensionalNilpotentLieAlgebrasWithBasis`

class ParentMethods

Bases: object

as_finite_dimensional_algebra()Return self as a `FiniteDimensionalAlgebra`.

EXAMPLES:

```

sage: L = lie_algebras.cross_product(QQ)
sage: x,y,z = L.basis()
sage: F = L.as_finite_dimensional_algebra()
sage: X,Y,Z = F.basis()
sage: x.bracket(y)
Z
sage: X * Y
Z

```

center()

Return the center of self.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: Z = L.center(); Z
An example of a finite dimensional Lie algebra with basis: the
  3-dimensional abelian Lie algebra over Rational Field
sage: Z.basis_matrix()
[1 0 0]
[0 1 0]
[0 0 1]

```

centralizer(S)

Return the centralizer of S in self.

INPUT:

- S – a subalgebra of self or a list of elements that represent generators for a subalgebra

See also:`centralizer_basis()`

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a,b,c = L.lie_algebra_generators()
sage: S = L.centralizer([a + b, 2*a + c]); S
An example of a finite dimensional Lie algebra with basis:
  the 3-dimensional abelian Lie algebra over Rational Field
sage: S.basis_matrix()
[1 0 0]
[0 1 0]
[0 0 1]

```

centralizer_basis(S)

Return a basis of the centralizer of S in self.

INPUT:

- S – a subalgebra of self or a list of elements that represent generators for a subalgebra

See also:

`centralizer()`

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a,b,c = L.lie_algebra_generators()
sage: L.centralizer_basis([a + b, 2*a + c])
[(1, 0, 0), (0, 1, 0), (0, 0, 1)]

sage: H = lie_algebras.Heisenberg(QQ, 2)
sage: H.centralizer_basis(H)
[z]

sage: D = DescentAlgebra(QQ, 4).D()
sage: L = LieAlgebra(associative=D)
sage: L.centralizer_basis(L)
[D{}],
D{1} + D{1, 2} + D{2, 3} + D{3},
D{1, 2, 3} + D{1, 3} + D{2}]
sage: D.center_basis()
[D{}],
D{1} + D{1, 2} + D{2, 3} + D{3},
D{1, 2, 3} + D{1, 3} + D{2}]

```

chevalley_eilenberg_complex(*M=None, dual=False, sparse=True, ncpus=None*)

Return the Chevalley-Eilenberg complex of `self`.

Let \mathfrak{g} be a Lie algebra and M be a right \mathfrak{g} -module. The *Chevalley-Eilenberg complex* is the chain complex on

$$C_{\bullet}(\mathfrak{g}, M) = M \otimes \bigwedge^{\bullet} \mathfrak{g},$$

where the differential is given by

$$d(m \otimes g_1 \wedge \cdots \wedge g_p) = \sum_{i=1}^p (-1)^{i+1} (mg_i) \otimes g_1 \wedge \cdots \wedge \hat{g}_i \wedge \cdots \wedge g_p + \sum_{1 \leq i < j \leq p} (-1)^{i+j} m \otimes [g_i, g_j] \wedge g_1 \wedge \cdots \wedge \hat{g}_i \wedge \cdots \wedge \hat{g}_j$$

INPUT:

- `M` – (default: the trivial 1-dimensional module) the module M
- `dual` – (default: `False`) if `True`, causes the dual of the complex to be computed
- `sparse` – (default: `True`) whether to use sparse or dense matrices
- `ncpus` – (optional) how many cpus to use

EXAMPLES:

```

sage: L = lie_algebras.sl(ZZ, 2)
sage: C = L.chevalley_eilenberg_complex(); C
Chain complex with at most 4 nonzero terms over Integer Ring
sage: ascii_art(C)
          [ 2  0  0]          [0]
          [ 0 -1  0]          [0]
          [ 0  0  2]          [0]
0 <-- C_0 <----- C_1 <----- C_2 <---- C_3 <-- 0

```

(continues on next page)

(continued from previous page)

```

sage: L = LieAlgebra(QQ, cartan_type=['C',2])
sage: C = L.chevalley_eilenberg_complex() # long time
sage: [C.free_module_rank(i) for i in range(11)] # long time
[1, 10, 45, 120, 210, 252, 210, 120, 45, 10, 1]

```

REFERENCES:

- [Wikipedia article Lie_algebra_cohomology#Chevalley-Eilenberg_complex](#)
- [Wei1994] Chapter 7

Todo: Currently this is only implemented for coefficients given by the trivial module R , where R is the base ring and $gR = 0$ for all $g \in \mathfrak{g}$. Allow generic coefficient modules M .

cohomology(*deg=None, M=None, sparse=True, ncpus=None*)

Return the Lie algebra cohomology of `self`.

The Lie algebra cohomology is the cohomology of the Chevalley-Eilenberg cochain complex (which is the dual of the Chevalley-Eilenberg chain complex).

Let \mathfrak{g} be a Lie algebra and M a left \mathfrak{g} -module. It is known that $H^0(\mathfrak{g}; M)$ is the subspace of \mathfrak{g} -invariants of M :

$$H^0(\mathfrak{g}; M) = M^{\mathfrak{g}} = \{m \in M \mid gm = 0 \text{ for all } g \in \mathfrak{g}\}.$$

Additionally, $H^1(\mathfrak{g}; M)$ is the space of derivations $\mathfrak{g} \rightarrow M$ modulo the space of inner derivations, and $H^2(\mathfrak{g}; M)$ is the space of equivalence classes of Lie algebra extensions of \mathfrak{g} by M .

INPUT:

- `deg` – the degree of the homology (optional)
- `M` – (default: the trivial module) a right module of `self`
- `sparse` – (default: `True`) whether to use sparse matrices for the Chevalley-Eilenberg chain complex
- `ncpus` – (optional) how many cpus to use when computing the Chevalley-Eilenberg chain complex

EXAMPLES:

```

sage: L = lie_algebras.so(QQ, 4)
sage: L.cohomology()
{0: Vector space of dimension 1 over Rational Field,
 1: Vector space of dimension 0 over Rational Field,
 2: Vector space of dimension 0 over Rational Field,
 3: Vector space of dimension 2 over Rational Field,
 4: Vector space of dimension 0 over Rational Field,
 5: Vector space of dimension 0 over Rational Field,
 6: Vector space of dimension 1 over Rational Field}

sage: L = lie_algebras.Heisenberg(QQ, 2)
sage: L.cohomology()
{0: Vector space of dimension 1 over Rational Field,
 1: Vector space of dimension 4 over Rational Field,
 2: Vector space of dimension 5 over Rational Field,
 3: Vector space of dimension 5 over Rational Field,
 4: Vector space of dimension 4 over Rational Field,
 5: Vector space of dimension 1 over Rational Field}

```

(continues on next page)

(continued from previous page)

```
sage: d = {'x': 'y': 2}
sage: L.<x,y> = LieAlgebra(ZZ, d)
sage: L.cohomology()
{0: Z, 1: Z, 2: C2}
```

See also:[chevalley_eilenberg_complex\(\)](#)

REFERENCES:

- [Wikipedia article Lie_algebra_cohomology](#)

derivations_basis()Return a basis for the Lie algebra of derivations of `self` as matrices.A derivation D of an algebra is an endomorphism of A such that

$$D([a, b]) = [D(a), b] + [a, D(b)]$$

for all $a, b \in A$. The set of all derivations form a Lie algebra.

EXAMPLES:

We construct the derivations of the Heisenberg Lie algebra:

```
sage: H = lie_algebras.Heisenberg(QQ, 1)
sage: H.derivations_basis()
(
 [1 0 0] [0 1 0] [0 0 0] [0 0 0] [0 0 0] [0 0 0]
 [0 0 0] [0 0 0] [1 0 0] [0 1 0] [0 0 0] [0 0 0]
 [0 0 1], [0 0 0], [0 0 0], [0 0 1], [1 0 0], [0 1 0]
)
```

We construct the derivations of \mathfrak{sl}_2 :

```
sage: sl2 = lie_algebras.sl(QQ, 2)
sage: sl2.derivations_basis()
(
 [ 1  0  0] [  0  1  0] [ 0  0  0]
 [ 0  0  0] [  0  0 -1/2] [ 1  0  0]
 [ 0  0 -1], [  0  0  0], [ 0 -2  0]
)
```

We verify these are derivations:

```
sage: D = [sl2.module_morphism(matrix=M, codomain=sl2)
.....:      for M in sl2.derivations_basis()]
sage: all(d(a.bracket(b)) == d(a).bracket(b) + a.bracket(d(b))
.....:      for a in sl2.basis() for b in sl2.basis() for d in D)
True
```

REFERENCES:

[Wikipedia article Derivation_\(differential_algebra\)](#)**derived_series()**Return the derived series $(\mathfrak{g}^{(i)})_i$ of `self` where the rightmost $\mathfrak{g}^{(k)} = \mathfrak{g}^{(k+1)} = \dots$.

We define the derived series of a Lie algebra \mathfrak{g} recursively by $\mathfrak{g}^{(0)} := \mathfrak{g}$ and

$$\mathfrak{g}^{(k+1)} = [\mathfrak{g}^{(k)}, \mathfrak{g}^{(k)}]$$

and recall that $\mathfrak{g}^{(k)} \supseteq \mathfrak{g}^{(k+1)}$. Alternatively we can express this as

$$\mathfrak{g} \supseteq [\mathfrak{g}, \mathfrak{g}] \supseteq [[\mathfrak{g}, \mathfrak{g}], [\mathfrak{g}, \mathfrak{g}]] \supseteq \left[[[\mathfrak{g}, \mathfrak{g}], [\mathfrak{g}, \mathfrak{g}]], [[\mathfrak{g}, \mathfrak{g}], [\mathfrak{g}, \mathfrak{g}]] \right] \supseteq \dots$$

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.derived_series()
(An example of a finite dimensional Lie algebra with basis:
 the 3-dimensional abelian Lie algebra over Rational Field,
 An example of a finite dimensional Lie algebra with basis:
 the 0-dimensional abelian Lie algebra over Rational Field
 with basis matrix:
 [])
```

```
sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: L.derived_series() # todo: not implemented - #17416
(Lie algebra on 2 generators (x, y) over Rational Field,
 Subalgebra generated of Lie algebra on 2 generators (x, y) over Rational_
↪Field with basis:
(x, ),
 Subalgebra generated of Lie algebra on 2 generators (x, y) over Rational_
↪Field with basis:
())
```

`derived_subalgebra()`

Return the derived subalgebra of self.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.derived_subalgebra()
An example of a finite dimensional Lie algebra with basis:
 the 0-dimensional abelian Lie algebra over Rational Field
 with basis matrix:
 []
```

If self is semisimple, then the derived subalgebra is self:

```
sage: sl3 = LieAlgebra(QQ, cartan_type=['A',2])
sage: sl3.derived_subalgebra()
Lie algebra of ['A', 2] in the Chevalley basis
sage: sl3 is sl3.derived_subalgebra()
True
```

`from_vector(v, order=None)`

Return the element of self corresponding to the vector v in `self.module()`.

Implement this if you implement `module()`; see the documentation of `sage.categories.lie_algebras.LieAlgebras.module()` for how this is to be done.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: u = L.from_vector(vector(QQ, (1, 0, 0))); u
(1, 0, 0)
sage: parent(u) is L
True

```

homology(*deg=None, M=None, sparse=True, ncpus=None*)

Return the Lie algebra homology of self.

The Lie algebra homology is the homology of the Chevalley-Eilenberg chain complex.

INPUT:

- *deg* – the degree of the homology (optional)
- *M* – (default: the trivial module) a right module of self
- *sparse* – (default: True) whether to use sparse matrices for the Chevalley-Eilenberg chain complex
- *ncpus* – (optional) how many cpus to use when computing the Chevalley-Eilenberg chain complex

EXAMPLES:

```

sage: L = lie_algebras.cross_product(QQ)
sage: L.homology()
{0: Vector space of dimension 1 over Rational Field,
 1: Vector space of dimension 0 over Rational Field,
 2: Vector space of dimension 0 over Rational Field,
 3: Vector space of dimension 1 over Rational Field}

sage: L = lie_algebras.pwitt(GF(5), 5)
sage: L.homology()
{0: Vector space of dimension 1 over Finite Field of size 5,
 1: Vector space of dimension 0 over Finite Field of size 5,
 2: Vector space of dimension 1 over Finite Field of size 5,
 3: Vector space of dimension 1 over Finite Field of size 5,
 4: Vector space of dimension 0 over Finite Field of size 5,
 5: Vector space of dimension 1 over Finite Field of size 5}

sage: d = {('x', 'y'): {'y': 2}}
sage: L.<x,y> = LieAlgebra(ZZ, d)
sage: L.homology()
{0: Z, 1: Z x C2, 2: 0}

```

See also:

[*chevalley_eilenberg_complex\(\)*](#)

ideal(*gens, **kws)

Return the ideal of self generated by gens.

INPUT:

- *gens* – a list of generators of the ideal
- *category* – (optional) a subcategory of subobjects of finite dimensional Lie algebras with basis

EXAMPLES:

```

sage: H = lie_algebras.Heisenberg(QQ, 2)
sage: p1,p2,q1,q2,z = H.basis()
sage: I = H.ideal([p1-p2, q1-q2])

```

(continues on next page)

(continued from previous page)

```
sage: I.basis().list()
[-p1 + p2, -q1 + q2, z]
sage: I.reduce(p1 + p2 + q1 + q2 + z)
2*p1 + 2*q1
```

Passing an extra category to an ideal:

```
sage: L.<x,y,z> = LieAlgebra(QQ, abelian=True)
sage: C = LieAlgebras(QQ).FiniteDimensional().WithBasis()
sage: C = C.Subobjects().Graded().Stratified()
sage: I = L.ideal(x, y, category=C)
sage: I.homogeneous_component_basis(1).list()
[x, y]
```

inner_derivations_basis()

Return a basis for the Lie algebra of inner derivations of `self` as matrices.

EXAMPLES:

```
sage: H = lie_algebras.Heisenberg(QQ, 1)
sage: H.inner_derivations_basis()
(
 [0 0 1]  [0 0 0]
 [0 0 0]  [0 0 1]
 [0 0 0], [0 0 0]
)
```

is_abelian()

Return if `self` is an abelian Lie algebra.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.is_abelian()
True
```

```
sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: L.is_abelian()
False
```

is_ideal(A)

Return if `self` is an ideal of `A`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: I = L.ideal([2*a - c, b + c])
sage: I.is_ideal(L)
True

sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: L.is_ideal(L)
True
```

(continues on next page)

(continued from previous page)

```
sage: F = LieAlgebra(QQ, 'F', representation='polynomial')
sage: L.is_ideal(F)
Traceback (most recent call last):
...
NotImplementedError: A must be a finite dimensional Lie algebra
with basis
```

is_nilpotent()

Return if `self` is a nilpotent Lie algebra.

A Lie algebra is nilpotent if the lower central series eventually becomes 0.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.is_nilpotent()
True
```

is_semisimple()

Return if `self` if a semisimple Lie algebra.

A Lie algebra is semisimple if the solvable radical is zero. In characteristic 0, this is equivalent to saying the Killing form is non-degenerate.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.is_semisimple()
False
```

is_solvable()

Return if `self` is a solvable Lie algebra.

A Lie algebra is solvable if the derived series eventually becomes 0.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.is_solvable()
True
```

```
sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: L.is_solvable() # todo: not implemented - #17416
False
```

killling_form(x, y)

Return the Killing form on `x` and `y`, where `x` and `y` are two elements of `self`.

The Killing form is defined as

$$\langle x | y \rangle = \text{tr}(\text{ad}_x \circ \text{ad}_y).$$

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a,b,c = L.lie_algebra_generators()
sage: L.killing_form(a, b)
0

```

killig_form_matrix()

Return the matrix of the Killing form of `self`.

The rows and the columns of this matrix are indexed by the elements of the basis of `self` (in the order provided by `basis()`).

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.killing_form_matrix()
[0 0 0]
[0 0 0]
[0 0 0]

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example(0)
sage: m = L.killing_form_matrix(); m
[]
sage: parent(m)
Full MatrixSpace of 0 by 0 dense matrices over Rational Field

```

killig_matrix(x, y)

Return the Killing matrix of `x` and `y`, where `x` and `y` are two elements of `self`.

The Killing matrix is defined as the matrix corresponding to the action of $\text{ad}_x \circ \text{ad}_y$ in the basis of `self`.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a,b,c = L.lie_algebra_generators()
sage: L.killing_matrix(a, b)
[0 0 0]
[0 0 0]
[0 0 0]

```

```

sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: L.killing_matrix(x, y)
[ 0  0]
[-1  0]

```

lower_central_series(submodule=False)

Return the lower central series $(\mathfrak{g}_i)_i$ of `self` where the rightmost $\mathfrak{g}_k = \mathfrak{g}_{k+1} = \dots$.

INPUT:

- `submodule` – (default: `False`) if `True`, then the result is given as submodules of `self`

We define the lower central series of a Lie algebra \mathfrak{g} recursively by $\mathfrak{g}_0 := \mathfrak{g}$ and

$$\mathfrak{g}_{k+1} = [\mathfrak{g}, \mathfrak{g}_k]$$

and recall that $\mathfrak{g}_k \supseteq \mathfrak{g}_{k+1}$. Alternatively we can express this as

$$\mathfrak{g} \supseteq [\mathfrak{g}, \mathfrak{g}] \supseteq [[\mathfrak{g}, \mathfrak{g}], \mathfrak{g}] \supseteq \left[[[\mathfrak{g}, \mathfrak{g}], \mathfrak{g}], \mathfrak{g} \right] \supseteq \dots$$

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.derived_series()
(An example of a finite dimensional Lie algebra with basis:
 the 3-dimensional abelian Lie algebra over Rational Field,
 An example of a finite dimensional Lie algebra with basis:
 the 0-dimensional abelian Lie algebra over Rational Field
 with basis matrix:
 [])
```

The lower central series as submodules:

```
sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: L.lower_central_series(submodule=True)
(Sparse vector space of dimension 2 over Rational Field,
 Vector space of degree 2 and dimension 1 over Rational Field
 Basis matrix:
 [1 0])
```

```
sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: L.lower_central_series() # todo: not implemented - #17416
(Lie algebra on 2 generators (x, y) over Rational Field,
 Subalgebra generated of Lie algebra on 2 generators (x, y) over Rational_
 ↪Field with basis:
 (x,))
```

module(*R=None*)

Return a dense free module associated to `self` over `R`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L._dense_free_module()
Vector space of dimension 3 over Rational Field
```

morphism(*on_generators, codomain=None, base_map=None, check=True*)

Return a Lie algebra morphism defined by images of a Lie generating subset of `self`.

INPUT:

- `on_generators` – dictionary `{X: Y}` of the images `Y` in codomain of elements `X` of domain
- `codomain` – a Lie algebra (optional); this is inferred from the values of `on_generators` if not given
- `base_map` – a homomorphism from the base ring to something coercing into the codomain
- `check` – (default: `True`) boolean; if `False` the values on the Lie brackets implied by `on_generators` will not be checked for contradictory values

Note: The keys of `on_generators` need to generate domain as a Lie algebra.

See also:

`sage.algebras.lie_algebras.morphism.LieAlgebraMorphism_from_generators`

EXAMPLES:

A quotient type Lie algebra morphism

```

sage: L.<X,Y,Z,W> = LieAlgebra(QQ, {'X','Y': {'Z':1}, ('X','Z'): {'W':1}})
sage: K.<A,B> = LieAlgebra(QQ, abelian=True)
sage: L.morphism({X: A, Y: B})
Lie algebra morphism:
  From: Lie algebra on 4 generators (X, Y, Z, W) over Rational Field
  To:   Abelian Lie algebra on 2 generators (A, B) over Rational Field
  Defn: X |--> A
        Y |--> B
        Z |--> 0
        W |--> 0

```

The reverse map $A \mapsto X, B \mapsto Y$ does not define a Lie algebra morphism, since $[A, B] = 0$, but $[X, Y] \neq 0$:

```

sage: K.morphism({A:X, B: Y})
Traceback (most recent call last):
...
ValueError: this does not define a Lie algebra morphism;
contradictory values for brackets of length 2

```

However, it is still possible to create a morphism that acts nontrivially on the coefficients, even though it's not a Lie algebra morphism (since it isn't linear):

```

sage: R.<x> = ZZ[]
sage: K.<i> = NumberField(x^2 + 1)
sage: cc = K.hom([-i])
sage: L.<X,Y,Z,W> = LieAlgebra(K, {'X','Y': {'Z':1}, ('X','Z'): {'W':1}})
sage: M.<A,B> = LieAlgebra(K, abelian=True)
sage: phi = L.morphism({X: A, Y: B}, base_map=cc)
sage: phi(X)
A
sage: phi(i*X)
-i*A

```

product_space(*L*, *submodule=False*)

Return the product space [*self*, *L*].

INPUT:

- *L* – a Lie subalgebra of *self*
- *submodule* – (default: *False*) if *True*, then the result is forced to be a submodule of *self*

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a,b,c = L.lie_algebra_generators()
sage: X = L.subalgebra([a, b+c])
sage: L.product_space(X)
An example of a finite dimensional Lie algebra with basis:
the 0-dimensional abelian Lie algebra over Rational Field
with basis matrix:
[]
sage: Y = L.subalgebra([a, 2*b-c])
sage: X.product_space(Y)
An example of a finite dimensional Lie algebra with basis:
the 0-dimensional abelian Lie algebra over Rational

```

(continues on next page)

(continued from previous page)

```
Field with basis matrix:
[]
```

```
sage: H = lie_algebras.Heisenberg(ZZ, 4)
sage: Hp = H.product_space(H, submodule=True).basis()
sage: [H.from_vector(v) for v in Hp]
[z]
```

```
sage: L.<x,y> = LieAlgebra(QQ, {'x','y':{'x':1}})
sage: Lp = L.product_space(L) # todo: not implemented - #17416
sage: Lp # todo: not implemented - #17416
Subalgebra generated of Lie algebra on 2 generators (x, y) over Rational_
↳Field with basis:
(x,)
sage: Lp.product_space(L) # todo: not implemented - #17416
Subalgebra generated of Lie algebra on 2 generators (x, y) over Rational_
↳Field with basis:
(x,)
sage: L.product_space(Lp) # todo: not implemented - #17416
Subalgebra generated of Lie algebra on 2 generators (x, y) over Rational_
↳Field with basis:
(x,)
sage: Lp.product_space(Lp) # todo: not implemented - #17416
Subalgebra generated of Lie algebra on 2 generators (x, y) over Rational_
↳Field with basis:
()
```

quotient(*I*, *names=None*, *category=None*)

Return the quotient of **self** by the ideal *I*.

A quotient Lie algebra.

INPUT:

- *I* – an ideal or a list of generators of the ideal
- *names* – (optional) a string or a list of strings; names for the basis elements of the quotient. If *names* is a string, the basis will be named `names_1, ..., names_n``.

EXAMPLES:

The Engel Lie algebra as a quotient of the free nilpotent Lie algebra of step 3 with 2 generators:

```
sage: L.<X,Y,Z,W,U> = LieAlgebra(QQ, 2, step=3)
sage: E = L.quotient(U); E
Lie algebra quotient L/I of dimension 4 over Rational Field where
L: Free Nilpotent Lie algebra on 5 generators (X, Y, Z, W, U) over Rational_
↳Field
I: Ideal (U)
sage: E.basis().list()
[X, Y, Z, W]
sage: E(X).bracket(E(Y))
Z
sage: Y.bracket(Z)
-U
sage: E(Y).bracket(E(Z))
```

(continues on next page)

(continued from previous page)

```

0
sage: E(U)
0

```

Quotients when the base ring is not a field are not implemented:

```

sage: L = lie_algebras.Heisenberg(ZZ, 1)
sage: L.quotient(L.an_element())
Traceback (most recent call last):
...
NotImplementedError: quotients over non-fields not implemented

```

structure_coefficients(*include_zeros=False*)

Return the structure coefficients of `self`.

INPUT:

- `include_zeros` – (default: `False`) if `True`, then include the $[x, y] = 0$ pairs in the output

OUTPUT:

A dictionary whose keys are pairs of basis indices (i, j) with $i < j$, and whose values are the corresponding *elements* $[b_i, b_j]$ in the Lie algebra.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.structure_coefficients()
Finite family {}
sage: L.structure_coefficients(True)
Finite family {(0, 1): (0, 0, 0), (0, 2): (0, 0, 0), (1, 2): (0, 0, 0)}

```

```

sage: G = SymmetricGroup(3)
sage: S = GroupAlgebra(G, QQ)
sage: L = LieAlgebra(associative=S)
sage: L.structure_coefficients()
Finite family {((2,3), (1,2)): (1,2,3) - (1,3,2),
               ((2,3), (1,3)): -(1,2,3) + (1,3,2),
               ((1,2,3), (2,3)): -(1,2) + (1,3),
               ((1,2,3), (1,2)): (2,3) - (1,3),
               ((1,2,3), (1,3)): -(2,3) + (1,2),
               ((1,3,2), (2,3)): (1,2) - (1,3),
               ((1,3,2), (1,2)): -(2,3) + (1,3),
               ((1,3,2), (1,3)): (2,3) - (1,2),
               ((1,3), (1,2)): -(1,2,3) + (1,3,2)}

```

subalgebra(**gens*, ***kwds*)

Return the subalgebra of `self` generated by `gens`.

INPUT:

- `gens` – a list of generators of the subalgebra
- `category` – (optional) a subcategory of subobjects of finite dimensional Lie algebras with basis

EXAMPLES:

```

sage: H = lie_algebras.Heisenberg(QQ, 2)
sage: p1,p2,q1,q2,z = H.basis()

```

(continues on next page)

(continued from previous page)

```

sage: S = H.subalgebra([p1, q1])
sage: S.basis().list()
[p1, q1, z]
sage: S.basis_matrix()
[1 0 0 0 0]
[0 0 1 0 0]
[0 0 0 0 1]

```

Passing an extra category to a subalgebra:

```

sage: L = LieAlgebra(QQ, 3, step=2)
sage: x,y,z = L.homogeneous_component_basis(1)
sage: C = LieAlgebras(QQ).FiniteDimensional().WithBasis()
sage: C = C.Subobjects().Graded().Stratified()
sage: S = L.subalgebra([x, y], category=C)
sage: S.homogeneous_component_basis(2).list()
[X_12]

```

universal_commutative_algebra()

Return the universal commutative algebra associated to `self`.

Let I be the index set of the basis of `self`. Let $\mathcal{P} = \{P_{a,i,j}\}_{a,i,j \in I}$ denote the universal polynomials of a Lie algebra L . The *universal commutative algebra* associated to L is the quotient ring $R[X_{ij}]_{i,j \in I}/(\mathcal{P})$.

EXAMPLES:

```

sage: L.<x,y> = LieAlgebra(QQ, {'x','y': {'x':1}})
sage: A = L.universal_commutative_algebra()
sage: a,b,c,d = A.gens()
sage: (a,b,c,d)
(X00bar, X01bar, 0, X11bar)
sage: a*d - a
0

```

universal_polynomials()

Return the family of universal polynomials of `self`.

The *universal polynomials* of a Lie algebra L with basis $\{e_i\}_{i \in I}$ and structure coefficients $[e_i, e_j] = \tau_{ij}^a e_a$ is given by

$$P_{aij} = \sum_{u \in I} \tau_{ij}^u X_{au} - \sum_{s,t \in I} \tau_{st}^a X_{si} X_{tj},$$

where $a, i, j \in I$.

REFERENCES:

- [AM2020]

EXAMPLES:

```

sage: L.<x,y> = LieAlgebra(QQ, {'x','y': {'x':1}})
sage: L.universal_polynomials()
Finite family {'x', 'x', 'y'): X01*X10 - X00*X11 + X00,
              ('y', 'x', 'y'): X10}

```

(continues on next page)

(continued from previous page)

```

sage: L = LieAlgebra(QQ, cartan_type=['A',1])
sage: list(L.universal_polynomials())
[-2*X01*X10 + 2*X00*X11 - 2*X00,
 -2*X02*X10 + 2*X00*X12 + X01,
 -2*X02*X11 + 2*X01*X12 - 2*X02,
 X01*X20 - X00*X21 - 2*X10,
 X02*X20 - X00*X22 + X11,
 X02*X21 - X01*X22 - 2*X12,
 -2*X11*X20 + 2*X10*X21 - 2*X20,
 -2*X12*X20 + 2*X10*X22 + X21,
 -2*X12*X21 + 2*X11*X22 - 2*X22]

sage: L = LieAlgebra(QQ, cartan_type=['B',2])
sage: al = RootSystem(['B',2]).root_lattice().simple_roots()
sage: k = list(L.basis().keys())[0]
sage: UP = L.universal_polynomials() # long time
sage: len(UP) # long time
450
sage: UP[al[2],al[1],-al[1]] # long time
X0_7*X4_1 - X0_1*X4_7 - 2*X0_7*X5_1 + 2*X0_1*X5_7 + X2_7*X7_1
 - X2_1*X7_7 - X3_7*X8_1 + X3_1*X8_7 + X0_4

```

class Subobjects(category, *args)

Bases: *sage.categories.subobjects.SubobjectsCategory*

A category for subalgebras of a finite dimensional Lie algebra with basis.

class ParentMethods

Bases: object

ambient()

Return the ambient Lie algebra of self.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: S = L.subalgebra([2*a+b, b + c])
sage: S.ambient() == L
True

```

basis_matrix()

Return the basis matrix of self.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: S = L.subalgebra([2*a+b, b + c])
sage: S.basis_matrix()
[ 1  0 -1/2]
[ 0  1  1]

```

example(n=3)

Return an example of a finite dimensional Lie algebra with basis as per *Category.example*.

EXAMPLES:

```
sage: C = LieAlgebras(QQ).FiniteDimensional().WithBasis()
sage: C.example()
An example of a finite dimensional Lie algebra with basis:
the 3-dimensional abelian Lie algebra over Rational Field
```

Other dimensions can be specified as an optional argument:

```
sage: C.example(5)
An example of a finite dimensional Lie algebra with basis:
the 5-dimensional abelian Lie algebra over Rational Field
```

3.53 Finite dimensional modules with basis

class `sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of finite dimensional modules with a distinguished basis

EXAMPLES:

```
sage: C = FiniteDimensionalModulesWithBasis(ZZ); C
Category of finite dimensional modules with basis over Integer Ring
sage: sorted(C.super_categories(), key=str)
[Category of finite dimensional modules over Integer Ring,
Category of modules with basis over Integer Ring]
sage: C is Modules(ZZ).WithBasis().FiniteDimensional()
True
```

class `ElementMethods`

Bases: `object`

dense_coefficient_list(*order=None*)

Return a list of *all* coefficients of `self`.

By default, this list is ordered in the same way as the indexing set of the basis of the parent of `self`.

INPUT:

- `order` – (optional) an ordering of the basis indexing set

EXAMPLES:

```
sage: v = vector([0, -1, -3])
sage: v.dense_coefficient_list()
[0, -1, -3]
sage: v.dense_coefficient_list([2, 1, 0])
[-3, -1, 0]
sage: sorted(v.coefficients())
[-3, -1]
```

class `MorphismMethods`

Bases: `object`

image()

Return the image of `self` as a submodule of the codomain.

EXAMPLES:

```
sage: SGA = SymmetricGroupAlgebra(QQ, 3)
sage: f = SGA.module_morphism(lambda x: SGA(x**2), codomain=SGA)
sage: f.image()
Free module generated by {0, 1, 2} over Rational Field
```

image_basis()

Return a basis for the image of `self` in echelon form.

EXAMPLES:

```
sage: SGA = SymmetricGroupAlgebra(QQ, 3)
sage: f = SGA.module_morphism(lambda x: SGA(x**2), codomain=SGA)
sage: f.image_basis()
([1, 2, 3], [2, 3, 1], [3, 1, 2])
```

kernel()

Return the kernel of `self` as a submodule of the domain.

EXAMPLES:

```
sage: SGA = SymmetricGroupAlgebra(QQ, 3)
sage: f = SGA.module_morphism(lambda x: SGA(x**2), codomain=SGA)
sage: K = f.kernel()
sage: K
Free module generated by {0, 1, 2} over Rational Field
sage: K.ambient()
Symmetric group algebra of order 3 over Rational Field
```

kernel_basis()

Return a basis of the kernel of `self` in echelon form.

EXAMPLES:

```
sage: SGA = SymmetricGroupAlgebra(QQ, 3)
sage: f = SGA.module_morphism(lambda x: SGA(x**2), codomain=SGA)
sage: f.kernel_basis()
([1, 2, 3] - [3, 2, 1], [1, 3, 2] - [3, 2, 1], [2, 1, 3] - [3, 2, 1])
```

matrix(*base_ring=None, side='left'*)

Return the matrix of this morphism in the distinguished bases of the domain and codomain.

INPUT:

- `base_ring` – a ring (default: `None`, meaning the base ring of the codomain)
- `side` – “left” or “right” (default: “left”)

If `side` is “left”, this morphism is considered as acting on the left; i.e. each column of the matrix represents the image of an element of the basis of the domain.

The order of the rows and columns matches with the order in which the bases are enumerated.

See also:

`Modules.WithBasis.ParentMethods.module_morphism()`

EXAMPLES:

```

sage: X = CombinatorialFreeModule(ZZ, [1,2]); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [3,4]); y = Y.basis()
sage: phi = X.module_morphism(on_basis = {1: y[3] + 3*y[4], 2: 2*y[3] +
↪5*y[4]}.__getitem__,
.....:                               codomain = Y)
sage: phi.matrix()
[1 2]
[3 5]
sage: phi.matrix(side="right")
[1 3]
[2 5]

sage: phi.matrix().parent()
Full MatrixSpace of 2 by 2 dense matrices over Integer Ring
sage: phi.matrix(QQ).parent()
Full MatrixSpace of 2 by 2 dense matrices over Rational Field

```

The resulting matrix is immutable:

```

sage: phi.matrix().is_mutable()
False

```

The zero morphism has a zero matrix:

```

sage: Hom(X,Y).zero().matrix()
[0 0]
[0 0]

```

Todo: Add support for morphisms where the codomain has a different base ring than the domain:

```

sage: Y = CombinatorialFreeModule(QQ, [3,4]); y = Y.basis()
sage: phi = X.module_morphism(on_basis = {1: y[3] + 3*y[4], 2: 2*y[3] + 5/
↪2*y[4]}.__getitem__,
.....:                               codomain = Y)
sage: phi.matrix().parent() # todo: not implemented
Full MatrixSpace of 2 by 2 dense matrices over Rational Field

```

This currently does not work because, in this case, the morphism is just in the category of commutative additive groups (i.e. the intersection of the categories of modules over \mathbf{Z} and over \mathbf{Q}):

```

sage: phi.parent().homset_category()
Category of commutative additive semigroups
sage: phi.parent().homset_category() # todo: not implemented
Category of finite dimensional modules with basis over Integer Ring

```

class ParentMethods

Bases: object

annihilator(*S*, *action*=<built-in function mul>, *side*='right', *category*=None)

Return the annihilator of a finite set.

INPUT:

- *S* – a finite set

- `action` – a function (default: `operator.mul`)
- `side` – ‘left’ or ‘right’ (default: ‘right’)
- `category` – a category

Assumptions:

- `action` takes elements of `self` as first argument and elements of `S` as second argument;
- The codomain is any vector space, and `action` is linear on its first argument; typically it is bilinear;
- If `side` is ‘left’, this is reversed.

OUTPUT:

The subspace of the elements x of `self` such that $\text{action}(x, s) = \mathbf{0}$ for all $s \in S$. If `side` is ‘left’ replace the above equation by $\text{action}(s, x) = \mathbf{0}$.

If `self` is a ring, `action` an action of `self` on a module M and S is a subset of M , we recover the [Wikipedia article Annihilator_%28ring_theory%29](#). Similarly this can be used to compute torsion or orthogonals.

See also:

`annihilator_basis()` for lots of examples.

EXAMPLES:

```
sage: F = FiniteDimensionalAlgebrasWithBasis(QQ).example(); F
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: x,y,a,b = F.basis()
sage: A = F.annihilator([a + 3*b + 2*y]); A
Free module generated by {0} over Rational Field
sage: [b.lift() for b in A.basis()]
[-1/2*a - 3/2*b + x]
```

The category can be used to specify other properties of this subspace, like that this is a subalgebra:

```
sage: center = F.annihilator(F.basis(), F.bracket,
.....:                      category=Algebras(QQ).Subobjects())
sage: (e,) = center.basis()
sage: e.lift()
x + y
sage: e * e == e
True
```

Taking `annihilator` is order reversing for inclusion:

```
sage: A = F.annihilator([]); A.rename("A")
sage: Ax = F.annihilator([x]); Ax.rename("Ax")
sage: Ay = F.annihilator([y]); Ay.rename("Ay")
sage: Axy = F.annihilator([x,y]); Axy.rename("Axy")
sage: P = Poset(([A, Ax, Ay, Axy], attrcall("is_submodule")))
sage: sorted(P.cover_relations(), key=str)
[[Ax, A], [Axy, Ax], [Axy, Ay], [Ay, A]]
```

`annihilator_basis(S, action=<built-in function mul>, side='right')`

Return a basis of the annihilator of a finite set of elements.

INPUT:

- `S` – a finite set of objects
- `action` – a function (default: `operator.mul`)

• `side` – ‘left’ or ‘right’ (default: ‘right’): on which side of `self` the elements of S acts. See `annihilator()` for the assumptions and definition of the annihilator.

EXAMPLES:

By default, the action is the standard $*$ operation. So our first example is about an algebra:

```
sage: F = FiniteDimensionalAlgebrasWithBasis(QQ).example(); F
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: x,y,a,b = F.basis()
```

In this algebra, multiplication on the right by x annihilates all basis elements but x :

```
sage: x*x, y*x, a*x, b*x
(x, 0, 0, 0)
```

So the annihilator is the subspace spanned by y , a , and b :

```
sage: F.annihilator_basis([x])
(y, a, b)
```

The same holds for a and b :

```
sage: x*a, y*a, a*a, b*a
(a, 0, 0, 0)
sage: F.annihilator_basis([a])
(y, a, b)
```

On the other hand, y annihilates only x :

```
sage: F.annihilator_basis([y])
(x,)
```

Here is a non trivial annihilator:

```
sage: F.annihilator_basis([a + 3*b + 2*y])
(-1/2*a - 3/2*b + x,)
```

Let’s check it:

```
sage: (-1/2*a - 3/2*b + x) * (a + 3*b + 2*y)
0
```

Doing the same calculations on the left exchanges the roles of x and y :

```
sage: F.annihilator_basis([y], side="left")
(x, a, b)
sage: F.annihilator_basis([a], side="left")
(x, a, b)
sage: F.annihilator_basis([b], side="left")
(x, a, b)
sage: F.annihilator_basis([x], side="left")
(y,)
```

(continues on next page)

(continued from previous page)

```
sage: F.annihilator_basis([a+3*b+2*x], side="left")
(-1/2*a - 3/2*b + y,)
```

By specifying an inner product, this method can be used to compute the orthogonal of a subspace:

```
sage: x,y,a,b = F.basis()
sage: def scalar(u,v): return vector([sum(u[i]*v[i] for i in F.basis().
↳keys())])
sage: F.annihilator_basis([x+y, a+b], scalar)
(x - y, a - b)
```

By specifying the standard Lie bracket as action, one can compute the commutator of a subspace of F :

```
sage: F.annihilator_basis([a+b], action=F.bracket)
(x + y, a, b)
```

In particular one can compute a basis of the center of the algebra. In our example, it is reduced to the identity:

```
sage: F.annihilator_basis(F.algebra_generators(), action=F.bracket)
(x + y,)
```

But see also [FiniteDimensionalAlgebrasWithBasis.ParentMethods.center_basis\(\)](#).

echelon_form(elements, row_reduced=False, order=None)

Return a basis in echelon form of the subspace spanned by a finite set of elements.

INPUT:

- `elements` – a list or finite iterable of elements of `self`
- `row_reduced` – (default: `False`) whether to compute the basis for the row reduced echelon form
- `order` – (optional) either something that can be converted into a tuple or a key function

OUTPUT:

A list of elements of `self` whose expressions as vectors form a matrix in echelon form. If `base_ring` is specified, then the calculation is achieved in this base ring.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x")
sage: x = X.basis()
sage: V = X.echelon_form([x[0]-x[1], x[0]-x[2],x[1]-x[2]]); V
[x[0] - x[2], x[1] - x[2]]
sage: matrix(list(map(vector, V)))
[ 1  0 -1]
[ 0  1 -1]
```

```
sage: F = CombinatorialFreeModule(ZZ, [1,2,3,4])
sage: B = F.basis()
sage: elements = [B[1]-17*B[2]+6*B[3], B[1]-17*B[2]+B[4]]
sage: F.echelon_form(elements)
[B[1] - 17*B[2] + B[4], 6*B[3] - B[4]]
```

```
sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: a,b,c = F.basis()
sage: F.echelon_form([8*a+b+10*c, -3*a+b-c, a-b-c])
[B['a'] + B['c'], B['b'] + 2*B['c']]
```

```
sage: R.<x,y> = QQ[]
sage: C = CombinatorialFreeModule(R, range(3), prefix='x')
sage: x = C.basis()
sage: C.echelon_form([x[0] - x[1], 2*x[1] - 2*x[2], x[0] - x[2]])
[x[0] - x[2], x[1] - x[2]]
```

```
sage: M = MatrixSpace(QQ, 3, 3)
sage: A = M([[0, 0, 2], [0, 0, 0], [0, 0, 0]])
sage: M.echelon_form([A, A])
[
[0 0 1]
[0 0 0]
[0 0 0]
]
```

from_vector(*vector*, *order=None*)

Build an element of *self* from a vector.

EXAMPLES:

```
sage: p_mult = matrix([[0,0,0],[0,0,-1],[0,0,0]])
sage: q_mult = matrix([[0,0,1],[0,0,0],[0,0,0]])
sage: A = algebras.FiniteDimensional(QQ, [p_mult, q_mult, matrix(QQ,3,3)],
....:                               'p,q,z')
sage: A.from_vector(vector([1,0,2]))
p + 2*z
```

gens()

Return the generators of *self*.

OUTPUT:

A tuple containing the basis elements of *self*.

EXAMPLES:

```
sage: F = CombinatorialFreeModule(ZZ, ['a', 'b', 'c'])
sage: F.gens()
(B['a'], B['b'], B['c'])
```

invariant_module(*S*, *action=<built-in function mul>*, *action_on_basis=None*, *side='left'*, ***kwargs*)

Return the submodule of *self* invariant under the action of *S*.

For a semigroup *S* acting on a module *M*, the invariant submodule is given by

$$M^S = \{m \in M : s \cdot m = m, \forall s \in S\}.$$

INPUT:

- *S* – a finitely-generated semigroup
- *action* – a function (default: `operator.mul`)
- *side* – 'left' or 'right' (default: 'right'); which side of *self* the elements of *S* acts

- `action_on_basis` – (optional) define the action of `S` on the basis of `self`

OUTPUT:

- `FiniteDimensionalInvariantModule`

EXAMPLES:

We build the invariant module of the permutation representation of the symmetric group:

```
sage: G = SymmetricGroup(3); G.rename('S3')
sage: M = FreeModule(ZZ, [1,2,3], prefix='M'); M.rename('M')
sage: action = lambda g, x: M.term(g(x))
sage: I = M.invariant_module(G, action_on_basis=action); I
(S3)-invariant submodule of M
sage: I.basis()
Finite family {0: B[0]}
sage: [I.lift(b) for b in I.basis()]
[M[1] + M[2] + M[3]]

sage: G.rename(); M.rename() # reset the names
```

We can construct the invariant module of any module that has an action of S . In this example, we consider the dihedral group $G = D_4$ and the subgroup $H < G$ of all rotations. We construct the H -invariant module of the group algebra $\mathbf{Q}[G]$:

```
sage: G = groups.permutation.Dihedral(4)
sage: H = G.subgroup(G.gen(0))
sage: H
Subgroup generated by [(1,2,3,4)] of (Dihedral group of order 8 as a
↳permutation group)
sage: H.cardinality()
4
sage: A = G.algebra(QQ)
sage: I = A.invariant_module(H)
sage: [I.lift(b) for b in I.basis()]
[() + (1,2,3,4) + (1,3)(2,4) + (1,4,3,2),
 (2,4) + (1,2)(3,4) + (1,3) + (1,4)(2,3)]
sage: all(h * I.lift(b) == I.lift(b) for b in I.basis() for h in H)
True
```

twisted_invariant_module(G , χ , $\text{action}=\langle \text{built-in function mul} \rangle$, $\text{action_on_basis}=\text{None}$, $\text{side}=\text{'left'}$, $**\text{kwards}$)

Create the isotypic component of the action of G on `self` with irreducible character given by χ .

INPUT:

- G – a finitely-generated group
- χ – a list/tuple of character values or an instance of `ClassFunction_gap`
- action – a function (default: `operator.mul`)
- action_on_basis – (optional) define the action of g on the basis of `self`
- side – 'left' or 'right' (default: 'right'); which side of `self` the elements of S acts

OUTPUT:

- `FiniteDimensionalTwistedInvariantModule`

EXAMPLES:

```
sage: M = CombinatorialFreeModule(QQ, [1,2,3])
sage: G = SymmetricGroup(3)
sage: def action(g,x): return(M.term(g(x))) # permute coordinates
```

(continues on next page)

(continued from previous page)

```
sage: T = M.twisted_invariant_module(G, [2,0,-1], action_on_basis=action)
sage: import __main__; __main__.action = action
sage: TestSuite(T).run()
```

3.54 Finite Dimensional Nilpotent Lie Algebras With Basis

AUTHORS:

- Eero Hakavuori (2018-08-16): initial version

class `sage.categories.finite_dimensional_nilpotent_lie_algebras_with_basis.FiniteDimensionalNilpotentLi`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

Category of finite dimensional nilpotent Lie algebras with basis.

class `ParentMethods`

Bases: `object`

is_nilpotent()

Return True since self is nilpotent.

EXAMPLES:

```
sage: L = LieAlgebra(QQ, {'x','y': {'z': 1}}, nilpotent=True)
sage: L.is_nilpotent()
True
```

lie_group(*name='G', **kws*)

Return the Lie group associated to self.

INPUT:

- *name* – string (default: 'G'); the name (symbol) given to the Lie group

EXAMPLES:

We define the Heisenberg group:

```
sage: L = lie_algebras.Heisenberg(QQ, 1)
sage: G = L.lie_group('G'); G
Lie group G of Heisenberg algebra of rank 1 over Rational Field
```

We test multiplying elements of the group:

```
sage: p,q,z = L.basis()
sage: g = G.exp(p); g
exp(p1)
sage: h = G.exp(q); h
exp(q1)
sage: g*h
exp(p1 + q1 + 1/2*z)
```

We extend an element of the Lie algebra to a left-invariant vector field:

```
sage: X = G.left_invariant_extension(2*p + 3*q, name='X'); X
Vector field X on the Lie group G of Heisenberg algebra of rank 1 over
↳Rational Field
```

(continues on next page)

(continued from previous page)

```
sage: X.at(G.one()).display()
X = 2 ∂/∂x_0 + 3 ∂/∂x_1
sage: X.display()
X = 2 ∂/∂x_0 + 3 ∂/∂x_1 + (3/2*x_0 - x_1) ∂/∂x_2
```

See also:[NilpotentLieGroup](#)**step()**Return the nilpotency step of `self`.

EXAMPLES:

```
sage: L = LieAlgebra(QQ, {'X','Y': {'Z': 1}}, nilpotent=True)
sage: L.step()
2
sage: sc = {'X','Y': {'Z': 1}, ('X','Z'): {'W': 1}}
sage: LieAlgebra(QQ, sc, nilpotent=True).step()
3
```

3.55 Finite dimensional semisimple algebras with basis

class `sage.categories.finite_dimensional_semisimple_algebras_with_basis.FiniteDimensionalSemisimpleAlgebrasWithBasis`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of finite dimensional semisimple algebras with a distinguished basis

EXAMPLES:

```
sage: from sage.categories.finite_dimensional_semisimple_algebras_with_basis import FiniteDimensionalSemisimpleAlgebrasWithBasis
sage: C = FiniteDimensionalSemisimpleAlgebrasWithBasis(QQ); C
Category of finite dimensional semisimple algebras with basis over Rational Field
```

This category is best constructed as:

```
sage: D = Algebras(QQ).Semisimple().FiniteDimensional().WithBasis(); D
Category of finite dimensional semisimple algebras with basis over Rational Field
sage: D is C
True
```

class `Commutative(base_category)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

class `ParentMethods`

Bases: `object`

central_orthogonal_idempotents()

Return the central orthogonal idempotents of this semisimple commutative algebra.

Those idempotents form a maximal decomposition of the identity into primitive orthogonal idempotents.

OUTPUT:

A list of orthogonal idempotents of `self`.

EXAMPLES:

```
sage: A4 = SymmetricGroup(4).algebra(QQ)
sage: Z4 = A4.center()
sage: idempotents = Z4.central_orthogonal_idempotents()
sage: idempotents
(1/24*B[0] + 1/24*B[1] + 1/24*B[2] + 1/24*B[3] + 1/24*B[4],
 3/8*B[0] + 1/8*B[1] - 1/8*B[2] - 1/8*B[4],
 1/6*B[0] + 1/6*B[2] - 1/12*B[3],
 3/8*B[0] - 1/8*B[1] - 1/8*B[2] + 1/8*B[4],
 1/24*B[0] - 1/24*B[1] + 1/24*B[2] + 1/24*B[3] - 1/24*B[4])
```

Lifting those idempotents from the center, we recognize among them the sum and alternating sum of all permutations:

```
sage: [e.lift() for e in idempotents]
[1/24*(() + 1/24*(3,4) + 1/24*(2,3) + 1/24*(2,3,4) + 1/24*(2,4,3)
 + 1/24*(2,4) + 1/24*(1,2) + 1/24*(1,2)(3,4) + 1/24*(1,2,3)
 + 1/24*(1,2,3,4) + 1/24*(1,2,4,3) + 1/24*(1,2,4) + 1/24*(1,3,2)
 + 1/24*(1,3,4,2) + 1/24*(1,3) + 1/24*(1,3,4) + 1/24*(1,3)(2,4)
 + 1/24*(1,3,2,4) + 1/24*(1,4,3,2) + 1/24*(1,4,2) + 1/24*(1,4,3)
 + 1/24*(1,4) + 1/24*(1,4,2,3) + 1/24*(1,4)(2,3)],
 ...,
 1/24*(() - 1/24*(3,4) - 1/24*(2,3) + 1/24*(2,3,4) + 1/24*(2,4,3)
 - 1/24*(2,4) - 1/24*(1,2) + 1/24*(1,2)(3,4) + 1/24*(1,2,3)
 - 1/24*(1,2,3,4) - 1/24*(1,2,4,3) + 1/24*(1,2,4) + 1/24*(1,3,2)
 - 1/24*(1,3,4,2) - 1/24*(1,3) + 1/24*(1,3,4) + 1/24*(1,3)(2,4)
 - 1/24*(1,3,2,4) - 1/24*(1,4,3,2) + 1/24*(1,4,2) + 1/24*(1,4,3)
 - 1/24*(1,4) - 1/24*(1,4,2,3) + 1/24*(1,4)(2,3)]
```

We check that they indeed form a decomposition of the identity of Z_4 into orthogonal idempotents:

```
sage: Z4.is_identity_decomposition_into_orthogonal_
      ↪ idempotents(idempotents)
True
```

class ParentMethods

Bases: object

central_orthogonal_idempotents()

Return a maximal list of central orthogonal idempotents of `self`.

Central orthogonal idempotents of an algebra A are idempotents (e_1, \dots, e_n) in the center of A such that $e_i e_j = 0$ whenever $i \neq j$.

With the maximality condition, they sum up to 1 and are uniquely determined (up to order).

EXAMPLES:

For the algebra of the (abelian) alternating group A_3 , we recover three idempotents corresponding to the three one-dimensional representations V_i on which $(1, 2, 3)$ acts on V_i as multiplication by the i -th power of a cube root of unity:

```
sage: R = CyclotomicField(3)
sage: A3 = AlternatingGroup(3).algebra(R)
```

(continues on next page)

(continued from previous page)

```

sage: idempotents = A3.central_orthogonal_idempotents()
sage: idempotents
(1/3*() + 1/3*(1,2,3) + 1/3*(1,3,2),
 1/3*() - (1/3*zeta3+1/3)*(1,2,3) - (-1/3*zeta3)*(1,3,2),
 1/3*() - (-1/3*zeta3)*(1,2,3) - (1/3*zeta3+1/3)*(1,3,2))
sage: A3.is_identity_decomposition_into_orthogonal_idempotents(idempotents)
True

```

For the semisimple quotient of a quiver algebra, we recover the vertices of the quiver:

```

sage: A = FiniteDimensionalAlgebrasWithBasis(QQ).example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver (containing
the arrows a:x->y and b:x->y) over Rational Field
sage: Aquo = A.semisimple_quotient()
sage: Aquo.central_orthogonal_idempotents()
(B['x'], B['y'])

```

radical_basis (**keywords)

Return a basis of the Jacobson radical of this algebra.

- **keywords** – for compatibility; ignored.

OUTPUT: the empty list since this algebra is semisimple.

EXAMPLES:

```

sage: A = SymmetricGroup(4).algebra(QQ)
sage: A.radical_basis()
()

```

3.56 Finite Enumerated Sets

class `sage.categories.finite_enumerated_sets.FiniteEnumeratedSets`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of finite enumerated sets

EXAMPLES:

```

sage: FiniteEnumeratedSets()
Category of finite enumerated sets
sage: FiniteEnumeratedSets().super_categories()
[Category of enumerated sets, Category of finite sets]
sage: FiniteEnumeratedSets().all_super_categories()
[Category of finite enumerated sets,
 Category of enumerated sets,
 Category of finite sets,
 Category of sets,
 Category of sets with partial maps,
 Category of objects]

```

Todo: `sage.combinat.debruijn_sequence.DeBruijnSequences` should not inherit from this class. If

that is solved, then `FiniteEnumeratedSets` shall be turned into a subclass of `Category_singleton`.

class CartesianProducts(*category*, *args)

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

class ParentMethods

Bases: object

cardinality()

Return the cardinality of self.

EXAMPLES:

```
sage: E = FiniteEnumeratedSet([1,2,3])
sage: C = cartesian_product([E, SymmetricGroup(4)])
sage: C.cardinality()
72

sage: E = FiniteEnumeratedSet([])
sage: C = cartesian_product([E, ZZ, QQ])
sage: C.cardinality()
0

sage: C = cartesian_product([ZZ, QQ])
sage: C.cardinality()
+Infinity

sage: cartesian_product([GF(5), Permutations(10)]).cardinality()
18144000
sage: cartesian_product([GF(71)]*20).cardinality() == 71**20
True
```

last()

Return the last element

EXAMPLES:

```
sage: C = cartesian_product([Zmod(42), Partitions(10), IntegerRange(5)])
sage: C.last()
(41, [1, 1, 1, 1, 1, 1, 1, 1, 1, 1], 4)
```

random_element(*args)

Return a random element of this Cartesian product.

The extra arguments are passed down to each of the factors of the Cartesian product.

EXAMPLES:

```
sage: C = cartesian_product([Permutations(10)]*5)
sage: C.random_element() # random
([2, 9, 4, 7, 1, 8, 6, 10, 5, 3],
 [8, 6, 5, 7, 1, 4, 9, 3, 10, 2],
 [5, 10, 3, 8, 2, 9, 1, 4, 7, 6],
 [9, 6, 10, 3, 2, 1, 5, 8, 7, 4],
 [8, 5, 2, 9, 10, 3, 7, 1, 4, 6])
```

(continues on next page)

(continued from previous page)

```

sage: C = cartesian_product([ZZ]*10)
sage: c1 = C.random_element()
sage: c1
# random
(3, 1, 4, 1, 1, -3, 0, -4, -17, 2)
sage: c2 = C.random_element(4,7)
sage: c2
# random
(6, 5, 6, 4, 5, 6, 6, 4, 5, 5)
sage: all(4 <= i < 7 for i in c2)
True

```

rank(*x*)

Return the rank of an element of this Cartesian product.

The *rank* of *x* is its position in the enumeration. It is an integer between 0 and *n*-1 where *n* is the cardinality of this set.

See also:

- [EnumeratedSets.ParentMethods.rank\(\)](#)
- [unrank\(\)](#)

EXAMPLES:

```

sage: C = cartesian_product([GF(2), GF(11), GF(7)])
sage: C.rank(C((1,2,5)))
96
sage: C.rank(C((0,0,0)))
0

sage: for c in C: print(C.rank(c))
0
1
2
3
4
5
...
150
151
152
153

sage: F1 = FiniteEnumeratedSet('abcdefgh')
sage: F2 = IntegerRange(250)
sage: F3 = Partitions(20)
sage: C = cartesian_product([F1, F2, F3])
sage: c = C(('a', 86, [7,5,4,4]))
sage: C.rank(c)
54213
sage: C.unrank(54213)
('a', 86, [7, 5, 4, 4])

```

unrank(*i*)

Return the *i*-th element of this Cartesian product.

INPUT:

- i – integer between 0 and $n-1$ where n is the cardinality of this set.

See also:

- [EnumeratedSets.ParentMethods.unrank\(\)](#)
- [rank\(\)](#)

EXAMPLES:

```
sage: C = cartesian_product([GF(3), GF(11), GF(7), GF(5)])
sage: c = C.unrank(123); c
(0, 3, 3, 3)
sage: C.rank(c)
123

sage: c = C.unrank(857); c
(2, 2, 3, 2)
sage: C.rank(c)
857

sage: C.unrank(2500)
Traceback (most recent call last):
...
IndexError: index i (=2) is greater than the cardinality
```

extra_super_categories()

A Cartesian product of finite enumerated sets is a finite enumerated set.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().CartesianProducts()
sage: C.extra_super_categories()
[Category of finite enumerated sets]
```

class IsomorphicObjects(*category, *args*)

Bases: [sage.categories.isomorphic_objects.IsomorphicObjectsCategory](#)

class ParentMethods

Bases: object

cardinality()

Returns the cardinality of `self` which is the same as that of the ambient set `self` is isomorphic to.

EXAMPLES:

```
sage: A = FiniteEnumeratedSets().IsomorphicObjects().example(); A
The image by some isomorphism of An example of a finite enumerated set:
↦ {1, 2, 3}
sage: A.cardinality()
3
```

example()

Returns an example of isomorphic object of a finite enumerated set, as per [Category.example](#).

EXAMPLES:

```
sage: FiniteEnumeratedSets().IsomorphicObjects().example()
The image by some isomorphism of An example of a finite enumerated set: {1,
↪2,3}
```

class ParentMethods

Bases: object

cardinality(*ignored_args, **ignored_kwds)Return the cardinality of `self`.

This brute force implementation of `cardinality()` iterates through the elements of `self` to count them.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example(); C
An example of a finite enumerated set: {1,2,3}
sage: C._cardinality_from_iterator()
3
```

iterator_range(start=None, stop=None, step=None)Iterate over the range of elements of `self` starting at `start`, ending at `stop`, and stepping by `step`.**See also:**`unrank()`, `unrank_range()`

EXAMPLES:

```
sage: F = FiniteEnumeratedSet([1,2,3])
sage: list(F.iterator_range(1))
[2, 3]
sage: list(F.iterator_range(stop=2))
[1, 2]
sage: list(F.iterator_range(stop=2, step=2))
[1]
sage: list(F.iterator_range(start=1, step=2))
[2]
sage: list(F.iterator_range(start=1, stop=2))
[2]
sage: list(F.iterator_range(start=0, stop=1))
[1]
sage: list(F.iterator_range(start=0, stop=3, step=2))
[1, 3]
sage: list(F.iterator_range(stop=-1))
[1, 2]

sage: F = FiniteEnumeratedSet([1,2,3,4])
sage: list(F.iterator_range(start=1, stop=3))
[2, 3]
sage: list(F.iterator_range(stop=10))
[1, 2, 3, 4]
```

last()The last element of `self`.`self.last()` returns the last element of `self`.

This is the default (brute force) implementation from the category `FiniteEnumeratedSet()` which can be used when the method `__iter__` is provided. Its complexity is $O(n)$ where n is the size of `self`.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: C.last()
3
sage: C._last_from_iterator()
3
```

`list()`

Return a list of the elements of `self`.

The elements of set `x` is created and cached on the first call of `x.list()`. Then each call of `x.list()` returns a new list from the cached result. Thus in looping, it may be better to do `for e in x:`, not `for e in x.list():`.

See also:

`_list_from_iterator()`, `_cardinality_from_list()`, `_iterator_from_list()`, and `_unrank_from_list()`

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: C.list()
[1, 2, 3]
```

`random_element()`

A random element in `self`.

`self.random_element()` returns a random element in `self` with uniform probability.

This is the default implementation from the category `EnumeratedSet()` which uses the method `unrank`.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: n = C.random_element()
sage: n in C
True

sage: n = C._random_element_from_unrank()
sage: n in C
True
```

TODO: implement `_test_random` which checks uniformness

`unrank_range(start=None, stop=None, step=None)`

Return the range of elements of `self` starting at `start`, ending at `stop`, and stepping by `step`.

See also `unrank()`.

EXAMPLES:

```

sage: F = FiniteEnumeratedSet([1,2,3])
sage: F.unrank_range(1)
[2, 3]
sage: F.unrank_range(stop=2)
[1, 2]
sage: F.unrank_range(stop=2, step=2)
[1]
sage: F.unrank_range(start=1, step=2)
[2]
sage: F.unrank_range(stop=-1)
[1, 2]

sage: F = FiniteEnumeratedSet([1,2,3,4])
sage: F.unrank_range(stop=10)
[1, 2, 3, 4]

```

3.57 Finite fields

class `sage.categories.finite_fields.FiniteFields`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of finite fields.

EXAMPLES:

```

sage: K = FiniteFields(); K
Category of finite enumerated fields

```

A finite field is a finite monoid with the structure of a field; it is currently assumed to be enumerated:

```

sage: K.super_categories()
[Category of fields,
 Category of finite commutative rings,
 Category of finite enumerated sets]

```

Some examples of membership testing and coercion:

```

sage: FiniteField(17) in K
True
sage: RationalField() in K
False
sage: K(RationalField())
Traceback (most recent call last):
...
TypeError: unable to canonically associate a finite field to Rational Field

```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

extra_super_categories()

Any finite field is assumed to be endowed with an enumeration.

3.58 Finite groups

class `sage.categories.finite_groups.FiniteGroups`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of finite (multiplicative) groups.

EXAMPLES:

```
sage: C = FiniteGroups(); C
Category of finite groups
sage: C.super_categories()
[Category of finite monoids, Category of groups]
sage: C.example()
General Linear Group of degree 2 over Finite Field of size 3
```

class `Algebras`(*category, *args*)

Bases: `sage.categories.algebra_functor.AlgebrasCategory`

class `ParentMethods`

Bases: `object`

extra_super_categories()

Implement Maschke's theorem.

In characteristic 0 all finite group algebras are semisimple.

EXAMPLES:

```
sage: FiniteGroups().Algebras(QQ).is_subcategory(Algebras(QQ).Semisimple())
True
sage: FiniteGroups().Algebras(FiniteField(7)).is_
↳subcategory(Algebras(FiniteField(7)).Semisimple())
False
sage: FiniteGroups().Algebras(ZZ).is_subcategory(Algebras(ZZ).Semisimple())
False
sage: FiniteGroups().Algebras(Fields()).is_subcategory(Algebras(Fields()).
↳Semisimple())
False

sage: Cat = CommutativeAdditiveGroups().Finite()
sage: Cat.Algebras(QQ).is_subcategory(Algebras(QQ).Semisimple())
True
sage: Cat.Algebras(GF(7)).is_subcategory(Algebras(GF(7)).Semisimple())
False
sage: Cat.Algebras(ZZ).is_subcategory(Algebras(ZZ).Semisimple())
False
sage: Cat.Algebras(Fields()).is_subcategory(Algebras(Fields()).Semisimple())
False
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

cardinality()

Returns the cardinality of `self`, as per `EnumeratedSets.ParentMethods.cardinality()`.

This default implementation calls `order()` if available, and otherwise resorts to `_cardinality_from_iterator()`. This is for backward compatibility only. Finite groups should override this method instead of `order()`.

EXAMPLES:

We need to use a finite group which uses this default implementation of cardinality:

```
sage: G = groups.misc.SemimonomialTransformation(GF(5), 3); G
Semimonomial transformation group over Finite Field of size 5 of degree 3
sage: G.cardinality.__module__
'sage.categories.finite_groups'
sage: G.cardinality()
384
```

cayley_graph_disabled(*connecting_set=None*)

AUTHORS:

- Bobby Moretti (2007-08-10)
- Robert Miller (2008-05-01): editing

conjugacy_classes()

Return a list with all the conjugacy classes of the group.

This will eventually be a fall-back method for groups not defined over GAP. Right now just raises a `NotImplementedError`, until we include a non-GAP way of listing the conjugacy classes representatives.

EXAMPLES:

```
sage: from sage.groups.group import FiniteGroup
sage: G = FiniteGroup()
sage: G.conjugacy_classes()
Traceback (most recent call last):
...
NotImplementedError: Listing the conjugacy classes for group <sage.groups.
↪group.FiniteGroup object at ...> is not implemented
```

conjugacy_classes_representatives()

Return a list of the conjugacy classes representatives of the group.

EXAMPLES:

```
sage: G = SymmetricGroup(3)
sage: G.conjugacy_classes_representatives()
[(), (1,2), (1,2,3)]
```

monoid_generators()

Return monoid generators for self.

For finite groups, the group generators are also monoid generators. Hence, this default implementation calls `group_generators()`.

EXAMPLES:

```
sage: A = AlternatingGroup(4)
sage: A.monoid_generators()
Family ((2,3,4), (1,2,3))
```


semigroup_generators()

Returns semigroup generators for self.

For finite groups, the group generators are also semigroup generators. Hence, this default implementation calls `group_generators()`.

EXAMPLES:

```
sage: A = AlternatingGroup(4)
sage: A.semigroup_generators()
Family ((2,3,4), (1,2,3))
```

some_elements()

Return some elements of self.

EXAMPLES:

```
sage: A = AlternatingGroup(4)
sage: A.some_elements()
Family ((2,3,4), (1,2,3))
```

example()

Return an example of finite group, as per `Category.example()`.

EXAMPLES:

```
sage: G = FiniteGroups().example(); G
General Linear Group of degree 2 over Finite Field of size 3
```

3.59 Finite lattice posets

class `sage.categories.finite_lattice_posets.FiniteLatticePosets`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of finite lattices, i.e. finite partially ordered sets which are also lattices.

EXAMPLES:

```
sage: FiniteLatticePosets()
Category of finite lattice posets
sage: FiniteLatticePosets().super_categories()
[Category of lattice posets, Category of finite posets]
sage: FiniteLatticePosets().example()
NotImplemented
```

See also:

`FinitePosets`, `LatticePosets`, `FiniteLatticePoset`

class `ParentMethods`

Bases: `object`

irreducibles_poset()

Return the poset of meet- or join-irreducibles of the lattice.

A *join-irreducible* element of a lattice is an element with exactly one lower cover. Dually a *meet-irreducible* element has exactly one upper cover.

This is the smallest poset with completion by cuts being isomorphic to the lattice. As a special case this returns one-element poset from one-element lattice.

See also:

`completion_by_cuts()`.

EXAMPLES:

```
sage: L = LatticePoset({1: [2, 3, 4], 2: [5, 6], 3: [5],
.....:                    4: [6], 5: [9, 7], 6: [9, 8], 7: [10],
.....:                    8: [10], 9: [10], 10: [11]})
sage: L_ = L.irreducibles_poset()
sage: sorted(L_)
[2, 3, 4, 7, 8, 9, 10, 11]
sage: L_.completion_by_cuts().is_isomorphic(L)
True
```

is_lattice_morphism(*f*, *codomain*)

Return whether *f* is a morphism of posets from *self* to *codomain*.

A map $f : P \rightarrow Q$ is a poset morphism if

$$x \leq y \Rightarrow f(x) \leq f(y)$$

for all $x, y \in P$.

INPUT:

- *f* – a function from *self* to *codomain*
- *codomain* – a lattice

EXAMPLES:

We build the boolean lattice of $\{2, 2, 3\}$ and the lattice of divisors of 60, and check that the map $b \mapsto 5 \prod_{x \in b} x$ is a morphism of lattices:

```
sage: D = LatticePoset((divisors(60), attrcall("divides")))
sage: B = LatticePoset((Subsets([2,2,3]), attrcall("issubset")))
sage: def f(b): return D(5*prod(b))
sage: B.is_lattice_morphism(f, D)
True
```

We construct the boolean lattice B_2 :

```
sage: B = posets.BooleanLattice(2)
sage: B.cover_relations()
[[0, 1], [0, 2], [1, 3], [2, 3]]
```

And the same lattice with new top and bottom elements numbered respectively -1 and 3 :

```
sage: L = LatticePoset(DiGraph({-1:[0], 0:[1,2], 1:[3], 2:[3],3:[4]}))
sage: L.cover_relations()
[[-1, 0], [0, 1], [0, 2], [1, 3], [2, 3], [3, 4]]

sage: f = { B(0): L(0), B(1): L(1), B(2): L(2), B(3): L(3) }.__getitem__
sage: B.is_lattice_morphism(f, L)
True
```

(continues on next page)

(continued from previous page)

```

sage: f = { B(0): L(-1), B(1): L(1), B(2): L(2), B(3): L(3) }.__getitem__
sage: B.is_lattice_morphism(f, L)
False

sage: f = { B(0): L(0), B(1): L(1), B(2): L(2), B(3): L(4) }.__getitem__
sage: B.is_lattice_morphism(f, L)
False

```

See also:`is_poset_morphism()`**join_irreducibles()**

Return the join-irreducible elements of this finite lattice.

A *join-irreducible element* of `self` is an element x that is not minimal and that can not be written as the join of two elements different from x .

EXAMPLES:

```

sage: L = LatticePoset({0:[1,2],1:[3],2:[3,4],3:[5],4:[5]})
sage: L.join_irreducibles()
[1, 2, 4]

```

See also:

- Dual function: `meet_irreducibles()`
- Other: `double_irreducibles()`, `join_irreducibles_poset()`

join_irreducibles_poset()

Return the poset of join-irreducible elements of this finite lattice.

A *join-irreducible element* of `self` is an element x that is not minimal and can not be written as the join of two elements different from x .

EXAMPLES:

```

sage: L = LatticePoset({0:[1,2,3],1:[4],2:[4],3:[4]})
sage: L.join_irreducibles_poset()
Finite poset containing 3 elements

```

See also:

- Dual function: `meet_irreducibles_poset()`
- Other: `join_irreducibles()`

meet_irreducibles()

Return the meet-irreducible elements of this finite lattice.

A *meet-irreducible element* of `self` is an element x that is not maximal and that can not be written as the meet of two elements different from x .

EXAMPLES:

```

sage: L = LatticePoset({0:[1,2],1:[3],2:[3,4],3:[5],4:[5]})
sage: L.meet_irreducibles()
[1, 3, 4]

```

See also:

- Dual function: `join_irreducibles()`
- Other: `double_irreducibles()`, `meet_irreducibles_poset()`

meet_irreducibles_poset()

Return the poset of join-irreducible elements of this finite lattice.

A *meet-irreducible element* of `self` is an element x that is not maximal and can not be written as the meet of two elements different from x .

EXAMPLES:

```
sage: L = LatticePoset({0:[1,2,3],1:[4],2:[4],3:[4]})
sage: L.join_irreducibles_poset()
Finite poset containing 3 elements
```

See also:

- Dual function: `join_irreducibles_poset()`
- Other: `meet_irreducibles()`

3.60 Finite monoids

class `sage.categories.finite_monoids.FiniteMonoids`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of finite (multiplicative) *monoids*.

A finite monoid is a *finite sets* endowed with an associative unital binary operation $*$.

EXAMPLES:

```
sage: FiniteMonoids()
Category of finite monoids
sage: FiniteMonoids().super_categories()
[Category of monoids, Category of finite semigroups]
```

class `ElementMethods`

Bases: `object`

pseudo_order()

Returns the pair $[k, j]$ with k minimal and $0 \leq j < k$ such that `self^k == self^j`.

Note that j is uniquely determined.

EXAMPLES:

```
sage: M = FiniteMonoids().example(); M
An example of a finite multiplicative monoid: the integers modulo 12

sage: x = M(2)
sage: [ x^i for i in range(7) ]
[1, 2, 4, 8, 4, 8, 4]
sage: x.pseudo_order()
[4, 2]

sage: x = M(3)
sage: [ x^i for i in range(7) ]
```

(continues on next page)

(continued from previous page)

```
[1, 3, 9, 3, 9, 3, 9]
sage: x.pseudo_order()
[3, 1]

sage: x = M(4)
sage: [ x^i for i in range(7) ]
[1, 4, 4, 4, 4, 4, 4]
sage: x.pseudo_order()
[2, 1]

sage: x = M(5)
sage: [ x^i for i in range(7) ]
[1, 5, 1, 5, 1, 5, 1]
sage: x.pseudo_order()
[2, 0]
```

TODO: more appropriate name? see, for example, Jean-Eric Pin's lecture notes on semigroups.

class ParentMethods

Bases: object

nerve()

The nerve (classifying space) of this monoid.

OUTPUT: the nerve BG (if G denotes this monoid), as a simplicial set. The k -dimensional simplices of this object are indexed by products of k elements in the monoid:

$$a_1 * a_2 * \cdots * a_k$$

The 0th face of this is obtained by deleting a_1 , and the k -th face is obtained by deleting a_k . The other faces are obtained by multiplying elements: the 1st face is

$$(a_1 * a_2) * \cdots * a_k$$

and so on. See [Wikipedia article Nerve_\(category_theory\)](#), which describes the construction of the nerve as a simplicial set.

A simplex in this simplicial set will be degenerate if in the corresponding product of k elements, one of those elements is the identity. So we only need to keep track of the products of non-identity elements. Similarly, if a product $a_{i-1}a_i$ is the identity element, then the corresponding face of the simplex will be a degenerate simplex.

EXAMPLES:

The nerve (classifying space) of the cyclic group of order 2 is infinite-dimensional real projective space.

```
sage: Sigma2 = groups.permutation.Cyclic(2)
sage: BSigma2 = Sigma2.nerve()
sage: BSigma2.cohomology(4, base_ring=GF(2))
Vector space of dimension 1 over Finite Field of size 2
```

The k -simplices of the nerve are named after the chains of k non-unit elements to be multiplied. The group Σ_2 has two elements, written $()$ (the identity element) and $(1, 2)$ in Sage. So the 1-cells and 2-cells in $B\Sigma_2$ are:

```
sage: BSigma2.n_cells(1)
[(1,2)]
sage: BSigma2.n_cells(2)
[(1,2) * (1,2)]
```

Another construction of the group, with different names for its elements:

```
sage: C2 = groups.misc.MultiplicativeAbelian([2])
sage: BC2 = C2.nerve()
sage: BC2.n_cells(0)
[1]
sage: BC2.n_cells(1)
[f]
sage: BC2.n_cells(2)
[f * f]
```

With mod p coefficients, $B\Sigma_p$ should have its first nonvanishing homology group in dimension p :

```
sage: Sigma3 = groups.permutation.Symmetric(3)
sage: BSigma3 = Sigma3.nerve()
sage: BSigma3.homology(range(4), base_ring=GF(3))
{0: Vector space of dimension 0 over Finite Field of size 3,
1: Vector space of dimension 0 over Finite Field of size 3,
2: Vector space of dimension 0 over Finite Field of size 3,
3: Vector space of dimension 1 over Finite Field of size 3}
```

Note that we can construct the n -skeleton for $B\Sigma_2$ for relatively large values of n , while for $B\Sigma_3$, the complexes get large pretty quickly:

```
sage: Sigma2.nerve().n_skeleton(14)
Simplicial set with 15 non-degenerate simplices

sage: BSigma3 = Sigma3.nerve()
sage: BSigma3.n_skeleton(3)
Simplicial set with 156 non-degenerate simplices
sage: BSigma3.n_skeleton(4)
Simplicial set with 781 non-degenerate simplices
```

Finally, note that the classifying space of the order p cyclic group is smaller than that of the symmetric group on p letters, and its first homology group appears earlier:

```
sage: C3 = groups.misc.MultiplicativeAbelian([3])
sage: list(C3)
[1, f, f^2]
sage: BC3 = C3.nerve()
sage: BC3.n_cells(1)
[f, f^2]
sage: BC3.n_cells(2)
[f * f, f * f^2, f^2 * f, f^2 * f^2]
sage: len(BSigma3.n_cells(2))
25
sage: len(BC3.n_cells(3))
8
```

(continues on next page)

(continued from previous page)

```

sage: len(BSigma3.n_cells(3))
125

sage: BC3.homology(range(5), base_ring=GF(3))
{0: Vector space of dimension 0 over Finite Field of size 3,
 1: Vector space of dimension 1 over Finite Field of size 3,
 2: Vector space of dimension 1 over Finite Field of size 3,
 3: Vector space of dimension 1 over Finite Field of size 3,
 4: Vector space of dimension 1 over Finite Field of size 3}

sage: BC5 = groups.permutation.Cyclic(5).nerve()
sage: BC5.homology(range(5), base_ring=GF(5))
{0: Vector space of dimension 0 over Finite Field of size 5,
 1: Vector space of dimension 1 over Finite Field of size 5,
 2: Vector space of dimension 1 over Finite Field of size 5,
 3: Vector space of dimension 1 over Finite Field of size 5,
 4: Vector space of dimension 1 over Finite Field of size 5}

```

rhodes_radical_congruence (*base_ring=None*)

Return the Rhodes radical congruence of the semigroup.

The Rhodes radical congruence is the congruence induced on S by the map $S \rightarrow kS \rightarrow kS/\text{rad}kS$ with k a field.

INPUT:

- `base_ring` (default: \mathbf{Q}) a field

OUTPUT:

- A list of couples (m, n) with $m \neq n$ in the lexicographic order for the enumeration of the monoid `self`.

EXAMPLES:

```

sage: M = Monoids().Finite().example()
sage: M.rhodes_radical_congruence()
[(0, 6), (2, 8), (4, 10)]
sage: from sage.monoids.hecke_monoid import HeckeMonoid
sage: H3 = HeckeMonoid(SymmetricGroup(3))
sage: H3.repr_element_method(style="reduced")
sage: H3.rhodes_radical_congruence()
[[([1, 2], [2, 1]), ([1, 2], [1, 2, 1]), ([2, 1], [1, 2, 1])]

```

By Maschke's theorem, every group algebra over \mathbf{Q} is semisimple hence the Rhodes radical of a group must be trivial:

```

sage: SymmetricGroup(3).rhodes_radical_congruence()
[]
sage: DihedralGroup(10).rhodes_radical_congruence()
[]

```

REFERENCES:

- [Rho69]

3.61 Finite Permutation Groups

class `sage.categories.finite_permutation_groups.FinitePermutationGroups`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of finite permutation groups, i.e. groups concretely represented as groups of permutations acting on a finite set.

It is currently assumed that any finite permutation group comes endowed with a distinguished finite set of generators (method `group_generators`); this is the case for all the existing implementations in Sage.

EXAMPLES:

```
sage: C = PermutationGroups().Finite(); C
Category of finite enumerated permutation groups
sage: C.super_categories()
[Category of permutation groups,
 Category of finite groups,
 Category of finite finitely generated semigroups]

sage: C.example()
Dihedral group of order 6 as a permutation group
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

cycle_index(*parent=None*)

Return the *cycle index* of `self`.

INPUT:

- `self` - a permutation group G
- `parent` – a free module with basis indexed by partitions, or behave as such, with a `term` and `sum` method (default: the symmetric functions over the rational field in the p basis)

The *cycle index* of a permutation group G ([Wikipedia article Cycle_index](#)) is a gadget counting the elements of G by cycle type, averaged over the group:

$$P = \frac{1}{|G|} \sum_{g \in G} p_{\text{cycle type}(g)}$$

EXAMPLES:

Among the permutations of the symmetric group S_4 , there is the identity, 6 cycles of length 2, 3 products of two cycles of length 2, 8 cycles of length 3, and 6 cycles of length 4:

```
sage: S4 = SymmetricGroup(4)
sage: P = S4.cycle_index()
sage: 24 * P
p[1, 1, 1, 1] + 6*p[2, 1, 1] + 3*p[2, 2] + 8*p[3, 1] + 6*p[4]
```

If $l = (l_1, \dots, l_k)$ is a partition, `|G| P[l]` is the number of elements of G with cycles of length (p_1, \dots, p_k) :

```
sage: 24 * P[ Partition([3,1]) ]
8
```


The cycle index plays an important role in the enumeration of objects modulo the action of a group (Pólya enumeration), via the use of symmetric functions and plethysms. It is therefore encoded as a symmetric function, expressed in the powersum basis:

```
sage: P.parent()
Symmetric Functions over Rational Field in the powersum basis
```

This symmetric function can have some nice properties; for example, for the symmetric group S_n , we get the complete symmetric function h_n :

```
sage: S = SymmetricFunctions(QQ); h = S.h()
sage: h( P )
h[4]
```

Todo: Add some simple examples of Pólya enumeration, once it will be easy to expand symmetric functions on any alphabet.

Here are the cycle indices of some permutation groups:

```
sage: 6 * CyclicPermutationGroup(6).cycle_index()
p[1, 1, 1, 1, 1, 1] + p[2, 2, 2] + 2*p[3, 3] + 2*p[6]

sage: 60 * AlternatingGroup(5).cycle_index()
p[1, 1, 1, 1, 1] + 15*p[2, 2, 1] + 20*p[3, 1, 1] + 24*p[5]

sage: for G in TransitiveGroups(5):                # long time
.....:     G.cardinality() * G.cycle_index()
p[1, 1, 1, 1, 1] + 4*p[5]
p[1, 1, 1, 1, 1] + 5*p[2, 2, 1] + 4*p[5]
p[1, 1, 1, 1, 1] + 5*p[2, 2, 1] + 10*p[4, 1] + 4*p[5]
p[1, 1, 1, 1, 1] + 15*p[2, 2, 1] + 20*p[3, 1, 1] + 24*p[5]
p[1, 1, 1, 1, 1] + 10*p[2, 1, 1, 1] + 15*p[2, 2, 1] + 20*p[3, 1, 1] +
↪20*p[3, 2] + 30*p[4, 1] + 24*p[5]
```

Permutation groups with arbitrary domains are supported (see [trac ticket #22765](#)):

```
sage: G = PermutationGroup(['b', 'c', 'a'], domain=['a', 'b', 'c'])
sage: G.cycle_index()
1/3*p[1, 1, 1] + 2/3*p[3]
```

One may specify another parent for the result:

```
sage: F = CombinatorialFreeModule(QQ, Partitions())
sage: P = CyclicPermutationGroup(6).cycle_index(parent = F)
sage: 6 * P
B[[1, 1, 1, 1, 1]] + B[[2, 2, 2]] + 2*B[[3, 3]] + 2*B[[6]]
sage: P.parent() is F
True
```

This parent should be a module with basis indexed by partitions:

```
sage: CyclicPermutationGroup(6).cycle_index(parent = QQ)
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: `parent` should be a module with basis indexed by partitions
```

REFERENCES:

- [Ke1991]

AUTHORS:

- Nicolas Borie and Nicolas M. Thiéry

profile(*n*, *using_polya=True*)

Return the value in *n* of the profile of the group *self*.

Optional argument *using_polya* allows to change the default method.

INPUT:

- *n* – a nonnegative integer
- *using_polya* (optional) – a boolean: if *True* (default), the computation uses Pólya enumeration (and all values of the profile are cached, so this should be the method used in case several of them are needed); if *False*, uses the GAP interface to compute the orbit.

OUTPUT:

- A nonnegative integer that is the number of orbits of *n*-subsets under the action induced by *self* on the subsets of its domain (i.e. the value of the profile of *self* in *n*)

See also:

- [profile_series\(\)](#)

EXAMPLES:

```
sage: C6 = CyclicPermutationGroup(6)
sage: C6.profile(2)
3
sage: C6.profile(3)
4
sage: D8 = DihedralGroup(8)
sage: D8.profile(4, using_polya=False)
8
```

profile_polynomial(*variable='z'*)

Return the (finite) generating series of the (finite) profile of the group.

The profile of a permutation group *G* is the counting function that maps each nonnegative integer *n* onto the number of orbits of the action induced by *G* on the *n*-subsets of its domain. If *f* is the profile of *G*, *f*(*n*) is thus the number of orbits of *n*-subsets of *G*.

INPUT:

- *variable* – a variable, or variable name as a string (default: *'z'*)

OUTPUT:

- A polynomial in *variable* with nonnegative integer coefficients. By default, a polynomial in *z* over \mathbb{Z} .

See also:

- [profile\(\)](#)

EXAMPLES:

```
sage: C8 = CyclicPermutationGroup(8)
sage: C8.profile_series()
z^8 + z^7 + 4*z^6 + 7*z^5 + 10*z^4 + 7*z^3 + 4*z^2 + z + 1
```

(continues on next page)

(continued from previous page)

```

sage: D8 = DihedralGroup(8)
sage: poly_D8 = D8.profile_series()
sage: poly_D8
z^8 + z^7 + 4*z^6 + 5*z^5 + 8*z^4 + 5*z^3 + 4*z^2 + z + 1
sage: poly_D8.parent()
Univariate Polynomial Ring in z over Rational Field
sage: D8.profile_series(variable='y')
y^8 + y^7 + 4*y^6 + 5*y^5 + 8*y^4 + 5*y^3 + 4*y^2 + y + 1
sage: u = var('u')
sage: D8.profile_series(u).parent()
Symbolic Ring

```

profile_series(variable='z')

Return the (finite) generating series of the (finite) profile of the group.

The profile of a permutation group G is the counting function that maps each nonnegative integer n onto the number of orbits of the action induced by G on the n -subsets of its domain. If f is the profile of G , $f(n)$ is thus the number of orbits of n -subsets of G .

INPUT:

- `variable` – a variable, or variable name as a string (default: `'z'`)

OUTPUT:

- A polynomial in `variable` with nonnegative integer coefficients. By default, a polynomial in z over \mathbb{Z} .

See also:

- [profile\(\)](#)

EXAMPLES:

```

sage: C8 = CyclicPermutationGroup(8)
sage: C8.profile_series()
z^8 + z^7 + 4*z^6 + 7*z^5 + 10*z^4 + 7*z^3 + 4*z^2 + z + 1
sage: D8 = DihedralGroup(8)
sage: poly_D8 = D8.profile_series()
sage: poly_D8
z^8 + z^7 + 4*z^6 + 5*z^5 + 8*z^4 + 5*z^3 + 4*z^2 + z + 1
sage: poly_D8.parent()
Univariate Polynomial Ring in z over Rational Field
sage: D8.profile_series(variable='y')
y^8 + y^7 + 4*y^6 + 5*y^5 + 8*y^4 + 5*y^3 + 4*y^2 + y + 1
sage: u = var('u')
sage: D8.profile_series(u).parent()
Symbolic Ring

```

example()

Returns an example of finite permutation group, as per [Category.example\(\)](#).

EXAMPLES:

```

sage: G = FinitePermutationGroups().example(); G
Dihedral group of order 6 as a permutation group

```

extra_super_categories()

Any permutation group is assumed to be endowed with a finite set of generators.

3.62 Finite posets

Here is some terminology used in this file:

- An *order filter* (or *upper set*) of a poset P is a subset S of P such that if $x \leq y$ and $x \in S$ then $y \in S$.
- An *order ideal* (or *lower set*) of a poset P is a subset S of P such that if $x \leq y$ and $y \in S$ then $x \in S$.

class `sage.categories.finite_posets.FinitePosets(base_category)`
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of finite posets i.e. finite sets with a partial order structure.

EXAMPLES:

```
sage: FinitePosets()
Category of finite posets
sage: FinitePosets().super_categories()
[Category of posets, Category of finite sets]
sage: FinitePosets().example()
NotImplemented
```

See also:

[Posets](#), [Poset\(\)](#)

class `ParentMethods`

Bases: `object`

antichains()

Return all antichains of `self`.

EXAMPLES:

```
sage: A = posets.PentagonPoset().antichains(); A
Set of antichains of Finite lattice containing 5 elements
sage: list(A)
[[], [0], [1], [1, 2], [1, 3], [2], [3], [4]]
```

birational_free_labelling(*linear_extension=None, prefix='x', base_field=None, reduced=False, addvars=None, labels=None, min_label=None, max_label=None*)

Return the birational free labelling of `self`.

Let us hold back defining this, and introduce birational toggles and birational rowmotion first. These notions have been introduced in [EP2013] as generalizations of the notions of toggles ([order_ideal_toggle\(\)](#)) and *rowmotion* on order ideals of a finite poset. They have been studied further in [GR2013].

Let \mathbf{K} be a field, and P be a finite poset. Let \widehat{P} denote the poset obtained from P by adding a new element 1 which is greater than all existing elements of P , and a new element 0 which is smaller than all existing elements of P and 1. Now, a \mathbf{K} -labelling of P will mean any function from \widehat{P} to \mathbf{K} . The image of an element v of \widehat{P} under this labelling will be called the *label* of this labelling at v . The set of all \mathbf{K} -labellings of P is clearly $\mathbf{K}^{\widehat{P}}$.

For any $v \in P$, we now define a rational map $T_v : \mathbf{K}^{\widehat{P}} \dashrightarrow \mathbf{K}^{\widehat{P}}$ as follows: For every $f \in \mathbf{K}^{\widehat{P}}$, the image $T_v f$ should send every element $u \in \widehat{P}$ distinct from v to $f(u)$ (so the labels at all $u \neq v$ don't change), while v is sent to

$$\frac{1}{f(v)} \cdot \frac{\sum_{u < v} f(u)}{\sum_{u > v} \frac{1}{f(u)}}$$

(both sums are over all $u \in \widehat{P}$ satisfying the respectively given conditions). Here, \prec and \succ mean (respectively) “covered by” and “covers”, interpreted with respect to the poset \widehat{P} . This rational map T_v is an involution and is called the (birational) v -toggle; see `birational_toggle()` for its implementation.

Now, *birational rowmotion* is defined as the composition $T_{v_1} \circ T_{v_2} \circ \cdots \circ T_{v_n}$, where (v_1, v_2, \dots, v_n) is a linear extension of P (written as a linear ordering of the elements of P). This is a rational map $\mathbf{K}^{\widehat{P}} \dashrightarrow \mathbf{K}^{\widehat{P}}$ which does not depend on the choice of the linear extension; it is denoted by R . See `birational_rowmotion()` for its implementation.

The definitions of birational toggles and birational rowmotion extend to the case of \mathbf{K} being any semi-field rather than necessarily a field (although it becomes less clear what constitutes a rational map in this generality). The most useful case is that of the `tropical semiring`, in which case birational rowmotion relates to classical constructions such as promotion of rectangular semistandard Young tableaux (page 5 of [EP2013b] and future work, via the related notion of birational *promotion*) and rowmotion on order ideals of the poset ([EP2013]).

The *birational free labelling* is a special labelling defined for every finite poset P and every linear extension (v_1, v_2, \dots, v_n) of P . It is given by sending every element v_i in P to x_i , sending the element 0 of \widehat{P} to a , and sending the element 1 of \widehat{P} to b , where the ground field \mathbf{K} is the field of rational functions in $n + 2$ indeterminates $a, x_1, x_2, \dots, x_n, b$ over \mathbb{Q} .

In Sage, a labelling f of a poset P is encoded as a 4-tuple (\mathbf{K}, d, u, v) , where \mathbf{K} is the ground field of the labelling (i. e., its target), d is the dictionary containing the values of f at the elements of P (the keys being the respective elements of P), u is the label of f at 0, and v is the label of f at 1.

Warning: The dictionary d is labelled by the elements of P . If P is a poset with facade option set to `False`, these might not be what they seem to be! (For instance, if `P == Poset({1: [2, 3]}, facade=False)`, then the value of d at 1 has to be accessed by `d[P(1)]`, not by `d[1]`.)

Warning: Dictionaries are mutable. They do compare correctly, but are not hashable and need to be cloned to avoid spooky action at a distance. Be careful!

INPUT:

- `linear_extension` – (default: the default linear extension of `self`) a linear extension of `self` (as a linear extension or as a list), or more generally a list of all elements of all elements of `self` each occurring exactly once
- `prefix` – (default: `'x'`) the prefix to name the indeterminates corresponding to the elements of `self` in the labelling (so, setting it to `'frog'` will result in these indeterminates being called `frog1`, `frog2`, `...`, `frogn` rather than `x1`, `x2`, `...`, `xn`).
- `base_field` – (default: `QQ`) the base field to be used instead of \mathbb{Q} to define the rational function field over; this is not going to be the base field of the labelling, because the latter will have indeterminates adjoined!
- `reduced` – (default: `False`) if set to `True`, the result will be the *reduced* birational free labelling, which differs from the regular one by having 0 and 1 both sent to 1 instead of a and b (the indeterminates a and b then also won't appear in the ground field)
- `addvars` – (default: `''`) a string containing names of extra variables to be adjoined to the ground field (these don't have an effect on the labels)
- `labels` – (default: `'x'`) Either a function that takes an element of the poset and returns a name for the indeterminate corresponding to that element, or a string containing a comma-separated list of indeterminates that will be assigned to elements in the order of `linear_extension`. If the list contains more indeterminates than needed, the excess will be ignored. If it contains too few, then

the needed indeterminates will be constructed from `prefix`.

- `min_label` – (default: 'a') a string to be used as the label for the element 0 of \widehat{P}
- `max_label` – (default: 'b') a string to be used as the label for the element 1 of \widehat{P}

OUTPUT:

The birational free labelling of the poset `self` and the linear extension `linear_extension`. Or, if `reduced` is set to `True`, the reduced birational free labelling.

EXAMPLES:

We construct the birational free labelling on a simple poset:

```
sage: P = Poset({1: [2, 3]})
sage: l = P.birational_free_labelling(); l
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, b over
↳Rational Field,
↳{...},
↳a,
↳b)
sage: sorted(l[1].items())
[(1, x1), (2, x2), (3, x3)]

sage: l = P.birational_free_labelling(linear_extension=[1, 3, 2]); l
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, b over
↳Rational Field,
↳{...},
↳a,
↳b)
sage: sorted(l[1].items())
[(1, x1), (2, x3), (3, x2)]

sage: l = P.birational_free_labelling(linear_extension=[1, 3, 2],
↳reduced=True, addvars="spam, eggs"); l
(Fraction Field of Multivariate Polynomial Ring in x1, x2, x3, spam, eggs
↳over Rational Field,
↳{...},
↳1,
↳1)
sage: sorted(l[1].items())
[(1, x1), (2, x3), (3, x2)]

sage: l = P.birational_free_labelling(linear_extension=[1, 3, 2], prefix=
↳"wut", reduced=True, addvars="spam, eggs"); l
(Fraction Field of Multivariate Polynomial Ring in wut1, wut2, wut3, spam,
↳eggs over Rational Field,
↳{...},
↳1,
↳1)
sage: sorted(l[1].items())
[(1, wut1), (2, wut3), (3, wut2)]

sage: l = P.birational_free_labelling(linear_extension=[1, 3, 2],
↳reduced=False, addvars="spam, eggs"); l
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, b, spam,
↳eggs over Rational Field,
```

(continues on next page)

(continued from previous page)

```
{...},
a,
b)
sage: sorted(l[1].items())
[(1, x1), (2, x3), (3, x2)]
sage: l[1][2]
x3
```

Illustrating labelling with a function:

```
sage: P = posets.ChainPoset(2).product(posets.ChainPoset(2))
sage: l = P.birational_free_labelling(labels=lambda e : 'x_' + str(e[0]) +
↳str(e[1]))
sage: sorted(l[1].items())
[((0, 0), x_00), ((0, 1), x_01), ((1, 0), x_10), ((1, 1), x_11)]
sage: l[2]
a
```

The same, but with min_label and max_label provided:

```
sage: P = posets.ChainPoset(2).product(posets.ChainPoset(2))
sage: l = P.birational_free_labelling(labels=lambda e : 'x_' + str(e[0]) +
↳str(e[1]), min_label="lambda", max_label="mu")
sage: sorted(l[1].items())
[((0, 0), x_00), ((0, 1), x_01), ((1, 0), x_10), ((1, 1), x_11)]
sage: l[2]
lambda
sage: l[3]
mu
```

Illustrating labelling with a comma separated list of labels:

```
sage: l = P.birational_free_labelling(labels='w,x,y,z')
sage: sorted(l[1].items())
[((0, 0), w), ((0, 1), x), ((1, 0), y), ((1, 1), z)]
sage: l = P.birational_free_labelling(labels='w,x,y,z,m')
sage: sorted(l[1].items())
[((0, 0), w), ((0, 1), x), ((1, 0), y), ((1, 1), z)]
sage: l = P.birational_free_labelling(labels='w')
sage: sorted(l[1].items())
[((0, 0), w), ((0, 1), x1), ((1, 0), x2), ((1, 1), x3)]
```

Illustrating the warning about facade:

```
sage: P = Poset({1: [2, 3]}, facade=False)
sage: l = P.birational_free_labelling(linear_extension=[1, 3, 2],
↳reduced=False, addvars="spam, eggs"); l
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, b, spam,
↳eggs over Rational Field,
{...},
a,
b)
sage: l[1][2]
```

(continues on next page)

(continued from previous page)

```
Traceback (most recent call last):
...
KeyError: 2
sage: l[1][P(2)]
x3
```

Another poset:

```
sage: P = posets.SSTPoset([2,1])
sage: lext = sorted(P)
sage: l = P.birational_free_labelling(linear_extension=lext, addvars="ohai")
sage: l
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, x4, x5,
↪x6, x7, x8, b, ohai over Rational Field,
{...},
a,
b)
sage: sorted(l[1].items())
([[1, 1], [2]], x1), ([[1, 1], [3]], x2), ([[1, 2], [2]], x3), ([[1, 2],
↪[3]], x4),
([[1, 3], [2]], x5), ([[1, 3], [3]], x6), ([[2, 2], [3]], x7), ([[2, 3],
↪[3]], x8)]
```

See [birational_rowmotion\(\)](#), [birational_toggle\(\)](#) and [birational_toggles\(\)](#) for more substantial examples of what one can do with the birational free labelling.

birational_rowmotion(labelling)

Return the result of applying birational rowmotion to the \mathbf{K} -labelling labelling of the poset self.

See the documentation of [birational_free_labelling\(\)](#) for a definition of birational rowmotion and \mathbf{K} -labellings and for an explanation of how \mathbf{K} -labellings are to be encoded to be understood by Sage. This implementation allows \mathbf{K} to be a semifield, not just a field. Birational rowmotion is only a rational map, so an exception (most likely, `ZeroDivisionError`) will be thrown if the denominator is zero.

INPUT:

- labelling – a \mathbf{K} -labelling of self in the sense as defined in the documentation of [birational_free_labelling\(\)](#)

OUTPUT:

The image of the \mathbf{K} -labelling f under birational rowmotion.

EXAMPLES:

```
sage: P = Poset({1: [2, 3], 2: [4], 3: [4]})
sage: lex = [1, 2, 3, 4]
sage: t = P.birational_free_labelling(linear_extension=lex); t
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, x4, b
↪over Rational Field,
{...},
a,
b)
sage: sorted(t[1].items())
[(1, x1), (2, x2), (3, x3), (4, x4)]
sage: t = P.birational_rowmotion(t); t
```

(continues on next page)

(continued from previous page)

```
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, x4, b_
↳over Rational Field,
 {...},
 a,
 b)
sage: sorted(t[1].items())
[(1, a*b/x4), (2, (x1*x2*b + x1*x3*b)/(x2*x4)),
 (3, (x1*x2*b + x1*x3*b)/(x3*x4)), (4, (x2*b + x3*b)/x4)]
```

A result of [GR2013] states that applying birational rowmotion $n + m$ times to a \mathbf{K} -labelling f of the poset $[n] \times [m]$ gives back f . Let us check this:

```
sage: def test_rectangle_periodicity(n, m, k):
.....:     P = posets.ChainPoset(n).product(posets.ChainPoset(m))
.....:     t0 = P.birational_free_labelling(P)
.....:     t = t0
.....:     for i in range(k):
.....:         t = P.birational_rowmotion(t)
.....:     return t == t0
sage: test_rectangle_periodicity(2, 2, 4)
True
sage: test_rectangle_periodicity(2, 2, 2)
False
sage: test_rectangle_periodicity(2, 3, 5) # long time
True
```

While computations with the birational free labelling quickly run out of memory due to the complexity of the rational functions involved, it is computationally cheap to check properties of birational rowmotion on examples in the tropical semiring:

```
sage: def test_rectangle_periodicity_tropical(n, m, k):
.....:     P = posets.ChainPoset(n).product(posets.ChainPoset(m))
.....:     TT = TropicalSemiring(ZZ)
.....:     t0 = (TT, {v: TT(floor(random()*100)) for v in P}, TT(0), TT(124))
.....:     t = t0
.....:     for i in range(k):
.....:         t = P.birational_rowmotion(t)
.....:     return t == t0
sage: test_rectangle_periodicity_tropical(7, 6, 13)
True
```

Tropicalization is also what relates birational rowmotion to classical rowmotion on order ideals. In fact, if T denotes the `tropical semiring` of \mathbf{Z} and P is a finite poset, then we can define an embedding ϕ from the set $J(P)$ of all order ideals of P into the set $T^{\hat{P}}$ of all T -labellings of P by sending every $I \in J(P)$ to the indicator function of I extended by the value 1 at the element 0 and the value 0 at the element 1. This map ϕ has the property that $R \circ \phi = \phi \circ r$, where R denotes birational rowmotion, and r denotes `classical rowmotion` on $J(P)$. An example:

```
sage: P = posets.IntegerPartitions(5)
sage: TT = TropicalSemiring(ZZ)
sage: def indicator_labelling(I):
.....:     # send order ideal `I` to a `T`-labelling of `P`.
```

(continues on next page)

(continued from previous page)

```

.....:   dct = {v: TT(v in I) for v in P}
.....:   return (TT, dct, TT(1), TT(0))
sage: all(indicator_labelling(P.rowmotion(I))
.....:      == P.birational_rowmotion(indicator_labelling(I))
.....:      for I in P.order_ideals_lattice(facade=True))
True

```

birational_toggle(*v*, *labelling*)

Return the result of applying the birational v -toggle T_v to the \mathbf{K} -labelling *labelling* of the poset *self*.

See the documentation of [birational_free_labelling\(\)](#) for a definition of this toggle and of \mathbf{K} -labellings as well as an explanation of how \mathbf{K} -labellings are to be encoded to be understood by Sage. This implementation allows \mathbf{K} to be a semifield, not just a field. The birational v -toggle is only a rational map, so an exception (most likely, `ZeroDivisionError`) will be thrown if the denominator is zero.

INPUT:

- *v* – an element of *self* (must have *self* as parent if *self* is a `facade=False` poset)
- *labelling* – a \mathbf{K} -labelling of *self* in the sense as defined in the documentation of [birational_free_labelling\(\)](#)

OUTPUT:

The \mathbf{K} -labelling $T_v f$ of *self*, where *f* is *labelling*.

EXAMPLES:

Let us start with the birational free labelling of the “V”-poset (the three-element poset with Hasse diagram looking like a “V”):

```

sage: V = Poset({1: [2, 3]})
sage: s = V.birational_free_labelling(); s
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, b over
↳Rational Field,
{...},
a,
b)
sage: sorted(s[1].items())
[(1, x1), (2, x2), (3, x3)]

```

The image of *s* under the 1-toggle T_1 is:

```

sage: s1 = V.birational_toggle(1, s); s1
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, b over
↳Rational Field,
{...},
a,
b)
sage: sorted(s1[1].items())
[(1, a*x2*x3/(x1*x2 + x1*x3)), (2, x2), (3, x3)]

```

Now let us apply the 2-toggle T_2 (to the old *s*):

```

sage: s2 = V.birational_toggle(2, s); s2
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, b over
↳Rational Field,

```

(continues on next page)

(continued from previous page)

```
{...},
a,
b)
sage: sorted(s2[1].items())
[(1, x1), (2, x1*b/x2), (3, x3)]
```

On the other hand, we can also apply T_2 to the image of s under T_1 :

```
sage: s12 = V.birational_toggle(2, s1); s12
(Fraction Field of Multivariate Polynomial Ring in a, x1, x2, x3, b over
↪Rational Field,
 {...},
 a,
 b)
sage: sorted(s12[1].items())
[(1, a*x2*x3/(x1*x2 + x1*x3)), (2, a*x3*b/(x1*x2 + x1*x3)), (3, x3)]
```

Each toggle is an involution:

```
sage: all( V.birational_toggle(i, V.birational_toggle(i, s)) == s
.....:      for i in V )
True
```

We can also start with a less generic labelling:

```
sage: t = (QQ, {1: 3, 2: 6, 3: 7}, 2, 10)
sage: t1 = V.birational_toggle(1, t); t1
(Rational Field, {...}, 2, 10)
sage: sorted(t1[1].items())
[(1, 28/13), (2, 6), (3, 7)]
sage: t13 = V.birational_toggle(3, t1); t13
(Rational Field, {...}, 2, 10)
sage: sorted(t13[1].items())
[(1, 28/13), (2, 6), (3, 40/13)]
```

However, labellings have to be sufficiently generic, lest denominators vanish:

```
sage: t = (QQ, {1: 3, 2: 5, 3: -5}, 1, 15)
sage: t1 = V.birational_toggle(1, t)
Traceback (most recent call last):
...
ZeroDivisionError: rational division by zero
```

We don't get into zero-division issues in the tropical semiring (unless the zero of the tropical semiring appears in the labelling):

```
sage: TT = TropicalSemiring(QQ)
sage: t = (TT, {1: TT(2), 2: TT(4), 3: TT(1)}, TT(6), TT(0))
sage: t1 = V.birational_toggle(1, t); t1
(Tropical semiring over Rational Field, {...}, 6, 0)
sage: sorted(t1[1].items())
[(1, 8), (2, 4), (3, 1)]
sage: t12 = V.birational_toggle(2, t1); t12
```

(continues on next page)

(continued from previous page)

```
(Tropical semiring over Rational Field, {...}, 6, 0)
sage: sorted(t12[1].items())
[(1, 8), (2, 4), (3, 1)]
sage: t123 = V.birational_toggle(3, t12); t123
(Tropical semiring over Rational Field, {...}, 6, 0)
sage: sorted(t123[1].items())
[(1, 8), (2, 4), (3, 7)]
```

We turn to more interesting posets. Here is the 6-element poset arising from the weak order on S_3 :

```
sage: P = posets.SymmetricGroupWeakOrderPoset(3)
sage: sorted(list(P))
['123', '132', '213', '231', '312', '321']
sage: t = (TT, {'123': TT(4), '132': TT(2), '213': TT(3), '231': TT(1), '321'
↪ ': TT(1), '312': TT(2)}, TT(7), TT(1))
sage: t1 = P.birational_toggle('123', t); t1
(Tropical semiring over Rational Field, {...}, 7, 1)
sage: sorted(t1[1].items())
[('123', 6), ('132', 2), ('213', 3), ('231', 1), ('312', 2), ('321', 1)]
sage: t13 = P.birational_toggle('213', t1); t13
(Tropical semiring over Rational Field, {...}, 7, 1)
sage: sorted(t13[1].items())
[('123', 6), ('132', 2), ('213', 4), ('231', 1), ('312', 2), ('321', 1)]
```

Let us verify on this example some basic properties of toggles. First of all, again let us check that T_v is an involution for every v :

```
sage: all( P.birational_toggle(v, P.birational_toggle(v, t)) == t
.....:      for v in P )
True
```

Furthermore, two toggles T_v and T_w commute unless one of v or w covers the other:

```
sage: all( P.covers(v, w) or P.covers(w, v)
.....:      or P.birational_toggle(v, P.birational_toggle(w, t))
.....:      == P.birational_toggle(w, P.birational_toggle(v, t))
.....:      for v in P for w in P )
True
```

birational_toggles(*vs, labelling*)

Return the result of applying a sequence of birational toggles (specified by *vs*) to the \mathbf{K} -labelling labelling of the poset self.

See the documentation of [birational_free_labelling\(\)](#) for a definition of birational toggles and \mathbf{K} -labellings and for an explanation of how \mathbf{K} -labellings are to be encoded to be understood by Sage. This implementation allows \mathbf{K} to be a semifield, not just a field. The birational v -toggle is only a rational map, so an exception (most likely, `ZeroDivisionError`) will be thrown if the denominator is zero.

INPUT:

- *vs* – an iterable comprising elements of *self* (which must have *self* as parent if *self* is a `facade=False` poset)
- *labelling* – a \mathbf{K} -labelling of *self* in the sense as defined in the documentation of [birational_free_labelling\(\)](#)

OUTPUT:

The \mathbf{K} -labelling $T_{v_n} T_{v_{n-1}} \cdots T_{v_1} f$ of `self`, where f is labelling and (v_1, v_2, \dots, v_n) is `vs` (written as list).

EXAMPLES:

```
sage: P = posets.SymmetricGroupBruhatOrderPoset(3)
sage: sorted(list(P))
['123', '132', '213', '231', '312', '321']
sage: TT = TropicalSemiring(ZZ)
sage: t = (TT, {'123': TT(4), '132': TT(2), '213': TT(3), '231': TT(1), '321'
↪ ': TT(1), '312': TT(2)}, TT(7), TT(1))
sage: tA = P.birational_toggles(['123', '231', '312'], t); tA
(Tropical semiring over Integer Ring, {...}, 7, 1)
sage: sorted(tA[1].items())
[('123', 6), ('132', 2), ('213', 3), ('231', 2), ('312', 1), ('321', 1)]
sage: tAB = P.birational_toggles(['132', '213', '321'], tA); tAB
(Tropical semiring over Integer Ring, {...}, 7, 1)
sage: sorted(tAB[1].items())
[('123', 6), ('132', 6), ('213', 5), ('231', 2), ('312', 1), ('321', 1)]

sage: P = Poset({1: [2, 3], 2: [4], 3: [4]})
sage: Qx = PolynomialRing(QQ, 'x').fraction_field()
sage: x = Qx.gen()
sage: t = (Qx, {1: 1, 2: x, 3: (x+1)/x, 4: x^2}, 1, 1)
sage: t1 = P.birational_toggles((i for i in range(1, 5)), t); t1
(Fraction Field of Univariate Polynomial Ring in x over Rational Field,
 {...},
 1,
 1)
sage: sorted(t1[1].items())
[(1, (x^2 + x)/(x^2 + x + 1)), (2, (x^3 + x^2)/(x^2 + x + 1)), (3, x^4/(x^2
↪ + x + 1)), (4, 1)]
sage: t2 = P.birational_toggles(reversed(range(1, 5)), t)
sage: sorted(t2[1].items())
[(1, 1/x^2), (2, (x^2 + x + 1)/x^4), (3, (x^2 + x + 1)/(x^3 + x^2)), (4, (x
↪ ^2 + x + 1)/x^3)]
```

Facade set to `False` works:

```
sage: P = Poset({'x': ['y', 'w'], 'y': ['z'], 'w': ['z']}, facade=False)
sage: lex = ['x', 'y', 'w', 'z']
sage: t = P.birational_free_labelling(linear_extension=lex)
sage: sorted(P.birational_toggles([P('x'), P('y')], t)[1].items())
[(x, a*x2*x3/(x1*x2 + x1*x3)), (y, a*x3*x4/(x1*x2 + x1*x3)), (w, x3), (z,
↪ x4)]
```

directed_subsets(*direction*)

Return the order filters (resp. order ideals) of `self`, as lists.

If *direction* is 'up', returns the order filters (upper sets).

If *direction* is 'down', returns the order ideals (lower sets).

INPUT:

- *direction* – 'up' or 'down'

EXAMPLES:

```
sage: P = Poset((divisors(12), attrcall("divides")), facade=True)
sage: A = P.directed_subsets('up')
sage: sorted(list(A))
[[], [1, 2, 4, 3, 6, 12], [2, 4, 3, 6, 12], [2, 4, 6, 12], [3, 6, 12], [4, 3, 6, 12], [4, 6, 12], [4, 12], [6, 12], [12]]
```

is_lattice()

Return whether the poset is a lattice.

A poset is a lattice if all pairs of elements have both a least upper bound (“join”) and a greatest lower bound (“meet”) in the poset.

EXAMPLES:

```
sage: P = Poset([[1, 3, 2], [4], [4, 5, 6], [6], [7], [7], [7], []])
sage: P.is_lattice()
True

sage: P = Poset([[1, 2], [3], [3], []])
sage: P.is_lattice()
True

sage: P = Poset({0: [2, 3], 1: [2, 3]})
sage: P.is_lattice()
False

sage: P = Poset({1: [2, 3, 4], 2: [5, 6], 3: [5, 7], 4: [6, 7], 5: [8, 9],
.....: 6: [8, 10], 7: [9, 10], 8: [11], 9: [11], 10: [11]})
sage: P.is_lattice()
False
```

See also:

- Weaker properties: `is_join_semilattice()`, `is_meet_semilattice()`

is_poset_isomorphism(*f*, *codomain*)

Return whether *f* is an isomorphism of posets from *self* to *codomain*.

INPUT:

- *f* – a function from *self* to *codomain*
- *codomain* – a poset

EXAMPLES:

We build the poset *D* of divisors of 30, and check that it is isomorphic to the boolean lattice *B* of the subsets of $\{2, 3, 5\}$ ordered by inclusion, via the reverse function $f : B \rightarrow D, b \mapsto \prod_{x \in b} x$:

```
sage: D = Poset((divisors(30), attrcall("divides")))
sage: B = Poset(([frozenset(s) for s in Subsets([2,3,5])], attrcall(
↪ "issubset")))
sage: def f(b): return D(prod(b))
sage: B.is_poset_isomorphism(f, D)
True
```

On the other hand, *f* is not an isomorphism to the chain of divisors of 30, ordered by usual comparison:

```
sage: P = Poset((divisors(30), operator.le))
sage: def f(b): return P(prod(b))
sage: B.is_poset_isomorphism(f, P)
False
```

A non surjective case:

```
sage: B = Poset(([frozenset(s) for s in Subsets([2,3])], attrcall("issubset
↪")))
sage: def f(b): return D(prod(b))
sage: B.is_poset_isomorphism(f, D)
False
```

A non injective case:

```
sage: B = Poset(([frozenset(s) for s in Subsets([2,3,5,6])], attrcall(
↪"issubset")))
sage: def f(b): return D(gcd(prod(b), 30))
sage: B.is_poset_isomorphism(f, D)
False
```

Note: since D and B are not facade posets, *f* is responsible for the conversions between integers and subsets to elements of D and B and back.

See also:

FiniteLatticePosets.ParentMethods.is_lattice_morphism()

is_poset_morphism(*f*, *codomain*)

Return whether *f* is a morphism of posets from *self* to *codomain*, that is

$$x \leq y \implies f(x) \leq f(y)$$

for all *x* and *y* in *self*.

INPUT:

- *f* – a function from *self* to *codomain*
- *codomain* – a poset

EXAMPLES:

We build the boolean lattice of the subsets of $\{2, 3, 5, 6\}$ and the lattice of divisors of 30, and check that the map $b \mapsto \gcd(\prod_{x \in b} x, 30)$ is a morphism of posets:

```
sage: D = Poset((divisors(30), attrcall("divides")))
sage: B = Poset(([frozenset(s) for s in Subsets([2,3,5,6])], attrcall(
↪"issubset")))
sage: def f(b): return D(gcd(prod(b), 30))
sage: B.is_poset_morphism(f, D)
True
```

Note: since D and B are not facade posets, *f* is responsible for the conversions between integers and subsets to elements of D and B and back.

f is also a morphism of posets to the chain of divisors of 30, ordered by usual comparison:

```

sage: P = Poset((divisors(30), operator.le))
sage: def f(b): return P(gcd(prod(b), 30))
sage: B.is_poset_morphism(f, P)
True

```

FIXME: should this be `is_order_preserving_morphism`?

See also:

[`is_poset_isomorphism\(\)`](#)

is_self_dual()

Return whether the poset is *self-dual*.

A poset is self-dual if it is isomorphic to its dual poset.

EXAMPLES:

```

sage: P = Poset({1: [3, 4], 2: [3, 4]})
sage: P.is_self_dual()
True

sage: P = Poset({1: [2, 3]})
sage: P.is_self_dual()
False

```

See also:

- Stronger properties: [`is_orthocomplemented\(\)`](#) (for lattices)
- Other: [`dual\(\)`](#)

order_filter_generators(*filter*)

Generators for an order filter

INPUT:

- *filter* – an order filter of `self`, as a list (or iterable)

EXAMPLES:

```

sage: P = Poset((Subsets([1,2,3]), attrcall("issubset")))
sage: I = P.order_filter([Set([1,2]), Set([2,3]), Set([1])])
sage: sorted(sorted(p) for p in I)
[[1], [1, 2], [1, 2, 3], [1, 3], [2, 3]]
sage: gen = P.order_filter_generators(I)
sage: sorted(sorted(p) for p in gen)
[[1], [2, 3]]

```

See also:

[`order_ideal_generators\(\)`](#)

order_ideal_complement_generators(*antichain*, *direction*='up')

Return the Panyushev complement of the antichain *antichain*.

Given an antichain *A* of a poset *P*, the Panyushev complement of *A* is defined to be the antichain consisting of the minimal elements of the order filter *B*, where *B* is the (set-theoretic) complement of the order ideal of *P* generated by *A*.

Setting the optional keyword variable *direction* to 'down' leads to the inverse Panyushev complement being computed instead of the Panyushev complement. The inverse Panyushev complement of an antichain *A* is the antichain whose Panyushev complement is *A*. It can be found as the antichain

consisting of the maximal elements of the order ideal C , where C is the (set-theoretic) complement of the order filter of P generated by A .

`panyushev_complement()` is an alias for this method.

Panyushev complementation is related (actually, isomorphic) to rowmotion (`rowmotion()`).

INPUT:

- `antichain` – an antichain of `self`, as a list (or iterable), or, more generally, generators of an order ideal (resp. order filter)
- `direction` – ‘up’ or ‘down’ (default: ‘up’)

OUTPUT:

- the generating antichain of the complement order filter (resp. order ideal) of the order ideal (resp. order filter) generated by the antichain `antichain`

EXAMPLES:

```
sage: P = Poset( ( [1,2,3], [ [1,3], [2,3] ] ) )
sage: P.order_ideal_complement_generators([1])
{2}
sage: P.order_ideal_complement_generators([3])
set()
sage: P.order_ideal_complement_generators([1,2])
{3}
sage: P.order_ideal_complement_generators([1,2,3])
set()

sage: P.order_ideal_complement_generators([1], direction="down")
{2}
sage: P.order_ideal_complement_generators([3], direction="down")
{1, 2}
sage: P.order_ideal_complement_generators([1,2], direction="down")
set()
sage: P.order_ideal_complement_generators([1,2,3], direction="down")
set()
```

Warning: This is a brute force implementation, building the order ideal generated by the antichain, and searching for order filter generators of its complement

order_ideal_generators(*ideal*, *direction*='down')

Return the antichain of (minimal) generators of the order ideal (resp. order filter) `ideal`.

INPUT:

- `ideal` – an order ideal I (resp. order filter) of `self`, as a list (or iterable); this should be an order ideal if `direction` is set to ‘down’, and an order filter if `direction` is set to ‘up’.
- `direction` – ‘up’ or ‘down’ (default: ‘down’).

The antichain of (minimal) generators of an order ideal I in a poset P is the set of all minimal elements of P . In the case of an order filter, the definition is similar, but with “maximal” used instead of “minimal”.

EXAMPLES:

We build the boolean lattice of all subsets of $\{1, 2, 3\}$ ordered by inclusion, and compute an order ideal there:

```
sage: P = Poset((Subsets([1,2,3]), attrcall("issubset")))
sage: I = P.order_ideal([Set([1,2]), Set([2,3]), Set([1])])
sage: sorted(sorted(p) for p in I)
[[], [1], [1, 2], [2], [2, 3], [3]]
```

Then, we retrieve the generators of this ideal:

```
sage: gen = P.order_ideal_generators(I)
sage: sorted(sorted(p) for p in gen)
[[1, 2], [2, 3]]
```

If `direction` is 'up', then this instead computes the minimal generators for an order filter:

```
sage: I = P.order_filter([Set([1,2]), Set([2,3]), Set([1])])
sage: sorted(sorted(p) for p in I)
[[1], [1, 2], [1, 2, 3], [1, 3], [2, 3]]
sage: gen = P.order_ideal_generators(I, direction='up')
sage: sorted(sorted(p) for p in gen)
[[1], [2, 3]]
```

Complexity: $O(n + m)$ where n is the cardinality of I , and m the number of upper covers of elements of I .

`order_ideals_lattice` (*as_ideals=True, facade=None*)

Return the lattice of order ideals of a poset `self`, ordered by inclusion.

The lattice of order ideals of a poset P is usually denoted by $J(P)$. Its underlying set is the set of order ideals of P , and its partial order is given by inclusion.

The order ideals of P are in a canonical bijection with the antichains of P . The bijection maps every order ideal to the antichain formed by its maximal elements. By setting the `as_ideals` keyword variable to `False`, one can make this method apply this bijection before returning the lattice.

INPUT:

- `as_ideals` – Boolean, if `True` (default) returns a poset on the set of order ideals, otherwise on the set of antichains
- `facade` – Boolean or `None` (default). Whether to return a facade lattice or not. By default return facade lattice if the poset is a facade poset.

EXAMPLES:

```
sage: P = posets.PentagonPoset()
sage: P.cover_relations()
[[0, 1], [0, 2], [1, 4], [2, 3], [3, 4]]
sage: J = P.order_ideals_lattice(); J
Finite lattice containing 8 elements
sage: sorted(sorted(e) for e in J)
[[], [0], [0, 1], [0, 1, 2], [0, 1, 2, 3], [0, 1, 2, 3, 4], [0, 2], [0, 2, 3]]
```

As a lattice on antichains:

```
sage: J2 = P.order_ideals_lattice(False); J2
Finite lattice containing 8 elements
sage: sorted(J2)
[(), (0,), (1,), (1, 2), (1, 3), (2,), (3,), (4,)]
```

panyushev_complement(*antichain*, *direction='up'*)

Return the Panyushev complement of the antichain *antichain*.

Given an antichain A of a poset P , the Panyushev complement of A is defined to be the antichain consisting of the minimal elements of the order filter B , where B is the (set-theoretic) complement of the order ideal of P generated by A .

Setting the optional keyword variable *direction* to 'down' leads to the inverse Panyushev complement being computed instead of the Panyushev complement. The inverse Panyushev complement of an antichain A is the antichain whose Panyushev complement is A . It can be found as the antichain consisting of the maximal elements of the order ideal C , where C is the (set-theoretic) complement of the order filter of P generated by A .

panyushev_complement() is an alias for this method.

Panyushev complementation is related (actually, isomorphic) to rowmotion (*rowmotion()*).

INPUT:

- *antichain* – an antichain of *self*, as a list (or iterable), or, more generally, generators of an order ideal (resp. order filter)
- *direction* – 'up' or 'down' (default: 'up')

OUTPUT:

- the generating antichain of the complement order filter (resp. order ideal) of the order ideal (resp. order filter) generated by the antichain *antichain*

EXAMPLES:

```
sage: P = Poset( ( [1,2,3], [ [1,3], [2,3] ] ) )
sage: P.order_ideal_complement_generators([1])
{2}
sage: P.order_ideal_complement_generators([3])
set()
sage: P.order_ideal_complement_generators([1,2])
{3}
sage: P.order_ideal_complement_generators([1,2,3])
set()

sage: P.order_ideal_complement_generators([1], direction="down")
{2}
sage: P.order_ideal_complement_generators([3], direction="down")
{1, 2}
sage: P.order_ideal_complement_generators([1,2], direction="down")
set()
sage: P.order_ideal_complement_generators([1,2,3], direction="down")
set()
```

Warning: This is a brute force implementation, building the order ideal generated by the antichain, and searching for order filter generators of its complement

panyushev_orbit_iter(*antichain*, *element_constructor=<class 'set'>*, *stop=True*, *check=True*)

Iterate over the Panyushev orbit of an antichain *antichain* of *self*.

The Panyushev orbit of an antichain is its orbit under Panyushev complementation (see *panyushev_complement()*).

INPUT:

- *antichain* – an antichain of *self*, given as an iterable.

- `element_constructor` (defaults to `set`) – a type constructor (`set`, `tuple`, `list`, `frozenset`, `iter`, etc.) which is to be applied to the antichains before they are yielded.
- `stop` – a Boolean (default: `True`) determining whether the iterator should stop once it completes its cycle (this happens when it is set to `True`) or go on forever (this happens when it is set to `False`).
- `check` – a Boolean (default: `True`) determining whether antichain should be checked for being an antichain.

OUTPUT:

- an iterator over the orbit of the antichain `antichain` under Panyushev complementation. This iterator I has the property that $I[0] == \text{antichain}$ and each i satisfies `self.order_ideal_complement_generators(I[i]) == I[i+1]`, where $I[i+1]$ has to be understood as $I[0]$ if it is undefined. The entries $I[i]$ are sets by default, but depending on the optional keyword variable `element_constructors` they can also be tuples, lists etc.

EXAMPLES:

```
sage: P = Poset( ( [1,2,3], [ [1,3], [2,3] ] ) )
sage: list(P.panyushev_orbit_iter(set([1, 2])))
[1, 2], {3}, set()
sage: list(P.panyushev_orbit_iter([1, 2]))
[1, 2], {3}, set()
sage: list(P.panyushev_orbit_iter([2, 1]))
[1, 2], {3}, set()
sage: list(P.panyushev_orbit_iter(set([1, 2]), element_constructor=list))
[[1, 2], [3], []]
sage: list(P.panyushev_orbit_iter(set([1, 2]), element_
↪ constructor=frozenset))
[frozenset({1, 2}), frozenset({3}), frozenset()]
sage: list(P.panyushev_orbit_iter(set([1, 2]), element_constructor=tuple))
[(1, 2), (3,), ()]

sage: P = Poset( {} )
sage: list(P.panyushev_orbit_iter([]))
[set()]

sage: P = Poset({ 1: [2, 3], 2: [4], 3: [4], 4: [] })
sage: Piter = P.panyushev_orbit_iter([2], stop=False)
sage: next(Piter)
{2}
sage: next(Piter)
{3}
sage: next(Piter)
{2}
sage: next(Piter)
{3}
```

panyushev_orbits(*element_constructor*=<class 'set'>)

Return the Panyushev orbits of antichains in `self`.

The Panyushev orbit of an antichain is its orbit under Panyushev complementation (see [panyushev_complement\(\)](#)).

INPUT:

- `element_constructor` (defaults to `set`) – a type constructor (`set`, `tuple`, `list`, `frozenset`, `iter`, etc.) which is to be applied to the antichains before they are returned.

OUTPUT:

- the partition of the set of all antichains of `self` into orbits under Panyushev complementation. This is returned as a list of lists `L` such that for each `L` and `i`, cyclically: `self.order_ideal_complement_generators(L[i]) == L[i+1]`. The entries `L[i]` are sets by default, but depending on the optional keyword variable `element_constructors` they can also be tuples, lists etc.

EXAMPLES:

```
sage: P = Poset( ( [1,2,3], [ [1,3], [2,3] ] ) )
sage: orb = P.panyushev_orbits()
sage: sorted(sorted(o) for o in orb)
[[set(), {1, 2}, {3}], [{2}, {1}]]
sage: orb = P.panyushev_orbits(element_constructor=list)
sage: sorted(sorted(o) for o in orb)
[[[], [1, 2], [3]], [[1], [2]]]
sage: orb = P.panyushev_orbits(element_constructor=frozenset)
sage: sorted(sorted(o) for o in orb)
[[frozenset(), frozenset({1, 2}), frozenset({3})],
 [frozenset({2}), frozenset({1})]]
sage: orb = P.panyushev_orbits(element_constructor=tuple)
sage: sorted(sorted(o) for o in orb)
[[(), (1, 2), (3,)], [(1,), (2,)]]
sage: P = Poset( {} )
sage: P.panyushev_orbits()
[[set()]]
```

rowmotion(*order_ideal*)

The image of the order ideal `order_ideal` under rowmotion in `self`.

Rowmotion on a finite poset P is an automorphism of the set $J(P)$ of all order ideals of P . One way to define it is as follows: Given an order ideal $I \in J(P)$, we let F be the set-theoretic complement of I in P . Furthermore we let A be the antichain consisting of all minimal elements of F . Then, the rowmotion of I is defined to be the order ideal of P generated by the antichain A (that is, the order ideal consisting of each element of P which has some element of A above it).

Rowmotion is related (actually, isomorphic) to Panyushev complementation (`panyushev_complement()`).

INPUT:

- `order_ideal` – an order ideal of `self`, as a set

OUTPUT:

- the image of `order_ideal` under rowmotion, as a set again

EXAMPLES:

```
sage: P = Poset( {1: [2, 3], 2: [], 3: [], 4: [8], 5: [], 6: [5], 7: [1, 4],
 ↪ 8: []} )
sage: I = Set({2, 6, 1, 7})
sage: P.rowmotion(I)
{1, 3, 4, 5, 6, 7}

sage: P = Poset( {} )
sage: I = Set({})
sage: P.rowmotion(I)
{}
```

rowmotion_orbit_iter(*oideal*, *element_constructor*=<class 'set'>, *stop*=True, *check*=True)

Iterate over the rowmotion orbit of an order ideal `oideal` of `self`.

The rowmotion orbit of an order ideal is its orbit under rowmotion (see `rowmotion()`).

INPUT:

- `oideal` – an order ideal of `self`, given as an iterable.
- `element_constructor` (defaults to `set`) – a type constructor (`set`, `tuple`, `list`, `frozenset`, `iter`, etc.) which is to be applied to the order ideals before they are yielded.
- `stop` – a Boolean (default: `True`) determining whether the iterator should stop once it completes its cycle (this happens when it is set to `True`) or go on forever (this happens when it is set to `False`).
- `check` – a Boolean (default: `True`) determining whether `oideal` should be checked for being an order ideal.

OUTPUT:

- an iterator over the orbit of the order ideal `oideal` under rowmotion. This iterator `I` has the property that `I[0] == oideal` and that every `i` satisfies `self.rowmotion(I[i]) == I[i+1]`, where `I[i+1]` has to be understood as `I[0]` if it is undefined. The entries `I[i]` are sets by default, but depending on the optional keyword variable `element_constructors` they can also be tuples, lists etc.

EXAMPLES:

```
sage: P = Poset( ( [1,2,3], [ [1,3], [2,3] ] ) )
sage: list(P.rowmotion_orbit_iter(set([1, 2])))
[1, 2], [1, 2, 3], set()
sage: list(P.rowmotion_orbit_iter([1, 2]))
[1, 2], [1, 2, 3], set()
sage: list(P.rowmotion_orbit_iter([2, 1]))
[1, 2], [1, 2, 3], set()
sage: list(P.rowmotion_orbit_iter(set([1, 2]), element_constructor=list))
[[1, 2], [1, 2, 3], []]
sage: list(P.rowmotion_orbit_iter(set([1, 2]), element_
↪ constructor=frozenset))
[frozenset({1, 2}), frozenset({1, 2, 3}), frozenset()]
sage: list(P.rowmotion_orbit_iter(set([1, 2]), element_constructor=tuple))
[(1, 2), (1, 2, 3), ()]

sage: P = Poset( {} )
sage: list(P.rowmotion_orbit_iter([]))
[set()]

sage: P = Poset({ 1: [2, 3], 2: [4], 3: [4], 4: [] })
sage: Piter = P.rowmotion_orbit_iter([1, 2, 3], stop=False)
sage: next(Piter)
{1, 2, 3}
sage: next(Piter)
{1, 2, 3, 4}
sage: next(Piter)
set()
sage: next(Piter)
{1}
sage: next(Piter)
{1, 2, 3}

sage: P = Poset({ 1: [4], 2: [4, 5], 3: [5] })
sage: list(P.rowmotion_orbit_iter([1, 2], element_constructor=list))
[[1, 2], [1, 2, 3, 4], [2, 3, 5], [1], [2, 3], [1, 2, 3, 5], [1, 2, 4], [3]]
```

rowmotion_orbits(*element_constructor*=<class 'set'>)

Return the rowmotion orbits of order ideals in *self*.

The rowmotion orbit of an order ideal is its orbit under rowmotion (see [rowmotion\(\)](#)).

INPUT:

- *element_constructor* (defaults to `set`) – a type constructor (`set`, `tuple`, `list`, `frozenset`, `iter`, etc.) which is to be applied to the antichains before they are returned.

OUTPUT:

- the partition of the set of all order ideals of *self* into orbits under rowmotion. This is returned as a list of lists *L* such that for each *L* and *i*, cyclically: `self.rowmotion(L[i]) == L[i+1]`. The entries *L*[*i*] are sets by default, but depending on the optional keyword variable *element_constructors* they can also be tuples, lists etc.

EXAMPLES:

```
sage: P = Poset( {1: [2, 3], 2: [], 3: [], 4: [2]} )
sage: sorted(len(o) for o in P.rowmotion_orbits())
[3, 5]
sage: orb = P.rowmotion_orbits(element_constructor=list)
sage: sorted(sorted(e) for e in orb)
[[[], [4, 1], [4, 1, 2, 3]], [[1], [1, 3], [4], [4, 1, 2], [4, 1, 3]]]
sage: orb = P.rowmotion_orbits(element_constructor=tuple)
sage: sorted(sorted(e) for e in orb)
[[(), (4, 1), (4, 1, 2, 3)], [(1,), (1, 3), (4,), (4, 1, 2), (4, 1, 3)]]
sage: P = Poset({})
sage: P.rowmotion_orbits(element_constructor=tuple)
[[()]]
```

rowmotion_orbits_plots()

Return plots of the rowmotion orbits of order ideals in *self*.

The rowmotion orbit of an order ideal is its orbit under rowmotion (see [rowmotion\(\)](#)).

EXAMPLES:

```
sage: P = Poset( {1: [2, 3], 2: [], 3: [], 4: [2]} )
sage: P.rowmotion_orbits_plots()
Graphics Array of size 2 x 5
sage: P = Poset({})
sage: P.rowmotion_orbits_plots()
Graphics Array of size 1 x 1
```

toggleing_orbit_iter(*vs*, *oideal*, *element_constructor*=<class 'set'>, *stop*=True, *check*=True)

Iterate over the orbit of an order ideal *oideal* of *self* under the operation of toggling the vertices *vs*[0], *vs*[1], ... in this order.

See [order_ideal_toggle\(\)](#) for a definition of toggling.

Warning: The orbit is that under the composition of toggles, *not* under the single toggles themselves. Thus, for example, if *vs* == [1, 2], then the orbit has the form $(I, T_2T_1I, T_2T_1T_2T_1I, \dots)$ (where *I* denotes *oideal* and T_i means toggling at *i*) rather than $(I, T_1I, T_2T_1I, T_1T_2T_1I, \dots)$.

INPUT:

- *vs*: a list (or other iterable) of elements of *self* (but since the output depends on the order, sets should not be used as *vs*).

- `oideal` – an order ideal of `self`, given as an iterable.
- `element_constructor` (defaults to `set`) – a type constructor (`set`, `tuple`, `list`, `frozenset`, `iter`, etc.) which is to be applied to the order ideals before they are yielded.
- `stop` – a Boolean (default: `True`) determining whether the iterator should stop once it completes its cycle (this happens when it is set to `True`) or go on forever (this happens when it is set to `False`).
- `check` – a Boolean (default: `True`) determining whether `oideal` should be checked for being an order ideal.

OUTPUT:

- an iterator over the orbit of the order ideal `oideal` under toggling the vertices in the list `vs` in this order. This iterator `I` has the property that `I[0] == oideal` and that every `i` satisfies `self.order_ideal_toggles(I[i], vs) == I[i+1]`, where `I[i+1]` has to be understood as `I[0]` if it is undefined. The entries `I[i]` are sets by default, but depending on the optional keyword variable `element_constructors` they can also be tuples, lists etc.

EXAMPLES:

```
sage: P = Poset( ( [1,2,3], [ [1,3], [2,3] ] ) )
sage: list(P.toggling_orbit_iter([1, 3, 1], set([1, 2])))
[1, 2]
sage: list(P.toggling_orbit_iter([1, 2, 3], set([1, 2])))
[1, 2], set(), {1, 2, 3}
sage: list(P.toggling_orbit_iter([3, 2, 1], set([1, 2])))
[1, 2], {1, 2, 3}, set()
sage: list(P.toggling_orbit_iter([3, 2, 1], set([1, 2]), element_
↪constructor=list))
[[1, 2], [1, 2, 3], []]
sage: list(P.toggling_orbit_iter([3, 2, 1], set([1, 2]), element_
↪constructor=frozenset))
[frozenset({1, 2}), frozenset({1, 2, 3}), frozenset()]
sage: list(P.toggling_orbit_iter([3, 2, 1], set([1, 2]), element_
↪constructor=tuple))
[(1, 2), (1, 2, 3), ()]
sage: list(P.toggling_orbit_iter([3, 2, 1], [2, 1], element_
↪constructor=tuple))
[(1, 2), (1, 2, 3), ()]

sage: P = Poset( {} )
sage: list(P.toggling_orbit_iter([], []))
[set()]

sage: P = Poset({ 1: [2, 3], 2: [4], 3: [4], 4: [] })
sage: Piter = P.toggling_orbit_iter([1, 2, 4, 3], [1, 2, 3], stop=False)
sage: next(Piter)
{1, 2, 3}
sage: next(Piter)
{1}
sage: next(Piter)
set()
sage: next(Piter)
{1, 2, 3}
sage: next(Piter)
{1}
```


toggling_orbits(*vs*, *element_constructor*=<class 'set'>)

Return the orbits of order ideals in *self* under the operation of toggling the vertices *vs*[0], *vs*[1], ... in this order.

See [order_ideal_toggle\(\)](#) for a definition of toggling.

Warning: The orbits are those under the composition of toggles, *not* under the single toggles themselves. Thus, for example, if *vs* == [1,2], then the orbits have the form $(I, T_2T_1I, T_2T_1T_2T_1I, \dots)$ (where *I* denotes an order ideal and T_i means toggling at *i*) rather than $(I, T_1I, T_2T_1I, T_1T_2T_1I, \dots)$.

INPUT:

- *vs*: a list (or other iterable) of elements of *self* (but since the output depends on the order, sets should not be used as *vs*).

OUTPUT:

- a partition of the order ideals of *self*, as a list of sets *L* such that for each *L* and *i*, cyclically: *self*.order_ideal_toggles(*L*[*i*], *vs*) == *L*[*i*+1].

EXAMPLES:

```
sage: P = Poset( {1: [2, 4], 2: [], 3: [4], 4: []} )
sage: sorted(len(o) for o in P.toggling_orbits([1, 2]))
[2, 3, 3]
sage: P = Poset( {1: [3], 2: [1, 4], 3: [], 4: [3]} )
sage: sorted(len(o) for o in P.toggling_orbits((1, 2, 4, 3)))
[3, 3]
```

toggling_orbits_plots(*vs*)

Return plots of the orbits of order ideals in *self* under the operation of toggling the vertices *vs*[0], *vs*[1], ... in this order.

See [toggling_orbits\(\)](#) for more information.

EXAMPLES:

```
sage: P = Poset( {1: [2, 3], 2: [], 3: [], 4: [2]} )
sage: P.toggling_orbits_plots([1,2,3,4])
Graphics Array of size 2 x 5
sage: P = Poset({})
sage: P.toggling_orbits_plots([])
Graphics Array of size 1 x 1
```

3.63 Finite semigroups

class sage.categories.finite_semigroups.FiniteSemigroups(*base_category*)

Bases: [sage.categories.category_with_axiom.CategoryWithAxiom_singleton](#)

The category of finite (multiplicative) semigroups.

A finite semigroup is a *finite set* endowed with an associative binary operation $*$.

Warning: Finite semigroups in Sage used to be automatically endowed with an *enumerated set* structure; the default enumeration is then obtained by iteratively multiplying the semigroup generators. This forced

any finite semigroup to either implement an enumeration, or provide semigroup generators; this was often inconvenient.

Instead, finite semigroups that provide a distinguished finite set of generators with `semigroup_generators()` should now explicitly declare themselves in the category of finitely generated semigroups:

```
sage: Semigroups().FinitelyGenerated()
Category of finitely generated semigroups
```

This is a backward incompatible change.

EXAMPLES:

```
sage: C = FiniteSemigroups(); C
Category of finite semigroups
sage: C.super_categories()
[Category of semigroups, Category of finite sets]
sage: sorted(C.axioms())
['Associative', 'Finite']
sage: C.example()
An example of a finite semigroup: the left regular band generated by ('a', 'b', 'c',
↪ 'd')
```

class ParentMethods

Bases: object

idempotents()

Returns the idempotents of the semigroup

EXAMPLES:

```
sage: S = FiniteSemigroups().example(alphabet=('x', 'y'))
sage: sorted(S.idempotents())
['x', 'xy', 'y', 'yx']
```

j_classes()

Returns the J -classes of the semigroup.

Two elements u and v of a monoid are in the same J -class if u divides v and v divides u .

OUTPUT:

All the J -classes of self, as a list of lists.

EXAMPLES:

```
sage: S = FiniteSemigroups().example(alphabet=('a', 'b', 'c'))
sage: sorted(map(sorted, S.j_classes()))
[['a'], ['ab', 'ba'], ['abc', 'acb', 'bac', 'bca', 'cab', 'cba'], ['ac', 'ca
↪'], ['b'], ['bc', 'cb'], ['c']]
```

j_classes_of_idempotents()

Returns all the idempotents of self, grouped by J -class.

OUTPUT:

a list of lists.

EXAMPLES:

```
sage: S = FiniteSemigroups().example(alphabet=('a','b','c'))
sage: sorted(map(sorted, S.j_classes_of_idempotents()))
[['a'], ['ab', 'ba'], ['abc', 'acb', 'bac', 'bca', 'cab', 'cba'], ['ac', 'ca'
↪], ['b'], ['bc', 'cb'], ['c']]
```

j_transversal_of_idempotents()

Returns a list of one idempotent per regular J-class

EXAMPLES:

```
sage: S = FiniteSemigroups().example(alphabet=('a','b','c'))
sage: sorted(S.j_transversal_of_idempotents()) # py2
['a', 'acb', 'b', 'ba', 'bc', 'c', 'ca']
```

The chosen elements depend on the order of each J -class, and that order is random when using Python 3.

```
sage: sorted(S.j_transversal_of_idempotents()) # py3 random
['a', 'ab', 'abc', 'ac', 'b', 'c', 'cb']
```

3.64 Finite sets

class `sage.categories.finite_sets.FiniteSets`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of finite sets.

EXAMPLES:

```
sage: C = FiniteSets(); C
Category of finite sets
sage: C.super_categories()
[Category of sets]
sage: C.all_super_categories()
[Category of finite sets,
Category of sets,
Category of sets with partial maps,
Category of objects]
sage: C.example()
NotImplemented
```

class `Algebras`(*category*, **args*)

Bases: `sage.categories.algebra_functor.AlgebrasCategory`

extra_super_categories()

EXAMPLES:

```
sage: FiniteSets().Algebras(QQ).extra_super_categories()
[Category of finite dimensional vector spaces with basis over Rational_
↪Field]
```

This implements the fact that the algebra of a finite set is finite dimensional:

```
sage: FiniteMonoids().Algebras(QQ).is_subcategory(AlgebrasWithBasis(QQ).
↳FiniteDimensional())
True
```

class ParentMethods

Bases: object

is_finite()

Return True since self is finite.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: C.is_finite()
True
```

class Subquotients(category, *args)Bases: *sage.categories.subquotients.SubquotientsCategory***extra_super_categories()**

EXAMPLES:

```
sage: FiniteSets().Subquotients().extra_super_categories()
[Category of finite sets]
```

This implements the fact that a subquotient (and therefore a quotient or subobject) of a finite set is finite:

```
sage: FiniteSets().Subquotients().is_subcategory(FiniteSets())
True
sage: FiniteSets().Quotients().is_subcategory(FiniteSets())
True
sage: FiniteSets().Subobjects().is_subcategory(FiniteSets())
True
```

3.65 Finite Weyl Groups

class *sage.categories.finite_weyl_groups.FiniteWeylGroups*(base_category)Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

The category of finite Weyl groups.

EXAMPLES:

```
sage: C = FiniteWeylGroups()
sage: C
Category of finite weyl groups
sage: C.super_categories()
[Category of finite coxeter groups, Category of weyl groups]
sage: C.example()
The symmetric group on {0, ..., 3}
```

class ElementMethods

Bases: object

class ParentMethods

Bases: object

3.66 Finitely Generated Lambda bracket Algebras

AUTHORS:

- Reimundo Heluani (2020-08-21): Initial implementation.

class sage.categories.finitely_generated_lambda_bracket_algebras.FinitelyGeneratedLambdaBracketAlgebras

Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

The category of finitely generated lambda bracket algebras.

EXAMPLES:

```
sage: from sage.categories.lambda_bracket_algebras import LambdaBracketAlgebras
sage: LambdaBracketAlgebras(QQbar).FinitelyGenerated()
Category of finitely generated lambda bracket algebras over Algebraic Field
```

class Graded(*base_category*)

Bases: *sage.categories.graded_modules.GradedModulesCategory*

The category of H-graded finitely generated Lie conformal algebras.

EXAMPLES:

```
sage: LieConformalAlgebras(QQbar).FinitelyGenerated().Graded()
Category of H-graded finitely generated lie conformal algebras over Algebraic Field
```

class ParentMethods

Bases: object

gen(*i*)

The *i*-th generator of this Lie conformal algebra.

EXAMPLES:

```
sage: V = lie_conformal_algebras.Affine(QQ, 'A1')
sage: V.gens()
(B[alpha[1]], B[alphacheck[1]], B[-alpha[1]], B['K'])
sage: V.gen(0)
B[alpha[1]]
sage: V.1
B[alphacheck[1]]
```

ngens()

The number of generators of this Lie conformal algebra.

EXAMPLES:

```
sage: Vir = lie_conformal_algebras.Virasoro(QQ)
sage: Vir.ngens()
2
sage: V = lie_conformal_algebras.Affine(QQ, 'A2')
```

(continues on next page)

(continued from previous page)

```
sage: V.ngens()
9
```

some_elements()

Some elements of this Lie conformal algebra.

This method returns a list with elements containing at least the generators.

EXAMPLES:

```
sage: V = lie_conformal_algebras.Affine(QQ, 'A1', names=('e', 'h', 'f'))
sage: V.some_elements()
[e, h, f, K, Th + 4*T^(2)e, 4*T^(2)h, Te + 4*T^(2)e, Te + 4*T^(2)h]
```

3.67 Finitely Generated Lie Conformal Algebras

AUTHORS:

- Reimundo Heluani (2019-10-05): Initial implementation.

class `sage.categories.finitely_generated_lie_conformal_algebras.FinitelyGeneratedLieConformalAlgebras(b)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of finitely generated Lie conformal algebras.

EXAMPLES:

```
sage: LieConformalAlgebras(QQbar).FinitelyGenerated()
Category of finitely generated lie conformal algebras over Algebraic Field
```

class `Graded(base_category)`

Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of H-graded finitely generated Lie conformal algebras.

EXAMPLES:

```
sage: LieConformalAlgebras(QQbar).FinitelyGenerated().Graded()
Category of H-graded finitely generated lie conformal algebras over Algebraic Field
```

class `ParentMethods`

Bases: `object`

some_elements()

Some elements of this Lie conformal algebra.

Returns a list with elements containing at least the generators.

EXAMPLES:

```
sage: V = lie_conformal_algebras.Affine(QQ, 'A1', names=('e', 'h', 'f'))
sage: V.some_elements()
[e, h, f, K, Th + 4*T^(2)e, 4*T^(2)h, Te + 4*T^(2)e, Te + 4*T^(2)h]
```

class Super(*base_category*)

Bases: *sage.categories.super_modules.SuperModulesCategory*

The category of super finitely generated Lie conformal algebras.

EXAMPLES:

```
sage: LieConformalAlgebras(AA).FinitelyGenerated().Super()
Category of super finitely generated lie conformal algebras over Algebraic Real_
↪Field
```

class Graded(*base_category*)

Bases: *sage.categories.graded_modules.GradedModulesCategory*

The category of H-graded super finitely generated Lie conformal algebras.

EXAMPLES:

```
sage: LieConformalAlgebras(QQbar).FinitelyGenerated().Super().Graded()
Category of H-graded super finitely generated lie conformal algebras over_
↪Algebraic Field
```

3.68 Finitely generated magmas

class *sage.categories.finitely_generated_magmas.FinitelyGeneratedMagmas*(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

The category of finitely generated (multiplicative) magmas.

See *Magmas.SubcategoryMethods.FinitelyGeneratedAsMagma()* for details.

EXAMPLES:

```
sage: C = Magmas().FinitelyGeneratedAsMagma(); C
Category of finitely generated magmas
sage: C.super_categories()
[Category of magmas]
sage: sorted(C.axioms())
['FinitelyGeneratedAsMagma']
```

class *ParentMethods*

Bases: object

magma_generators()

Return distinguished magma generators for self.

OUTPUT: a finite family

This method should be implemented by all *finitely generated magmas*.

EXAMPLES:

```
sage: S = FiniteSemigroups().example()
sage: S.magma_generators()
Family ('a', 'b', 'c', 'd')
```

3.69 Finitely generated semigroups

class `sage.categories.finitely_generated_semigroups.FinitelyGeneratedSemigroups`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of finitely generated (multiplicative) semigroups.

A *finitely generated semigroup* is a *semigroup* endowed with a distinguished finite set of generators (see `FinitelyGeneratedSemigroups.ParentMethods.semigroup_generators()`). This makes it into an *enumerated set*.

EXAMPLES:

```
sage: C = Semigroups().FinitelyGenerated(); C
Category of finitely generated semigroups
sage: C.super_categories()
[Category of semigroups,
 Category of finitely generated magmas,
 Category of enumerated sets]
sage: sorted(C.axioms())
['Associative', 'Enumerated', 'FinitelyGeneratedAsMagma']
sage: C.example()
An example of a semigroup: the free semigroup generated
by ('a', 'b', 'c', 'd')
```

class `Finite`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

class `ParentMethods`

Bases: `object`

some_elements()

Return an iterable containing some elements of the semigroup.

OUTPUT: the ten first elements of the semigroup, if they exist.

EXAMPLES:

```
sage: S = FiniteSemigroups().example(alphabet=('x','y'))
sage: sorted(S.some_elements())
['x', 'xy', 'y', 'yx']
sage: S = FiniteSemigroups().example(alphabet=('x','y','z'))
sage: X = S.some_elements()
sage: len(X)
10
sage: all(x in S for x in X)
True
```

class `ParentMethods`

Bases: `object`

ideal(*gens*, *side='twosided'*)

Return the side-sided ideal generated by *gens*.

This brute force implementation recursively multiplies the elements of *gens* by the distinguished generators of this semigroup.

See also:

[*semigroup_generators\(\)*](#)

INPUT:

- `gens` – a list (or iterable) of elements of `self`
- `side` – [default: “twosided”] “left”, “right” or “twosided”

EXAMPLES:

```
sage: S = FiniteSemigroups().example()
sage: sorted(S.ideal([S('cab')]), side="left")
['abc', 'abcd', 'abdc', 'acb', 'acbd', 'acdb', 'adbc',
 'adcb', 'bac', 'bacd', 'badc', 'bca', 'bcad', 'bcda',
 'bdac', 'bdca', 'cab', 'cabd', 'cadb', 'cba', 'cbad',
 'cbda', 'cdab', 'cdba', 'dabc', 'dacb', 'dbac', 'dbca',
 'dcab', 'dcba']
sage: list(S.ideal([S('cab')]), side="right")
['cab', 'cabd']
sage: sorted(S.ideal([S('cab')]), side="twosided")
['abc', 'abcd', 'abdc', 'acb', 'acbd', 'acdb', 'adbc',
 'adcb', 'bac', 'bacd', 'badc', 'bca', 'bcad', 'bcda',
 'bdac', 'bdca', 'cab', 'cabd', 'cadb', 'cba', 'cbad',
 'cbda', 'cdab', 'cdba', 'dabc', 'dacb', 'dbac', 'dbca',
 'dcab', 'dcba']
sage: sorted(S.ideal([S('cab')]))
['abc', 'abcd', 'abdc', 'acb', 'acbd', 'acdb', 'adbc',
 'adcb', 'bac', 'bacd', 'badc', 'bca', 'bcad', 'bcda',
 'bdac', 'bdca', 'cab', 'cabd', 'cadb', 'cba', 'cbad',
 'cbda', 'cdab', 'cdba', 'dabc', 'dacb', 'dbac', 'dbca',
 'dcab', 'dcba']
```

semigroup_generators()

Return distinguished semigroup generators for `self`.

OUTPUT: a finite family

This method should be implemented by all semigroups in *FinitelyGeneratedSemigroups*.

EXAMPLES:

```
sage: S = FiniteSemigroups().example()
sage: S.semigroup_generators()
Family ('a', 'b', 'c', 'd')
```

succ_generators(*side='twosided'*)

Return the successor function of the `side`-sided Cayley graph of `self`.

This is a function that maps an element of `self` to all the products of `x` by a generator of this semigroup, where the product is taken on the left, right, or both sides.

INPUT:

- `side`: “left”, “right”, or “twosided”

Todo: Design choice:

- find a better name for this method
 - should we return a set? a family?
-

EXAMPLES:

```
sage: S = FiniteSemigroups().example()
sage: S.succ_generators("left" )(S('ca'))
('ac', 'bca', 'ca', 'dca')
sage: S.succ_generators("right" )(S('ca'))
('ca', 'cab', 'ca', 'cad')
sage: S.succ_generators("twosided" )(S('ca'))
('ac', 'bca', 'ca', 'dca', 'ca', 'cab', 'ca', 'cad')
```

example()

EXAMPLES:

```
sage: Semigroups().FinitelyGenerated().example()
An example of a semigroup: the free semigroup generated
by ('a', 'b', 'c', 'd')
```

extra_super_categories()

State that a finitely generated semigroup is endowed with a default enumeration.

EXAMPLES:

```
sage: Semigroups().FinitelyGenerated().extra_super_categories()
[Category of enumerated sets]
```

3.70 Function fields

class `sage.categories.function_fields.FunctionFields`(*s=None*)

Bases: `sage.categories.category.Category`

The category of function fields.

EXAMPLES:

We create the category of function fields:

```
sage: C = FunctionFields()
sage: C
Category of function fields
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

super_categories()

Returns the Category of which this is a direct sub-Category For a list off all super categories see `all_super_categories`

EXAMPLES:

```
sage: FunctionFields().super_categories()
[Category of fields]
```

3.71 G-Sets

class `sage.categories.g_sets.GSets(G)`

Bases: `sage.categories.category.Category`

The category of G -sets, for a group G .

EXAMPLES:

```
sage: S = SymmetricGroup(3)
sage: GSets(S)
Category of G-sets for Symmetric group of order 3! as a permutation group
```

TODO: should this derive from `Category_over_base`?

classmethod `an_instance()`

Returns an instance of this class.

EXAMPLES:

```
sage: GSets.an_instance() # indirect doctest
Category of G-sets for Symmetric group of order 8! as a permutation group
```

super_categories()

EXAMPLES:

```
sage: GSets(SymmetricGroup(8)).super_categories()
[Category of sets]
```

3.72 Gcd domains

class `sage.categories.gcd_domains.GcdDomains(s=None)`

Bases: `sage.categories.category_singleton.Category_singleton`

The category of gcd domains domains where gcd can be computed but where there is no guarantee of factorisation into irreducibles

EXAMPLES:

```
sage: GcdDomains()
Category of gcd domains
sage: GcdDomains().super_categories()
[Category of integral domains]
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

additional_structure()

Return `None`.

Indeed, the category of gcd domains defines no additional structure: a ring morphism between two gcd domains is a gcd domain morphism.

See also:

`Category.additional_structure()`

EXAMPLES:

```
sage: GcdDomains().additional_structure()
```

`super_categories()`

EXAMPLES:

```
sage: GcdDomains().super_categories()
[Category of integral domains]
```

3.73 Generalized Coxeter Groups

`class sage.categories.generalized_coxeter_groups.GeneralizedCoxeterGroups(s=None)`

Bases: `sage.categories.category_singleton.Category_singleton`

The category of generalized Coxeter groups.

A generalized Coxeter group is a group with a presentation of the following form:

$$\langle s_i \mid s_i^{p_i}, s_i s_j \cdots = s_j s_i \cdots \rangle,$$

where $p_i > 1$, $i \in I$, and the factors in the braid relation occur $m_{ij} = m_{ji}$ times for all $i \neq j \in I$.

EXAMPLES:

```
sage: from sage.categories.generalized_coxeter_groups import _
↪ GeneralizedCoxeterGroups
sage: C = GeneralizedCoxeterGroups(); C
Category of generalized coxeter groups
```

`class Finite(base_category)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of finite generalized Coxeter groups.

`extra_super_categories()`

Implement that a finite generalized Coxeter group is a well-generated complex reflection group.

EXAMPLES:

```
sage: from sage.categories.generalized_coxeter_groups import _
↪ GeneralizedCoxeterGroups
sage: from sage.categories.complex_reflection_groups import _
↪ ComplexReflectionGroups

sage: Cat = GeneralizedCoxeterGroups().Finite()
sage: Cat.extra_super_categories()
[Category of well generated finite complex reflection groups]
sage: Cat.is_subcategory(ComplexReflectionGroups().Finite().WellGenerated())
True
```

additional_structure()

Return None.

Indeed, all the structure generalized Coxeter groups have in addition to groups (simple reflections, ...) is already defined in the super category.

See also:

Category.additional_structure()

EXAMPLES:

```
sage: from sage.categories.generalized_coxeter_groups import GeneralizedCoxeterGroups
sage: GeneralizedCoxeterGroups().additional_structure()
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.generalized_coxeter_groups import GeneralizedCoxeterGroups
sage: GeneralizedCoxeterGroups().super_categories()
[Category of complex reflection or generalized coxeter groups]
```

3.74 Graded Algebras

class `sage.categories.graded_algebras.GradedAlgebras`(*base_category*)

Bases: *sage.categories.graded_modules.GradedModulesCategory*

The category of graded algebras

EXAMPLES:

```
sage: GradedAlgebras(ZZ)
Category of graded algebras over Integer Ring
sage: GradedAlgebras(ZZ).super_categories()
[Category of filtered algebras over Integer Ring,
Category of graded modules over Integer Ring]
```

class `ElementMethods`

Bases: object

class `ParentMethods`

Bases: object

graded_algebra()

Return the associated graded algebra to self.

Since self is already graded, this just returns self.

EXAMPLES:

```
sage: m = SymmetricFunctions(QQ).m()
sage: m.graded_algebra() is m
True
```

class `SignedTensorProducts`(*category*, *args)

Bases: *sage.categories.signed_tensor.SignedTensorProductsCategory*

extra_super_categories()

EXAMPLES:

```
sage: Algebras(QQ).Graded().SignedTensorProducts().extra_super_categories()
[Category of graded algebras over Rational Field]
sage: Algebras(QQ).Graded().SignedTensorProducts().super_categories()
[Category of graded algebras over Rational Field]
```

Meaning: a signed tensor product of algebras is an algebra

class SubcategoryMethods

Bases: object

SignedTensorProducts()

Return the full subcategory of objects of `self` constructed as signed tensor products.

See also:

- [SignedTensorProductsCategory](#)
- [CovariantFunctorialConstruction](#)

EXAMPLES:

```
sage: AlgebrasWithBasis(QQ).Graded().SignedTensorProducts()
Category of signed tensor products of graded algebras with basis
over Rational Field
```

3.75 Graded algebras with basis

class `sage.categories.graded_algebras_with_basis.GradedAlgebrasWithBasis`(*base_category*)

Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of graded algebras with a distinguished basis

EXAMPLES:

```
sage: C = GradedAlgebrasWithBasis(ZZ); C
Category of graded algebras with basis over Integer Ring
sage: sorted(C.super_categories(), key=str)
[Category of filtered algebras with basis over Integer Ring,
Category of graded algebras over Integer Ring,
Category of graded modules with basis over Integer Ring]
```

class ElementMethods

Bases: object

class ParentMethods

Bases: object

graded_algebra()

Return the associated graded algebra to `self`.

This is `self`, because `self` is already graded. See `graded_algebra()` for the general behavior of this method, and see [AssociatedGradedAlgebra](#) for the definition and properties of associated graded algebras.

EXAMPLES:

```
sage: m = SymmetricFunctions(QQ).m()
sage: m.graded_algebra() is m
True
```

class SignedTensorProducts(*category*, *args)

Bases: *sage.categories.signed_tensor.SignedTensorProductsCategory*

The category of algebras with basis constructed by signed tensor product of algebras with basis.

class ParentMethods

Bases: object

Implements operations on tensor products of super algebras with basis.

one_basis()

Return the index of the one of this signed tensor product of algebras, as per *AlgebrasWithBasis.ParentMethods.one_basis*.

It is the tuple whose operands are the indices of the ones of the operands, as returned by their *one_basis()* methods.

EXAMPLES:

```
sage: A.<x,y> = ExteriorAlgebra(QQ)
sage: A.one_basis()
()
sage: B = tensor((A, A, A))
sage: B.one_basis()
(((), (), ()))
sage: B.one()
1 # 1 # 1
```

product_on_basis(*t0*, *t1*)

The product of the algebra on the basis, as per *AlgebrasWithBasis.ParentMethods.product_on_basis*.

EXAMPLES:

Test the sign in the super tensor product:

```
sage: A = SteenrodAlgebra(3)
sage: x = A.Q(0)
sage: y = x.coproduct()
sage: y^2
0
```

TODO: optimize this implementation!

extra_super_categories()

EXAMPLES:

```
sage: Cat = AlgebrasWithBasis(QQ).Graded()
sage: Cat.SignedTensorProducts().extra_super_categories()
[Category of graded algebras with basis over Rational Field]
sage: Cat.SignedTensorProducts().super_categories()
[Category of graded algebras with basis over Rational Field,
Category of signed tensor products of graded algebras over Rational Field]
```

3.76 Graded bialgebras

`sage.categories.graded_bialgebras.GradedBialgebras(base_ring)`
 The category of graded bialgebras

EXAMPLES:

```
sage: C = GradedBialgebras(QQ); C
Join of Category of graded algebras over Rational Field
and Category of bialgebras over Rational Field
and Category of graded coalgebras over Rational Field
sage: C is Bialgebras(QQ).Graded()
True
```

3.77 Graded bialgebras with basis

`sage.categories.graded_bialgebras_with_basis.GradedBialgebrasWithBasis(base_ring)`
 The category of graded bialgebras with a distinguished basis

EXAMPLES:

```
sage: C = GradedBialgebrasWithBasis(QQ); C
Join of Category of ...
sage: sorted(C.super_categories(), key=str)
[Category of bialgebras with basis over Rational Field,
Category of graded algebras with basis over Rational Field,
Category of graded coalgebras with basis over Rational Field]
```

3.78 Graded Coalgebras

`class sage.categories.graded_coalgebras.GradedCoalgebras(base_category)`
 Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of graded coalgebras

EXAMPLES:

```
sage: C = GradedCoalgebras(QQ); C
Category of graded coalgebras over Rational Field
sage: C is Coalgebras(QQ).Graded()
True
```

`class SignedTensorProducts(category, *args)`
 Bases: `sage.categories.signed_tensor.SignedTensorProductsCategory`

`extra_super_categories()`

EXAMPLES:

```
sage: Coalgebras(QQ).Graded().SignedTensorProducts().extra_super_
categories()
[Category of graded coalgebras over Rational Field]
```

(continues on next page)

(continued from previous page)

```
sage: Coalgebras(QQ).Graded().SignedTensorProducts().super_categories()
[Category of graded coalgebras over Rational Field]
```

Meaning: a signed tensor product of coalgebras is a coalgebra

class SubcategoryMethods

Bases: object

SignedTensorProducts()

Return the full subcategory of objects of `self` constructed as signed tensor products.

See also:

- [SignedTensorProductsCategory](#)
- [CovariantFunctorialConstruction](#)

EXAMPLES:

```
sage: CoalgebrasWithBasis(QQ).Graded().SignedTensorProducts()
Category of signed tensor products of graded coalgebras with basis
over Rational Field
```

3.79 Graded coalgebras with basis

class `sage.categories.graded_coalgebras_with_basis.GradedCoalgebrasWithBasis`(*base_category*)

Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of graded coalgebras with a distinguished basis.

EXAMPLES:

```
sage: C = GradedCoalgebrasWithBasis(QQ); C
Category of graded coalgebras with basis over Rational Field
sage: C is Coalgebras(QQ).WithBasis().Graded()
True
```

class `SignedTensorProducts`(*category*, *args)

Bases: `sage.categories.signed_tensor.SignedTensorProductsCategory`

The category of coalgebras with basis constructed by signed tensor product of coalgebras with basis.

`extra_super_categories()`

EXAMPLES:

```
sage: Cat = CoalgebrasWithBasis(QQ).Graded()
sage: Cat.SignedTensorProducts().extra_super_categories()
[Category of graded coalgebras with basis over Rational Field]
sage: Cat.SignedTensorProducts().super_categories()
[Category of graded coalgebras with basis over Rational Field,
Category of signed tensor products of graded coalgebras over Rational
↪Field]
```

3.80 Graded Hopf algebras

`sage.categories.graded_hopf_algebras.GradedHopfAlgebras`(*base_ring*)
The category of graded Hopf algebras.

EXAMPLES:

```
sage: C = GradedHopfAlgebras(QQ); C
Join of Category of hopf algebras over Rational Field
      and Category of graded algebras over Rational Field
      and Category of graded coalgebras over Rational Field
sage: C is HopfAlgebras(QQ).Graded()
True
```

Note: This is not a graded Hopf algebra as is typically defined in algebraic topology as the product in the tensor square $(x \otimes y)(a \otimes b) = (xa) \otimes (yb)$ does not carry an additional sign. For this, instead use *super Hopf algebras*.

3.81 Graded Hopf algebras with basis

`class sage.categories.graded_hopf_algebras_with_basis.GradedHopfAlgebrasWithBasis`(*base_category*)
Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of graded Hopf algebras with a distinguished basis.

EXAMPLES:

```
sage: C = GradedHopfAlgebrasWithBasis(ZZ); C
Category of graded hopf algebras with basis over Integer Ring
sage: C.super_categories()
[Category of filtered hopf algebras with basis over Integer Ring,
 Category of graded algebras with basis over Integer Ring,
 Category of graded coalgebras with basis over Integer Ring]

sage: C is HopfAlgebras(ZZ).WithBasis().Graded()
True
sage: C is HopfAlgebras(ZZ).Graded().WithBasis()
False
```

`class Connected`(*base_category*)
Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

`class ElementMethods`

Bases: object

`class ParentMethods`

Bases: object

`antipode_on_basis`(*index*)

The antipode on the basis element indexed by *index*.

INPUT:

- *index* – an element of the index set

For a graded connected Hopf algebra, we can define an antipode recursively by

$$S(x) := - \sum_{x^L \neq x} S(x^L) \times x^R$$

when $|x| > 0$, and by $S(x) = x$ when $|x| = 0$.

counit_on_basis(*i*)

The default counit of a graded connected Hopf algebra.

INPUT:

- *i* – an element of the index set

OUTPUT:

- an element of the base ring

$$c(i) := \begin{cases} 1 & \text{if } i \text{ indexes the 1 of the algebra} \\ 0 & \text{otherwise.} \end{cases}$$

EXAMPLES:

```
sage: H = GradedHopfAlgebrasWithBasis(QQ).Connected().example()
sage: H.monomial(4).counit() # indirect doctest
0
sage: H.monomial(0).counit() # indirect doctest
1
```

example()

Return an example of a graded connected Hopf algebra with a distinguished basis.

class ElementMethods

Bases: object

class ParentMethods

Bases: object

class WithRealizations(*category*, **args*)

Bases: *sage.categories.with_realizations.WithRealizationsCategory*

super_categories()

EXAMPLES:

```
sage: GradedHopfAlgebrasWithBasis(QQ).WithRealizations().super_categories()
[Join of Category of hopf algebras over Rational Field
and Category of graded algebras over Rational Field
and Category of graded coalgebras over Rational Field]
```

example()

Return an example of a graded Hopf algebra with a distinguished basis.

3.82 Graded Lie Algebras

AUTHORS:

- Eero Hakavuori (2018-08-16): initial version

class *sage.categories.graded_lie_algebras*.**GradedLieAlgebras**(*base_category*)

Bases: *sage.categories.graded_modules.GradedModulesCategory*

Category of graded Lie algebras.

class Stratified(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

Category of stratified Lie algebras.

A graded Lie algebra $L = \bigoplus_{k=1}^M L_k$ (where possibly $M = \infty$) is called *stratified* if it is generated by L_1 ; in other words, we have $L_{k+1} = [L_1, L_k]$.

class FiniteDimensional(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

Category of finite dimensional stratified Lie algebras.

EXAMPLES:

```
sage: LieAlgebras(QQ).Graded().Stratified().FiniteDimensional()
Category of finite dimensional stratified Lie algebras over Rational Field
```

extra_super_categories()

Implements the fact that a finite dimensional stratified Lie algebra is nilpotent.

EXAMPLES:

```
sage: C = LieAlgebras(QQ).Graded().Stratified().FiniteDimensional()
sage: C.extra_super_categories()
[Category of nilpotent Lie algebras over Rational Field]
sage: C is C.Nilpotent()
True
sage: C.is_subcategory(LieAlgebras(QQ).Nilpotent())
True
```

class SubcategoryMethods

Bases: object

Stratified()

Return the full subcategory of stratified objects of self.

A Lie algebra is stratified if it is graded and generated as a Lie algebra by its component of degree one.

EXAMPLES:

```
sage: LieAlgebras(QQ).Graded().Stratified()
Category of stratified Lie algebras over Rational Field
```

3.83 Graded Lie Algebras With Basis

class *sage.categories.graded_lie_algebras_with_basis.GradedLieAlgebrasWithBasis*(*base_category*)

Bases: *sage.categories.graded_modules.GradedModulesCategory*

The category of graded Lie algebras with a distinguished basis.

EXAMPLES:

```
sage: C = LieAlgebras(ZZ).WithBasis().Graded(); C
Category of graded lie algebras with basis over Integer Ring
sage: C.super_categories()
[Category of graded modules with basis over Integer Ring,
```

(continues on next page)

(continued from previous page)

```
Category of lie algebras with basis over Integer Ring,
Category of graded Lie algebras over Integer Ring]
```

```
sage: C is LieAlgebras(ZZ).WithBasis().Graded()
True
sage: C is LieAlgebras(ZZ).Graded().WithBasis()
False
```

FiniteDimensional

alias of `sage.categories.finite_dimensional_graded_lie_algebras_with_basis.FiniteDimensionalGradedLieAlgebrasWithBasis`

3.84 Graded Lie Conformal Algebras

AUTHORS:

- Reimundo Heluani (2019-10-05): Initial implementation.

```
class sage.categories.graded_lie_conformal_algebras.GradedLieConformalAlgebras(base_category)
Bases: sage.categories.graded_lie_conformal_algebras.GradedLieConformalAlgebrasCategory
```

The category of graded Lie conformal algebras.

EXAMPLES:

```
sage: C = LieConformalAlgebras(QQbar).Graded(); C
Category of H-graded Lie conformal algebras over Algebraic Field

sage: CS = LieConformalAlgebras(QQ).Graded().Super(); CS
Category of H-graded super Lie conformal algebras over Rational Field
sage: CS is LieConformalAlgebras(QQ).Super().Graded()
True
```

```
class sage.categories.graded_lie_conformal_algebras.GradedLieConformalAlgebrasCategory(base_category)
Bases: sage.categories.graded_modules.GradedModulesCategory
```

Super(*base_ring=None*)

Return the super-analogue category of self.

INPUT:

- `base_ring` – this is ignored

EXAMPLES:

```
sage: C = LieConformalAlgebras(QQbar)
sage: C.Graded().Super() is C.Super().Graded()
True
sage: Cp = C.WithBasis()
sage: Cp.Graded().Super() is Cp.Super().Graded()
True
```

3.85 Graded modules

class `sage.categories.graded_modules.GradedModules`(*base_category*)

Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of graded modules.

We consider every graded module $M = \bigoplus_i M_i$ as a filtered module under the (natural) filtration given by

$$F_i = \bigoplus_{j < i} M_j.$$

EXAMPLES:

```
sage: GradedModules(ZZ)
Category of graded modules over Integer Ring
sage: GradedModules(ZZ).super_categories()
[Category of filtered modules over Integer Ring]
```

The category of graded modules defines the graded structure which shall be preserved by morphisms:

```
sage: Modules(ZZ).Graded().additional_structure()
Category of graded modules over Integer Ring
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

class `sage.categories.graded_modules.GradedModulesCategory`(*base_category*)

Bases: `sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory`,
`sage.categories.category_types.Category_over_base_ring`

EXAMPLES:

```
sage: C = GradedAlgebras(QQ)
sage: C
Category of graded algebras over Rational Field
sage: C.base_category()
Category of algebras over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of filtered algebras over Rational Field,
Category of graded vector spaces over Rational Field]

sage: AlgebrasWithBasis(QQ).Graded().base_ring()
Rational Field
sage: GradedHopfAlgebrasWithBasis(QQ).base_ring()
Rational Field
```

classmethod `default_super_categories`(*category*, **args*)

Return the default super categories of `category.Graded()`.

Mathematical meaning: every graded object (module, algebra, etc.) is a filtered object with the (implicit) filtration defined by $F_i = \bigoplus_{j \leq i} G_j$.

INPUT:

- `cls` – the class `GradedModulesCategory`
- `category` – a category

OUTPUT: a (join) category

In practice, this returns `category.Filtered()`, joined together with the result of the method `RegressiveCovariantConstructionCategory.default_super_categories()` (that is the join of `category.Filtered()` and `cat` for each `cat` in the super categories of `category`).

EXAMPLES:

Consider `category=Algebras()`, which has `cat=Modules()` as super category. Then, a grading of an algebra G is also a filtration of G :

```
sage: Algebras(QQ).Graded().super_categories()
[Category of filtered algebras over Rational Field,
 Category of graded vector spaces over Rational Field]
```

This resulted from the following call:

```
sage: sage.categories.graded_modules.GradedModulesCategory.default_super_
↪categories(Algebras(QQ))
Join of Category of filtered algebras over Rational Field
and Category of graded vector spaces over Rational Field
```

3.86 Graded modules with basis

class `sage.categories.graded_modules_with_basis.GradedModulesWithBasis`(*base_category*)
 Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of graded modules with a distinguished basis.

EXAMPLES:

```
sage: C = GradedModulesWithBasis(ZZ); C
Category of graded modules with basis over Integer Ring
sage: sorted(C.super_categories(), key=str)
[Category of filtered modules with basis over Integer Ring,
 Category of graded modules over Integer Ring]
sage: C is ModulesWithBasis(ZZ).Graded()
True
```

class `ElementMethods`

Bases: `object`

degree_negation()

Return the image of `self` under the degree negation automorphism of the graded module to which `self` belongs.

The degree negation is the module automorphism which scales every homogeneous element of degree k by $(-1)^k$ (for all k). This assumes that the module to which `self` belongs (that is, the module `self.parent()`) is \mathbb{Z} -graded.

EXAMPLES:

```

sage: E.<a,b> = ExteriorAlgebra(QQ)
sage: ((1 + a) * (1 + b)).degree_negation()
a*b - a - b + 1
sage: E.zero().degree_negation()
0

sage: P = GradedModulesWithBasis(ZZ).example(); P
An example of a graded module with basis: the free module on partitions.
↳over Integer Ring
sage: pbp = lambda x: P.basis()[Partition(list(x))]
sage: p = pbp([3,1]) - 2 * pbp([2]) + 4 * pbp([1])
sage: p.degree_negation()
-4*P[1] - 2*P[2] + P[3, 1]

```

class ParentMethods

Bases: object

degree_negation(*element*)Return the image of *element* under the degree negation automorphism of the graded module *self*.The degree negation is the module automorphism which scales every homogeneous element of degree k by $(-1)^k$ (for all k). This assumes that the module *self* is \mathbf{Z} -graded.

INPUT:

- *element* – element of the module *self*

EXAMPLES:

```

sage: E.<a,b> = ExteriorAlgebra(QQ)
sage: E.degree_negation((1 + a) * (1 + b))
a*b - a - b + 1
sage: E.degree_negation(E.zero())
0

sage: P = GradedModulesWithBasis(ZZ).example(); P
An example of a graded module with basis: the free module on partitions.
↳over Integer Ring
sage: pbp = lambda x: P.basis()[Partition(list(x))]
sage: p = pbp([3,1]) - 2 * pbp([2]) + 4 * pbp([1])
sage: P.degree_negation(p)
-4*P[1] - 2*P[2] + P[3, 1]

```

3.87 Graphs

class sage.categories.graphs.**Graphs**(*s=None*)Bases: *sage.categories.category_singleton.Category_singleton*

The category of graphs.

EXAMPLES:

```

sage: from sage.categories.graphs import Graphs
sage: C = Graphs(); C
Category of graphs

```


class Connected(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of connected graphs.

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: C = Graphs().Connected()
sage: TestSuite(C).run()
```

extra_super_categories()

Return the extra super categories of self.

A connected graph is also a metric space.

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: Graphs().Connected().super_categories() # indirect doctest
[Category of connected topological spaces,
Category of connected simplicial complexes,
Category of graphs,
Category of metric spaces]
```

class ParentMethods

Bases: object

dimension()

Return the dimension of self as a CW complex.

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: C.dimension()
1
```

edges()

Return the edges of self.

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: C.edges()
[(0, 1), (1, 2), (2, 3), (3, 4), (4, 0)]
```

faces()

Return the faces of self.

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: sorted(C.faces(), key=lambda x: (x.dimension(), x.value))
[0, 1, 2, 3, 4, (0, 1), (1, 2), (2, 3), (3, 4), (4, 0)]
```

facets()

Return the facets of self.

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: C.facets()
[(0, 1), (1, 2), (2, 3), (3, 4), (4, 0)]
```

vertices()

Return the vertices of self.

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: C.vertices()
[0, 1, 2, 3, 4]
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: Graphs().super_categories()
[Category of simplicial complexes]
```

3.88 Group Algebras

This module implements the category of group algebras for arbitrary groups over arbitrary commutative rings. For details, see [sage.categories.algebra_functor](#).

AUTHOR:

- David Loeffler (2008-08-24): initial version
- Martin Raum (2009-08): update to use new coercion model – see [trac ticket #6670](#).
- John Palmieri (2011-07): more updates to coercion, categories, etc., group algebras constructed using `CombinatorialFreeModule` – see [trac ticket #6670](#).
- Nicolas M. Thiéry (2010-2017), Travis Scrimshaw (2017): generalization to a covariant functorial construction for monoid algebras, and beyond – see e.g. [trac ticket #18700](#).

class `sage.categories.group_algebras.GroupAlgebras`(*category*, **args*)

Bases: [sage.categories.algebra_functor.AlgebrasCategory](#)

The category of group algebras over a given base ring.

EXAMPLES:

```
sage: C = Groups().Algebras(ZZ); C
Category of group algebras over Integer Ring
sage: C.super_categories()
[Category of hopf algebras with basis over Integer Ring,
 Category of monoid algebras over Integer Ring]
```

We can also construct this category with:

```
sage: C is GroupAlgebras(ZZ)
True
```

Here is how to create the group algebra of a group G :

```
sage: G = DihedralGroup(5)
sage: QG = G.algebra(QQ); QG
Algebra of Dihedral group of order 10 as a permutation group over Rational Field
```

and an example of computation:

```
sage: g = G.an_element(); g
(1,4)(2,3)
sage: (QG.term(g) + 1)**3
4*(1) + 4*(1,4)(2,3)
```

Todo:

- Check which methods would be better located in `Monoid.Algebras` or `Groups.Finite.Algebras`.
-

class ElementMethods

Bases: object

central_form()

Return `self` expressed in the canonical basis of the center of the group algebra.

INPUT:

- `self` – an element of the center of the group algebra

OUTPUT:

- A formal linear combination of the conjugacy class representatives representing its coordinates in the canonical basis of the center. See `Groups.Algebras.ParentMethods.center_basis()` for details.

Warning:

- This method requires the underlying group to have a method `conjugacy_classes_representatives` (every permutation group has one, thanks GAP!).
- This method does not check that the element is indeed central. Use the method `Monoids.Algebras.ElementMethods.is_central()` for this purpose.
- This function has a complexity linear in the number of conjugacy classes of the group. One could easily implement a function whose complexity is linear in the size of the support of `self`.

EXAMPLES:

```
sage: QS3 = SymmetricGroup(3).algebra(QQ)
sage: A = QS3([2,3,1]) + QS3([3,1,2])
sage: A.central_form()
B[(1,2,3)]
sage: QS4 = SymmetricGroup(4).algebra(QQ)
sage: B = sum(len(s.cycle_type())*QS4(s) for s in Permutations(4))
```

(continues on next page)

(continued from previous page)

```
sage: B.central_form()
4*B[()] + 3*B[(1,2)] + 2*B[(1,2)(3,4)] + 2*B[(1,2,3)] + B[(1,2,3,4)]
```

The following test fails due to a bug involving combinatorial free modules and the coercion system (see [trac ticket #28544](#)):

```
sage: QG = GroupAlgebras(QQ).example(PermutationGroup([[ (1,2,3), (4,5) ], [(3,
↪4)]]))
sage: s = sum(i for i in QG.basis())
sage: s.central_form() # not tested
B[()] + B[(4,5)] + B[(3,4,5)] + B[(2,3)(4,5)] + B[(2,3,4,5)] + B[(1,2)(3,4,
↪5)] + B[(1,2,3,4,5)]
```

See also:

- `Groups.Algebras.ParentMethods.center_basis()`
- `Monoids.Algebras.ElementMethods.is_central()`

class ParentMethods

Bases: object

antipode_on_basis(*g*)

Return the antipode of the element *g* of the basis.

Each basis element *g* is group-like, and so has antipode g^{-1} . This method is used to compute the antipode of any element.

EXAMPLES:

```
sage: A = CyclicPermutationGroup(6).algebra(ZZ); A
Algebra of Cyclic group of order 6 as a permutation group over Integer Ring
sage: g = CyclicPermutationGroup(6).an_element(); g
(1,2,3,4,5,6)
sage: A.antipode_on_basis(g)
(1,6,5,4,3,2)
sage: a = A.an_element(); a
() + 3*(1,2,3,4,5,6) + 3*(1,3,5)(2,4,6)
sage: a.antipode()
() + 3*(1,5,3)(2,6,4) + 3*(1,6,5,4,3,2)
```

center_basis()

Return a basis of the center of the group algebra.

The canonical basis of the center of the group algebra is the family $(f_\sigma)_{\sigma \in C}$, where C is any collection of representatives of the conjugacy classes of the group, and f_σ is the sum of the elements in the conjugacy class of σ .

OUTPUT:

- tuple of elements of self

Warning:

- This method requires the underlying group to have a method `conjugacy_classes` (every permutation group has one, thanks GAP!).

EXAMPLES:

```
sage: SymmetricGroup(3).algebra(QQ).center_basis()
((), (2,3) + (1,2) + (1,3), (1,2,3) + (1,3,2))
```

See also:

- `Groups.Algebras.ElementMethods.central_form()`
- `Monoids.Algebras.ElementMethods.is_central()`

`coproduct_on_basis(g)`

Return the coproduct of the element g of the basis.

Each basis element g is group-like. This method is used to compute the coproduct of any element.

EXAMPLES:

```
sage: A = CyclicPermutationGroup(6).algebra(ZZ); A
Algebra of Cyclic group of order 6 as a permutation group over Integer Ring
sage: g = CyclicPermutationGroup(6).an_element(); g
(1,2,3,4,5,6)
sage: A.coproduct_on_basis(g)
(1,2,3,4,5,6) # (1,2,3,4,5,6)
sage: a = A.an_element(); a
() + 3*(1,2,3,4,5,6) + 3*(1,3,5)(2,4,6)
sage: a.coproduct()
() # () + 3*(1,2,3,4,5,6) # (1,2,3,4,5,6) + 3*(1,3,5)(2,4,6) # (1,3,5)(2,4,
↪6)
```

`counit(x)`

Return the counit of the element x of the group algebra.

This is the sum of all coefficients of x with respect to the standard basis of the group algebra.

EXAMPLES:

```
sage: A = CyclicPermutationGroup(6).algebra(ZZ); A
Algebra of Cyclic group of order 6 as a permutation group over Integer Ring
sage: a = A.an_element(); a
() + 3*(1,2,3,4,5,6) + 3*(1,3,5)(2,4,6)
sage: a.counit()
7
```

`counit_on_basis(g)`

Return the counit of the element g of the basis.

Each basis element g is group-like, and so has counit 1. This method is used to compute the counit of any element.

EXAMPLES:

```
sage: A=CyclicPermutationGroup(6).algebra(ZZ);A
Algebra of Cyclic group of order 6 as a permutation group over Integer Ring
sage: g=CyclicPermutationGroup(6).an_element();g
(1,2,3,4,5,6)
sage: A.counit_on_basis(g)
1
```

`group()`

Return the underlying group of the group algebra.

EXAMPLES:

```
sage: GroupAlgebras(QQ).example(GL(3, GF(11))).group()
General Linear Group of degree 3 over Finite Field of size 11
sage: SymmetricGroup(10).algebra(QQ).group()
Symmetric group of order 10! as a permutation group
```

is_integral_domain(*proof=True*)

Return True if self is an integral domain.

This is false unless `self.base_ring()` is an integral domain, and even then it is false unless `self.group()` has no nontrivial elements of finite order. I don't know if this condition suffices, but it obviously does if the group is abelian and finitely generated.

EXAMPLES:

```
sage: GroupAlgebra(SymmetricGroup(2)).is_integral_domain()
False
sage: GroupAlgebra(SymmetricGroup(1)).is_integral_domain()
True
sage: GroupAlgebra(SymmetricGroup(1), IntegerModRing(4)).is_integral_
↳domain()
False
sage: GroupAlgebra(AbelianGroup(1)).is_integral_domain()
True
sage: GroupAlgebra(AbelianGroup(2, [0,2])).is_integral_domain()
False
sage: GroupAlgebra(GL(2, ZZ)).is_integral_domain() # not implemented
False
```

example(*G=None*)

Return an example of group algebra.

EXAMPLES:

```
sage: GroupAlgebras(QQ['x']).example()
Algebra of Dihedral group of order 8 as a permutation group over Univariate_
↳Polynomial Ring in x over Rational Field
```

An other group can be specified as optional argument:

```
sage: GroupAlgebras(QQ).example(AlternatingGroup(4))
Algebra of Alternating group of order 4!/2 as a permutation group over Rational_
↳Field
```

extra_super_categories()

Implement the fact that the algebra of a group is a Hopf algebra.

EXAMPLES:

```
sage: C = Groups().Algebras(QQ)
sage: C.extra_super_categories()
[Category of hopf algebras over Rational Field]
sage: sorted(C.super_categories(), key=str)
[Category of hopf algebras with basis over Rational Field,
Category of monoid algebras over Rational Field]
```

3.89 Groupoid

class `sage.categories.groupoid.Groupoid(G=None)`

Bases: `sage.categories.category.CategoryWithParameters`

The category of groupoids, for a set (usually a group) G .

FIXME:

- Groupoid or Groupoids ?
- definition and link with [Wikipedia article Groupoid](#)
- Should Groupoid inherit from `Category_over_base`?

EXAMPLES:

```
sage: Groupoid(DihedralGroup(3))
Groupoid with underlying set Dihedral group of order 6 as a permutation group
```

classmethod `an_instance()`

Returns an instance of this class.

EXAMPLES:

```
sage: Groupoid.an_instance() # indirect doctest
Groupoid with underlying set Symmetric group of order 8! as a permutation group
```

super_categories()

EXAMPLES:

```
sage: Groupoid(DihedralGroup(3)).super_categories()
[Category of sets]
```

3.90 Groups

class `sage.categories.groups.Groups(base_category)`

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of (multiplicative) groups, i.e. monoids with inverses.

EXAMPLES:

```
sage: Groups()
Category of groups
sage: Groups().super_categories()
[Category of monoids, Category of inverse unital magmas]
```

Algebras

alias of `sage.categories.group_algebras.GroupAlgebras`

class `CartesianProducts(category, *args)`

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

The category of groups constructed as Cartesian products of groups.

This construction gives the direct product of groups. See [Wikipedia article Direct_product](#) and [Wikipedia article Direct_product_of_groups](#) for more information.

class ElementMethods

Bases: object

multiplicative_order()

Return the multiplicative order of this element.

EXAMPLES:

```
sage: G1 = SymmetricGroup(3)
sage: G2 = SL(2,3)
sage: G = cartesian_product([G1,G2])
sage: G((G1.gen(0), G2.gen(1))).multiplicative_order()
12
```

class ParentMethods

Bases: object

group_generators()

Return the group generators of self.

EXAMPLES:

```
sage: C5 = CyclicPermutationGroup(5)
sage: C4 = CyclicPermutationGroup(4)
sage: S4 = SymmetricGroup(3)
sage: C = cartesian_product([C5, C4, S4])
sage: C.group_generators()
Family (((1,2,3,4,5), (), ()),
        (((), (1,2,3,4), ()),
        (((), (), (1,2)),
        (((), (), (2,3))))
```

We check the other portion of [trac ticket #16718](#) is fixed:

```
sage: len(C.j_classes())
1
```

An example with an infinitely generated group (a better output is needed):

```
sage: G = Groups.free([1,2])
sage: H = Groups.free(ZZ)
sage: C = cartesian_product([G, H])
sage: C.monoid_generators()
Lazy family (gen(i))_{i in The Cartesian product of (...)}
```

order()

Return the cardinality of self.

EXAMPLES:

```
sage: C = cartesian_product([SymmetricGroup(10), SL(2,GF(3))])
sage: C.order()
87091200
```

Todo: this method is just here to prevent `FiniteGroups.ParentMethods` to call `_cardinality_from_iterator`.

extra_super_categories()

A Cartesian product of groups is endowed with a natural group structure.

EXAMPLES:

```
sage: C = Groups().CartesianProducts()
sage: C.extra_super_categories()
[Category of groups]
sage: sorted(C.super_categories(), key=str)
[Category of Cartesian products of inverse unital magmas,
Category of Cartesian products of monoids,
Category of groups]
```

class Commutative(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

Category of commutative (abelian) groups.

A group G is *commutative* if $xy = yx$ for all $x, y \in G$.

static free(*index_set=None, names=None, **kwds*)

Return the free commutative group.

INPUT:

- *index_set* – (optional) an index set for the generators; if an integer, then this represents $\{0, 1, \dots, n - 1\}$
- *names* – a string or list/tuple/iterable of strings (default: 'x'); the generator names or name prefix

EXAMPLES:

```
sage: Groups.Commutative.free(index_set=ZZ)
Free abelian group indexed by Integer Ring
sage: Groups().Commutative().free(ZZ)
Free abelian group indexed by Integer Ring
sage: Groups().Commutative().free(5)
Multiplicative Abelian group isomorphic to Z x Z x Z x Z x Z
sage: F.<x,y,z> = Groups().Commutative().free(); F
Multiplicative Abelian group isomorphic to Z x Z x Z
```

class ElementMethods

Bases: object

conjugacy_class()

Return the conjugacy class of self.

EXAMPLES:

```
sage: D = DihedralGroup(5)
sage: g = D((1,3,5,2,4))
sage: g.conjugacy_class()
Conjugacy class of (1,3,5,2,4) in Dihedral group of order 10 as a
↪ permutation group

sage: H = MatrixGroup([matrix(GF(5),2,[1,2,-1,1]), matrix(GF(5),2,[1,1,
↪ 0,1])])
sage: h = H(matrix(GF(5),2,[1,2,-1,1]))
sage: h.conjugacy_class()
Conjugacy class of [1 2]
```

(continues on next page)

(continued from previous page)

```

[4 1] in Matrix group over Finite Field of size 5 with 2 generators (
[1 2]  [1 1]
[4 1], [0 1]
)

sage: G = SL(2, GF(2))
sage: g = G.gens()[0]
sage: g.conjugacy_class()
Conjugacy class of [1 1]
[0 1] in Special Linear Group of degree 2 over Finite Field of size 2

sage: G = SL(2, QQ)
sage: g = G([[1,1],[0,1]])
sage: g.conjugacy_class()
Conjugacy class of [1 1]
[0 1] in Special Linear Group of degree 2 over Rational Field

```

Finitealias of `sage.categories.finite_groups.FiniteGroups`**Lie**alias of `sage.categories.lie_groups.LieGroups`**class ParentMethods**

Bases: object

cayley_table(names='letters', elements=None)

Return the “multiplication” table of this multiplicative group, which is also known as the “Cayley table”.

Note: The order of the elements in the row and column headings is equal to the order given by the table’s `column_keys()` method. The association between the actual elements and the names/symbols used in the table can also be retrieved as a dictionary with the `translation()` method.

For groups, this routine should behave identically to the `multiplication_table()` method for magmas, which applies in greater generality.

INPUT:

- **names** - the type of names used, values are:
 - 'letters' - lowercase ASCII letters are used for a base 26 representation of the elements' positions in the list given by `list()`, padded to a common width with leading 'a's.
 - 'digits' - base 10 representation of the elements' positions in the list given by `column_keys()`, padded to a common width with leading zeros.
 - 'elements' - the string representations of the elements themselves.
 - a list - a list of strings, where the length of the list equals the number of elements.
- **elements** - default = None. A list of elements of the group, in forms that can be coerced into the structure, eg. their string representations. This may be used to impose an alternate ordering on the elements, perhaps when this is used in the context of a particular structure. The default is to use whatever ordering is provided by the the group, which is reported by the `column_keys()` method. Or the `elements` can be a subset which is closed under the operation. In particular, this can be used when the base set is infinite.

OUTPUT: An object representing the multiplication table. This is an `OperationTable` object and even more documentation can be found there.

EXAMPLES:

Permutation groups, matrix groups and abelian groups can all compute their multiplication tables.

```
sage: G = DiCyclicGroup(3)
sage: T = G.cayley_table()
sage: T.column_keys()
((), (5,6,7), ..., (1,4,2,3)(5,7))
sage: T
* a b c d e f g h i j k l
+-----+
a| a b c d e f g h i j k l
b| b c a e f d i g h l j k
c| c a b f d e h i g k l j
d| d e f a b c j k l g h i
e| e f d b c a l j k i g h
f| f d e c a b k l j h i g
g| g h i j k l d e f a b c
h| h i g k l j f d e c a b
i| i g h l j k e f d b c a
j| j k l g h i a b c d e f
k| k l j h i g c a b f d e
l| l j k i g h b c a e f d
```

```
sage: M = SL(2, 2)
sage: M.cayley_table()
* a b c d e f
+-----+
a| a b c d e f
b| b a d c f e
c| c e a f b d
d| d f b e a c
e| e c f a d b
f| f d e b c a
```

```
sage: A = AbelianGroup([2, 3])
sage: A.cayley_table()
* a b c d e f
+-----+
a| a b c d e f
b| b c a e f d
c| c a b f d e
d| d e f a b c
e| e f d b c a
f| f d e c a b
```

Lowercase ASCII letters are the default symbols used for the table, but you can also specify the use of decimal digit strings, or provide your own strings (in the proper order if they have meaning). Also, if the elements themselves are not too complex, you can choose to just use the string representations of the elements themselves.

```
sage: C=CyclicPermutationGroup(11)
sage: C.cayley_table(names='digits')
* 00 01 02 03 04 05 06 07 08 09 10
```

(continues on next page)

(continued from previous page)

```

+-----+
00| 00 01 02 03 04 05 06 07 08 09 10
01| 01 02 03 04 05 06 07 08 09 10 00
02| 02 03 04 05 06 07 08 09 10 00 01
03| 03 04 05 06 07 08 09 10 00 01 02
04| 04 05 06 07 08 09 10 00 01 02 03
05| 05 06 07 08 09 10 00 01 02 03 04
06| 06 07 08 09 10 00 01 02 03 04 05
07| 07 08 09 10 00 01 02 03 04 05 06
08| 08 09 10 00 01 02 03 04 05 06 07
09| 09 10 00 01 02 03 04 05 06 07 08
10| 10 00 01 02 03 04 05 06 07 08 09

```

```

sage: G=QuaternionGroup()
sage: names=['1', 'I', '-1', '-I', 'J', '-K', '-J', 'K']
sage: G.cayley_table(names=names)
*   1  I -1 -I  J -K -J  K
+-----+
1|  1  I -1 -I  J -K -J  K
I|  I -1 -I  1  K  J -K -J
-1| -1 -I  1  I -J  K  J -K
-I| -I  1  I -1 -K -J  K  J
 J|  J -K -J  K -1 -I  1  I
-K| -K -J  K  J  I -1 -I  1
-J| -J  K  J -K  1  I -1 -I
 K|  K  J -K -J -I  1  I -1

```

```

sage: A=AbelianGroup([2,2])
sage: A.cayley_table(names='elements')
*       1      f1      f0 f0*f1
+-----+
1|       1      f1      f0 f0*f1
f1|      f1       1 f0*f1      f0
f0|      f0 f0*f1       1      f1
f0*f1| f0*f1      f0      f1       1

```

The `change_names()` routine behaves similarly, but changes an existing table “in-place.”

```

sage: G=AlternatingGroup(3)
sage: T=G.cayley_table()
sage: T.change_names('digits')
sage: T
*   0 1 2
+-----+
0| 0 1 2
1| 1 2 0
2| 2 0 1

```

For an infinite group, you can still work with finite sets of elements, provided the set is closed under multiplication. Elements will be coerced into the group as part of setting up the table.

```

sage: G=SL(2,ZZ)
sage: G
Special Linear Group of degree 2 over Integer Ring
sage: identity = matrix(ZZ, [[1,0], [0,1]])
sage: G.cayley_table(elements=[identity, -identity])
*   a b
  +----
a|  a b
b|  b a

```

The `OperationTable` class provides even greater flexibility, including changing the operation. Here is one such example, illustrating the computation of commutators. `commutator` is defined as a function of two variables, before being used to build the table. From this, the commutator subgroup seems obvious, and creating a Cayley table with just these three elements confirms that they form a closed subset in the group.

```

sage: from sage.matrix.operation_table import OperationTable
sage: G = DiCyclicGroup(3)
sage: commutator = lambda x, y: x*y*x^-1*y^-1
sage: T = OperationTable(G, commutator)
sage: T
.   a b c d e f g h i j k l
+-----
a|  a a a a a a a a a a a
b|  a a a a a a c c c c c
c|  a a a a a a b b b b b
d|  a a a a a a a a a a a
e|  a a a a a a c c c c c
f|  a a a a a a b b b b b
g|  a b c a b c a c b a c b
h|  a b c a b c b a c b a c
i|  a b c a b c c b a c b a
j|  a b c a b c a c b a c b
k|  a b c a b c b a c b a c
l|  a b c a b c c b a c b a

sage: trans = T.translation()
sage: comm = [trans['a'], trans['b'], trans['c']]
sage: comm
[(), (5,6,7), (5,7,6)]
sage: P = G.cayley_table(elements=comm)
sage: P
*   a b c
  +-----
a|  a b c
b|  b c a
c|  c a b

```

Todo: Arrange an ordering of elements into cosets of a normal subgroup close to size \sqrt{n} . Then the quotient group structure is often apparent in the table. See comments on [trac ticket #7555](#).

AUTHOR:

- Rob Beezer (2010-03-15)

conjugacy_class(*g*)

Return the conjugacy class of the element *g*.

This is a fall-back method for groups not defined over GAP.

EXAMPLES:

```
sage: A = AbelianGroup([2,2])
sage: c = A.conjugacy_class(A.an_element())
sage: type(c)
<class 'sage.groups.conjugacy_classes.ConjugacyClass_with_category'>
```

group_generators()

Return group generators for self.

This default implementation calls `gens()`, for backward compatibility.

EXAMPLES:

```
sage: A = AlternatingGroup(4)
sage: A.group_generators()
Family ((2,3,4), (1,2,3))
```

holomorph()

The holomorph of a group

The holomorph of a group G is the semidirect product $G \rtimes_{id} Aut(G)$, where id is the identity function on $Aut(G)$, the automorphism group of G .

See [Wikipedia article Holomorph \(mathematics\)](#)

EXAMPLES:

```
sage: G = Groups().example()
sage: G.holomorph()
Traceback (most recent call last):
...
NotImplementedError: holomorph of General Linear Group of degree 4 over_
↳Rational Field not yet implemented
```

monoid_generators()

Return the generators of self as a monoid.

Let G be a group with generating set X . In general, the generating set of G as a monoid is given by $X \cup X^{-1}$, where X^{-1} is the set of inverses of X . If G is a finite group, then the generating set as a monoid is X .

EXAMPLES:

```
sage: A = AlternatingGroup(4)
sage: A.monoid_generators()
Family ((2,3,4), (1,2,3))
sage: F.<x,y> = FreeGroup()
sage: F.monoid_generators()
Family (x, y, x^-1, y^-1)
```

semidirect_product(*N*, *mapping*, *check=True*)

The semi-direct product of two groups

EXAMPLES:

```
sage: G = Groups().example()
sage: G.semidirect_product(G,Morphism(G,G))
Traceback (most recent call last):
...
NotImplementedError: semidirect product of General Linear Group of degree 4
↳over Rational Field and General Linear Group of degree 4 over Rational
↳Field not yet implemented
```

class Topological(*category, *args*)

Bases: *sage.categories.topological_spaces.TopologicalSpacesCategory*

Category of topological groups.

A topological group G is a group which has a topology such that multiplication and taking inverses are continuous functions.

REFERENCES:

- [Wikipedia article Topological_group](#)

example()

EXAMPLES:

```
sage: Groups().example()
General Linear Group of degree 4 over Rational Field
```

static free(*index_set=None, names=None, **kws*)

Return the free group.

INPUT:

- *index_set* – (optional) an index set for the generators; if an integer, then this represents $\{0, 1, \dots, n-1\}$
- *names* – a string or list/tuple/iterable of strings (default: 'x'); the generator names or name prefix

When the index set is an integer or only variable names are given, this returns `FreeGroup_class`, which currently has more features due to the interface with GAP than `IndexedFreeGroup`.

EXAMPLES:

```
sage: Groups.free(index_set=ZZ)
Free group indexed by Integer Ring
sage: Groups().free(ZZ)
Free group indexed by Integer Ring
sage: Groups().free(5)
Free Group on generators {x0, x1, x2, x3, x4}
sage: F.<x,y,z> = Groups().free(); F
Free Group on generators {x, y, z}
```

3.91 Hecke modules

class `sage.categories.hecke_modules.HeckeModules(R)`

Bases: `sage.categories.category_types.Category_module`

The category of Hecke modules.

A Hecke module is a module M over the anemic Hecke algebra, i.e., the Hecke algebra generated by Hecke operators T_n with n coprime to the level of M . (Every Hecke module defines a level function, which is a positive integer.) The reason we require that M only be a module over the anemic Hecke algebra is that many natural maps, e.g., degeneracy maps, Atkin-Lehner operators, etc., are T -module homomorphisms; but they are homomorphisms over the anemic Hecke algebra.

EXAMPLES:

We create the category of Hecke modules over \mathbb{Q} :

```
sage: C = HeckeModules(RationalField()); C
Category of Hecke modules over Rational Field
```

TODO: check that this is what we want:

```
sage: C.super_categories()
[Category of vector spaces with basis over Rational Field]
```

```
# [Category of vector spaces over Rational Field]
```

Note that the base ring can be an arbitrary commutative ring:

```
sage: HeckeModules(IntegerRing())
Category of Hecke modules over Integer Ring
sage: HeckeModules(FiniteField(5))
Category of Hecke modules over Finite Field of size 5
```

The base ring doesn't have to be a principal ideal domain:

```
sage: HeckeModules(PolynomialRing(IntegerRing(), 'x'))
Category of Hecke modules over Univariate Polynomial Ring in x over Integer Ring
```

class `Homsets(category, *args)`

Bases: `sage.categories.homsets.HomsetsCategory`

class `ParentMethods`

Bases: `object`

`extra_super_categories()`

class `ParentMethods`

Bases: `object`

`super_categories()`

EXAMPLES:

```
sage: HeckeModules(QQ).super_categories()
[Category of vector spaces with basis over Rational Field]
```


3.92 Highest Weight Crystals

class `sage.categories.highest_weight_crystals.HighestWeightCrystalHomset`(*X*, *Y*,
category=None)

Bases: `sage.categories.crystals.CrystalHomset`

The set of crystal morphisms from a highest weight crystal to another crystal.

See also:

See `sage.categories.crystals.CrystalHomset` for more information.

Element

alias of `HighestWeightCrystalMorphism`

class `sage.categories.highest_weight_crystals.HighestWeightCrystalMorphism`(*parent*, *on_gens*,
cartan_type=None,
virtualization=None,
scaling_factors=None,
gens=None,
check=True)

Bases: `sage.categories.crystals.CrystalMorphismByGenerators`

A virtual crystal morphism whose domain is a highest weight crystal.

INPUT:

- *parent* – a homset
- *on_gens* – a function or list that determines the image of the generators (if given a list, then this uses the order of the generators of the domain) of the domain under *self*
- *cartan_type* – (optional) a Cartan type; the default is the Cartan type of the domain
- *virtualization* – (optional) a dictionary whose keys are in the index set of the domain and whose values are lists of entries in the index set of the codomain
- *scaling_factors* – (optional) a dictionary whose keys are in the index set of the domain and whose values are scaling factors for the weight, ε and φ
- *gens* – (optional) a list of generators to define the morphism; the default is to use the highest weight vectors of the crystal
- *check* – (default: `True`) check if the crystal morphism is valid

class `sage.categories.highest_weight_crystals.HighestWeightCrystals`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of highest weight crystals.

A crystal is highest weight if it is acyclic; in particular, every connected component has a unique highest weight element, and that element generate the component.

EXAMPLES:

```
sage: C = HighestWeightCrystals()
sage: C
Category of highest weight crystals
sage: C.super_categories()
```

(continues on next page)

(continued from previous page)

```
[Category of crystals]
sage: C.example()
Highest weight crystal of type A_3 of highest weight omega_1
```

class ElementMethods

Bases: object

string_parameters(word=None)Return the string parameters of `self` corresponding to the reduced word `word`.

Given a reduced expression $w = s_{i_1} \cdots s_{i_k}$, the string parameters of $b \in B$ corresponding to w are (a_1, \dots, a_k) such that

$$\begin{aligned} e_{i_m}^{a_m} \cdots e_{i_1}^{a_1} b &\neq 0 \\ e_{i_m}^{a_m+1} \cdots e_{i_1}^{a_1} b &= 0 \end{aligned}$$

for all $1 \leq m \leq k$.

For connected components isomorphic to $B(\lambda)$ or $B(\infty)$, if $w = w_0$ is the longest element of the Weyl group, then the path determined by the string parametrization terminates at the highest weight vector.

INPUT:

- `word` – a word in the alphabet of the index set; if not specified and we are in finite type, then this will be some reduced expression for the long element determined by the Weyl group

EXAMPLES:

```
sage: B = crystals.infinity.NakajimaMonomials(['A', 3])
sage: mg = B.highest_weight_vector()
sage: w0 = [1, 2, 1, 3, 2, 1]
sage: mg.string_parameters(w0)
[0, 0, 0, 0, 0, 0]
sage: mg.f_string([1]).string_parameters(w0)
[1, 0, 0, 0, 0, 0]
sage: mg.f_string([1, 1, 1]).string_parameters(w0)
[3, 0, 0, 0, 0, 0]
sage: mg.f_string([1, 1, 1, 2, 2]).string_parameters(w0)
[1, 2, 2, 0, 0, 0]
sage: mg.f_string([1, 1, 1, 2, 2]) == mg.f_string([1, 1, 2, 2, 1])
True
sage: x = mg.f_string([1, 1, 1, 2, 2, 1, 3, 3, 2, 1, 1, 1])
sage: x.string_parameters(w0)
[4, 1, 1, 2, 2, 2]
sage: x.string_parameters([3, 2, 1, 3, 2, 3])
[2, 3, 7, 0, 0, 0]
sage: x == mg.f_string([1]*7 + [2]*3 + [3]*2)
True
```

```
sage: B = crystals.infinity.Tableaux("A5")
sage: b = B(rows=[[1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 3, 6, 6, 6, 6, 6, 6],
.....:             [2, 2, 2, 2, 2, 2, 2, 2, 4, 5, 5, 5, 6],
.....:             [3, 3, 3, 3, 3, 3, 3, 5],
.....:             [4, 4, 4, 6, 6, 6],
.....:             [5, 6]])
```

(continues on next page)

(continued from previous page)

```

sage: b.string_parameters([1,2,1,3,2,1,4,3,2,1,5,4,3,2,1])
[0, 1, 1, 1, 1, 0, 4, 4, 3, 0, 11, 10, 7, 7, 6]

sage: B = crystals.infinity.Tableaux("G2")
sage: b = B(rows=[[1,1,1,1,1,3,3,0,-3,-3,-2,-2,-1,-1,-1,-1],[2,3,3,3]])
sage: b.string_parameters([2,1,2,1,2,1])
[5, 13, 11, 15, 4, 4]
sage: b.string_parameters([1,2,1,2,1,2])
[7, 12, 15, 8, 10, 0]

```

```

sage: C = crystals.Tableaux(['C',2], shape=[2,1])
sage: mg = C.highest_weight_vector()
sage: lw = C.lowest_weight_vectors()[0]
sage: lw.string_parameters([1,2,1,2])
[1, 2, 3, 1]
sage: lw.string_parameters([2,1,2,1])
[1, 3, 2, 1]
sage: lw.e_string([2,1,1,1,2,2,1]) == mg
True
sage: lw.e_string([1,2,2,1,1,1,2]) == mg
True

```

class ParentMethods

Bases: object

connected_components_generators()

Returns the highest weight vectors of self

This default implementation selects among the module generators those that are highest weight, and caches the result. A crystal element b is highest weight if $e_i(b) = 0$ for all i in the index set.

EXAMPLES:

```

sage: C = crystals.Letters(['A',5])
sage: C.highest_weight_vectors()
(1,)

```

```

sage: C = crystals.Letters(['A',2])
sage: T = crystals.TensorProduct(C,C,C,generators=[[C(2),C(1),C(1)],[C(1),
↪C(2),C(1)])
sage: T.highest_weight_vectors()
([2, 1, 1], [1, 2, 1])

```

digraph(subset=None, index_set=None, depth=None)

Return the DiGraph associated to self.

INPUT:

- subset – (optional) a subset of vertices for which the digraph should be constructed
- index_set – (optional) the index set to draw arrows
- depth – the depth to draw; optional only for finite crystals

EXAMPLES:

```

sage: T = crystals.Tableaux(['A',2], shape=[2,1])
sage: T.digraph()

```

(continues on next page)

(continued from previous page)

```
Digraph on 8 vertices
sage: S = T.subcrystal(max_depth=2)
sage: len(S)
5
sage: G = T.digraph(subset=list(S))
sage: G.is_isomorphic(T.digraph(depth=2), edge_labels=True)
True
```

highest_weight_vector()

Returns the highest weight vector if there is a single one; otherwise, raises an error.

Caveat: this assumes that `highest_weight_vectors()` returns a list or tuple.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C.highest_weight_vector()
1
```

highest_weight_vectors()

Returns the highest weight vectors of `self`

This default implementation selects among the module generators those that are highest weight, and caches the result. A crystal element b is highest weight if $e_i(b) = 0$ for all i in the index set.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C.highest_weight_vectors()
(1,)
```

```
sage: C = crystals.Letters(['A', 2])
sage: T = crystals.TensorProduct(C, C, C, generators=[[C(2), C(1), C(1)], [C(1),
↪ C(2), C(1)]])
sage: T.highest_weight_vectors()
([2, 1, 1], [1, 2, 1])
```

lowest_weight_vectors()

Return the lowest weight vectors of `self`.

This default implementation selects among all elements of the crystal those that are lowest weight, and cache the result. A crystal element b is lowest weight if $f_i(b) = 0$ for all i in the index set.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C.lowest_weight_vectors()
(6,)
```

```
sage: C = crystals.Letters(['A', 2])
sage: T = crystals.TensorProduct(C, C, C, generators=[[C(2), C(1), C(1)], [C(1),
↪ C(2), C(1)]])
sage: T.lowest_weight_vectors()
([3, 2, 3], [3, 3, 2])
```

q_dimension(*q=None, prec=None, use_product=False*)

Return the q -dimension of self.

Let $B(\lambda)$ denote a highest weight crystal. Recall that the degree of the μ -weight space of $B(\lambda)$ (under the principal gradation) is equal to $\langle \rho^\vee, \lambda - \mu \rangle$ where $\langle \rho^\vee, \alpha_i \rangle = 1$ for all $i \in I$ (in particular, take $\rho^\vee = \sum_{i \in I} h_i$).

The q -dimension of a highest weight crystal $B(\lambda)$ is defined as

$$\dim_q B(\lambda) := \sum_{j \geq 0} \dim(B_j) q^j,$$

where B_j denotes the degree j portion of $B(\lambda)$. This can be expressed as the product

$$\dim_q B(\lambda) = \prod_{\alpha^\vee \in \Delta_+^\vee} \left(\frac{1 - q^{\langle \lambda + \rho, \alpha^\vee \rangle}}{1 - q^{\langle \rho, \alpha^\vee \rangle}} \right)^{\text{mult } \alpha},$$

where Δ_+^\vee denotes the set of positive coroots. Taking the limit as $q \rightarrow 1$ gives the dimension of $B(\lambda)$. For more information, see [Ka1990] Section 10.10.

INPUT:

- **q** – the (generic) parameter q
- **prec** – (default: None) The precision of the power series ring to use if the crystal is not known to be finite (i.e. the number of terms returned). If None, then the result is returned as a lazy power series.
- **use_product** – (default: False) if we have a finite crystal and True, use the product formula

EXAMPLES:

```

sage: C = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: qdim = C.q_dimension(); qdim
q^4 + 2*q^3 + 2*q^2 + 2*q + 1
sage: qdim(1)
8
sage: len(C) == qdim(1)
True
sage: C.q_dimension(use_product=True) == qdim
True
sage: C.q_dimension(prec=20)
q^4 + 2*q^3 + 2*q^2 + 2*q + 1
sage: C.q_dimension(prec=2)
2*q + 1

sage: R.<t> = QQ[]
sage: C.q_dimension(q=t^2)
t^8 + 2*t^6 + 2*t^4 + 2*t^2 + 1

sage: C = crystals.Tableaux(['A', 2], shape=[5, 2])
sage: C.q_dimension()
q^10 + 2*q^9 + 4*q^8 + 5*q^7 + 6*q^6 + 6*q^5
+ 6*q^4 + 5*q^3 + 4*q^2 + 2*q + 1

sage: C = crystals.Tableaux(['B', 2], shape=[2, 1])
sage: qdim = C.q_dimension(); qdim
q^10 + 2*q^9 + 3*q^8 + 4*q^7 + 5*q^6 + 5*q^5
+ 5*q^4 + 4*q^3 + 3*q^2 + 2*q + 1

```

(continues on next page)

(continued from previous page)

```

sage: qdim == C.q_dimension(use_product=True)
True

sage: C = crystals.Tableaux(['D',4], shape=[2,1])
sage: C.q_dimension()
q^16 + 2*q^15 + 4*q^14 + 7*q^13 + 10*q^12 + 13*q^11
+ 16*q^10 + 18*q^9 + 18*q^8 + 18*q^7 + 16*q^6 + 13*q^5
+ 10*q^4 + 7*q^3 + 4*q^2 + 2*q + 1

```

We check with a finite tensor product:

```

sage: TP = crystals.TensorProduct(C, C)
sage: TP.cardinality()
25600

sage: qdim = TP.q_dimension(use_product=True); qdim # long time
q^32 + 2*q^31 + 8*q^30 + 15*q^29 + 34*q^28 + 63*q^27 + 110*q^26
+ 175*q^25 + 276*q^24 + 389*q^23 + 550*q^22 + 725*q^21
+ 930*q^20 + 1131*q^19 + 1362*q^18 + 1548*q^17 + 1736*q^16
+ 1858*q^15 + 1947*q^14 + 1944*q^13 + 1918*q^12 + 1777*q^11
+ 1628*q^10 + 1407*q^9 + 1186*q^8 + 928*q^7 + 720*q^6
+ 498*q^5 + 342*q^4 + 201*q^3 + 117*q^2 + 48*q + 26

sage: qdim(1) # long time
25600

sage: TP.q_dimension() == qdim # long time
True

```

The q -dimensions of infinite crystals are returned as formal power series:

```

sage: C = crystals.LSPaths(['A',2,1], [1,0,0])
sage: C.q_dimension(prec=5)
1 + q + 2*q^2 + 2*q^3 + 4*q^4 + O(q^5)

sage: C.q_dimension(prec=10)
1 + q + 2*q^2 + 2*q^3 + 4*q^4 + 5*q^5 + 7*q^6
+ 9*q^7 + 13*q^8 + 16*q^9 + O(q^10)

sage: qdim = C.q_dimension(); qdim
1 + q + 2*q^2 + 2*q^3 + 4*q^4 + 5*q^5 + 7*q^6
+ 9*q^7 + 13*q^8 + 16*q^9 + 22*q^10 + O(x^11)

sage: qdim.compute_coefficients(15)
sage: qdim
1 + q + 2*q^2 + 2*q^3 + 4*q^4 + 5*q^5 + 7*q^6
+ 9*q^7 + 13*q^8 + 16*q^9 + 22*q^10 + 27*q^11
+ 36*q^12 + 44*q^13 + 57*q^14 + 70*q^15 + O(x^16)

```

class `TensorProducts`(*category*, **args*)

Bases: `sage.categories.tensor.TensorProductsCategory`

The category of highest weight crystals constructed by tensor product of highest weight crystals.

class `ParentMethods`

Bases: `object`

Implements operations on tensor products of crystals.

highest_weight_vectors()

Return the highest weight vectors of `self`.

This works by using a backtracing algorithm since if $b_2 \otimes b_1$ is highest weight then b_1 is highest weight.

EXAMPLES:

```
sage: C = crystals.Tableaux(['D',4], shape=[2,2])
sage: D = crystals.Tableaux(['D',4], shape=[1])
sage: T = crystals.TensorProduct(D, C)
sage: T.highest_weight_vectors()
([[[1]], [[1, 1], [2, 2]]],
 [[3]], [[1, 1], [2, 2]]],
 [[-2]], [[1, 1], [2, 2]])
sage: L = filter(lambda x: x.is_highest_weight(), T)
sage: tuple(L) == T.highest_weight_vectors()
True
```

`highest_weight_vectors_iterator()`

Iterate over the highest weight vectors of `self`.

This works by using a backtracing algorithm since if $b_2 \otimes b_1$ is highest weight then b_1 is highest weight.

EXAMPLES:

```
sage: C = crystals.Tableaux(['D',4], shape=[2,2])
sage: D = crystals.Tableaux(['D',4], shape=[1])
sage: T = crystals.TensorProduct(D, C)
sage: tuple(T.highest_weight_vectors_iterator())
([[[1]], [[1, 1], [2, 2]]],
 [[3]], [[1, 1], [2, 2]]],
 [[-2]], [[1, 1], [2, 2]])
sage: L = filter(lambda x: x.is_highest_weight(), T)
sage: tuple(L) == tuple(T.highest_weight_vectors_iterator())
True
```

`extra_super_categories()`

EXAMPLES:

```
sage: HighestWeightCrystals().TensorProducts().extra_super_categories()
[Category of highest weight crystals]
```

`additional_structure()`

Return `None`.

Indeed, the category of highest weight crystals defines no additional structure: it only guarantees the existence of a unique highest weight element in each component.

See also:

[*Category.additional_structure\(\)*](#)

Todo: Should this category be a `CategoryWithAxiom?`

EXAMPLES:

```
sage: HighestWeightCrystals().additional_structure()
```

example()

Returns an example of highest weight crystals, as per `Category.example()`.

EXAMPLES:

```
sage: B = HighestWeightCrystals().example(); B
Highest weight crystal of type A_3 of highest weight omega_1
```

super_categories()

EXAMPLES:

```
sage: HighestWeightCrystals().super_categories()
[Category of crystals]
```

3.93 Hopf algebras

class `sage.categories.hopf_algebras.HopfAlgebras`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of Hopf algebras.

EXAMPLES:

```
sage: HopfAlgebras(QQ)
Category of hopf algebras over Rational Field
sage: HopfAlgebras(QQ).super_categories()
[Category of bialgebras over Rational Field]
```

class `DualCategory`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of Hopf algebras constructed as dual of a Hopf algebra

class `ParentMethods`

Bases: object

class `ElementMethods`

Bases: object

antipode()

Return the antipode of self

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis: the group algebra of the Dihedral_
↪group of order 6 as a permutation group over Rational Field
sage: [a,b] = A.algebra_generators()
sage: a, a.antipode()
(B[(1,2,3)], B[(1,3,2)])
sage: b, b.antipode()
(B[(1,3)], B[(1,3)])
```

class `Morphism`(*s=None*)

Bases: `sage.categories.category.Category`

The category of Hopf algebra morphisms.

class ParentMethods

Bases: object

class Realizations(category, *args)Bases: *sage.categories.realizations.RealizationsCategory***class ParentMethods**

Bases: object

antipode_by_coercion(x)

Returns the image of x by the antipode

This default implementation coerces to the default realization, computes the antipode there, and coerces the result back.

EXAMPLES:

```
sage: N = NonCommutativeSymmetricFunctions(QQ)
sage: R = N.ribbon()
sage: R.antipode_by_coercion.__module__
'sage.categories.hopf_algebras'
sage: R.antipode_by_coercion(R[1,3,1])
-R[2, 1, 2]
```

class Super(base_category)Bases: *sage.categories.super_modules.SuperModulesCategory*

The category of super Hopf algebras.

Note: A super Hopf algebra is *not* simply a Hopf algebra with a $\mathbb{Z}/2\mathbb{Z}$ grading due to the signed bialgebra compatibility conditions.

class ElementMethods

Bases: object

antipode()

Return the antipode of self.

EXAMPLES:

```
sage: A = SteenrodAlgebra(3)
sage: a = A.an_element()
sage: a, a.antipode()
(2 Q_1 Q_3 P(2,1), Q_1 Q_3 P(2,1))
```

dual()

Return the dual category.

EXAMPLES:

The category of super Hopf algebras over any field is self dual:

```
sage: C = HopfAlgebras(QQ).Super()
sage: C.dual()
Category of super hopf algebras over Rational Field
```

class TensorProducts(category, *args)Bases: *sage.categories.tensor.TensorProductsCategory*

The category of Hopf algebras constructed by tensor product of Hopf algebras

class ElementMethods

Bases: object

class ParentMethods

Bases: object

extra_super_categories()

EXAMPLES:

```
sage: C = HopfAlgebras(QQ).TensorProducts()
sage: C.extra_super_categories()
[Category of hopf algebras over Rational Field]
sage: sorted(C.super_categories(), key=str)
[Category of hopf algebras over Rational Field,
Category of tensor products of algebras over Rational Field,
Category of tensor products of coalgebras over Rational Field]
```

WithBasis

alias of `sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis`

dual()

Return the dual category

EXAMPLES:

The category of Hopf algebras over any field is self dual:

```
sage: C = HopfAlgebras(QQ)
sage: C.dual()
Category of hopf algebras over Rational Field
```

super_categories()

EXAMPLES:

```
sage: HopfAlgebras(QQ).super_categories()
[Category of bialgebras over Rational Field]
```

3.94 Hopf algebras with basis

class `sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of Hopf algebras with a distinguished basis

EXAMPLES:

```
sage: C = HopfAlgebrasWithBasis(QQ)
sage: C
Category of hopf algebras with basis over Rational Field
sage: C.super_categories()
[Category of hopf algebras over Rational Field,
Category of bialgebras with basis over Rational Field]
```

We now show how to use a simple Hopf algebra, namely the group algebra of the dihedral group (see also `AlgebrasWithBasis`):

```

sage: A = C.example(); A
An example of Hopf algebra with basis: the group algebra of the Dihedral group of_
↳order 6 as a permutation group over Rational Field
sage: A.__custom_name = "A"
sage: A.category()
Category of finite dimensional hopf algebras with basis over Rational Field

sage: A.one_basis()
()
sage: A.one()
B[()]

sage: A.base_ring()
Rational Field
sage: A.basis().keys()
Dihedral group of order 6 as a permutation group

sage: [a,b] = A.algebra_generators()
sage: a, b
(B[(1,2,3)], B[(1,3)])
sage: a^3, b^2
(B[()], B[()])
sage: a*b
B[(1,2)]

sage: A.product          # todo: not quite ...
<bound method MyGroupAlgebra_with_category._product_from_product_on_basis_multiply_
↳of A>
sage: A.product(b,b)
B[()]

sage: A.zero().coproduct()
0
sage: A.zero().coproduct().parent()
A # A
sage: a.coproduct()
B[(1,2,3)] # B[(1,2,3)]

sage: TestSuite(A).run(verbose=True)
running ._test_additive_associativity() . . . pass
running ._test_an_element() . . . pass
running ._test_antipode() . . . pass
running ._test_associativity() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_characteristic() . . . pass
running ._test_construction() . . . pass
running ._test_distributivity() . . . pass
running ._test_elements() . . .
    Running the test suite of self.an_element()
running ._test_category() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass

```

(continues on next page)

(continued from previous page)

```

running ._test_nonzero_equal() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_one() . . . pass
running ._test_pickling() . . . pass
running ._test_prod() . . . pass
running ._test_some_elements() . . . pass
running ._test_zero() . . . pass
sage: A.__class__
<class 'sage.categories.examples.hopf_algebras_with_basis.MyGroupAlgebra_with_
↳category'>
sage: A.element_class
<class 'sage.categories.examples.hopf_algebras_with_basis.MyGroupAlgebra_with_
↳category.element_class'>

```

Let us look at the code for implementing A:

```
sage: A?? # todo: not implemented
```

class ElementMethods

Bases: object

Filtered

alias of `sage.categories.filtered_hopf_algebras_with_basis.FilteredHopfAlgebrasWithBasis`

FiniteDimensional

alias of `sage.categories.finite_dimensional_hopf_algebras_with_basis.FiniteDimensionalHopfAlgebrasWithBasis`

Graded

alias of `sage.categories.graded_hopf_algebras_with_basis.GradedHopfAlgebrasWithBasis`

class ParentMethods

Bases: object

antipode()

The antipode of this Hopf algebra.

If `antipode_basis()` is available, this constructs the antipode morphism from `self` to `self` by extending it by linearity. Otherwise, `self.antipode_by_coercion()` is used, if available.

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(ZZ).example(); A
An example of Hopf algebra with basis: the group algebra of the Dihedral_
↳group of order 6 as a permutation group over Integer Ring
```

(continues on next page)

(continued from previous page)

```

sage: A = HopfAlgebrasWithBasis(QQ).example()
sage: [a,b] = A.algebra_generators()
sage: a, A.antipode(a)
(B[(1,2,3)], B[(1,3,2)])
sage: b, A.antipode(b)
(B[(1,3)], B[(1,3)])

```

antipode_on_basis(x)

The antipode of the Hopf algebra on the basis (optional)

INPUT:

- x – an index of an element of the basis of `self`

Returns the antipode of the basis element indexed by x .

If this method is implemented, then `antipode()` is defined from this by linearity.

EXAMPLES:

```

sage: A = HopfAlgebrasWithBasis(QQ).example()
sage: W = A.basis().keys(); W
Dihedral group of order 6 as a permutation group
sage: w = W.gen(0); w
(1,2,3)
sage: A.antipode_on_basis(w)
B[(1,3,2)]

```

Super

alias of `sage.categories.super_hopf_algebras_with_basis.SuperHopfAlgebrasWithBasis`

class TensorProducts(category, *args)

Bases: `sage.categories.tensor.TensorProductsCategory`

The category of hopf algebras with basis constructed by tensor product of hopf algebras with basis

class ElementMethods

Bases: object

class ParentMethods

Bases: object

extra_super_categories()

EXAMPLES:

```

sage: C = HopfAlgebrasWithBasis(QQ).TensorProducts()
sage: C.extra_super_categories()
[Category of hopf algebras with basis over Rational Field]
sage: sorted(C.super_categories(), key=str)
[Category of hopf algebras with basis over Rational Field,
Category of tensor products of algebras with basis over Rational Field,
Category of tensor products of hopf algebras over Rational Field]

```

example(G=None)

Returns an example of algebra with basis:

```

sage: HopfAlgebrasWithBasis(QQ['x']).example()
An example of Hopf algebra with basis: the group algebra of the Dihedral group
↳ of order 6 as a permutation group over Univariate Polynomial Ring in x over
↳ Rational Field

```

(continues on next page)

(continued from previous page)

An other group can be specified as optional argument:

```
sage: HopfAlgebrasWithBasis(QQ).example(SymmetricGroup(4))
An example of Hopf algebra with basis: the group algebra of the Symmetric group
↳ of order 4! as a permutation group over Rational Field
```

3.95 H-trivial semigroups

```
class sage.categories.h_trivial_semigroups.HTrivialSemigroups(base_category)
Bases: sage.categories.category_with_axiom.CategoryWithAxiom
```

```
Finite_extra_super_categories()
```

Implement the fact that a finite H -trivial is aperiodic

EXAMPLES:

```
sage: Semigroups().HTrivial().Finite_extra_super_categories()
[Category of aperiodic semigroups]
sage: Semigroups().HTrivial().Finite() is Semigroups().Aperiodic().Finite()
True
```

```
Inverse_extra_super_categories()
```

Implement the fact that an H -trivial inverse semigroup is J -trivial.

Todo: Generalization for inverse semigroups.

Recall that there are two invertibility axioms for a semigroup S :

- One stating the existence, for all x , of a local inverse y satisfying $x = xyx$ and $y = yxy$;
- One stating the existence, for all x , of a global inverse y satisfying $xy = yx = 1$, where 1 is the unit of S (which must of course exist).

It is sufficient to have local inverses for H -triviality to imply J -triviality. However, at this stage, only the second axiom is implemented in Sage (see [Magmas.Unital.SubcategoryMethods.Inverse\(\)](#)). Therefore this fact is only implemented for semigroups with global inverses, that is groups. However the trivial group is the unique H -trivial group, so this is rather boring.

EXAMPLES:

```
sage: Semigroups().HTrivial().Inverse_extra_super_categories()
[Category of j trivial semigroups]
sage: Monoids().HTrivial().Inverse()
Category of h trivial groups
```

3.96 Infinite Enumerated Sets

AUTHORS:

- Florent Hivert (2009-11): initial revision.

class `sage.categories.infinite_enumerated_sets.InfiniteEnumeratedSets`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of infinite enumerated sets

An infinite enumerated sets is a countable set together with a canonical enumeration of its elements.

EXAMPLES:

```
sage: InfiniteEnumeratedSets()
Category of infinite enumerated sets
sage: InfiniteEnumeratedSets().super_categories()
[Category of enumerated sets, Category of infinite sets]
sage: InfiniteEnumeratedSets().all_super_categories()
[Category of infinite enumerated sets,
Category of enumerated sets,
Category of infinite sets,
Category of sets,
Category of sets with partial maps,
Category of objects]
```

class `ParentMethods`

Bases: `object`

list()

Returns an error since self is an infinite enumerated set.

EXAMPLES:

```
sage: NN = InfiniteEnumeratedSets().example()
sage: NN.list()
Traceback (most recent call last):
...
NotImplementedError: cannot list an infinite set
```

random_element()

Returns an error since self is an infinite enumerated set.

EXAMPLES:

```
sage: NN = InfiniteEnumeratedSets().example()
sage: NN.random_element()
Traceback (most recent call last):
...
NotImplementedError: infinite set
```

TODO: should this be an optional `abstract_method` instead?

3.97 Integral domains

class `sage.categories.integral_domains.IntegralDomains`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of integral domains

An integral domain is commutative ring with no zero divisors, or equivalently a commutative domain.

EXAMPLES:

```
sage: C = IntegralDomains(); C
Category of integral domains
sage: sorted(C.super_categories(), key=str)
[Category of commutative rings, Category of domains]
sage: C is Domains().Commutative()
True
sage: C is Rings().Commutative().NoZeroDivisors()
True
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

is_integral_domain()

Return True, since this is an object of the category of integral domains.

EXAMPLES:

```
sage: QQ.is_integral_domain()
True
sage: Parent(QQ, category=IntegralDomains()).is_integral_domain()
True
```

3.98 J-trivial semigroups

class `sage.categories.j_trivial_semigroups.JTrivialSemigroups`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

extra_super_categories()

Implement the fact that a J -trivial semigroup is L and R -trivial.

EXAMPLES:

```
sage: Semigroups().JTrivial().extra_super_categories()
[Category of l trivial semigroups, Category of r trivial semigroups]
```


3.99 Kac-Moody Algebras

AUTHORS:

- Travis Scrimshaw (07-15-2017): Initial implementation

class `sage.categories.kac_moody_algebras.KacMoodyAlgebras`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

Category of Kac-Moody algebras.

class `ParentMethods`

Bases: `object`

cartan_type()

Return the Cartan type of self.

EXAMPLES:

```
sage: L = LieAlgebra(QQ, cartan_type=['A', 2])
sage: L.cartan_type()
['A', 2]
```

weyl_group()

Return the Weyl group of self.

EXAMPLES:

```
sage: L = LieAlgebra(QQ, cartan_type=['A', 2])
sage: L.weyl_group()
Weyl Group of type ['A', 2] (as a matrix group acting on the ambient space)
```

example(*n=2*)

Return an example of a Kac-Moody algebra as per *Category.example*.

EXAMPLES:

```
sage: from sage.categories.kac_moody_algebras import KacMoodyAlgebras
sage: KacMoodyAlgebras(QQ).example()
Lie algebra of ['A', 2] in the Chevalley basis
```

We can specify the rank of the example:

```
sage: KacMoodyAlgebras(QQ).example(4)
Lie algebra of ['A', 4] in the Chevalley basis
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.kac_moody_algebras import KacMoodyAlgebras
sage: KacMoodyAlgebras(QQ).super_categories()
[Category of Lie algebras over Rational Field]
```

3.100 Lambda Bracket Algebras

AUTHORS:

- Reimundo Heluani (2019-10-05): Initial implementation.

class `sage.categories.lambda_bracket_algebras.LambdaBracketAlgebras`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of Lambda bracket algebras.

This is an abstract base category for Lie conformal algebras and super Lie conformal algebras.

class `ElementMethods`

Bases: object

`T(n=1)`

The n-th derivative of `self`.

INPUT:

- `n` – integer (default:1); how many times to apply T to this element

OUTPUT:

$T^n a$ where a is this element. Notice that we use the *divided powers* notation $T^{(j)} = \frac{T^j}{j!}$.

EXAMPLES:

```
sage: Vir = lie_conformal_algebras.Virasoro(QQ)
sage: Vir.inject_variables()
Defining L, C
sage: L.T()
TL
sage: L.T(3)
6*T^(3)L
sage: C.T()
0
```

bracket(*rhs*)

The λ -bracket of these two elements.

EXAMPLES:

The brackets of the Virasoro Lie conformal algebra:

```
sage: Vir = lie_conformal_algebras.Virasoro(QQ); L = Vir.0
sage: L.bracket(L)
{0: TL, 1: 2*L, 3: 1/2*C}
sage: L.bracket(L.T())
{0: 2*T^(2)L, 1: 3*TL, 2: 4*L, 4: 2*C}
```

Now with a current algebra:

```
sage: V = lie_conformal_algebras.Affine(QQ, 'A1')
sage: V.gens()
(B[alpha[1]], B[alphacheck[1]], B[-alpha[1]], B['K'])
sage: E = V.0; H = V.1; F = V.2;
sage: H.bracket(H)
{1: 2*B['K']}
```

(continues on next page)

(continued from previous page)

```
sage: E.bracket(F)
{0: B[alphacheck[1]], 1: B['K']}
```

nproduct(*rhs, n*)The *n*-th product of these two elements.

EXAMPLES:

```
sage: Vir = lie_conformal_algebras.Virasoro(QQ); L = Vir.0
sage: L.nproduct(L, 3)
1/2*C
sage: L.nproduct(L.T(), 0)
2*T^(2)L
sage: V = lie_conformal_algebras.Affine(QQ, 'A1')
sage: E = V.0; H = V.1; F = V.2;
sage: E.nproduct(H, 0) == - 2*E
True
sage: E.nproduct(F, 1)
B['K']
```

FinitelyGeneratedAsLambdaBracketAlgebra

alias of `sage.categories.finitely_generated_lambda_bracket_algebras.FinitelyGeneratedLambdaBracketAlgebras`

class ParentMethods

Bases: object

ideal(*gens, **kwds)

The ideal of this Lambda bracket algebra generated by gens.

Todo: Ideals of Lie Conformal Algebras are not implemented yet.

EXAMPLES:

```
sage: Vir = lie_conformal_algebras.Virasoro(QQ)
sage: Vir.ideal()
Traceback (most recent call last):
...
NotImplementedError: ideals of Lie Conformal algebras are not implemented_
↪yet
```

class SubcategoryMethods

Bases: object

FinitelyGenerated()

The category of finitely generated Lambda bracket algebras.

EXAMPLES:

```
sage: LieConformalAlgebras(QQ).FinitelyGenerated()
Category of finitely generated lie conformal algebras over Rational Field
```

FinitelyGeneratedAsLambdaBracketAlgebra()

The category of finitely generated Lambda bracket algebras.

EXAMPLES:

```
sage: LieConformalAlgebras(QQ).FinitelyGenerated()
Category of finitely generated lie conformal algebras over Rational Field
```

WithBasis

alias of `sage.categories.lambda_bracket_algebras_with_basis.LambdaBracketAlgebrasWithBasis`

super_categories()

The list of super categories of this category.

EXAMPLES:

```
sage: from sage.categories.lambda_bracket_algebras import LambdaBracketAlgebras
sage: LambdaBracketAlgebras(QQ).super_categories()
[Category of vector spaces over Rational Field]
```

3.101 Lambda Bracket Algebras With Basis

AUTHORS:

- Reimundo Heluani (2020-08-21): Initial implementation.

class `sage.categories.lambda_bracket_algebras_with_basis.LambdaBracketAlgebrasWithBasis`(*base_category*)
Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of Lambda bracket algebras with basis.

EXAMPLES:

```
sage: LieConformalAlgebras(QQbar).WithBasis()
Category of Lie conformal algebras with basis over Algebraic Field
```

class `ElementMethods`

Bases: `object`

index()

The index of this basis element.

EXAMPLES:

```
sage: V = lie_conformal_algebras.NeveuSchwarz(QQ)
sage: V.inject_variables()
Defining L, G, C
sage: G.T(3).index()
('G', 3)
sage: v = V.an_element(); v
L + G + C
sage: v.index()
Traceback (most recent call last):
...
ValueError: index can only be computed for monomials, got L + G + C
```

class `FinitelyGeneratedAsLambdaBracketAlgebra`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of finitely generated lambda bracket algebras with basis.

EXAMPLES:

```
sage: C = LieConformalAlgebras(QQbar)
sage: C.WithBasis().FinitelyGenerated()
Category of finitely generated Lie conformal algebras with basis over Algebraic_
↳Field
sage: C.WithBasis().FinitelyGenerated() is C.FinitelyGenerated().WithBasis()
True
```

class `Graded(base_category)`

Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of H-graded finitely generated lambda bracket algebras with basis.

EXAMPLES:

```
sage: LieConformalAlgebras(QQbar).WithBasis().FinitelyGenerated().Graded()
Category of H-graded finitely generated Lie conformal algebras with basis_
↳over Algebraic Field
```

class `ParentMethods`

Bases: object

degree_on_basis(m)

Return the degree of the basis element indexed by `m` in `self`.

EXAMPLES:

```
sage: V = lie_conformal_algebras.Virasoro(QQ)
sage: V.degree_on_basis(('L',2))
4
```

3.102 Lattice posets

class `sage.categories.lattice_posets.LatticePosets(s=None)`

Bases: `sage.categories.category.Category`

The category of lattices, i.e. partially ordered sets in which any two elements have a unique supremum (the elements' least upper bound; called their *join*) and a unique infimum (greatest lower bound; called their *meet*).

EXAMPLES:

```
sage: LatticePosets()
Category of lattice posets
sage: LatticePosets().super_categories()
[Category of posets]
sage: LatticePosets().example()
NotImplemented
```

See also:

`Posets`, `FiniteLatticePosets`, `LatticePoset()`

Finite

alias of `sage.categories.finite_lattice_posets.FiniteLatticePosets`

class ParentMethods

Bases: object

join(x , y)Returns the join of x and y in this lattice

INPUT:

- x, y – elements of self

EXAMPLES:

```
sage: D = LatticePoset((divisors(60), attrcall("divides")))
sage: D.join( D(6), D(10) )
30
```

meet(x , y)Returns the meet of x and y in this lattice

INPUT:

- x, y – elements of self

EXAMPLES:

```
sage: D = LatticePoset((divisors(30), attrcall("divides")))
sage: D.meet( D(6), D(15) )
3
```

super_categories()Returns a list of the (immediate) super categories of self, as per *Category.super_categories()*.

EXAMPLES:

```
sage: LatticePosets().super_categories()
[Category of posets]
```

3.103 Left modules

class sage.categories.left_modules.**LeftModules**(*base*, *name=None*)Bases: *sage.categories.category_types.Category_over_base_ring*

The category of left modules over an rng (ring not necessarily with unit), i.e. an abelian group with left multiplication by elements of the rng

EXAMPLES:

```
sage: LeftModules(ZZ)
Category of left modules over Integer Ring
sage: LeftModules(ZZ).super_categories()
[Category of commutative additive groups]
```

class ElementMethods

Bases: object

class ParentMethods

Bases: object

super_categories()

EXAMPLES:

```
sage: LeftModules(QQ).super_categories()
[Category of commutative additive groups]
```

3.104 Lie Algebras

AUTHORS:

- Travis Scrimshaw (07-15-2013): Initial implementation

class `sage.categories.lie_algebras.LieAlgebras`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of Lie algebras.

EXAMPLES:

```
sage: C = LieAlgebras(QQ); C
Category of Lie algebras over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of vector spaces over Rational Field]
```

We construct a typical parent in this category, and do some computations with it:

```
sage: A = C.example(); A
An example of a Lie algebra: the Lie algebra from the associative
algebra Symmetric group algebra of order 3 over Rational Field
generated by ([2, 1, 3], [2, 3, 1])

sage: A.category()
Category of Lie algebras over Rational Field

sage: A.base_ring()
Rational Field

sage: a,b = A.lie_algebra_generators()
sage: a.bracket(b)
-[1, 3, 2] + [3, 2, 1]
sage: b.bracket(2*a + b)
2*[1, 3, 2] - 2*[3, 2, 1]

sage: A.bracket(a, b)
-[1, 3, 2] + [3, 2, 1]
```

Please see the source code of `A` (with `A??`) for how to implement other Lie algebras.

Todo: Many of these tests should use Lie algebras that are not the minimal example and need to be added after [trac ticket #16820](#) (and [trac ticket #16823](#)).

class `ElementMethods`

Bases: `object`

bracket(*rhs*)

Return the Lie bracket [`self`, `rhs`].

EXAMPLES:

```
sage: L = LieAlgebras(QQ).example()
sage: x,y = L.lie_algebra_generators()
sage: x.bracket(y)
-[1, 3, 2] + [3, 2, 1]
sage: x.bracket(0)
0
```

exp(*lie_group=None*)

Return the exponential of *self* in *lie_group*.

INPUT:

- *lie_group* – (optional) the Lie group to map into; If *lie_group* is not given, the Lie group associated to the parent Lie algebra of *self* is used.

EXAMPLES:

```
sage: L.<X,Y,Z> = LieAlgebra(QQ, 2, step=2)
sage: g = (X + Y + Z).exp(); g
exp(X + Y + Z)
sage: h = X.exp(); h
exp(X)
sage: g.parent()
Lie group G of Free Nilpotent Lie algebra on 3 generators (X, Y, Z) over
↪Rational Field
sage: g.parent() is h.parent()
True
```

The Lie group can be specified explicitly:

```
sage: H = L.lie_group('H')
sage: k = Z.exp(lie_group=H); k
exp(Z)
sage: k.parent()
Lie group H of Free Nilpotent Lie algebra on 3 generators (X, Y, Z) over
↪Rational Field
sage: g.parent() == k.parent()
False
```

killling_form(*x*)

Return the Killing form of *self* and *x*.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: a.killing_form(b)
0
```

lift()

Return the image of *self* under the canonical lift from the Lie algebra to its universal enveloping algebra.

EXAMPLES:


```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: elt = 3*a + b - c
sage: elt.lift()
3*b0 + b1 - b2

```

```

sage: L.<x,y> = LieAlgebra(QQ, abelian=True)
sage: x.lift()
x

```

to_vector(*order=None*)

Return the vector in `g.module()` corresponding to the element `self` of `g` (where `g` is the parent of `self`).

Implement this if you implement `g.module()`. See `LieAlgebras.module()` for how this is to be done.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: u = L((1, 0, 0)).to_vector(); u
(1, 0, 0)
sage: parent(u)
Vector space of dimension 3 over Rational Field

```

class FiniteDimensional(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

WithBasis

alias of `sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis`

extra_super_categories()

Implements the fact that a finite dimensional Lie algebra over a finite ring is finite.

EXAMPLES:

```

sage: LieAlgebras(IntegerModRing(4)).FiniteDimensional().extra_super_
↪categories()
[Category of finite sets]
sage: LieAlgebras(ZZ).FiniteDimensional().extra_super_categories()
[]
sage: LieAlgebras(GF(5)).FiniteDimensional().is_subcategory(Sets().Finite())
True
sage: LieAlgebras(ZZ).FiniteDimensional().is_subcategory(Sets().Finite())
False
sage: LieAlgebras(GF(5)).WithBasis().FiniteDimensional().is_
↪subcategory(Sets().Finite())
True

```

Graded

alias of `sage.categories.graded_lie_algebras.GradedLieAlgebras`

class Nilpotent(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

Category of nilpotent Lie algebras.

class ParentMethods

Bases: object

is_nilpotent()

Return True since self is nilpotent.

EXAMPLES:

```
sage: h = lie_algebras.Heisenberg(ZZ, oo)
sage: h.is_nilpotent()
True
```

step()

Return the nilpotency step of self.

EXAMPLES:

```
sage: h = lie_algebras.Heisenberg(ZZ, oo)
sage: h.step()
2
```

class ParentMethods

Bases: object

baker_campbell_hausdorff(X, Y, prec=None)Return the element $\log(\exp(X)\exp(Y))$.

The BCH formula is an expression for $\log(\exp(X)\exp(Y))$ as a sum of Lie brackets of X and Y with rational coefficients. It is only defined if the base ring of self has a coercion from the rationals.

INPUT:

- X – an element of self
- Y – an element of self
- prec – an integer; the maximum length of Lie brackets to be considered in the formula

EXAMPLES:

The BCH formula for the generators of a free nilpotent Lie algebra of step 4:

```
sage: L = LieAlgebra(QQ, 2, step=4)
sage: L.inject_variables()
Defining X_1, X_2, X_12, X_112, X_122, X_1112, X_1122, X_1222
sage: L.bch(X_1, X_2)
X_1 + X_2 + 1/2*X_12 + 1/12*X_112 + 1/12*X_122 + 1/24*X_1122
```

An example of the BCH formula in a quotient:

```
sage: Q = L.quotient(X_112 + X_122)
sage: x, y = Q.basis().list()[:2]
sage: Q.bch(x, y)
X_1 + X_2 + 1/2*X_12 - 1/24*X_1112
```

The BCH formula for a non-nilpotent Lie algebra requires the precision to be explicitly stated:

```
sage: L.<X,Y> = LieAlgebra(QQ)
sage: L.bch(X, Y)
Traceback (most recent call last):
...
ValueError: the Lie algebra is not known to be nilpotent, so you must
↪ specify the precision
```

(continues on next page)

(continued from previous page)

```
sage: L.bch(X, Y, 4)
X + 1/12*[X, [X, Y]] + 1/24*[X, [[X, Y], Y]] + 1/2*[X, Y] + 1/12*[[X, Y],
↪Y] + Y
```

The BCH formula requires a coercion from the rationals:

```
sage: L.<X,Y,Z> = LieAlgebra(ZZ, 2, step=2)
sage: L.bch(X, Y)
Traceback (most recent call last):
...
TypeError: the BCH formula is not well defined since Integer Ring has no
↪coercion from Rational Field
```

bch(*X*, *Y*, *prec=None*)

Return the element $\log(\exp(X)\exp(Y))$.

The BCH formula is an expression for $\log(\exp(X)\exp(Y))$ as a sum of Lie brackets of X and Y with rational coefficients. It is only defined if the base ring of `self` has a coercion from the rationals.

INPUT:

- X – an element of `self`
- Y – an element of `self`
- `prec` – an integer; the maximum length of Lie brackets to be considered in the formula

EXAMPLES:

The BCH formula for the generators of a free nilpotent Lie algebra of step 4:

```
sage: L = LieAlgebra(QQ, 2, step=4)
sage: L.inject_variables()
Defining X_1, X_2, X_12, X_112, X_122, X_1112, X_1122, X_1222
sage: L.bch(X_1, X_2)
X_1 + X_2 + 1/2*X_12 + 1/12*X_112 + 1/12*X_122 + 1/24*X_1122
```

An example of the BCH formula in a quotient:

```
sage: Q = L.quotient(X_112 + X_122)
sage: x, y = Q.basis().list()[:2]
sage: Q.bch(x, y)
X_1 + X_2 + 1/2*X_12 - 1/24*X_1112
```

The BCH formula for a non-nilpotent Lie algebra requires the precision to be explicitly stated:

```
sage: L.<X,Y> = LieAlgebra(QQ)
sage: L.bch(X, Y)
Traceback (most recent call last):
...
ValueError: the Lie algebra is not known to be nilpotent, so you must
↪specify the precision
sage: L.bch(X, Y, 4)
X + 1/12*[X, [X, Y]] + 1/24*[X, [[X, Y], Y]] + 1/2*[X, Y] + 1/12*[[X, Y],
↪Y] + Y
```

The BCH formula requires a coercion from the rationals:

```

sage: L.<X,Y,Z> = LieAlgebra(ZZ, 2, step=2)
sage: L.bch(X, Y)
Traceback (most recent call last):
...
TypeError: the BCH formula is not well defined since Integer Ring has no
↳ coercion from Rational Field

```

bracket(*lhs, rhs*)

Return the Lie bracket [*lhs*, *rhs*] after coercing *lhs* and *rhs* into elements of *self*.

If *lhs* and *rhs* are Lie algebras, then this constructs the product space, and if only one of them is a Lie algebra, then it constructs the corresponding ideal.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).example()
sage: x,y = L.lie_algebra_generators()
sage: L.bracket(x, x + y)
-[1, 3, 2] + [3, 2, 1]
sage: L.bracket(x, 0)
0
sage: L.bracket(0, x)
0

```

Constructing the product space:

```

sage: L = lie_algebras.Heisenberg(QQ, 1)
sage: Z = L.bracket(L, L); Z
Ideal (z) of Heisenberg algebra of rank 1 over Rational Field
sage: L.bracket(L, Z)
Ideal () of Heisenberg algebra of rank 1 over Rational Field

```

Constructing ideals:

```

sage: p,q,z = L.basis(); (p,q,z)
(p1, q1, z)
sage: L.bracket(3*p, L)
Ideal (3*p1) of Heisenberg algebra of rank 1 over Rational Field
sage: L.bracket(L, q+p)
Ideal (p1 + q1) of Heisenberg algebra of rank 1 over Rational Field

```

from_vector(*v, order=None*)

Return the element of *self* corresponding to the vector *v* in *self.module*() .

Implement this if you implement *module*(); see the documentation of the latter for how this is to be done.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: u = L.from_vector(vector(QQ, (1, 0, 0))); u
(1, 0, 0)
sage: parent(u) is L
True

```

ideal(*gens, **kws)

Return the ideal of self generated by gens.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: L.ideal([2*a - c, b + c])
An example of a finite dimensional Lie algebra with basis:
the 2-dimensional abelian Lie algebra over Rational Field
with basis matrix:
[ 1  0 -1/2]
[ 0  1  1]
```

```
sage: L = LieAlgebras(QQ).example()
sage: x,y = L.lie_algebra_generators()
sage: L.ideal([x + y])
Traceback (most recent call last):
...
NotImplementedError: ideals not yet implemented: see #16824
```

is_abelian()

Return True if this Lie algebra is abelian.

A Lie algebra \mathfrak{g} is abelian if $[x, y] = 0$ for all $x, y \in \mathfrak{g}$.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).example()
sage: L.is_abelian()
False
sage: R = QQ['x,y']
sage: L = LieAlgebras(QQ).example(R.gens())
sage: L.is_abelian()
True
```

```
sage: L.<x> = LieAlgebra(QQ,1) # todo: not implemented - #16823
sage: L.is_abelian() # todo: not implemented - #16823
True
sage: L.<x,y> = LieAlgebra(QQ,2) # todo: not implemented - #16823
sage: L.is_abelian() # todo: not implemented - #16823
False
```

is_commutative()

Return if self is commutative. This is equivalent to self being abelian.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).example()
sage: L.is_commutative()
False
```

```
sage: L.<x> = LieAlgebra(QQ, 1) # todo: not implemented - #16823
sage: L.is_commutative() # todo: not implemented - #16823
True
```

is_ideal(A)

Return if `self` is an ideal of A.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).example()
sage: L.is_ideal(L)
True
```

is_nilpotent()

Return if `self` is a nilpotent Lie algebra.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.is_nilpotent()
True
```

is_solvable()

Return if `self` is a solvable Lie algebra.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.is_solvable()
True
```

killling_form(x, y)

Return the Killing form of x and y.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: L.killing_form(a, b+c)
0
```

lie_group(name='G', **kwds)

Return the simply connected Lie group related to `self`.

INPUT:

- name – string (default: 'G'); the name (symbol) given to the Lie group

EXAMPLES:

```
sage: L = lie_algebras.Heisenberg(QQ, 1)
sage: G = L.lie_group('G'); G
Lie group G of Heisenberg algebra of rank 1 over Rational Field
```

lift()

Construct the lift morphism from `self` to the universal enveloping algebra of `self` (the latter is implemented as `universal_enveloping_algebra()`).

This is a Lie algebra homomorphism. It is injective if `self` is a free module over its base ring, or if the base ring is a \mathbb{Q} -algebra.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: lifted = L.lift(2*a + b - c); lifted
2*b0 + b1 - b2
sage: lifted.parent() is L.universal_enveloping_algebra()
True

```

module()

Return an R -module which is isomorphic to the underlying R -module of `self`.

The rationale behind this method is to enable linear algebraic functionality on `self` (such as computing the span of a list of vectors in `self`) via an isomorphism from `self` to an R -module (typically, although not always, an R -module of the form R^n for an $n \in \mathbf{N}$) on which such functionality already exists. For this method to be of any use, it should return an R -module which has linear algebraic functionality that `self` does not have.

For instance, if `self` has ordered basis (e, f, h) , then `self.module()` will be the R -module R^3 , and the elements e, f and h of `self` will correspond to the basis vectors $(1, 0, 0)$, $(0, 1, 0)$ and $(0, 0, 1)$ of `self.module()`.

This method `module()` needs to be set whenever a finite-dimensional Lie algebra with basis is intended to support linear algebra (which is, e.g., used in the computation of centralizers and lower central series). One then needs to also implement the R -module isomorphism from `self` to `self.module()` in both directions; that is, implement:

- a `to_vector` ElementMethod which sends every element of `self` to the corresponding element of `self.module()`;
- a `from_vector` ParentMethod which sends every element of `self.module()` to an element of `self`.

The `from_vector` method will automatically serve as an element constructor of `self` (that is, `self(v)` for any v in `self.module()` will return `self.from_vector(v)`).

Todo: Ensure that this is actually so.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.module()
Vector space of dimension 3 over Rational Field

```

subalgebra(*gens, names=None, index_set=None, category=None*)

Return the subalgebra of `self` generated by `gens`.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: L.subalgebra([2*a - c, b + c])
An example of a finite dimensional Lie algebra with basis:
the 2-dimensional abelian Lie algebra over Rational Field
with basis matrix:
[ 1  0 -1/2]
[ 0  1  1]

```

```
sage: L = LieAlgebras(QQ).example()
sage: x,y = L.lie_algebra_generators()
sage: L.subalgebra([x + y])
Traceback (most recent call last):
...
NotImplementedError: subalgebras not yet implemented: see #17416
```

universal_enveloping_algebra()

Return the universal enveloping algebra of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.universal_enveloping_algebra()
Noncommutative Multivariate Polynomial Ring in b0, b1, b2
over Rational Field, nc-relations: {}
```

```
sage: L = LieAlgebra(QQ, 3, 'x', abelian=True)
sage: L.universal_enveloping_algebra()
Multivariate Polynomial Ring in x0, x1, x2 over Rational Field
```

See also:

[`lift\(\)`](#)

class SubcategoryMethods

Bases: object

Nilpotent()

Return the full subcategory of nilpotent objects of `self`.

A Lie algebra L is nilpotent if there exist an integer s such that all iterated brackets of L of length more than s vanish. The integer s is called the nilpotency step. For instance any abelian Lie algebra is nilpotent of step 1.

EXAMPLES:

```
sage: LieAlgebras(QQ).Nilpotent()
Category of nilpotent Lie algebras over Rational Field
sage: LieAlgebras(QQ).WithBasis().Nilpotent()
Category of nilpotent lie algebras with basis over Rational Field
```

WithBasis

alias of `sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis`

example(gens=None)

Return an example of a Lie algebra as per *Category.example*.

EXAMPLES:

```
sage: LieAlgebras(QQ).example()
An example of a Lie algebra: the Lie algebra from the associative algebra
Symmetric group algebra of order 3 over Rational Field
generated by ([2, 1, 3], [2, 3, 1])
```

Another set of generators can be specified as an optional argument:


```

sage: F.<x,y,z> = FreeAlgebra(QQ)
sage: LieAlgebras(QQ).example(F.gens())
An example of a Lie algebra: the Lie algebra from the associative algebra
Free Algebra on 3 generators (x, y, z) over Rational Field
generated by (x, y, z)

```

super_categories()

EXAMPLES:

```

sage: LieAlgebras(QQ).super_categories()
[Category of vector spaces over Rational Field]

```

class `sage.categories.lie_algebras.LiftMorphism`(*domain, codomain*)

Bases: `sage.categories.morphism.Morphism`

The natural lifting morphism from a Lie algebra to its enveloping algebra.

3.105 Lie Algebras With Basis

AUTHORS:

- Travis Scrimshaw (07-15-2013): Initial implementation

class `sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

Category of Lie algebras with a basis.

class `ElementMethods`

Bases: object

lift()

Lift self to the universal enveloping algebra.

EXAMPLES:

```

sage: S = SymmetricGroup(3).algebra(QQ)
sage: L = LieAlgebra(associative=S)
sage: x = L.gen(3)
sage: y = L.gen(1)
sage: x.lift()
b3
sage: y.lift()
b1
sage: x * y
b1*b3 + b4 - b5

```

to_vector(*order=None*)

Return the vector in `g.module()` corresponding to the element self of `g` (where `g` is the parent of self).

Implement this if you implement `g.module()`. See `sage.categories.lie_algebras.LieAlgebras.module()` for how this is to be done.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.an_element().to_vector()
(0, 0, 0)
```

Todo: Doctest this implementation on an example not overshadowed.

Graded

alias of `sage.categories.graded_lie_algebras_with_basis.GradedLieAlgebrasWithBasis`

class ParentMethods

Bases: object

bracket_on_basis(*x*, *y*)

Return the bracket of basis elements indexed by *x* and *y* where $x < y$. If this is not implemented, then the method `_bracket_()` for the elements must be overwritten.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).WithBasis().example()
sage: L.bracket_on_basis(Partition([3,1]), Partition([2,2,1,1]))
0
```

dimension()

Return the dimension of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.dimension()
3
```

```
sage: L = LieAlgebra(QQ, 'x,y', {'x','y': {'x':1}})
sage: L.dimension()
2
```

from_vector(*v*, *order=None*)

Return the element of `self` corresponding to the vector *v* in `self.module()`.

Implement this if you implement `module()`; see the documentation of `sage.categories.lie_algebras.LieAlgebras.module()` for how this is to be done.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: u = L.from_vector(vector(QQ, (1, 0, 0))); u
(1, 0, 0)
sage: parent(u) is L
True
```

module()

Return an *R*-module which is isomorphic to the underlying *R*-module of `self`.

See `sage.categories.lie_algebras.LieAlgebras.module()` for an explanation.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).WithBasis().example()
sage: L.module()
Free module generated by Partitions over Rational Field
```

pbw_basis(*basis_key=None, **kws*)

Return the Poincare-Birkhoff-Witt basis of the universal enveloping algebra corresponding to self.

EXAMPLES:

```
sage: L = lie_algebras.sl(QQ, 2)
sage: PBW = L.pbw_basis()
```

poincare_birkhoff_witt_basis(*basis_key=None, **kws*)

Return the Poincare-Birkhoff-Witt basis of the universal enveloping algebra corresponding to self.

EXAMPLES:

```
sage: L = lie_algebras.sl(QQ, 2)
sage: PBW = L.pbw_basis()
```

example(*gens=None*)

Return an example of a Lie algebra as per *Category.example*.

EXAMPLES:

```
sage: LieAlgebras(QQ).WithBasis().example()
An example of a Lie algebra: the abelian Lie algebra on the
generators indexed by Partitions over Rational Field
```

Another set of generators can be specified as an optional argument:

```
sage: LieAlgebras(QQ).WithBasis().example(Compositions())
An example of a Lie algebra: the abelian Lie algebra on the
generators indexed by Compositions of non-negative integers
over Rational Field
```

3.106 Lie Conformal Algebras

Let R be a commutative ring, a *super Lie conformal algebra* [Kac1997] over R (also known as a *vertex Lie algebra*) is an $R[T]$ super module L together with a $\mathbb{Z}/2\mathbb{Z}$ -graded R -bilinear operation (called the λ -bracket) $L \otimes L \rightarrow L[\lambda]$ (polynomials in λ with coefficients in L), $a \otimes b \mapsto [a_\lambda b]$ satisfying

1. Sesquilinearity:

$$[T a_\lambda b] = -\lambda [a_\lambda b], \quad [a_\lambda T b] = (\lambda + T)[a_\lambda b].$$

2. Skew-Symmetry:

$$[a_\lambda b] = -(-1)^{p(a)p(b)} [b_{-\lambda - T} a],$$

where $p(a)$ is 0 if a is *even* and 1 if a is *odd*. The bracket in the RHS is computed as follows. First we evaluate $[b_\mu a]$ with the formal parameter μ to the *left*, then replace each appearance of the formal variable μ by $-\lambda - T$. Finally apply T to the coefficients in L .

3. Jacobi identity:

$$[a_\lambda[b_\mu c]] = [[a_{\lambda+\mu} b]_\mu c] + (-1)^{p(a)p(b)} [b_\mu [a_\lambda c]],$$

which is understood as an equality in $L[\lambda, \mu]$.

T is usually called the *translation operation* or the *derivative*. For an element $a \in L$ we will say that Ta is the *derivative of a* . We define the *n -th products* $a_{(n)}b$ for $a, b \in L$ by

$$[a_\lambda b] = \sum_{n \geq 0} \frac{\lambda^n}{n!} a_{(n)} b.$$

A Lie conformal algebra is called *H -Graded* [DSK2006] if there exists a decomposition $L = \bigoplus L_n$ such that the λ -bracket becomes graded of degree -1 , that is:

$$a_{(n)} b \in L_{p+q-n-1} \quad a \in L_p, b \in L_q, n \geq 0.$$

In particular this implies that the action of T increases degree by 1.

Note: In the literature arbitrary gradings are allowed. In this implementation we only support non-negative rational gradings.

EXAMPLES:

1. The **Virasoro** Lie conformal algebra Vir over a ring R where 12 is invertible has two generators L, C as an $R[T]$ -module. It is the direct sum of a free module of rank 1 generated by L , and a free rank one R module generated by C satisfying $TC = 0$. C is central (the λ -bracket of C with any other vector vanishes). The remaining λ -bracket is given by

$$[L_\lambda L] = TL + 2\lambda L + \frac{\lambda^3}{12} C.$$

2. The **affine** or current Lie conformal algebra $L(\mathfrak{g})$ associated to a finite dimensional Lie algebra \mathfrak{g} with non-degenerate, invariant R -bilinear form $(,)$ is given as a central extension of the free $R[T]$ module generated by \mathfrak{g} by a central element K . The λ -bracket of generators is given by

$$[a_\lambda b] = [a, b] + \lambda(a, b)K, \quad a, b \in \mathfrak{g}$$

3. The **Weyl** Lie conformal algebra, or $\beta - \gamma$ system is given as the central extension of a free $R[T]$ module with two generators β and γ , by a central element K . The only non-trivial brackets among generators are

$$[\beta_\lambda \gamma] = -[\gamma_\lambda \beta] = K$$

4. The **Neveu-Schwarz** super Lie conformal algebra is a super Lie conformal algebra which is an extension of the Virasoro Lie conformal algebra. It consists of a Virasoro generator L as in example 1 above and an *odd* generator G . The remaining brackets are given by:

$$[L_\lambda G] = \left(T + \frac{3}{2}\lambda\right) G \quad [G_\lambda G] = 2L + \frac{\lambda^2}{3} C$$

See also:

- `sage.algebras.lie_conformal_algebras.lie_conformal_algebra`
- `sage.algebras.lie_conformal_algebras.examples`

AUTHORS:

- Reimundo Heluani (2019-10-05): Initial implementation.

class `sage.categories.lie_conformal_algebras.LieConformalAlgebras`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of Lie conformal algebras.

This is the base category for all Lie conformal algebras. Subcategories with axioms are `FinitelyGenerated` and `WithBasis`. A *finitely generated* Lie conformal algebra is a Lie conformal algebra over R which is finitely generated as an $R[T]$ -module. A Lie conformal algebra *with basis* is one with a preferred basis as an R -module.

EXAMPLES:

The base category:

```
sage: C = LieConformalAlgebras(QQ); C
Category of Lie conformal algebras over Rational Field
sage: C.is_subcategory(VectorSpaces(QQ))
True
```

Some subcategories:

```
sage: LieConformalAlgebras(QQbar).FinitelyGenerated().WithBasis()
Category of finitely generated Lie conformal algebras with basis over Algebraic_
↪Field
```

In addition we support functorial constructions `Graded` and `Super`. These functors commute:

```
sage: LieConformalAlgebras(AA).Graded().Super()
Category of H-graded super Lie conformal algebras over Algebraic Real Field
sage: LieConformalAlgebras(AA).Graded().Super() is LieConformalAlgebras(AA).Super().
↪Graded()
True
```

That is, we only consider gradings on super Lie conformal algebras that are compatible with the $\mathbf{Z}/2\mathbf{Z}$ grading.

The base ring needs to be a commutative ring:

```
sage: LieConformalAlgebras(QuaternionAlgebra(2))
Traceback (most recent call last):
ValueError: base must be a commutative ring got Quaternion Algebra (-1, -1) with_
↪base ring Rational Field
```

class `ElementMethods`

Bases: `object`

is_even_odd()

Return `0` if this element is *even* and `1` if it is *odd*.

Note: This method returns `0` by default since every Lie conformal algebra can be thought as a purely even Lie conformal algebra. In order to implement a super Lie conformal algebra, the user needs to implement this method.

EXAMPLES:

```

sage: R = lie_conformal_algebras.NeveuSchwarz(QQ);
sage: R.inject_variables()
Defining L, G, C
sage: G.is_even_odd()
1

```

FinitelyGeneratedAsLambdaBracketAlgebra

alias of `sage.categories.finitely_generated_lie_conformal_algebras.FinitelyGeneratedLieConformalAlgebras`

Graded

alias of `sage.categories.graded_lie_conformal_algebras.GradedLieConformalAlgebras`

class ParentMethods

Bases: object

Super

alias of `sage.categories.super_lie_conformal_algebras.SuperLieConformalAlgebras`

WithBasis

alias of `sage.categories.lie_conformal_algebras_with_basis.LieConformalAlgebrasWithBasis`

example()

An example of parent in this category.

EXAMPLES:

```

sage: LieConformalAlgebras(QQ).example()
The Virasoro Lie conformal algebra over Rational Field

```

super_categories()

The list of super categories of this category.

EXAMPLES:

```

sage: C = LieConformalAlgebras(QQ)
sage: C.super_categories()
[Category of Lambda bracket algebras over Rational Field]
sage: C = LieConformalAlgebras(QQ).FinitelyGenerated(); C
Category of finitely generated lie conformal algebras over Rational Field
sage: C.super_categories()
[Category of finitely generated lambda bracket algebras over Rational Field,
Category of Lie conformal algebras over Rational Field]
sage: C.all_super_categories()
[Category of finitely generated lie conformal algebras over Rational Field,
Category of finitely generated lambda bracket algebras over Rational Field,
Category of Lie conformal algebras over Rational Field,
Category of Lambda bracket algebras over Rational Field,
Category of vector spaces over Rational Field,
Category of modules over Rational Field,
Category of bimodules over Rational Field on the left and Rational Field on
↳the right,
Category of right modules over Rational Field,
Category of left modules over Rational Field,
Category of commutative additive groups,

```

(continues on next page)

(continued from previous page)

```

Category of additive groups,
Category of additive inverse additive unital additive magmas,
Category of commutative additive monoids,
Category of additive monoids,
Category of additive unital additive magmas,
Category of commutative additive semigroups,
Category of additive commutative additive magmas,
Category of additive semigroups,
Category of additive magmas,
Category of sets,
Category of sets with partial maps,
Category of objects]

```

3.107 Lie Conformal Algebras With Basis

AUTHORS:

- Reimundo Heluani (2019-10-05): Initial implementation.

```

class sage.categories.lie_conformal_algebras_with_basis.LieConformalAlgebrasWithBasis(base_category)
  Bases: sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing

```

The category of Lie conformal algebras with basis.

EXAMPLES:

```

sage: LieConformalAlgebras(QQbar).WithBasis()
Category of Lie conformal algebras with basis over Algebraic Field

```

```

class FinitelyGeneratedAsLambdaBracketAlgebra(base_category)
  Bases: sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing

```

The category of finitely generated Lie conformal algebras with basis.

EXAMPLES:

```

sage: C = LieConformalAlgebras(QQbar)
sage: C.WithBasis().FinitelyGenerated()
Category of finitely generated Lie conformal algebras with basis over Algebraic_
↪Field
sage: C.WithBasis().FinitelyGenerated() is C.FinitelyGenerated().WithBasis()
True

```

```

class Graded(base_category)
  Bases: sage.categories.graded_lie_conformal_algebras.
  GradedLieConformalAlgebrasCategory

```

The category of H-graded finitely generated Lie conformal algebras with basis.

EXAMPLES:

```

sage: LieConformalAlgebras(QQbar).WithBasis().FinitelyGenerated().Graded()
Category of H-graded finitely generated Lie conformal algebras with basis_
↪over Algebraic Field

```

class Super(*base_category*)

Bases: *sage.categories.super_modules.SuperModulesCategory*

The category of super finitely generated Lie conformal algebras with basis.

EXAMPLES:

```
sage: LieConformalAlgebras(AA).WithBasis().FinitelyGenerated().Super()
Category of super finitely generated Lie conformal algebras with basis over
↪ Algebraic Real Field
```

class Graded(*base_category*)

Bases: *sage.categories.graded_modules.GradedModulesCategory*

The category of H-graded super finitely generated Lie conformal algebras with basis.

EXAMPLES:

```
sage: C = LieConformalAlgebras(QQbar).WithBasis().FinitelyGenerated()
sage: C.Graded().Super()
Category of H-graded super finitely generated Lie conformal algebras
↪ with basis over Algebraic Field
sage: C.Graded().Super() is C.Super().Graded()
True
```

class Graded(*base_category*)

Bases: *sage.categories.graded_lie_conformal_algebras.GradedLieConformalAlgebrasCategory*

The category of H-graded Lie conformal algebras with basis.

EXAMPLES:

```
sage: LieConformalAlgebras(QQbar).WithBasis().Graded()
Category of H-graded Lie conformal algebras with basis over Algebraic Field
```

class Super(*base_category*)

Bases: *sage.categories.super_modules.SuperModulesCategory*

The category of super Lie conformal algebras with basis.

EXAMPLES:

```
sage: LieConformalAlgebras(AA).WithBasis().Super()
Category of super Lie conformal algebras with basis over Algebraic Real Field
```

class Graded(*base_category*)

Bases: *sage.categories.graded_lie_conformal_algebras.GradedLieConformalAlgebrasCategory*

The category of H-graded super Lie conformal algebras with basis.

EXAMPLES:

```
sage: LieConformalAlgebras(QQbar).WithBasis().Super().Graded()
Category of H-graded super Lie conformal algebras with basis over Algebraic
↪ Field
```

class ParentMethods

Bases: object

3.108 Lie Groups

class `sage.categories.lie_groups.LieGroups`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of Lie groups.

A Lie group is a topological group with a smooth manifold structure.

EXAMPLES:

```
sage: from sage.categories.lie_groups import LieGroups
sage: C = LieGroups(QQ); C
Category of Lie groups over Rational Field
```

additional_structure()

Return None.

Indeed, the category of Lie groups defines no new structure: a morphism of topological spaces and of smooth manifolds is a morphism as Lie groups.

See also:

`Category.additional_structure()`

EXAMPLES:

```
sage: from sage.categories.lie_groups import LieGroups
sage: LieGroups(QQ).additional_structure()
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.lie_groups import LieGroups
sage: LieGroups(QQ).super_categories()
[Category of topological groups,
 Category of smooth manifolds over Rational Field]
```

3.109 Loop Crystals

class `sage.categories.loop_crystals.KirillovReshetikhinCrystals`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

Category of Kirillov-Reshetikhin crystals.

class `ElementMethods`

Bases: object

energy_function()

Return the energy function of self.

Let B be a KR crystal. Let b^\sharp denote the unique element such that $\varphi(b^\sharp) = \ell\Lambda_0$ with $\ell = \min\{\langle c, \varphi(b) \mid b \in B\}$. Let u_B denote the maximal element of B . The *energy* of $b \in B$ is given by

$$D(b) = H(b \otimes b^\sharp) - H(u_B \otimes b^\sharp),$$

where H is the *local energy function*.

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['D',4,1], 2,1)
sage: for x in K.classically_highest_weight_vectors():
.....:     x, x.energy_function()
([], 1)
([[1], [2]], 0)

sage: K = crystals.KirillovReshetikhin(['D',4,3], 1,2)
sage: for x in K.classically_highest_weight_vectors():
.....:     x, x.energy_function()
([], 2)
([[1]], 1)
([[1, 1]], 0)
```

lusztig_involution()

Return the result of the classical Lusztig involution on self.

EXAMPLES:

```
sage: KRT = crystals.KirillovReshetikhin(['D',4,1], 2, 3, model='KR')
sage: mg = KRT.module_generators[1]
sage: mg.lusztig_involution()
[[-2, -2, 1], [-1, -1, 2]]
sage: elt = mg.f_string([2,1,3,2]); elt
[[3, -2, 1], [4, -1, 2]]
sage: elt.lusztig_involution()
[[-4, -2, 1], [-3, -1, 2]]
```

class ParentMethods

Bases: object

R_matrix(K)

Return the combinatorial R -matrix of self to K .

The *combinatorial R -matrix* is the affine crystal isomorphism $R : L \otimes K \rightarrow K \otimes L$ which maps $u_L \otimes u_K$ to $u_K \otimes u_L$, where u_K is the unique element in $K = B^{r,s}$ of weight $s\Lambda_r - sc\Lambda_0$ (see [maximal_vector\(\)](#)).

INPUT:

- self – a crystal L
- K – a Kirillov-Reshetikhin crystal of the same type as L

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',2,1],1,1)
sage: L = crystals.KirillovReshetikhin(['A',2,1],1,2)
sage: f = K.R_matrix(L)
sage: [[b,f(b)] for b in crystals.TensorProduct(K,L)]
[[[[[1]], [[1, 1]]], [[1, 1]], [[1]]],
 [[[[1]], [[1, 2]]], [[1, 1]], [[2]]],
 [[[[1]], [[2, 2]]], [[1, 2]], [[2]]],
 [[[[1]], [[1, 3]]], [[1, 1]], [[3]]],
 [[[[1]], [[2, 3]]], [[1, 2]], [[3]]],
 [[[[1]], [[3, 3]]], [[1, 3]], [[3]]],
 [[[[2]], [[1, 1]]], [[1, 2]], [[1]]],
 [[[[2]], [[1, 2]]], [[2, 2]], [[1]]],
```

(continues on next page)

(continued from previous page)

```

[[[[2]], [[2, 2]], [[2, 2]], [[2]]],
[[[[2]], [[1, 3]], [[2, 3]], [[1]]],
[[[[2]], [[2, 3]], [[2, 2]], [[3]]],
[[[[2]], [[3, 3]], [[2, 3]], [[3]]],
[[[[3]], [[1, 1]], [[1, 3]], [[1]]],
[[[[3]], [[1, 2]], [[1, 3]], [[2]]],
[[[[3]], [[2, 2]], [[2, 3]], [[2]]],
[[[[3]], [[1, 3]], [[3, 3]], [[1]]],
[[[[3]], [[2, 3]], [[3, 3]], [[2]]],
[[[[3]], [[3, 3]], [[3, 3]], [[3]]]]

```

```

sage: K = crystals.KirillovReshetikhin(['D',4,1],1,1)
sage: L = crystals.KirillovReshetikhin(['D',4,1],2,1)
sage: f = K.R_matrix(L)
sage: T = crystals.TensorProduct(K,L)
sage: b = T( K(rows=[[1]]), L(rows=[]) )
sage: f(b)
[[[2], [-2]], [[1]]]

```

Alternatively, one can compute the combinatorial R -matrix using the isomorphism method of digraphs:

```

sage: K1 = crystals.KirillovReshetikhin(['A',2,1],1,1)
sage: K2 = crystals.KirillovReshetikhin(['A',2,1],2,1)
sage: T1 = crystals.TensorProduct(K1,K2)
sage: T2 = crystals.TensorProduct(K2,K1)
sage: T1.digraph().is_isomorphic(T2.digraph(), edge_labels=True,
↪certificate=True) #todo: not implemented (see #10904 and #10549)
(True, {[[[1]], [[2], [3]]]: [[1], [3]], [[2]], [[3]], [[2], [3]]}:
↪[[[2], [3]], [[3]],
[[3]], [[1], [3]]]: [[1], [3]], [[3]], [[1], [1], [3]]]: [[1], [3]],
↪[[1]], [[1]],
[[1], [2]]]: [[1], [2]], [[1]], [[2]], [[1], [2]]]: [[1], [2]],
↪[[3]],
[[1], [2]]]: [[2], [3]], [[1]], [[2]], [[1], [3]]]: [[1], [2]],
↪[[2]], [[2], [3]]]: [[2], [3]], [[2]]})

```

affinization()

Return the corresponding affinization crystal of self.

EXAMPLES:

```

sage: K = crystals.KirillovReshetikhin(['A',2,1], 1, 1)
sage: K.affinization()
Affinization of Kirillov-Reshetikhin crystal of type ['A', 2, 1] with (r,
↪s)=(1,1)

sage: K = crystals.KirillovReshetikhin(['A',2,1], 1, 1, model='KR')
sage: K.affinization()
Affinization of Kirillov-Reshetikhin tableaux of type ['A', 2, 1] and shape
↪(1, 1)

```

b_sharp()

Return the element b^\sharp of self.

Let B be a KR crystal. The element b^\sharp is the unique element such that $\varphi(b^\sharp) = \ell\Lambda_0$ with $\ell = \min\{c, \varphi(b)\} \mid b \in B\}$.

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',6,2], 2,1)
sage: K.b_sharp()
[]
sage: K.b_sharp().Phi()
Lambda[0]

sage: K = crystals.KirillovReshetikhin(['C',3,1], 1,3)
sage: K.b_sharp()
[[-1]]
sage: K.b_sharp().Phi()
2*Lambda[0]

sage: K = crystals.KirillovReshetikhin(['D',6,2], 2,2)
sage: K.b_sharp() # long time
[]
sage: K.b_sharp().Phi() # long time
2*Lambda[0]
```

cardinality()

Return the cardinality of self.

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['E',6,1], 1,1)
sage: K.cardinality()
27
sage: K = crystals.KirillovReshetikhin(['C',6,1], 4,3)
sage: K.cardinality()
4736732
```

classical_decomposition()

Return the classical decomposition of self.

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',3,1], 2,2)
sage: K.classical_decomposition()
The crystal of tableaux of type ['A', 3] and shape(s) [[2, 2]]
```

classically_highest_weight_vectors()

Return the classically highest weight elements of self.

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['E',6,1],1,1)
sage: K.classically_highest_weight_vectors()
([(1,)],)
```

is_perfect(ell=None)

Check if self is a perfect crystal of level ell.

A crystal B is perfect of level ℓ if:

1. \mathcal{B} is isomorphic to the crystal graph of a finite-dimensional $U'_q(\mathfrak{g})$ -module.
2. $\mathcal{B} \otimes \mathcal{B}$ is connected.
3. There exists a $\lambda \in X$, such that $\text{wt}(\mathcal{B}) \subset \lambda + \sum_{i \in I} \mathbf{Z}_{\leq 0} \alpha_i$ and there is a unique element in \mathcal{B} of classical weight λ .
4. For all $b \in \mathcal{B}$, $\text{level}(\varepsilon(b)) \geq \ell$.
5. For all Λ dominant weights of level ℓ , there exist unique elements $b_\Lambda, b^\Lambda \in \mathcal{B}$, such that $\varepsilon(b_\Lambda) = \Lambda = \varphi(b^\Lambda)$.

Points (1)-(3) are known to hold. This method checks points (4) and (5).

If `self` is the Kirillov-Reshetikhin crystal $B^{r,s}$, then it was proven for non-exceptional types in [FOS2010] that it is perfect if and only if s/c_r is an integer (where c_r is a constant related to the type of the crystal).

It is conjectured this is true for all affine types.

INPUT:

- `ell` – (default: s/c_r) integer; the level

REFERENCES:

[FOS2010]

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',2,1], 1, 1)
sage: K.is_perfect()
True

sage: K = crystals.KirillovReshetikhin(['C',2,1], 1, 1)
sage: K.is_perfect()
False

sage: K = crystals.KirillovReshetikhin(['C',2,1], 1, 2)
sage: K.is_perfect()
True

sage: K = crystals.KirillovReshetikhin(['E',6,1], 1,3)
sage: K.is_perfect()
True
```

Todo: Implement a version for tensor products of KR crystals.

level()

Return the level of `self` when `self` is a perfect crystal.

See also:

[`is_perfect\(\)`](#)

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',2,1], 1, 1)
sage: K.level()
1
sage: K = crystals.KirillovReshetikhin(['C',2,1], 1, 2)
sage: K.level()
1
```

(continues on next page)

(continued from previous page)

```

sage: K = crystals.KirillovReshetikhin(['D',4,1], 1, 3)
sage: K.level()
3

sage: K = crystals.KirillovReshetikhin(['C',2,1], 1, 1)
sage: K.level()
Traceback (most recent call last):
...
ValueError: this crystal is not perfect

```

local_energy_function(B)

Return the local energy function of `self` and `B`.

See [LocalEnergyFunction](#) for a definition.

EXAMPLES:

```

sage: K = crystals.KirillovReshetikhin(['A',6,2], 2,1)
sage: Kp = crystals.KirillovReshetikhin(['A',6,2], 1,1)
sage: H = K.local_energy_function(Kp); H
Local energy function of
Kirillov-Reshetikhin crystal of type ['BC', 3, 2] with (r,s)=(2,1)
tensor
Kirillov-Reshetikhin crystal of type ['BC', 3, 2] with (r,s)=(1,1)

```

maximal_vector()

Return the unique element of classical weight $s\Lambda_r$ in `self`.

EXAMPLES:

```

sage: K = crystals.KirillovReshetikhin(['C',2,1],1,2)
sage: K.maximal_vector()
[[1, 1]]
sage: K = crystals.KirillovReshetikhin(['E',6,1],1,1)
sage: K.maximal_vector()
[(1,)]

sage: K = crystals.KirillovReshetikhin(['D',4,1],2,1)
sage: K.maximal_vector()
[[1], [2]]

```

module_generator()

Return the unique module generator of classical weight $s\Lambda_r$ of the Kirillov-Reshetikhin crystal $B^{r,s}$.

EXAMPLES:

```

sage: La = RootSystem(['G',2,1]).weight_space().fundamental_weights()
sage: K = crystals.ProjectedLevelZeroLSPaths(La[1])
sage: K.module_generator()
(-Lambda[0] + Lambda[1],)

```

q_dimension(q=None, prec=None, use_product=False)

Return the q -dimension of `self`.

The q -dimension of a KR crystal is defined as the q -dimension of the underlying classical crystal.

EXAMPLES:

```
sage: KRC = crystals.KirillovReshetikhin(['A',2,1], 2,2)
sage: KRC.q_dimension()
q^4 + q^3 + 2*q^2 + q + 1
sage: KRC = crystals.KirillovReshetikhin(['D',4,1], 2,1)
sage: KRC.q_dimension()
q^10 + q^9 + 3*q^8 + 3*q^7 + 4*q^6 + 4*q^5 + 4*q^4 + 3*q^3 + 3*q^2 + q + 2
```

r()

Return the value r in `self` written as $B^{r,s}$.

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',3,1], 2,4)
sage: K.r()
2
```

s()

Return the value s in `self` written as $B^{r,s}$.

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',3,1], 2,4)
sage: K.s()
4
```

class TensorProducts(*category*, *args)

Bases: `sage.categories.tensor.TensorProductsCategory`

The category of tensor products of Kirillov-Reshetikhin crystals.

class ElementMethods

Bases: `object`

affine_grading()

Return the affine grading of `self`.

The affine grading is calculated by finding a path from `self` to a ground state path (using the helper method `e_string_to_ground_state()`) and counting the number of affine Kashiwara operators e_0 applied on the way.

OUTPUT: an integer

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',2,1],1,1)
sage: T = crystals.TensorProduct(K,K)
sage: t = T.module_generators[0]
sage: t.affine_grading()
1

sage: K = crystals.KirillovReshetikhin(['A',2,1],1,1)
sage: T = crystals.TensorProduct(K,K,K)
sage: hw = T.classically_highest_weight_vectors()
sage: for b in hw:
.....:     print("{} {}".format(b, b.affine_grading()))
[[[1]], [[1]], [[1]]] 3
```

(continues on next page)

(continued from previous page)

```

[[[2]], [[1]], [[1]]] 2
[[[1]], [[2]], [[1]]] 1
[[[3]], [[2]], [[1]]] 0

sage: K = crystals.KirillovReshetikhin(['C',2,1],1,1)
sage: T = crystals.TensorProduct(K,K,K)
sage: hw = T.classically_highest_weight_vectors()
sage: for b in hw:
....:     print("{} {}".format(b, b.affine_grading()))
[[[1]], [[1]], [[1]]] 2
[[[2]], [[1]], [[1]]] 1
[[[-1]], [[1]], [[1]]] 1
[[[1]], [[2]], [[1]]] 1
[[[-2]], [[2]], [[1]]] 0
[[[1]], [[-1]], [[1]]] 0

```

e_string_to_ground_state()

Return a string of integers in the index set (i_1, \dots, i_k) such that $e_{i_k} \cdots e_{i_1}$ of **self** is the ground state.

This method calculates a path from **self** to a ground state path using Demazure arrows as defined in Lemma 7.3 in [ST2011].

OUTPUT: a tuple of integers (i_1, \dots, i_k)

EXAMPLES:

```

sage: K = crystals.KirillovReshetikhin(['A',2,1],1,1)
sage: T = crystals.TensorProduct(K,K)
sage: t = T.module_generators[0]
sage: t.e_string_to_ground_state()
(0, 2)

sage: K = crystals.KirillovReshetikhin(['C',2,1],1,1)
sage: T = crystals.TensorProduct(K,K)
sage: t = T.module_generators[0]; t
[[[1]], [[1]]]
sage: t.e_string_to_ground_state()
(0,)
sage: x = t.e(0)
sage: x.e_string_to_ground_state()
()
sage: y = t.f_string([1,2,1,1,0]); y
[[[2]], [[1]]]
sage: y.e_string_to_ground_state()
()

```

energy_function(*algorithm=None*)

Return the energy function of **self**.

ALGORITHM:

definition

Let T be a tensor product of Kirillov-Reshetikhin crystals. Let R_i and H_i be the combinatorial R -matrix and local energy functions, respectively, acting on the i and $i + 1$ factors. Let D_B be the energy function of a single Kirillov-Reshetikhin crystal. The *energy function* is given by

$$D = \sum_{j>i} H_i R_{i+1} R_{i+2} \cdots R_{j-1} + \sum_j D_B R_1 R_2 \cdots R_{j-1},$$

where D_B acts on the rightmost factor.

grading

If `self` is an element of T , a tensor product of perfect crystals of the same level, then use the affine grading to determine the energy. Specifically, let g denote the affine grading of `self` and d the affine grading of the maximal vector in T . Then the energy of `self` is given by $d - g$.

For more details, see Theorem 7.5 in [ST2011].

INPUT:

- `algorithm` – (default: `None`) use one of the following algorithms to determine the energy function:
 - `'definition'` - use the definition of the energy function;
 - `'grading'` - use the affine grading;
 if not specified, then this uses `'grading'` if all factors are perfect of the same level and otherwise this uses `'definition'`

OUTPUT: an integer

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['A',2,1], 1, 1)
sage: T = crystals.TensorProduct(K,K)
sage: hw = T.classically_highest_weight_vectors()
sage: for b in hw:
....:     print("{} {}".format(b, b.energy_function()))
[[[1]], [[1]], [[1]]] 0
[[[2]], [[1]], [[1]]] 1
[[[1]], [[2]], [[1]]] 2
[[[3]], [[2]], [[1]]] 3

sage: K = crystals.KirillovReshetikhin(['C',2,1], 1, 2)
sage: T = crystals.TensorProduct(K,K)
sage: hw = T.classically_highest_weight_vectors()
sage: for b in hw:
....:     print("{} {}".format(b, b.energy_function()))
[[], []] 4
[[[1, 1]], []] 3
[[], [[1, 1]]] 1
[[[1, 1]], [[1, 1]]] 0
[[[1, 2]], [[1, 1]]] 1
[[[2, 2]], [[1, 1]]] 2
[[[-1, -1]], [[1, 1]]] 2
[[[1, -1]], [[1, 1]]] 2
[[[2, -1]], [[1, 1]]] 2
```

(continues on next page)

(continued from previous page)

```

sage: K = crystals.KirillovReshetikhin(['C',2,1], 1, 1)
sage: T = crystals.TensorProduct(K)
sage: t = T.module_generators[0]
sage: t.energy_function('grading')
Traceback (most recent call last):
...
NotImplementedError: all crystals in the tensor product
need to be perfect of the same level

```

class ParentMethods

Bases: object

cardinality()Return the cardinality of `self`.

EXAMPLES:

```

sage: RC = RiggedConfigurations(['A', 3, 1], [[3, 2], [1, 2]])
sage: RC.cardinality()
100
sage: len(RC.list())
100

sage: RC = RiggedConfigurations(['E', 7, 1], [[1,1]])
sage: RC.cardinality()
134
sage: len(RC.list())
134

sage: RC = RiggedConfigurations(['B', 3, 1], [[2,2],[1,2]])
sage: RC.cardinality()
5130

```

classically_highest_weight_vectors()Return the classically highest weight elements of `self`.

This works by using a backtracking algorithm since if $b_2 \otimes b_1$ is classically highest weight then b_1 is classically highest weight.

EXAMPLES:

```

sage: K = crystals.KirillovReshetikhin(['A',2,1],1,1)
sage: T = crystals.TensorProduct(K,K,K)
sage: T.classically_highest_weight_vectors()
([[1]], [[1]], [[1]]),
 [[2]], [[1]], [[1]]),
 [[1]], [[2]], [[1]]),
 [[3]], [[2]], [[1]])

```

maximal_vector()Return the maximal vector of `self`.

EXAMPLES:

```

sage: K = crystals.KirillovReshetikhin(['A',2,1],1,1)
sage: T = crystals.TensorProduct(K,K,K)
sage: T.maximal_vector()
[[[1]], [[1]], [[1]]]

```

one_dimensional_configuration_sum(*q=None, group_components=True*)

Compute the one-dimensional configuration sum of `self`.

INPUT:

- `q` – (default: `None`) a variable or `None`; if `None`, a variable `q` is set in the code
- `group_components` – (default: `True`) boolean; if `True`, then the terms are grouped by classical component

The one-dimensional configuration sum is the sum of the weights of all elements in the crystal weighted by the energy function.

EXAMPLES:

```

sage: K = crystals.KirillovReshetikhin(['A',2,1],1,1)
sage: T = crystals.TensorProduct(K,K)
sage: T.one_dimensional_configuration_sum()
B[-2*Lambda[1] + 2*Lambda[2]] + (q+1)*B[-Lambda[1]]
+ (q+1)*B[Lambda[1] - Lambda[2]] + B[2*Lambda[1]]
+ B[-2*Lambda[2]] + (q+1)*B[Lambda[2]]
sage: R.<t> = ZZ[]
sage: T.one_dimensional_configuration_sum(t, False)
B[-2*Lambda[1] + 2*Lambda[2]] + (t+1)*B[-Lambda[1]]
+ (t+1)*B[Lambda[1] - Lambda[2]] + B[2*Lambda[1]]
+ B[-2*Lambda[2]] + (t+1)*B[Lambda[2]]

sage: R = RootSystem(['A',2,1])
sage: La = R.weight_space().basis()
sage: LS = crystals.ProjectedListZeroLSPaths(2*La[1])
sage: LS.one_dimensional_configuration_sum() == T.one_dimensional_
↪configuration_sum() # long time
True

```

extra_super_categories()

EXAMPLES:

```

sage: from sage.categories.loop_crystals import KirillovReshetikhinCrystals
sage: KirillovReshetikhinCrystals().TensorProducts().extra_super_
↪categories()
[Category of finite regular loop crystals]

```

super_categories()

EXAMPLES:

```

sage: from sage.categories.loop_crystals import KirillovReshetikhinCrystals
sage: KirillovReshetikhinCrystals().super_categories()
[Category of finite regular loop crystals]

```

class `sage.categories.loop_crystals.LocalEnergyFunction`(*B, Bp, normalization=0*)

Bases: `sage.categories.map.Map`

The local energy function.

Let B and B' be Kirillov-Reshetikhin crystals with maximal vectors u_B and $u_{B'}$ respectively. The *local energy function* $H : B \otimes B' \rightarrow \mathbf{Z}$ is the function which satisfies

$$H(e_0(b \otimes b')) = H(b \otimes b') + \begin{cases} 1 & \text{if } i = 0 \text{ and LL,} \\ -1 & \text{if } i = 0 \text{ and RR,} \\ 0 & \text{otherwise,} \end{cases}$$

where LL (resp. RR) denote e_0 acts on the left (resp. right) on both $b \otimes b'$ and $R(b \otimes b')$, and normalized by $H(u_B \otimes u_{B'}) = 0$.

INPUT:

- B – a Kirillov-Reshetikhin crystal
- B' – a Kirillov-Reshetikhin crystal
- `normalization` – (default: 0) the normalization value

EXAMPLES:

```
sage: K = crystals.KirillovReshetikhin(['C', 2, 1], 1, 2)
sage: K2 = crystals.KirillovReshetikhin(['C', 2, 1], 2, 1)
sage: H = K.local_energy_function(K2)
sage: T = tensor([K, K2])
sage: hw = T.classically_highest_weight_vectors()
sage: for b in hw:
.....:     b, H(b)
([[], [[1], [2]]], 1)
([[1, 1]], [[1], [2]]], 0)
([[2, -2]], [[1], [2]]], 1)
([[1, -2]], [[1], [2]]], 1)
```

REFERENCES:

[KKMMNN1992]

class `sage.categories.loop_crystals.LoopCrystals`($s=None$)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of $U'_q(\mathfrak{g})$ -crystals, where \mathfrak{g} is of affine type.

The category is called loop crystals as we can also consider them as crystals corresponding to the loop algebra $\mathfrak{g}_0[t]$, where \mathfrak{g}_0 is the corresponding classical type.

EXAMPLES:

```
sage: from sage.categories.loop_crystals import LoopCrystals
sage: C = LoopCrystals()
sage: C
Category of loop crystals
sage: C.super_categories()
[Category of crystals]
sage: C.example()
Kirillov-Reshetikhin crystal of type ['A', 3, 1] with (r,s)=(1,1)
```

class `ParentMethods`

Bases: `object`

digraph($subset=None$, $index_set=None$)

Return the `DiGraph` associated to `self`.

INPUT:

- `subset` – (optional) a subset of vertices for which the digraph should be constructed
- `index_set` – (optional) the index set to draw arrows

See also:

`sage.categories.crystals.Crystals.ParentMethods.digraph()`

EXAMPLES:

```
sage: C = crystals.KirillovReshetikhin(['D',4,1], 2, 1)
sage: G = C.digraph()
sage: G.latex_options() # optional - dot2tex
LaTeX options for Digraph on 29 vertices:
{...'edge_options': <function ... at ...>...}
sage: view(G, tightpage=True) # optional - dot2tex graphviz, not tested.
↪(opens external window)
```

weight_lattice_realization()

Return the weight lattice realization used to express weights of elements in `self`.

The default is to use the non-extended affine weight lattice.

EXAMPLES:

```
sage: C = crystals.Letters(['A', 5])
sage: C.weight_lattice_realization()
Ambient space of the Root system of type ['A', 5]
sage: K = crystals.KirillovReshetikhin(['A',2,1], 1, 1)
sage: K.weight_lattice_realization()
Weight lattice of the Root system of type ['A', 2, 1]
```

example($n=3$)

Return an example of Kirillov-Reshetikhin crystals, as per `Category.example()`.

EXAMPLES:

```
sage: from sage.categories.loop_crystals import LoopCrystals
sage: B = LoopCrystals().example(); B
Kirillov-Reshetikhin crystal of type ['A', 3, 1] with (r,s)=(1,1)
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.loop_crystals import LoopCrystals
sage: LoopCrystals().super_categories()
[Category of crystals]
```

class `sage.categories.loop_crystals.RegularLoopCrystals($s=None$)`

Bases: `sage.categories.category_singleton.Category_singleton`

The category of regular $U'_q(\mathfrak{g})$ -crystals, where \mathfrak{g} is of affine type.

class `ElementMethods`

Bases: `object`

classical_weight()

Return the classical weight of `self`.

EXAMPLES:

```

sage: R = RootSystem(['A',2,1])
sage: La = R.weight_space().basis()
sage: LS = crystals.ProjectLevelZeroLSPaths(2*La[1])
sage: hw = LS.classically_highest_weight_vectors()
sage: [(v.weight(), v.classical_weight()) for v in hw]
[(-2*Lambda[0] + 2*Lambda[1], (2, 0, 0)),
 (-Lambda[0] + Lambda[2], (1, 1, 0))]

```

super_categories()

EXAMPLES:

```

sage: from sage.categories.loop_crystals import RegularLoopCrystals
sage: RegularLoopCrystals().super_categories()
[Category of regular crystals,
 Category of loop crystals]

```

3.110 L-trivial semigroups

class `sage.categories.l_trivial_semigroups.LTrivialSemigroups`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

Commutative_extra_super_categories()

Implement the fact that a commutative R -trivial semigroup is J -trivial.

EXAMPLES:

```

sage: Semigroups().LTrivial().Commutative_extra_super_categories()
[Category of j trivial semigroups]

```

RTrivial_extra_super_categories()

Implement the fact that an L -trivial and R -trivial semigroup is J -trivial.

EXAMPLES:

```

sage: Semigroups().LTrivial().RTrivial_extra_super_categories()
[Category of j trivial magmas]

```

extra_super_categories()

Implement the fact that a L -trivial semigroup is H -trivial.

EXAMPLES:

```

sage: Semigroups().LTrivial().extra_super_categories()
[Category of h trivial semigroups]

```

3.111 Magmas

class `sage.categories.magmas.Magmas`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of (multiplicative) magmas.

A magma is a set with a binary operation $*$.

EXAMPLES:

```
sage: Magmas()
Category of magmas
sage: Magmas().super_categories()
[Category of sets]
sage: Magmas().all_super_categories()
[Category of magmas, Category of sets,
Category of sets with partial maps, Category of objects]
```

The following axioms are defined by this category:

```
sage: Magmas().Associative()
Category of semigroups
sage: Magmas().Unital()
Category of unital magmas
sage: Magmas().Commutative()
Category of commutative magmas
sage: Magmas().Unital().Inverse()
Category of inverse unital magmas
sage: Magmas().Associative()
Category of semigroups
sage: Magmas().Associative().Unital()
Category of monoids
sage: Magmas().Associative().Unital().Inverse()
Category of groups
```

class `Algebras`(*category, *args*)

Bases: `sage.categories.algebra_functor.AlgebrasCategory`

class `ParentMethods`

Bases: `object`

is_field(*proof=True*)

Return True if `self` is a field.

For a magma algebra RS this is always false unless S is trivial and the base ring R is a field.

EXAMPLES:

```
sage: SymmetricGroup(1).algebra(QQ).is_field()
True
sage: SymmetricGroup(1).algebra(ZZ).is_field()
False
sage: SymmetricGroup(2).algebra(QQ).is_field()
False
```

extra_super_categories()

EXAMPLES:

```
sage: Magmas().Commutative().Algebras(QQ).extra_super_categories()
[Category of commutative magmas]
```

This implements the fact that the algebra of a commutative magma is commutative:

```
sage: Magmas().Commutative().Algebras(QQ).super_categories()
[Category of magma algebras over Rational Field, Category of commutative_
↪magmas]
```

In particular, commutative monoid algebras are commutative algebras:

```
sage: Monoids().Commutative().Algebras(QQ).is_subcategory(Algebras(QQ).
↪Commutative())
True
```

Associative

alias of *sage.categories.semigroups.Semigroups*

class CartesianProducts(category, *args)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

class ParentMethods

Bases: object

product(left, right)

EXAMPLES:

```
sage: C = Magmas().CartesianProducts().example(); C
The Cartesian product of (Rational Field, Integer Ring, Integer Ring)
sage: x = C.an_element(); x
(1/2, 1, 1)
sage: x * x
(1/4, 1, 1)

sage: A = SymmetricGroupAlgebra(QQ, 3)
sage: x = cartesian_product([A([1,3,2]), A([2,3,1])])
sage: y = cartesian_product([A([1,3,2]), A([2,3,1])])
sage: cartesian_product([A,A]).product(x,y)
B[(0, [1, 2, 3])] + B[(1, [3, 1, 2])]
sage: x*y
B[(0, [1, 2, 3])] + B[(1, [3, 1, 2])]
```

example()

Return an example of Cartesian product of magmas.

EXAMPLES:

```
sage: C = Magmas().CartesianProducts().example(); C
The Cartesian product of (Rational Field, Integer Ring, Integer Ring)
sage: C.category()
Join of Category of Cartesian products of commutative rings and
Category of Cartesian products of metric spaces
sage: sorted(C.category().axioms())
```

(continues on next page)

(continued from previous page)

```
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse',
 'AdditiveUnital', 'Associative', 'Commutative',
 'Distributive', 'Unital']
```

```
sage: TestSuite(C).run()
```

extra_super_categories()

This implements the fact that a subquotient (and therefore a quotient or subobject) of a finite set is finite.

EXAMPLES:

```
sage: Semigroups().CartesianProducts().extra_super_categories()
[Category of semigroups]
sage: Semigroups().CartesianProducts().super_categories()
[Category of semigroups, Category of Cartesian products of magmas]
```

class Commutative(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

class Algebras(*category, *args*)

Bases: *sage.categories.algebra_functor.AlgebrasCategory*

extra_super_categories()

EXAMPLES:

```
sage: Magmas().Commutative().Algebras(QQ).extra_super_categories()
[Category of commutative magmas]
```

This implements the fact that the algebra of a commutative magma is commutative:

```
sage: Magmas().Commutative().Algebras(QQ).super_categories()
[Category of magma algebras over Rational Field,
 Category of commutative magmas]
```

In particular, commutative monoid algebras are commutative algebras:

```
sage: Monoids().Commutative().Algebras(QQ).is_subcategory(Algebras(QQ).
 ↪Commutative())
True
```

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

extra_super_categories()

Implement the fact that a Cartesian product of commutative additive magmas is still an commutative additive magmas.

EXAMPLES:

```
sage: C = Magmas().Commutative().CartesianProducts()
sage: C.extra_super_categories()
[Category of commutative magmas]
sage: C.axioms()
frozenset({'Commutative'})
```

class ParentMethods

Bases: object

is_commutative()

Return True, since commutative magmas are commutative.

EXAMPLES:

```
sage: Parent(QQ, category=CommutativeRings()).is_commutative()
True
```

class ElementMethods

Bases: object

is_idempotent()

Test whether self is idempotent.

EXAMPLES:

```
sage: S = Semigroups().example("free"); S
An example of a semigroup: the free semigroup generated by ('a', 'b', 'c',
↪ 'd')
sage: a = S('a')
sage: a^2
'aa'
sage: a.is_idempotent()
False
```

```
sage: L = Semigroups().example("leftzero"); L
An example of a semigroup: the left zero semigroup
sage: x = L('x')
sage: x^2
'x'
sage: x.is_idempotent()
True
```

FinitelyGeneratedAsMagmaalias of *sage.categories.finitely_generated_magmas.FinitelyGeneratedMagmas***class JTrivial(base_category)**Bases: *sage.categories.category_with_axiom.CategoryWithAxiom***class ParentMethods**

Bases: object

multiplication_table(names='letters', elements=None)

Returns a table describing the multiplication operation.

Note: The order of the elements in the row and column headings is equal to the order given by the table's `list()` method. The association can also be retrieved with the `dict()` method.

INPUT:

- names - the type of names used
 - 'letters' - lowercase ASCII letters are used for a base 26 representation of the elements' positions in the list given by `column_keys()`, padded to a common width with leading 'a's.
 - 'digits' - base 10 representation of the elements' positions in the list given by `column_keys()`, padded to a common width with leading zeros.

- 'elements' - the string representations of the elements themselves.
- a list - a list of strings, where the length of the list equals the number of elements.
- elements - default = None. A list of elements of the magma, in forms that can be coerced into the structure, eg. their string representations. This may be used to impose an alternate ordering on the elements, perhaps when this is used in the context of a particular structure. The default is to use whatever ordering the `S.list` method returns. Or the `elements` can be a subset which is closed under the operation. In particular, this can be used when the base set is infinite.

OUTPUT: The multiplication table as an object of the class `OperationTable` which defines several methods for manipulating and displaying the table. See the documentation there for full details to supplement the documentation here.

EXAMPLES:

The default is to represent elements as lowercase ASCII letters.

```
sage: G = CyclicPermutationGroup(5)
sage: G.multiplication_table()
*  a b c d e
  +-----
a| a b c d e
b| b c d e a
c| c d e a b
d| d e a b c
e| e a b c d
```

All that is required is that an algebraic structure has a multiplication defined. A *LeftRegularBand* is an example of a finite semigroup. The `names` argument allows displaying the elements in different ways.

```
sage: from sage.categories.examples.finite_semigroups import LeftRegularBand
sage: L = LeftRegularBand(('a', 'b'))
sage: T = L.multiplication_table(names='digits')
sage: T.column_keys()
('a', 'ab', 'b', 'ba')
sage: T
*  0 1 2 3
  +-----
0| 0 1 1 1
1| 1 1 1 1
2| 3 3 2 3
3| 3 3 3 3
```

Specifying the elements in an alternative order can provide more insight into how the operation behaves.

```
sage: L = LeftRegularBand(('a', 'b', 'c'))
sage: elts = sorted(L.list())
sage: L.multiplication_table(elements=elts)
*  a b c d e f g h i j k l m n o
  +-----
a| a b c d e b b c c c d d e e e
b| b b c c c b b c c c c c c c c
c| c c c c c c c c c c c c c c c
d| d e e d e e e e e d d e e e
e| e e e e e e e e e e e e e e
```

(continues on next page)

(continued from previous page)

```

f| g g h h h f g h i j i j j i j
g| g g h h h g g h h h h h h h
h| h h h h h h h h h h h h h h
i| j j j j j i j j i j i j j i j
j| j j j j j j j j j j j j j j
k| l m m l m n o o n o k l m n o
l| l m m l m m m m m l l m m m
m| m m m m m m m m m m m m m m
n| o o o o o n o o n o n o o n o
o| o o o o o o o o o o o o o o

```

The `elements` argument can be used to provide a subset of the elements of the structure. The subset must be closed under the operation. Elements need only be in a form that can be coerced into the set. The `names` argument can also be used to request that the elements be represented with their usual string representation.

```

sage: L=LeftRegularBand(('a','b','c'))
sage: elts=['a', 'c', 'ac', 'ca']
sage: L.multiplication_table(names='elements', elements=elts)
*   'a'  'c' 'ac' 'ca'
+-----+
'a'| 'a' 'ac' 'ac' 'ac'
'c'| 'ca' 'c' 'ca' 'ca'
'ac'| 'ac' 'ac' 'ac' 'ac'
'ca'| 'ca' 'ca' 'ca' 'ca'

```

The table returned can be manipulated in various ways. See the documentation for [OperationTable](#) for more comprehensive documentation.

```

sage: G=AlternatingGroup(3)
sage: T=G.multiplication_table()
sage: T.column_keys()
((), (1,2,3), (1,3,2))
sage: T.translation()
{'a': (), 'b': (1,2,3), 'c': (1,3,2)}
sage: T.change_names(['x', 'y', 'z'])
sage: T.translation()
{'x': (), 'y': (1,2,3), 'z': (1,3,2)}
sage: T
*   x y z
+-----+
x| x y z
y| y z x
z| z x y

```

product(x, y)

The binary multiplication of the magma.

INPUT:

- x, y – elements of this magma

OUTPUT:

- an element of the magma (the product of x and y)

EXAMPLES:

```
sage: S = Semigroups().example("free")
sage: x = S('a'); y = S('b')
sage: S.product(x, y)
'ab'
```

A parent in `Magma`s() must either implement `product()` in the parent class or `_mul_` in the element class. By default, the addition method on elements `x`, `_mul_(y)` calls `S.product(x,y)`, and reciprocally.

As a bonus, `S.product` models the binary function from `S` to `S`:

```
sage: bin = S.product
sage: bin(x,y)
'ab'
```

Currently, `S.product` is just a bound method:

```
sage: bin # py2
<bound method FreeSemigroup_with_category.product of An example of a
↳semigroup: the free semigroup generated by ('a', 'b', 'c', 'd')>
sage: bin # py3, due to difference in how bound methods are repr'd
<bound method FreeSemigroup.product of An example of a semigroup: the free
↳semigroup generated by ('a', 'b', 'c', 'd')>
```

When Sage will support multivariate morphisms, it will be possible, and in fact recommended, to enrich `S.product` with extra mathematical structure. This will typically be implemented using lazy attributes.:

```
sage: bin # todo: not implemented
Generic binary morphism:
From: (S x S)
To: S
```

`product_from_element_class_mul(x, y)`

The binary multiplication of the magma.

INPUT:

- `x, y` – elements of this magma

OUTPUT:

- an element of the magma (the product of `x` and `y`)

EXAMPLES:

```
sage: S = Semigroups().example("free")
sage: x = S('a'); y = S('b')
sage: S.product(x, y)
'ab'
```

A parent in `Magma`s() must either implement `product()` in the parent class or `_mul_` in the element class. By default, the addition method on elements `x`, `_mul_(y)` calls `S.product(x,y)`, and reciprocally.

As a bonus, `S.product` models the binary function from `S` to `S`:

```
sage: bin = S.product
sage: bin(x,y)
'ab'
```

Currently, `S.product` is just a bound method:

```
sage: bin # py2
<bound method FreeSemigroup_with_category.product of An example of a
↳semigroup: the free semigroup generated by ('a', 'b', 'c', 'd')>
sage: bin # py3, due to difference in how bound methods are repr'd
<bound method FreeSemigroup.product of An example of a semigroup: the free
↳semigroup generated by ('a', 'b', 'c', 'd')>
```

When Sage will support multivariate morphisms, it will be possible, and in fact recommended, to enrich `S.product` with extra mathematical structure. This will typically be implemented using lazy attributes.:

```
sage: bin # todo: not implemented
Generic binary morphism:
From: (S x S)
To: S
```

class Realizations(*category*, *args)

Bases: `sage.categories.realizations.RealizationsCategory`

class ParentMethods

Bases: object

product_by_coercion(*left*, *right*)

Default implementation of product for realizations.

This method coerces to the realization specified by `self.realization_of().a_realization()`, computes the product in that realization, and then coerces back.

EXAMPLES:

```
sage: Out = Sets().WithRealizations().example().Out(); Out
The subset algebra of {1, 2, 3} over Rational Field in the Out basis
sage: Out.product
<bound method SubsetAlgebra.Out_with_category.product_by_coercion of The
↳subset algebra of {1, 2, 3} over Rational Field in the Out basis>
sage: Out.product.__module__
'sage.categories.magnas'
sage: x = Out.an_element()
sage: y = Out.an_element()
sage: Out.product(x, y)
Out[{}] + 4*Out[{1}] + 9*Out[{2}] + Out[{1, 2}]
```

class SubcategoryMethods

Bases: object

Associative()

Return the full subcategory of the associative objects of `self`.

A (multiplicative) magma `Magnas M` is *associative* if, for all $x, y, z \in M$,

$$x * (y * z) = (x * y) * z$$

See also:

[Wikipedia article Associative_property](#)

EXAMPLES:

```
sage: Magmas().Associative()
Category of semigroups
```

Commutative()

Return the full subcategory of the commutative objects of `self`.

A (multiplicative) magma `Magmas M` is *commutative* if, for all $x, y \in M$,

$$x * y = y * x$$

See also:

[Wikipedia article Commutative_property](#)

EXAMPLES:

```
sage: Magmas().Commutative()
Category of commutative magmas
sage: Monoids().Commutative()
Category of commutative monoids
```

Distributive()

Return the full subcategory of the objects of `self` where `*` is distributive on `+`.

INPUT:

- `self` – a subcategory of *Magmas* and *AdditiveMagmas*

Given that Sage does not yet know that the category `MagmasAndAdditiveMagmas` is the intersection of the categories *Magmas* and *AdditiveMagmas*, the method `MagmasAndAdditiveMagmas.SubcategoryMethods.Distributive()` is not available, as would be desirable, for this intersection.

This method is a workaround. It checks that `self` is a subcategory of both *Magmas* and *AdditiveMagmas* and upgrades it to a subcategory of `MagmasAndAdditiveMagmas` before applying the axiom. It complains otherwise, since the `Distributive` axiom does not make sense for a plain magma.

EXAMPLES:

```
sage: (Magmas() & AdditiveMagmas()).Distributive()
Category of distributive magmas and additive magmas
sage: (Monoids() & CommutativeAdditiveGroups()).Distributive()
Category of rings

sage: Magmas().Distributive()
Traceback (most recent call last):
...
ValueError: The distributive axiom only makes sense on a magma which is,
↳simultaneously an additive magma
sage: Semigroups().Distributive()
Traceback (most recent call last):
...
ValueError: The distributive axiom only makes sense on a magma which is,
↳simultaneously an additive magma
```

FinitelyGenerated()

Return the subcategory of the objects of `self` that are endowed with a distinguished finite set of (multiplicative) magma generators.

EXAMPLES:

This is a shorthand for `FinitelyGeneratedAsMagma()`, which see:

```
sage: Magmas().FinitelyGenerated()
Category of finitely generated magmas
sage: Semigroups().FinitelyGenerated()
Category of finitely generated semigroups
sage: Groups().FinitelyGenerated()
Category of finitely generated enumerated groups
```

An error is raised if this is ambiguous:

```
sage: (Magmas() & AdditiveMagmas()).FinitelyGenerated()
Traceback (most recent call last):
...
ValueError: FinitelyGenerated is ambiguous for
Join of Category of magmas and Category of additive magmas.
Please use explicitly one of the FinitelyGeneratedAsXXX methods
```

Note: Checking that there is no ambiguity currently assumes that all the other “finitely generated” axioms involve an additive structure. As of Sage 6.4, this is correct.

The use of this shorthand should be reserved for casual interactive use or when there is no risk of ambiguity.

FinitelyGeneratedAsMagma()

Return the subcategory of the objects of `self` that are endowed with a distinguished finite set of (multiplicative) magma generators.

A set S of elements of a multiplicative magma form a *set of generators* if any element of the magma can be expressed recursively from elements of S and products thereof.

It is not imposed that morphisms shall preserve the distinguished set of generators; hence this is a full subcategory.

See also:

[Wikipedia article Unital_magma#unital](#)

EXAMPLES:

```
sage: Magmas().FinitelyGeneratedAsMagma()
Category of finitely generated magmas
```

Being finitely generated does depend on the structure: for a ring, being finitely generated as a magma, as an additive magma, or as a ring are different concepts. Hence the name of this axiom is explicit:

```
sage: Rings().FinitelyGeneratedAsMagma()
Category of finitely generated as magma enumerated rings
```

On the other hand, it does not depend on the multiplicative structure: for example a group is finitely generated if and only if it is finitely generated as a magma. A short hand is provided when there is no ambiguity, and the output tries to reflect that:


```

sage: Semigroups().FinitelyGenerated()
Category of finitely generated semigroups
sage: Groups().FinitelyGenerated()
Category of finitely generated enumerated groups

sage: Semigroups().FinitelyGenerated().axioms()
frozenset({'Associative', 'Enumerated', 'FinitelyGeneratedAsMagma'})

```

Note that the set of generators may depend on the actual category; for example, in a group, one can often use less generators since it is allowed to take inverses.

JTrivial()

Return the full subcategory of the J -trivial objects of `self`.

This axiom is in fact only meaningful for *semigroups*. This stub definition is here as a workaround for [trac ticket #20515](#), in order to define the J -trivial axiom as the intersection of the L and R -trivial axioms.

See also:

[Semigroups.SubcategoryMethods.JTrivial\(\)](#)

Unital()

Return the subcategory of the unital objects of `self`.

A (multiplicative) magma `Magma` M is *unital* if it admits an element 1 , called *unit*, such that for all $x \in M$,

$$1 * x = x * 1 = x$$

This element is necessarily unique, and should be provided as `M.one()`.

See also:

[Wikipedia article Unital_magma#unital](#)

EXAMPLES:

```

sage: Magmas().Unital()
Category of unital magmas
sage: Semigroups().Unital()
Category of monoids
sage: Monoids().Unital()
Category of monoids
sage: from sage.categories.associative_algebras import AssociativeAlgebras
sage: AssociativeAlgebras(QQ).Unital()
Category of algebras over Rational Field

```

class Subquotients(category, *args)

Bases: [sage.categories.subquotients.SubquotientsCategory](#)

The category of subquotient magmas.

See [Sets.SubcategoryMethods.Subquotients\(\)](#) for the general setup for subquotients. In the case of a subquotient magma S of a magma G , the condition that r be a morphism in \mathcal{A}_S can be rewritten as follows:

- for any two $a, b \in S$ the identity $a \times_S b = r(l(a) \times_G l(b))$ holds.

This is used by this category to implement the product \times_S of S from l and r and the product of G .

EXAMPLES:

```
sage: Semigroups().Subquotients().all_super_categories()
[Category of subquotients of semigroups, Category of semigroups,
Category of subquotients of magmas, Category of magmas,
Category of subquotients of sets, Category of sets,
Category of sets with partial maps,
Category of objects]
```

class ParentMethods

Bases: object

product(x, y)

Return the product of two elements of self.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: S
An example of a (sub)quotient semigroup:
a quotient of the left zero semigroup
sage: S.product(S(19), S(3))
19
```

Here is a more elaborate example involving a sub algebra:

```
sage: Z = SymmetricGroup(5).algebra(QQ).center()
sage: B = Z.basis()
sage: B[3] * B[2]
4*B[2] + 6*B[3] + 5*B[6]
```

class Unital(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

class Algebras(*category, *args*)

Bases: *sage.categories.algebra_functor.AlgebrasCategory*

extra_super_categories()

EXAMPLES:

```
sage: Magmas().Commutative().Algebras(QQ).extra_super_categories()
[Category of commutative magmas]
```

This implements the fact that the algebra of a commutative magma is commutative:

```
sage: Magmas().Commutative().Algebras(QQ).super_categories()
[Category of magma algebras over Rational Field,
Category of commutative magmas]
```

In particular, commutative monoid algebras are commutative algebras:

```
sage: Monoids().Commutative().Algebras(QQ).is_subcategory(Algebras(QQ).
↳Commutative())
True
```

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

class ElementMethods

Bases: object

class ParentMethods

Bases: object

one()

Return the unit of this Cartesian product.

It is built from the units for the Cartesian factors of `self`.

EXAMPLES:

```
sage: cartesian_product([QQ, ZZ, RR]).one()
(1, 1, 1.0000000000000000)
```

extra_super_categories()

Implement the fact that a Cartesian product of unital magmas is a unital magma

EXAMPLES:

```
sage: C = Magmas().Unital().CartesianProducts()
sage: C.extra_super_categories()
[Category of unital magmas]
sage: C.axioms()
frozenset({'Unital'})

sage: Monoids().CartesianProducts().is_subcategory(Monoids())
True
```

class ElementMethods

Bases: object

class Inverse(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

extra_super_categories()

Implement the fact that a Cartesian product of magmas with inverses is a magma with inverse.

EXAMPLES:

```
sage: C = Magmas().Unital().Inverse().CartesianProducts()
sage: C.extra_super_categories()
[Category of inverse unital magmas]
sage: sorted(C.axioms())
['Inverse', 'Unital']
```

class ParentMethods

Bases: object

is_empty()

Return whether `self` is empty.

Since this set is a unital magma it is not empty and this method always return False.

EXAMPLES:

```
sage: S = SymmetricGroup(2)
sage: S.is_empty()
False

sage: M = Monoids().example()
sage: M.is_empty()
False
```

one()

Return the unit of the monoid, that is the unique neutral element for $*$.

Note: The default implementation is to coerce 1 into `self`. It is recommended to override this method because the coercion from the integers:

- is not always meaningful (except for 1);
 - often uses `self.one()`.
-

EXAMPLES:

```
sage: M = Monoids().example(); M
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
sage: M.one()
''
```

class Realizations(*category*, *args)

Bases: [sage.categories.realizations.RealizationsCategory](#)

class ParentMethods

Bases: object

one()

Return the unit element of `self`.

```
sage: from sage.combinat.root_system.extended_affine_weyl_group import ExtendedAffineWeylGroup
sage: PvW0 = ExtendedAffineWeylGroup(['A',2,1]).PvW0()
sage: PvW0 in Magmas().Unital().Realizations() True
sage: PvW0.one() 1
```

class SubcategoryMethods

Bases: object

Inverse()

Return the full subcategory of the inverse objects of `self`.

An inverse :class:` (multiplicative) magma <Magmas>` is a *unital magma* such that every element admits both an inverse on the left and on the right. Such a magma is also called a *loop*.

See also:

[Wikipedia article Inverse_element](#), [Wikipedia article Quasigroup](#)

EXAMPLES:

```
sage: Magmas().Unital().Inverse()
Category of inverse unital magmas
sage: Monoids().Inverse()
Category of groups
```

additional_structure()

Return self.

Indeed, the category of unital magmas defines an additional structure, namely the unit of the magma which shall be preserved by morphisms.

See also:

[Category.additional_structure\(\)](#)

EXAMPLES:

```
sage: Magmas().Unital().additional_structure()
Category of unital magmas
```

super_categories()

EXAMPLES:

```
sage: Magmas().super_categories()
[Category of sets]
```

3.112 Magmas and Additive Magmas

class sage.categories.magmas_and_additive_magmas.**MagmasAndAdditiveMagmas**(s=None)

Bases: [sage.categories.category_singleton.Category_singleton](#)

The category of sets $(S, +, *)$ with an additive operation '+' and a multiplicative operation *

EXAMPLES:

```
sage: from sage.categories.magmas_and_additive_magmas import MagmasAndAdditiveMagmas
sage: C = MagmasAndAdditiveMagmas(); C
Category of magmas and additive magmas
```

This is the base category for the categories of rings and their variants:

```
sage: C.Distributive()
Category of distributive magmas and additive magmas
sage: C.Distributive().Associative().AdditiveAssociative().AdditiveCommutative().
->AdditiveUnital().AdditiveInverse()
Category of rngs
sage: C.Distributive().Associative().AdditiveAssociative().AdditiveCommutative().
->AdditiveUnital().Unital()
Category of semirings
sage: C.Distributive().Associative().AdditiveAssociative().AdditiveCommutative().
->AdditiveUnital().AdditiveInverse().Unital()
Category of rings
```

This category is really meant to represent the intersection of the categories of [Magmas](#) and [AdditiveMagmas](#); however Sage's infrastructure does not allow yet to model this:

```
sage: Magmas() & AdditiveMagmas()
Join of Category of magmas and Category of additive magmas
```

(continues on next page)

(continued from previous page)

```
sage: Magmas() & AdditiveMagmas()      # todo: not implemented
Category of magmas and additive magmas
```

```
class CartesianProducts(category, *args)
```

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

```
extra_super_categories()
```

Implement the fact that this structure is stable under Cartesian products.

Distributive

alias of `sage.categories.distributive_magmas_and_additive_magmas.DistributiveMagmasAndAdditiveMagmas`

```
class SubcategoryMethods
```

Bases: object

```
Distributive()
```

Return the full subcategory of the objects of `self` where `*` is distributive on `+`.

A *magma* and *additive magma* M is *distributive* if, for all $x, y, z \in M$,

$$x * (y + z) = x * y + x * z \text{ and } (x + y) * z = x * z + y * z$$

EXAMPLES:

```
sage: from sage.categories.magmas_and_additive_magmas import
↳ MagmasAndAdditiveMagmas
sage: C = MagmasAndAdditiveMagmas().Distributive(); C
Category of distributive magmas and additive magmas
```

Note: Given that Sage does not know that `MagmasAndAdditiveMagmas` is the intersection of `Magmas` and `AdditiveMagmas`, this method is not available for:

```
sage: Magmas() & AdditiveMagmas()
Join of Category of magmas and Category of additive magmas
```

Still, the natural syntax works:

```
sage: (Magmas() & AdditiveMagmas()).Distributive()
Category of distributive magmas and additive magmas
```

thanks to a workaround implemented in `Magmas.SubcategoryMethods.Distributive()`:

```
sage: (Magmas() & AdditiveMagmas()).Distributive.__module__
'sage.categories.magmas'
```

```
additional_structure()
```

Return None.

Indeed, this category is meant to represent the join of `AdditiveMagmas` and `Magmas`. As such, it defines no additional structure.

See also:

`Category.additional_structure()`

EXAMPLES:

```
sage: from sage.categories.magmas_and_additive_magmas import ↵
↵MagmasAndAdditiveMagmas
sage: MagmasAndAdditiveMagmas().additional_structure()
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.magmas_and_additive_magmas import ↵
↵MagmasAndAdditiveMagmas
sage: MagmasAndAdditiveMagmas().super_categories()
[Category of magmas, Category of additive magmas]
```

3.113 Non-unital non-associative algebras

class `sage.categories.magmatic_algebras.MagmaticAlgebras`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of algebras over a given base ring.

An algebra over a ring R is a module over R endowed with a bilinear multiplication.

Warning: `MagmaticAlgebras` will eventually replace the current `Algebras` for consistency with e.g. Wikipedia article `Algebras` which assumes neither associativity nor the existence of a unit (see [trac ticket #15043](#)).

EXAMPLES:

```
sage: from sage.categories.magmatic_algebras import MagmaticAlgebras
sage: C = MagmaticAlgebras(ZZ); C
Category of magmatic algebras over Integer Ring
sage: C.super_categories()
[Category of additive commutative additive associative additive unital distributive ↵
↵magmas and additive magmas,
Category of modules over Integer Ring]
```

Associative

alias of `sage.categories.associative_algebras.AssociativeAlgebras`

class `ParentMethods`

Bases: `object`

algebra_generators()

Return a family of generators of this algebra.

EXAMPLES:

```
sage: F = AlgebrasWithBasis(QQ).example(); F
An example of an algebra with basis: the free algebra on the generators ('a
↵', 'b', 'c') over Rational Field
sage: F.algebra_generators()
Family (B[word: a], B[word: b], B[word: c])
```

Unitalalias of `sage.categories.unital_algebras.UnitalAlgebras`**class WithBasis**(*base_category*)Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`**class FiniteDimensional**(*base_category*)Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`**class ParentMethods**

Bases: object

derivations_basis()Return a basis for the Lie algebra of derivations of `self` as matrices.A derivation D of an algebra is an endomorphism of A such that

$$D(ab) = D(a)b + aD(b)$$

for all $a, b \in A$. The set of all derivations form a Lie algebra.

EXAMPLES:

We construct the Heisenberg Lie algebra as a multiplicative algebra:

```

sage: p_mult = matrix([[0,0,0],[0,0,-1],[0,0,0]])
sage: q_mult = matrix([[0,0,1],[0,0,0],[0,0,0]])
sage: A = algebras.FiniteDimensional(QQ,
.....:      [p_mult,q_mult,matrix(QQ,3,3)], 'p,q,z')
sage: A.inject_variables()
Defining p, q, z
sage: p*q
z
sage: q*p
-z
sage: A.derivations_basis()
(
[1 0 0]  [0 1 0]  [0 0 0]  [0 0 0]  [0 0 0]  [0 0 0]
[0 0 0]  [0 0 0]  [1 0 0]  [0 1 0]  [0 0 0]  [0 0 0]
[0 0 1], [0 0 0], [0 0 0], [0 0 1], [1 0 0], [0 1 0]
)

```

We construct another example using the exterior algebra and verify we obtain a derivation:

```

sage: A = algebras.Exterior(QQ, 1)
sage: A.derivations_basis()
(
[0 0]
[0 1]
)
sage: D = A.module_morphism(matrix=A.derivations_basis()[0],
->codomain=A)
sage: one, e = A.basis()
sage: all(D(a*b) == D(a) * b + a * D(b)
.....:      for a in A.basis() for b in A.basis())
True

```

REFERENCES:

Wikipedia article [Derivation_\(differential_algebra\)](#)

class ParentMethods

Bases: object

algebra_generators()

Return generators for this algebra.

This default implementation returns the basis of this algebra.

OUTPUT: a family

See also:

- [basis\(\)](#)
- [MagmaticAlgebras.ParentMethods.algebra_generators\(\)](#)

EXAMPLES:

```
sage: D4 = DescentAlgebra(QQ, 4).B()
sage: D4.algebra_generators()
Lazy family (...)_{i in Compositions of 4}

sage: R.<x> = ZZ[]
sage: P = PartitionAlgebra(1, x, R)
sage: P.algebra_generators()
Lazy family (Term map from Partition diagrams of order 1 to
Partition Algebra of rank 1 with parameter x over Univariate Polynomial_
↳Ring in x
over Integer Ring(i))_{i in Partition diagrams of order 1}
```

product()

The product of the algebra, as per [Magmas.ParentMethods.product\(\)](#)

By default, this is implemented using one of the following methods, in the specified order:

- [product_on_basis\(\)](#)
- [product_by_coercion\(\)](#)

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example()
sage: a, b, c = A.algebra_generators()
sage: A.product(a + 2*b, 3*c)
3*B[word: ac] + 6*B[word: bc]
```

product_on_basis(i, j)

The product of the algebra on the basis (optional).

INPUT:

- i, j – the indices of two elements of the basis of `self`

Return the product of the two corresponding basis elements indexed by i and j .

If implemented, [product\(\)](#) is defined from it by bilinearity.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example()
sage: Word = A.basis().keys()
sage: A.product_on_basis(Word("abc"), Word("cba"))
B[word: abccba]
```

additional_structure()

Return None.

Indeed, the category of (magmatic) algebras defines no new structure: a morphism of modules and of magmas between two (magmatic) algebras is a (magmatic) algebra morphism.

See also:

[Category.additional_structure\(\)](#)

Todo: This category should be a *CategoryWithAxiom*, the axiom specifying the compatibility between the magma and module structure.

EXAMPLES:

```
sage: from sage.categories.magmatic_algebras import MagmaticAlgebras
sage: MagmaticAlgebras(ZZ).additional_structure()
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.magmatic_algebras import MagmaticAlgebras
sage: MagmaticAlgebras(ZZ).super_categories()
[Category of additive commutative additive associative additive unital
↳ distributive magmas and additive magmas, Category of modules over Integer
↳ Ring]

sage: from sage.categories.additive_semigroups import AdditiveSemigroups
sage: MagmaticAlgebras(ZZ).is_subcategory((AdditiveSemigroups() & Magmas()).
↳ Distributive())
True
```

3.114 Manifolds

class `sage.categories.manifolds.ComplexManifolds`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of complex manifolds.

A d -dimensional complex manifold is a manifold whose underlying vector space is \mathbb{C}^d and has a holomorphic atlas.

super_categories()

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).super_categories()
[Category of topological spaces]
```

class `sage.categories.manifolds.Manifolds`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of manifolds over any topological field.

Let k be a topological field. A d -dimensional k -manifold M is a second countable Hausdorff space such that the neighborhood of any point $x \in M$ is homeomorphic to k^d .

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: C = Manifolds(RR); C
Category of manifolds over Real Field with 53 bits of precision
sage: C.super_categories()
[Category of topological spaces]
```

class AlmostComplex(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of almost complex manifolds.

An *almost complex manifold* M is a manifold with a smooth tensor field J of rank $(1, 1)$ such that $J^2 = -1$ when regarded as a vector bundle isomorphism $J : TM \rightarrow TM$ on the tangent bundle. The tensor field J is called the *almost complex structure* of M .

extra_super_categories()

Return the extra super categories of self.

An almost complex manifold is smooth.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).AlmostComplex().super_categories() # indirect doctest
[Category of smooth manifolds
over Real Field with 53 bits of precision]
```

class Analytic(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of complex manifolds.

An analytic manifold is a manifold with an analytic atlas.

extra_super_categories()

Return the extra super categories of self.

An analytic manifold is smooth.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).Analytic().super_categories() # indirect doctest
[Category of smooth manifolds
over Real Field with 53 bits of precision]
```

class Connected(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of connected manifolds.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: C = Manifolds(RR).Connected()
sage: TestSuite(C).run(skip="_test_category_over_bases")
```

class Differentiable(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

The category of differentiable manifolds.

A differentiable manifold is a manifold with a differentiable atlas.

class FiniteDimensional(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

Category of finite dimensional manifolds.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: C = Manifolds(RR).FiniteDimensional()
sage: TestSuite(C).run(skip="_test_category_over_bases")
```

class ParentMethods

Bases: object

dimension()

Return the dimension of self.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: M = Manifolds(RR).example()
sage: M.dimension()
3
```

class Smooth(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

The category of smooth manifolds.

A smooth manifold is a manifold with a smooth atlas.

extra_super_categories()

Return the extra super categories of self.

A smooth manifold is differentiable.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).Smooth().super_categories() # indirect doctest
[Category of differentiable manifolds
over Real Field with 53 bits of precision]
```

class SubcategoryMethods

Bases: object

AlmostComplex()

Return the subcategory of the almost complex objects of self.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).AlmostComplex()
```

(continues on next page)

(continued from previous page)

```
Category of almost complex manifolds
over Real Field with 53 bits of precision
```

Analytic()

Return the subcategory of the analytic objects of self.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).Analytic()
Category of analytic manifolds
over Real Field with 53 bits of precision
```

Complex()

Return the subcategory of manifolds over \mathbb{C} of self.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(CC).Complex()
Category of complex manifolds over
Complex Field with 53 bits of precision
```

Connected()

Return the full subcategory of the connected objects of self.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).Connected()
Category of connected manifolds
over Real Field with 53 bits of precision
```

Differentiable()

Return the subcategory of the differentiable objects of self.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).Differentiable()
Category of differentiable manifolds
over Real Field with 53 bits of precision
```

FiniteDimensional()

Return the full subcategory of the finite dimensional objects of self.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: C = Manifolds(RR).Connected().FiniteDimensional(); C
Category of finite dimensional connected manifolds
over Real Field with 53 bits of precision
```

Smooth()

Return the subcategory of the smooth objects of self.

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).Smooth()
Category of smooth manifolds
over Real Field with 53 bits of precision
```

additional_structure()

Return None.

Indeed, the category of manifolds defines no new structure: a morphism of topological spaces between manifolds is a manifold morphism.

See also:

Category.additional_structure()

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).additional_structure()
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.manifolds import Manifolds
sage: Manifolds(RR).super_categories()
[Category of topological spaces]
```

3.115 Matrix algebras

class `sage.categories.matrix_algebras.MatrixAlgebras`(*base, name=None*)

Bases: *sage.categories.category_types.Category_over_base_ring*

The category of matrix algebras over a field.

EXAMPLES:

```
sage: MatrixAlgebras(RationalField())
Category of matrix algebras over Rational Field
```

super_categories()

EXAMPLES:

```
sage: MatrixAlgebras(QQ).super_categories()
[Category of algebras over Rational Field]
```

3.116 Metric Spaces

class `sage.categories.metric_spaces.MetricSpaces`(*category*, **args*)

Bases: `sage.categories.metric_spaces.MetricSpacesCategory`

The category of metric spaces.

A *metric* on a set S is a function $d : S \times S \rightarrow \mathbf{R}$ such that:

- $d(a, b) \geq 0$,
- $d(a, b) = 0$ if and only if $a = b$.

A metric space is a set S with a distinguished metric.

Implementation

Objects in this category must implement either a `dist` on the parent or the elements or `metric` on the parent; otherwise this will cause an infinite recursion.

Todo:

- Implement a general geodesics class.
 - Implement a category for metric additive groups and move the generic distance $d(a, b) = |a - b|$ there.
 - Incorporate the length of a geodesic as part of the default distance cycle.
-

EXAMPLES:

```
sage: from sage.categories.metric_spaces import MetricSpaces
sage: C = MetricSpaces()
sage: C
Category of metric spaces
sage: TestSuite(C).run()
```

class `CartesianProducts`(*category*, **args*)

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

class `ParentMethods`

Bases: `object`

dist(*a*, *b*)

Return the distance between *a* and *b* in `self`.

It is defined as the maximum of the distances within the Cartesian factors.

EXAMPLES:

```
sage: from sage.categories.metric_spaces import MetricSpaces
sage: Q2 = QQ.cartesian_product(QQ)
sage: Q2.category()
Join of
Category of Cartesian products of commutative rings and
Category of Cartesian products of metric spaces
sage: Q2 in MetricSpaces()
True
```

(continues on next page)

(continued from previous page)

```
sage: Q2.dist((0, 0), (2, 3))
3
```

extra_super_categories()

Implement the fact that a (finite) Cartesian product of metric spaces is a metric space.

EXAMPLES:

```
sage: from sage.categories.metric_spaces import MetricSpaces
sage: C = MetricSpaces().CartesianProducts()
sage: C.extra_super_categories()
[Category of metric spaces]
sage: C.super_categories()
[Category of Cartesian products of topological spaces,
 Category of metric spaces]
sage: C.axioms()
frozenset()
```

class Complete(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

The category of complete metric spaces.

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

extra_super_categories()

Implement the fact that a (finite) Cartesian product of complete metric spaces is a complete metric space.

EXAMPLES:

```
sage: from sage.categories.metric_spaces import MetricSpaces
sage: C = MetricSpaces().Complete().CartesianProducts()
sage: C.extra_super_categories()
[Category of complete metric spaces]
sage: C.super_categories()
[Category of Cartesian products of metric spaces,
 Category of complete metric spaces]
sage: C.axioms()
frozenset({'Complete'})

sage: R2 = RR.cartesian_product(RR)
sage: R2 in MetricSpaces()
True
sage: R2 in MetricSpaces().Complete()
True

sage: QR = QQ.cartesian_product(RR)
sage: QR in MetricSpaces()
True
sage: QR in MetricSpaces().Complete()
False
```

class ElementMethods

Bases: object

abs()

Return the absolute value of `self`.

EXAMPLES:

```
sage: CC(I).abs()
1.0000000000000000
```

dist(*b*)

Return the distance between `self` and `other`.

EXAMPLES:

```
sage: UHP = HyperbolicPlane().UHP()
sage: p1 = UHP.get_point(5 + 7*I)
sage: p2 = UHP.get_point(1 + I)
sage: p1.dist(p2)
arccosh(33/7)
```

class Homsets(*category*, **args*)

Bases: `sage.categories.homsets.HomsetsCategory`

The category of homsets of metric spaces

It consists of the metric maps, that is, the Lipschitz functions with Lipschitz constant 1.

class ElementMethods

Bases: object

class ParentMethods

Bases: object

dist(*a*, *b*)

Return the distance between `a` and `b` in `self`.

EXAMPLES:

```
sage: UHP = HyperbolicPlane().UHP()
sage: p1 = UHP.get_point(5 + 7*I)
sage: p2 = UHP.get_point(1.0 + I)
sage: UHP.dist(p1, p2)
2.23230104635820

sage: PD = HyperbolicPlane().PD()
sage: PD.dist(PD.get_point(0), PD.get_point(I/2))
arccosh(5/3)
```

metric(args*, ***kws*)**

Deprecated: Use `metric_function()` instead. See [trac ticket #30062](#) for details.

metric_function()

Return the metric function of `self`.

EXAMPLES:

```
sage: UHP = HyperbolicPlane().UHP()
sage: m = UHP.metric_function()
sage: p1 = UHP.get_point(5 + 7*I)
sage: p2 = UHP.get_point(1.0 + I)
```

(continues on next page)

(continued from previous page)

```
sage: m(p1, p2)
2.23230104635820
```

class SubcategoryMethods

Bases: object

Complete()Return the full subcategory of the complete objects of `self`.

EXAMPLES:

```
sage: Sets().Metric().Complete()
Category of complete metric spaces
```

class WithRealizations(*category, *args*)Bases: `sage.categories.with_realizations.WithRealizationsCategory`**class ParentMethods**

Bases: object

dist(*a, b*)Return the distance between *a* and *b* by converting them to a realization of `self` and doing the computation.

EXAMPLES:

```
sage: H = HyperbolicPlane()
sage: PD = H.PD()
sage: p1 = PD.get_point(0)
sage: p2 = PD.get_point(I/2)
sage: H.dist(p1, p2)
arccosh(5/3)
```

class `sage.categories.metric_spaces.MetricSpacesCategory`(*category, *args*)Bases: `sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory`**classmethod** `default_super_categories`(*category*)Return the default super categories of `category.Metric()`.Mathematical meaning: if *A* is a metric space in the category *C*, then *A* is also a topological space.

INPUT:

- `cls` – the class `MetricSpaces`
- `category` – a category *Cat*

OUTPUT:

A (join) category

In practice, this returns `category.Metric()`, joined together with the result of the method `RegressiveCovariantConstructionCategory.default_super_categories()` (that is the join of `category` and `cat.Metric()` for each `cat` in the super categories of `category`).

EXAMPLES:

Consider `category=Groups()`. Then, a group *G* with a metric is simultaneously a topological group by itself, and a metric space:

```
sage: Groups().Metric().super_categories()
[Category of topological groups, Category of metric spaces]
```

This resulted from the following call:

```
sage: sage.categories.metric_spaces.MetricSpacesCategory.default_super_
      ↪categories(Groups())
Join of Category of topological groups and Category of metric spaces
```

3.117 Modular abelian varieties

```
class sage.categories.modular_abelian_varieties.ModularAbelianVarieties(Y)
```

Bases: *sage.categories.category_types.Category_over_base*

The category of modular abelian varieties over a given field.

EXAMPLES:

```
sage: ModularAbelianVarieties(QQ)
Category of modular abelian varieties over Rational Field
```

```
class Homsets(category, *args)
```

Bases: *sage.categories.homsets.HomsetsCategory*

```
class Endset(base_category)
```

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

```
extra_super_categories()
```

Implement the fact that an endset of modular abelian variety is a ring.

EXAMPLES:

```
sage: ModularAbelianVarieties(QQ).Endsets().extra_super_categories()
[Category of rings]
```

```
base_field()
```

EXAMPLES:

```
sage: ModularAbelianVarieties(QQ).base_field()
Rational Field
```

```
super_categories()
```

EXAMPLES:

```
sage: ModularAbelianVarieties(QQ).super_categories()
[Category of sets]
```

3.118 Modules

class `sage.categories.modules.Modules`(*base*, *name=None*)

Bases: `sage.categories.category_types.Category_module`

The category of all modules over a base ring R .

An R -module M is a left and right R -module over a commutative ring R such that:

$$r * (x * s) = (r * x) * s \quad \forall r, s \in R \text{ and } x \in M$$

INPUT:

- `base_ring` – a ring R or subcategory of `Rings()`
- `dispatch` – a boolean (for internal use; default: `True`)

When the base ring is a field, the category of vector spaces is returned instead (unless `dispatch == False`).

Warning: Outside of the context of symmetric modules over a commutative ring, the specifications of this category are fuzzy and not yet set in stone (see below). The code in this category and its subcategories is therefore prone to bugs or arbitrary limitations in this case.

EXAMPLES:

```
sage: Modules(ZZ)
Category of modules over Integer Ring
sage: Modules(QQ)
Category of vector spaces over Rational Field

sage: Modules(Rings())
Category of modules over rings
sage: Modules(FiniteFields())
Category of vector spaces over finite enumerated fields

sage: Modules(Integers(9))
Category of modules over Ring of integers modulo 9

sage: Modules(Integers(9)).super_categories()
[Category of bimodules over Ring of integers modulo 9 on the left and Ring of
↳integers modulo 9 on the right]

sage: Modules(ZZ).super_categories()
[Category of bimodules over Integer Ring on the left and Integer Ring on the right]

sage: Modules == RingModules
True

sage: Modules(ZZ['x']).is_abelian() # see #6081
True
```

Todo:

- Clarify the distinction, if any, with `BiModules(R, R)`. In particular, if R is a commutative ring (e.g. a field), some pieces of the code possibly assume that M is a *symmetric* R - R -bimodule:

$$r * x = x * r \quad \forall r \in R \text{ and } x \in M$$

- Make sure that non symmetric modules are properly supported by all the code, and advertise it.
- Make sure that non commutative rings are properly supported by all the code, and advertise it.
- Add support for base semirings.
- Implement a `FreeModules(R)` category, when so prompted by a concrete use case: e.g. modeling a free module with several bases (using `Sets.SubcategoryMethods.Realizations()`) or with an atlas of local maps (see e.g. [trac ticket #15916](#)).

class CartesianProducts(*category, *args*)

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

The category of modules constructed as Cartesian products of modules

This construction gives the direct product of modules. The implementation is based on the following resources:

- http://groups.google.fr/group/sage-devel/browse_thread/thread/35a72b1d0a2fc77a/348f42ae77a66d16#348f42ae77a66d16
- [Wikipedia article Direct_product](#)

class ElementMethods

Bases: `object`

class ParentMethods

Bases: `object`

extra_super_categories()

A Cartesian product of modules is endowed with a natural module structure.

EXAMPLES:

```
sage: Modules(ZZ).CartesianProducts().extra_super_categories()
[Category of modules over Integer Ring]
sage: Modules(ZZ).CartesianProducts().super_categories()
[Category of Cartesian products of commutative additive groups,
Category of modules over Integer Ring]
```

class ElementMethods

Bases: `object`

Filtered

alias of `sage.categories.filtered_modules.FilteredModules`

class FiniteDimensional(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

extra_super_categories()

Implement the fact that a finite dimensional module over a finite ring is finite.

EXAMPLES:

```

sage: Modules(IntegerModRing(4)).FiniteDimensional().extra_super_
↪categories()
[Category of finite sets]
sage: Modules(ZZ).FiniteDimensional().extra_super_categories()
[]
sage: Modules(GF(5)).FiniteDimensional().is_subcategory(Sets().Finite())
True
sage: Modules(ZZ).FiniteDimensional().is_subcategory(Sets().Finite())
False

sage: Modules(Rings().Finite()).FiniteDimensional().is_subcategory(Sets().
↪Finite())
True
sage: Modules(Rings()).FiniteDimensional().is_subcategory(Sets().Finite())
False

```

Graded

alias of `sage.categories.graded_modules.GradedModules`

class Homsets(*category, *args*)

Bases: `sage.categories.homsets.HomsetsCategory`

The category of homomorphism sets $\text{hom}(X, Y)$ for X, Y modules.

class Endset(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

The category of endomorphism sets $\text{End}(X)$ for X a module (this is not used yet)

extra_super_categories()

Implement the fact that the endomorphism set of a module is an algebra.

See also:

`CategoryWithAxiom.extra_super_categories()`

EXAMPLES:

```

sage: Modules(ZZ).Endsets().extra_super_categories()
[Category of magmatic algebras over Integer Ring]

sage: End(ZZ^3) in Algebras(ZZ)
True

```

class ParentMethods

Bases: object

base_ring()

Return the base ring of self.

EXAMPLES:

```

sage: E = CombinatorialFreeModule(ZZ, [1,2,3])
sage: F = CombinatorialFreeModule(ZZ, [2,3,4])
sage: H = Hom(E, F)
sage: H.base_ring()
Integer Ring

```

This `base_ring` method is actually overridden by `sage.structure.category_object.CategoryObject.base_ring()`:

```
sage: H.base_ring.__module__
```

Here we call it directly:

```
sage: method = H.category().parent_class.base_ring
sage: method.__get__(H)()
Integer Ring
```

`zero()`

EXAMPLES:

```
sage: E = CombinatorialFreeModule(ZZ, [1,2,3])
sage: F = CombinatorialFreeModule(ZZ, [2,3,4])
sage: H = Hom(E, F)
sage: f = H.zero()
sage: f
Generic morphism:
  From: Free module generated by {1, 2, 3} over Integer Ring
  To:   Free module generated by {2, 3, 4} over Integer Ring
sage: f(E.monomial(2))
0
sage: f(E.monomial(3)) == F.zero()
True
```

`base_ring()`

EXAMPLES:

```
sage: Modules(ZZ).Homsets().base_ring()
Integer Ring
```

Todo: Generalize this so that any homset category of a full subcategory of modules over a base ring is a category over this base ring.

`extra_super_categories()`

EXAMPLES:

```
sage: Modules(ZZ).Homsets().extra_super_categories()
[Category of modules over Integer Ring]
```

class `ParentMethods`

Bases: `object`

`linear_combination(iter_of_elements_coeff, factor_on_left=True)`

Return the linear combination $\lambda_1 v_1 + \dots + \lambda_k v_k$ (resp. the linear combination $v_1 \lambda_1 + \dots + v_k \lambda_k$) where `iter_of_elements_coeff` iterates through the sequence $((\lambda_1, v_1), \dots, (\lambda_k, v_k))$.

INPUT:

- `iter_of_elements_coeff` – iterator of pairs (`element`, `coeff`) with `element` in `self` and `coeff` in `self.base_ring()`
- `factor_on_left` – (optional) if `True`, the coefficients are multiplied from the left; if `False`, the coefficients are multiplied from the right

EXAMPLES:

```
sage: m = matrix([[0,1],[1,1]])
sage: J.<a,b,c> = JordanAlgebra(m)
sage: J.linear_combination(((a+b, 1), (-2*b + c, -1)))
1 + (3, -1)
```

module_morphism(*function, category, codomain, **keywords*)

Construct a module morphism from `self` to `codomain`.

Let `self` be a module X over a ring R . This constructs a morphism $f : X \rightarrow Y$.

INPUT:

- `self` – a parent X in `Modules(R)`.
- `function` – a function f from X to Y
- `codomain` – the codomain Y of the morphism (default: `f.codomain()` if it's defined; otherwise it must be specified)
- `category` – a category or `None` (default: `None`)

EXAMPLES:

```
sage: V = FiniteRankFreeModule(QQ, 2)
sage: e = V.basis('e'); e
Basis (e_0,e_1) on the 2-dimensional vector space over the Rational Field
sage: neg = V.module_morphism(function=operator.neg, codomain=V); neg
Generic endomorphism of 2-dimensional vector space over the Rational Field
sage: neg(e[0])
Element -e_0 of the 2-dimensional vector space over the Rational Field
```

tensor_square()

Returns the tensor square of `self`

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example()
sage: A.tensor_square()
An example of Hopf algebra with basis:
the group algebra of the Dihedral group of order 6
as a permutation group over Rational Field # An example
of Hopf algebra with basis: the group algebra of the Dihedral
group of order 6 as a permutation group over Rational Field
```

class SubcategoryMethods

Bases: object

DualObjects()

Return the category of spaces constructed as duals of spaces of `self`.

The *dual* of a vector space V is the space consisting of all linear functionals on V (see [Wikipedia article Dual_space](#)). Additional structure on V can endow its dual with additional structure; for example, if V is a finite dimensional algebra, then its dual is a coalgebra.

This returns the category of spaces constructed as dual of spaces in `self`, endowed with the appropriate additional structure.

Warning:

- This semantic of `dual` and `DualObject` is imposed on all subcategories, in particular to make `dual` a covariant functorial construction.
A subcategory that defines a different notion of dual needs to use a different name.
- Typically, the category of graded modules should define a separate `graded_dual` construction (see [trac ticket #15647](#)). For now the two constructions are not distinguished which is an oversimplified model.

See also:

- [`dual.DualObjectsCategory`](#)
- [CovariantFunctorialConstruction](#).

EXAMPLES:

```
sage: VectorSpaces(QQ).DualObjects()
Category of duals of vector spaces over Rational Field
```

The dual of a vector space is a vector space:

```
sage: VectorSpaces(QQ).DualObjects().super_categories()
[Category of vector spaces over Rational Field]
```

The dual of an algebra is a coalgebra:

```
sage: sorted(Algebras(QQ).DualObjects().super_categories(), key=str)
[Category of coalgebras over Rational Field,
 Category of duals of vector spaces over Rational Field]
```

The dual of a coalgebra is an algebra:

```
sage: sorted(Coalgebras(QQ).DualObjects().super_categories(), key=str)
[Category of algebras over Rational Field,
 Category of duals of vector spaces over Rational Field]
```

As a shorthand, this category can be accessed with the `dual()` method:

```
sage: VectorSpaces(QQ).dual()
Category of duals of vector spaces over Rational Field
```

Filtered(*base_ring=None*)

Return the subcategory of the filtered objects of `self`.

INPUT:

- `base_ring` – this is ignored

EXAMPLES:

```
sage: Modules(ZZ).Filtered()
Category of filtered modules over Integer Ring

sage: Coalgebras(QQ).Filtered()
Category of filtered coalgebras over Rational Field

sage: AlgebrasWithBasis(QQ).Filtered()
Category of filtered algebras with basis over Rational Field
```

Todo:

- Explain why this does not commute with `WithBasis()`
 - Improve the support for covariant functorial constructions categories over a base ring so as to get rid of the `base_ring` argument.
-

FiniteDimensional()

Return the full subcategory of the finite dimensional objects of `self`.

EXAMPLES:

```
sage: Modules(ZZ).FiniteDimensional()
Category of finite dimensional modules over Integer Ring
sage: Coalgebras(QQ).FiniteDimensional()
Category of finite dimensional coalgebras over Rational Field
sage: AlgebrasWithBasis(QQ).FiniteDimensional()
Category of finite dimensional algebras with basis over Rational Field
```

Graded(*base_ring=None*)

Return the subcategory of the graded objects of `self`.

INPUT:

- `base_ring` – this is ignored

EXAMPLES:

```
sage: Modules(ZZ).Graded()
Category of graded modules over Integer Ring

sage: Coalgebras(QQ).Graded()
Category of graded coalgebras over Rational Field

sage: AlgebrasWithBasis(QQ).Graded()
Category of graded algebras with basis over Rational Field
```

Todo:

- Explain why this does not commute with `WithBasis()`
 - Improve the support for covariant functorial constructions categories over a base ring so as to get rid of the `base_ring` argument.
-

Super(*base_ring=None*)

Return the super-analogue category of `self`.

INPUT:

- `base_ring` – this is ignored

EXAMPLES:

```
sage: Modules(ZZ).Super()
Category of super modules over Integer Ring

sage: Coalgebras(QQ).Super()
Category of super coalgebras over Rational Field

sage: AlgebrasWithBasis(QQ).Super()
Category of super algebras with basis over Rational Field
```

Todo:

- Explain why this does not commute with `WithBasis()`
- Improve the support for covariant functorial constructions categories over a base ring so as to get rid of the `base_ring` argument.

TensorProducts()

Return the full subcategory of objects of `self` constructed as tensor products.

See also:

- `tensor.TensorProductsCategory`
- `RegressiveCovariantFunctorialConstruction`.

EXAMPLES:

```
sage: ModulesWithBasis(QQ).TensorProducts()
Category of tensor products of vector spaces with basis over Rational Field
```

WithBasis()

Return the full subcategory of the objects of `self` with a distinguished basis.

EXAMPLES:

```
sage: Modules(ZZ).WithBasis()
Category of modules with basis over Integer Ring
sage: Coalgebras(QQ).WithBasis()
Category of coalgebras with basis over Rational Field
sage: AlgebrasWithBasis(QQ).WithBasis()
Category of algebras with basis over Rational Field
```

base_ring()

Return the base ring (category) for `self`.

This implements a `base_ring` method for all subcategories of `Modules(K)`.

EXAMPLES:

```
sage: C = Modules(QQ) & Semigroups(); C
Join of Category of semigroups and Category of vector spaces over Rational_
↪Field
sage: C.base_ring()
Rational Field
sage: C.base_ring.__module__
'sage.categories.modules'

sage: C = Modules(Rings()) & Semigroups(); C
Join of Category of semigroups and Category of modules over rings
sage: C.base_ring()
Category of rings
sage: C.base_ring.__module__
'sage.categories.modules'

sage: C = DescentAlgebra(QQ,3).B().category()
sage: C.base_ring.__module__
'sage.categories.modules'
```

(continues on next page)

(continued from previous page)

```

sage: C.base_ring()
Rational Field

sage: C = QuasiSymmetricFunctions(QQ).F().category()
sage: C.base_ring.__module__
'sage.categories.modules'
sage: C.base_ring()
Rational Field

```

dual()

Return the category of spaces constructed as duals of spaces of `self`.

The *dual* of a vector space V is the space consisting of all linear functionals on V (see [Wikipedia article Dual_space](#)). Additional structure on V can endow its dual with additional structure; for example, if V is a finite dimensional algebra, then its dual is a coalgebra.

This returns the category of spaces constructed as dual of spaces in `self`, endowed with the appropriate additional structure.

Warning:

- This semantic of `dual` and `DualObject` is imposed on all subcategories, in particular to make `dual` a covariant functorial construction.
A subcategory that defines a different notion of dual needs to use a different name.
- Typically, the category of graded modules should define a separate `graded_dual` construction (see [trac ticket #15647](#)). For now the two constructions are not distinguished which is an oversimplified model.

See also:

- [`dual.DualObjectsCategory`](#)
- [`CovariantFunctorialConstruction`](#).

EXAMPLES:

```

sage: VectorSpaces(QQ).DualObjects()
Category of duals of vector spaces over Rational Field

```

The dual of a vector space is a vector space:

```

sage: VectorSpaces(QQ).DualObjects().super_categories()
[Category of vector spaces over Rational Field]

```

The dual of an algebra is a coalgebra:

```

sage: sorted(Algebras(QQ).DualObjects().super_categories(), key=str)
[Category of coalgebras over Rational Field,
 Category of duals of vector spaces over Rational Field]

```

The dual of a coalgebra is an algebra:

```
sage: sorted(Coalgebras(QQ).DualObjects().super_categories(), key=str)
[Category of algebras over Rational Field,
 Category of duals of vector spaces over Rational Field]
```

As a shorthand, this category can be accessed with the `dual()` method:

```
sage: VectorSpaces(QQ).dual()
Category of duals of vector spaces over Rational Field
```

Super

alias of `sage.categories.super_modules.SuperModules`

class `TensorProducts`(*category*, **args*)

Bases: `sage.categories.tensor.TensorProductsCategory`

The category of modules constructed by tensor product of modules.

extra_super_categories()

EXAMPLES:

```
sage: Modules(ZZ).TensorProducts().extra_super_categories()
[Category of modules over Integer Ring]
sage: Modules(ZZ).TensorProducts().super_categories()
[Category of modules over Integer Ring]
```

WithBasis

alias of `sage.categories.modules_with_basis.ModulesWithBasis`

additional_structure()

Return None.

Indeed, the category of modules defines no additional structure: a bimodule morphism between two modules is a module morphism.

See also:

`Category.additional_structure()`

Todo: Should this category be a `CategoryWithAxiom`?

EXAMPLES:

```
sage: Modules(ZZ).additional_structure()
```

super_categories()

EXAMPLES:

```
sage: Modules(ZZ).super_categories()
[Category of bimodules over Integer Ring on the left and Integer Ring on the
->right]
```

Nota bene:

```
sage: Modules(QQ)
Category of vector spaces over Rational Field
sage: Modules(QQ).super_categories()
[Category of modules over Rational Field]
```

3.119 Modules With Basis

AUTHORS:

- Nicolas M. Thiery (2008-2014): initial revision, axiomatization
- Jason Bandlow and Florent Hivert (2010): Triangular Morphisms
- Christian Stump (2010): [trac ticket #9648](#) module_morphism's to a wider class of codomains

class `sage.categories.modules_with_basis.ModulesWithBasis`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of modules with a distinguished basis.

The elements are represented by expanding them in the distinguished basis. The morphisms are not required to respect the distinguished basis.

EXAMPLES:

```
sage: ModulesWithBasis(ZZ)
Category of modules with basis over Integer Ring
sage: ModulesWithBasis(ZZ).super_categories()
[Category of modules over Integer Ring]
```

If the base ring is actually a field, this constructs instead the category of vector spaces with basis:

```
sage: ModulesWithBasis(QQ)
Category of vector spaces with basis over Rational Field

sage: ModulesWithBasis(QQ).super_categories()
[Category of modules with basis over Rational Field,
 Category of vector spaces over Rational Field]
```

Let X and Y be two modules with basis. We can build $\text{Hom}(X, Y)$:

```
sage: X = CombinatorialFreeModule(QQ, [1,2]); X.__custom_name = "X"
sage: Y = CombinatorialFreeModule(QQ, [3,4]); Y.__custom_name = "Y"
sage: H = Hom(X, Y); H
Set of Morphisms from X to Y in Category of finite dimensional vector spaces with
↳basis over Rational Field
```

The simplest morphism is the zero map:

```
sage: H.zero()           # todo: move this test into module once we have an example
Generic morphism:
  From: X
  To:   Y
```

which we can apply to elements of X :

```
sage: x = X.monomial(1) + 3 * X.monomial(2)
sage: H.zero()(x)
0
```

EXAMPLES:

We now construct a more interesting morphism by extending a function by linearity:

```
sage: phi = H(on_basis = lambda i: Y.monomial(i+2)); phi
Generic morphism:
  From: X
  To:   Y
sage: phi(x)
B[3] + 3*B[4]
```

We can retrieve the function acting on indices of the basis:

```
sage: f = phi.on_basis()
sage: f(1), f(2)
(B[3], B[4])
```

$\text{Hom}(X, Y)$ has a natural module structure (except for the zero, the operations are not yet implemented though). However since the dimension is not necessarily finite, it is not a module with basis; but see *FiniteDimensionalModulesWithBasis* and *GradedModulesWithBasis*:

```
sage: H in ModulesWithBasis(QQ), H in Modules(QQ)
(False, True)
```

Some more playing around with categories and higher order homsets:

```
sage: H.category()
Category of homsets of modules with basis over Rational Field
sage: Hom(H, H).category()
Category of endsets of homsets of modules with basis over Rational Field
```

Todo: $\text{End}(X)$ is an algebra.

Note: This category currently requires an implementation of an `element` method `support`. Once [trac ticket #18066](#) is merged, an implementation of an `items` method will be required.

class `CartesianProducts`(*category*, **args*)

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

The category of modules with basis constructed by Cartesian products of modules with basis.

class `ParentMethods`

Bases: `object`

extra_super_categories()

EXAMPLES:

```
sage: ModulesWithBasis(QQ).CartesianProducts().extra_super_categories()
[Category of vector spaces with basis over Rational Field]
sage: ModulesWithBasis(QQ).CartesianProducts().super_categories()
[Category of Cartesian products of modules with basis over Rational Field,
Category of vector spaces with basis over Rational Field,
Category of Cartesian products of vector spaces over Rational Field]
```

class `DualObjects`(*category*, **args*)

Bases: `sage.categories.dual.DualObjectsCategory`

extra_super_categories()

EXAMPLES:

```
sage: ModulesWithBasis(ZZ).DualObjects().extra_super_categories()
[Category of modules over Integer Ring]
sage: ModulesWithBasis(QQ).DualObjects().super_categories()
[Category of duals of vector spaces over Rational Field, Category of duals_
↪of modules with basis over Rational Field]
```

class ElementMethods

Bases: object

coefficient(*m*)

Return the coefficient of *m* in *self* and raise an error if *m* is not in the basis indexing set.

INPUT:

- *m* – a basis index of the parent of *self*

OUTPUT:

The $B[m]$ -coordinate of *self* with respect to the basis *B*. Here, *B* denotes the given basis of the parent of *self*.

EXAMPLES:

```
sage: s = CombinatorialFreeModule(QQ, Partitions())
sage: z = s([4]) - 2*s([2,1]) + s([1,1,1]) + s([1])
sage: z.coefficient([4])
1
sage: z.coefficient([2,1])
-2
sage: z.coefficient(Partition([2,1]))
-2
sage: z.coefficient([1,2])
Traceback (most recent call last):
...
AssertionError: [1, 2] should be an element of Partitions
sage: z.coefficient(Composition([2,1]))
Traceback (most recent call last):
...
AssertionError: [2, 1] should be an element of Partitions
```

Test that `coefficient` also works for those parents that do not have an `element_class`:

```
sage: H = pAdicWeightSpace(3)
sage: F = CombinatorialFreeModule(QQ, H)
sage: hasattr(H, "element_class")
False
sage: h = H.an_element()
sage: (2*F.monomial(h)).coefficient(h)
2
```

coefficients(*sort=True*)

Return a list of the (non-zero) coefficients appearing on the basis elements in *self* (in an arbitrary order).

INPUT:

- *sort* – (default: `True`) to sort the coefficients based upon the default ordering of the indexing set

See also:

`dense_coefficient_list()`

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a','b','c'])
sage: B = F.basis()
sage: f = B['a'] - 3*B['c']
sage: f.coefficients()
[1, -3]
sage: f = B['c'] - 3*B['a']
sage: f.coefficients()
[-3, 1]
```

```
sage: s = SymmetricFunctions(QQ).schur()
sage: z = s([4]) + s([2,1]) + s([1,1,1]) + s([1])
sage: z.coefficients()
[1, 1, 1, 1]
```

is_zero()

Return True if and only if `self == 0`.

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a','b','c'])
sage: B = F.basis()
sage: f = B['a'] - 3*B['c']
sage: f.is_zero()
False
sage: F.zero().is_zero()
True
```

```
sage: s = SymmetricFunctions(QQ).schur()
sage: s([2,1]).is_zero()
False
sage: s(0).is_zero()
True
sage: (s([2,1]) - s([2,1])).is_zero()
True
```

leading_coefficient(*args, **kws)

Return the leading coefficient of `self`.

This is the coefficient of the term whose corresponding basis element is maximal. Note that this may not be the term which actually appears first when `self` is printed.

If the default term ordering is not what is desired, a comparison key, `key(x, y)`, can be provided.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X")
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + X.monomial(3)
sage: x.leading_coefficient()
1
sage: def key(x): return -x
```

(continues on next page)

(continued from previous page)

```

sage: x.leading_coefficient(key=key)
3

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.leading_coefficient()
-5

```

leading_item(*args, **kws)

Return the pair (k, c) where

 $c \cdot$ (the basis element indexed by k)is the leading term of `self`.

Here ‘leading term’ means that the corresponding basis element is maximal. Note that this may not be the term which actually appears first when `self` is printed.

If the default term ordering is not what is desired, a comparison function, `key(x)`, can be provided.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.
↳basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + 4*X.monomial(3)
sage: x.leading_item()
(3, 4)
sage: def key(x): return -x
sage: x.leading_item(key=key)
(1, 3)

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.leading_item()
([3], -5)

```

leading_monomial(*args, **kws)Return the leading monomial of `self`.

This is the monomial whose corresponding basis element is maximal. Note that this may not be the term which actually appears first when `self` is printed.

If the default term ordering is not what is desired, a comparison key, `key(x)`, can be provided.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.
↳basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + X.monomial(3)
sage: x.leading_monomial()
B[3]
sage: def key(x): return -x
sage: x.leading_monomial(key=key)
B[1]

sage: s = SymmetricFunctions(QQ).schur()

```

(continues on next page)

(continued from previous page)

```
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.leading_monomial()
s[3]
```

leading_support(*args, **kws)

Return the maximal element of the support of `self`.

Note that this may not be the term which actually appears first when `self` is printed.

If the default ordering of the basis elements is not what is desired, a comparison key, `key(x)`, can be provided.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3])
sage: X.rename("X"); x = X.basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + 4*X.monomial(3)
sage: x.leading_support()
3
sage: def key(x): return -x
sage: x.leading_support(key=key)
1

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.leading_support()
[3]
```

leading_term(*args, **kws)

Return the leading term of `self`.

This is the term whose corresponding basis element is maximal. Note that this may not be the term which actually appears first when `self` is printed.

If the default term ordering is not what is desired, a comparison key, `key(x)`, can be provided.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.
↳basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + X.monomial(3)
sage: x.leading_term()
B[3]
sage: def key(x): return -x
sage: x.leading_term(key=key)
3*B[1]

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.leading_term()
-5*s[3]
```

length()

Return the number of basis elements whose coefficients in `self` are nonzero.

EXAMPLES:

```

sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: B = F.basis()
sage: f = B['a'] - 3*B['c']
sage: f.length()
2

```

```

sage: s = SymmetricFunctions(QQ).schur()
sage: z = s([4]) + s([2,1]) + s([1,1,1]) + s([1])
sage: z.length()
4

```

map_coefficients(*f*)

Mapping a function on coefficients.

INPUT:

- *f* – an endofunction on the coefficient ring of the free module

Return a new element of `self.parent()` obtained by applying the function *f* to all of the coefficients of `self`.

EXAMPLES:

```

sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: B = F.basis()
sage: f = B['a'] - 3*B['c']
sage: f.map_coefficients(lambda x: x+5)
6*B['a'] + 2*B['c']

```

Killed coefficients are handled properly:

```

sage: f.map_coefficients(lambda x: 0)
0
sage: list(f.map_coefficients(lambda x: 0))
[]

```

```

sage: s = SymmetricFunctions(QQ).schur()
sage: a = s([2,1])+2*s([3,2])
sage: a.map_coefficients(lambda x: x*2)
2*s[2, 1] + 4*s[3, 2]

```

map_item(*f*)

Mapping a function on items.

INPUT:

- *f* – a function mapping pairs (`index`, `coeff`) to other such pairs

Return a new element of `self.parent()` obtained by applying the function *f* to all items (`index`, `coeff`) of `self`.

EXAMPLES:

```

sage: B = CombinatorialFreeModule(ZZ, [-1, 0, 1])
sage: x = B.an_element(); x
2*B[-1] + 2*B[0] + 3*B[1]
sage: x.map_item(lambda i, c: (-i, 2*c))
6*B[-1] + 4*B[0] + 4*B[1]

```

f needs not be injective:

```

sage: x.map_item(lambda i, c: (1, 2*c))
14*B[1]

sage: s = SymmetricFunctions(QQ).schur()
sage: f = lambda m,c: (m.conjugate(), 2*c)
sage: a = s([2,1]) + s([1,1,1])
sage: a.map_item(f)
2*s[2, 1] + 2*s[3]

```

map_support(*f*)

Mapping a function on the support.

INPUT:

- *f* – an endofunction on the indices of the free module

Return a new element of `self.parent()` obtained by applying the function *f* to all of the objects indexing the basis elements.

EXAMPLES:

```

sage: B = CombinatorialFreeModule(ZZ, [-1, 0, 1])
sage: x = B.an_element(); x
2*B[-1] + 2*B[0] + 3*B[1]
sage: x.map_support(lambda i: -i)
3*B[-1] + 2*B[0] + 2*B[1]

```

f needs not be injective:

```

sage: x.map_support(lambda i: 1)
7*B[1]

sage: s = SymmetricFunctions(QQ).schur()
sage: a = s([2,1])+2*s([3,2])
sage: a.map_support(lambda x: x.conjugate())
s[2, 1] + 2*s[2, 2, 1]

```

map_support_skip_none(*f*)

Mapping a function on the support.

INPUT:

- *f* – an endofunction on the indices of the free module

Returns a new element of `self.parent()` obtained by applying the function *f* to all of the objects indexing the basis elements.

EXAMPLES:

```

sage: B = CombinatorialFreeModule(ZZ, [-1, 0, 1])
sage: x = B.an_element(); x
2*B[-1] + 2*B[0] + 3*B[1]
sage: x.map_support_skip_none(lambda i: -i if i else None)
3*B[-1] + 2*B[1]

```

f needs not be injective:

```

sage: x.map_support_skip_none(lambda i: 1 if i else None)
5*B[1]

```

monomial_coefficients(*copy=True*)

Return a dictionary whose keys are indices of basis elements in the support of `self` and whose values are the corresponding coefficients.

INPUT:

- `copy` – (default: `True`) if `self` is internally represented by a dictionary `d`, then make a copy of `d`; if `False`, then this can cause undesired behavior by mutating `d`

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: B = F.basis()
sage: f = B['a'] + 3*B['c']
sage: d = f.monomial_coefficients()
sage: d['a']
1
sage: d['c']
3
```

monomials()

Return a list of the monomials of `self` (in an arbitrary order).

The monomials of an element a are defined to be the basis elements whose corresponding coefficients of a are non-zero.

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: B = F.basis()
sage: f = B['a'] + 2*B['c']
sage: f.monomials()
[B['a'], B['c']]

sage: (F.zero()).monomials()
[]
```

support()

Return a list of the objects indexing the basis of `self.parent()` whose corresponding coefficients of `self` are non-zero.

This method returns these objects in an arbitrary order.

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: B = F.basis()
sage: f = B['a'] - 3*B['c']
sage: sorted(f.support())
['a', 'c']
```

```
sage: s = SymmetricFunctions(QQ).schur()
sage: z = s([4]) + s([2, 1]) + s([1, 1, 1]) + s([1])
sage: sorted(z.support())
[[1], [1, 1, 1], [2, 1], [4]]
```

support_of_term()

Return the support of `self`, where `self` is a monomial (possibly with coefficient).

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3,4]); X.rename("X")
sage: X.monomial(2).support_of_term()
2
sage: X.term(3, 2).support_of_term()
3
```

An exception is raised if `self` has more than one term:

```
sage: (X.monomial(2) + X.monomial(3)).support_of_term()
Traceback (most recent call last):
...
ValueError: B[2] + B[3] is not a single term
```

tensor(*elements)

Return the tensor product of its arguments, as an element of the tensor product of the parents of those elements.

EXAMPLES:

```
sage: C = AlgebrasWithBasis(QQ)
sage: A = C.example()
sage: (a,b,c) = A.algebra_generators()
sage: a.tensor(b, c)
B[word: a] # B[word: b] # B[word: c]
```

FIXME: is this a policy that we want to enforce on all parents?

terms()

Return a list of the (non-zero) terms of `self` (in an arbitrary order).

See also:

[*monomials\(\)*](#)

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a','b','c'])
sage: B = F.basis()
sage: f = B['a'] + 2*B['c']
sage: f.terms()
[B['a'], 2*B['c']]
```

trailing_coefficient(*args, **kws)

Return the trailing coefficient of `self`.

This is the coefficient of the monomial whose corresponding basis element is minimal. Note that this may not be the term which actually appears last when `self` is printed.

If the default term ordering is not what is desired, a comparison key `key(x)`, can be provided.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.
↪basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + X.monomial(3)
sage: x.trailing_coefficient()
```

(continues on next page)

(continued from previous page)

```

3
sage: def key(x): return -x
sage: x.trailing_coefficient(key=key)
1

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.trailing_coefficient()
2

```

trailing_item(*args, **kws)

Return the pair (c, k) where $c \cdot \text{self.parent().monomial}(k)$ is the trailing term of `self`.

This is the monomial whose corresponding basis element is minimal. Note that this may not be the term which actually appears last when `self` is printed.

If the default term ordering is not what is desired, a comparison key `key(x)`, can be provided.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.
↳basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + X.monomial(3)
sage: x.trailing_item()
(1, 3)
sage: def key(x): return -x
sage: x.trailing_item(key=key)
(3, 1)

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.trailing_item()
([1], 2)

```

trailing_monomial(*args, **kws)

Return the trailing monomial of `self`.

This is the monomial whose corresponding basis element is minimal. Note that this may not be the term which actually appears last when `self` is printed.

If the default term ordering is not what is desired, a comparison key `key(x)`, can be provided.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.
↳basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + X.monomial(3)
sage: x.trailing_monomial()
B[1]
sage: def key(x): return -x
sage: x.trailing_monomial(key=key)
B[3]

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]

```

(continues on next page)

(continued from previous page)

```
sage: f.trailing_monomial()
s[1]
```

trailing_support(*args, **kws)

Return the minimal element of the support of `self`. Note that this may not be the term which actually appears last when `self` is printed.

If the default ordering of the basis elements is not what is desired, a comparison key, `key(x)`, can be provided.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.
↳basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + 4*X.monomial(3)
sage: x.trailing_support()
1

sage: def key(x): return -x
sage: x.trailing_support(key=key)
3

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.trailing_support()
[1]
```

trailing_term(*args, **kws)

Return the trailing term of `self`.

This is the term whose corresponding basis element is minimal. Note that this may not be the term which actually appears last when `self` is printed.

If the default term ordering is not what is desired, a comparison key `key(x)`, can be provided.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.
↳basis()
sage: x = 3*X.monomial(1) + 2*X.monomial(2) + X.monomial(3)
sage: x.trailing_term()
3*B[1]

sage: def key(x): return -x
sage: x.trailing_term(key=key)
B[3]

sage: s = SymmetricFunctions(QQ).schur()
sage: f = 2*s[1] + 3*s[2,1] - 5*s[3]
sage: f.trailing_term()
2*s[1]
```

Filtered

alias of `sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis`

FiniteDimensional

alias of `sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis`

Graded

alias of `sage.categories.graded_modules_with_basis.GradedModulesWithBasis`

class Homsets(*category, *args*)

Bases: `sage.categories.homsets.HomsetsCategory`

class ParentMethods

Bases: object

class MorphismMethods

Bases: object

on_basis()

Return the action of this morphism on basis elements.

OUTPUT:

- a function from the indices of the basis of the domain to the codomain

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); X.rename("X")
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4]); Y.rename("Y")
sage: H = Hom(X, Y)
sage: x = X.basis()

sage: f = H(lambda x: Y.zero()).on_basis()
sage: f(2)
0

sage: f = lambda i: Y.monomial(i) + 2*Y.monomial(i+1)
sage: g = H(on_basis = f).on_basis()
sage: g(2)
B[2] + 2*B[3]
sage: g == f
True
```

class ParentMethods

Bases: object

basis()

Return the basis of self.

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a','b','c'])
sage: F.basis()
Finite family {'a': B['a'], 'b': B['b'], 'c': B['c']}
```

```
sage: QS3 = SymmetricGroupAlgebra(QQ,3)
sage: list(QS3.basis())
[[1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 3, 1], [3, 1, 2], [3, 2, 1]]
```

cardinality()

Return the cardinality of self.

EXAMPLES:

```

sage: S = SymmetricGroupAlgebra(QQ, 4)
sage: S.cardinality()
+Infinity
sage: S = SymmetricGroupAlgebra(GF(2), 4) # not tested -- MRO bug trac
↪ #15475
sage: S.cardinality() # not tested -- MRO bug trac #15475
16777216
sage: S.cardinality().factor() # not tested -- MRO bug trac #15475
2^24

sage: E.<x,y> = ExteriorAlgebra(QQ)
sage: E.cardinality()
+Infinity
sage: E.<x,y> = ExteriorAlgebra(GF(3))
sage: E.cardinality()
81

sage: s = SymmetricFunctions(GF(2)).s()
sage: s.cardinality()
+Infinity

```

dimension()

Return the dimension of `self`.

EXAMPLES:

```

sage: A.<x,y> = algebras.DifferentialWeyl(QQ)
sage: A.dimension()
+Infinity

```

echelon_form(*elements*, *row_reduced=False*, *order=None*)

Return a basis in echelon form of the subspace spanned by a finite set of elements.

INPUT:

- `elements` – a list or finite iterable of elements of `self`
- `row_reduced` – (default: `False`) whether to compute the basis for the row reduced echelon form
- `order` – (optional) either something that can be converted into a tuple or a key function

OUTPUT:

A list of elements of `self` whose expressions as vectors form a matrix in echelon form. If `base_ring` is specified, then the calculation is achieved in this base ring.

EXAMPLES:

```

sage: R.<x,y> = QQ[]
sage: C = CombinatorialFreeModule(R, ZZ, prefix='z')
sage: z = C.basis()
sage: C.echelon_form([z[0] - z[1], 2*z[1] - 2*z[2], z[0] - z[2]])
[z[0] - z[2], z[1] - z[2]]

```

is_finite()

Return whether `self` is finite.

This is true if and only if `self.basis().keys()` and `self.base_ring()` are both finite.

EXAMPLES:

```

sage: GroupAlgebra(SymmetricGroup(2), IntegerModRing(10)).is_finite()
True
sage: GroupAlgebra(SymmetricGroup(2)).is_finite()
False
sage: GroupAlgebra(AbelianGroup(1), IntegerModRing(10)).is_finite()
False

```

module_morphism(*on_basis=None, matrix=None, function=None, diagonal=None, triangular=None, unitriangular=False, **keywords*)

Construct a module morphism from *self* to *codomain*.

Let *self* be a module X with a basis indexed by I . This constructs a morphism $f : X \rightarrow Y$ by linearity from a map $I \rightarrow Y$ which is to be its restriction to the basis $(x_i)_{i \in I}$ of X . Some variants are possible too.

INPUT:

- *self* – a parent X in `ModulesWithBasis(R)` with basis $x = (x_i)_{i \in I}$.

Exactly one of the four following options must be specified in order to define the morphism:

- *on_basis* – a function f from I to Y
- *diagonal* – a function d from I to R
- *function* – a function f from X to Y
- *matrix* – a matrix of size $\dim Y \times \dim X$ (if the keyword *side* is set to 'left') or $\dim Y \times \dim X$ (if this keyword is 'right')

Further options include:

- *codomain* – the codomain Y of the morphism (default: `f.codomain()` if it's defined; otherwise it must be specified)
- *category* – a category or `None` (default: `None`)
- *zero* – the zero of the codomain (default: `codomain.zero()`); can be used (with care) to define affine maps. Only meaningful with *on_basis*.
- *position* – a non-negative integer specifying which positional argument is used as the input of the function f (default: 0); this is currently only used with *on_basis*.
- *triangular* – (default: `None`) "upper" or "lower" or `None`:
 - "upper" - if the `leading_support()` of the image of the basis vector x_i is i , or
 - "lower" - if the `trailing_support()` of the image of the basis vector x_i is i .
- *unitriangular* – (default: `False`) a boolean. Only meaningful for a triangular morphism. As a shorthand, one may use `unitriangular="lower"` for `triangular="lower"`, `unitriangular=True`.
- *side* – "left" or "right" (default: "left") Only meaningful for a morphism built from a matrix.

EXAMPLES:

With the *on_basis* option, this returns a function g obtained by extending f by linearity on the *position*-th positional argument. For example, for `position == 1` and a ternary function f , one has:

$$g\left(a, \sum_i \lambda_i x_i, c\right) = \sum_i \lambda_i f(a, i, c).$$

```

sage: X = CombinatorialFreeModule(QQ, [1,2,3]); X.rename("X")
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4]); Y.rename("Y")
sage: phi = X.module_morphism(lambda i: Y.monomial(i) + 2*Y.monomial(i+1),
↵ codomain = Y)
sage: x = X.basis(); y = Y.basis()
sage: phi(x[1] + x[3])
B[1] + 2*B[2] + B[3] + 2*B[4]

```

(continues on next page)

(continued from previous page)

```
sage: phi
Generic morphism:
From: X
To: Y
```

By default, the category is the first of `Modules(R).WithBasis().FiniteDimensional()`, `Modules(R).WithBasis()`, `Modules(R)`, and `CommutativeAdditiveMonoids()` that contains both the domain and the codomain:

```
sage: phi.category_for()
Category of finite dimensional vector spaces with basis over Rational Field
```

With the zero argument, one can define affine morphisms:

```
sage: phi = X.module_morphism(lambda i: Y.monomial(i) + 2*Y.monomial(i+1),
....:                          codomain = Y, zero = 10*y[1])
sage: phi(x[1] + x[3])
11*B[1] + 2*B[2] + B[3] + 2*B[4]
```

In this special case, the default category is `Sets()`:

```
sage: phi.category_for()
Category of sets
```

One can construct morphisms with the base ring as codomain:

```
sage: X = CombinatorialFreeModule(ZZ,[1,-1])
sage: phi = X.module_morphism( on_basis=lambda i: i, codomain=ZZ )
sage: phi( 2 * X.monomial(1) + 3 * X.monomial(-1) )
-1
sage: phi.category_for()
Category of commutative additive semigroups
sage: phi.category_for() # todo: not implemented (ZZ is currently not in
↳Modules(ZZ))
Category of modules over Integer Ring
```

Or more generally any ring admitting a coercion map from the base ring:

```
sage: phi = X.module_morphism(on_basis=lambda i: i, codomain=RR )
sage: phi( 2 * X.monomial(1) + 3 * X.monomial(-1) )
-1.0000000000000000
sage: phi.category_for()
Category of commutative additive semigroups
sage: phi.category_for() # todo: not implemented (RR is currently not in
↳Modules(ZZ))
Category of modules over Integer Ring

sage: phi = X.module_morphism(on_basis=lambda i: i, codomain=Zmod(4) )
sage: phi( 2 * X.monomial(1) + 3 * X.monomial(-1) )
3
sage: phi = Y.module_morphism(on_basis=lambda i: i, codomain=Zmod(4) )
```

(continues on next page)

(continued from previous page)

```
Traceback (most recent call last):
...
ValueError: codomain(=Ring of integers modulo 4) should be a module over
↳the base ring of the domain(=Y)
```

One can also define module morphisms between free modules over different base rings; here we implement the natural map from $X = \mathbf{R}^2$ to $Y = \mathbf{C}$:

```
sage: X = CombinatorialFreeModule(RR,['x','y'])
sage: Y = CombinatorialFreeModule(CC,['z'])
sage: x = X.monomial('x')
sage: y = X.monomial('y')
sage: z = Y.monomial('z')
sage: def on_basis( a ):
.....:     if a == 'x':
.....:         return CC(1) * z
.....:     elif a == 'y':
.....:         return CC(I) * z
sage: phi = X.module_morphism( on_basis=on_basis, codomain=Y )
sage: v = 3 * x + 2 * y; v
3.000000000000000*B['x'] + 2.000000000000000*B['y']
sage: phi(v)
(3.000000000000000+2.000000000000000*I)*B['z']
sage: phi.category_for()
Category of commutative additive semigroups
sage: phi.category_for() # todo: not implemented (CC is currently not in
↳Modules(RR)!)
Category of vector spaces over Real Field with 53 bits of precision

sage: Y = CombinatorialFreeModule(CC['q'],['z'])
sage: z = Y.monomial('z')
sage: phi = X.module_morphism( on_basis=on_basis, codomain=Y )
sage: phi(v)
(3.000000000000000+2.000000000000000*I)*B['z']
```

Of course, there should be a coercion between the respective base rings of the domain and the codomain for this to be meaningful:

```
sage: Y = CombinatorialFreeModule(QQ,['z'])
sage: phi = X.module_morphism( on_basis=on_basis, codomain=Y )
Traceback (most recent call last):
...
ValueError: codomain(=Free module generated by {'z'} over Rational Field)
should be a module over the base ring of the
domain(=Free module generated by {'x', 'y'} over Real Field with 53 bits
↳of precision)

sage: Y = CombinatorialFreeModule(RR['q'],['z'])
sage: phi = Y.module_morphism( on_basis=on_basis, codomain=X )
Traceback (most recent call last):
...
ValueError: codomain(=Free module generated by {'x', 'y'} over Real Field
↳with 53 bits of precision)
```

(continues on next page)

(continued from previous page)

```

should be a module over the base ring of the
domain(=Free module generated by {'z'} over Univariate Polynomial Ring in z
↳ q over Real Field with 53 bits of precision)

```

With the `diagonal=d` argument, this constructs the module morphism g such that

$$g(x_i) = d(i)y_i.$$

This assumes that the respective bases x and y of X and Y have the same index set I :

```

sage: X = CombinatorialFreeModule(ZZ, [1,2,3]); X.rename("X")
sage: phi = X.module_morphism(diagonal=factorial, codomain=X)
sage: x = X.basis()
sage: phi(x[1]), phi(x[2]), phi(x[3])
(B[1], 2*B[2], 6*B[3])

```

See also: `sage.modules.with_basis.morphism.DiagonalModuleMorphism`.

With the `matrix=m` argument, this constructs the module morphism whose matrix in the distinguished basis of X and Y is m :

```

sage: X = CombinatorialFreeModule(ZZ, [1,2,3]); X.rename("X"); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [3,4]); Y.rename("Y"); y = Y.basis()
sage: m = matrix([[0,1,2],[3,5,0]])
sage: phi = X.module_morphism(matrix=m, codomain=Y)
sage: phi(x[1])
3*B[4]
sage: phi(x[2])
B[3] + 5*B[4]

```

See also: `sage.modules.with_basis.morphism.ModuleMorphismFromMatrix`.

With `triangular="upper"`, the constructed module morphism is assumed to be upper triangular; that is its matrix in the distinguished basis of X and Y would be upper triangular with invertible elements on its diagonal. This is used to compute preimages and to invert the morphism:

```

sage: I = list(range(1, 200))
sage: X = CombinatorialFreeModule(QQ, I); X.rename("X"); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, I); Y.rename("Y"); y = Y.basis()
sage: f = Y.sum_of_monomials * divisors
sage: phi = X.module_morphism(f, triangular="upper", codomain = Y)
sage: phi(x[2])
B[1] + B[2]
sage: phi(x[6])
B[1] + B[2] + B[3] + B[6]
sage: phi(x[30])
B[1] + B[2] + B[3] + B[5] + B[6] + B[10] + B[15] + B[30]
sage: phi.preimage(y[2])
-B[1] + B[2]
sage: phi.preimage(y[6])
B[1] - B[2] - B[3] + B[6]
sage: phi.preimage(y[30])
-B[1] + B[2] + B[3] + B[5] - B[6] - B[10] - B[15] + B[30]
sage: (phi^-1)(y[30])
-B[1] + B[2] + B[3] + B[5] - B[6] - B[10] - B[15] + B[30]

```

Since [trac ticket #8678](#), one can also define a triangular morphism from a function:

```
sage: X = CombinatorialFreeModule(QQ, [0,1,2,3,4]); x = X.basis()
sage: from sage.modules.with_basis.morphism import_
↳TriangularModuleMorphismFromFunction
sage: def f(x): return x + X.term(0, sum(x.coefficients()))
sage: phi = X.module_morphism(function=f, codomain=X, triangular="upper")
sage: phi(x[2] + 3*x[4])
4*B[0] + B[2] + 3*B[4]
sage: phi.preimage(_)
B[2] + 3*B[4]
```

For details and further optional arguments, see [sage.modules.with_basis.morphism.TriangularModuleMorphism](#).

Warning: As a temporary measure, until multivariate morphisms are implemented, the constructed morphism is in $\text{Hom}(\text{codomain}, \text{domain}, \text{category})$. This is only correct for unary functions.

Todo:

- Should codomain be self by default in the diagonal, triangular, and matrix cases?
 - Support for diagonal morphisms between modules not sharing the same index set
-

monomial(*i*)

Return the basis element indexed by *i*.

INPUT:

- *i* – an element of the index set

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: F.monomial('a')
B['a']
```

`F.monomial` is in fact (almost) a map:

```
sage: F.monomial
Term map from {'a', 'b', 'c'} to Free module generated by {'a', 'b', 'c'}_
↳over Rational Field
```

monomial_or_zero_if_none(*i*)

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: F.monomial_or_zero_if_none('a')
B['a']
sage: F.monomial_or_zero_if_none(None)
0
```

quotient_module(*submodule*, *check=True*, *already_echelonized=False*, *category=None*)

Construct the quotient module `self / submodule`.

INPUT:

- `submodule` – a submodule with basis of `self`, or something that can be turned into one via `self.submodule(submodule)`
- `check`, `already_echelonized` – passed down to `ModulesWithBasis.ParentMethods.submodule()`

Warning: At this point, this only supports quotients by free submodules admitting a basis in unitriangular echelon form. In this case, the quotient is also a free module, with a basis consisting of the retract of a subset of the basis of `self`.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x")
sage: x = X.basis()
sage: Y = X.quotient_module([x[0]-x[1], x[1]-x[2]], already_
↪echelonized=True)
sage: Y.print_options(prefix='y'); Y
Free module generated by {2} over Rational Field
sage: y = Y.basis()
sage: y[2]
y[2]
sage: y[2].lift()
x[2]
sage: Y.retract(x[0]+2*x[1])
3*y[2]

sage: R.<a,b> = QQ[]
sage: C = CombinatorialFreeModule(R, range(3), prefix='x')
sage: x = C.basis()
sage: gens = [x[0] - x[1], 2*x[1] - 2*x[2], x[0] - x[2]]
sage: Y = X.quotient_module(gens)
```

See also:

- `Modules.WithBasis.ParentMethods.submodule()`
- `Rings.ParentMethods.quotient()`
- `sage.modules.with_basis.subquotient.QuotientModuleWithBasis`

random_element(*n=2*)

Return a ‘random’ element of `self`.

INPUT:

- `n` – integer (default: 2); number of summands

ALGORITHM:

Return a sum of `n` terms, each of which is formed by multiplying a random element of the base ring by a random element of the group.

EXAMPLES:

```
sage: x = DihedralGroup(6).algebra(QQ).random_element()
sage: x.parent() is DihedralGroup(6).algebra(QQ)
True
```

Note, this result can depend on the PRNG state in `libgap` in a way that depends on which packages are loaded, so we must re-seed GAP to ensure a consistent result for this example:

```

sage: libgap.set_seed(0)
0
sage: m = SU(2, 13).algebra(QQ).random_element(1)
sage: m.parent() is SU(2, 13).algebra(QQ)
True
sage: p = CombinatorialFreeModule(ZZ, Partitions(4)).random_element()
sage: p.parent() is CombinatorialFreeModule(ZZ, Partitions(4))
True

```

submodule(*gens*, *check=True*, *already_echelonized=False*, *unitriangular=False*, *support_order=None*, *category=None*, **args*, ***opts*)

The submodule spanned by a finite set of elements.

INPUT:

- *gens* – a list or family of elements of self
- **check** – (default: **True**) whether to verify that the elements of *gens* are in self
- **already_echelonized** – (default: **False**) whether the elements of *gens* are already in (not necessarily reduced) echelon form
- **unitriangular** – (default: **False**) whether the lift morphism is unitriangular
- **support_order** – (optional) either something that can be converted into a tuple or a key function

If *already_echelonized* is **False**, then the generators are put in reduced echelon form using `echelonize()`, and reindexed by 0, 1,

Warning: At this point, this method only works for finite dimensional submodules and if matrices can be echelonized over the base ring.

If in addition *unitriangular* is **True**, then the generators are made such that the coefficients of the pivots are 1, so that lifting map is unitriangular.

The basis of the submodule uses the same index set as the generators, and the lifting map sends y_i to $gens[i]$.

See also:

- `ModulesWithBasis.FiniteDimensional.ParentMethods.quotient_module()`
- `sage.modules.with_basis.subquotient.SubmoduleWithBasis`

EXAMPLES:

We construct a submodule of the free \mathbf{Q} -module generated by x_0, x_1, x_2 . The submodule is spanned by $y_0 = x_0 - x_1$ and $y_1 = x_1 - x_2$, and its basis elements are indexed by 0 and 1:

```

sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x")
sage: x = X.basis()
sage: gens = [x[0] - x[1], x[1] - x[2]]; gens
[x[0] - x[1], x[1] - x[2]]
sage: Y = X.submodule(gens, already_echelonized=True)
sage: Y.print_options(prefix='y'); Y
Free module generated by {0, 1} over Rational Field
sage: y = Y.basis()
sage: y[1]
y[1]
sage: y[1].lift()
x[1] - x[2]

```

(continues on next page)

(continued from previous page)

```

sage: Y.retract(x[0]-x[2])
y[0] + y[1]
sage: Y.retract(x[0])
Traceback (most recent call last):
...
ValueError: x[0] is not in the image

```

By using a family to specify a basis of the submodule, we obtain a submodule whose index set coincides with the index set of the family:

```

sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x")
sage: x = X.basis()
sage: gens = Family({1 : x[0] - x[1], 3: x[1] - x[2]}); gens
Finite family {1: x[0] - x[1], 3: x[1] - x[2]}
sage: Y = X.submodule(gens, already_echelonized=True)
sage: Y.print_options(prefix='y'); Y
Free module generated by {1, 3} over Rational Field
sage: y = Y.basis()
sage: y[1]
y[1]
sage: y[1].lift()
x[0] - x[1]
sage: y[3].lift()
x[1] - x[2]
sage: Y.retract(x[0]-x[2])
y[1] + y[3]
sage: Y.retract(x[0])
Traceback (most recent call last):
...
ValueError: x[0] is not in the image

```

It is not necessary that the generators of the submodule form a basis (an explicit basis will be computed):

```

sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x")
sage: x = X.basis()
sage: gens = [x[0] - x[1], 2*x[1] - 2*x[2], x[0] - x[2]]; gens
[x[0] - x[1], 2*x[1] - 2*x[2], x[0] - x[2]]
sage: Y = X.submodule(gens, already_echelonized=False)
sage: Y.print_options(prefix='y')
sage: Y
Free module generated by {0, 1} over Rational Field
sage: [b.lift() for b in Y.basis()]
[x[0] - x[2], x[1] - x[2]]

```

We now implement by hand the center of the algebra of the symmetric group S_3 :

```

sage: S3 = SymmetricGroup(3)
sage: S3A = S3.algebra(QQ)
sage: basis = S3A.annihilator_basis(S3A.algebra_generators(), S3A.bracket)
sage: basis
((), (1,2,3) + (1,3,2), (2,3) + (1,2) + (1,3))
sage: center = S3A.submodule(basis,

```

(continues on next page)

(continued from previous page)

```

.....:                                     category=AlgebrasWithBasis(QQ).Subobjects(),
.....:                                     already_echelonized=True)
sage: center
Free module generated by {0, 1, 2} over Rational Field
sage: center in Algebras
True
sage: center.print_options(prefix='c')
sage: c = center.basis()
sage: c[1].lift()
(1,2,3) + (1,3,2)
sage: c[0]^2
c[0]
sage: e = 1/6*(c[0]+c[1]+c[2])
sage: e.is_idempotent()
True

```

Of course, this center is best constructed using:

```
sage: center = S3A.center()
```

We can also automatically construct a basis such that the lift morphism is (lower) unitriangular:

```

sage: R.<a,b> = QQ[]
sage: C = CombinatorialFreeModule(R, range(3), prefix='x')
sage: x = C.basis()
sage: gens = [x[0] - x[1], 2*x[1] - 2*x[2], x[0] - x[2]]
sage: Y = C.submodule(gens, unitriangular=True)
sage: Y.lift.matrix()
[ 1  0]
[ 0  1]
[-1 -1]

```

We now construct a (finite-dimensional) submodule of an infinite dimensional free module:

```

sage: C = CombinatorialFreeModule(QQ, ZZ, prefix='z')
sage: z = C.basis()
sage: gens = [z[0] - z[1], 2*z[1] - 2*z[2], z[0] - z[2]]
sage: Y = C.submodule(gens)
sage: [Y.lift(b) for b in Y.basis()]
[z[0] - z[2], z[1] - z[2]]

```

sum_of_monomials()

Return the sum of the basis elements with indices in `indices`.

INPUT:

- `indices` – an list (or iterable) of indices of basis elements

EXAMPLES:

```

sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: F.sum_of_monomials(['a', 'b'])
B['a'] + B['b']

sage: F.sum_of_monomials(['a', 'b', 'a'])
2*B['a'] + B['b']

```

`F.sum_of_monomials` is in fact (almost) a map:

```
sage: F.sum_of_monomials
A map to Free module generated by {'a', 'b', 'c'} over Rational Field
```

sum_of_terms(*terms*)

Construct a sum of terms of `self`.

INPUT:

- `terms` – a list (or iterable) of pairs (`index`, `coeff`)

OUTPUT:

Sum of `coeff * B[index]` over all (`index`, `coeff`) in `terms`, where `B` is the basis of `self`.

EXAMPLES:

```
sage: m = matrix([[0,1],[1,1]])
sage: J.<a,b,c> = JordanAlgebra(m)
sage: J.sum_of_terms([(0, 2), (2, -3)])
2 + (0, -3)
```

tensor(**parents, **kwargs*)

Return the tensor product of the parents.

EXAMPLES:

```
sage: C = AlgebrasWithBasis(QQ)
sage: A = C.example(); A.rename("A")
sage: A.tensor(A,A)
A # A # A
sage: A.rename(None)
```

term(*index, coeff=None*)

Construct a term in `self`.

INPUT:

- `index` – the index of a basis element
- `coeff` – an element of the coefficient ring (default: one)

OUTPUT:

`coeff * B[index]`, where `B` is the basis of `self`.

EXAMPLES:

```
sage: m = matrix([[0,1],[1,1]])
sage: J.<a,b,c> = JordanAlgebra(m)
sage: J.term(1, -2)
0 + (-2, 0)
```

Design: should this do coercion on the coefficient ring?

Super

alias of `sage.categories.super_modules_with_basis.SuperModulesWithBasis`

class TensorProducts(*category, *args*)

Bases: `sage.categories.tensor.TensorProductsCategory`

The category of modules with basis constructed by tensor product of modules with basis.

class ElementMethods

Bases: object

Implements operations on elements of tensor products of modules with basis.

apply_multilinear_morphism(*f*, *codomain=None*)Return the result of applying the morphism induced by *f* to *self*.

INPUT:

- *f* – a multilinear morphism from the component modules of the parent tensor product to any module
- *codomain* – the codomain of *f* (optional)

By the universal property of the tensor product, *f* induces a linear morphism from *self.parent()* to the target module. Returns the result of applying that morphism to *self*.The codomain is used for optimizations purposes only. If it's not provided, it's recovered by calling *f* on the zero input.

EXAMPLES:

We start with simple (admittedly not so interesting) examples, with two modules *A* and *B*:

```
sage: A = CombinatorialFreeModule(ZZ, [1,2], prefix="A"); A.rename("A")
sage: B = CombinatorialFreeModule(ZZ, [3,4], prefix="B"); B.rename("B")
```

and *f* the bilinear morphism $(a, b) \mapsto b \otimes a$ from $A \times B$ to $B \otimes A$:

```
sage: def f(a,b):
.....:     return tensor([b,a])
```

Now, calling applying *f* on $a \otimes b$ returns the same as $f(a, b)$:

```
sage: a = A.monomial(1) + 2 * A.monomial(2); a
A[1] + 2*A[2]
sage: b = B.monomial(3) - 2 * B.monomial(4); b
B[3] - 2*B[4]
sage: f(a,b)
B[3] # A[1] + 2*B[3] # A[2] - 2*B[4] # A[1] - 4*B[4] # A[2]
sage: tensor([a,b]).apply_multilinear_morphism(f)
B[3] # A[1] + 2*B[3] # A[2] - 2*B[4] # A[1] - 4*B[4] # A[2]
```

f may be a bilinear morphism to any module over the base ring of *A* and *B*. Here the codomain is \mathbf{Z} :

```
sage: def f(a,b):
.....:     return sum(a.coefficients(), 0) * sum(b.coefficients(), 0)
sage: f(a,b)
-3
sage: tensor([a,b]).apply_multilinear_morphism(f)
-3
```

Mind the 0 in the sums above; otherwise *f* would not return 0 in \mathbf{Z} :

```
sage: def f(a,b):
.....:     return sum(a.coefficients()) * sum(b.coefficients())
sage: type(f(A.zero(), B.zero()))
<... 'int'>
```

Which would be wrong and break this method:

```
sage: tensor([a,b]).apply_multilinear_morphism(f)
Traceback (most recent call last):
...
AttributeError: 'int' object has no attribute 'parent'
```

Here we consider an example where the codomain is a module with basis with a different base ring:

```
sage: C = CombinatorialFreeModule(QQ, [(1,3),(2,4)], prefix="C"); C.
↳rename("C")
sage: def f(a,b):
...:     return C.sum_of_terms( [((1,3), QQ(a[1]*b[3])), ((2,4),
↳QQ(a[2]*b[4]))] )
sage: f(a,b)
C[(1, 3)] - 4*C[(2, 4)]
sage: tensor([a,b]).apply_multilinear_morphism(f)
C[(1, 3)] - 4*C[(2, 4)]
```

We conclude with a real life application, where we check that the antipode of the Hopf algebra of Symmetric functions on the Schur basis satisfies its defining formula::

```
sage: Sym = SymmetricFunctions(QQ)
sage: s = Sym.schur()
sage: def f(a,b): return a*b.antipode()
sage: x = 4*s.an_element(); x
8*s[] + 8*s[1] + 12*s[2]
sage: x.coproduct().apply_multilinear_morphism(f)
8*s[]
sage: x.coproduct().apply_multilinear_morphism(f) == x.counit()
True
```

We recover the constant term of x , as desired.

Todo: Extract a method to linearize a multilinear morphism, and delegate the work there.

class ParentMethods

Bases: object

Implements operations on tensor products of modules with basis.

extra_super_categories()

EXAMPLES:

```
sage: ModulesWithBasis(QQ).TensorProducts().extra_super_categories()
[Category of vector spaces with basis over Rational Field]
sage: ModulesWithBasis(QQ).TensorProducts().super_categories()
[Category of tensor products of modules with basis over Rational Field,
Category of vector spaces with basis over Rational Field,
Category of tensor products of vector spaces over Rational Field]
```

is_abelian()

Return whether this category is abelian.

This is the case if and only if the base ring is a field.

EXAMPLES:

```
sage: ModulesWithBasis(QQ).is_abelian()
True
sage: ModulesWithBasis(ZZ).is_abelian()
False
```

3.120 Monoid algebras

`sage.categories.monoid_algebras.MonoidAlgebras`(*base_ring*)

The category of monoid algebras over *base_ring*.

EXAMPLES:

```
sage: C = MonoidAlgebras(QQ); C
Category of monoid algebras over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of bialgebras with basis over Rational Field,
Category of semigroup algebras over Rational Field,
Category of unital magma algebras over Rational Field]
```

This is just an alias for:

```
sage: C is Monoids().Algebras(QQ)
True
```

3.121 Monoids

class `sage.categories.monoids.Monoids`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of (multiplicative) monoids.

A *monoid* is a unital *semigroup*, that is a set endowed with a multiplicative binary operation $*$ which is associative and admits a unit (see [Wikipedia article Monoid](#)).

EXAMPLES:

```
sage: Monoids()
Category of monoids
sage: Monoids().super_categories()
[Category of semigroups, Category of unital magmas]
sage: Monoids().all_super_categories()
[Category of monoids,
Category of semigroups,
Category of unital magmas, Category of magmas,
Category of sets,
```

(continues on next page)

(continued from previous page)

```
Category of sets with partial maps,
Category of objects]
```

```
sage: Monoids().axioms()
frozenset({'Associative', 'Unital'})
```

```
sage: Semigroups().Unital()
Category of monoids
```

```
sage: Monoids().example()
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
```

```
class Algebras(category, *args)
```

```
Bases: sage.categories.algebra_functor.AlgebrasCategory
```

```
class ElementMethods
```

```
Bases: object
```

```
is_central()
```

```
Return whether the element self is central.
```

```
EXAMPLES:
```

```
sage: SG4 = SymmetricGroupAlgebra(ZZ,4)
sage: SG4(1).is_central()
True
sage: SG4(Permutation([1,3,2,4])).is_central()
False
sage: A = GroupAlgebras(QQ).example(); A
Algebra of Dihedral group of order 8 as a permutation group over
↳Rational Field
sage: sum(i for i in A.basis()).is_central()
True
```

```
class ParentMethods
```

```
Bases: object
```

```
algebra_generators()
```

```
Return generators for this algebra.
```

```
For a monoid algebra, the algebra generators are built from the monoid generators if available and from the semigroup generators otherwise.
```

```
See also:
```

- [Semigroups.Algebras.ParentMethods.algebra_generators\(\)](#)
- [MagmaticAlgebras.ParentMethods.algebra_generators\(\)](#)

```
EXAMPLES:
```

```
sage: M = Monoids().example(); M
An example of a monoid:
the free monoid generated by ('a', 'b', 'c', 'd')
sage: M.monoid_generators()
Finite family {'a': 'a', 'b': 'b', 'c': 'c', 'd': 'd'}
sage: M.algebra(ZZ).algebra_generators()
Finite family {'a': B['a'], 'b': B['b'], 'c': B['c'], 'd': B['d']}
```

(continues on next page)

(continued from previous page)

```

sage: Z12 = Monoids().Finite().example(); Z12
An example of a finite multiplicative monoid:
the integers modulo 12
sage: Z12.monoid_generators()
Traceback (most recent call last):
...
AttributeError: 'IntegerModMonoid_with_category' object
has no attribute 'monoid_generators'
sage: Z12.semigroup_generators()
Family (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11)
sage: Z12.algebra(QQ).algebra_generators()
Finite family {0: B[0], 1: B[1], 2: B[2], 3: B[3], 4: B[4], 5: B[5],
               6: B[6], 7: B[7], 8: B[8], 9: B[9], 10: B[10], 11: B[11]}

sage: GroupAlgebras(QQ).example(AlternatingGroup(10)).algebra_
↳generators()
Finite family {0: (8,9,10), 1: (1,2,3,4,5,6,7,8,9)}

sage: A = DihedralGroup(3).algebra(QQ); A
Algebra of Dihedral group of order 6 as a permutation group
over Rational Field
sage: A.algebra_generators()
Finite family {0: (1,2,3), 1: (1,3)}

```

one_basis()

Return the unit of the monoid, which indexes the unit of this algebra, as per `AlgebrasWithBasis.ParentMethods.one_basis()`.

EXAMPLES:

```

sage: A = Monoids().example().algebra(ZZ)
sage: A.one_basis()
''
sage: A.one()
B['']
sage: A(3)
3*B['']

```

extra_super_categories()

The algebra of a monoid is a bialgebra and a monoid.

EXAMPLES:

```

sage: C = Monoids().Algebras(QQ)
sage: C.extra_super_categories()
[Category of bialgebras over Rational Field,
 Category of monoids]
sage: Monoids().Algebras(QQ).super_categories()
[Category of bialgebras with basis over Rational Field,
 Category of semigroup algebras over Rational Field,
 Category of unital magma algebras over Rational Field]

```

class CartesianProducts(*category, *args*)

Bases: [sage.categories.cartesian_product.CartesianProductsCategory](#)

The category of monoids constructed as Cartesian products of monoids.

This construction gives the direct product of monoids. See [Wikipedia article Direct_product](#) for more information.

class ParentMethods

Bases: object

monoid_generators()

Return the generators of self.

EXAMPLES:

```
sage: M = Monoids.free([1,2,3])
sage: N = Monoids.free(['a','b'])
sage: C = cartesian_product([M, N])
sage: C.monoid_generators()
Family ((F[1], 1), (F[2], 1), (F[3], 1),
        (1, F['a']), (1, F['b']))
```

An example with an infinitely generated group (a better output is needed):

```
sage: N = Monoids.free(ZZ)
sage: C = cartesian_product([M, N])
sage: C.monoid_generators()
Lazy family (gen(i))_{i in The Cartesian product of (...)}
```

extra_super_categories()

A Cartesian product of monoids is endowed with a natural group structure.

EXAMPLES:

```
sage: C = Monoids().CartesianProducts()
sage: C.extra_super_categories()
[Category of monoids]
sage: sorted(C.super_categories(), key=str)
[Category of Cartesian products of semigroups,
 Category of Cartesian products of unital magmas,
 Category of monoids]
```

class Commutative(*base_category*)

Bases: [sage.categories.category_with_axiom.CategoryWithAxiom_singleton](#)

Category of commutative (abelian) monoids.

A monoid M is *commutative* if $xy = yx$ for all $x, y \in M$.

static free(*index_set=None, names=None, **kwds*)

Return a free abelian monoid on n generators or with the generators indexed by a set I .

A free monoid is constructed by specifying either:

- the number of generators and/or the names of the generators, or
- the indexing set for the generators.

INPUT:

- *index_set* – (optional) an index set for the generators; if an integer, then this represents $\{0, 1, \dots, n - 1\}$
- *names* – a string or list/tuple/iterable of strings (default: 'x'); the generator names or name prefix

EXAMPLES:

```
sage: Monoids.Commutative.free(index_set=ZZ)
Free abelian monoid indexed by Integer Ring
sage: Monoids().Commutative().free(ZZ)
Free abelian monoid indexed by Integer Ring
sage: F.<x,y,z> = Monoids().Commutative().free(); F
Free abelian monoid indexed by {'x', 'y', 'z'}
```

class ElementMethods

Bases: object

is_one()

Return whether `self` is the one of the monoid.

The default implementation is to compare with `self.one()`.

powers(*n*)

Return the list $[x^0, x^1, \dots, x^{n-1}]$.

EXAMPLES:

```
sage: A = Matrix([[1, 1], [-1, 0]])
sage: A.powers(6)
[
 [1 0] [ 1 1] [ 0 1] [-1 0] [-1 -1] [ 0 -1]
 [0 1], [-1 0], [-1 -1], [ 0 -1], [ 1 0], [ 1 1]
]
```

Finite

alias of `sage.categories.finite_monoids.FiniteMonoids`

Inverse

alias of `sage.categories.groups.Groups`

class ParentMethods

Bases: object

prod(*args*)

n-ary product of elements of `self`.

INPUT:

- `args` – a list (or iterable) of elements of `self`

Returns the product of the elements in `args`, as an element of `self`.

EXAMPLES:

```
sage: S = Monoids().example()
sage: S.prod([S('a'), S('b')])
'ab'
```

semigroup_generators()

Return the generators of `self` as a semigroup.

The generators of a monoid M as a semigroup are the generators of M as a monoid and the unit.

EXAMPLES:

```
sage: M = Monoids().free([1,2,3])
sage: M.semigroup_generators()
Family (1, F[1], F[2], F[3])
```

submonoid(*generators, category=None*)

Return the multiplicative submonoid generated by *generators*.

INPUT:

- *generators* – a finite family of elements of *self*, or a list, iterable, ... that can be converted into one (see *Family*).
- *category* – a category

This is a shorthand for *Semigroups.ParentMethods.subsemigroup()* that specifies that this is a submonoid, and in particular that the unit is *self.one()*.

EXAMPLES:

```
sage: R = IntegerModRing(15)
sage: M = R.submonoid([R(3),R(5)]); M
A submonoid of (Ring of integers modulo 15) with 2 generators
sage: M.list()
[1, 3, 5, 9, 0, 10, 12, 6]
```

Not the presence of the unit, unlike in:

```
sage: S = R.subsemigroup([R(3),R(5)]); S
A subsemigroup of (Ring of integers modulo 15) with 2 generators
sage: S.list()
[3, 5, 9, 0, 10, 12, 6]
```

This method is really a shorthand for *subsemigroup*:

```
sage: M2 = R.subsemigroup([R(3),R(5)], one=R.one())
sage: M2 is M
True
```

class Subquotients(*category, *args*)

Bases: *sage.categories.subquotients.SubquotientsCategory*

class ParentMethods

Bases: *object*

one()

Returns the multiplicative unit of this monoid, obtained by retracting that of the ambient monoid.

EXAMPLES:

```
sage: S = Monoids().Subquotients().example() # todo: not implemented
sage: S.one() # todo: not implemented
```

class WithRealizations(*category, *args*)

Bases: *sage.categories.with_realizations.WithRealizationsCategory*

class ParentMethods

Bases: *object*

one()

Return the unit of this monoid.

This default implementation returns the unit of the realization of `self` given by `a_realization()`.

EXAMPLES:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.one.__module__
'sage.categories.monoids'
sage: A.one()
F[{}]
```

static free(*index_set=None, names=None, **kws*)

Return a free monoid on n generators or with the generators indexed by a set I .

A free monoid is constructed by specifying either:

- the number of generators and/or the names of the generators
- the indexing set for the generators

INPUT:

- `index_set` – (optional) an index set for the generators; if an integer, then this represents $\{0, 1, \dots, n-1\}$
- `names` – a string or list/tuple/iterable of strings (default: `'x'`); the generator names or name prefix

EXAMPLES:

```
sage: Monoids.free(index_set=ZZ)
Free monoid indexed by Integer Ring
sage: Monoids().free(ZZ)
Free monoid indexed by Integer Ring
sage: F.<x,y,z> = Monoids().free(); F
Free monoid indexed by {'x', 'y', 'z'}
```

3.122 Number fields

class `sage.categories.number_fields.NumberFields`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of number fields.

EXAMPLES:

We create the category of number fields:

```
sage: C = NumberFields()
sage: C
Category of number fields
```

By definition, it is infinite:

```
sage: NumberFields().Infinite() is NumberFields()
True
```

Notice that the rational numbers \mathbb{Q} are considered as an object in this category:

```
sage: RationalField() in C
True
```

However, we can define a degree 1 extension of \mathbb{Q} , which is of course also in this category:

```
sage: x = PolynomialRing(RationalField(), 'x').gen()
sage: K = NumberField(x - 1, 'a'); K
Number Field in a with defining polynomial x - 1
sage: K in C
True
```

Number fields all lie in this category, regardless of the name of the variable:

```
sage: K = NumberField(x^2 + 1, 'a')
sage: K in C
True
```

class ElementMethods

Bases: object

class ParentMethods

Bases: object

zeta_function(*prec=53, max_imaginary_part=0, max_asymp_coeffs=40, algorithm='pari'*)

Return the Dedekind zeta function of this number field.

Actually, this returns an interface for computing with the Dedekind zeta function $\zeta_F(s)$ of the number field F .

INPUT:

- *prec* – optional integer (default 53) bits precision
- *max_imaginary_part* – optional real number (default 0)
- *max_asymp_coeffs* – optional integer (default 40)
- *algorithm* – optional (default “pari”) either “gp” or “pari”

OUTPUT: The zeta function of this number field.

If algorithm is “gp”, this returns an interface to Tim Dokchitser’s gp script for computing with L-functions.

If algorithm is “pari”, this returns instead an interface to Pari’s own general implementation of L-functions.

EXAMPLES:

```
sage: K.<a> = NumberField(ZZ['x'].0^2+ZZ['x'].0-1)
sage: Z = K.zeta_function(); Z
PARI zeta function associated to Number Field in a with defining polynomial
↪ x^2 + x - 1
sage: Z(-1)
0.03333333333333333
sage: L.<a, b, c> = NumberField([x^2 - 5, x^2 + 3, x^2 + 1])
sage: Z = L.zeta_function()
sage: Z(5)
1.00199015670185
```

Using the algorithm “pari”:

```

sage: K.<a> = NumberField(ZZ['x'].0^2+ZZ['x'].0-1)
sage: Z = K.zeta_function(algorithm="pari")
sage: Z(-1)
0.03333333333333333
sage: L.<a, b, c> = NumberField([x^2 - 5, x^2 + 3, x^2 + 1])
sage: Z = L.zeta_function(algorithm="pari")
sage: Z(5)
1.00199015670185

```

super_categories()

EXAMPLES:

```

sage: NumberFields().super_categories()
[Category of infinite fields]

```

3.123 Objects

class sage.categories.objects.**Objects**(*s=None*)

Bases: *sage.categories.category_singleton.Category_singleton*

The category of all objects the basic category

EXAMPLES:

```

sage: Objects()
Category of objects
sage: Objects().super_categories()
[]

```

class ParentMethods

Bases: object

Methods for all category objects

class SubcategoryMethods

Bases: object

Endsets()

Return the category of endsets between objects of this category.

EXAMPLES:

```

sage: Sets().Endsets()
Category of endsets of sets

sage: Rings().Endsets()
Category of endsets of unital magmas and additive unital additive magmas

```

See also:

- *Homsets()*

Homsets()

Return the category of homsets between objects of this category.

EXAMPLES:


```
sage: Sets().Homsets()
Category of homsets of sets
```

```
sage: Rings().Homsets()
Category of homsets of unital magmas and additive unital additive magmas
```

Note: Background

Information, code, documentation, and tests about the category of homsets of a category `Cs` should go in the nested class `Cs.Homsets`. They will then be made available to homsets of any subcategory of `Cs`.

Assume, for example, that homsets of `Cs` are `Cs` themselves. This information can be implemented in the method `Cs.Homsets.extra_super_categories` to make `Cs.Homsets()` a subcategory of `Cs()`.

Methods about the homsets themselves should go in the nested class `Cs.Homsets.ParentMethods`.

Methods about the morphisms can go in the nested class `Cs.Homsets.ElementMethods`. However it's generally preferable to put them in the nested class `Cs.MorphimMethods`; indeed they will then apply to morphisms of all subcategories of `Cs`, and not only full subcategories.

See also:

`FunctorialConstruction`

Todo:

- Design a mechanism to specify that an axiom is compatible with taking subsets. Examples: `Finite`, `Associative`, `Commutative` (when meaningful), but not `Infinite` nor `Unital`.
- Design a mechanism to specify that, when B is a subcategory of A , a B -homset is a subset of the corresponding A homset. And use it to recover all the relevant axioms from homsets in super categories.
- For instances of redundant code due to this missing feature, see:
 - `AdditiveMonoids.Homsets.extra_super_categories()`
 - `HomsetsCategory.extra_super_categories()` (slightly different nature)
 - plus plenty of spots where this is not implemented.

additional_structure()

Return None

Indeed, by convention, the category of objects defines no additional structure.

See also:

[Category.additional_structure\(\)](#)

EXAMPLES:

```
sage: Objects().additional_structure()
```

super_categories()

EXAMPLES:

```
sage: Objects().super_categories()
[]
```

3.124 Partially ordered monoids

class `sage.categories.partially_ordered_monoids.PartiallyOrderedMonoids`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of partially ordered monoids, that is partially ordered sets which are also monoids, and such that multiplication preserves the ordering: $x \leq y$ implies $x * z < y * z$ and $z * x < z * y$.

See [Wikipedia article Ordered_monoid](#)

EXAMPLES:

```
sage: PartiallyOrderedMonoids()
Category of partially ordered monoids
sage: PartiallyOrderedMonoids().super_categories()
[Category of posets, Category of monoids]
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

super_categories()

EXAMPLES:

```
sage: PartiallyOrderedMonoids().super_categories()
[Category of posets, Category of monoids]
```

3.125 Permutation groups

class `sage.categories.permutation_groups.PermutationGroups`(*s=None*)

Bases: `sage.categories.category.Category`

The category of permutation groups.

A *permutation group* is a group whose elements are concretely represented by permutations of some set. In other words, the group comes endowed with a distinguished action on some set.

This distinguished action should be preserved by permutation group morphisms. For details, see [Wikipedia article Permutation_group#Permutation_isomorphic_groups](#).

Todo: shall we accept only permutations with finite support or not?

EXAMPLES:

```
sage: PermutationGroups()
Category of permutation groups
sage: PermutationGroups().super_categories()
[Category of groups]
```

The category of permutation groups defines additional structure that should be preserved by morphisms, namely the distinguished action:

```
sage: PermutationGroups().additional_structure()
Category of permutation groups
```

Finite

alias of `sage.categories.finite_permutation_groups.FinitePermutationGroups`

super_categories()

Return a list of the immediate super categories of self.

EXAMPLES:

```
sage: PermutationGroups().super_categories()
[Category of groups]
```

3.126 Pointed sets

```
class sage.categories.pointed_sets.PointedSets(s=None)
```

Bases: `sage.categories.category_singleton.Category_singleton`

The category of pointed sets.

EXAMPLES:

```
sage: PointedSets()
Category of pointed sets
```

super_categories()

EXAMPLES:

```
sage: PointedSets().super_categories()
[Category of sets]
```

3.127 Polyhedral subsets of free ZZ, QQ or RR-modules.

```
class sage.categories.polyhedra.PolyhedralSets(R)
```

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of polyhedra over a ring.

EXAMPLES:

We create the category of polyhedra over \mathbb{Q} :

```
sage: PolyhedralSets(QQ)
Category of polyhedral sets over Rational Field
```

super_categories()

EXAMPLES:

```
sage: PolyhedralSets(QQ).super_categories()
[Category of commutative magmas, Category of additive monoids]
```

3.128 Posets

class `sage.categories.posets.Posets`(*s=None*)

Bases: `sage.categories.category.Category`

The category of posets i.e. sets with a partial order structure.

EXAMPLES:

```
sage: Posets()
Category of posets
sage: Posets().super_categories()
[Category of sets]
sage: P = Posets().example(); P
An example of a poset: sets ordered by inclusion
```

The partial order is implemented by the mandatory method `le()`:

```
sage: x = P(Set([1,3])); y = P(Set([1,2,3]))
sage: x, y
({1, 3}, {1, 2, 3})
sage: P.le(x, y)
True
sage: P.le(x, x)
True
sage: P.le(y, x)
False
```

The other comparison methods are called `lt()`, `ge()`, `gt()`, following Python's naming convention in `operator`. Default implementations are provided:

```
sage: P.lt(x, x)
False
sage: P.ge(y, x)
True
```

Unless the poset is a facade (see `Sets.Facade`), one can compare directly its elements using the usual Python operators:

```
sage: D = Poset((divisors(30), attrcall("divides")), facade = False)
sage: D(3) <= D(6)
True
sage: D(3) <= D(3)
True
sage: D(3) <= D(5)
False
sage: D(3) < D(3)
False
sage: D(10) >= D(5)
True
```

At this point, this has to be implemented by hand. Once [trac ticket #10130](#) will be resolved, this will be automatically provided by this category:

```

sage: x < y      # todo: not implemented
True
sage: x < x      # todo: not implemented
False
sage: x <= x     # todo: not implemented
True
sage: y >= x     # todo: not implemented
True

```

See also:

`Poset()`, `FinitePosets`, `LatticePosets`

class ElementMethods

Bases: object

Finite

alias of `sage.categories.finite_posets.FinitePosets`

class ParentMethods

Bases: object

CartesianProduct

alias of `sage.combinat.posets.cartesian_product.CartesianProductPoset`

directed_subset(*elements*, *direction*)

Return the order filter or the order ideal generated by a list of elements.

If *direction* is 'up', the order filter (upper set) is being returned.

If *direction* is 'down', the order ideal (lower set) is being returned.

INPUT:

- *elements* – a list of elements.
- *direction* – 'up' or 'down'.

EXAMPLES:

```

sage: B = posets.BooleanLattice(4)
sage: B.directed_subset([3, 8], 'up')
[3, 7, 8, 9, 10, 11, 12, 13, 14, 15]
sage: B.directed_subset([7, 10], 'down')
[0, 1, 2, 3, 4, 5, 6, 7, 8, 10]

```

ge(*x*, *y*)

Return whether $x \geq y$ in the poset `self`.

INPUT:

- *x*, *y* – elements of `self`.

This default implementation delegates the work to `le()`.

EXAMPLES:

```

sage: D = Poset((divisors(30), attrcall("divides")))
sage: D.ge( 6, 3 )
True
sage: D.ge( 3, 3 )
True
sage: D.ge( 3, 5 )
False

```

gt(x, y)Return whether $x > y$ in the poset self.

INPUT:

- x, y – elements of self.

This default implementation delegates the work to `lt()`.

EXAMPLES:

```
sage: D = Poset((divisors(30), attrcall("divides")))
sage: D.gt( 3, 6 )
False
sage: D.gt( 3, 3 )
False
sage: D.gt( 3, 5 )
False
```

is_antichain_of_poset(o)Return whether an iterable o is an antichain of self.

INPUT:

- o – an iterable (e. g., list, set, or tuple) containing some elements of self

OUTPUT:

True if the subset of self consisting of the entries of o is an antichain of self, and False otherwise.

EXAMPLES:

```
sage: P = Poset((divisors(12), attrcall("divides")), facade=True, linear_
↪extension=True)
sage: sorted(P.list())
[1, 2, 3, 4, 6, 12]
sage: P.is_antichain_of_poset([1, 3])
False
sage: P.is_antichain_of_poset([3, 1])
False
sage: P.is_antichain_of_poset([1, 1, 3])
False
sage: P.is_antichain_of_poset([])
True
sage: P.is_antichain_of_poset([1])
True
sage: P.is_antichain_of_poset([1, 1])
True
sage: P.is_antichain_of_poset([3, 4])
True
sage: P.is_antichain_of_poset([3, 4, 12])
False
sage: P.is_antichain_of_poset([6, 4])
True
sage: P.is_antichain_of_poset(i for i in divisors(12) if (2 < i and i < 6))
True
sage: P.is_antichain_of_poset(i for i in divisors(12) if (2 <= i and i < 6))
False

sage: Q = Poset({2: [3, 1], 3: [4], 1: [4]})
```

(continues on next page)

(continued from previous page)

```

sage: Q.is_antichain_of_poset((1, 2))
False
sage: Q.is_antichain_of_poset((2, 4))
False
sage: Q.is_antichain_of_poset((4, 2))
False
sage: Q.is_antichain_of_poset((2, 2))
True
sage: Q.is_antichain_of_poset((3, 4))
False
sage: Q.is_antichain_of_poset((3, 1))
True
sage: Q.is_antichain_of_poset((1, ))
True
sage: Q.is_antichain_of_poset(())
True

```

An infinite poset:

```

sage: from sage.categories.examples.posets import FiniteSetsOrderedByInclusion
sage: R = FiniteSetsOrderedByInclusion()
sage: R.is_antichain_of_poset([R(set([3, 1, 2])), R(set([1, 4])), R(set([4, 5]))])
True
sage: R.is_antichain_of_poset([R(set([3, 1, 2, 4])), R(set([1, 4])), R(set([4, 5]))])])
False

```

is_chain_of_poset(*o*, *ordered=False*)

Return whether an iterable *o* is a chain of *self*, including a check for *o* being ordered from smallest to largest element if the keyword *ordered* is set to *True*.

INPUT:

- *o* – an iterable (e. g., list, set, or tuple) containing some elements of *self*
- *ordered* – a Boolean (default: *False*) which decides whether the notion of a chain includes being ordered

OUTPUT:

If *ordered* is set to *False*, the truth value of the following assertion is returned: The subset of *self* formed by the elements of *o* is a chain in *self*.

If *ordered* is set to *True*, the truth value of the following assertion is returned: Every element of the list *o* is (strictly!) smaller than its successor in *self*. (This makes no sense if *ordered* is a set.)

EXAMPLES:

```

sage: P = Poset((divisors(12), attrcall("divides")), facade=True, linear_
↳ extension=True)
sage: sorted(P.list())
[1, 2, 3, 4, 6, 12]
sage: P.is_chain_of_poset([1, 3])
True
sage: P.is_chain_of_poset([3, 1])

```

(continues on next page)

(continued from previous page)

```

True
sage: P.is_chain_of_poset([1, 3], ordered=True)
True
sage: P.is_chain_of_poset([3, 1], ordered=True)
False
sage: P.is_chain_of_poset([])
True
sage: P.is_chain_of_poset([], ordered=True)
True
sage: P.is_chain_of_poset((2, 12, 6))
True
sage: P.is_chain_of_poset((2, 6, 12), ordered=True)
True
sage: P.is_chain_of_poset((2, 12, 6), ordered=True)
False
sage: P.is_chain_of_poset((2, 12, 6, 3))
False
sage: P.is_chain_of_poset((2, 3))
False

sage: Q = Poset({2: [3, 1], 3: [4], 1: [4]})
sage: Q.is_chain_of_poset([1, 2], ordered=True)
False
sage: Q.is_chain_of_poset([1, 2])
True
sage: Q.is_chain_of_poset([2, 1], ordered=True)
True
sage: Q.is_chain_of_poset([2, 1, 1], ordered=True)
False
sage: Q.is_chain_of_poset([3])
True
sage: Q.is_chain_of_poset([4, 2, 3])
True
sage: Q.is_chain_of_poset([4, 2, 3], ordered=True)
False
sage: Q.is_chain_of_poset([2, 3, 4], ordered=True)
True

```

Examples with infinite posets:

```

sage: from sage.categories.examples.posets import _
↳ FiniteSetsOrderedByInclusion
sage: R = FiniteSetsOrderedByInclusion()
sage: R.is_chain_of_poset([R(set([3, 1, 2])), R(set([1, 4])), R(set([4, _
↳ 5]))])
False
sage: R.is_chain_of_poset([R(set([3, 1, 2])), R(set([1, 2])), R(set([1]))], _
↳ ordered=True)
False
sage: R.is_chain_of_poset([R(set([3, 1, 2])), R(set([1, 2])), R(set([1]))])
True

```

(continues on next page)

(continued from previous page)

```

sage: from sage.categories.examples.posets import
↳PositiveIntegersOrderedByDivisibilityFacade
sage: T = PositiveIntegersOrderedByDivisibilityFacade()
sage: T.is_chain_of_poset((T(3), T(4), T(7)))
False
sage: T.is_chain_of_poset((T(3), T(6), T(3)))
True
sage: T.is_chain_of_poset((T(3), T(6), T(3)), ordered=True)
False
sage: T.is_chain_of_poset((T(3), T(3), T(6)))
True
sage: T.is_chain_of_poset((T(3), T(3), T(6)), ordered=True)
False
sage: T.is_chain_of_poset((T(3), T(6)), ordered=True)
True
sage: T.is_chain_of_poset((), ordered=True)
True
sage: T.is_chain_of_poset((T(3),), ordered=True)
True
sage: T.is_chain_of_poset((T(q) for q in divisors(27)))
True
sage: T.is_chain_of_poset((T(q) for q in divisors(18)))
False

```

is_order_filter(*o*)

Return whether *o* is an order filter of *self*, assuming *self* has no infinite ascending path.

INPUT:

- *o* – a list (or set, or tuple) containing some elements of *self*

EXAMPLES:

```

sage: P = Poset((divisors(12), attrcall("divides")), facade=True, linear_
↳extension=True)
sage: sorted(P.list())
[1, 2, 3, 4, 6, 12]
sage: P.is_order_filter([4, 12])
True
sage: P.is_order_filter([])
True
sage: P.is_order_filter({3, 4, 12})
False
sage: P.is_order_filter({3, 6, 12})
True

```

is_order_ideal(*o*)

Return whether *o* is an order ideal of *self*, assuming *self* has no infinite descending path.

INPUT:

- *o* – a list (or set, or tuple) containing some elements of *self*

EXAMPLES:

```

sage: P = Poset((divisors(12), attrcall("divides")), facade=True, linear_
↳extension=True)

```

(continues on next page)

(continued from previous page)

```

sage: sorted(P.list())
[1, 2, 3, 4, 6, 12]
sage: P.is_order_ideal([1, 3])
True
sage: P.is_order_ideal([])
True
sage: P.is_order_ideal({1, 3})
True
sage: P.is_order_ideal([1, 3, 4])
False

```

le(x, y)Return whether $x \leq y$ in the poset self.

INPUT:

- x, y – elements of self.

EXAMPLES:

```

sage: D = Poset((divisors(30), attrcall("divides")))
sage: D.le( 3, 6 )
True
sage: D.le( 3, 3 )
True
sage: D.le( 3, 5 )
False

```

lower_covers(x)Return the lower covers of x , that is, the elements y such that $y < x$ and there exists no z such that $y < z < x$.

EXAMPLES:

```

sage: D = Poset((divisors(30), attrcall("divides")))
sage: D.lower_covers(15)
[3, 5]

```

lt(x, y)Return whether $x < y$ in the poset self.

INPUT:

- x, y – elements of self.

This default implementation delegates the work to `le()`.

EXAMPLES:

```

sage: D = Poset((divisors(30), attrcall("divides")))
sage: D.lt( 3, 6 )
True
sage: D.lt( 3, 3 )
False
sage: D.lt( 3, 5 )
False

```

order_filter($elements$)

Return the order filter generated by a list of elements.

A subset I of a poset is said to be an order filter if, for any x in I and y such that $y \geq x$, then y is in I . This is also called the upper set generated by these elements.

EXAMPLES:

```
sage: B = posets.BooleanLattice(4)
sage: B.order_filter([3,8])
[3, 7, 8, 9, 10, 11, 12, 13, 14, 15]
```

order_ideal(*elements*)

Return the order ideal in `self` generated by the elements of an iterable `elements`.

A subset I of a poset is said to be an order ideal if, for any x in I and y such that $y \leq x$, then y is in I .

This is also called the lower set generated by these elements.

EXAMPLES:

```
sage: B = posets.BooleanLattice(4)
sage: B.order_ideal([7,10])
[0, 1, 2, 3, 4, 5, 6, 7, 8, 10]
```

order_ideal_toggle(I, v)

Return the result of toggling the element v in the order ideal I .

If v is an element of a poset P , then toggling the element v is an automorphism of the set $J(P)$ of all order ideals of P . It is defined as follows: If I is an order ideal of P , then the image of I under toggling the element v is

- the set $I \cup \{v\}$, if $v \notin I$ but every element of P smaller than v is in I ;
- the set $I \setminus \{v\}$, if $v \in I$ but no element of P greater than v is in I ;
- I otherwise.

This image always is an order ideal of P .

EXAMPLES:

```
sage: P = Poset({1: [2,3], 2: [4], 3: []})
sage: I = Set({1, 2})
sage: I in P.order_ideals_lattice()
True
sage: P.order_ideal_toggle(I, 1)
{1, 2}
sage: P.order_ideal_toggle(I, 2)
{1}
sage: P.order_ideal_toggle(I, 3)
{1, 2, 3}
sage: P.order_ideal_toggle(I, 4)
{1, 2, 4}
sage: P4 = Posets(4)
sage: all(all(all(P.order_ideal_toggle(P.order_ideal_toggle(I, i), i) == I
.....:         for i in range(4))
.....:         for I in P.order_ideals_lattice(facade=True))
.....:         for P in P4)
True
```

order_ideal_toggles(I, vs)

Return the result of toggling the elements of the list (or iterable) `vs` (one by one, from left to right) in the order ideal I .

See `order_ideal_toggle()` for a definition of toggling.

EXAMPLES:

```
sage: P = Poset({1: [2,3], 2: [4], 3: []})
sage: I = Set({1, 2})
sage: P.order_ideal_toggles(I, [1,2,3,4])
{1, 3}
sage: P.order_ideal_toggles(I, (1,2,3,4))
{1, 3}
```

principal_lower_set(x)

Return the order ideal generated by an element x .

This is also called the lower set generated by this element.

EXAMPLES:

```
sage: B = posets.BooleanLattice(4)
sage: B.principal_order_ideal(6)
[0, 2, 4, 6]
```

principal_order_filter(x)

Return the order filter generated by an element x .

This is also called the upper set generated by this element.

EXAMPLES:

```
sage: B = posets.BooleanLattice(4)
sage: B.principal_order_filter(2)
[2, 3, 6, 7, 10, 11, 14, 15]
```

principal_order_ideal(x)

Return the order ideal generated by an element x .

This is also called the lower set generated by this element.

EXAMPLES:

```
sage: B = posets.BooleanLattice(4)
sage: B.principal_order_ideal(6)
[0, 2, 4, 6]
```

principal_upper_set(x)

Return the order filter generated by an element x .

This is also called the upper set generated by this element.

EXAMPLES:

```
sage: B = posets.BooleanLattice(4)
sage: B.principal_order_filter(2)
[2, 3, 6, 7, 10, 11, 14, 15]
```

upper_covers(x)

Return the upper covers of x , that is, the elements y such that $x < y$ and there exists no z such that $x < z < y$.

EXAMPLES:

```
sage: D = Poset((divisors(30), attrcall("divides")))
sage: D.upper_covers(3)
[6, 15]
```

example(*choice=None*)

Return examples of objects of `Posets()`, as per *Category.example()*.

EXAMPLES:

```
sage: Posets().example()
An example of a poset: sets ordered by inclusion

sage: Posets().example("facade")
An example of a facade poset: the positive integers ordered by divisibility
```

super_categories()

Return a list of the (immediate) super categories of `self`, as per *Category.super_categories()*.

EXAMPLES:

```
sage: Posets().super_categories()
[Category of sets]
```

3.129 Principal ideal domains

class `sage.categories.principal_ideal_domains.PrincipalIdealDomains`(*s=None*)

Bases: *sage.categories.category_singleton.Category_singleton*

The category of (constructive) principal ideal domains

By constructive, we mean that a single generator can be constructively found for any ideal given by a finite set of generators. Note that this constructive definition only implies that finitely generated ideals are principal. It is not clear what we would mean by an infinitely generated ideal.

EXAMPLES:

```
sage: PrincipalIdealDomains()
Category of principal ideal domains
sage: PrincipalIdealDomains().super_categories()
[Category of unique factorization domains]
```

See also [Wikipedia article Principal_ideal_domain](#)

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

additional_structure()

Return `None`.

Indeed, the category of principal ideal domains defines no additional structure: a ring morphism between two principal ideal domains is a principal ideal domain morphism.

EXAMPLES:

```
sage: PrincipalIdealDomains().additional_structure()
```

super_categories()

EXAMPLES:

```
sage: PrincipalIdealDomains().super_categories()
[Category of unique factorization domains]
```

3.130 Quotient fields

class sage.categories.quotient_fields.**QuotientFields**(*s=None*)

Bases: *sage.categories.category_singleton.Category_singleton*

The category of quotient fields over an integral domain

EXAMPLES:

```
sage: QuotientFields()
Category of quotient fields
sage: QuotientFields().super_categories()
[Category of fields]
```

class **ElementMethods**

Bases: object

denominator()

Constructor for abstract methods

EXAMPLES:

```
sage: def f(x):
.....:     "doc of f"
.....:     return 1
sage: x = abstract_method(f); x
<abstract method f at ...>
sage: x.__doc__
'doc of f'
sage: x.__name__
'f'
sage: x.__module__
'__main__'
```

derivative(*args)

The derivative of this rational function, with respect to variables supplied in args.

Multiple variables and iteration counts may be supplied; see documentation for the global derivative() function for more details.

See also:

`_derivative()`

EXAMPLES:

```
sage: F.<x> = Frac(QQ['x'])
sage: (1/x).derivative()
-1/x^2
```

```
sage: (x+1/x).derivative(x, 2)
2/x^3
```

```
sage: F.<x,y> = Frac(QQ['x,y'])
sage: (1/(x+y)).derivative(x,y)
2/(x^3 + 3*x^2*y + 3*x*y^2 + y^3)
```

factor(*args, **kws)

Return the factorization of `self` over the base ring.

INPUT:

- `*args` - Arbitrary arguments suitable over the base ring
- `**kws` - Arbitrary keyword arguments suitable over the base ring

OUTPUT:

- Factorization of `self` over the base ring

EXAMPLES:

```
sage: K.<x> = QQ[]
sage: f = (x^3+x)/(x-3)
sage: f.factor()
(x - 3)^-1 * x * (x^2 + 1)
```

Here is an example to show that [trac ticket #7868](#) has been resolved:

```
sage: R.<x,y> = GF(2)[]
sage: f = x*y/(x+y)
sage: f.factor()
(x + y)^-1 * y * x
```

gcd(other)

Greatest common divisor

Note: In a field, the greatest common divisor is not very informative, as it is only determined up to a unit. But in the fraction field of an integral domain that provides both `gcd` and `lcm`, it is possible to be a bit more specific and define the `gcd` uniquely up to a unit of the base ring (rather than in the fraction field).

AUTHOR:

- Simon King (2011-02): See [trac ticket #10771](#)

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: p = (1+x)^3*(1+2*x^2)/(1-x^5)
sage: q = (1+x)^2*(1+3*x^2)/(1-x^4)
sage: factor(p)
(-2) * (x - 1)^-1 * (x + 1)^3 * (x^2 + 1/2) * (x^4 + x^3 + x^2 + x + 1)^-1
sage: factor(q)
(-3) * (x - 1)^-1 * (x + 1) * (x^2 + 1)^-1 * (x^2 + 1/3)
```

(continues on next page)

(continued from previous page)

```

sage: gcd(p,q)
(x + 1)/(x^7 + x^5 - x^2 - 1)
sage: factor(gcd(p,q))
(x - 1)^-1 * (x + 1) * (x^2 + 1)^-1 * (x^4 + x^3 + x^2 + x + 1)^-1
sage: factor(gcd(p,1+x))
(x - 1)^-1 * (x + 1) * (x^4 + x^3 + x^2 + x + 1)^-1
sage: factor(gcd(1+x,q))
(x - 1)^-1 * (x + 1) * (x^2 + 1)^-1

```

lcm(*other*)

Least common multiple

In a field, the least common multiple is not very informative, as it is only determined up to a unit. But in the fraction field of an integral domain that provides both gcd and lcm, it is reasonable to be a bit more specific and to define the least common multiple so that it restricts to the usual least common multiple in the base ring and is unique up to a unit of the base ring (rather than up to a unit of the fraction field).

The least common multiple is easily described in terms of the prime decomposition. A rational number can be written as a product of primes with integer (positive or negative) powers in a unique way. The least common multiple of two rational numbers x and y can then be defined by specifying that the exponent of every prime p in $\text{lcm}(x, y)$ is the supremum of the exponents of p in x , and the exponent of p in y (where the primes that does not appear in the decomposition of x or y are considered to have exponent zero).

AUTHOR:

- Simon King (2011-02): See [trac ticket #10771](#)

EXAMPLES:

```

sage: lcm(2/3, 1/5)
2

```

Indeed $2/3 = 2^1 3^{-1} 5^0$ and $1/5 = 2^0 3^0 5^{-1}$, so $\text{lcm}(2/3, 1/5) = 2^1 3^0 5^0 = 2$.

```
sage: lcm(1/3, 1/5) 1 sage: lcm(1/3, 1/6) 1/3
```

Some more involved examples:

```

sage: R.<x> = QQ[]
sage: p = (1+x)^3*(1+2*x^2)/(1-x^5)
sage: q = (1+x)^2*(1+3*x^2)/(1-x^4)
sage: factor(p)
(-2) * (x - 1)^-1 * (x + 1)^3 * (x^2 + 1/2) * (x^4 + x^3 + x^2 + x + 1)^-1
sage: factor(q)
(-3) * (x - 1)^-1 * (x + 1) * (x^2 + 1)^-1 * (x^2 + 1/3)
sage: factor(lcm(p,q))
(x - 1)^-1 * (x + 1)^3 * (x^2 + 1/3) * (x^2 + 1/2)
sage: factor(lcm(p,1+x))
(x + 1)^3 * (x^2 + 1/2)
sage: factor(lcm(1+x,q))
(x + 1) * (x^2 + 1/3)

```

numerator()

Constructor for abstract methods

EXAMPLES:


```

sage: def f(x):
.....:     "doc of f"
.....:     return 1
sage: x = abstract_method(f); x
<abstract method f at ...>
sage: x.__doc__
'doc of f'
sage: x.__name__
'f'
sage: x.__module__
'__main__'

```

`partial_fraction_decomposition`(*decompose_powers=True*)

Decomposes fraction field element into a whole part and a list of fraction field elements over prime power denominators.

The sum will be equal to the original fraction.

INPUT:

- **decompose_powers** – whether to decompose prime power denominators as opposed to having a single term for each irreducible factor of the denominator (default: True)

OUTPUT:

- Partial fraction decomposition of self over the base ring.

AUTHORS:

- Robert Bradshaw (2007-05-31)

EXAMPLES:

```

sage: S.<t> = QQ[]
sage: q = 1/(t+1) + 2/(t+2) + 3/(t-3); q
(6*t^2 + 4*t - 6)/(t^3 - 7*t - 6)
sage: whole, parts = q.partial_fraction_decomposition(); parts
[3/(t - 3), 1/(t + 1), 2/(t + 2)]
sage: sum(parts) == q
True
sage: q = 1/(t^3+1) + 2/(t^2+2) + 3/(t-3)^5
sage: whole, parts = q.partial_fraction_decomposition(); parts
[1/3/(t + 1), 3/(t^5 - 15*t^4 + 90*t^3 - 270*t^2 + 405*t - 243), (-1/3*t +
↪ 2/3)/(t^2 - t + 1), 2/(t^2 + 2)]
sage: sum(parts) == q
True
sage: q = 2*t / (t + 3)^2
sage: q.partial_fraction_decomposition()
(0, [2/(t + 3), -6/(t^2 + 6*t + 9)])
sage: for p in q.partial_fraction_decomposition()[1]: print(p.factor())
(2) * (t + 3)^-1
(-6) * (t + 3)^-2
sage: q.partial_fraction_decomposition(decompose_powers=False)
(0, [2*t/(t^2 + 6*t + 9)])

```

We can decompose over a given algebraic extension:

```

sage: R.<x> = QQ[sqrt(2)][]
sage: r = 1/(x^4+1)
sage: r.partial_fraction_decomposition()

```

(continues on next page)

(continued from previous page)

```
(0,
 [(-1/4*sqrt(2)*x + 1/2)/(x^2 - sqrt(2)*x + 1),
 (1/4*sqrt(2)*x + 1/2)/(x^2 + sqrt(2)*x + 1)])

sage: R.<x> = QQ[I][] # of QQ[sqrt(-1)]
sage: r = 1/(x^4+1)
sage: r.partial_fraction_decomposition()
(0, [(-1/2*I)/(x^2 - I), 1/2*I/(x^2 + I)])
```

We can also ask Sage to find the least extension where the denominator factors in linear terms:

```
sage: R.<x> = QQ[]
sage: r = 1/(x^4+2)
sage: N = r.denominator().splitting_field('a')
sage: N
Number Field in a with defining polynomial x^8 - 8*x^6 + 28*x^4 + 16*x^2 + 2
↪36
sage: R1.<x1>=N[]
sage: r1 = 1/(x1^4+2)
sage: r1.partial_fraction_decomposition()
(0,
 [(-1/224*a^6 + 13/448*a^4 - 5/56*a^2 - 25/224)/(x1 - 1/28*a^6 + 13/56*a^4 -
↪ 5/7*a^2 - 25/28),
 (1/224*a^6 - 13/448*a^4 + 5/56*a^2 + 25/224)/(x1 + 1/28*a^6 - 13/56*a^4 +
↪ 5/7*a^2 + 25/28),
 (-5/1344*a^7 + 43/1344*a^5 - 85/672*a^3 - 31/672*a)/(x1 - 5/168*a^7 + 43/
↪ 168*a^5 - 85/84*a^3 - 31/84*a),
 (5/1344*a^7 - 43/1344*a^5 + 85/672*a^3 + 31/672*a)/(x1 + 5/168*a^7 - 43/
↪ 168*a^5 + 85/84*a^3 + 31/84*a)])
```

Or we may work directly over an algebraically closed field:

```
sage: R.<x> = QQbar[]
sage: r = 1/(x^4+1)
sage: r.partial_fraction_decomposition()
(0,
 [(-0.1767766952966369? - 0.1767766952966369?*I)/(x - 0.7071067811865475? -
↪ 0.7071067811865475?*I),
 (-0.1767766952966369? + 0.1767766952966369?*I)/(x - 0.7071067811865475? +
↪ 0.7071067811865475?*I),
 (0.1767766952966369? - 0.1767766952966369?*I)/(x + 0.7071067811865475? -
↪ 0.7071067811865475?*I),
 (0.1767766952966369? + 0.1767766952966369?*I)/(x + 0.7071067811865475? +
↪ 0.7071067811865475?*I)])
```

We do the best we can over inexact fields:

```
sage: R.<x> = RealField(20)[]
sage: q = 1/(x^2 + x + 2)^2 + 1/(x-1); q
(x^4 + 2.0000*x^3 + 5.0000*x^2 + 5.0000*x + 3.0000)/(x^5 + x^4 + 3.0000*x^3
↪ - x^2 - 4.0000)
sage: whole, parts = q.partial_fraction_decomposition(); parts
[1.0000/(x - 1.0000), 1.0000/(x^4 + 2.0000*x^3 + 5.0000*x^2 + 4.0000*x + 4.
↪ 0000)]
```

(continues on next page)

(continued from previous page)

```
sage: sum(parts)
(x^4 + 2.0000*x^3 + 5.0000*x^2 + 5.0000*x + 3.0000)/(x^5 + x^4 + 3.0000*x^3
↪ - x^2 - 4.0000)
```

xgcd(other)

Return a triple (g, s, t) of elements of that field such that g is the greatest common divisor of self and other and $g = s*\text{self} + t*\text{other}$.

Note: In a field, the greatest common divisor is not very informative, as it is only determined up to a unit. But in the fraction field of an integral domain that provides both xgcd and lcm, it is possible to be a bit more specific and define the gcd uniquely up to a unit of the base ring (rather than in the fraction field).

EXAMPLES:

```
sage: QQ(3).xgcd(QQ(2))
(1, 1, -1)
sage: QQ(3).xgcd(QQ(1/2))
(1/2, 0, 1)
sage: QQ(1/3).xgcd(QQ(2))
(1/3, 1, 0)
sage: QQ(3/2).xgcd(QQ(5/2))
(1/2, 2, -1)

sage: R.<x> = QQ['x']
sage: p = (1+x)^3*(1+2*x^2)/(1-x^5)
sage: q = (1+x)^2*(1+3*x^2)/(1-x^4)
sage: factor(p)
(-2) * (x - 1)^-1 * (x + 1)^3 * (x^2 + 1/2) * (x^4 + x^3 + x^2 + x + 1)^-1
sage: factor(q)
(-3) * (x - 1)^-1 * (x + 1) * (x^2 + 1)^-1 * (x^2 + 1/3)
sage: g,s,t = xgcd(p,q)
sage: g
(x + 1)/(x^7 + x^5 - x^2 - 1)
sage: g == s*p + t*q
True
```

An example without a well defined gcd or xgcd on its base ring:

```
sage: K = QuadraticField(5)
sage: O = K.maximal_order()
sage: R = PolynomialRing(O, 'x')
sage: F = R.fraction_field()
sage: x = F.gen(0)
sage: x.gcd(x+1)
1
sage: x.xgcd(x+1)
(1, 1/x, 0)
sage: zero = F.zero()
sage: zero.gcd(x)
1
```

(continues on next page)

(continued from previous page)

```
sage: zero.xgcd(x)
(1, 0, 1/x)
sage: zero.xgcd(zero)
(0, 0, 0)
```

class ParentMethods

Bases: object

super_categories()

EXAMPLES:

```
sage: QuotientFields().super_categories()
[Category of fields]
```

3.131 Quantum Group Representations

AUTHORS:

- Travis Scrimshaw (2018): initial version

class sage.categories.quantum_group_representations.**QuantumGroupRepresentations**(*base*, *name=None*)

Bases: *sage.categories.category_types.Category_module*

The category of quantum group representations.

class ParentMethods

Bases: object

cartan_type()

Return the Cartan type of self.

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import_
↳ MinusculeRepresentation
sage: C = crystals.Tableaux(['C',4], shape=[1])
sage: R = ZZ['q'].fraction_field()
sage: V = MinusculeRepresentation(R, C)
sage: V.cartan_type()
['C', 4]
```

index_set()

Return the index set of self.

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import_
↳ MinusculeRepresentation
sage: C = crystals.Tableaux(['C',4], shape=[1])
sage: R = ZZ['q'].fraction_field()
sage: V = MinusculeRepresentation(R, C)
sage: V.index_set()
(1, 2, 3, 4)
```

q()Return the quantum parameter q of self.

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import_
↳ MinusculeRepresentation
sage: C = crystals.Tableaux(['C', 4], shape=[1])
sage: R = ZZ['q'].fraction_field()
sage: V = MinusculeRepresentation(R, C)
sage: V.q()
q
```

class TensorProducts(category, *args)Bases: *sage.categories.tensor.TensorProductsCategory*

The category of quantum group representations constructed by tensor product of quantum group representations.

Warning: We use the reversed coproduct in order to match the tensor product rule on crystals.

class ParentMethods

Bases: object

cartan_type()

Return the Cartan type of self.

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import_
↳ MinusculeRepresentation
sage: C = crystals.Tableaux(['C', 2], shape=[1])
sage: R = ZZ['q'].fraction_field()
sage: V = MinusculeRepresentation(R, C)
sage: T = tensor([V, V])
sage: T.cartan_type()
['C', 2]
```

extra_super_categories()

EXAMPLES:

```
sage: from sage.categories.quantum_group_representations import_
↳ QuantumGroupRepresentations
sage: Cat = QuantumGroupRepresentations(ZZ['q'].fraction_field())
sage: Cat.TensorProducts().extra_super_categories()
[Category of quantum group representations over
Fraction Field of Univariate Polynomial Ring in q over Integer Ring]
```

class WithBasis(base_category)Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

The category of quantum group representations with a distinguished basis.

class ElementMethods

Bases: object

$K(i, power=1)$ Return the action of K_i on self to the power power.

INPUT:

- i – an element of the index set
- power – (default: 1) the power of K_i

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import_
      ↪ AdjointRepresentation
sage: K = crystals.KirillovReshetikhin(['D',4,2], 1,1)
sage: R = ZZ['q'].fraction_field()
sage: V = AdjointRepresentation(R, K)
sage: v = V.an_element(); v
2*B[[[]]] + 2*B[[[1]]] + 3*B[[[2]]]
sage: v.K(0)
2*B[[[]]] + 2/q^2*B[[[1]]] + 3*B[[[2]]]
sage: v.K(1)
2*B[[[]]] + 2*q^2*B[[[1]]] + 3/q^2*B[[[2]]]
sage: v.K(1, 2)
2*B[[[]]] + 2*q^4*B[[[1]]] + 3/q^4*B[[[2]]]
sage: v.K(1, -1)
2*B[[[]]] + 2/q^2*B[[[1]]] + 3*q^2*B[[[2]]]
```

 $e(i)$ Return the action of e_i on self.

INPUT:

- i – an element of the index set

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import_
      ↪ AdjointRepresentation
sage: C = crystals.Tableaux(['G',2], shape=[1,1])
sage: R = ZZ['q'].fraction_field()
sage: V = AdjointRepresentation(R, C)
sage: v = V.an_element(); v
2*B[[[1], [2]]] + 2*B[[[1], [3]]] + 3*B[[[2], [3]]]
sage: v.e(1)
((3*q^4+3*q^2+3)/q^2)*B[[[1], [3]]]
sage: v.e(2)
2*B[[[1], [2]]]
```

 $f(i)$ Return the action of f_i on self.

INPUT:

- i – an element of the index set

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import_
      ↪ AdjointRepresentation
sage: K = crystals.KirillovReshetikhin(['D',4,1], 2,1)
sage: R = ZZ['q'].fraction_field()
sage: V = AdjointRepresentation(R, K)
```

(continues on next page)

(continued from previous page)

```

sage: v = V.an_element(); v
2*B[[[]] + 2*B[[[1], [2]]] + 3*B[[[1], [3]]]
sage: v.f(0)
((2*q^2+2)/q)*B[[[1], [2]]]
sage: v.f(1)
3*B[[[2], [3]]]
sage: v.f(2)
2*B[[[1], [3]]]
sage: v.f(3)
3*B[[[1], [4]]]
sage: v.f(4)
3*B[[[1], [-4]]]

```

class ParentMethods

Bases: object

tensor(*factors)Return the tensor product of `self` with the representations factors.

EXAMPLES:

```

sage: from sage.algebras.quantum_groups.representations import
↳      ....: MinusculeRepresentation, AdjointRepresentation
sage: R = ZZ['q'].fraction_field()
sage: CM = crystals.Tableaux(['D',4], shape=[1])
sage: CA = crystals.Tableaux(['D',4], shape=[1,1])
sage: V = MinusculeRepresentation(R, CM)
sage: V.tensor(V, V)
V((1, 0, 0, 0)) # V((1, 0, 0, 0)) # V((1, 0, 0, 0))
sage: A = MinusculeRepresentation(R, CA)
sage: V.tensor(A)
V((1, 0, 0, 0)) # V((1, 1, 0, 0))
sage: B = crystals.Tableaux(['A',2], shape=[1])
sage: W = MinusculeRepresentation(R, B)
sage: tensor([W,V])
Traceback (most recent call last):
...
ValueError: all factors must be of the same Cartan type
sage: tensor([V,A,W])
Traceback (most recent call last):
...
ValueError: all factors must be of the same Cartan type

```

class TensorProducts(category, *args)Bases: `sage.categories.tensor.TensorProductsCategory`

The category of quantum group representations with a distinguished basis constructed by tensor product of quantum group representations with a distinguished basis.

class ParentMethods

Bases: object

K_on_basis(i, b, power=1)Return the action of K_i on the basis element indexed by `b` to the power `power`.

INPUT:

- i – an element of the index set
- b – an element of basis keys
- *power* – (default: 1) the power of K_i

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import \
.....: MinusculeRepresentation, AdjointRepresentation
sage: R = ZZ['q'].fraction_field()
sage: CM = crystals.Tableaux(['A', 2], shape=[1])
sage: VM = MinusculeRepresentation(R, CM)
sage: CA = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: VA = AdjointRepresentation(R, CA)
sage: v = tensor([sum(VM.basis()), VA.module_generator()]); v
B[[[1]]] # B[[[1, 1], [2]]]
+ B[[[2]]] # B[[[1, 1], [2]]]
+ B[[[3]]] # B[[[1, 1], [2]]]
sage: v.K(1) # indirect doctest
q^2*B[[[1]]] # B[[[1, 1], [2]]]
+ B[[[2]]] # B[[[1, 1], [2]]]
+ q*B[[[3]]] # B[[[1, 1], [2]]]
sage: v.K(2, -1) # indirect doctest
1/q*B[[[1]]] # B[[[1, 1], [2]]]
+ 1/q^2*B[[[2]]] # B[[[1, 1], [2]]]
+ B[[[3]]] # B[[[1, 1], [2]]]
```

$e_{\text{on_basis}}(i, b)$

Return the action of e_i on the basis element indexed by b .

INPUT:

- i – an element of the index set
- b – an element of basis keys

EXAMPLES:

```
sage: from sage.algebras.quantum_groups.representations import \
.....: MinusculeRepresentation, AdjointRepresentation
sage: R = ZZ['q'].fraction_field()
sage: CM = crystals.Tableaux(['D', 4], shape=[1])
sage: VM = MinusculeRepresentation(R, CM)
sage: CA = crystals.Tableaux(['D', 4], shape=[1, 1])
sage: VA = AdjointRepresentation(R, CA)
sage: v = tensor([VM.an_element(), VA.an_element()]); v
4*B[[[1]]] # B[[[1], [2]]] + 4*B[[[1]]] # B[[[1], [3]]]
+ 6*B[[[1]]] # B[[[2], [3]]] + 4*B[[[2]]] # B[[[1], [2]]]
+ 4*B[[[2]]] # B[[[1], [3]]] + 6*B[[[2]]] # B[[[2], [3]]]
+ 6*B[[[3]]] # B[[[1], [2]]] + 6*B[[[3]]] # B[[[1], [3]]]
+ 9*B[[[3]]] # B[[[2], [3]]]
sage: v.e(1) # indirect doctest
4*B[[[1]]] # B[[[1], [2]]]
+ ((4*q+6)/q)*B[[[1]]] # B[[[1], [3]]]
+ 6*B[[[1]]] # B[[[2], [3]]]
+ 6*q*B[[[2]]] # B[[[1], [3]]]
+ 9*B[[[3]]] # B[[[1], [3]]]
sage: v.e(2) # indirect doctest
4*B[[[1]]] # B[[[1], [2]]]
```

(continues on next page)

(continued from previous page)

```

+ ((6*q+4)/q)*B[[[2]]] # B[[[1], [2]]]
+ 6*B[[[2]]] # B[[[1], [3]]]
+ 9*B[[[2]]] # B[[[2], [3]]]
+ 6*q*B[[[3]]] # B[[[1], [2]]]
sage: v.e(3) # indirect doctest
0
sage: v.e(4) # indirect doctest
0

```

f_on_basis(i, b)Return the action of f_i on the basis element indexed by b.

INPUT:

- i – an element of the index set
- b – an element of basis keys

EXAMPLES:

```

sage: from sage.algebras.quantum_groups.representations import \
....: MinusculaRepresentation, AdjointRepresentation
sage: R = ZZ['q'].fraction_field()
sage: KM = crystals.KirillovReshetikhin(['B',3,1], 3,1)
sage: VM = MinusculaRepresentation(R, KM)
sage: KA = crystals.KirillovReshetikhin(['B',3,1], 2,1)
sage: VA = AdjointRepresentation(R, KA)
sage: v = tensor([VM.an_element(), VA.an_element()]); v
4*B[[+++], []] # B[[[]] + 4*B[[+++], []] # B[[[1], [2]]]
+ 6*B[[+++], []] # B[[[1], [3]]] + 4*B[[++-, []] # B[[[]]
+ 4*B[[++-, []] # B[[[1], [2]]]
+ 6*B[[++-, []] # B[[[1], [3]]] + 6*B[[+--, []] # B[[[]]
+ 6*B[[+--, []] # B[[[1], [2]]]
+ 9*B[[+--, []] # B[[[1], [3]]]
sage: v.f(0) # indirect doctest
((4*q^4+4)/q^2)*B[[+++], []] # B[[[1], [2]]]
+ ((4*q^4+4)/q^2)*B[[++-, []] # B[[[1], [2]]]
+ ((6*q^4+6)/q^2)*B[[+--, []] # B[[[1], [2]]]
sage: v.f(1) # indirect doctest
6*B[[+++], []] # B[[[2], [3]]]
+ 6*B[[++-, []] # B[[[2], [3]]]
+ 9*B[[+--, []] # B[[[2], [3]]]
+ 6*B[[+--, []] # B[[[]]
+ 6*B[[+--, []] # B[[[1], [2]]]
+ 9*q^2*B[[+--, []] # B[[[1], [3]]]
sage: v.f(2) # indirect doctest
4*B[[+++], []] # B[[[1], [3]]]
+ 4*B[[++-, []] # B[[[1], [3]]]
+ 4*B[[+--, []] # B[[[]]
+ 4*q^2*B[[+--, []] # B[[[1], [2]]]
+ ((6*q^2+6)/q^2)*B[[+--, []] # B[[[1], [3]]]
sage: v.f(3) # indirect doctest
6*B[[+++], []] # B[[[1], [0]]]
+ 4*B[[++-, []] # B[[[]]
+ 4*B[[++-, []] # B[[[1], [2]]]
+ 6*q^2*B[[++-, []] # B[[[1], [3]]]

```

(continues on next page)

(continued from previous page)

```

+ 6*B[[+--, []]] # B[[[1], [0]]]
+ 9*B[[+--, []]] # B[[[1], [0]]]
+ 6*B[[+--, []]] # B[[[]]]
+ 6*B[[+--, []]] # B[[[1], [2]]]
+ 9*q^2*B[[+--, []]] # B[[[1], [3]]]

```

extra_super_categories()

EXAMPLES:

```

sage: from sage.categories.quantum_group_representations import_
↳QuantumGroupRepresentations
sage: Cat = QuantumGroupRepresentations(ZZ['q'].fraction_field())
sage: Cat.WithBasis().TensorProducts().extra_super_categories()
[Category of quantum group representations with basis over
Fraction Field of Univariate Polynomial Ring in q over Integer Ring]

```

example()Return an example of a quantum group representation as per *Category.example*.

EXAMPLES:

```

sage: from sage.categories.quantum_group_representations import_
↳QuantumGroupRepresentations
sage: Cat = QuantumGroupRepresentations(ZZ['q'].fraction_field())
sage: Cat.example()
V((2, 1, 0))

```

super_categories()

Return the super categories of self.

EXAMPLES:

```

sage: from sage.categories.quantum_group_representations import_
↳QuantumGroupRepresentations
sage: QuantumGroupRepresentations(ZZ['q'].fraction_field()).super_categories()
[Category of vector spaces over
Fraction Field of Univariate Polynomial Ring in q over Integer Ring]

```

3.132 Regular Crystals

class `sage.categories.regular_crystals.RegularCrystals`(*s=None*)Bases: `sage.categories.category_singleton.Category_singleton`

The category of regular crystals.

A crystal is called *regular* if every vertex b satisfies

$$\varepsilon_i(b) = \max\{k \mid e_i^k(b) \neq 0\} \quad \text{and} \quad \varphi_i(b) = \max\{k \mid f_i^k(b) \neq 0\}.$$

Note: Regular crystals are sometimes referred to as *normal*. When only one of the conditions (on either φ_i or ε_i) holds, these crystals are sometimes called *seminormal* or *semiregular*.

EXAMPLES:

```
sage: C = RegularCrystals()
sage: C
Category of regular crystals
sage: C.super_categories()
[Category of crystals]
sage: C.example()
Highest weight crystal of type A_3 of highest weight omega_1
```

class ElementMethods

Bases: object

demazure_operator_simple(*i*, *ring=None*)

Return the Demazure operator D_i applied to self.

INPUT:

- *i* – an element of the index set of the underlying crystal
- *ring* – (default: QQ) a ring

OUTPUT:

An element of the ring-free module indexed by the underlying crystal.

Let $r = \langle \text{wt}(b), \alpha_i^\vee \rangle$, then $D_i(b)$ is defined as follows:

- If $r \geq 0$, this returns the sum of the elements obtained from self by application of f_i^k for $0 \leq k \leq r$.
- If $r < 0$, this returns the opposite of the sum of the elements obtained by application of e_i^k for $0 < k < -r$.

REFERENCES:

- [Li1995]
- [Ka1993]

EXAMPLES:

```
sage: T = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: t = T(rows=[[1, 2], [2]])
sage: t.demazure_operator_simple(2)
B[[[1, 2], [2]]] + B[[[1, 3], [2]]] + B[[[1, 3], [3]]]
sage: t.demazure_operator_simple(2).parent()
Algebra of The crystal of tableaux of type ['A', 2] and shape(s) [[2, 1]]
over Integer Ring

sage: t.demazure_operator_simple(1)
0

sage: K = crystals.KirillovReshetikhin(['A', 2, 1], 2, 1)
sage: t = K(rows=[[3], [2]])
sage: t.demazure_operator_simple(0)
B[[[1, 2]]] + B[[[2, 3]]]
```

dual_equivalence_class(*index_set=None*)

Return the dual equivalence class indexed by *index_set* of self.

The dual equivalence class of an element $b \in B$ is the set of all elements of B reachable from b via sequences of i -elementary dual equivalence relations (i.e., i -elementary dual equivalence transformations and their inverses) for i in the index set of B .

For this to be well-defined, the element b has to be of weight 0 with respect to I ; that is, we need to

have $\varepsilon_j(b) = \varphi_j(b)$ for all $j \in I$.

See [As2008]. See also `dual_equivalence_graph()` for a definition of i -elementary dual equivalence transformations.

INPUT:

- `index_set` – (optional) the index set I (default: the whole index set of the crystal); this has to be a subset of the index set of the crystal (as a list or tuple)

OUTPUT:

The dual equivalence class of `self` indexed by the subset `index_set`. This class is returned as an undirected edge-colored multigraph. The color of an edge is the index i of the dual equivalence relation it encodes.

See also:

- `dual_equivalence_graph()`
- `sage.combinat.partition.Partition.dual_equivalence_graph()`

EXAMPLES:

```
sage: T = crystals.Tableaux(['A',3], shape=[2,2])
sage: G = T(2,1,4,3).dual_equivalence_class()
sage: sorted(G.edges())
[[[1, 3], [2, 4]], [[1, 2], [3, 4]], 2),
 [[1, 3], [2, 4]], [[1, 2], [3, 4]], 3)]
sage: T = crystals.Tableaux(['A',4], shape=[3,2])
sage: G = T(2,1,4,3,5).dual_equivalence_class()
sage: sorted(G.edges())
[[[1, 3, 5], [2, 4]], [[1, 3, 4], [2, 5]], 4),
 [[1, 3, 5], [2, 4]], [[1, 2, 5], [3, 4]], 2),
 [[1, 3, 5], [2, 4]], [[1, 2, 5], [3, 4]], 3),
 [[1, 3, 4], [2, 5]], [[1, 2, 4], [3, 5]], 2),
 [[1, 2, 4], [3, 5]], [[1, 2, 3], [4, 5]], 3),
 [[1, 2, 4], [3, 5]], [[1, 2, 3], [4, 5]], 4)]
```

epsilon(i)

Return ε_i of `self`.

EXAMPLES:

```
sage: C = crystals.Letters(['A',5])
sage: C(1).epsilon(1)
0
sage: C(2).epsilon(1)
1
```

phi(i)

Return φ_i of `self`.

EXAMPLES:

```
sage: C = crystals.Letters(['A',5])
sage: C(1).phi(1)
1
sage: C(2).phi(1)
0
```

stembridgeDel_depth(*i, j*)

Return the difference in the j -depth of `self` and f_i of `self`, where i and j are in the index set of the underlying crystal. This function is useful for checking the Stembridge local axioms for crystal bases.

The i -depth of a crystal node x is $\varepsilon_i(x)$.

EXAMPLES:

```
sage: T = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: t=T(rows=[[1, 1], [2]])
sage: t.stembridgeDel_depth(1, 2)
0
sage: s=T(rows=[[1, 3], [3]])
sage: s.stembridgeDel_depth(1, 2)
-1
```

stembridgeDel_rise(*i, j*)

Return the difference in the j -rise of `self` and f_i of `self`, where i and j are in the index set of the underlying crystal. This function is useful for checking the Stembridge local axioms for crystal bases.

The i -rise of a crystal node x is $\varphi_i(x)$.

EXAMPLES:

```
sage: T = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: t=T(rows=[[1, 1], [2]])
sage: t.stembridgeDel_rise(1, 2)
-1
sage: s=T(rows=[[1, 3], [3]])
sage: s.stembridgeDel_rise(1, 2)
0
```

stembridgeDelta_depth(*i, j*)

Return the difference in the j -depth of `self` and e_i of `self`, where i and j are in the index set of the underlying crystal. This function is useful for checking the Stembridge local axioms for crystal bases.

The i -depth of a crystal node x is $-\varepsilon_i(x)$.

EXAMPLES:

```
sage: T = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: t=T(rows=[[1, 2], [2]])
sage: t.stembridgeDelta_depth(1, 2)
0
sage: s=T(rows=[[2, 3], [3]])
sage: s.stembridgeDelta_depth(1, 2)
-1
```

stembridgeDelta_rise(*i, j*)

Return the difference in the j -rise of `self` and e_i of `self`, where i and j are in the index set of the underlying crystal. This function is useful for checking the Stembridge local axioms for crystal bases.

The i -rise of a crystal node x is $\varphi_i(x)$.

EXAMPLES:

```
sage: T = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: t=T(rows=[[1, 2], [2]])
```

(continues on next page)

(continued from previous page)

```

sage: t.stembridgeDelta_rise(1,2)
-1
sage: s=T(rows=[[2,3],[3]])
sage: s.stembridgeDelta_rise(1,2)
0

```

stembridgeTriple(*i*, *j*)

Let A be the Cartan matrix of the crystal, x a crystal element, and let i and j be in the index set of the crystal. Further, set $b = \text{stembridgeDelta_depth}(x, i, j)$, and $c = \text{stembridgeDelta_rise}(x, i, j)$. If $x.e(i)$ is non-empty, this function returns the triple (A_{ij}, b, c) ; otherwise it returns None. By the Stembridge local characterization of crystal bases, one should have $A_{ij} = b + c$.

EXAMPLES:

```

sage: T = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: t=T(rows=[[1, 1], [2]])
sage: t.stembridgeTriple(1, 2)
sage: s=T(rows=[[1, 2], [2]])
sage: s.stembridgeTriple(1, 2)
(-1, 0, -1)

sage: T = crystals.Tableaux(['B', 2], shape=[2, 1])
sage: t=T(rows=[[1, 2], [2]])
sage: t.stembridgeTriple(1, 2)
(-2, 0, -2)
sage: s=T(rows=[[-1, -1], [0]])
sage: s.stembridgeTriple(1, 2)
(-2, -2, 0)
sage: u=T(rows=[[0, 2], [1]])
sage: u.stembridgeTriple(1, 2)
(-2, -1, -1)

```

weight()

Return the weight of this crystal element.

EXAMPLES:

```

sage: C = crystals.Letters(['A', 5])
sage: C(1).weight()
(1, 0, 0, 0, 0, 0)

```

class MorphismMethods

Bases: object

is_isomorphism()

Check if self is a crystal isomorphism, which is true if and only if this is a strict embedding with the same number of connected components.

EXAMPLES:

```

sage: La = RootSystem(['A', 2, 1]).weight_space(extended=True).fundamental_
↳weights()
sage: B = crystals.LSPaths(La[0])
sage: La = RootSystem(['A', 2, 1]).weight_lattice(extended=True).fundamental_
↳weights()

```

(continues on next page)

(continued from previous page)

```

sage: C = crystals.GeneralizedYoungWalls(2, La[0])
sage: H = Hom(B, C)
sage: from sage.categories.highest_weight_crystals import_
↳HighestWeightCrystalMorphism
sage: class Psi(HighestWeightCrystalMorphism):
.....:     def is_strict(self):
.....:         return True
sage: psi = Psi(H, C.module_generators)
sage: psi
['A', 2, 1] Crystal morphism:
  From: The crystal of LS paths of type ['A', 2, 1] and weight Lambda[0]
  To:   Highest weight crystal of generalized Young walls of Cartan type ['A
↳', 2, 1]
        and highest weight Lambda[0]
  Defn: (Lambda[0],) |--> []
sage: psi.is_isomorphism()
True

```

class ParentMethods

Bases: object

demazure_operator(*element, reduced_word*)Returns the application of Demazure operators D_i for i from *reduced_word* on *element*.

INPUT:

- *element* – an element of a free module indexed by the underlying crystal
- *reduced_word* – a reduced word of the Weyl group of the same type as the underlying crystal

OUTPUT:

- an element of the free module indexed by the underlying crystal

EXAMPLES:

```

sage: T = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: C = CombinatorialFreeModule(QQ, T)
sage: t = T.highest_weight_vector()
sage: b = 2*C(t)
sage: T.demazure_operator(b, [1, 2, 1])
2*B[[[1, 1], [2]]] + 2*B[[[1, 2], [2]]] + 2*B[[[1, 3], [2]]] + 2*B[[[1, 1], 1],
↳[3]]
↳[3]]
+ 2*B[[[1, 2], [3]]] + 2*B[[[1, 3], [3]]] + 2*B[[[2, 2], [3]]] + 2*B[[[2, 1],
↳3], [3]]

```

The Demazure operator is idempotent:

```

sage: T = crystals.Tableaux("A1", shape=[4])
sage: C = CombinatorialFreeModule(QQ, T)
sage: b = C(T.module_generators[0]); b
B[[[1, 1, 1, 1]]]
sage: e = T.demazure_operator(b, [1]); e
B[[[1, 1, 1, 1]]] + B[[[1, 1, 1, 2]]] + B[[[1, 1, 2, 2]]] + B[[[1, 2, 2, 1],
↳2]]
↳2]] + B[[[2, 2, 2, 2]]]
sage: e == T.demazure_operator(e, [1])
True

```

(continues on next page)

(continued from previous page)

```
sage: all(T.demazure_operator(T.demazure_operator(C(t), [1]), [1]) == T.
↪demazure_operator(C(t), [1]) for t in T)
True
```

demazure_subcrystal(*element*, *reduced_word*, *only_support=True*)

Return the subcrystal corresponding to the application of Demazure operators D_i for i from *reduced_word* on *element*.

INPUT:

- *element* – an element of a free module indexed by the underlying crystal
- *reduced_word* – a reduced word of the Weyl group of the same type as the underlying crystal
- *only_support* – (default: True) only include arrows corresponding to the support of *reduced_word*

OUTPUT:

- the Demazure subcrystal

EXAMPLES:

```
sage: T = crystals.Tableaux(['A', 2], shape=[2, 1])
sage: t = T.highest_weight_vector()
sage: S = T.demazure_subcrystal(t, [1, 2])
sage: list(S)
[[[1, 1], [2]], [[1, 2], [2]], [[1, 1], [3]],
 [[1, 2], [3]], [[2, 2], [3]]]
sage: S = T.demazure_subcrystal(t, [2, 1])
sage: list(S)
[[[1, 1], [2]], [[1, 2], [2]], [[1, 1], [3]],
 [[1, 3], [2]], [[1, 3], [3]]]
```

We construct an example where we don't only want the arrows indicated by the support of the reduced word:

```
sage: K = crystals.KirillovReshetikhin(['A', 1, 1], 1, 2)
sage: mg = K.module_generator()
sage: S = K.demazure_subcrystal(mg, [1])
sage: S.digraph().edges()
[[([1, 1], [1, 2]), ([1, 2], 1), ([1, 2], [2, 2]), ([2, 2], 1)]
sage: S = K.demazure_subcrystal(mg, [1], only_support=False)
sage: S.digraph().edges()
[[([1, 1], [1, 2]), ([1, 2], 1),
 ([1, 2], [1, 1]), ([1, 1], 0),
 ([1, 2], [2, 2]), ([2, 2], 1),
 ([2, 2], [1, 2]), ([1, 2], 0)]
```

dual_equivalence_graph(*X=None*, *index_set=None*, *directed=True*)

Return the dual equivalence graph indexed by *index_set* on the subset *X* of *self*.

Let $b \in B$ be an element of weight 0, so $\varepsilon_j(b) = \varphi_j(b)$ for all $j \in I$, where I is the indexing set. We say b' is an i -elementary dual equivalence transformation of b (where $i \in I$) if

- $\varepsilon_i(b) = 1$ and $\varepsilon_{i-1}(b) = 0$, and
- $b' = f_{i-1}f_i e_{i-1} e_i b$.

We can do the inverse procedure by interchanging i and $i - 1$ above.

Note: If the index set is not an ordered interval, we let $i - 1$ mean the index appearing before i in I .

This definition comes from [As2008] Section 4 (where our $\varphi_j(b)$ and $\varepsilon_j(b)$ are denoted by $\epsilon(b, j)$ and $-\delta(b, j)$, respectively).

The dual equivalence graph of B is defined to be the colored graph whose vertices are the elements of B of weight 0, and whose edges of color i (for $i \in I$) connect pairs $\{b, b'\}$ such that b' is an i -elementary dual equivalence transformation of b .

Note: This dual equivalence graph is a generalization of $\mathcal{G}(\mathcal{X})$ in [As2008] Section 4 except we do not require $\varepsilon_i(b) = 0, 1$ for all i .

This definition can be generalized by choosing a subset X of the set of all vertices of B of weight 0, and restricting the dual equivalence graph to the vertex set X .

INPUT:

- **X** – (optional) the vertex set X (default: the whole set of vertices of `self` of weight 0)
- **index_set** – (optional) the index set I (default: the whole index set of `self`); this has to be a subset of the index set of `self` (as a list or tuple)
- **directed** – (default: `True`) whether to have the dual equivalence graph be directed, where the head of an edge $b - b'$ is b and the tail is $b' = f_{i-1}f_i e_{i-1} e_i b$

See also:

`sage.combinat.partition.Partition.dual_equivalence_graph()`

EXAMPLES:

```
sage: T = crystals.Tableaux(['A', 3], shape=[2, 2])
sage: G = T.dual_equivalence_graph()
sage: sorted(G.edges())
[[[1, 3], [2, 4]], [[1, 2], [3, 4]], 2),
 [[1, 2], [3, 4]], [[1, 3], [2, 4]], 3)]
sage: T = crystals.Tableaux(['A', 4], shape=[3, 2])
sage: G = T.dual_equivalence_graph()
sage: sorted(G.edges())
[[[1, 3, 5], [2, 4]], [[1, 3, 4], [2, 5]], 4),
 [[1, 3, 5], [2, 4]], [[1, 2, 5], [3, 4]], 2),
 [[1, 3, 4], [2, 5]], [[1, 2, 4], [3, 5]], 2),
 [[1, 2, 5], [3, 4]], [[1, 3, 5], [2, 4]], 3),
 [[1, 2, 4], [3, 5]], [[1, 2, 3], [4, 5]], 3),
 [[1, 2, 3], [4, 5]], [[1, 2, 4], [3, 5]], 4)]

sage: T = crystals.Tableaux(['A', 4], shape=[3, 1])
sage: G = T.dual_equivalence_graph(index_set=[1, 2, 3])
sage: G.vertices()
[[[1, 3, 4], [2]], [[1, 2, 4], [3]], [[1, 2, 3], [4]]]
sage: G.edges()
[[[1, 3, 4], [2]], [[1, 2, 4], [3]], 2),
 [[1, 2, 4], [3]], [[1, 2, 3], [4]], 3)]
```

class `TensorProducts`(*category*, *args)

Bases: `sage.categories.tensor.TensorProductsCategory`

The category of regular crystals constructed by tensor product of regular crystals.

extra_super_categories()

EXAMPLES:

```
sage: RegularCrystals().TensorProducts().extra_super_categories()
[Category of regular crystals]
```

additional_structure()

Return None.

Indeed, the category of regular crystals defines no new structure: it only relates ε_a and φ_a to e_a and f_a respectively.

See also:

Category.additional_structure()

Todo: Should this category be a `CategoryWithAxiom`?

EXAMPLES:

```
sage: RegularCrystals().additional_structure()
```

example($n=3$)

Returns an example of highest weight crystals, as per *Category.example()*.

EXAMPLES:

```
sage: B = RegularCrystals().example(); B
Highest weight crystal of type A_3 of highest weight omega_1
```

super_categories()

EXAMPLES:

```
sage: RegularCrystals().super_categories()
[Category of crystals]
```

3.133 Regular Supercrystals

class `sage.categories.regular_supercrystals.RegularSuperCrystals($s=None$)`

Bases: *sage.categories.category_singleton.Category_singleton*

The category of crystals for super Lie algebras.

EXAMPLES:

```
sage: from sage.categories.regular_supercrystals import RegularSuperCrystals
sage: C = RegularSuperCrystals()
sage: C
Category of regular super crystals
sage: C.super_categories()
[Category of finite super crystals]
```

Parents in this category should implement the following methods:

- either an attribute `_cartan_type` or a method `cartan_type`
- `module_generators`: a list (or container) of distinct elements that generate the crystal using f_i and e_i

Furthermore, their elements x should implement the following methods:

- $x.e(i)$ (returning $e_i(x)$)
- $x.f(i)$ (returning $f_i(x)$)
- $x.weight()$ (returning $wt(x)$)

EXAMPLES:

```
sage: from sage.misc.abstract_method import abstract_methods_of_class
sage: from sage.categories.regular_supercrystals import RegularSuperCrystals
sage: abstract_methods_of_class(RegularSuperCrystals().element_class)
{'optional': [], 'required': ['e', 'f', 'weight']}
```

class ElementMethods

Bases: object

epsilon(i)

Return ε_i of self.

EXAMPLES:

```
sage: C = crystals.Tableaux(['A', [1, 2]], shape = [2, 1])
sage: c = C.an_element(); c
[[-2, -2], [-1]]
sage: c.epsilon(2)
0
sage: c.epsilon(0)
0
sage: c.epsilon(-1)
0
```

phi(i)

Return φ_i of self.

EXAMPLES:

```
sage: C = crystals.Tableaux(['A', [1, 2]], shape = [2, 1])
sage: c = C.an_element(); c
[[-2, -2], [-1]]
sage: c.phi(1)
0
sage: c.phi(2)
0
sage: c.phi(0)
1
```

class TensorProducts($category, *args$)

Bases: [sage.categories.tensor.TensorProductsCategory](#)

The category of regular crystals constructed by tensor product of regular crystals.

extra_super_categories()

EXAMPLES:

```
sage: from sage.categories.regular_supercrystals import RegularSuperCrystals
sage: RegularSuperCrystals().TensorProducts().extra_super_categories()
[Category of regular super crystals]
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.regular_supercrystals import RegularSuperCrystals
sage: C = RegularSuperCrystals()
sage: C.super_categories()
[Category of finite super crystals]
```

3.134 Right modules

class `sage.categories.right_modules.RightModules`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of right modules right modules over an rng (ring not necessarily with unit), i.e. an abelian group with right multiplication by elements of the rng

EXAMPLES:

```
sage: RightModules(QQ)
Category of right modules over Rational Field
sage: RightModules(QQ).super_categories()
[Category of commutative additive groups]
```

class `ElementMethods`

Bases: `object`

class `ParentMethods`

Bases: `object`

super_categories()

EXAMPLES:

```
sage: RightModules(QQ).super_categories()
[Category of commutative additive groups]
```

3.135 Ring ideals

class `sage.categories.ring_ideals.RingIdeals`(*R*)

Bases: `sage.categories.category_types.Category_ideal`

The category of two-sided ideals in a fixed ring.

EXAMPLES:

```
sage: Ideals(Integers(200))
Category of ring ideals in Ring of integers modulo 200
sage: C = Ideals(IntegerRing()); C
Category of ring ideals in Integer Ring
sage: I = C([8,12,18])
sage: I
Principal ideal (2) of Integer Ring
```

See also: *CommutativeRingIdeals*.

Todo:

- If useful, implement `RingLeftIdeals` and `RingRightIdeals` of which `RingIdeals` would be a subcategory.
 - Make `RingIdeals(R)`, return `CommutativeRingIdeals(R)` when `R` is commutative.
-

super_categories()

EXAMPLES:

```
sage: RingIdeals(ZZ).super_categories()
[Category of modules over Integer Ring]
sage: RingIdeals(QQ).super_categories()
[Category of vector spaces over Rational Field]
```

3.136 Rings

class `sage.categories.rings.Rings`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of rings

Associative rings with unit, not necessarily commutative

EXAMPLES:

```
sage: Rings()
Category of rings
sage: sorted(Rings().super_categories(), key=str)
[Category of rngs, Category of semirings]

sage: sorted(Rings().axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse',
 'AdditiveUnital', 'Associative', 'Distributive', 'Unital']

sage: Rings() is (CommutativeAdditiveGroups() & Monoids()).Distributive()
True
sage: Rings() is Rngs().Unital()
True
sage: Rings() is Semirings().AdditiveInverse()
True
```

Todo: (see: http://trac.sagemath.org/sage_trac/wiki/CategoriesRoadMap)

- Make `Rings()` into a subcategory or alias of `Algebras(ZZ)`;
 - A parent `P` in the category `Rings()` should automatically be in the category `Algebras(P)`.
-

Commutative

alias of `sage.categories.commutative_rings.CommutativeRings`

Divisionalias of `sage.categories.division_rings.DivisionRings`**class ElementMethods**

Bases: object

inverse_of_unit()

Return the inverse of this element if it is a unit.

OUTPUT:

An element in the same ring as this element.

EXAMPLES:

```
sage: R.<x> = ZZ[]
sage: S = R.quo(x^2 + x + 1)
sage: S(1).inverse_of_unit()
1
```

This method fails when the element is not a unit:

```
sage: 2.inverse_of_unit()
Traceback (most recent call last):
...
ArithmeticError: inverse does not exist
```

The inverse returned is in the same ring as this element:

```
sage: a = -1
sage: a.parent()
Integer Ring
sage: a.inverse_of_unit().parent()
Integer Ring
```

Note that this is often not the case when computing inverses in other ways:

```
sage: (~a).parent()
Rational Field
sage: (1/a).parent()
Rational Field
```

is_unit()

Return whether this element is a unit in the ring.

Note: This is a generic implementation for (non-commutative) rings which only works for the one element, its additive inverse, and the zero element. Most rings should provide a more specialized implementation.

EXAMPLES:

```
sage: MS = MatrixSpace(ZZ, 2)
sage: MS.one().is_unit()
True
sage: MS.zero().is_unit()
False
```

(continues on next page)

(continued from previous page)

```
sage: MS([1,2,3,4]).is_unit()
False
```

class MorphismMethods

Bases: object

extend_to_fraction_field()

Return the extension of this morphism to fraction fields of the domain and the codomain.

EXAMPLES:

```
sage: S.<x> = QQ[]
sage: f = S.hom([x+1]); f
Ring endomorphism of Univariate Polynomial Ring in x over Rational Field
Defn: x |--> x + 1

sage: g = f.extend_to_fraction_field(); g
Ring endomorphism of Fraction Field of Univariate Polynomial Ring in x over
↪Rational Field
Defn: x |--> x + 1
sage: g(x)
x + 1
sage: g(1/x)
1/(x + 1)
```

If this morphism is not injective, it does not extend to the fraction field and an error is raised:

```
sage: f = GF(5).coerce_map_from(ZZ)
sage: f.extend_to_fraction_field()
Traceback (most recent call last):
...
ValueError: the morphism is not injective
```

is_injective()

Return whether or not this morphism is injective.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: R.hom([x, y^2], R).is_injective()
True
sage: R.hom([x, x^2], R).is_injective()
False
sage: S.<u,v> = R.quotient(x^3*y)
sage: R.hom([v, u], S).is_injective()
False
sage: S.hom([-u, v], S).is_injective()
True
sage: S.cover().is_injective()
False
```

If the domain is a field, the homomorphism is injective:

```

sage: K.<x> = FunctionField(QQ)
sage: L.<y> = FunctionField(QQ)
sage: f = K.hom([y]); f
Function Field morphism:
  From: Rational function field in x over Rational Field
  To:   Rational function field in y over Rational Field
  Defn: x |--> y
sage: f.is_injective()
True

```

Unless the codomain is the zero ring:

```

sage: codomain = Integers(1)
sage: f = QQ.hom([Zmod(1)(0)], check=False)
sage: f.is_injective()
False

```

Homomorphism from rings of characteristic zero to rings of positive characteristic can not be injective:

```

sage: R.<x> = ZZ[]
sage: f = R.hom([GF(3)(1)]); f
Ring morphism:
  From: Univariate Polynomial Ring in x over Integer Ring
  To:   Finite Field of size 3
  Defn: x |--> 1
sage: f.is_injective()
False

```

A morphism whose domain is an order in a number field is injective if the codomain has characteristic zero:

```

sage: K.<x> = FunctionField(QQ)
sage: f = ZZ.hom(K); f
Composite map:
  From: Integer Ring
  To:   Rational function field in x over Rational Field
  Defn: Conversion via FractionFieldElement_1poly_field map:
        From: Integer Ring
        To:   Fraction Field of Univariate Polynomial Ring in x over
↳Rational Field
        then
        Isomorphism:
        From: Fraction Field of Univariate Polynomial Ring in x over
↳Rational Field
        To:   Rational function field in x over Rational Field
sage: f.is_injective()
True

```

A coercion to the fraction field is injective:

```

sage: R = ZpFM(3)
sage: R.fraction_field().coerce_map_from(R).is_injective()
True

```


NoZeroDivisorsalias of `sage.categories.domains.Domains`**class ParentMethods**

Bases: object

bracket(x, y)Returns the Lie bracket $[x, y] = xy - yx$ of x and y .

INPUT:

- x, y – elements of self

EXAMPLES:

```
sage: F = AlgebrasWithBasis(QQ).example()
sage: F
An example of an algebra with basis: the free algebra on the generators ('a
↪', 'b', 'c') over Rational Field
sage: a,b,c = F.algebra_generators()
sage: F.bracket(a,b)
B[word: ab] - B[word: ba]
```

This measures the default of commutation between x and y . F endowed with the bracket operation is a Lie algebra; in particular, it satisfies Jacobi's identity:

```
sage: F.bracket( F.bracket(a,b), c) + F.bracket(F.bracket(b,c),a) + F.
↪bracket(F.bracket(c,a),b)
0
```

characteristic()

Return the characteristic of this ring.

EXAMPLES:

```
sage: QQ.characteristic()
0
sage: GF(19).characteristic()
19
sage: Integers(8).characteristic()
8
sage: Zp(5).characteristic()
0
```

free_module(*base=None, basis=None, map=True*)Return a free module V over the specified subring together with maps to and from V .

The default implementation only supports the case that the base ring is the ring itself.

INPUT:

- *base* – a subring R so that this ring is isomorphic to a finite-rank free R -module V
- *basis* – (optional) a basis for this ring over the base
- *map* – boolean (default True), whether to return R -linear maps to and from V

OUTPUT:

- A finite-rank free R -module V
- An R -module isomorphism from V to this ring (only included if *map* is True)
- An R -module isomorphism from this ring to V (only included if *map* is True)

EXAMPLES:

```

sage: R.<x> = QQ[[[]]]
sage: V, from_V, to_V = R.free_module(R)
sage: v = to_V(1+x); v
(1 + x)
sage: from_V(v)
1 + x
sage: W, from_W, to_W = R.free_module(R, basis=(1-x))
sage: W is V
True
sage: w = to_W(1+x); w
(1 - x^2)
sage: from_W(w)
1 + x + O(x^20)

```

ideal(*args, **kws)

Create an ideal of this ring.

NOTE:

The code is copied from the base class `Ring`. This is because there are rings that do not inherit from that class, such as matrix algebras. See [trac ticket #7797](#).

INPUT:

- An element or a list/tuple/sequence of elements.
- `coerce` (optional bool, default True): First coerce the elements into this ring.
- `side`, optional string, one of "twosided" (default), "left", "right": determines whether the resulting ideal is twosided, a left ideal or a right ideal.

EXAMPLES:

```

sage: MS = MatrixSpace(QQ,2,2)
sage: isinstance(MS,Ring)
False
sage: MS in Rings()
True
sage: MS.ideal(2)
Twosided Ideal
(
  [2 0]
  [0 2]
)
of Full MatrixSpace of 2 by 2 dense matrices over Rational Field
sage: MS.ideal([MS.0,MS.1],side='right')
Right Ideal
(
  [1 0]
  [0 0],

  [0 1]
  [0 0]
)
of Full MatrixSpace of 2 by 2 dense matrices over Rational Field

```

ideal_monoid()

The monoid of the ideals of this ring.

NOTE:

The code is copied from the base class of rings. This is since there are rings that do not inherit from that class, such as matrix algebras. See [trac ticket #7797](#).

EXAMPLES:

```
sage: MS = MatrixSpace(QQ,2,2)
sage: isinstance(MS,Ring)
False
sage: MS in Rings()
True
sage: MS.ideal_monoid()
Monoid of ideals of Full MatrixSpace of 2 by 2 dense matrices
over Rational Field
```

Note that the monoid is cached:

```
sage: MS.ideal_monoid() is MS.ideal_monoid()
True
```

is_ring()

Return True, since this is an object of the category of rings.

EXAMPLES:

```
sage: Parent(QQ,category=Rings()).is_ring()
True
```

is_zero()

Return True if this is the zero ring.

EXAMPLES:

```
sage: Integers(1).is_zero()
True
sage: Integers(2).is_zero()
False
sage: QQ.is_zero()
False
sage: R.<x> = ZZ[]
sage: R.quo(1).is_zero()
True
sage: R.<x> = GF(101)[]
sage: R.quo(77).is_zero()
True
sage: R.quo(x^2+1).is_zero()
False
```

quo(*I*, names=None, **kwds)

Quotient of a ring by a two-sided ideal.

NOTE:

This is a synonym for `quotient()`.

EXAMPLES:

```
sage: MS = MatrixSpace(QQ,2)
sage: I = MS*MS.gens()*MS
```

MS is not an instance of `Ring`.

However it is an instance of the parent class of the category of rings. The quotient method is inherited from there:

```
sage: isinstance(MS, sage.rings.ring.Ring)
False
sage: isinstance(MS, Rings().parent_class)
True
sage: MS.quot(I, names = ['a', 'b', 'c', 'd'])
Quotient of Full MatrixSpace of 2 by 2 dense matrices over Rational Field
↳by the ideal
(
  [1 0]
  [0 0],

  [0 1]
  [0 0],

  [0 0]
  [1 0],

  [0 0]
  [0 1]
)
```

quotient(*I*, *names*=None, ***kws*)

Quotient of a ring by a two-sided ideal.

INPUT:

- *I*: A twosided ideal of this ring.
- *names*: a list of strings to be used as names for the variables in the quotient ring.
- further named arguments that may be passed to the quotient ring constructor.

EXAMPLES:

Usually, a ring inherits a method `sage.rings.ring.Ring.quotient()`. So, we need a bit of effort to make the following example work with the category framework:

```
sage: F.<x,y,z> = FreeAlgebra(QQ)
sage: from sage.rings.noncommutative_ideals import Ideal_nc
sage: from itertools import product
sage: class PowerIdeal(Ideal_nc):
.....:     def __init__(self, R, n):
.....:         self._power = n
.....:         Ideal_nc.__init__(self, R, [R.prod(m) for m in product(R.gens(),
↳repeat=n)])
.....:     def reduce(self, x):
.....:         R = self.ring()
.....:         return add([c*R(m) for m,c in x if len(m) < self._power], R(0))
sage: I = PowerIdeal(F, 3)
sage: Q = Rings().parent_class.quotient(F, I); Q
Quotient of Free Algebra on 3 generators (x, y, z) over Rational Field by
↳the ideal (x^3, x^2*y, x^2*z, x*y*x, x*y^2, x*y*z, x*z*x, x*z*y, x*z^2,
↳y*x^2, y*x*y, y*x*z, y^2*x, y^3, y^2*z, y*z*x, y*z*y, y*z^2, z*x^2, z*x*y,
↳z*x*z, z*y*x, z*y^2, z*y*z, z^2*x, z^2*y, z^3)
```

(continues on next page)

(continued from previous page)

```

sage: Q.0
xbar
sage: Q.1
ybar
sage: Q.2
zbar
sage: Q.0*Q.1
xbar*ybar
sage: Q.0*Q.1*Q.0
0

```

quotient_ring(*I*, *names=None*, ***kws*)

Quotient of a ring by a two-sided ideal.

NOTE:

This is a synonyme for *quotient()*.

EXAMPLES:

```

sage: MS = MatrixSpace(QQ,2)
sage: I = MS*MS.gens()*MS

```

MS is not an instance of `Ring`, but it is an instance of the parent class of the category of rings. The quotient method is inherited from there:

```

sage: isinstance(MS, sage.rings.ring.Ring)
False
sage: isinstance(MS, Rings().parent_class)
True
sage: MS.quotient_ring(I, names = ['a', 'b', 'c', 'd'])
Quotient of Full MatrixSpace of 2 by 2 dense matrices over Rational Field
↳by the ideal
(
  [1 0]
  [0 0],

  [0 1]
  [0 0],

  [0 0]
  [1 0],

  [0 0]
  [0 1]
)

```

class SubcategoryMethods

Bases: object

Division()

Return the full subcategory of the division objects of *self*.

A ring satisfies the *division axiom* if all non-zero elements have multiplicative inverses.

Note: This could be generalized to `MagnasAndAdditiveMagnas.Distributive.AdditiveUnital`.

EXAMPLES:

```
sage: Rings().Division()
Category of division rings
sage: Rings().Commutative().Division()
Category of fields
```

NoZeroDivisors()

Return the full subcategory of the objects of `self` having no nonzero zero divisors.

A *zero divisor* in a ring R is an element $x \in R$ such that there exists a nonzero element $y \in R$ such that $x \cdot y = 0$ or $y \cdot x = 0$ (see [Wikipedia article Zero_divisor](#)).

EXAMPLES:

```
sage: Rings().NoZeroDivisors()
Category of domains
```

Note: This could be generalized to `MagnasAndAdditiveMagnas.Distributive.AdditiveUnital`.

3.137 Rngs

class `sage.categories.rngs.Rngs`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of rngs.

An *rng* $(S, +, *)$ is similar to a ring but not necessarily unital. In other words, it is a combination of a commutative additive group $(S, +)$ and a multiplicative semigroup $(S, *)$, where $*$ distributes over $+$.

EXAMPLES:

```
sage: C = Rngs(); C
Category of rngs
sage: sorted(C.super_categories(), key=str)
[Category of associative additive commutative additive associative additive unital_
↔distributive magnas and additive magnas,
Category of commutative additive groups]

sage: sorted(C.axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveInverse',
'AdditiveUnital', 'Associative', 'Distributive']

sage: C is (CommutativeAdditiveGroups() & Semigroups()).Distributive()
True
sage: C.Unital()
Category of rings
```

Unitalalias of `sage.categories.rings.Rings`

3.138 R-trivial semigroups

class `sage.categories.r_trivial_semigroups.RTrivialSemigroups`(*base_category*)Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`**Commutative_extra_super_categories()**Implement the fact that a commutative R -trivial semigroup is J -trivial.

EXAMPLES:

```
sage: Semigroups().RTrivial().Commutative_extra_super_categories()
[Category of j trivial semigroups]
```

extra_super_categories()Implement the fact that a R -trivial semigroup is H -trivial.

EXAMPLES:

```
sage: Semigroups().RTrivial().extra_super_categories()
[Category of h trivial semigroups]
```

3.139 Schemes

class `sage.categories.schemes.Schemes`(*s=None*)Bases: `sage.categories.category.Category`

The category of all schemes.

EXAMPLES:

```
sage: Schemes()
Category of schemes
```

Schemes can also be used to construct the category of schemes over a given base:

```
sage: Schemes(Spec(ZZ))
Category of schemes over Integer Ring

sage: Schemes(ZZ)
Category of schemes over Integer Ring
```

Todo: Make `Schemes()` a singleton category (and remove `Schemes` from the workaround in `category_types.Category_over_base._test_category_over_bases()`).

This is currently incompatible with the dispatching below.

super_categories()

EXAMPLES:

```
sage: Schemes().super_categories()
[Category of sets]
```

class `sage.categories.schemes.Schemes_over_base`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base`

The category of schemes over a given base scheme.

EXAMPLES:

```
sage: Schemes(Spec(ZZ))
Category of schemes over Integer Ring
```

base_scheme()

EXAMPLES:

```
sage: Schemes(Spec(ZZ)).base_scheme()
Spectrum of Integer Ring
```

super_categories()

EXAMPLES:

```
sage: Schemes(Spec(ZZ)).super_categories()
[Category of schemes]
```

3.140 Semigroups

class `sage.categories.semigroups.Semigroups`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of (multiplicative) semigroups.

A *semigroup* is an associative *magma*, that is a set endowed with a multiplicative binary operation $*$ which is associative (see [Wikipedia article Semigroup](#)).

The operation $*$ is not required to have a neutral element. A semigroup for which such an element exists is a *monoid*.

EXAMPLES:

```
sage: C = Semigroups(); C
Category of semigroups
sage: C.super_categories()
[Category of magmas]
sage: C.all_super_categories()
[Category of semigroups, Category of magmas,
Category of sets, Category of sets with partial maps, Category of objects]
sage: C.axioms()
frozenset({'Associative'})
sage: C.example()
An example of a semigroup: the left zero semigroup
```

class `Algebras`(*category, *args*)

Bases: `sage.categories.algebra_functor.AlgebrasCategory`

class ParentMethods

Bases: object

algebra_generators()

The generators of this algebra, as per *MagmaticAlgebras.ParentMethods.algebra_generators()*.

They correspond to the generators of the semigroup.

EXAMPLES:

```
sage: M = FiniteSemigroups().example(); M
An example of a finite semigroup:
the left regular band generated by ('a', 'b', 'c', 'd')
sage: M.semigroup_generators()
Family ('a', 'b', 'c', 'd')
sage: M.algebra(ZZ).algebra_generators()
Finite family {0: B['a'], 1: B['b'], 2: B['c'], 3: B['d']}
```

gen(*i=0*)

Return the *i*-th generator of self.

EXAMPLES:

```
sage: A = GL(3, GF(7)).algebra(ZZ)
sage: A.gen(0)
[3 0 0]
[0 1 0]
[0 0 1]
```

gens()

Return the generators of self.

EXAMPLES:

```
sage: a, b = SL2Z.algebra(ZZ).gens(); a, b
([ 0 -1]
 [ 1  0],
 [1  1]
 [0  1])
sage: 2*a + b
2*[ 0 -1]
 [ 1  0]
+
[1  1]
[0  1]
```

ngens()

Return the number of generators of self.

EXAMPLES:

```
sage: SL2Z.algebra(ZZ).ngens()
2
sage: DihedralGroup(4).algebra(RR).ngens()
2
```

product_on_basis(*g1, g2*)

Product, on basis elements, as per *MagmaticAlgebras.WithBasis.ParentMethods.product_on_basis()*.

The product of two basis elements is induced by the product of the corresponding elements of the group.

EXAMPLES:

```
sage: S = FiniteSemigroups().example(); S
An example of a finite semigroup: the left regular band generated by ('a
↪', 'b', 'c', 'd')
sage: A = S.algebra(QQ)
sage: a,b,c,d = A.algebra_generators()
sage: a * b + b * d * c * d
B['ab'] + B['bdc']
```

regular_representation(*side='left'*)

Return the regular representation of self.

INPUT:

- *side* – (default: "left") whether this is the "left" or "right" regular representation

EXAMPLES:

```
sage: G = groups.permutation.Dihedral(4)
sage: A = G.algebra(QQ)
sage: V = A.regular_representation()
sage: V == G.regular_representation(QQ)
True
```

trivial_representation(*side='twosided'*)

Return the trivial representation of self.

INPUT:

- *side* – ignored

EXAMPLES:

```
sage: G = groups.permutation.Dihedral(4)
sage: A = G.algebra(QQ)
sage: V = A.trivial_representation()
sage: V == G.trivial_representation(QQ)
True
```

extra_super_categories()

Implement the fact that the algebra of a semigroup is indeed a (not necessarily unital) algebra.

EXAMPLES:

```
sage: Semigroups().Algebras(QQ).extra_super_categories()
[Category of semigroups]
sage: Semigroups().Algebras(QQ).super_categories()
[Category of associative algebras over Rational Field,
Category of magma algebras over Rational Field]
```

Aperiodic

alias of *sage.categories.aperiodic_semigroups.AperiodicSemigroups*

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

extra_super_categories()

Implement the fact that a Cartesian product of semigroups is a semigroup.

EXAMPLES:

```
sage: Semigroups().CartesianProducts().extra_super_categories()
[Category of semigroups]
sage: Semigroups().CartesianProducts().super_categories()
[Category of semigroups, Category of Cartesian products of magmas]
```

class ElementMethods

Bases: object

Finite

alias of *sage.categories.finite_semigroups.FiniteSemigroups*

FinitelyGeneratedAsMagma

alias of *sage.categories.finitely_generated_semigroups.FinitelyGeneratedSemigroups*

HTrivial

alias of *sage.categories.h_trivial_semigroups.HTrivialSemigroups*

JTrivial

alias of *sage.categories.j_trivial_semigroups.JTrivialSemigroups*

LTrivial

alias of *sage.categories.l_trivial_semigroups.LTrivialSemigroups*

class ParentMethods

Bases: object

cayley_graph(*side='right', simple=False, elements=None, generators=None, connecting_set=None*)

Return the Cayley graph for this finite semigroup.

INPUT:

- *side* – “left”, “right”, or “twosided”: the side on which the generators act (default: “right”)
- *simple* – boolean (default: False): if True, returns a simple graph (no loops, no labels, no multiple edges)
- *generators* – a list, tuple, or family of elements of *self* (default: *self.semigroup_generators()*)
- *connecting_set* – alias for *generators*; deprecated
- *elements* – a list (or iterable) of elements of *self*

OUTPUT:

- *DiGraph*

EXAMPLES:

We start with the (right) Cayley graphs of some classical groups:

```
sage: D4 = DihedralGroup(4); D4
Dihedral group of order 8 as a permutation group
sage: G = D4.cayley_graph()
sage: show(G, color_by_label=True, edge_labels=True)
sage: A5 = AlternatingGroup(5); A5
Alternating group of order 5!/2 as a permutation group
sage: G = A5.cayley_graph()
sage: G.show3d(color_by_label=True, edge_size=0.01, edge_size2=0.02, vertex_
size=0.03)
```

(continues on next page)

(continued from previous page)

```

sage: G.show3d(vertex_size=0.03, edge_size=0.01, edge_size2=0.02, vertex_
↳ colors={(1,1,1):G.vertices()}, bgcolor=(0,0,0), color_by_label=True,
↳ xres=700, yres=700, iterations=200) # long time (less than a minute)
sage: G.num_edges()
120

sage: w = WeylGroup(['A', 3])
sage: d = w.cayley_graph(); d
Digraph on 24 vertices
sage: d.show3d(color_by_label=True, edge_size=0.01, vertex_size=0.03)

```

Alternative generators may be specified:

```

sage: G = A5.cayley_graph(generators=[A5.gens()[0]])
sage: G.num_edges()
60
sage: g=PermutationGroup([(i+1,j+1) for i in range(5) for j in range(5) if
↳ j!=i])
sage: g.cayley_graph(generators=[(1,2),(2,3)])
Digraph on 120 vertices

```

If `elements` is specified, then only the subgraph induced and those elements is returned. Here we use it to display the Cayley graph of the free monoid truncated on the elements of length at most 3:

```

sage: M = Monoids().example(); M
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
sage: elements = [ M.prod(w) for w in sum((list(Words(M.semigroup_
↳ generators(),k)) for k in range(4)),[]) ]
sage: G = M.cayley_graph(elements = elements)
sage: G.num_verts(), G.num_edges()
(85, 84)
sage: G.show3d(color_by_label=True, edge_size=0.001, vertex_size=0.01)

```

We now illustrate the side and simple options on a semigroup:

```

sage: S = FiniteSemigroups().example(alphabet=('a','b'))
sage: g = S.cayley_graph(simple=True)
sage: g.vertices()
['a', 'ab', 'b', 'ba']
sage: g.edges()
[('a', 'ab', None), ('b', 'ba', None)]

```

```

sage: g = S.cayley_graph(side="left", simple=True)
sage: g.vertices()
['a', 'ab', 'b', 'ba']
sage: g.edges()
[('a', 'ba', None), ('ab', 'ba', None), ('b', 'ab', None),
('ba', 'ab', None)]

```

```

sage: g = S.cayley_graph(side="twosided", simple=True)
sage: g.vertices()
['a', 'ab', 'b', 'ba']

```

(continues on next page)

(continued from previous page)

```
sage: g.edges()
[('a', 'ab', None), ('a', 'ba', None), ('ab', 'ba', None),
 ('b', 'ab', None), ('b', 'ba', None), ('ba', 'ab', None)]
```

```
sage: g = S.cayley_graph(side="twosided")
sage: g.vertices()
['a', 'ab', 'b', 'ba']
sage: g.edges()
[('a', 'a', (0, 'left')), ('a', 'a', (0, 'right')), ('a', 'ab', (1, 'right
→')), ('a', 'ba', (1, 'left')), ('ab', 'ab', (0, 'left')), ('ab', 'ab', (0,
→ 'right')), ('ab', 'ab', (1, 'right')), ('ab', 'ba', (1, 'left')), ('b',
→ 'ab', (0, 'left')), ('b', 'b', (1, 'left')), ('b', 'b', (1, 'right')), ('b
→', 'ba', (0, 'right')), ('ba', 'ab', (0, 'left')), ('ba', 'ba', (0, 'right
→')), ('ba', 'ba', (1, 'left')), ('ba', 'ba', (1, 'right'))]
```

```
sage: s1 = SymmetricGroup(1); s = s1.cayley_graph(); s.vertices()
[()]
```

Todo:

- Add more options for constructing subgraphs of the Cayley graph, handling the standard use cases when exploring large/infinite semigroups (a predicate, generators of an ideal, a maximal length in term of the generators)
- Specify good default layout/plot/latex options in the graph
- Generalize to combinatorial modules with module generators / operators

AUTHORS:

- Bobby Moretti (2007-08-10)
- Robert Miller (2008-05-01): editing
- Nicolas M. Thiery (2008-12): extension to semigroups, `side`, `simple`, and `elements` options, ...

magma_generators()

An alias for `semigroup_generators()`.

EXAMPLES:

```
sage: S = Semigroups().example("free"); S
An example of a semigroup: the free semigroup generated by ('a', 'b', 'c',
→ 'd')
sage: S.magma_generators()
Family ('a', 'b', 'c', 'd')
sage: S.semigroup_generators()
Family ('a', 'b', 'c', 'd')
```

prod(args)

Return the product of the list of elements `args` inside `self`.

EXAMPLES:

```
sage: S = Semigroups().example("free")
sage: S.prod([S('a'), S('b'), S('c')])
'abc'
```

(continues on next page)

(continued from previous page)

```
sage: S.prod([])
Traceback (most recent call last):
...
AssertionError: Cannot compute an empty product in a semigroup
```

regular_representation(*base_ring=None, side='left'*)

Return the regular representation of *self* over *base_ring*.

- *side* – (default: "left") whether this is the "left" or "right" regular representation

EXAMPLES:

```
sage: G = groups.permutation.Dihedral(4)
sage: G.regular_representation()
Left Regular Representation of Dihedral group of order 8
as a permutation group over Integer Ring
```

semigroup_generators()

Return distinguished semigroup generators for *self*.

OUTPUT: a family

This method is optional.

EXAMPLES:

```
sage: S = Semigroups().example("free"); S
An example of a semigroup: the free semigroup generated by ('a', 'b', 'c',
↪ 'd')
sage: S.semigroup_generators()
Family ('a', 'b', 'c', 'd')
```

subsemigroup(*generators, one=None, category=None*)

Return the multiplicative subsemigroup generated by *generators*.

INPUT:

- *generators* – a finite family of elements of *self*, or a list, iterable, ... that can be converted into one (see `Family`).
- *one* – a unit for the subsemigroup, or `None`.
- *category* – a category

This implementation lazily constructs all the elements of the semigroup, and the right Cayley graph relations between them, and uses the latter as an automaton.

See `AutomaticSemigroup` for details.

EXAMPLES:

```
sage: R = IntegerModRing(15)
sage: M = R.subsemigroup([R(3),R(5)]); M
A subsemigroup of (Ring of integers modulo 15) with 2 generators
sage: M.list()
[3, 5, 9, 0, 10, 12, 6]
```

By default, *M* is just in the category of subsemigroups:

```
sage: M in Semigroups().Subobjects()
True
```

In the following example, we specify that M is a submonoid of the finite monoid R (it shares the same unit), and a group by itself:

```
sage: M = R.subsemigroup([R(-1)],
.....: category=Monoids().Finite().Subobjects() & Groups()); M
A submonoid of (Ring of integers modulo 15) with 1 generators
sage: M.list()
[1, 14]
sage: M.one()
1
```

In the following example M is a group; however its unit does not coincide with that of R , so M is only a subsemigroup, and we need to specify its unit explicitly:

```
sage: M = R.subsemigroup([R(5)],
.....: category=Semigroups().Finite().Subobjects() & Groups()); M
Traceback (most recent call last):
...
ValueError: For a monoid which is just a subsemigroup, the unit should be_
↪specified

sage: M = R.subsemigroup([R(5)], one=R(10),
.....: category=Semigroups().Finite().Subobjects() & Groups()); M
A subsemigroup of (Ring of integers modulo 15) with 1 generators
sage: M in Groups()
True
sage: M.list()
[10, 5]
sage: M.one()
10
```

Todo:

- Fix the failure in TESTS by providing a default implementation of `__invert__` for finite groups (or even finite monoids).
- Provide a default implementation of `one` for a finite monoid, so that we would not need to specify it explicitly?

trivial_representation(*base_ring=None, side='twosided'*)

Return the trivial representation of `self` over `base_ring`.

INPUT:

- `base_ring` – (optional) the base ring; the default is \mathbb{Z}
- `side` – ignored

EXAMPLES:

```
sage: G = groups.permutation.Dihedral(4)
sage: G.trivial_representation()
Trivial representation of Dihedral group of order 8
as a permutation group over Integer Ring
```

class `Quotients`(*category, *args*)

Bases: `sage.categories.quotients.QuotientsCategory`

class `ParentMethods`

Bases: object

semigroup_generators()

Return semigroup generators for `self` by retracting the semigroup generators of the ambient semigroup.

EXAMPLES:

```
sage: S = FiniteSemigroups().Quotients().example().semigroup_
      ↪ generators() # todo: not implemented
```

example()

Return an example of quotient of a semigroup, as per `Category.example()`.

EXAMPLES:

```
sage: Semigroups().Quotients().example()
An example of a (sub)quotient semigroup: a quotient of the left zero_
      ↪ semigroup
```

RTrivial

alias of `sage.categories.r_trivial_semigroups.RTrivialSemigroups`

class SubcategoryMethods

Bases: object

Aperiodic()

Return the full subcategory of the aperiodic objects of `self`.

A (multiplicative) *semigroup* S is *aperiodic* if for any element $s \in S$, the sequence s, s^2, s^3, \dots eventually stabilizes.

In terms of variety, this can be described by the equation $s^\omega s = s$.

EXAMPLES:

```
sage: Semigroups().Aperiodic()
Category of aperiodic semigroups
```

An aperiodic semigroup is H -trivial:

```
sage: Semigroups().Aperiodic().axioms()
frozenset({'Aperiodic', 'Associative', 'HTrivial'})
```

In the finite case, the two notions coincide:

```
sage: Semigroups().Aperiodic().Finite() is Semigroups().HTrivial().Finite()
True
```

See also:

- [Wikipedia article Aperiodic_semigroup](#)
- `Semigroups.SubcategoryMethods.RTrivial`
- `Semigroups.SubcategoryMethods.LTrivial`
- `Semigroups.SubcategoryMethods.JTrivial`
- `Semigroups.SubcategoryMethods.Aperiodic`

HTrivial()

Return the full subcategory of the H -trivial objects of `self`.

Let S be (multiplicative) *semigroup*. Two elements of S are in the same H -class if they are in the same L -class and in the same R -class.

The semigroup S is *H-trivial* if all its H -classes are trivial (that is of cardinality 1).

EXAMPLES:

```
sage: C = Semigroups().HTrivial(); C
Category of h trivial semigroups
sage: Semigroups().HTrivial().Finite().example()
NotImplemented
```

See also:

- [Wikipedia article Green%27s_relations](#)
- [Semigroups.SubcategoryMethods.RTrivial](#)
- [Semigroups.SubcategoryMethods.LTrivial](#)
- [Semigroups.SubcategoryMethods.JTrivial](#)
- [Semigroups.SubcategoryMethods.Aperiodic](#)

JTrivial()

Return the full subcategory of the J -trivial objects of `self`.

Let S be (multiplicative) *semigroup*. The J -preorder \leq_J on S is defined by:

$$x \leq_J y \iff x \in SyS$$

The J -classes are the equivalence classes for the associated equivalence relation. The semigroup S is *J-trivial* if all its J -classes are trivial (that is of cardinality 1), or equivalently if the J -preorder is in fact a partial order.

EXAMPLES:

```
sage: C = Semigroups().JTrivial(); C
Category of j trivial semigroups
```

A semigroup is J -trivial if and only if it is L -trivial and R -trivial:

```
sage: sorted(C.axioms())
['Associative', 'HTrivial', 'JTrivial', 'LTrivial', 'RTrivial']
sage: Semigroups().LTrivial().RTrivial()
Category of j trivial semigroups
```

For a commutative semigroup, all three axioms are equivalent:

```
sage: Semigroups().Commutative().LTrivial()
Category of commutative j trivial semigroups
sage: Semigroups().Commutative().RTrivial()
Category of commutative j trivial semigroups
```

See also:

- [Wikipedia article Green%27s_relations](#)
- [Semigroups.SubcategoryMethods.LTrivial](#)
- [Semigroups.SubcategoryMethods.RTrivial](#)
- [Semigroups.SubcategoryMethods.HTrivial](#)

LTrivial()

Return the full subcategory of the L -trivial objects of `self`.

Let S be (multiplicative) *semigroup*. The L -preorder \leq_L on S is defined by:

$$x \leq_L y \iff x \in Sy$$

The L -classes are the equivalence classes for the associated equivalence relation. The semigroup S is L -trivial if all its L -classes are trivial (that is of cardinality 1), or equivalently if the L -preorder is in fact a partial order.

EXAMPLES:

```
sage: C = Semigroups().LTrivial(); C
Category of 1 trivial semigroups
```

A L -trivial semigroup is H -trivial:

```
sage: sorted(C.axioms())
['Associative', 'HTrivial', 'LTrivial']
```

See also:

- [Wikipedia article Green%27s_relations](#)
- `Semigroups.SubcategoryMethods.RTrivial`
- `Semigroups.SubcategoryMethods.JTrivial`
- `Semigroups.SubcategoryMethods.HTrivial`

RTrivial()

Return the full subcategory of the R -trivial objects of `self`.

Let S be (multiplicative) *semigroup*. The R -preorder \leq_R on S is defined by:

$$x \leq_R y \iff x \in yS$$

The R -classes are the equivalence classes for the associated equivalence relation. The semigroup S is R -trivial if all its R -classes are trivial (that is of cardinality 1), or equivalently if the R -preorder is in fact a partial order.

EXAMPLES:

```
sage: C = Semigroups().RTrivial(); C
Category of r trivial semigroups
```

An R -trivial semigroup is H -trivial:

```
sage: sorted(C.axioms())
['Associative', 'HTrivial', 'RTrivial']
```

See also:

- [Wikipedia article Green%27s_relations](#)
- `Semigroups.SubcategoryMethods.LTrivial`
- `Semigroups.SubcategoryMethods.JTrivial`
- `Semigroups.SubcategoryMethods.HTrivial`

class Subquotients(*category*, *args)

Bases: `sage.categories.subquotients.SubquotientsCategory`

The category of subquotient semi-groups.

EXAMPLES:

```
sage: Semigroups().Subquotients().all_super_categories()
```

```
[Category of subquotients of semigroups,
Category of semigroups,
Category of subquotients of magmas,
Category of magmas,
Category of subquotients of sets,
Category of sets,
Category of sets with partial maps,
Category of objects]
```

```
[Category of subquotients of semigroups,
Category of semigroups,
Category of subquotients of magmas,
Category of magmas,
Category of subquotients of sets,
Category of sets,
Category of sets with partial maps,
Category of objects]
```

example()

Returns an example of subquotient of a semigroup, as per *Category.example()*.

EXAMPLES:

```
sage: Semigroups().Subquotients().example()
```

```
An example of a (sub)quotient semigroup: a quotient of the left zero
↪ semigroup
```

Unital

alias of *sage.categories.monoids.Monoids*

example(*choice='leftzero', **kwds***)**

Returns an example of a semigroup, as per *Category.example()*.

INPUT:

- *choice* – str (default: 'leftzero'). Can be either 'leftzero' for the left zero semigroup, or 'free' for the free semigroup.
- ***kwds* – keyword arguments passed onto the constructor for the chosen semigroup.

EXAMPLES:

```
sage: Semigroups().example(choice='leftzero')
```

```
An example of a semigroup: the left zero semigroup
```

```
sage: Semigroups().example(choice='free')
```

```
An example of a semigroup: the free semigroup generated by ('a', 'b', 'c', 'd')
```

```
sage: Semigroups().example(choice='free', alphabet=('a', 'b'))
```

```
An example of a semigroup: the free semigroup generated by ('a', 'b')
```

3.141 Semirings

class `sage.categories.semiring.Semirings`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

The category of semirings.

A semiring $(S, +, *)$ is similar to a ring, but without the requirement that each element must have an additive inverse. In other words, it is a combination of a commutative additive monoid $(S, +)$ and a multiplicative monoid $(S, *)$, where $*$ distributes over $+$.

See also:

[Wikipedia article Semiring](#)

EXAMPLES:

```
sage: Semirings()
Category of semirings
sage: Semirings().super_categories()
[Category of associative additive commutative additive associative additive unital_
↪distributive magmas and additive magmas,
Category of monoids]

sage: sorted(Semirings().axioms())
['AdditiveAssociative', 'AdditiveCommutative', 'AdditiveUnital', 'Associative',
↪'Distributive', 'Unital']

sage: Semirings() is (CommutativeAdditiveMonoids() & Monoids()).Distributive()
True

sage: Semirings().AdditiveInverse()
Category of rings
```

3.142 Semisimple Algebras

class `sage.categories.semisimple_algebras.SemisimpleAlgebras`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of semisimple algebras over a given base ring.

EXAMPLES:

```
sage: from sage.categories.semisimple_algebras import SemisimpleAlgebras
sage: C = SemisimpleAlgebras(QQ); C
Category of semisimple algebras over Rational Field
```

This category is best constructed as:

```
sage: D = Algebras(QQ).Semisimple(); D
Category of semisimple algebras over Rational Field
sage: D is C
True
```

(continues on next page)

(continued from previous page)

```
sage: C.super_categories()
[Category of algebras over Rational Field]
```

Typically, finite group algebras are semisimple:

```
sage: DihedralGroup(5).algebra(QQ) in SemisimpleAlgebras
True
```

Unless the characteristic of the field divides the order of the group:

```
sage: DihedralGroup(5).algebra(IntegerModRing(5)) in SemisimpleAlgebras
False
```

```
sage: DihedralGroup(5).algebra(IntegerModRing(7)) in SemisimpleAlgebras
True
```

See also:

[Wikipedia article Semisimple_algebra](#)

class FiniteDimensional(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

WithBasis

alias of *sage.categories.finite_dimensional_semisimple_algebras_with_basis.FiniteDimensionalSemisimpleAlgebrasWithBasis*

class ParentMethods

Bases: object

radical_basis(***keywords*)

Return a basis of the Jacobson radical of this algebra.

- *keywords* – for compatibility; ignored.

OUTPUT: the empty list since this algebra is semisimple.

EXAMPLES:

```
sage: A = SymmetricGroup(4).algebra(QQ)
sage: A.radical_basis()
()
```

super_categories()

EXAMPLES:

```
sage: Algebras(QQ).Semisimple().super_categories()
[Category of algebras over Rational Field]
```

3.143 Sets

exception `sage.categories.sets_cat.EmptySetError`

Bases: `ValueError`

Exception raised when some operation can't be performed on the empty set.

EXAMPLES:

```
sage: def first_element(st):
.....: if not st: raise EmptySetError("no elements")
.....: else: return st[0]
sage: first_element(Set((1,2,3)))
1
sage: first_element(Set([]))
Traceback (most recent call last):
...
EmptySetError: no elements
```

class `sage.categories.sets_cat.Sets`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of sets.

The base category for collections of elements with = (equality).

This is also the category whose objects are all parents.

EXAMPLES:

```
sage: Sets()
Category of sets
sage: Sets().super_categories()
[Category of sets with partial maps]
sage: Sets().all_super_categories()
[Category of sets, Category of sets with partial maps, Category of objects]
```

Let us consider an example of set:

```
sage: P = Sets().example("inherits")
sage: P
Set of prime numbers
```

See P?? for the code.

P is in the category of sets:

```
sage: P.category()
Category of sets
```

and therefore gets its methods from the following classes:

```
sage: for cl in P.__class__.mro(): print(cl)
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Inherits_with_category'>
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Inherits'>
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Abstract'>
<class 'sage.structure.unique_representation.UniqueRepresentation'>
```

(continues on next page)

(continued from previous page)

```

<class 'sage.structure.unique_representation.CachedRepresentation'>
<type 'sage.misc.fast_methods.WithEqualityById'>
<type 'sage.structure.parent.Parent'>
<type 'sage.structure.category_object.CategoryObject'>
<type 'sage.structure.sage_object.SageObject'>
<class 'sage.categories.sets_cat.Sets.parent_class'>
<class 'sage.categories.sets_with_partial_maps.SetsWithPartialMaps.parent_class'>
<class 'sage.categories.objects.Objects.parent_class'>
<... 'object'>

```

We run some generic checks on P:

```

sage: TestSuite(P).run(verbose=True)
running ._test_an_element() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass

```

Now, we manipulate some elements of P:

```

sage: P.an_element()
47
sage: x = P(3)
sage: x.parent()
Set of prime numbers
sage: x in P, 4 in P
(True, False)
sage: x.is_prime()
True

```

They get their methods from the following classes:

```

sage: for cl in x.__class__.__mro(): print(cl)
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Inherits_with_category.
↪element_class'>
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Inherits.Element'>

```

(continues on next page)

(continued from previous page)

```

<type 'sage.rings.integer.IntegerWrapper'>
<type 'sage.rings.integer.Integer'>
<type 'sage.structure.element.EuclideanDomainElement'>
<type 'sage.structure.element.PrincipalIdealDomainElement'>
<type 'sage.structure.element.DedekindDomainElement'>
<type 'sage.structure.element.IntegralDomainElement'>
<type 'sage.structure.element.CommutativeRingElement'>
<type 'sage.structure.element.RingElement'>
<type 'sage.structure.element.ModuleElement'>
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Abstract.Element'>
<type 'sage.structure.element.Element'>
<type 'sage.structure.sage_object.SageObject'>
<class 'sage.categories.sets_cat.Sets.element_class'>
<class 'sage.categories.sets_with_partial_maps.SetsWithPartialMaps.element_class'>
<class 'sage.categories.objects.Objects.element_class'>
<... 'object'>

```

FIXME: Objects.element_class is not very meaningful ...

class Algebras(*category*, *args)

Bases: *sage.categories.algebra_functor.AlgebrasCategory*

class ParentMethods

Bases: object

construction()

Return the functorial construction of self.

EXAMPLES:

```

sage: A = GroupAlgebra(KleinFourGroup(), QQ)
sage: F, arg = A.construction(); F, arg
(GroupAlgebraFunctor, Rational Field)
sage: F(arg) is A
True

```

This also works for structures such as monoid algebras (see [trac ticket #27937](#)):

```

sage: A = FreeAbelianMonoid('x,y').algebra(QQ)
sage: F, arg = A.construction(); F, arg
(The algebra functorial construction,
Free abelian monoid on 2 generators (x, y))
sage: F(arg) is A
True

```

extra_super_categories()

EXAMPLES:

```

sage: Sets().Algebras(ZZ).super_categories()
[Category of modules with basis over Integer Ring]

sage: Sets().Algebras(QQ).extra_super_categories()
[Category of vector spaces with basis over Rational Field]

sage: Sets().example().algebra(ZZ).categories()

```

(continues on next page)

(continued from previous page)

```
[Category of set algebras over Integer Ring,
Category of modules with basis over Integer Ring,
...
Category of objects]
```

class CartesianProducts(category, *args)

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

EXAMPLES:

```
sage: C = Sets().CartesianProducts().example()
sage: C
The Cartesian product of (Set of prime numbers (basic implementation),
An example of an infinite enumerated set: the non negative integers,
An example of a finite enumerated set: {1,2,3})
sage: C.category()
Category of Cartesian products of sets
sage: C.categories()
[Category of Cartesian products of sets, Category of sets,
Category of sets with partial maps,
Category of objects]
sage: TestSuite(C).run()
```

class ElementMethods

Bases: object

cartesian_factors()

Return the Cartesian factors of self.

EXAMPLES:

```
sage: F = CombinatorialFreeModule(ZZ, [4,5]); F.__custom_name = "F"
sage: G = CombinatorialFreeModule(ZZ, [4,6]); G.__custom_name = "G"
sage: H = CombinatorialFreeModule(ZZ, [4,7]); H.__custom_name = "H"
sage: S = cartesian_product([F, G, H])
sage: x = S.monomial((0,4)) + 2 * S.monomial((0,5)) + 3 * S.monomial((1,
-6)) + 4 * S.monomial((2,4)) + 5 * S.monomial((2,7))
sage: x.cartesian_factors()
(B[4] + 2*B[5], 3*B[6], 4*B[4] + 5*B[7])
sage: [s.parent() for s in x.cartesian_factors()]
[F, G, H]
sage: S.zero().cartesian_factors()
(0, 0, 0)
sage: [s.parent() for s in S.zero().cartesian_factors()]
[F, G, H]
```

cartesian_projection(i)

Return the projection of self onto the i -th factor of the Cartesian product.

INPUT:

- i – the index of a factor of the Cartesian product

EXAMPLES:

```
sage: F = CombinatorialFreeModule(ZZ, [4,5]); F.__custom_name = "F"
sage: G = CombinatorialFreeModule(ZZ, [4,6]); G.__custom_name = "G"
```

(continues on next page)

(continued from previous page)

```

sage: S = cartesian_product([F, G])
sage: x = S.monomial((0,4)) + 2 * S.monomial((0,5)) + 3 * S.monomial((1,
↪6))
sage: x.cartesian_projection(0)
B[4] + 2*B[5]
sage: x.cartesian_projection(1)
3*B[6]

```

class ParentMethods

Bases: object

an_element()

EXAMPLES:

```

sage: C = Sets().CartesianProducts().example(); C
The Cartesian product of (Set of prime numbers (basic implementation),
An example of an infinite enumerated set: the non negative integers,
An example of a finite enumerated set: {1,2,3})
sage: C.an_element()
(47, 42, 1)

```

cardinality()

Return the cardinality of self.

EXAMPLES:

```

sage: E = FiniteEnumeratedSet([1,2,3])
sage: C = cartesian_product([E, SymmetricGroup(4)])
sage: C.cardinality()
72

sage: E = FiniteEnumeratedSet([])
sage: C = cartesian_product([E, ZZ, QQ])
sage: C.cardinality()
0

sage: C = cartesian_product([ZZ, QQ])
sage: C.cardinality()
+Infinity

sage: cartesian_product([GF(5), Permutations(10)]).cardinality()
18144000
sage: cartesian_product([GF(71)]*20).cardinality() == 71**20
True

```

cartesian_factors()

Return the Cartesian factors of self.

EXAMPLES:

```

sage: cartesian_product([QQ, ZZ, ZZ]).cartesian_factors()
(Rational Field, Integer Ring, Integer Ring)

```

cartesian_projection(*i*)Return the natural projection onto the *i*-th Cartesian factor of self.

INPUT:

- i – the index of a Cartesian factor of `self`

EXAMPLES:

```
sage: C = Sets().CartesianProducts().example(); C
The Cartesian product of (Set of prime numbers (basic implementation),
An example of an infinite enumerated set: the non negative integers,
An example of a finite enumerated set: {1,2,3})
sage: x = C.an_element(); x
(47, 42, 1)
sage: pi = C.cartesian_projection(1)
sage: pi(x)
42
```

is_empty()

Return whether this set is empty.

EXAMPLES:

```
sage: S1 = FiniteEnumeratedSet([1,2,3])
sage: S2 = Set([])
sage: cartesian_product([S1,ZZ]).is_empty()
False
sage: cartesian_product([S1,S2,S1]).is_empty()
True
```

is_finite()

Return whether this set is finite.

EXAMPLES:

```
sage: E = FiniteEnumeratedSet([1,2,3])
sage: C = cartesian_product([E, SymmetricGroup(4)])
sage: C.is_finite()
True

sage: cartesian_product([ZZ,ZZ]).is_finite()
False
sage: cartesian_product([ZZ, Set(), ZZ]).is_finite()
True
```

random_element(*args)

Return a random element of this Cartesian product.

The extra arguments are passed down to each of the factors of the Cartesian product.

EXAMPLES:

```
sage: C = cartesian_product([Permutations(10)]*5)
sage: C.random_element() # random
([2, 9, 4, 7, 1, 8, 6, 10, 5, 3],
 [8, 6, 5, 7, 1, 4, 9, 3, 10, 2],
 [5, 10, 3, 8, 2, 9, 1, 4, 7, 6],
 [9, 6, 10, 3, 2, 1, 5, 8, 7, 4],
 [8, 5, 2, 9, 10, 3, 7, 1, 4, 6])
```

(continues on next page)

(continued from previous page)

```

sage: C = cartesian_product([ZZ]*10)
sage: c1 = C.random_element()
sage: c1
(3, 1, 4, 1, 1, -3, 0, -4, -17, 2)
sage: c2 = C.random_element(4,7)
sage: c2
(6, 5, 6, 4, 5, 6, 6, 4, 5, 5)
sage: all(4 <= i < 7 for i in c2)
True

```

example()

EXAMPLES:

```

sage: Sets().CartesianProducts().example()
The Cartesian product of (Set of prime numbers (basic implementation),
An example of an infinite enumerated set: the non negative integers,
An example of a finite enumerated set: {1,2,3})

```

extra_super_categories()

A Cartesian product of sets is a set.

EXAMPLES:

```

sage: Sets().CartesianProducts().extra_super_categories()
[Category of sets]
sage: Sets().CartesianProducts().super_categories()
[Category of sets]

```

class ElementMethods

Bases: object

cartesian_product(*elements)

Return the Cartesian product of its arguments, as an element of the Cartesian product of the parents of those elements.

EXAMPLES:

```

sage: C = AlgebrasWithBasis(QQ)
sage: A = C.example()
sage: (a,b,c) = A.algebra_generators()
sage: a.cartesian_product(b, c)
B[(0, word: a)] + B[(1, word: b)] + B[(2, word: c)]

```

FIXME: is this a policy that we want to enforce on all parents?

Enumeratedalias of `sage.categories.enumerated_sets.EnumeratedSets`**Facade**alias of `sage.categories.facade_sets.FacadeSets`**Finite**alias of `sage.categories.finite_sets.FiniteSets`**class Infinite(base_category)**Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

class ParentMethods

Bases: object

cardinality()

Count the elements of the enumerated set.

EXAMPLES:

```
sage: NN = InfiniteEnumeratedSets().example()
sage: NN.cardinality()
+Infinity
```

is_empty()

Return whether this set is empty.

Since this set is infinite this always returns False.

EXAMPLES:

```
sage: C = InfiniteEnumeratedSets().example()
sage: C.is_empty()
False
```

is_finite()

Return whether this set is finite.

Since this set is infinite this always returns False.

EXAMPLES:

```
sage: C = InfiniteEnumeratedSets().example()
sage: C.is_finite()
False
```

class IsomorphicObjects(*category, *args*)Bases: *sage.categories.isomorphic_objects.IsomorphicObjectsCategory*

A category for isomorphic objects of sets.

EXAMPLES:

```
sage: Sets().IsomorphicObjects()
Category of isomorphic objects of sets
sage: Sets().IsomorphicObjects().all_super_categories()
[Category of isomorphic objects of sets,
Category of subobjects of sets, Category of quotients of sets,
Category of subquotients of sets,
Category of sets,
Category of sets with partial maps,
Category of objects]
```

class ParentMethods

Bases: object

Metricalias of *sage.categories.metric_spaces.MetricSpaces***class MorphismMethods**

Bases: object

is_injective()

Return whether this map is injective.

EXAMPLES:

```
sage: f = ZZ.hom(GF(3)); f
Natural morphism:
  From: Integer Ring
  To:   Finite Field of size 3
sage: f.is_injective()
False
```

class ParentMethods

Bases: object

CartesianProduct

alias of `sage.sets.cartesian_product.CartesianProduct`

algebra(*base_ring*, *category=None*, *kwds*)**

Return the algebra of `self` over `base_ring`.

INPUT:

- `self` – a parent S
- `base_ring` – a ring K
- `category` – a super category of the category of S , or `None`

This returns the space of formal linear combinations of elements of G with coefficients in R , endowed with whatever structure can be induced from that of S . See the documentation of `sage.categories.algebra_functor` for details.

EXAMPLES:

If S is a *group*, the result is its group algebra KS :

```
sage: S = DihedralGroup(4); S
Dihedral group of order 8 as a permutation group
sage: A = S.algebra(QQ); A
Algebra of Dihedral group of order 8 as a permutation group
over Rational Field
sage: A.category()
Category of finite group algebras over Rational Field
sage: a = A.an_element(); a
() + (1,3) + 2*(1,3)(2,4) + 3*(1,4,3,2)
```

This space is endowed with an algebra structure, obtained by extending by bilinearity the multiplication of G to a multiplication on RG :

```
sage: a * a
6*() + 4*(2,4) + 3*(1,2)(3,4) + 12*(1,2,3,4) + 2*(1,3)
+ 13*(1,3)(2,4) + 6*(1,4,3,2) + 3*(1,4)(2,3)
```

If S is a *monoid*, the result is its monoid algebra KS :

```
sage: S = Monoids().example(); S
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
sage: A = S.algebra(QQ); A
Algebra of An example of a monoid: the free monoid generated by ('a', 'b',
↪ 'c', 'd')
```

(continues on next page)

(continued from previous page)

```

    over Rational Field
sage: A.category()
Category of monoid algebras over Rational Field

```

Similarly, we can construct algebras for additive magmas, monoids, and groups.

One may specify for which category one takes the algebra; here we build the algebra of the additive group GF_3 :

```

sage: from sage.categories.additive_groups import AdditiveGroups
sage: S = GF(7)
sage: A = S.algebra(QQ, category=AdditiveGroups()); A
Algebra of Finite Field of size 7 over Rational Field
sage: A.category()
Category of finite dimensional additive group algebras
    over Rational Field

sage: a = A(S(1))
sage: a
1
sage: 1 + a * a * a
0 + 3

```

Note that the `category` keyword needs to be fed with the structure on S to be used, not the induced structure on the result.

`an_element()`

Return a (preferably typical) element of this parent.

This is used both for illustration and testing purposes. If the set `self` is empty, `an_element()` should raise the exception `EmptySetError`.

This default implementation calls `_an_element_()` and caches the result. Any parent should implement either `an_element()` or `_an_element_()`.

EXAMPLES:

```

sage: CDF.an_element()
1.0*I
sage: ZZ[['t']].an_element()
t

```

`cartesian_product(*parents, **kwargs)`

Return the Cartesian product of the parents.

INPUT:

- `parents` – a list (or other iterable) of parents.
- `category` – (default: `None`) the category the Cartesian product belongs to. If `None` is passed, then `category_from_parents()` is used to determine the category.
- `extra_category` – (default: `None`) a category that is added to the Cartesian product in addition to the categories obtained from the parents.
- other keyword arguments will be passed on to the class used for this Cartesian product (see also `CartesianProduct`).

OUTPUT:

The Cartesian product.

EXAMPLES:

```
sage: C = AlgebrasWithBasis(QQ)
sage: A = C.example(); A.rename("A")
sage: A.cartesian_product(A,A)
A (+) A (+) A
sage: ZZ.cartesian_product(GF(2), FiniteEnumeratedSet([1,2,3]))
The Cartesian product of (Integer Ring, Finite Field of size 2, {1, 2, 3})

sage: C = ZZ.cartesian_product(A); C
The Cartesian product of (Integer Ring, A)
```

construction()

Return a pair (functor, parent) such that functor(parent) returns self. If self does not have a functorial construction, return None.

EXAMPLES:

```
sage: QQ.construction()
(FractionField, Integer Ring)
sage: f, R = QQ['x'].construction()
sage: f
Poly[x]
sage: R
Rational Field
sage: f(R)
Univariate Polynomial Ring in x over Rational Field
```

is_parent_of(element)

Return whether self is the parent of element.

INPUT:

- element – any object

EXAMPLES:

```
sage: S = ZZ
sage: S.is_parent_of(1)
True
sage: S.is_parent_of(2/1)
False
```

This method differs from `__contains__()` because it does not attempt any coercion:

```
sage: 2/1 in S, S.is_parent_of(2/1)
(True, False)
sage: int(1) in S, S.is_parent_of(int(1))
(True, False)
```

some_elements()

Return a list (or iterable) of elements of self.

This is typically used for running generic tests (see `TestSuite`).

This default implementation calls `an_element()`.

EXAMPLES:


```

sage: S = Sets().example(); S
Set of prime numbers (basic implementation)
sage: S.an_element()
47
sage: S.some_elements()
[47]
sage: S = Set([])
sage: S.some_elements()
[]

```

This method should return an iterable, *not* an iterator.

class `Quotients`(*category*, **args*)

Bases: `sage.categories.quotients.QuotientsCategory`

A category for quotients of sets.

See also:

`Sets().Quotients()`

EXAMPLES:

```

sage: Sets().Quotients()
Category of quotients of sets
sage: Sets().Quotients().all_super_categories()
[Category of quotients of sets,
Category of subquotients of sets,
Category of sets,
Category of sets with partial maps,
Category of objects]

```

class `ParentMethods`

Bases: `object`

class `Realizations`(*category*, **args*)

Bases: `sage.categories.realizations.RealizationsCategory`

class `ParentMethods`

Bases: `object`

realization_of()

Return the parent this is a realization of.

EXAMPLES:

```

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: In = A.In(); In
The subset algebra of {1, 2, 3} over Rational Field in the In basis
sage: In.realization_of()
The subset algebra of {1, 2, 3} over Rational Field

```

class `SubcategoryMethods`

Bases: `object`

Algebras(*base_ring*)

Return the category of objects constructed as algebras of objects of `self` over `base_ring`.

INPUT:

- `base_ring` – a ring

See [Sets.ParentMethods.algebra\(\)](#) for the precise meaning in Sage of the *algebra of an object*.

EXAMPLES:

```
sage: Monoids().Algebras(QQ)
Category of monoid algebras over Rational Field

sage: Groups().Algebras(QQ)
Category of group algebras over Rational Field

sage: AdditiveMagmas().AdditiveAssociative().Algebras(QQ)
Category of additive semigroup algebras over Rational Field

sage: Monoids().Algebras(Rings())
Category of monoid algebras over Category of rings
```

See also:

- [algebra_functor.AlgebrasCategory](#)
- [CovariantFunctorialConstruction](#)

CartesianProducts()

Return the full subcategory of the objects of `self` constructed as Cartesian products.

See also:

- [cartesian_product.CartesianProductFunctor](#)
- [RegressiveCovariantFunctorialConstruction](#)

EXAMPLES:

```
sage: Sets().CartesianProducts()
Category of Cartesian products of sets

sage: Semigroups().CartesianProducts()
Category of Cartesian products of semigroups

sage: EuclideanDomains().CartesianProducts()
Category of Cartesian products of commutative rings
```

Enumerated()

Return the full subcategory of the enumerated objects of `self`.

An enumerated object can be iterated to get its elements.

EXAMPLES:

```
sage: Sets().Enumerated()
Category of enumerated sets

sage: Rings().Finite().Enumerated()
Category of finite enumerated rings

sage: Rings().Infinite().Enumerated()
Category of infinite enumerated rings
```

Facade()

Return the full subcategory of the facade objects of `self`.

What is a facade set?

Recall that, in Sage, *sets are modelled by *parents**, and their elements know which distinguished set they belong to. For example, the ring of integers \mathbf{Z} is modelled by the parent `ZZ`, and integers know that they belong to this set:

```
sage: ZZ
Integer Ring
sage: 42.parent()
Integer Ring
```

Sometimes, it is convenient to represent the elements of a parent P by elements of some other parent. For example, the elements of the set of prime numbers are represented by plain integers:

```
sage: Primes()
Set of all prime numbers: 2, 3, 5, 7, ...
sage: p = Primes().an_element(); p
43
sage: p.parent()
Integer Ring
```

In this case, P is called a *facade set*.

This feature is advertised through the category of P :

```
sage: Primes().category()
Category of facade infinite enumerated sets
sage: Sets().Facade()
Category of facade sets
```

Typical use cases include modeling a subset of an existing parent:

```
sage: Set([4,6,9]) # random
{4, 6, 9}
sage: Sets().Facade().example()
An example of facade set: the monoid of positive integers
```

or the union of several parents:

```
sage: Sets().Facade().example("union")
An example of a facade set: the integers completed by +-infinity
```

or endowing an existing parent with more (or less!) structure:

```
sage: Posets().example("facade")
An example of a facade poset: the positive integers ordered by divisibility
```

Let us investigate in detail a close variant of this last example: let P be set of divisors of 12 partially ordered by divisibility. There are two options for representing its elements:

1. as plain integers:

```
sage: P = Poset((divisors(12), attrcall("divides")), facade=True)
```

2. as integers, modified to be aware that their parent is P :

```
sage: Q = Poset((divisors(12), attrcall("divides")), facade=False)
```

The advantage of option 1. is that one needs not do conversions back and forth between P and \mathbf{Z} . The disadvantage is that this introduces an ambiguity when writing $2 < 3$: does this compare 2 and 3 w.r.t. the natural order on integers or w.r.t. divisibility?:

```
sage: 2 < 3
True
```

To raise this ambiguity, one needs to explicitly specify the underlying poset as in $2 <_P 3$:

```
sage: P = Posets().example("facade")
sage: P.lt(2,3)
False
```

On the other hand, with option 2. and once constructed, the elements know unambiguously how to compare themselves:

```
sage: Q(2) < Q(3)
False
sage: Q(2) < Q(6)
True
```

Beware that $P(2)$ is still the integer 2. Therefore $P(2) < P(3)$ still compares 2 and 3 as integers!:

```
sage: P(2) < P(3)
True
```

In short P being a facade parent is one of the programmatic counterparts (with e.g. coercions) of the usual mathematical idiom: “for ease of notation, we identify an element of P with the corresponding integer”. Too many identifications lead to confusion; the lack thereof leads to heavy, if not obfuscated, notations. Finding the right balance is an art, and even though there are common guidelines, it is ultimately up to the writer to choose which identifications to do. This is no different in code.

See also:

The following examples illustrate various ways to implement subsets like the set of prime numbers; look at their code for details:

```
sage: Sets().example("facade")
Set of prime numbers (facade implementation)
sage: Sets().example("inherits")
Set of prime numbers
sage: Sets().example("wrapper")
Set of prime numbers (wrapper implementation)
```

Specifications

A parent which is a facade must either:

- call `Parent.__init__()` using the facade parameter to specify a parent, or tuple thereof.
- overload the method `facade_for()`.

Note: The concept of facade parents was originally introduced in the computer algebra system MuPAD.

Finite()

Return the full subcategory of the finite objects of `self`.

EXAMPLES:

```
sage: Sets().Finite()
Category of finite sets
sage: Rings().Finite()
Category of finite rings
```

Infinite()

Return the full subcategory of the infinite objects of `self`.

EXAMPLES:

```
sage: Sets().Infinite()
Category of infinite sets
sage: Rings().Infinite()
Category of infinite rings
```

IsomorphicObjects()

Return the full subcategory of the objects of `self` constructed by isomorphism.

Given a concrete category `As()` (i.e. a subcategory of `Sets()`), `As().IsomorphicObjects()` returns the category of objects of `As()` endowed with a distinguished description as the image of some other object of `As()` by an isomorphism in this category.

See `Subquotients()` for background.

EXAMPLES:

In the following example, A is defined as the image by $x \mapsto x^2$ of the finite set $B = \{1, 2, 3\}$:

```
sage: A = FiniteEnumeratedSets().IsomorphicObjects().example(); A
The image by some isomorphism of An example of a finite enumerated set: {1,
↪2, 3}
```

Since B is a finite enumerated set, so is A :

```
sage: A in FiniteEnumeratedSets()
True
sage: A.cardinality()
3
sage: A.list()
[1, 4, 9]
```

The isomorphism from B to A is available as:

```
sage: A.retract(3)
9
```

and its inverse as:

```
sage: A.lift(9)
3
```

It often is natural to declare those morphisms as coercions so that one can do $A(b)$ and $B(a)$ to go back and forth between A and B (TODO: refer to a category example where the maps are declared as a coercion). This is not done by default. Indeed, in many cases one only wants to transport part of the structure of B to A . Assume for example, that one wants to construct the set of integers $B = \mathbb{Z}$, endowed with `max` as addition, and `+` as multiplication instead of the usual `+` and `*`. One can construct A as isomorphic to B as an infinite enumerated set. However A is *not* isomorphic to B as a ring; for example, for $a \in A$ and $a \in B$, the expressions $a + A(b)$ and $B(a) + b$ give completely different results; hence we would not want the expression $a + b$ to be implicitly resolved to any one of above two, as the coercion mechanism would do.

Coercions also cannot be used with facade parents (see [Sets.Facade](#)) like in the example above.

We now look at a category of isomorphic objects:

```
sage: C = Sets().IsomorphicObjects(); C
Category of isomorphic objects of sets

sage: C.super_categories()
[Category of subobjects of sets, Category of quotients of sets]

sage: C.all_super_categories()
[Category of isomorphic objects of sets,
 Category of subobjects of sets,
 Category of quotients of sets,
 Category of subquotients of sets,
 Category of sets,
 Category of sets with partial maps,
 Category of objects]
```

Unless something specific about isomorphic objects is implemented for this category, one actually get an optimized super category:

```
sage: C = Semigroups().IsomorphicObjects(); C
Join of Category of quotients of semigroups
and Category of isomorphic objects of sets
```

See also:

- [Subquotients\(\)](#) for background
- [isomorphic_objects.IsomorphicObjectsCategory](#)
- [RegressiveCovariantFunctorialConstruction](#)

Metric()

Return the subcategory of the metric objects of `self`.

Quotients()

Return the full subcategory of the objects of `self` constructed as quotients.

Given a concrete category `As()` (i.e. a subcategory of `Sets()`), `As().Quotients()` returns the category of objects of `As()` endowed with a distinguished description as quotient (in fact homomorphic image) of some other object of `As()`.

Implementing an object of `As().Quotients()` is done in the same way as for `As().Subquotients()`; namely by providing an ambient space and a lift and a retract map. See [Subquotients\(\)](#) for detailed instructions.

See also:

- [Subquotients\(\)](#) for background
- [quotients.QuotientsCategory](#)
- [RegressiveCovariantFunctorialConstruction](#)

EXAMPLES:

```
sage: C = Semigroups().Quotients(); C
Category of quotients of semigroups
sage: C.super_categories()
[Category of subquotients of semigroups, Category of quotients of sets]
sage: C.all_super_categories()
[Category of quotients of semigroups,
Category of subquotients of semigroups,
Category of semigroups,
Category of subquotients of magmas,
Category of magmas,
Category of quotients of sets,
Category of subquotients of sets,
Category of sets,
Category of sets with partial maps,
Category of objects]
```

The caller is responsible for checking that the given category admits a well defined category of quotients:

```
sage: EuclideanDomains().Quotients()
Join of Category of euclidean domains
and Category of subquotients of monoids
and Category of quotients of semigroups
```

Subobjects()

Return the full subcategory of the objects of `self` constructed as subobjects.

Given a concrete category `As()` (i.e. a subcategory of `Sets()`), `As().Subobjects()` returns the category of objects of `As()` endowed with a distinguished embedding into some other object of `As()`.

Implementing an object of `As().Subobjects()` is done in the same way as for `As().Subquotients()`; namely by providing an ambient space and a lift and a retract map. In the case of a trivial embedding, the two maps will typically be identity maps that just change the parent of their argument. See [Subquotients\(\)](#) for detailed instructions.

See also:

- [Subquotients\(\)](#) for background
- [subobjects.SubobjectsCategory](#)
- [RegressiveCovariantFunctorialConstruction](#)

EXAMPLES:

```
sage: C = Sets().Subobjects(); C
Category of subobjects of sets
```

```
sage: C.super_categories()
[Category of subquotients of sets]
```

```
sage: C.all_super_categories()
[Category of subobjects of sets,
Category of subquotients of sets,
Category of sets,
Category of sets with partial maps,
Category of objects]
```

Unless something specific about subobjects is implemented for this category, one actually gets an optimized super category:

```
sage: C = Semigroups().Subobjects(); C
Join of Category of subquotients of semigroups
and Category of subobjects of sets
```

The caller is responsible for checking that the given category admits a well defined category of subobjects.

Subquotients()

Return the full subcategory of the objects of `self` constructed as subquotients.

Given a concrete category `self == As()` (i.e. a subcategory of `Sets()`), `As().Subquotients()` returns the category of objects of `As()` endowed with a distinguished description as subquotient of some other object of `As()`.

EXAMPLES:

```
sage: Monoids().Subquotients()
Category of subquotients of monoids
```

A parent A in `As()` is further in `As().Subquotients()` if there is a distinguished parent B in `As()`, called the *ambient set*, a subobject B' of B , and a pair of maps:

$$l : A \rightarrow B' \text{ and } r : B' \rightarrow A$$

called respectively the *lifting map* and *retract map* such that $r \circ l$ is the identity of A and r is a morphism in `As()`.

Todo: Draw the typical commutative diagram.

It follows that, for each operation op of the category, we have some property like:

$$op_A(e) = r(op_B(l(e))), \text{ for all } e \in A$$

This allows for implementing the operations on A from those on B .

The two most common use cases are:

- *homomorphic images* (or *quotients*), when $B' = B$, r is an homomorphism from B to A (typically a canonical quotient map), and l a section of it (not necessarily a homomorphism); see `Quotients()`;

- *subjects* (up to an isomorphism), when l is an embedding from A into B ; in this case, B' is typically isomorphic to A through the inverse isomorphisms r and l ; see `Subobjects()`;

Note:

- The usual definition of “subquotient” ([Wikipedia article Subquotient](#)) does not involve the lifting map l . This map is required in Sage’s context to make the definition constructive. It is only used in computations and does not affect their results. This is relatively harmless since the category is a concrete category (i.e., its objects are sets and its morphisms are set maps).
- In mathematics, especially in the context of quotients, the retract map r is often referred to as a *projection map* instead.
- Since B' is not specified explicitly, it is possible to abuse the framework with situations where B' is not quite a subobject and r not quite a morphism, as long as the lifting and retract maps can be used as above to compute all the operations in A . Use at your own risk!

Assumptions:

- For any category `As()`, `As().Subquotients()` is a subcategory of `As()`.

Example: a subquotient of a group is a group (e.g., a left or right quotient of a group by a non-normal subgroup is not in this category).

- This construction is covariant: if `As()` is a subcategory of `Bs()`, then `As().Subquotients()` is a subcategory of `Bs().Subquotients()`.

Example: if A is a subquotient of B in the category of groups, then it is also a subquotient of B in the category of monoids.

- If the user (or a program) calls `As().Subquotients()`, then it is assumed that subquotients are well defined in this category. This is not checked, and probably never will be. Note that, if a category `As()` does not specify anything about its subquotients, then its subquotient category looks like this:

```
sage: EuclideanDomains().Subquotients()
Join of Category of euclidean domains
and Category of subquotients of monoids
```

Interface: the ambient set B of A is given by `A.ambient()`. The subset B' needs not be specified, so the retract map is handled as a partial map from B to A .

The lifting and retract map are implemented respectively as methods `A.lift(a)` and `A.retract(b)`. As a shorthand for the former, one can use alternatively `a.lift()`:

```
sage: S = Semigroups().Subquotients().example(); S
An example of a (sub)quotient semigroup: a quotient of the left zero
↪semigroup
sage: S.ambient()
An example of a semigroup: the left zero semigroup
sage: S(3).lift().parent()
An example of a semigroup: the left zero semigroup
sage: S(3) * S(1) == S.retract( S(3).lift() * S(1).lift() )
True
```

See `S?` for more.

Todo: use a more interesting example, like $\mathbb{Z}/n\mathbb{Z}$.

See also:

- `Quotients()`, `Subobjects()`, `IsomorphicObjects()`
- `subquotients.SubquotientsCategory`
- `RegressiveCovariantFunctorialConstruction`

Topological()

Return the subcategory of the topological objects of self.

class Subobjects(*category*, *args)

Bases: `sage.categories.subobjects.SubobjectsCategory`

A category for subobjects of sets.

See also:

`Sets().Subobjects()`

EXAMPLES:

```
sage: Sets().Subobjects()
Category of subobjects of sets
sage: Sets().Subobjects().all_super_categories()
[Category of subobjects of sets,
Category of subquotients of sets,
Category of sets,
Category of sets with partial maps,
Category of objects]
```

class ParentMethods

Bases: object

class Subquotients(*category*, *args)

Bases: `sage.categories.subquotients.SubquotientsCategory`

A category for subquotients of sets.

See also:

`Sets().Subquotients()`

EXAMPLES:

```
sage: Sets().Subquotients()
Category of subquotients of sets
sage: Sets().Subquotients().all_super_categories()
[Category of subquotients of sets, Category of sets,
Category of sets with partial maps,
Category of objects]
```

class ElementMethods

Bases: object

lift()

Lift self to the ambient space for its parent.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: s = S.an_element()
sage: s, s.parent()
(42, An example of a (sub)quotient semigroup: a quotient of the left_
↳ zero semigroup)
```

(continues on next page)

(continued from previous page)

```
sage: S.lift(s), S.lift(s).parent()
(42, An example of a semigroup: the left zero semigroup)
sage: s.lift(), s.lift().parent()
(42, An example of a semigroup: the left zero semigroup)
```

class ParentMethods

Bases: object

ambient()

Return the ambient space for self.

EXAMPLES:

```
sage: Semigroups().Subquotients().example().ambient()
An example of a semigroup: the left zero semigroup
```

See also:

[Sets.SubcategoryMethods.Subquotients\(\)](#) for the specifications and [lift\(\)](#) and [retract\(\)](#).

lift(*x*)Lift *x* to the ambient space for self.

INPUT:

- *x* – an element of self

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: s = S.an_element()
sage: s, s.parent()
(42, An example of a (sub)quotient semigroup: a quotient of the left_
↳ zero semigroup)
sage: S.lift(s), S.lift(s).parent()
(42, An example of a semigroup: the left zero semigroup)
sage: s.lift(), s.lift().parent()
(42, An example of a semigroup: the left zero semigroup)
```

See also:

[Sets.SubcategoryMethods.Subquotients](#) for the specifications, [ambient\(\)](#), [retract\(\)](#), and also [Sets.Subquotients.ElementMethods.lift\(\)](#).

retract(*x*)Retract *x* to self.

INPUT:

- *x* – an element of the ambient space for self

See also:

[Sets.SubcategoryMethods.Subquotients](#) for the specifications, [ambient\(\)](#), [retract\(\)](#), and also [Sets.Subquotients.ElementMethods.retract\(\)](#).

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: s = S.ambient().an_element()
```

(continues on next page)

(continued from previous page)

```

sage: s, s.parent()
(42, An example of a semigroup: the left zero semigroup)
sage: S.retract(s), S.retract(s).parent()
(42, An example of a (sub)quotient semigroup: a quotient of the left_
↳zero semigroup)

```

Topologicalalias of `sage.categories.topological_spaces.TopologicalSpaces`**class WithRealizations**(*category, *args*)Bases: `sage.categories.with_realizations.WithRealizationsCategory`**class ParentMethods**

Bases: object

class Realizations(*parent_with_realization*)Bases: `sage.categories.realizations.Category_realization_of_parent`**super_categories()**

EXAMPLES:

```

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.Realizations().super_categories()
[Category of realizations of sets]

```

a_realization()

Return a realization of self.

EXAMPLES:

```

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.a_realization()
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental_
↳basis

```

facade_for()

Return the parents self is a facade for, that is the realizations of self

EXAMPLES:

```

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.facade_for()
[The subset algebra of {1, 2, 3} over Rational Field in the Fundamental_
↳basis, The subset algebra of {1, 2, 3} over Rational Field in the In_
↳basis, The subset algebra of {1, 2, 3} over Rational Field in the Out_
↳basis]

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: f = A.F().an_element(); f
F[{}] + 2*F[{1}] + 3*F[{2}] + F[{1, 2}]
sage: i = A.In().an_element(); i

```

(continues on next page)

(continued from previous page)

```
In[{}] + 2*In[{1}] + 3*In[{2}] + In[{1, 2}]
sage: o = A.Out().an_element(); o
Out[{}] + 2*Out[{1}] + 3*Out[{2}] + Out[{1, 2}]
sage: f in A, i in A, o in A
(True, True, True)
```

inject_shorthands(*shorthands=None, verbose=True*)

Import standard shorthands into the global namespace.

INPUT:

- **shorthands** – a list (or iterable) of strings (default: `self._shorthands`) or "all" (for `self._shorthands_all`)
- **verbose** – **boolean (default True)**; whether to print the defined shorthands

EXAMPLES:

When computing with a set with multiple realizations, like `SymmetricFunctions` or `SubsetAlgebra`, it is convenient to define shorthands for the various realizations, but cumbersome to do it by hand:

```
sage: S = SymmetricFunctions(ZZ); S
Symmetric Functions over Integer Ring
sage: s = S.s(); s
Symmetric Functions over Integer Ring in the Schur basis
sage: e = S.e(); e
Symmetric Functions over Integer Ring in the elementary basis
```

This method automates the process:

```
sage: S.inject_shorthands()
Defining e as shorthand for Symmetric Functions over Integer Ring in the
↳elementary basis
Defining f as shorthand for Symmetric Functions over Integer Ring in the
↳forgotten basis
Defining h as shorthand for Symmetric Functions over Integer Ring in the
↳homogeneous basis
Defining m as shorthand for Symmetric Functions over Integer Ring in the
↳monomial basis
Defining p as shorthand for Symmetric Functions over Integer Ring in the
↳powersum basis
Defining s as shorthand for Symmetric Functions over Integer Ring in the
↳Schur basis
sage: s[1] + e[2] * p[1,1] + 2*h[3] + m[2,1]
s[1] - 2*s[1, 1, 1] + s[1, 1, 1, 1] + s[2, 1] + 2*s[2, 1, 1] + s[2, 2] +
↳2*s[3] + s[3, 1]

sage: e
Symmetric Functions over Integer Ring in the elementary basis
sage: p
Symmetric Functions over Integer Ring in the powersum basis
sage: s
Symmetric Functions over Integer Ring in the Schur basis
```

Sometimes, like for symmetric functions, one can request for all shorthands to be defined, including less common ones:

```

sage: S.inject_shorthands("all")
Defining e as shorthand for Symmetric Functions over Integer Ring in the
↳elementary basis
Defining f as shorthand for Symmetric Functions over Integer Ring in the
↳forgotten basis
Defining h as shorthand for Symmetric Functions over Integer Ring in the
↳homogeneous basis
Defining ht as shorthand for Symmetric Functions over Integer Ring in
↳the induced trivial symmetric group character basis
Defining m as shorthand for Symmetric Functions over Integer Ring in the
↳monomial basis
Defining o as shorthand for Symmetric Functions over Integer Ring in the
↳orthogonal basis
Defining p as shorthand for Symmetric Functions over Integer Ring in the
↳powersum basis
Defining s as shorthand for Symmetric Functions over Integer Ring in the
↳Schur basis
Defining sp as shorthand for Symmetric Functions over Integer Ring in
↳the symplectic basis
Defining st as shorthand for Symmetric Functions over Integer Ring in
↳the irreducible symmetric group character basis
Defining w as shorthand for Symmetric Functions over Integer Ring in the
↳Witt basis

```

The messages can be silenced by setting `verbose=False`:

```

sage: Q = QuasiSymmetricFunctions(ZZ)
sage: Q.inject_shorthands(verbose=False)

sage: F[1,2,1] + 5*M[1,3] + F[2]^2
5*F[1, 1, 1, 1] - 5*F[1, 1, 2] - 3*F[1, 2, 1] + 6*F[1, 3] +
2*F[2, 2] + F[3, 1] + F[4]

sage: F
Quasisymmetric functions over the Integer Ring in the
Fundamental basis
sage: M
Quasisymmetric functions over the Integer Ring in the
Monomial basis

```

One can also just import a subset of the shorthands:

```

sage: SQ = SymmetricFunctions(QQ)
sage: SQ.inject_shorthands(['p', 's'], verbose=False)
sage: p
Symmetric Functions over Rational Field in the powersum basis
sage: s
Symmetric Functions over Rational Field in the Schur basis

```

Note that `e` is left unchanged:

```

sage: e
Symmetric Functions over Integer Ring in the elementary basis

```

realizations()

Return all the realizations of `self` that `self` is aware of.

EXAMPLES:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.realizations()
[The subset algebra of {1, 2, 3} over Rational Field in the Fundamental_
↳basis, The subset algebra of {1, 2, 3} over Rational Field in the In_
↳basis, The subset algebra of {1, 2, 3} over Rational Field in the Out_
↳basis]
```

Note: Constructing a parent `P` in the category `A.Realizations()` automatically adds `P` to this list by calling `A._register_realization(A)`

example(*base_ring=None, set=None*)

Return an example of set with multiple realizations, as per [Category.example\(\)](#).

EXAMPLES:

```
sage: Sets().WithRealizations().example()
The subset algebra of {1, 2, 3} over Rational Field
sage: Sets().WithRealizations().example(ZZ, Set([1,2]))
The subset algebra of {1, 2} over Integer Ring
```

extra_super_categories()

A set with multiple realizations is a facade parent.

EXAMPLES:

```
sage: Sets().WithRealizations().extra_super_categories()
[Category of facade sets]
sage: Sets().WithRealizations().super_categories()
[Category of facade sets]
```

example(*choice=None*)

Return examples of objects of `Sets()`, as per [Category.example\(\)](#).

EXAMPLES:

```
sage: Sets().example()
Set of prime numbers (basic implementation)
sage: Sets().example("inherits")
Set of prime numbers
sage: Sets().example("facade")
Set of prime numbers (facade implementation)
sage: Sets().example("wrapper")
Set of prime numbers (wrapper implementation)
```

super_categories()

We include `SetsWithPartialMaps` between `Sets` and `Objects` so that we can define morphisms between sets that are only partially defined. This is also to have the `Homset` constructor not complain that `SetsWithPartialMaps` is not a supercategory of `Fields`, for example.

EXAMPLES:

```
sage: Sets().super_categories()
[Category of sets with partial maps]
```

`sage.categories.sets_cat.print_compare(x, y)`

Helper method used in `Sets.ParentMethods._test_elements_eq_symmetric()`, `Sets.ParentMethods._test_elements_eq_transitive()`.

INPUT:

- `x` – an element
- `y` – an element

EXAMPLES:

```
sage: from sage.categories.sets_cat import print_compare
sage: print_compare(1,2)
1 != 2
sage: print_compare(1,1)
1 == 1
```

3.144 Sets With a Grading

class `sage.categories.sets_with_grading.SetsWithGrading(s=None)`

Bases: `sage.categories.category.Category`

The category of sets with a grading.

A *set with a grading* is a set S equipped with a grading by some other set I (by default the set \mathbf{N} of the non-negative integers):

$$S = \bigsqcup_{i \in I} S_i$$

where the *graded components* S_i are (usually finite) sets. The *grading* function maps each element s of S to its *grade* i , so that $s \in S_i$.

From implementation point of view, if the graded set is enumerated then each graded component should be enumerated (there is a check in the method `_test_graded_components()`). The contrary needs not be true.

To implement this category, a parent must either implement `graded_component()` or `subset()`. If only `subset()` is implemented, the first argument must be the grading for compatibility with `graded_component()`. Additionally either the parent must implement `grading()` or its elements must implement a method `grade()`. See the example `sage.categories.examples.sets_with_grading.NonNegativeIntegers`.

Finally, if the graded set is enumerated (see `EnumeratedSets`) then each graded component should be enumerated. The contrary needs not be true.

EXAMPLES:

A typical example of a set with a grading is the set of non-negative integers graded by themselves:


```

sage: N = SetsWithGrading().example(); N
Non negative integers
sage: N.category()
Category of facade infinite sets with grading
sage: N.grading_set()
Non negative integers

```

The *grading function* is given by `N.grading`:

```

sage: N.grading(4)
4

```

The graded component N_i is the set with one element i :

```

sage: N.graded_component(grade=5)
{5}
sage: N.graded_component(grade=42)
{42}

```

Here are some information about this category:

```

sage: SetsWithGrading()
Category of sets with grading
sage: SetsWithGrading().super_categories()
[Category of sets]
sage: SetsWithGrading().all_super_categories()
[Category of sets with grading,
Category of sets,
Category of sets with partial maps,
Category of objects]

```

Todo:

- This should be moved to `Sets().WithGrading()`.
 - Should the grading set be a parameter for this category?
 - Does the enumeration need to be compatible with the grading? Be careful that the fact that graded components are allowed to be finite or infinite make the answer complicated.
-

class ParentMethods

Bases: object

generating_series()

Default implementation for generating series.

OUTPUT:

A series, indexed by the grading set.

EXAMPLES:

```

sage: N = SetsWithGrading().example(); N
Non negative integers
sage: N.generating_series()
1/(-z + 1)

```

graded_component(*grade*)

Return the graded component of `self` with grade `grade`.

The default implementation just calls the method `subset()` with the first argument `grade`.

EXAMPLES:

```
sage: N = SetsWithGrading().example(); N
Non negative integers
sage: N.graded_component(3)
{3}
```

grading(*elt*)

Return the grading of the element `elt` of `self`.

This default implementation calls `elt.grade()`.

EXAMPLES:

```
sage: N = SetsWithGrading().example(); N
Non negative integers
sage: N.grading(4)
4
```

grading_set()

Return the set `self` is graded by. By default, this is the set of non-negative integers.

EXAMPLES:

```
sage: SetsWithGrading().example().grading_set()
Non negative integers
```

subset(**args*, ***options*)

Return the subset of `self` described by the given parameters.

See also:

-[graded_component\(\)](#)

EXAMPLES:

```
sage: W = WeightedIntegerVectors([3,2,1]); W
Integer vectors weighted by [3, 2, 1]
sage: W.subset(4)
Integer vectors of 4 weighted by [3, 2, 1]
```

super_categories()

EXAMPLES:

```
sage: SetsWithGrading().super_categories()
[Category of sets]
```

3.145 SetsWithPartialMaps

class `sage.categories.sets_with_partial_maps.SetsWithPartialMaps`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category whose objects are sets and whose morphisms are maps that are allowed to raise a `ValueError` on some inputs.

This category is equivalent to the category of pointed sets, via the equivalence sending an object X to X union $\{\text{error}\}$, a morphism f to the morphism of pointed sets that sends x to $f(x)$ if f does not raise an error on x , or to error if it does.

EXAMPLES:

```
sage: SetsWithPartialMaps()
Category of sets with partial maps
```

```
sage: SetsWithPartialMaps().super_categories()
[Category of objects]
```

super_categories()

EXAMPLES:

```
sage: SetsWithPartialMaps().super_categories()
[Category of objects]
```

3.146 Shephard Groups

class `sage.categories.shephard_groups.ShephardGroups`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of Shephard groups.

EXAMPLES:

```
sage: from sage.categories.shephard_groups import ShephardGroups
sage: C = ShephardGroups(); C
Category of shephard groups
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.shephard_groups import ShephardGroups
sage: ShephardGroups().super_categories()
[Category of finite generalized coxeter groups]
```

3.147 Simplicial Complexes

class `sage.categories.simplicial_complexes.SimplicialComplexes`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of abstract simplicial complexes.

An abstract simplicial complex A is a collection of sets X such that:

- $\emptyset \in A$,
- if $X \subset Y \in A$, then $X \in A$.

Todo: Implement the category of simplicial complexes considered as *CW complexes* and rename this to the category of `AbstractSimplicialComplexes` with appropriate functors.

EXAMPLES:

```
sage: from sage.categories.simplicial_complexes import SimplicialComplexes
sage: C = SimplicialComplexes(); C
Category of simplicial complexes
```

class `Connected`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of connected simplicial complexes.

EXAMPLES:

```
sage: from sage.categories.simplicial_complexes import SimplicialComplexes
sage: C = SimplicialComplexes().Connected()
sage: TestSuite(C).run()
```

class `Finite`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

Category of finite simplicial complexes.

class `ParentMethods`

Bases: `object`

dimension()

Return the dimension of `self`.

EXAMPLES:

```
sage: S = SimplicialComplex([[1,3,4], [1,2],[2,5],[4,5]])
sage: S.dimension()
2
```

class `ParentMethods`

Bases: `object`

faces()

Return the faces of `self`.

EXAMPLES:

```
sage: S = SimplicialComplex([[1,3,4], [1,2],[2,5],[4,5]])
sage: S.faces()
{-1: {()},
 0: {(1,), (2,), (3,), (4,), (5,)},
 1: {(1, 2), (1, 3), (1, 4), (2, 5), (3, 4), (4, 5)},
 2: {(1, 3, 4)}}
```

facets()

Return the facets of `self`.

EXAMPLES:

```
sage: S = SimplicialComplex([[1,3,4], [1,2],[2,5],[4,5]])
sage: sorted(S.faces())
[(1, 2), (1, 3, 4), (2, 5), (4, 5)]
```

class SubcategoryMethods

Bases: `object`

Connected()

Return the full subcategory of the connected objects of `self`.

EXAMPLES:

```
sage: from sage.categories.simplicial_complexes import SimplicialComplexes
sage: SimplicialComplexes().Connected()
Category of connected simplicial complexes
```

super_categories()

Return the super categories of `self`.

EXAMPLES:

```
sage: from sage.categories.simplicial_complexes import SimplicialComplexes
sage: SimplicialComplexes().super_categories()
[Category of sets]
```

3.148 Simplicial Sets

class sage.categories.simplicial_sets.SimplicialSets(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of simplicial sets.

A simplicial set X is a collection of sets X_i , indexed by the non-negative integers, together with maps

$$\begin{aligned} d_i : X_n &\rightarrow X_{n-1}, & 0 \leq i \leq n & \text{ (face maps)} \\ s_j : X_n &\rightarrow X_{n+1}, & 0 \leq j \leq n & \text{ (degeneracy maps)} \end{aligned}$$

satisfying the *simplicial identities*:

$$\begin{aligned} d_i d_j &= d_{j-1} d_i & \text{if } i < j \\ d_i s_j &= s_{j-1} d_i & \text{if } i < j \\ d_j s_j &= 1 = d_{j+1} s_j \\ d_i s_j &= s_j d_{i-1} & \text{if } i > j + 1 \\ s_i s_j &= s_{j+1} s_i & \text{if } i \leq j \end{aligned}$$

Morphisms are sequences of maps $f_i : X_i \rightarrow Y_i$ which commute with the face and degeneracy maps.

EXAMPLES:

```
sage: from sage.categories.simplicial_sets import SimplicialSets
sage: C = SimplicialSets(); C
Category of simplicial sets
```

class Finite(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

Category of finite simplicial sets.

The objects are simplicial sets with finitely many non-degenerate simplices.

class Homsets(*category*, *args)

Bases: *sage.categories.homsets.HomsetsCategory*

class Endset(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

class ParentMethods

Bases: object

one()

Return the identity morphism in $\text{Hom}(S, S)$.

EXAMPLES:

```
sage: T = simplicial_sets.Torus()
sage: Hom(T, T).identity()
Simplicial set endomorphism of Torus
Defn: Identity map
```

class ParentMethods

Bases: object

is_finite()

Return True if this simplicial set is finite, i.e., has a finite number of nondegenerate simplices.

EXAMPLES:

```
sage: simplicial_sets.Torus().is_finite()
True
sage: C5 = groups.misc.MultiplicativeAbelian([5])
sage: simplicial_sets.ClassifyingSpace(C5).is_finite()
False
```

is_pointed()

Return True if this simplicial set is pointed, i.e., has a base point.

EXAMPLES:

```
sage: from sage.topology.simplicial_set import AbstractSimplex, ↵
↵SimplicialSet
sage: v = AbstractSimplex(0)
sage: w = AbstractSimplex(0)
sage: e = AbstractSimplex(1)
sage: X = SimplicialSet({e: (v, w)})
```

(continues on next page)

(continued from previous page)

```

sage: Y = SimplicialSet({e: (v, w)}, base_point=w)
sage: X.is_pointed()
False
sage: Y.is_pointed()
True

```

set_base_point(*point*)

Return a copy of this simplicial set in which the base point is set to *point*.

INPUT:

- *point* – a 0-simplex in this simplicial set

EXAMPLES:

```

sage: from sage.topology.simplicial_set import AbstractSimplex, SimplicialSet
sage: v = AbstractSimplex(0, name='v_0')
sage: w = AbstractSimplex(0, name='w_0')
sage: e = AbstractSimplex(1)
sage: X = SimplicialSet({e: (v, w)})
sage: Y = SimplicialSet({e: (v, w)}, base_point=w)
sage: Y.base_point()
w_0
sage: X_star = X.set_base_point(w)
sage: X_star.base_point()
w_0
sage: Y_star = Y.set_base_point(v)
sage: Y_star.base_point()
v_0

```

class Pointed(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

class Finite(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

class ParentMethods

Bases: object

fat_wedge(*n*)

Return the *n*-th fat wedge of this pointed simplicial set.

This is the subcomplex of the *n*-fold product X^n consisting of those points in which at least one factor is the base point. Thus when $n = 2$, this is the wedge of the simplicial set with itself, but when n is larger, the fat wedge is larger than the *n*-fold wedge.

EXAMPLES:

```

sage: S1 = simplicial_sets.Sphere(1)
sage: S1.fat_wedge(0)
Point
sage: S1.fat_wedge(1)
S^1
sage: S1.fat_wedge(2).fundamental_group()
Finitely presented group < e0, e1 | >
sage: S1.fat_wedge(4).homology()
{0: 0, 1: Z x Z x Z x Z, 2: Z^6, 3: Z x Z x Z x Z}

```

smash_product(*others)

Return the smash product of this simplicial set with others.

INPUT:

- others – one or several simplicial sets

EXAMPLES:

```
sage: S1 = simplicial_sets.Sphere(1)
sage: RP2 = simplicial_sets.RealProjectiveSpace(2)
sage: X = S1.smash_product(RP2)
sage: X.homology(base_ring=GF(2))
{0: Vector space of dimension 0 over Finite Field of size 2,
 1: Vector space of dimension 0 over Finite Field of size 2,
 2: Vector space of dimension 1 over Finite Field of size 2,
 3: Vector space of dimension 1 over Finite Field of size 2}

sage: T = S1.product(S1)
sage: X = T.smash_product(S1)
sage: X.homology(reduced=False)
{0: Z, 1: 0, 2: Z x Z, 3: Z}
```

unset_base_point()

Return a copy of this simplicial set in which the base point has been forgotten.

EXAMPLES:

```
sage: from sage.topology.simplicial_set import AbstractSimplex,
↳SimplicialSet
sage: v = AbstractSimplex(0, name='v_0')
sage: w = AbstractSimplex(0, name='w_0')
sage: e = AbstractSimplex(1)
sage: Y = SimplicialSet({e: (v, w)}, base_point=w)
sage: Y.is_pointed()
True
sage: Y.base_point()
w_0
sage: Z = Y.unset_base_point()
sage: Z.is_pointed()
False
```

class ParentMethods

Bases: object

base_point()

Return this simplicial set's base point

EXAMPLES:

```
sage: from sage.topology.simplicial_set import AbstractSimplex,
↳SimplicialSet
sage: v = AbstractSimplex(0, name='*')
sage: e = AbstractSimplex(1)
sage: S1 = SimplicialSet({e: (v, v)}, base_point=v)
sage: S1.is_pointed()
True
```

(continues on next page)

(continued from previous page)

```
sage: S1.base_point()
*
```

base_point_map(*domain=None*)

Return a map from a one-point space to this one, with image the base point.

This raises an error if this simplicial set does not have a base point.

INPUT:

- *domain* – optional, default `None`. Use this to specify a particular one-point space as the domain. The default behavior is to use the `sage.topology.simplicial_set.Point()` function to use a standard one-point space.

EXAMPLES:

```
sage: T = simplicial_sets.Torus()
sage: f = T.base_point_map(); f
Simplicial set morphism:
  From: Point
  To:   Torus
  Defn: Constant map at (v_0, v_0)
sage: S3 = simplicial_sets.Sphere(3)
sage: g = S3.base_point_map()
sage: f.domain() == g.domain()
True
sage: RP3 = simplicial_sets.RealProjectiveSpace(3)
sage: temp = simplicial_sets.Simplex(0)
sage: pt = temp.set_base_point(temp.n_cells(0)[0])
sage: h = RP3.base_point_map(domain=pt)
sage: f.domain() == h.domain()
False

sage: C5 = groups.misc.MultiplicativeAbelian([5])
sage: BC5 = simplicial_sets.ClassifyingSpace(C5)
sage: BC5.base_point_map()
Simplicial set morphism:
  From: Point
  To:   Classifying space of Multiplicative Abelian group isomorphic to
  ↪ C5
  Defn: Constant map at 1
```

connectivity(*max_dim=None*)

Return the connectivity of this pointed simplicial set.

INPUT:

- *max_dim* – specify a maximum dimension through which to check. This is required if this simplicial set is simply connected and not finite.

The dimension of the first nonzero homotopy group. If simply connected, this is the same as the dimension of the first nonzero homology group.

Warning: See the warning for the `is_simply_connected()` method.

The connectivity of a contractible space is `+Infinity`.

EXAMPLES:

```

sage: simplicial_sets.Sphere(3).connectivity()
2
sage: simplicial_sets.Sphere(0).connectivity()
-1
sage: K = simplicial_sets.Simplex(4)
sage: K = K.set_base_point(K.n_cells(0)[0])
sage: K.connectivity()
+Infinity
sage: X = simplicial_sets.Torus().suspension(2)
sage: X.connectivity()
2

sage: C2 = groups.misc.MultiplicativeAbelian([2])
sage: BC2 = simplicial_sets.ClassifyingSpace(C2)
sage: BC2.connectivity()
0

```

fundamental_group(*simplify=True*)

Return the fundamental group of this pointed simplicial set.

INPUT:

- *simplify* (bool, optional True) – if False, then return a presentation of the group in terms of generators and relations. If True, the default, simplify as much as GAP is able to.

Algorithm: we compute the edge-path group – see Section 19 of [Kan1958] and [Wikipedia article Fundamental_group](#). Choose a spanning tree for the connected component of the 1-skeleton containing the base point, and then the group’s generators are given by the non-degenerate edges. There are two types of relations: $e = 1$ if e is in the spanning tree, and for every 2-simplex, if its faces are e_0 , e_1 , and e_2 , then we impose the relation $e_0 e_1^{-1} e_2 = 1$, where we first set $e_i = 1$ if e_i is degenerate.

EXAMPLES:

```

sage: S1 = simplicial_sets.Sphere(1)
sage: eight = S1.wedge(S1)
sage: eight.fundamental_group() # free group on 2 generators
Finitely presented group < e0, e1 | >

```

The fundamental group of a disjoint union of course depends on the choice of base point:

```

sage: T = simplicial_sets.Torus()
sage: K = simplicial_sets.KleinBottle()
sage: X = T.disjoint_union(K)

sage: X_0 = X.set_base_point(X.n_cells(0)[0])
sage: X_0.fundamental_group().is_abelian()
True
sage: X_1 = X.set_base_point(X.n_cells(0)[1])
sage: X_1.fundamental_group().is_abelian()
False

sage: RP3 = simplicial_sets.RealProjectiveSpace(3)
sage: RP3.fundamental_group()
Finitely presented group < e | e^2 >

```

Compute the fundamental group of some classifying spaces:

```

sage: C5 = groups.misc.MultiplicativeAbelian([5])
sage: BC5 = C5.nerve()
sage: BC5.fundamental_group()
Finitely presented group < e0 | e0^5 >

sage: Sigma3 = groups.permutation.Symmetric(3)
sage: BSigma3 = Sigma3.nerve()
sage: pi = BSigma3.fundamental_group(); pi
Finitely presented group < e0, e1 | e0^2, e1^3, (e0*e1^-1)^2 >
sage: pi.order()
6
sage: pi.is_abelian()
False

```

The sphere has a trivial fundamental group:

```

sage: S2 = simplicial_sets.Sphere(2)
sage: S2.fundamental_group()
Finitely presented group < | >

```

`is_simply_connected()`

Return True if this pointed simplicial set is simply connected.

Warning: Determining simple connectivity is not always possible, because it requires determining when a group, as given by generators and relations, is trivial. So this conceivably may give a false negative in some cases.

EXAMPLES:

```

sage: T = simplicial_sets.Torus()
sage: T.is_simply_connected()
False
sage: T.suspension().is_simply_connected()
True
sage: simplicial_sets.KleinBottle().is_simply_connected()
False

sage: S2 = simplicial_sets.Sphere(2)
sage: S3 = simplicial_sets.Sphere(3)
sage: (S2.wedge(S3)).is_simply_connected()
True
sage: X = S2.disjoint_union(S3)
sage: X = X.set_base_point(X.n_cells(0)[0])
sage: X.is_simply_connected()
False

sage: C3 = groups.misc.MultiplicativeAbelian([3])
sage: BC3 = simplicial_sets.ClassifyingSpace(C3)
sage: BC3.is_simply_connected()
False

```

`class SubcategoryMethods`

Bases: object

Pointed()

A simplicial set is *pointed* if it has a distinguished base point.

EXAMPLES:

```
sage: from sage.categories.simplicial_sets import SimplicialSets
sage: SimplicialSets().Pointed().Finite()
Category of finite pointed simplicial sets
sage: SimplicialSets().Finite().Pointed()
Category of finite pointed simplicial sets
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.simplicial_sets import SimplicialSets
sage: SimplicialSets().super_categories()
[Category of sets]
```

3.149 Super Algebras

class sage.categories.super_algebras.**SuperAlgebras**(*base_category*)

Bases: *sage.categories.super_modules.SuperModulesCategory*

The category of super algebras.

An *R*-super algebra is an *R*-super module *A* endowed with an *R*-algebra structure satisfying

$$A_0 A_0 \subseteq A_0, \quad A_0 A_1 \subseteq A_1, \quad A_1 A_0 \subseteq A_1, \quad A_1 A_1 \subseteq A_0$$

and $1 \in A_0$.

EXAMPLES:

```
sage: Algebras(ZZ).Super()
Category of super algebras over Integer Ring
```

class ParentMethods

Bases: object

graded_algebra()

Return the associated graded algebra to self.

Warning: Because a super module M is naturally $\mathbf{Z}/2\mathbf{Z}$ -graded, and graded modules have a natural filtration induced by the grading, if M has a different filtration, then the associated graded module $\text{gr } M \neq M$. This is most apparent with super algebras, such as the *differential Weyl algebra*, and the multiplication may not coincide.

tensor(*parents, **kwargs)

Return the tensor product of the parents.

EXAMPLES:

```

sage: A.<x,y,z> = ExteriorAlgebra(ZZ); A.rename("A")
sage: T = A.tensor(A,A); T
A # A # A
sage: T in Algebras(ZZ).Graded().SignedTensorProducts()
True
sage: T in Algebras(ZZ).Graded().TensorProducts()
False
sage: A.rename(None)

```

This also works when the other elements do not have a signed tensor product (trac ticket #31266):

```

sage: a = SteenrodAlgebra(3).an_element()
sage: M = CombinatorialFreeModule(GF(3), ['s', 't', 'u'])
sage: s = M.basis()['s']
sage: tensor([a, s])
2*Q_1 Q_3 P(2,1) # B['s']

```

class SignedTensorProducts(category, *args)

Bases: [sage.categories.signed_tensor.SignedTensorProductsCategory](#)

extra_super_categories()

EXAMPLES:

```

sage: Coalgebras(QQ).Graded().SignedTensorProducts().extra_super_
↪categories()
[Category of graded coalgebras over Rational Field]
sage: Coalgebras(QQ).Graded().SignedTensorProducts().super_categories()
[Category of graded coalgebras over Rational Field]

```

Meaning: a signed tensor product of coalgebras is a coalgebra

class SubcategoryMethods

Bases: object

Supercommutative()

Return the full subcategory of the supercommutative objects of self.

A super algebra M is *supercommutative* if, for all homogeneous $x, y \in M$,

$$x \cdot y = (-1)^{|x||y|} y \cdot x.$$

REFERENCES:

[Wikipedia article Supercommutative_algebra](#)

EXAMPLES:

```

sage: Algebras(ZZ).Super().Supercommutative()
Category of supercommutative algebras over Integer Ring
sage: Algebras(ZZ).Super().WithBasis().Supercommutative()
Category of supercommutative algebras with basis over Integer Ring

```

Supercommutative

alias of [sage.categories.supercommutative_algebras.SupercommutativeAlgebras](#)

extra_super_categories()

EXAMPLES:

```
sage: Algebras(ZZ).Super().super_categories() # indirect doctest
[Category of graded algebras over Integer Ring,
Category of super modules over Integer Ring]
```

3.150 Super algebras with basis

```
class sage.categories.super_algebras_with_basis.SuperAlgebrasWithBasis(base_category)
Bases: sage.categories.super_modules.SuperModulesCategory
```

The category of super algebras with a distinguished basis

EXAMPLES:

```
sage: C = Algebras(ZZ).WithBasis().Super(); C
Category of super algebras with basis over Integer Ring
```

```
class ParentMethods
```

Bases: object

```
graded_algebra()
```

Return the associated graded module to self.

See [AssociatedGradedAlgebra](#) for the definition and the properties of this.

See also:

```
graded_algebra()
```

EXAMPLES:

```
sage: W.<x,y> = algebras.DifferentialWeyl(QQ)
sage: W.graded_algebra()
Graded Algebra of Differential Weyl algebra of
polynomials in x, y over Rational Field
```

```
class SignedTensorProducts(category, *args)
```

Bases: [sage.categories.signed_tensor.SignedTensorProductsCategory](#)

The category of super algebras with basis constructed by tensor product of super algebras with basis.

```
extra_super_categories()
```

EXAMPLES:

```
sage: Algebras(QQ).Super().SignedTensorProducts().extra_super_categories()
[Category of super algebras over Rational Field]
sage: Algebras(QQ).Super().SignedTensorProducts().super_categories()
[Category of signed tensor products of graded algebras over Rational Field,
Category of super algebras over Rational Field]
```

Meaning: a signed tensor product of super algebras is a super algebra

```
extra_super_categories()
```

EXAMPLES:

```

sage: C = Algebras(ZZ).WithBasis().Super()
sage: sorted(C.super_categories(), key=str) # indirect doctest
[Category of graded algebras with basis over Integer Ring,
Category of super algebras over Integer Ring,
Category of super modules with basis over Integer Ring]

```

3.151 Super Hopf algebras with basis

class `sage.categories.super_hopf_algebras_with_basis.SuperHopfAlgebrasWithBasis`(*base_category*)
 Bases: `sage.categories.super_modules.SuperModulesCategory`

The category of super Hopf algebras with a distinguished basis.

EXAMPLES:

```

sage: C = HopfAlgebras(ZZ).WithBasis().Super(); C
Category of super hopf algebras with basis over Integer Ring
sage: sorted(C.super_categories(), key=str)
[Category of super algebras with basis over Integer Ring,
Category of super coalgebras with basis over Integer Ring,
Category of super hopf algebras over Integer Ring]

```

class `ParentMethods`

Bases: `object`

antipode()

The antipode of this Hopf algebra.

If `antipode_basis()` is available, this constructs the antipode morphism from `self` to `self` by extending it by linearity. Otherwise, `self.antipode_by_coercion()` is used, if available.

EXAMPLES:

```

sage: A = SteenrodAlgebra(7)
sage: a = A.an_element()
sage: a, A.antipode(a)
(6 Q_1 Q_3 P(2,1), Q_1 Q_3 P(2,1))

```

3.152 Super Lie Conformal Algebras

AUTHORS:

- Reimundo Heluani (2019-10-05): Initial implementation.

class `sage.categories.super_lie_conformal_algebras.SuperLieConformalAlgebras`(*base_category*)
 Bases: `sage.categories.super_modules.SuperModulesCategory`

The category of super Lie conformal algebras.

EXAMPLES:

```

sage: LieConformalAlgebras(AA).Super()
Category of super Lie conformal algebras over Algebraic Real Field

```

Notice that we can force to have a *purely even* super Lie conformal algebra:

```
sage: bosondict = {'a', 'a':{1:({'K', 0):1}}}
sage: R = LieConformalAlgebra(QQ, bosondict, names=('a',),
....:                          central_elements=('K',), super=True)
sage: [g.is_even_odd() for g in R.gens()]
[0, 0]
```

class ElementMethods

Bases: object

is_even_odd()

Return 0 if this element is *even* and 1 if it is *odd*.

EXAMPLES:

```
sage: R = lie_conformal_algebras.NeveuSchwarz(QQ);
sage: R.inject_variables()
Defining L, G, C
sage: G.is_even_odd()
1
```

class Graded(base_category)

Bases: `sage.categories.graded_modules.GradedModulesCategory`

The category of H-graded super Lie conformal algebras.

EXAMPLES:

```
sage: LieConformalAlgebras(AA).Super().Graded()
Category of H-graded super Lie conformal algebras over Algebraic Real Field
```

class ParentMethods

Bases: object

example()

An example parent in this category.

EXAMPLES:

```
sage: LieConformalAlgebras(QQ).Super().example()
The Neveu-Schwarz super Lie conformal algebra over Rational Field
```

extra_super_categories()

The extra super categories of self.

EXAMPLES:

```
sage: LieConformalAlgebras(QQ).Super().super_categories()
[Category of super modules over Rational Field,
 Category of Lambda bracket algebras over Rational Field]
```


3.153 Super modules

class `sage.categories.super_modules.SuperModules`(*base_category*)

Bases: `sage.categories.super_modules.SuperModulesCategory`

The category of super modules.

An R -super module (where R is a ring) is an R -module M equipped with a decomposition $M = M_0 \oplus M_1$ into two R -submodules M_0 and M_1 (called the *even part* and the *odd part* of M , respectively).

Thus, an R -super module automatically becomes a $\mathbf{Z}/2\mathbf{Z}$ -graded R -module, with M_0 being the degree-0 component and M_1 being the degree-1 component.

EXAMPLES:

```
sage: Modules(ZZ).Super()
Category of super modules over Integer Ring
sage: Modules(ZZ).Super().super_categories()
[Category of graded modules over Integer Ring]
```

The category of super modules defines the super structure which shall be preserved by morphisms:

```
sage: Modules(ZZ).Super().additional_structure()
Category of super modules over Integer Ring
```

class `ElementMethods`

Bases: `object`

is_even()

Return if `self` is an even element.

EXAMPLES:

```
sage: cat = Algebras(QQ).WithBasis().Super()
sage: C = CombinatorialFreeModule(QQ, Partitions(), category=cat)
sage: C.degree_on_basis = sum
sage: C.basis()[2,2,1].is_even()
False
sage: C.basis()[2,2].is_even()
True
```

is_even_odd()

Return `0` if `self` is an even element or `1` if an odd element.

Note: The default implementation assumes that the even/odd is determined by the parity of `degree()`.

Overwrite this method if the even/odd behavior is desired to be independent.

EXAMPLES:

```
sage: cat = Algebras(QQ).WithBasis().Super()
sage: C = CombinatorialFreeModule(QQ, Partitions(), category=cat)
sage: C.degree_on_basis = sum
sage: C.basis()[2,2,1].is_even_odd()
1
```

(continues on next page)

(continued from previous page)

```
sage: C.basis()[2,2].is_even_odd()
0
```

is_odd()

Return if self is an odd element.

EXAMPLES:

```
sage: cat = Algebras(QQ).WithBasis().Super()
sage: C = CombinatorialFreeModule(QQ, Partitions(), category=cat)
sage: C.degree_on_basis = sum
sage: C.basis()[2,2,1].is_odd()
True
sage: C.basis()[2,2].is_odd()
False
```

class ParentMethods

Bases: object

extra_super_categories()Adds *VectorSpaces* to the super categories of self if the base ring is a field.

EXAMPLES:

```
sage: Modules(QQ).Super().extra_super_categories()
[Category of vector spaces over Rational Field]
sage: Modules(ZZ).Super().extra_super_categories()
[]
```

This makes sure that `Modules(QQ).Super()` returns an instance of *SuperModules* and not a join category of an instance of this class and of *VectorSpaces(QQ)*:

```
sage: type(Modules(QQ).Super())
<class 'sage.categories.super_modules.SuperModules_with_category'>
```

Todo: Get rid of this workaround once there is a more systematic approach for the alias `Modules(QQ) -> VectorSpaces(QQ)`. Probably the latter should be a category with axiom, and covariant constructions should play well with axioms.

super_categories()

EXAMPLES:

```
sage: Modules(ZZ).Super().super_categories()
[Category of graded modules over Integer Ring]
```

Nota bene:

```
sage: Modules(QQ).Super()
Category of super modules over Rational Field
sage: Modules(QQ).Super().super_categories()
[Category of graded modules over Rational Field]
```

class `sage.categories.super_modules.SuperModulesCategory`(*base_category*)
 Bases: `sage.categories.covariant_functorial_construction.CovariantConstructionCategory`,
`sage.categories.category_types.Category_over_base_ring`

EXAMPLES:

```
sage: C = Algebras(QQ).Super()
sage: C
Category of super algebras over Rational Field
sage: C.base_category()
Category of algebras over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of graded algebras over Rational Field,
Category of super modules over Rational Field]

sage: AlgebrasWithBasis(QQ).Super().base_ring()
Rational Field
sage: HopfAlgebrasWithBasis(QQ).Super().base_ring()
Rational Field
```

classmethod `default_super_categories`(*category*, **args*)

Return the default super categories of $F_{Cat}(A, B, \dots)$ for A, B, \dots parents in Cat .

INPUT:

- `cls` – the category class for the functor F
- `category` – a category Cat
- *`args` – further arguments for the functor

OUTPUT:

A join category.

This implements the property that subcategories constructed by the set of whitelisted axioms is a subcategory.

EXAMPLES:

```
sage: HopfAlgebras(ZZ).WithBasis().FiniteDimensional().Super() # indirect_
↳ doctest
Category of finite dimensional super hopf algebras with basis over Integer Ring
```

3.154 Super modules with basis

class `sage.categories.super_modules_with_basis.SuperModulesWithBasis`(*base_category*)

Bases: `sage.categories.super_modules.SuperModulesCategory`

The category of super modules with a distinguished basis.

An R -super module with a distinguished basis is an R -super module equipped with an R -module basis whose elements are homogeneous.

EXAMPLES:

```

sage: C = GradedModulesWithBasis(QQ); C
Category of graded vector spaces with basis over Rational Field
sage: sorted(C.super_categories(), key=str)
[Category of filtered vector spaces with basis over Rational Field,
Category of graded modules with basis over Rational Field,
Category of graded vector spaces over Rational Field]
sage: C is ModulesWithBasis(QQ).Graded()
True

```

class ElementMethods

Bases: object

even_component()

Return the even component of self.

EXAMPLES:

```

sage: Q = QuadraticForm(QQ, 2, [1,2,3])
sage: C.<x,y> = CliffordAlgebra(Q)
sage: a = x*y + x - 3*y + 4
sage: a.even_component()
x*y + 4

```

is_even_odd()

Return 0 if self is an even element and 1 if self is an odd element.

EXAMPLES:

```

sage: Q = QuadraticForm(QQ, 2, [1,2,3])
sage: C.<x,y> = CliffordAlgebra(Q)
sage: a = x + y
sage: a.is_even_odd()
1
sage: a = x*y + 4
sage: a.is_even_odd()
0
sage: a = x + 4
sage: a.is_even_odd()
Traceback (most recent call last):
...
ValueError: element is not homogeneous

sage: E.<x,y> = ExteriorAlgebra(QQ)
sage: (x*y).is_even_odd()
0

```

is_super_homogeneous()

Return whether this element is homogeneous, in the sense of a super module (i.e., is even or odd).

EXAMPLES:

```

sage: Q = QuadraticForm(QQ, 2, [1,2,3])
sage: C.<x,y> = CliffordAlgebra(Q)
sage: a = x + y
sage: a.is_super_homogeneous()

```

(continues on next page)

(continued from previous page)

```

True
sage: a = x*y + 4
sage: a.is_super_homogeneous()
True
sage: a = x*y + x - 3*y + 4
sage: a.is_super_homogeneous()
False

```

The exterior algebra has a \mathbf{Z} grading, which induces the $\mathbf{Z}/2\mathbf{Z}$ grading. However the definition of homogeneous elements differs because of the different gradings:

```

sage: E.<x,y> = ExteriorAlgebra(QQ)
sage: a = x*y + 4
sage: a.is_super_homogeneous()
True
sage: a.is_homogeneous()
False

```

odd_component()

Return the odd component of self.

EXAMPLES:

```

sage: Q = QuadraticForm(QQ, 2, [1,2,3])
sage: C.<x,y> = CliffordAlgebra(Q)
sage: a = x*y + x - 3*y + 4
sage: a.odd_component()
x - 3*y

```

class ParentMethods

Bases: object

3.155 Supercommutative Algebras

class sage.categories.supercommutative_algebras.**SupercommutativeAlgebras**(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring*

The category of supercommutative algebras.

An *R*-supercommutative algebra is an *R*-super algebra $A = A_0 \oplus A_1$ endowed with an *R*-super algebra structure satisfying:

$$x_0 x'_0 = x'_0 x_0, \quad x_1 x'_1 = -x'_1 x_1, \quad x_0 x_1 = x_1 x_0,$$

for all $x_0, x'_0 \in A_0$ and $x_1, x'_1 \in A_1$.

EXAMPLES:

```

sage: Algebras(ZZ).Supercommutative()
Category of supercommutative algebras over Integer Ring

```

class SignedTensorProducts(*category, *args*)

Bases: *sage.categories.signed_tensor.SignedTensorProductsCategory*

extra_super_categories()

Return the extra super categories of `self`.

A signed tensor product of supercommutative algebras is a supercommutative algebra.

EXAMPLES:

```
sage: C = Algebras(ZZ).Supercommutative().SignedTensorProducts()
sage: C.extra_super_categories()
[Category of supercommutative algebras over Integer Ring]
```

class WithBasis(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring*

class ParentMethods

Bases: object

3.156 Supercrystals

class `sage.categories.supercrystals.SuperCrystals`(*s=None*)

Bases: *sage.categories.category_singleton.Category_singleton*

class `Finite`(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom_singleton*

class `ElementMethods`

Bases: object

is_genuine_highest_weight(*index_set=None*)

Return whether `self` is a genuine highest weight element.

INPUT:

- `index_set` – (optional) the index set of the (sub)crystal on which to check

EXAMPLES:

```
sage: B = crystals.Tableaux(['A', [1,1]], shape=[3,2,1])
sage: for b in B.highest_weight_vectors():
....:     print("{} {}".format(b, b.is_genuine_highest_weight()))
[[-2, -2, -2], [-1, -1], [1]] True
[[-2, -2, -2], [-1, 2], [1]] False
[[-2, -2, 2], [-1, -1], [1]] False
sage: [b for b in B if b.is_genuine_highest_weight([-1,0])]
[[[-2, -2, -2], [-1, -1], [1]],
 [[-2, -2, -2], [-1, -1], [2]],
 [[-2, -2, -2], [-1, 2], [2]],
 [[-2, -2, 2], [-1, -1], [2]],
 [[-2, -2, 2], [-1, 2], [2]],
 [[-2, -2, -2], [-1, 2], [1]],
 [[-2, -2, 2], [-1, -1], [1]],
 [[-2, -2, 2], [-1, 2], [1]]]
```

is_genuine_lowest_weight(*index_set=None*)

Return whether `self` is a genuine lowest weight element.

INPUT:

- `index_set` – (optional) the index set of the (sub)crystal on which to check

EXAMPLES:

```

sage: B = crystals.Tableaux(['A', [1,1]], shape=[3,2,1])
sage: for b in sorted(B.lowest_weight_vectors()):
.....:     print("{} {}".format(b, b.is_genuine_lowest_weight()))
[[-2, 1, 2], [-1, 2], [1]] False
[[-2, 1, 2], [-1, 2], [2]] False
[[-1, 1, 2], [1, 2], [2]] True
sage: [b for b in B if b.is_genuine_lowest_weight([-1,0])]
[[[-2, -1, 1], [-1, 1], [1]],
 [[-2, -1, 1], [-1, 1], [2]],
 [[-2, 1, 2], [-1, 1], [2]],
 [[-2, 1, 2], [-1, 1], [1]],
 [[-1, -1, 1], [1, 2], [2]],
 [[-1, -1, 1], [1, 2], [1]],
 [[-1, 1, 2], [1, 2], [2]],
 [[-1, 1, 2], [1, 2], [1]]]

```

class ParentMethods

Bases: object

character()Return the character of `self`.

Todo: Once the *WeylCharacterRing* is implemented, make this consistent with the implementation in `sage.categories.classical_crystals.ClassicalCrystals.ParentMethods.character()`.

EXAMPLES:

```

sage: B = crystals.Letters(['A', [1,2]])
sage: B.character()
B[(1, 0, 0, 0, 0)] + B[(0, 1, 0, 0, 0)] + B[(0, 0, 1, 0, 0)]
+ B[(0, 0, 0, 1, 0)] + B[(0, 0, 0, 0, 1)]

```

connected_components()Return the connected components of `self` as subcrystals.

EXAMPLES:

```

sage: B = crystals.Letters(['A', [1,2]])
sage: B.connected_components()
[Subcrystal of The crystal of letters for type ['A', [1, 2]]]

sage: T = B.tensor(B)
sage: T.connected_components()
[Subcrystal of Full tensor product of the crystals
 [The crystal of letters for type ['A', [1, 2]],
  The crystal of letters for type ['A', [1, 2]]],
 Subcrystal of Full tensor product of the crystals
 [The crystal of letters for type ['A', [1, 2]],
  The crystal of letters for type ['A', [1, 2]]]]

```

connected_components_generators()Return the tuple of genuine highest weight elements of `self`.

EXAMPLES:

```

sage: B = crystals.Letters(['A', [1,2]])
sage: B.genuine_highest_weight_vectors()
(-2,)

sage: T = B.tensor(B)
sage: T.genuine_highest_weight_vectors()
([-2, -1], [-2, -2])
sage: s1, s2 = T.connected_components()
sage: s = s1 + s2
sage: s.genuine_highest_weight_vectors()
([-2, -1], [-2, -2])

```

digraph(*index_set=None*)

Return the `DiGraph` associated to `self`.

EXAMPLES:

```

sage: B = crystals.Letters(['A', [1,3]])
sage: G = B.digraph(); G
Multi-digraph on 6 vertices
sage: Q = crystals.Letters(['Q', 3])
sage: G = Q.digraph(); G
Multi-digraph on 3 vertices
sage: G.edges()
[(1, 2, -1), (1, 2, 1), (2, 3, -2), (2, 3, 2)]

```

The edges of the crystal graph are by default colored using blue for edge 1, red for edge 2, green for edge 3, and dashed with the corresponding color for barred edges. Edge 0 is dotted black:

```

sage: view(G) # optional - dot2tex graphviz, not tested (opens external_
↪window)

```

genuine_highest_weight_vectors()

Return the tuple of genuine highest weight elements of `self`.

EXAMPLES:

```

sage: B = crystals.Letters(['A', [1,2]])
sage: B.genuine_highest_weight_vectors()
(-2,)

sage: T = B.tensor(B)
sage: T.genuine_highest_weight_vectors()
([-2, -1], [-2, -2])
sage: s1, s2 = T.connected_components()
sage: s = s1 + s2
sage: s.genuine_highest_weight_vectors()
([-2, -1], [-2, -2])

```

genuine_lowest_weight_vectors()

Return the tuple of genuine lowest weight elements of `self`.

EXAMPLES:


```

sage: B = crystals.Letters(['A', [1,2]])
sage: B.genuine_lowest_weight_vectors()
(3,)

sage: T = B.tensor(B)
sage: T.genuine_lowest_weight_vectors()
([3, 3], [3, 2])
sage: s1, s2 = T.connected_components()
sage: s = s1 + s2
sage: s.genuine_lowest_weight_vectors()
([3, 3], [3, 2])

```

highest_weight_vectors()

Return the highest weight vectors of `self`.

EXAMPLES:

```

sage: B = crystals.Letters(['A', [1,2]])
sage: B.highest_weight_vectors()
(-2,)

sage: T = B.tensor(B)
sage: T.highest_weight_vectors()
([-2, -2], [-2, -1])

```

We give an example from [BKK2000] that has fake highest weight vectors:

```

sage: B = crystals.Tableaux(['A', [1,1]], shape=[3,2,1])
sage: B.highest_weight_vectors()
([[[-2, -2, -2], [-1, -1], [1]],
  [[-2, -2, -2], [-1, 2], [1]],
  [[-2, -2, 2], [-1, -1], [1]])]
sage: B.genuine_highest_weight_vectors()
([[[-2, -2, -2], [-1, -1], [1]],])

```

lowest_weight_vectors()

Return the lowest weight vectors of `self`.

EXAMPLES:

```

sage: B = crystals.Letters(['A', [1,2]])
sage: B.lowest_weight_vectors()
(3,)

sage: T = B.tensor(B)
sage: sorted(T.lowest_weight_vectors())
[[3, 2], [3, 3]]

```

We give an example from [BKK2000] that has fake lowest weight vectors:

```

sage: B = crystals.Tableaux(['A', [1,1]], shape=[3,2,1])
sage: sorted(B.lowest_weight_vectors())
[[[-2, 1, 2], [-1, 2], [1]],
  [[-2, 1, 2], [-1, 2], [2]],]

```

(continues on next page)

(continued from previous page)

```

[[-1, 1, 2], [1, 2], [2]]]
sage: B.genuine_lowest_weight_vectors()
([[-1, 1, 2], [1, 2], [2]],)

```

class ParentMethods

Bases: object

tensor(*crystals, **options)

Return the tensor product of self with the crystals B.

EXAMPLES:

```

sage: B = crystals.Letters(['A', [1,2]])
sage: C = crystals.Tableaux(['A', [1,2]], shape = [2,1])
sage: T = C.tensor(B); T
Full tensor product of the crystals [Crystal of BKK tableaux of shape [2, ↵
↵1] of gl(2|3),
The crystal of letters for type ['A', [1, 2]]]
sage: S = B.tensor(C); S
Full tensor product of the crystals [The crystal of letters for type ['A', ↵
↵[1, 2]],
Crystal of BKK tableaux of shape [2, 1] of gl(2|3)]
sage: G = T.digraph()
sage: H = S.digraph()
sage: G.is_isomorphic(H, edge_labels= True)
True

```

class TensorProducts(category, *args)Bases: *sage.categories.tensor.TensorProductsCategory*

The category of regular crystals constructed by tensor product of regular crystals.

extra_super_categories()

EXAMPLES:

```

sage: from sage.categories.supercrystals import SuperCrystals
sage: SuperCrystals().TensorProducts().extra_super_categories()
[Category of super crystals]

```

super_categories()

EXAMPLES:

```

sage: from sage.categories.supercrystals import SuperCrystals
sage: C = SuperCrystals()
sage: C.super_categories()
[Category of crystals]

```

3.157 Topological Spaces

class `sage.categories.topological_spaces.TopologicalSpaces`(*category*, **args*)
 Bases: `sage.categories.topological_spaces.TopologicalSpacesCategory`

The category of topological spaces.

EXAMPLES:

```
sage: Sets().Topological()
Category of topological spaces
sage: Sets().Topological().super_categories()
[Category of sets]
```

The category of topological spaces defines the topological structure, which shall be preserved by morphisms:

```
sage: Sets().Topological().additional_structure()
Category of topological spaces
```

class `CartesianProducts`(*category*, **args*)
 Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

extra_super_categories()

Implement the fact that a (finite) Cartesian product of topological spaces is a topological space.

EXAMPLES:

```
sage: from sage.categories.topological_spaces import TopologicalSpaces
sage: C = TopologicalSpaces().CartesianProducts()
sage: C.extra_super_categories()
[Category of topological spaces]
sage: C.super_categories()
[Category of Cartesian products of sets, Category of topological spaces]
sage: C.axioms()
frozenset()
```

class `Compact`(*base_category*)
 Bases: `sage.categories.category_with_axiom.CategoryWithAxiom`

The category of compact topological spaces.

class `CartesianProducts`(*category*, **args*)
 Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

extra_super_categories()

Implement the fact that a (finite) Cartesian product of compact topological spaces is compact.

EXAMPLES:

```
sage: from sage.categories.topological_spaces import TopologicalSpaces
sage: C = TopologicalSpaces().Compact().CartesianProducts()
sage: C.extra_super_categories()
[Category of compact topological spaces]
sage: C.super_categories()
[Category of Cartesian products of topological spaces,
 Category of compact topological spaces]
sage: C.axioms()
frozenset({'Compact'})
```

class `Connected`(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiom*

The category of connected topological spaces.

class `CartesianProducts`(*category*, **args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

extra_super_categories()

Implement the fact that a (finite) Cartesian product of connected topological spaces is connected.

EXAMPLES:

```
sage: from sage.categories.topological_spaces import TopologicalSpaces
sage: C = TopologicalSpaces().Connected().CartesianProducts()
sage: C.extra_super_categories()
[Category of connected topological spaces]
sage: C.super_categories()
[Category of Cartesian products of topological spaces,
Category of connected topological spaces]
sage: C.axioms()
frozenset({'Connected'})
```

class `SubcategoryMethods`

Bases: `object`

Compact()

Return the subcategory of the compact objects of `self`.

EXAMPLES:

```
sage: Sets().Topological().Compact()
Category of compact topological spaces
```

Connected()

Return the full subcategory of the connected objects of `self`.

EXAMPLES:

```
sage: Sets().Topological().Connected()
Category of connected topological spaces
```

class `sage.categories.topological_spaces.TopologicalSpacesCategory`(*category*, **args*)

Bases: *sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory*

3.158 Kac-Moody Algebras With Triangular Decomposition Basis

AUTHORS:

- Travis Scrimshaw (07-15-2017): Initial implementation

class `sage.categories.triangular_kac_moody_algebras.TriangularKacMoodyAlgebras`(*base*,
name=None)

Bases: *sage.categories.category_types.Category_over_base_ring*

Category of Kac-Moody algebras with a distinguished basis that respects the triangular decomposition.

We require that the grading group is the root lattice of the appropriate Cartan type.

class ElementMethods

Bases: object

part()Return whether the element v is in the lower, zero, or upper part of `self`.

OUTPUT:

-1 if v is in the lower part, 0 if in the zero part, or 1 if in the upper part

EXAMPLES:

```

sage: L = LieAlgebra(QQ, cartan_type="F4")
sage: L.inject_variables()
Defining e1, e2, e3, e4, f1, f2, f3, f4, h1, h2, h3, h4
sage: e1.part()
1
sage: f4.part()
-1
sage: (h2 + h3).part()
0
sage: (f1.bracket(f2) + 4*f4).part()
-1
sage: (e1 + f1).part()
Traceback (most recent call last):
...
ValueError: element is not in one part

```

class ParentMethods

Bases: object

e($i=None$)Return the generators e of `self`.

INPUT:

- i – (optional) if specified, return just the generator e_i

EXAMPLES:

```

sage: L = lie_algebras.so(QQ, 5)
sage: L.e()
Finite family {1: E[alpha[1]], 2: E[alpha[2]]}
sage: L.e(1)
E[alpha[1]]

```

f($i=None$)Return the generators f of `self`.

INPUT:

- i – (optional) if specified, return just the generator f_i

EXAMPLES:

```

sage: L = lie_algebras.so(QQ, 5)
sage: L.f()
Finite family {1: E[-alpha[1]], 2: E[-alpha[2]]}
sage: L.f(1)
E[-alpha[1]]

```

verma_module(*la*, *basis_key=None*, ***kws*)
Return the Verma module with highest weight *la* over *self*.

INPUT:

- *basis_key* – (optional) a key function for the indexing set of the basis elements of *self*

EXAMPLES:

```
sage: L = lie_algebras.sl(QQ, 3)
sage: P = L.cartan_type().root_system().weight_lattice()
sage: La = P.fundamental_weights()
sage: M = L.verma_module(La[1]+La[2])
sage: M
Verma module with highest weight Lambda[1] + Lambda[2]
of Lie algebra of ['A', 2] in the Chevalley basis
```

super_categories()

EXAMPLES:

```
sage: from sage.categories.triangular_kac_moody_algebras import _
↳TriangularKacMoodyAlgebras
sage: TriangularKacMoodyAlgebras(QQ).super_categories()
[Join of Category of graded lie algebras with basis over Rational Field
and Category of kac moody algebras over Rational Field]
```

3.159 Unique factorization domains

class `sage.categories.unique_factorization_domains.UniqueFactorizationDomains`(*s=None*)

Bases: `sage.categories.category_singleton.Category_singleton`

The category of unique factorization domains constructive unique factorization domains, i.e. where one can constructively factor members into a product of a finite number of irreducible elements

EXAMPLES:

```
sage: UniqueFactorizationDomains()
Category of unique factorization domains
sage: UniqueFactorizationDomains().super_categories()
[Category of gcd domains]
```

class `ElementMethods`

Bases: `object`

radical(**args*, ***kws*)

Return the radical of this element, i.e. the product of its irreducible factors.

This default implementation calls `squarefree_decomposition` if available, and `factor` otherwise.

See also:

[`squarefree_part\(\)`](#)

EXAMPLES:

```
sage: Pol.<x> = QQ[]
sage: (x^2*(x-1)^3).radical()
x^2 - x
```

(continues on next page)

(continued from previous page)

```

sage: pol = 37 * (x-1)^3 * (x-2)^2 * (x-1/3)^7 * (x-3/7)
sage: pol.radical()
37*x^4 - 2923/21*x^3 + 1147/7*x^2 - 1517/21*x + 74/7

sage: Integer(10).radical()
10
sage: Integer(-100).radical()
10
sage: Integer(0).radical()
Traceback (most recent call last):
...
ArithmeticError: Radical of 0 not defined.

```

The next example shows how to compute the radical of a number, assuming no prime > 100000 has exponent > 1 in the factorization:

```

sage: n = 2^1000-1; n / radical(n, limit=100000)
125

```

squarefree_part()

Return the square-free part of this element, i.e. the product of its irreducible factors appearing with odd multiplicity.

This default implementation calls `squarefree_decomposition`.

See also:

`radical()`

EXAMPLES:

```

sage: Pol.<x> = QQ[]
sage: (x^2*(x-1)^3).squarefree_part()
x - 1
sage: pol = 37 * (x-1)^3 * (x-2)^2 * (x-1/3)^7 * (x-3/7)
sage: pol.squarefree_part()
37*x^3 - 1369/21*x^2 + 703/21*x - 37/7

```

class ParentMethods

Bases: object

is_unique_factorization_domain(*proof=True*)

Return True, since this is an object of the category of unique factorization domains.

EXAMPLES:

```

sage: Parent(QQ, category=UniqueFactorizationDomains()).is_unique_
↪ factorization_domain()
True

```

additional_structure()

Return whether `self` is a structure category.

See also:

`Category.additional_structure()`

The category of unique factorization domains does not define additional structure: a ring morphism between unique factorization domains is a unique factorization domain morphism.

EXAMPLES:

```
sage: UniqueFactorizationDomains().additional_structure()
```

super_categories()

EXAMPLES:

```
sage: UniqueFactorizationDomains().super_categories()
[Category of gcd domains]
```

3.160 Unital algebras

class `sage.categories.unital_algebras.UnitalAlgebras`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

The category of non-associative algebras over a given base ring.

A non-associative algebra over a ring R is a module over R which is also a unital magma.

Warning: Until [trac ticket #15043](#) is implemented, `Algebras` is the category of associative unital algebras; thus, unlike the name suggests, `UnitalAlgebras` is not a subcategory of `Algebras` but of `MagmaticAlgebras`.

EXAMPLES:

```
sage: from sage.categories.unital_algebras import UnitalAlgebras
sage: C = UnitalAlgebras(ZZ); C
Category of unital algebras over Integer Ring
```

class `ParentMethods`

Bases: `object`

from_base_ring(*r*)

Return the canonical embedding of *r* into self.

INPUT:

- *r* – an element of `self.base_ring()`

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example(); A
An example of an algebra with basis: the free algebra on the generators ('a
↪', 'b', 'c') over Rational Field
sage: A.from_base_ring(1)
B[word: ]
```

class `WithBasis`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing`

class `ParentMethods`

Bases: `object`

from_base_ring(*r*)

from_base_ring_from_one_basis(*r*)

Implement the canonical embedding from the ground ring.

INPUT:

- *r* – an element of the coefficient ring

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example()
sage: A.from_base_ring_from_one_basis(3)
3*B[word: ]
sage: A.from_base_ring(3)
3*B[word: ]
sage: A(3)
3*B[word: ]
```

one()

Return the multiplicative unit element.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example()
sage: A.one_basis()
word:
sage: A.one()
B[word: ]
```

one_basis()

When the one of an algebra with basis is an element of this basis, this optional method can return the index of this element. This is used to provide a default implementation of `one()`, and an optimized default implementation of `from_base_ring()`.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example()
sage: A.one_basis()
word:
sage: A.one()
B[word: ]
sage: A.from_base_ring(4)
4*B[word: ]
```

one_from_one_basis()

Return the one of the algebra, as per `Monoids.ParentMethods.one()`

By default, this is implemented from `one_basis()`, if available.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example()
sage: A.one_basis()
word:
sage: A.one_from_one_basis()
B[word: ]
sage: A.one()
B[word: ]
```

Even if called in the wrong order, they should returns their respective one:

```
sage: Bone().parent() is B
True
sage: Aone().parent() is A
True
```

3.161 Vector Bundles

class `sage.categories.vector_bundles.VectorBundles`(*base_space*, *base_field*, *name=None*)

Bases: `sage.categories.category_types.Category_over_base_ring`

The category of vector bundles over any base space and base field.

See also:

`TopologicalVectorBundle`

EXAMPLES:

```
sage: M = Manifold(2, 'M', structure='top')
sage: from sage.categories.vector_bundles import VectorBundles
sage: C = VectorBundles(M, RR); C
Category of vector bundles over Real Field with 53 bits of precision
with base space 2-dimensional topological manifold M
sage: C.super_categories()
[Category of topological spaces]
```

class `Differentiable`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

The category of differentiable vector bundles.

A differentiable vector bundle is a differentiable manifold with differentiable surjective projection on a differentiable base space.

class `Smooth`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_over_base_ring`

The category of smooth vector bundles.

A smooth vector bundle is a smooth manifold with smooth surjective projection on a smooth base space.

class `SubcategoryMethods`

Bases: `object`

Differentiable()

Return the subcategory of the differentiable objects of `self`.

EXAMPLES:

```
sage: M = Manifold(2, 'M')
sage: from sage.categories.vector_bundles import VectorBundles
sage: VectorBundles(M, RR).Differentiable()
Category of differentiable vector bundles over Real Field with
53 bits of precision with base space 2-dimensional
differentiable manifold M
```

Smooth()

Return the subcategory of the smooth objects of self.

EXAMPLES:

```
sage: M = Manifold(2, 'M')
sage: from sage.categories.vector_bundles import VectorBundles
sage: VectorBundles(M, RR).Smooth()
Category of smooth vector bundles over Real Field with 53 bits
of precision with base space 2-dimensional differentiable
manifold M
```

base_space()

Return the base space of this category.

EXAMPLES:

```
sage: M = Manifold(2, 'M', structure='top')
sage: from sage.categories.vector_bundles import VectorBundles
sage: VectorBundles(M, RR).base_space()
2-dimensional topological manifold M
```

super_categories()

EXAMPLES:

```
sage: M = Manifold(2, 'M')
sage: from sage.categories.vector_bundles import VectorBundles
sage: VectorBundles(M, RR).super_categories()
[Category of topological spaces]
```

3.162 Vector Spaces

class `sage.categories.vector_spaces.VectorSpaces(K)`

Bases: `sage.categories.category_types.Category_module`

The category of (abstract) vector spaces over a given field

??? with an embedding in an ambient vector space ???

EXAMPLES:

```
sage: VectorSpaces(QQ)
Category of vector spaces over Rational Field
sage: VectorSpaces(QQ).super_categories()
[Category of modules over Rational Field]
```

class `CartesianProducts(category, *args)`

Bases: `sage.categories.cartesian_product.CartesianProductsCategory`

extra_super_categories()

The category of vector spaces is closed under Cartesian products:

```
sage: C = VectorSpaces(QQ)
sage: C.CartesianProducts()
Category of Cartesian products of vector spaces over Rational Field
```

(continues on next page)

(continued from previous page)

```
sage: C in C.CartesianProducts().super_categories()
True
```

class DualObjects(*category, *args*)

Bases: *sage.categories.dual.DualObjectsCategory*

extra_super_categories()

Returns the dual category

EXAMPLES:

The category of algebras over the Rational Field is dual to the category of coalgebras over the same field:

```
sage: C = VectorSpaces(QQ)
sage: C.dual()
Category of duals of vector spaces over Rational Field
sage: C.dual().super_categories() # indirect doctest
[Category of vector spaces over Rational Field]
```

class ElementMethods

Bases: object

class Filtered(*base_category*)

Bases: *sage.categories.filtered_modules.FilteredModulesCategory*

Category of filtered vector spaces.

class Graded(*base_category*)

Bases: *sage.categories.graded_modules.GradedModulesCategory*

Category of graded vector spaces.

class ParentMethods

Bases: object

dimension()

Return the dimension of this vector space.

EXAMPLES:

```
sage: M = FreeModule(FiniteField(19), 100)
sage: W = M.submodule([M.gen(50)])
sage: W.dimension()
1

sage: M = FiniteRankFreeModule(QQ, 3)
sage: M.dimension()
3
sage: M.tensor_module(1,2).dimension()
27
```

class TensorProducts(*category, *args*)

Bases: *sage.categories.tensor.TensorProductsCategory*

extra_super_categories()

The category of vector spaces is closed under tensor products:

```

sage: C = VectorSpaces(QQ)
sage: C.TensorProducts()
Category of tensor products of vector spaces over Rational Field
sage: C in C.TensorProducts().super_categories()
True

```

class WithBasis(*base_category*)

Bases: *sage.categories.category_with_axiom.CategoryWithAxiomOverBaseRing*

class CartesianProducts(*category, *args*)

Bases: *sage.categories.cartesian_product.CartesianProductsCategory*

extra_super_categories()

The category of vector spaces with basis is closed under Cartesian products:

```

sage: C = VectorSpaces(QQ).WithBasis()
sage: C.CartesianProducts()
Category of Cartesian products of vector spaces with basis over Rational
↳Field
sage: C in C.CartesianProducts().super_categories()
True

```

class Filtered(*base_category*)

Bases: *sage.categories.filtered_modules.FilteredModulesCategory*

Category of filtered vector spaces with basis.

example(*base_ring=None*)

Return an example of a graded vector space with basis, as per *Category.example()*.

EXAMPLES:

```

sage: Modules(QQ).WithBasis().Graded().example()
An example of a graded module with basis:
the free module on partitions over Rational Field

```

class Graded(*base_category*)

Bases: *sage.categories.graded_modules.GradedModulesCategory*

Category of graded vector spaces with basis.

example(*base_ring=None*)

Return an example of a graded vector space with basis, as per *Category.example()*.

EXAMPLES:

```

sage: Modules(QQ).WithBasis().Graded().example()
An example of a graded module with basis:
the free module on partitions over Rational Field

```

class TensorProducts(*category, *args*)

Bases: *sage.categories.tensor.TensorProductsCategory*

extra_super_categories()

The category of vector spaces with basis is closed under tensor products:

```

sage: C = VectorSpaces(QQ).WithBasis()
sage: C.TensorProducts()

```

(continues on next page)

(continued from previous page)

```
Category of tensor products of vector spaces with basis over Rational
↳Field
sage: C in C.TensorProducts().super_categories()
True
```

is_abelian()

Return whether this category is abelian.

This is always True since the base ring is a field.

EXAMPLES:

```
sage: VectorSpaces(QQ).WithBasis().is_abelian()
True
```

additional_structure()

Return None.

Indeed, the category of vector spaces defines no additional structure: a bimodule morphism between two vector spaces is a vector space morphism.

See also:

[Category.additional_structure\(\)](#)

Todo: Should this category be a `CategoryWithAxiom`?

EXAMPLES:

```
sage: VectorSpaces(QQ).additional_structure()
```

base_field()

Returns the base field over which the vector spaces of this category are all defined.

EXAMPLES:

```
sage: VectorSpaces(QQ).base_field()
Rational Field
```

super_categories()

EXAMPLES:

```
sage: VectorSpaces(QQ).super_categories()
[Category of modules over Rational Field]
```

3.163 Weyl Groups

class sage.categories.weyl_groups.WeylGroups(*s=None*)

Bases: *sage.categories.category_singleton.Category_singleton*

The category of Weyl groups

See the [Wikipedia page of Weyl Groups](#).

EXAMPLES:

```
sage: WeylGroups()
Category of weyl groups
sage: WeylGroups().super_categories()
[Category of coxeter groups]
```

Here are some examples:

```
sage: WeylGroups().example()           # todo: not implemented
sage: FiniteWeylGroups().example()
The symmetric group on {0, ..., 3}
sage: AffineWeylGroups().example()     # todo: not implemented
sage: WeylGroup(["B", 3])
Weyl Group of type ['B', 3] (as a matrix group acting on the ambient space)
```

This one will eventually be also in this category:

```
sage: SymmetricGroup(4)
Symmetric group of order 4! as a permutation group
```

class ElementMethods

Bases: object

bruhat_lower_covers_coroots()

Return all 2-tuples (v, α) where v is covered by `self` and α is the positive coroot such that `self` = $v s_\alpha$ where s_α is the reflection orthogonal to α .

ALGORITHM:

See `bruhat_lower_covers()` and `bruhat_lower_covers_reflections()` for Coxeter groups.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3], prefix="s")
sage: w = W.from_reduced_word([3, 1, 2, 1])
sage: w.bruhat_lower_covers_coroots()
[(s1*s2*s1, alphacheck[1] + alphacheck[2] + alphacheck[3]),
 (s3*s2*s1, alphacheck[2]), (s3*s1*s2, alphacheck[1])]
```

bruhat_upper_covers_coroots()

Returns all 2-tuples (v, α) where v is covers `self` and α is the positive coroot such that `self` = $v s_\alpha$ where s_α is the reflection orthogonal to α .

ALGORITHM:

See `bruhat_upper_covers()` and `bruhat_upper_covers_reflections()` for Coxeter groups.

EXAMPLES:

```

sage: W = WeylGroup(['A', 4], prefix="s")
sage: w = W.from_reduced_word([3, 1, 2, 1])
sage: w.bruhat_upper_covers_coroots()
[(s1*s2*s3*s2*s1, alphacheck[3]),
 (s2*s3*s1*s2*s1, alphacheck[2] + alphacheck[3]),
 (s3*s4*s1*s2*s1, alphacheck[4]),
 (s4*s3*s1*s2*s1, alphacheck[1] + alphacheck[2] + alphacheck[3] +
 ↪ alphacheck[4])]

```

inversion_arrangement(*side='right'*)

Return the inversion hyperplane arrangement of `self`.

INPUT:

- `side` – 'right' (default) or 'left'

OUTPUT:

A (central) hyperplane arrangement whose hyperplanes correspond to the inversions of `self` given as roots.

The `side` parameter determines on which side to compute the inversions.

EXAMPLES:

```

sage: W = WeylGroup(['A', 3])
sage: w = W.from_reduced_word([1, 2, 3, 1, 2])
sage: A = w.inversion_arrangement(); A
Arrangement of 5 hyperplanes of dimension 3 and rank 3
sage: A.hyperplanes()
(Hyperplane 0*a1 + 0*a2 + a3 + 0,
 Hyperplane 0*a1 + a2 + 0*a3 + 0,
 Hyperplane 0*a1 + a2 + a3 + 0,
 Hyperplane a1 + a2 + 0*a3 + 0,
 Hyperplane a1 + a2 + a3 + 0)

```

The identity element gives the empty arrangement:

```

sage: W = WeylGroup(['A', 3])
sage: W.one().inversion_arrangement()
Empty hyperplane arrangement of dimension 3

```

inversions(*side='right', inversion_type='reflections'*)

Returns the set of inversions of `self`.

INPUT:

- `side` – 'right' (default) or 'left'
- `inversion_type` – 'reflections' (default), 'roots', or 'coroots'.

OUTPUT:

For reflections, the set of reflections `r` in the Weyl group such that `self r < self`. For (co)roots, the set of positive (co)roots that are sent by `self` to negative (co)roots; their associated reflections are described above.

If `side` is 'left', the inverse Weyl group element is used.

EXAMPLES:


```

sage: W=WeylGroup(['C',2], prefix="s")
sage: w=W.from_reduced_word([1,2])
sage: w.inversions()
[s2, s2*s1*s2]
sage: w.inversions(inversion_type = 'reflections')
[s2, s2*s1*s2]
sage: w.inversions(inversion_type = 'roots')
[alpha[2], alpha[1] + alpha[2]]
sage: w.inversions(inversion_type = 'coroots')
[alphacheck[2], alphacheck[1] + 2*alphacheck[2]]
sage: w.inversions(side = 'left')
[s1, s1*s2*s1]
sage: w.inversions(side = 'left', inversion_type = 'roots')
[alpha[1], 2*alpha[1] + alpha[2]]
sage: w.inversions(side = 'left', inversion_type = 'coroots')
[alphacheck[1], alphacheck[1] + alphacheck[2]]

```

is_pieri_factor()

Returns whether self is a Pieri factor, as used for computing Stanley symmetric functions.

See also:

- [stanley_symmetric_function\(\)](#)
- [WeylGroups.ParentMethods.pieri_factors\(\)](#)

EXAMPLES:

```

sage: W = WeylGroup(['A', 5, 1])
sage: W.from_reduced_word([3,2,5]).is_pieri_factor()
True
sage: W.from_reduced_word([3,2,4,5]).is_pieri_factor()
False

sage: W = WeylGroup(['C', 4, 1])
sage: W.from_reduced_word([0,2,1]).is_pieri_factor()
True
sage: W.from_reduced_word([0,2,1,0]).is_pieri_factor()
False

sage: W = WeylGroup(['B', 3])
sage: W.from_reduced_word([3,2,3]).is_pieri_factor()
False
sage: W.from_reduced_word([2,1,2]).is_pieri_factor()
True

```

left_pieri_factorizations(max_length=None)

Returns all factorizations of self as uv , where u is a Pieri factor and v is an element of the Weyl group.

See also:

- [WeylGroups.ParentMethods.pieri_factors\(\)](#)
- [sage.combinat.root_system.pieri_factors](#)

EXAMPLES:

If we take $w = w_0$ the maximal element of a strict parabolic subgroup of type $A_{n_1} \times \cdots \times A_{n_k}$, then the Pieri factorizations are in correspondence with all Pieri factors, and there are $\prod 2^{n_i}$ of them:

```

sage: W = WeylGroup(['A', 4, 1])
sage: W.from_reduced_word([]).left_pieri_factorizations().cardinality()
1
sage: W.from_reduced_word([1]).left_pieri_factorizations().cardinality()
2
sage: W.from_reduced_word([1,2,1]).left_pieri_factorizations().cardinality()
4
sage: W.from_reduced_word([1,2,3,1,2,1]).left_pieri_factorizations().
↳cardinality()
8

sage: W.from_reduced_word([1,3]).left_pieri_factorizations().cardinality()
4
sage: W.from_reduced_word([1,3,4,3]).left_pieri_factorizations().
↳cardinality()
8

sage: W.from_reduced_word([2,1]).left_pieri_factorizations().cardinality()
3
sage: W.from_reduced_word([1,2]).left_pieri_factorizations().cardinality()
2
sage: [W.from_reduced_word([1,2]).left_pieri_factorizations(max_length=i).
↳cardinality() for i in [-1, 0, 1, 2]]
[0, 1, 2, 2]

sage: W = WeylGroup(['C', 4, 1])
sage: w = W.from_reduced_word([0,3,2,1,0])
sage: w.left_pieri_factorizations().cardinality()
7
sage: [(u.reduced_word(),v.reduced_word()) for (u,v) in w.left_pieri_
↳factorizations()]
[([], [3, 2, 0, 1, 0]),
 ([0], [3, 2, 1, 0]),
 ([3], [2, 0, 1, 0]),
 ([3, 0], [2, 1, 0]),
 ([3, 2], [0, 1, 0]),
 ([3, 2, 0], [1, 0]),
 ([3, 2, 0, 1], [0])]

sage: W = WeylGroup(['B', 4, 1])
sage: W.from_reduced_word([0,2,1,0]).left_pieri_factorizations().
↳cardinality()
6

```

quantum_bruhat_successors(*index_set=None, roots=False, quantum_only=False*)

Return the successors of `self` in the quantum Bruhat graph on the parabolic quotient of the Weyl group determined by the subset of Dynkin nodes `index_set`.

INPUT:

- `self` – a Weyl group element, which is assumed to be of minimum length in its coset with respect to the parabolic subgroup
- `index_set` – (default: `None`) indicates the set of simple reflections used to generate the parabolic

- subgroup; the default value indicates that the subgroup is the identity
- `roots` – (default: `False`) if `True`, returns the list of 2-tuples (w, α) where w is a successor and α is the positive root associated with the successor relation
 - `quantum_only` – (default: `False`) if `True`, returns only the quantum successors

EXAMPLES:

```
sage: W = WeylGroup(['A', 3], prefix="s")
sage: w = W.from_reduced_word([3, 1, 2])
sage: w.quantum_bruhat_successors([1], roots = True)
[(s3, alpha[2]), (s1*s2*s3*s2, alpha[3]),
 (s2*s3*s1*s2, alpha[1] + alpha[2] + alpha[3])]
sage: w.quantum_bruhat_successors([1, 3])
[1, s2*s3*s1*s2]
sage: w.quantum_bruhat_successors(roots = True)
[(s3*s1*s2*s1, alpha[1]),
 (s3*s1, alpha[2]),
 (s1*s2*s3*s2, alpha[3]),
 (s2*s3*s1*s2, alpha[1] + alpha[2] + alpha[3])]
sage: w.quantum_bruhat_successors()
[s3*s1*s2*s1, s3*s1, s1*s2*s3*s2, s2*s3*s1*s2]
sage: w.quantum_bruhat_successors(quantum_only = True)
[s3*s1]
sage: w = W.from_reduced_word([2, 3])
sage: w.quantum_bruhat_successors([1, 3])
Traceback (most recent call last):
...
ValueError: s2*s3 is not of minimum length in its coset of the parabolic_
↳subgroup generated by the reflections (1, 3)
```

`reflection_to_coroot()`

Returns the coroot associated with the reflection self.

EXAMPLES:

```
sage: W=WeylGroup(['C', 2], prefix="s")
sage: W.from_reduced_word([1, 2, 1]).reflection_to_coroot()
alphacheck[1] + alphacheck[2]
sage: W.from_reduced_word([1, 2]).reflection_to_coroot()
Traceback (most recent call last):
...
ValueError: s1*s2 is not a reflection
sage: W.long_element().reflection_to_coroot()
Traceback (most recent call last):
...
ValueError: s2*s1*s2*s1 is not a reflection
```

`reflection_to_root()`

Returns the root associated with the reflection self.

EXAMPLES:

```
sage: W=WeylGroup(['C', 2], prefix="s")
sage: W.from_reduced_word([1, 2, 1]).reflection_to_root()
2*alpha[1] + alpha[2]
sage: W.from_reduced_word([1, 2]).reflection_to_root()
```

(continues on next page)

(continued from previous page)

```

Traceback (most recent call last):
...
ValueError: s1*s2 is not a reflection
sage: W.long_element().reflection_to_root()
Traceback (most recent call last):
...
ValueError: s2*s1*s2*s1 is not a reflection

```

stanley_symmetric_function()

Return the affine Stanley symmetric function indexed by `self`.

INPUT:

- `self` – an element w of a Weyl group

Returns the affine Stanley symmetric function indexed by w . Stanley symmetric functions are defined as generating series of the factorizations of w into Pieri factors and weighted by a statistic on Pieri factors.

See also:

- [stanley_symmetric_function_as_polynomial\(\)](#)
- [WeylGroups.ParentMethods.pieri_factors\(\)](#)
- [sage.combinat.root_system.pieri_factors](#)

EXAMPLES:

```

sage: W = WeylGroup(['A', 3, 1])
sage: W.from_reduced_word([3,1,2,0,3,1,0]).stanley_symmetric_function()
8*m[1, 1, 1, 1, 1, 1, 1] + 4*m[2, 1, 1, 1, 1, 1] + 2*m[2, 2, 1, 1, 1] + m[2,
↪ 2, 2, 1]
sage: A = AffinePermutationGroup(['A', 3, 1])
sage: A.from_reduced_word([3,1,2,0,3,1,0]).stanley_symmetric_function()
8*m[1, 1, 1, 1, 1, 1, 1] + 4*m[2, 1, 1, 1, 1, 1] + 2*m[2, 2, 1, 1, 1] + m[2,
↪ 2, 2, 1]

sage: W = WeylGroup(['C', 3, 1])
sage: W.from_reduced_word([0,2,1,0]).stanley_symmetric_function()
32*m[1, 1, 1, 1] + 16*m[2, 1, 1] + 8*m[2, 2] + 4*m[3, 1]

sage: W = WeylGroup(['B', 3, 1])
sage: W.from_reduced_word([3,2,1]).stanley_symmetric_function()
2*m[1, 1, 1] + m[2, 1] + 1/2*m[3]

sage: W = WeylGroup(['B', 4])
sage: w = W.from_reduced_word([3,2,3,1])
sage: w.stanley_symmetric_function() # long time (6s on sage.math, 2011)
48*m[1, 1, 1, 1] + 24*m[2, 1, 1] + 12*m[2, 2] + 8*m[3, 1] + 2*m[4]

sage: A = AffinePermutationGroup(['A', 4, 1])
sage: a = A([-2,0,1,4,12])
sage: a.stanley_symmetric_function()
6*m[1, 1, 1, 1, 1, 1, 1, 1] + 5*m[2, 1, 1, 1, 1, 1, 1] + 4*m[2, 2, 1, 1, 1,
↪ 1]
+ 3*m[2, 2, 2, 1, 1] + 2*m[2, 2, 2, 2] + 4*m[3, 1, 1, 1, 1, 1] + 3*m[3, 2,
↪ 1, 1, 1]

```

(continues on next page)

(continued from previous page)

```
+ 2*m[3, 2, 2, 1] + 2*m[3, 3, 1, 1] + m[3, 3, 2] + 3*m[4, 1, 1, 1, 1] +
↪ 2*m[4, 2, 1, 1]
+ m[4, 2, 2] + m[4, 3, 1]
```

One more example (trac ticket #14095):

```
sage: G = SymmetricGroup(4)
sage: w = G.from_reduced_word([3,2,3,1])
sage: w.stanley_symmetric_function()
3*m[1, 1, 1, 1] + 2*m[2, 1, 1] + m[2, 2] + m[3, 1]
```

REFERENCES:

- [BH1994]
- [Lam2008]
- [LSS2009]
- [Pon2010]

stanley_symmetric_function_as_polynomial(*max_length=None*)

Returns a multivariate generating function for the number of factorizations of a Weyl group element into Pieri factors of decreasing length, weighted by a statistic on Pieri factors.

See also:

- [stanley_symmetric_function\(\)](#)
- [WeylGroups.ParentMethods.pieri_factors\(\)](#)
- [sage.combinat.root_system.pieri_factors](#)

INPUT:

- *self* – an element w of a Weyl group W
- *max_length* – a non negative integer or infinity (default: infinity)

Returns the generating series for the Pieri factorizations $w = u_1 \cdots u_k$, where u_i is a Pieri factor for all i , $l(w) = \sum_{i=1}^k l(u_i)$ and $\max_length \geq l(u_1) \geq \cdots \geq l(u_k)$.

A factorization $u_1 \cdots u_k$ contributes a monomial of the form $\prod_i x^{l(u_i)}$, with coefficient given by $\prod_i 2^{c(u_i)}$, where c is a type-dependent statistic on Pieri factors, as returned by the method `u[i].stanley_symm_poly_weight()`.

EXAMPLES:

```
sage: W = WeylGroup(['A', 3, 1])
sage: W.from_reduced_word([]).stanley_symmetric_function_as_polynomial()
1
sage: W.from_reduced_word([1]).stanley_symmetric_function_as_polynomial()
x1
sage: W.from_reduced_word([1,2]).stanley_symmetric_function_as_polynomial()
x1^2
sage: W.from_reduced_word([2,1]).stanley_symmetric_function_as_polynomial()
x1^2 + x2
sage: W.from_reduced_word([1,2,1]).stanley_symmetric_function_as_
↪ polynomial()
2*x1^3 + x1*x2
sage: W.from_reduced_word([1,2,1,0]).stanley_symmetric_function_as_
↪ polynomial()
3*x1^4 + 2*x1^2*x2 + x2^2 + x1*x3
sage: W.from_reduced_word([1,2,3,1,2,1,0]).stanley_symmetric_function_as_
↪ polynomial() # long time
```

(continues on next page)

(continued from previous page)

```

22*x1^7 + 11*x1^5*x2 + 5*x1^3*x2^2 + 3*x1^4*x3 + 2*x1*x2^3 + x1^2*x2*x3
sage: W.from_reduced_word([3,1,2,0,3,1,0]).stanley_symmetric_function_as_
↳polynomial() # long time
8*x1^7 + 4*x1^5*x2 + 2*x1^3*x2^2 + x1*x2^3

sage: W = WeylGroup(['C',3,1])
sage: W.from_reduced_word([0,2,1,0]).stanley_symmetric_function_as_
↳polynomial()
32*x1^4 + 16*x1^2*x2 + 8*x2^2 + 4*x1*x3

sage: W = WeylGroup(['B',3,1])
sage: W.from_reduced_word([3,2,1]).stanley_symmetric_function_as_
↳polynomial()
2*x1^3 + x1*x2 + 1/2*x3

```

Algorithm: Induction on the left Pieri factors. Note that this induction preserves subsets of W which are stable by taking right factors, and in particular Grassmanian elements.

Finite

alias of `sage.categories.finite_weyl_groups.FiniteWeylGroups`

class ParentMethods

Bases: object

coxeter_matrix()

Return the Coxeter matrix associated to `self`.

EXAMPLES:

```

sage: G = WeylGroup(['A',3])
sage: G.coxeter_matrix()
[1 3 2]
[3 1 3]
[2 3 1]

```

pieri_factors(*args, **keywords)

Returns the set of Pieri factors in this Weyl group.

For any type, the set of Pieri factors forms a lower ideal in Bruhat order, generated by all the conjugates of some special element of the Weyl group. In type A_n , this special element is $s_n \cdots s_1$, and the conjugates are obtained by rotating around this reduced word.

These are used to compute Stanley symmetric functions.

See also:

- `WeylGroups.ElementMethods.stanley_symmetric_function()`
- `sage.combinat.root_system.pieri_factors`

EXAMPLES:

```

sage: W = WeylGroup(['A',5,1])
sage: PF = W.pieri_factors()
sage: PF.cardinality()
63

sage: W = WeylGroup(['B',3])

```

(continues on next page)

(continued from previous page)

```

sage: PF = W.pieri_factors()
sage: sorted([w.reduced_word() for w in PF])
[],
 [1],
 [1, 2],
 [1, 2, 1],
 [1, 2, 3],
 [1, 2, 3, 1],
 [1, 2, 3, 2],
 [1, 2, 3, 2, 1],
 [2],
 [2, 1],
 [2, 3],
 [2, 3, 1],
 [2, 3, 2],
 [2, 3, 2, 1],
 [3],
 [3, 1],
 [3, 1, 2],
 [3, 1, 2, 1],
 [3, 2],
 [3, 2, 1]]
sage: W = WeylGroup(['C', 4, 1])
sage: PF = W.pieri_factors()
sage: W.from_reduced_word([3, 2, 0]) in PF
True

```

quantum_bruhat_graph(*index_set=()*)

Return the quantum Bruhat graph of the quotient of the Weyl group by a parabolic subgroup W_J .

INPUT:

- *index_set* – (default: ()) a tuple J of nodes of the Dynkin diagram

By default, the value for *index_set* indicates that the subgroup is trivial and the quotient is the full Weyl group.

EXAMPLES:

```

sage: W = WeylGroup(['A', 3], prefix="s")
sage: g = W.quantum_bruhat_graph((1, 3))
sage: g
Parabolic Quantum Bruhat Graph of Weyl Group of type ['A', 3] (as a matrix_
↪group acting on the ambient space) for nodes (1, 3): Digraph on 6 vertices
sage: g.vertices()
[s2*s3*s1*s2, s3*s1*s2, s1*s2, s3*s2, s2, 1]
sage: g.edges()
[(s2*s3*s1*s2, s2, alpha[2]),
 (s3*s1*s2, s2*s3*s1*s2, alpha[1] + alpha[2] + alpha[3]),
 (s3*s1*s2, 1, alpha[2]),
 (s1*s2, s3*s1*s2, alpha[2] + alpha[3]),
 (s3*s2, s3*s1*s2, alpha[1] + alpha[2]),
 (s2, s1*s2, alpha[1] + alpha[2]),
 (s2, s3*s2, alpha[2] + alpha[3]),
 (1, s2, alpha[2])]

```

(continues on next page)

(continued from previous page)

```
sage: W = WeylGroup(['A', 3, 1], prefix="s")
sage: g = W.quantum_bruhat_graph()
Traceback (most recent call last):
...
ValueError: the Cartan type ['A', 3, 1] is not finite
```

additional_structure()

Return None.

Indeed, the category of Weyl groups defines no additional structure: Weyl groups are a special class of Coxeter groups.

See also:*Category.additional_structure()*

Todo: Should this category be a `CategoryWithAxiom`?

EXAMPLES:

```
sage: WeylGroups().additional_structure()
```

super_categories()

EXAMPLES:

```
sage: WeylGroups().super_categories()
[Category of coxeter groups]
```

3.164 Technical Categories

3.164.1 Facade Sets

For background, see *What is a facade set?*.

class `sage.categories.facade_sets.FacadeSets`(*base_category*)

Bases: `sage.categories.category_with_axiom.CategoryWithAxiom_singleton`

class `ParentMethods`Bases: `object`**facade_for()**

Returns the parents this set is a facade for

This default implementation assumes that `self` has an attribute `_facade_for`, typically initialized by `Parent.__init__()`. If the attribute is not present, the method raises a `NotImplementedError`.

EXAMPLES:

```
sage: S = Sets().Facade().example(); S
An example of facade set: the monoid of positive integers
sage: S.facade_for()
(Integer Ring,)
```

Check that [trac ticket #13801](#) is corrected:


```

sage: class A(Parent):
.....:     def __init__(self):
.....:         Parent.__init__(self, category=Sets(), facade=True)
sage: a = A()
sage: a.facade_for()
Traceback (most recent call last):
...
NotImplementedError: this parent did not specify which parents it is a
↳ facade for

```

is_parent_of(*element*)

Returns whether *self* is the parent of *element*

INPUT:

- *element* – any object

Since *self* is a facade domain, this actually tests whether the parent of *element* is any of the parent *self* is a facade for.

EXAMPLES:

```

sage: S = Sets().Facade().example(); S
An example of facade set: the monoid of positive integers
sage: S.is_parent_of(1)
True
sage: S.is_parent_of(1/2)
False

```

This method differs from `__contains__()` in two ways. First, this does not take into account the fact that *self* may be a strict subset of the parent(s) it is a facade for:

```

sage: -1 in S, S.is_parent_of(-1)
(False, True)

```

Furthermore, there is no coercion attempted:

```

sage: int(1) in S, S.is_parent_of(int(1))
(True, False)

```

Warning: this implementation does not handle facade parents of facade parents. Is this a feature we want generically?

example(*choice*='subset')

Returns an example of facade set, as per `Category.example()`.

INPUT:

- *choice* – 'union' or 'subset' (default: 'subset').

EXAMPLES:

```

sage: Sets().Facade().example()
An example of facade set: the monoid of positive integers
sage: Sets().Facade().example(choice='union')
An example of a facade set: the integers completed by +-infinity

```

(continues on next page)

(continued from previous page)

```
sage: Sets().Facade().example(choice='subset')  
An example of facade set: the monoid of positive integers
```

FUNCTORIAL CONSTRUCTIONS

4.1 Covariant Functorial Constructions

A *functorial construction* is a collection of functors $(F_{Cat})_{Cat}$ (indexed by a collection of categories) which associate to a sequence of parents (A, B, \dots) in a category Cat a parent $F_{Cat}(A, B, \dots)$. Typical examples of functorial constructions are `cartesian_product` and `tensor_product`.

The category of $F_{Cat}(A, B, \dots)$, which only depends on Cat , is called the (functorial) construction category.

A functorial construction is *(category)-covariant* if for every categories Cat and $SuperCat$, the category of $F_{Cat}(A, B, \dots)$ is a subcategory of the category of $F_{SuperCat}(A, B, \dots)$ whenever Cat is a subcategory of $SuperCat$. A functorial construction is *(category)-regressive* if the category of $F_{Cat}(A, B, \dots)$ is a subcategory of Cat .

The goal of this module is to provide generic support for covariant functorial constructions. In particular, given some parents A, B, \dots , in respective categories Cat_A, Cat_B, \dots , it provides tools for calculating the best known category for the parent $F(A, B, \dots)$. For examples, knowing that Cartesian products of semigroups (resp. monoids, groups) have a semigroup (resp. monoid, group) structure, and given a group B and two monoids A and C it can calculate that $A \times B \times C$ is naturally endowed with a monoid structure.

See `CovariantFunctorialConstruction`, `CovariantConstructionCategory` and `RegressiveCovariantConstructionCategory` for more details.

AUTHORS:

- Nicolas M. Thiery (2010): initial revision

class `sage.categories.covariant_functorial_construction.CovariantConstructionCategory`(*category*,
**args*)

Bases: `sage.categories.covariant_functorial_construction.FunctorialConstructionCategory`

Abstract class for categories F_{Cat} obtained through a covariant functorial construction

additional_structure()

Return the additional structure defined by `self`.

By default, a functorial construction category `A.F()` defines additional structure if and only if A is the category defining F . The rationale is that, for a subcategory B of A , the fact that $B.F()$ morphisms shall preserve the F -specific structure is already imposed by $A.F()$.

See also:

- `Category.additional_structure()`.
- `is_construction_defined_by_base()`.

EXAMPLES:

```
sage: Modules(ZZ).Graded().additional_structure()
Category of graded modules over Integer Ring
sage: Algebras(ZZ).Graded().additional_structure()
```

classmethod `default_super_categories`(*category*, **args*)

Return the default super categories of $F_{Cat}(A, B, \dots)$ for A, B, \dots parents in Cat .

INPUT:

- `cls` – the category class for the functor F
- `category` – a category Cat
- *`args` – further arguments for the functor

OUTPUT: a (join) category

The default implementation is to return the join of the categories of $F(A, B, \dots)$ for A, B, \dots in turn in each of the super categories of `category`.

This is implemented as a class method, in order to be able to reconstruct the functorial category associated to each of the super categories of `category`.

EXAMPLES:

Bialgebras are both algebras and coalgebras:

```
sage: Bialgebras(QQ).super_categories()
[Category of algebras over Rational Field, Category of coalgebras over Rational_
↪Field]
```

Hence tensor products of bialgebras are tensor products of algebras and tensor products of coalgebras:

```
sage: Bialgebras(QQ).TensorProducts().super_categories()
[Category of tensor products of algebras over Rational Field,
Category of tensor products of coalgebras over Rational Field]
```

Here is how `default_super_categories()` was called internally:

```
sage: sage.categories.tensor.TensorProductsCategory.default_super_
↪categories(Bialgebras(QQ))
Join of Category of tensor products of algebras over Rational Field and_
↪Category of tensor products of coalgebras over Rational Field
```

We now show a similar example, with the Algebra functor which takes a parameter \mathbb{Q} :

```
sage: FiniteMonoids().super_categories()
[Category of monoids, Category of finite semigroups]
sage: sorted(FiniteMonoids().Algebras(QQ).super_categories(), key=str)
[Category of finite dimensional algebras with basis over Rational Field,
Category of finite set algebras over Rational Field,
Category of monoid algebras over Rational Field]
```

Note that neither the category of *finite* semigroup algebras nor that of monoid algebras appear in the result; this is because there is currently nothing specific implemented about them.

Here is how `default_super_categories()` was called internally:

```

sage: sage.categories.algebra_functor.AlgebrasCategory.default_super_
↳categories(FiniteMonoids(), QQ)
Join of Category of finite dimensional algebras with basis over Rational Field
and Category of monoid algebras over Rational Field
and Category of finite set algebras over Rational Field

```

is_construction_defined_by_base()

Return whether the construction is defined by the base of self.

EXAMPLES:

The graded functorial construction is defined by the modules category. Hence this method returns True for graded modules and False for other graded xxx categories:

```

sage: Modules(ZZ).Graded().is_construction_defined_by_base()
True
sage: Algebras(QQ).Graded().is_construction_defined_by_base()
False
sage: Modules(ZZ).WithBasis().Graded().is_construction_defined_by_base()
False

```

This is implemented as follows: given the base category A and the construction F of self, that is $\text{self}=A.F()$, check whether no super category of A has F defined.

Note: Recall that, when A does not implement the construction F , a join category is returned. Therefore, in such cases, this method is not available:

```

sage: Bialgebras(QQ).Graded().is_construction_defined_by_base()
Traceback (most recent call last):
...
AttributeError: 'JoinCategory_with_category' object has no attribute 'is_
↳construction_defined_by_base'

```

class sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.sage_object.SageObject`

An abstract class for construction functors F (eg $F =$ Cartesian product, tensor product, \mathbf{Q} -algebra, ...) such that:

- Each category Cat (eg $Cat = \text{Groups}()$) can provide a category F_{Cat} for parents constructed via this functor (e.g. $F_{Cat} = \text{CartesianProductsOf}(\text{Groups}())$).
- For every category Cat , F_{Cat} is a subcategory of $F_{SuperCat}$ for every super category $SuperCat$ of Cat (the functorial construction is (category)-covariant).
- For parents A, B, \dots , respectively in the categories Cat_A, Cat_B, \dots , the category of $F(A, B, \dots)$ is F_{Cat} where Cat is the meet of the categories Cat_A, Cat_B, \dots .

This covers two slightly different use cases:

- In the first use case, one uses directly the construction functor to create new parents:

```

sage: tensor() # todo: not implemented (add an example)

```

or even new elements, which indirectly constructs the corresponding parent:

```
sage: tensor(...) # todo: not implemented
```

- In the second use case, one implements a parent, and then put it in the category F_{Cat} to specify supplementary mathematical information about that parent.

The main purpose of this class is to handle automatically the trivial part of the category hierarchy. For example, `CartesianProductsOf(Groups())` is set automatically as a subcategory of `CartesianProductsOf(Monoids())`.

In practice, each subclass of this class should provide the following attributes:

- `_functor_category` - a string which should match the name of the nested category class to be used in each category to specify information and generic operations for elements of this category.
- `_functor_name` - an string which specifies the name of the functor, and also (when relevant) of the method on parents and elements used for calling the construction.

TODO: What syntax do we want for F_{Cat} ? For example, for the tensor product construction, which one do we want among (see chat on IRC, on 07/12/2009):

- `tensor(Cat)`
- `tensor((Cat, Cat))`
- `tensor.of((Cat, Cat))`
- `tensor.category_from_categories((Cat, Cat, Cat))`
- `Cat.TensorProducts()`

The syntax `Cat.TensorProducts()` does not supports well multivariate constructions like `tensor.of([Algebras(), HopfAlgebras(), ...])`. Also it forces every category to be (somehow) aware of all the tensorial construction that could apply to it, even those which are only induced from super categories.

Note: for each functorial construction, there probably is one (or several) largest categories on which it applies. For example, the `CartesianProducts()` construction makes only sense for concrete categories, that is subcategories of `Sets()`. Maybe we want to model this one way or the other.

category_from_categories(*categories*)

Return the category of $F(A, B, \dots)$ for A, B, \dots parents in the given categories.

INPUT:

- `self`: a functor F
- `categories`: a non empty tuple of categories

EXAMPLES:

```
sage: Cat1 = Rings()
sage: Cat2 = Groups()
sage: cartesian_product.category_from_categories((Cat1, Cat1, Cat1))
Join of Category of rings and ...
    and Category of Cartesian products of monoids
    and Category of Cartesian products of commutative additive groups

sage: cartesian_product.category_from_categories((Cat1, Cat2))
Category of Cartesian products of monoids
```

category_from_category(*category*)

Return the category of $F(A, B, \dots)$ for A, B, \dots parents in category.

INPUT:

- self: a functor F
- category: a category

EXAMPLES:

```
sage: tensor.category_from_category(ModulesWithBasis(QQ))
Category of tensor products of vector spaces with basis over Rational Field
```

TODO: add support for parametrized functors

category_from_parents(parents)

Return the category of $F(A, B, \dots)$ for A, B, \dots parents.

INPUT:

- self: a functor F
- parents: a list (or iterable) of parents.

EXAMPLES:

```
sage: E = CombinatorialFreeModule(QQ, ["a", "b", "c"])
sage: tensor.category_from_parents((E, E, E))
Category of tensor products of vector spaces with basis over Rational Field
```

class sage.categories.covariant_functorial_construction.**FunctorialConstructionCategory**(category, *args)

Bases: *sage.categories.category.Category*

Abstract class for categories F_{Cat} obtained through a functorial construction

base_category()

Return the base category of the category self.

For any category $B = F_{Cat}$ obtained through a functorial construction F , the call $B.base_category()$ returns the category Cat .

EXAMPLES:

```
sage: Semigroups().Quotients().base_category()
Category of semigroups
```

classmethod **category_of**(category, *args)

Return the image category of the functor F_{Cat} .

This is the main entry point for constructing the category F_{Cat} of parents $F(A, B, \dots)$ constructed from parents A, B, \dots in Cat .

INPUT:

- cls – the category class for the functorial construction F
- category – a category Cat
- *args – further arguments for the functor

EXAMPLES:

```
sage: sage.categories.tensor.TensorProductsCategory.category_of(
↳ of(ModulesWithBasis(QQ))
Category of tensor products of vector spaces with basis over Rational Field
```

(continues on next page)

(continued from previous page)

```

sage: sage.categories.algebra_functor.AlgebrasCategory.category_
↳of(FiniteMonoids(), QQ)
Join of Category of finite dimensional algebras with basis over Rational Field
and Category of monoid algebras over Rational Field
and Category of finite set algebras over Rational Field

```

extra_super_categories()

Return the extra super categories of a construction category.

Default implementation which returns [].

EXAMPLES:

```

sage: Sets().Subquotients().extra_super_categories()
[]
sage: Semigroups().Quotients().extra_super_categories()
[]

```

super_categories()

Return the super categories of a construction category.

EXAMPLES:

```

sage: Sets().Subquotients().super_categories()
[Category of sets]
sage: Semigroups().Quotients().super_categories()
[Category of subquotients of semigroups, Category of quotients of sets]

```

class sage.categories.covariant_functorial_construction.**RegressiveCovariantConstructionCategory**(*category*, **args*)

Bases: *sage.categories.covariant_functorial_construction.CovariantConstructionCategory*

Abstract class for categories F_{Cat} obtained through a regressive covariant functorial construction

classmethod **default_super_categories**(*category*, **args*)

Return the default super categories of $F_{Cat}(A, B, \dots)$ for A, B, \dots parents in Cat .

INPUT:

- *cls* – the category class for the functor F
- *category* – a category Cat
- **args* – further arguments for the functor

OUTPUT:

A join category.

This implements the property that an induced subcategory is a subcategory.

EXAMPLES:

A subquotient of a monoid is a monoid, and a subquotient of semigroup:

```

sage: Monoids().Subquotients().super_categories()
[Category of monoids, Category of subquotients of semigroups]

```


4.2 Cartesian Product Functorial Construction

AUTHORS:

- Nicolas M. Thiery (2008-2010): initial revision and refactorization

class `sage.categories.cartesian_product.CartesianProductFunctor`(*category=None*)
 Bases: `sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction`,
`sage.categories.pushout.MultivariateConstructionFunctor`

The Cartesian product functor.

EXAMPLES:

```
sage: cartesian_product
The cartesian_product functorial construction
```

`cartesian_product` takes a finite collection of sets, and constructs the Cartesian product of those sets:

```
sage: A = FiniteEnumeratedSet(['a', 'b', 'c'])
sage: B = FiniteEnumeratedSet([1,2])
sage: C = cartesian_product([A, B]); C
The Cartesian product of ({'a', 'b', 'c'}, {1, 2})
sage: C.an_element()
('a', 1)
sage: C.list()           # todo: not implemented
[['a', 1], ['a', 2], ['b', 1], ['b', 2], ['c', 1], ['c', 2]]
```

If those sets are endowed with more structure, say they are monoids (hence in the category `Monoids()`), then the result is automatically endowed with its natural monoid structure:

```
sage: M = Monoids().example()
sage: M
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
sage: M.rename('M')
sage: C = cartesian_product([M, ZZ, QQ])
sage: C
The Cartesian product of (M, Integer Ring, Rational Field)
sage: C.an_element()
('abcd', 1, 1/2)
sage: C.an_element()^2
('abcdabcd', 1, 1/4)
sage: C.category()
Category of Cartesian products of monoids

sage: Monoids().CartesianProducts()
Category of Cartesian products of monoids
```

The Cartesian product functor is covariant: if `A` is a subcategory of `B`, then `A.CartesianProducts()` is a subcategory of `B.CartesianProducts()` (see also [CovariantFunctorialConstruction](#)):

```
sage: C.categories()
[Category of Cartesian products of monoids,
 Category of monoids,
 Category of Cartesian products of semigroups,
```

(continues on next page)

(continued from previous page)

```

Category of semigroups,
Category of Cartesian products of unital magmas,
Category of Cartesian products of magmas,
Category of unital magmas,
Category of magmas,
Category of Cartesian products of sets,
Category of sets, ...]

```

```

[Category of Cartesian products of monoids,
Category of monoids,
Category of Cartesian products of semigroups,
Category of semigroups,
Category of Cartesian products of magmas,
Category of unital magmas,
Category of magmas,
Category of Cartesian products of sets,
Category of sets,
Category of sets with partial maps,
Category of objects]

```

Hence, the role of `Monoids().CartesianProducts()` is solely to provide mathematical information and algorithms which are relevant to Cartesian product of monoids. For example, it specifies that the result is again a monoid, and that its multiplicative unit is the Cartesian product of the units of the underlying sets:

```

sage: C.one()
('', 1, 1)

```

Those are implemented in the nested class `Monoids.CartesianProducts` of `Monoids(QQ)`. This nested class is itself a subclass of `CartesianProductsCategory`.

```

class sage.categories.cartesian_product.CartesianProductsCategory(category, *args)
Bases: sage.categories.covariant_functorial_construction.CovariantConstructionCategory

```

An abstract base class for all `CartesianProducts` categories.

`CartesianProducts()`

Return the category of (finite) Cartesian products of objects of `self`.

By associativity of Cartesian products, this is `self` (a Cartesian product of Cartesian products of A 's is a Cartesian product of A 's).

EXAMPLES:

```

sage: ModulesWithBasis(QQ).CartesianProducts().CartesianProducts()
Category of Cartesian products of vector spaces with basis over Rational Field

```

`base_ring()`

The base ring of a Cartesian product is the base ring of the underlying category.

EXAMPLES:

```

sage: Algebras(ZZ).CartesianProducts().base_ring()
Integer Ring

```

4.3 Tensor Product Functorial Construction

AUTHORS:

- Nicolas M. Thiéry (2008-2010): initial revision and refactorization

class `sage.categories.tensor.TensorProductFunctor`

Bases: `sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction`

A singleton class for the tensor functor.

This functor takes a collection of vector spaces (or modules with basis), and constructs the tensor product of those vector spaces. If this vector space is in a subcategory, say that of `Algebras(QQ)`, it is automatically endowed with its natural algebra structure, thanks to the category `Algebras(QQ).TensorProducts()` of tensor products of algebras. For elements, it constructs the natural tensor product element in the corresponding tensor product of their parents.

The tensor functor is covariant: if `A` is a subcategory of `B`, then `A.TensorProducts()` is a subcategory of `B.TensorProducts()` (see also *CovariantFunctorialConstruction*). Hence, the role of `Algebras(QQ).TensorProducts()` is solely to provide mathematical information and algorithms which are relevant to tensor product of algebras.

Those are implemented in the nested class *TensorProducts* of `Algebras(QQ)`. This nested class is itself a subclass of *TensorProductsCategory*.

class `sage.categories.tensor.TensorProductsCategory(category, *args)`

Bases: `sage.categories.covariant_functorial_construction.CovariantConstructionCategory`

An abstract base class for all `TensorProducts`'s categories

TensorProducts()

Returns the category of tensor products of objects of `self`

By associativity of tensor products, this is `self` (a tensor product of tensor products of *Cat*'s is a tensor product of *Cat*'s)

EXAMPLES:

```
sage: ModulesWithBasis(QQ).TensorProducts().TensorProducts()
Category of tensor products of vector spaces with basis over Rational Field
```

base()

The base of a tensor product is the base (usually a ring) of the underlying category.

EXAMPLES:

```
sage: ModulesWithBasis(ZZ).TensorProducts().base()
Integer Ring
```

`sage.categories.tensor.tensor = The tensor functorial construction`

The tensor product functorial construction

See *TensorProductFunctor* for more information

EXAMPLES:

```
sage: tensor
The tensor functorial construction
```

4.4 Signed Tensor Product Functorial Construction

AUTHORS:

- Travis Scrimshaw (2019-07): initial version

class `sage.categories.signed_tensor.SignedTensorProductFunctor`

Bases: `sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction`

A singleton class for the signed tensor functor.

This functor takes a collection of graded algebras (possibly with basis) and constructs the signed tensor product of those algebras. If this algebra is in a subcategory, say that of `Algebras(QQ).Graded()`, it is automatically endowed with its natural algebra structure, thanks to the category `Algebras(QQ).Graded().SignedTensorProducts()` of signed tensor products of graded algebras. For elements, it constructs the natural tensor product element in the corresponding tensor product of their parents.

The signed tensor functor is covariant: if `A` is a subcategory of `B`, then `A.SignedTensorProducts()` is a subcategory of `B.SignedTensorProducts()` (see also *CovariantFunctorialConstruction*). Hence, the role of `Algebras(QQ).Graded().SignedTensorProducts()` is solely to provide mathematical information and algorithms which are relevant to signed tensor product of graded algebras.

Those are implemented in the nested class `SignedTensorProducts` of `Algebras(QQ).Graded()`. This nested class is itself a subclass of *SignedTensorProductsCategory*.

EXAMPLES:

```
sage: tensor_signed
The signed tensor functorial construction
```

class `sage.categories.signed_tensor.SignedTensorProductsCategory(category, *args)`

Bases: `sage.categories.covariant_functorial_construction.CovariantConstructionCategory`

An abstract base class for all `SignedTensorProducts`'s categories.

SignedTensorProducts()

Return the category of signed tensor products of objects of `self`.

By associativity of signed tensor products, this is `self` (a tensor product of signed tensor products of `Cat`'s is a tensor product of `Cat`'s with the same twisting morphism)

EXAMPLES:

```
sage: AlgebrasWithBasis(QQ).Graded().SignedTensorProducts().
↳SignedTensorProducts()
Category of signed tensor products of graded algebras with basis
over Rational Field
```

base()

The base of a signed tensor product is the base (usually a ring) of the underlying category.

EXAMPLES:

```
sage: AlgebrasWithBasis(ZZ).Graded().SignedTensorProducts().base()
Integer Ring
```

`sage.categories.signed_tensor.tensor_signed = The signed tensor functorial construction`

4.5 Dual functorial construction

AUTHORS:

- Nicolas M. Thiery (2009-2010): initial revision

class sage.categories.dual.DualFunctor

Bases: `sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction`

A singleton class for the dual functor

class sage.categories.dual.DualObjectsCategory(*category*, *args)

Bases: `sage.categories.covariant_functorial_construction.CovariantConstructionCategory`

4.6 Group algebras and beyond: the Algebra functorial construction

4.6.1 Introduction: group algebras

Let G be a group and R be a ring. For example:

```
sage: G = DihedralGroup(3)
sage: R = QQ
```

The *group algebra* $A = RG$ of G over R is the space of formal linear combinations of elements of *group* with coefficients in R :

```
sage: A = G.algebra(R); A
Algebra of Dihedral group of order 6 as a permutation group
over Rational Field
sage: a = A.an_element(); a
() + (1,2) + 3*(1,2,3) + 2*(1,3,2)
```

This space is endowed with an algebra structure, obtained by extending by bilinearity the multiplication of G to a multiplication on RG :

```
sage: A in Algebras
True
sage: a * a
14*() + 5*(2,3) + 2*(1,2) + 10*(1,2,3) + 13*(1,3,2) + 5*(1,3)
```

In particular, the product of two basis elements is induced by the product of the corresponding elements of the group, and the unit of the group algebra is indexed by the unit of the group:

```
sage: (s, t) = A.algebra_generators()
sage: s*t
(1,2)
sage: A.one_basis()
()
sage: A.one()
()
```

For the user convenience and backward compatibility, the group algebra can also be constructed with:

```
sage: GroupAlgebra(G, R)
Algebra of Dihedral group of order 6 as a permutation group
over Rational Field
```

Since [trac ticket #18700](#), both constructions are strictly equivalent:

```
sage: GroupAlgebra(G, R) is G.algebra(R)
True
```

Group algebras are further endowed with a Hopf algebra structure; see below.

4.6.2 Generalizations

The above construction extends to weaker multiplicative structures than groups: magmas, semigroups, monoids. For a monoid S , we obtain the monoid algebra RS , which is defined exactly as above:

```
sage: S = Monoids().example(); S
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
sage: A = S.algebra(QQ); A
Algebra of An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
over Rational Field
sage: A.category()
Category of monoid algebras over Rational Field
```

This construction also extends to additive structures: magmas, semigroups, monoids, or groups:

```
sage: S = CommutativeAdditiveMonoids().example(); S
An example of a commutative monoid:
the free commutative monoid generated by ('a', 'b', 'c', 'd')
sage: U = S.algebra(QQ); U
Algebra of An example of a commutative monoid:
the free commutative monoid generated by ('a', 'b', 'c', 'd')
over Rational Field
```

Despite saying “free module”, this is really an algebra, whose multiplication is induced by the addition of elements of S :

```
sage: U in Algebras(QQ)
True
sage: (a,b,c,d) = S.additive_semigroup_generators()
sage: U(a) * U(b)
B[a + b]
```

To cater uniformly for the use cases above and some others, for S a set and K a ring, we define in Sage the *algebra of S* as the K -free module with basis indexed by S , endowed with whatever algebraic structure can be induced from that of S .

Warning: In most use cases, the result is actually an algebra, hence the name of this construction. In other cases this name is misleading:

```
sage: A = Sets().example().algebra(QQ); A
Algebra of Set of prime numbers (basic implementation)
over Rational Field
```

```

sage: A.category()
Category of set algebras over Rational Field
sage: A in Algebras(QQ)
False

Suggestions for a uniform, meaningful, and non misleading name are welcome!

```

To achieve this flexibility, the features are implemented as a *Covariant Functorial Constructions* that is essentially a hierarchy of categories each providing the relevant additional features:

```

sage: A = DihedralGroup(3).algebra(QQ)
sage: A.categories()
[Category of finite group algebras over Rational Field,
...
Category of group algebras over Rational Field,
...
Category of monoid algebras over Rational Field,
...
Category of semigroup algebras over Rational Field,
...
Category of unital magma algebras over Rational Field,
...
Category of magma algebras over Rational Field,
...
Category of set algebras over Rational Field,
...]

```

4.6.3 Specifying the algebraic structure

Constructing the algebra of a set endowed with both an additive and a multiplicative structure is ambiguous:

```

sage: Z3 = IntegerModRing(3)
sage: A = Z3.algebra(QQ)
Traceback (most recent call last):
...
TypeError: `S = Ring of integers modulo 3` is both
an additive and a multiplicative semigroup.
Constructing its algebra is ambiguous.
Please use, e.g., S.algebra(QQ, category=Semigroups())

```

This ambiguity can be resolved using the `category` argument of the construction:

```

sage: A = Z3.algebra(QQ, category=Monoids()); A
Algebra of Ring of integers modulo 3 over Rational Field
sage: A.category()
Category of finite dimensional monoid algebras over Rational Field

sage: A = Z3.algebra(QQ, category=CommutativeAdditiveGroups()); A
Algebra of Ring of integers modulo 3 over Rational Field
sage: A.category()
Category of finite dimensional commutative additive group algebras
over Rational Field

```

In general, the category argument can be used to specify which structure of S shall be extended to KS .

4.6.4 Group algebras, continued

Let us come back to the case of a group algebra $A = RG$. It is endowed with more structure and in particular that of a *Hopf algebra*:

```
sage: G = DihedralGroup(3)
sage: A = G.algebra(R); A
Algebra of Dihedral group of order 6 as a permutation group
      over Rational Field
sage: A in HopfAlgebras(R).FiniteDimensional().WithBasis()
True
```

The basis elements are *group-like* for the coproduct: $\Delta(g) = g \otimes g$:

```
sage: s
(1, 2, 3)
sage: s.coproduct()
(1, 2, 3) # (1, 2, 3)
```

The counit is the constant function 1 on the basis elements:

```
sage: A = GroupAlgebra(DihedralGroup(6), QQ)
sage: [A.counit(g) for g in A.basis()]
[1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1]
```

The antipode is given on basis elements by $\chi(g) = g^{-1}$:

```
sage: A = GroupAlgebra(DihedralGroup(3), QQ)
sage: s
(1, 2, 3)
sage: s.antipode()
(1, 3, 2)
```

By Maschke's theorem, for a finite group whose cardinality does not divide the characteristic of the base field, the algebra is semisimple:

```
sage: SymmetricGroup(5).algebra(QQ) in Algebras(QQ).Semisimple()
True
sage: CyclicPermutationGroup(10).algebra(FiniteField(7)) in Algebras.Semisimple
True
sage: CyclicPermutationGroup(10).algebra(FiniteField(5)) in Algebras.Semisimple
False
```


4.6.5 Coercions

Let RS be the algebra of some structure S . Then RS admits the natural coercion from any other algebra $R'S'$ of some structure S' , as long as R' coerces into R and S' coerces into S .

For example, since there is a natural inclusion from the dihedral group D_2 of order 4 into the symmetric group S_4 of order $4!$, and since there is a natural map from the integers to the rationals, there is a natural map from $\mathbf{Z}[D_2]$ to $\mathbf{Q}[S_4]$:

```
sage: A = DihedralGroup(2).algebra(ZZ)
sage: B = SymmetricGroup(4).algebra(QQ)
sage: a = A.an_element(); a
() + 2*(3,4) + 3*(1,2) + (1,2)(3,4)
sage: b = B.an_element(); b
() + (2,3,4) + 2*(1,3)(2,4) + 3*(1,4)(2,3)
sage: B(a)
() + 2*(3,4) + 3*(1,2) + (1,2)(3,4)
sage: a * b # a is automatically converted to an element of B
() + 2*(3,4) + 2*(2,3) + (2,3,4) + 3*(1,2) + (1,2)(3,4) + (1,3,2)
+ 3*(1,3,4,2) + 5*(1,3)(2,4) + 13*(1,3,2,4) + 12*(1,4,2,3) + 5*(1,4)(2,3)
sage: parent(a * b)
Symmetric group algebra of order 4 over Rational Field
```

There is no obvious map in the other direction, though:

```
sage: A(b)
Traceback (most recent call last):
...
TypeError: do not know how to make x (= () + (2,3,4) + 2*(1,3)(2,4) + 3*(1,4)(2,3))
an element of self
(=Algebra of Dihedral group of order 4 as a permutation group over Integer Ring)
```

If S is a unital (additive) magma, then RS is a unital algebra, and thus admits a coercion from its base ring R and any ring that coerces into R .

```
sage: G = DihedralGroup(2)
sage: A = G.algebra(ZZ)
sage: A(2)
2*(())
```

If S is a multiplicative group, then RS admits a coercion from S and from any group which coerces into S :

```
sage: g = DihedralGroup(2).gen(0); g
(3,4)
sage: A(g)
(3,4)
sage: A(2) * g
2*(3,4)
```

Note that there is an ambiguity if S' is a group which coerces into both R and S . For example) if S is the additive group $(\mathbf{Z}, +)$, and $A = RS$ is its group algebra, then the integer 2 can be coerced into A in two ways – via S , or via the base ring R – and *the answers are different*. In that case the coercion to R takes precedence. In particular, if \mathbf{Z} is the ring (or group) of integers, then \mathbf{Z} will coerce to any RS , by sending \mathbf{Z} to R . In generic code, it is therefore recommended to always explicitly use `A.monomial(g)` to convert an element of the group into A .

AUTHORS:

- David Loeffler (2008-08-24): initial version
- Martin Raum (2009-08): update to use new coercion model – see [trac ticket #6670](#).
- John Palmieri (2011-07): more updates to coercion, categories, etc., group algebras constructed using `CombinatorialFreeModule` – see [trac ticket #6670](#).
- Nicolas M. Thiéry (2010-2017), Travis Scrimshaw (2017): generalization to a covariant functorial construction for monoid algebras, and beyond – see e.g. [trac ticket #18700](#).

class `sage.categories.algebra_functor.AlgebraFunctor`(*base_ring*)

Bases: `sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction`

For a fixed ring, a functor sending a group/... to the corresponding group/... algebra.

EXAMPLES:

```
sage: from sage.categories.algebra_functor import AlgebraFunctor
sage: F = AlgebraFunctor(QQ); F
The algebra functorial construction
sage: F(DihedralGroup(3))
Algebra of Dihedral group of order 6 as a permutation group
      over Rational Field
```

base_ring()

Return the base ring for this functor.

EXAMPLES:

```
sage: from sage.categories.algebra_functor import AlgebraFunctor
sage: AlgebraFunctor(QQ).base_ring()
Rational Field
```

class `sage.categories.algebra_functor.AlgebrasCategory`(*category*, *args)

Bases: `sage.categories.covariant_functorial_construction.CovariantConstructionCategory`,
`sage.categories.category_types.Category_over_base_ring`

An abstract base class for categories of monoid algebras, groups algebras, and the like.

See also:

- `Sets.ParentMethods.algebra()`
- `Sets.SubcategoryMethods.Algebras()`
- `CovariantFunctorialConstruction`

INPUT:

- `base_ring` – a ring

EXAMPLES:

```
sage: C = Groups().Algebras(QQ); C
Category of group algebras over Rational Field
sage: C = Monoids().Algebras(QQ); C
Category of monoid algebras over Rational Field

sage: C._short_name()
'Algebras'
```

(continues on next page)

(continued from previous page)

```
sage: latex(C) # todo: improve that
\mathbf{Algebras}\mathbf{Monoids}
```

class ParentMethods

Bases: object

coproduct_on_basis(g)

Return the coproduct of the element g of the basis.

Each basis element g is group-like. This method is used to compute the coproduct of any element.

EXAMPLES:

```
sage: PF = NonDecreasingParkingFunctions(4)
sage: A = PF.algebra(ZZ); A
Algebra of Non-decreasing parking functions of size 4 over Integer Ring
sage: g = PF.an_element(); g
[1, 1, 1, 1]
sage: A.coproduct_on_basis(g)
B[[1, 1, 1, 1]] # B[[1, 1, 1, 1]]
sage: a = A.an_element(); a
2*B[[1, 1, 1, 1]] + 2*B[[1, 1, 1, 2]] + 3*B[[1, 1, 1, 3]]
sage: a.coproduct()
2*B[[1, 1, 1, 1]] # B[[1, 1, 1, 1]] +
2*B[[1, 1, 1, 2]] # B[[1, 1, 1, 2]] +
3*B[[1, 1, 1, 3]] # B[[1, 1, 1, 3]]
```

class sage.categories.algebra_functor.GroupAlgebraFunctor(group)Bases: *sage.categories.pushout.ConstructionFunctor*

For a fixed group, a functor sending a commutative ring to the corresponding group algebra.

INPUT:

- group – the group associated to each group algebra under consideration

EXAMPLES:

```
sage: from sage.categories.algebra_functor import GroupAlgebraFunctor
sage: F = GroupAlgebraFunctor(KleinFourGroup()); F
GroupAlgebraFunctor
sage: A = F(QQ); A
Algebra of The Klein 4 group of order 4, as a permutation group over Rational Field
```

group()

Return the group which is associated to this functor.

EXAMPLES:

```
sage: from sage.categories.algebra_functor import GroupAlgebraFunctor
sage: GroupAlgebraFunctor(CyclicPermutationGroup(17)).group() ==
↪ CyclicPermutationGroup(17)
True
```

4.7 Subquotient Functorial Construction

AUTHORS:

- Nicolas M. Thiery (2010): initial revision

class `sage.categories.subquotients.SubquotientsCategory(category, *args)`

Bases: `sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory`

4.8 Quotients Functorial Construction

AUTHORS:

- Nicolas M. Thiery (2010): initial revision

class `sage.categories.quotients.QuotientsCategory(category, *args)`

Bases: `sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory`

classmethod `default_super_categories(category)`

Returns the default super categories of `category.Quotients()`

Mathematical meaning: if A is a quotient of B in the category C , then A is also a subquotient of B in the category C .

INPUT:

- `cls` – the class `QuotientsCategory`
- `category` – a category Cat

OUTPUT: a (join) category

In practice, this returns `category.Subquotients()`, joined together with the result of the method `RegressiveCovariantConstructionCategory.default_super_categories()` (that is the join of `category` and `cat.Quotients()` for each `cat` in the super categories of `category`).

EXAMPLES:

Consider `category=Groups()`, which has `cat=Monoids()` as super category. Then, a subgroup of a group G is simultaneously a subquotient of G , a group by itself, and a quotient monoid of G :

```
sage: Groups().Quotients().super_categories()
[Category of groups, Category of subquotients of monoids, Category of quotients_
↳of semigroups]
```

Mind the last item above: there is indeed currently nothing implemented about quotient monoids.

This resulted from the following call:

```
sage: sage.categories.quotients.QuotientsCategory.default_super_
↳categories(Groups())
Join of Category of groups and Category of subquotients of monoids and Category_
↳of quotients of semigroups
```

4.9 Subobjects Functorial Construction

AUTHORS:

- Nicolas M. Thiery (2010): initial revision

class `sage.categories.subobjects.SubobjectsCategory(category, *args)`

Bases: `sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory`

classmethod `default_super_categories(category)`

Returns the default super categories of `category.Subobjects()`

Mathematical meaning: if A is a subobject of B in the category C , then A is also a subquotient of B in the category C .

INPUT:

- `cls` – the class `SubobjectsCategory`
- `category` – a category Cat

OUTPUT: a (join) category

In practice, this returns `category.Subquotients()`, joined together with the result of the method `RegressiveCovariantConstructionCategory.default_super_categories()` (that is the join of `category` and `cat.Subobjects()` for each `cat` in the super categories of `category`).

EXAMPLES:

Consider `category=Groups()`, which has `cat=Monoids()` as super category. Then, a subgroup of a group G is simultaneously a subquotient of G , a group by itself, and a submonoid of G :

```
sage: Groups().Subobjects().super_categories()
[Category of groups, Category of subquotients of monoids, Category of
↳subobjects of sets]
```

Mind the last item above: there is indeed currently nothing implemented about submonoids.

This resulted from the following call:

```
sage: sage.categories.subobjects.SubobjectsCategory.default_super_
↳categories(Groups())
Join of Category of groups and Category of subquotients of monoids and Category
↳of subobjects of sets
```

4.10 Isomorphic Objects Functorial Construction

AUTHORS:

- Nicolas M. Thiery (2010): initial revision

class `sage.categories.isomorphic_objects.IsomorphicObjectsCategory(category, *args)`

Bases: `sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory`

classmethod `default_super_categories(category)`

Returns the default super categories of `category.IsomorphicObjects()`

Mathematical meaning: if A is the image of B by an isomorphism in the category C , then A is both a subobject of B and a quotient of B in the category C .

INPUT:

- `cls` – the class `IsomorphicObjectsCategory`
- `category` – a category Cat

OUTPUT: a (join) category

In practice, this returns `category.Subobjects()` and `category.Quotients()`, joined together with the result of the method `RegressiveCovariantConstructionCategory.default_super_categories()` (that is the join of `category` and `cat.IsomorphicObjects()` for each `cat` in the super categories of `category`).

EXAMPLES:

Consider `category=Groups()`, which has `cat=Monoids()` as super category. Then, the image of a group G' by a group isomorphism is simultaneously a subgroup of G , a subquotient of G , a group by itself, and the image of G by a monoid isomorphism:

```
sage: Groups().IsomorphicObjects().super_categories()
[Category of groups,
 Category of subquotients of monoids,
 Category of quotients of semigroups,
 Category of isomorphic objects of sets]
```

Mind the last item above: there is indeed currently nothing implemented about isomorphic objects of monoids.

This resulted from the following call:

```
sage: sage.categories.isomorphic_objects.IsomorphicObjectsCategory.default_
↪super_categories(Groups())
Join of Category of groups and
Category of subquotients of monoids and
Category of quotients of semigroups and
Category of isomorphic objects of sets
```

4.11 Homset categories

```
class sage.categories.homsets.Homsets(s=None)
```

Bases: `sage.categories.category_singleton.Category_singleton`

The category of all homsets.

EXAMPLES:

```
sage: from sage.categories.homsets import Homsets
sage: Homsets()
Category of homsets
```

This is a subcategory of `Sets()`:

```
sage: Homsets().super_categories()
[Category of sets]
```

By this, we assume that all homsets implemented in Sage are sets, or equivalently that we only implement locally small categories. See [Wikipedia article Category_\(mathematics\)](#).

trac ticket #17364: every homset category shall be a subcategory of the category of all homsets:

```
sage: Schemes().Homsets().is_subcategory(Homsets())
True
sage: AdditiveMagmas().Homsets().is_subcategory(Homsets())
True
sage: AdditiveMagmas().AdditiveUnital().Homsets().is_subcategory(Homsets())
True
```

This is tested in `HomsetsCategory._test_homsets_category()`.

class Endset(*base_category*)

Bases: [sage.categories.category_with_axiom.CategoryWithAxiom](#)

The category of all endomorphism sets.

This category serves two purposes: making sure that the `Endset` axiom is implemented in the category where it's defined, namely `Homsets`, and specifying that `Endsets` are monoids.

EXAMPLES:

```
sage: from sage.categories.homsets import Homsets
sage: Homsets().Endset()
Category of endsets
```

class ParentMethods

Bases: `object`

is_endomorphism_set()

Return `True` as `self` is in the category of `Endsets`.

EXAMPLES:

```
sage: P.<t> = ZZ[]
sage: E = End(P)
sage: E.is_endomorphism_set()
True
```

extra_super_categories()

Implement the fact that endsets are monoids.

See also:

[CategoryWithAxiom.extra_super_categories\(\)](#)

EXAMPLES:

```
sage: from sage.categories.homsets import Homsets
sage: Homsets().Endset().extra_super_categories()
[Category of monoids]
```

class ParentMethods

Bases: `object`

is_endomorphism_set()

Return `True` if the domain and codomain of `self` are the same object.

EXAMPLES:

```

sage: P.<t> = ZZ[]
sage: f = P.hom([1/2*t])
sage: f.parent().is_endomorphism_set()
False
sage: g = P.hom([2*t])
sage: g.parent().is_endomorphism_set()
True

```

class SubcategoryMethods

Bases: object

Endset()Return the subcategory of the homsets of `self` that are endomorphism sets.

EXAMPLES:

```

sage: Sets().Homsets().Endset()
Category of endsets of sets

sage: Posets().Homsets().Endset()
Category of endsets of posets

```

super_categories()Return the super categories of `self`.

EXAMPLES:

```

sage: from sage.categories.homsets import Homsets
sage: Homsets()
Category of homsets

```

class sage.categories.homsets.HomsetsCategory(category, *args)Bases: *sage.categories.covariant_functorial_construction.FunctorialConstructionCategory***base()**

If this homsets category is subcategory of a category with a base, return that base.

Todo: Is this really useful?

EXAMPLES:

```

sage: ModulesWithBasis(ZZ).Homsets().base()
Integer Ring

```

classmethod default_super_categories(category)Return the default super categories of `category.Homsets()`.

INPUT:

- `cls` – the category class for the functor F
- `category` – a category Cat

OUTPUT: a category

As for the other functorial constructions, if `category` implements a nested `Homsets` class, this method is used in combination with `category.Homsets().extra_super_categories()` to compute the super categories of `category.Homsets()`.

EXAMPLES:

If `category` has one or more full super categories, then the join of their respective homsets category is returned. In this example, this join consists of a single category:

```
sage: from sage.categories.homsets import HomsetsCategory
sage: from sage.categories.additive_groups import AdditiveGroups

sage: C = AdditiveGroups()
sage: C.full_super_categories()
[Category of additive inverse additive unital additive magmas,
 Category of additive monoids]
sage: H = HomsetsCategory.default_super_categories(C); H
Category of homsets of additive monoids
sage: type(H)
<class 'sage.categories.additive_monoids.AdditiveMonoids.Homsets_with_category'>
```

and, given that nothing specific is currently implemented for homsets of additive groups, H is directly the category thereof:

```
sage: C.Homsets()
Category of homsets of additive monoids
```

Similarly for rings: a ring homset is just a homset of unital magmas and additive magmas:

```
sage: Rings().Homsets()
Category of homsets of unital magmas and additive unital additive magmas
```

Otherwise, if `category` implements a nested class `Homsets`, this method returns the category of all homsets:

```
sage: AdditiveMagmas.Homsets
<class 'sage.categories.additive_magmas.AdditiveMagmas.Homsets'>
sage: HomsetsCategory.default_super_categories(AdditiveMagmas())
Category of homsets
```

which gives one of the super categories of `category.Homsets()`:

```
sage: AdditiveMagmas().Homsets().super_categories()
[Category of additive magmas, Category of homsets]
sage: AdditiveMagmas().AdditiveUnital().Homsets().super_categories()
[Category of additive unital additive magmas, Category of homsets]
```

the other coming from `category.Homsets().extra_super_categories()`:

```
sage: AdditiveMagmas().Homsets().extra_super_categories()
[Category of additive magmas]
```

Finally, as a last resort, this method returns a stub category modelling the homsets of this category:

```
sage: hasattr(Posets, "Homsets")
False
```

(continues on next page)

(continued from previous page)

```

sage: H = HomsetsCategory.default_super_categories(Posets()); H
Category of homsets of posets
sage: type(H)
<class 'sage.categories.homsets.HomsetsOf_with_category'>
sage: Posets().Homsets()
Category of homsets of posets

```

class `sage.categories.homsets.HomsetsOf(category, *args)`

Bases: `sage.categories.homsets.HomsetsCategory`

Default class for homsets of a category.

This is used when a category C defines some additional structure but not a homset category of its own. Indeed, unlike for covariant functorial constructions, we cannot represent the homset category of C by just the join of the homset categories of its super categories.

EXAMPLES:

```

sage: C = (Magmas() & Posets()).Homsets(); C
Category of homsets of magmas and posets
sage: type(C)
<class 'sage.categories.homsets.HomsetsOf_with_category'>

```

super_categories()

Return the super categories of self.

A stub homset category admits a single super category, namely the category of all homsets.

EXAMPLES:

```

sage: C = (Magmas() & Posets()).Homsets(); C
Category of homsets of magmas and posets
sage: type(C)
<class 'sage.categories.homsets.HomsetsOf_with_category'>
sage: C.super_categories()
[Category of homsets]

```

4.12 Realizations Covariant Functorial Construction

See also:

- `Sets().WithRealizations` for an introduction to *realizations* and *with realizations*.
- `sage.categories.covariant_functorial_construction` for an introduction to covariant functorial constructions.
- `sage.categories.examples.with_realizations` for an example.

class `sage.categories.realizations.Category_realization_of_parent(parent_with_realization)`

Bases: `sage.categories.category_types.Category_over_base`, `sage.misc.bindable_class.BindableClass`

An abstract base class for categories of all realizations of a given parent

INPUT:

- `parent_with_realization` – a parent

See also:

[Sets\(\).WithRealizations](#)

EXAMPLES:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
```

The role of this base class is to implement some technical goodies, like the binding `A.Realizations()` when a subclass `Realizations` is implemented as a nested class in `A` (see the [code of the example](#)):

```
sage: C = A.Realizations(); C
Category of realizations of The subset algebra of {1, 2, 3} over Rational Field
```

as well as the name for that category.

`sage.categories.realizations.Realizations(self)`

Return the category of realizations of the parent `self` or of objects of the category `self`

INPUT:

- `self` – a parent or a concrete category

Note: this *function* is actually inserted as a *method* in the class `Category` (see [Realizations\(\)](#)). It is defined here for code locality reasons.

EXAMPLES:

The category of realizations of some algebra:

```
sage: Algebras(QQ).Realizations()
Join of Category of algebras over Rational Field and Category of realizations of
↳ unital magmas
```

The category of realizations of a given algebra:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.Realizations()
Category of realizations of The subset algebra of {1, 2, 3} over Rational Field

sage: C = GradedHopfAlgebrasWithBasis(QQ).Realizations(); C
Join of Category of graded hopf algebras with basis over Rational Field and
↳ Category of realizations of hopf algebras over Rational Field
sage: C.super_categories()
[Category of graded hopf algebras with basis over Rational Field, Category of
↳ realizations of hopf algebras over Rational Field]

sage: TestSuite(C).run()
```

See also:

- [Sets\(\).WithRealizations](#)
- `ClasscallMetaclass`

Todo: Add an optional argument to allow for:

sage: `Realizations(A, category = Blahs()) # todo: not implemented`

class `sage.categories.realizations.RealizationsCategory(category, *args)`

Bases: `sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory`

An abstract base class for all categories of realizations category

Realization are implemented as `RegressiveCovariantConstructionCategory`. See there for the documentation of how the various bindings such as `Sets().Realizations()` and `P.Realizations()`, where P is a parent, work.

See also:

`Sets().WithRealizations`

4.13 With Realizations Covariant Functorial Construction

See also:

- `Sets().WithRealizations` for an introduction to *realizations* and *with realizations*.
- `sage.categories.covariant_functorial_construction` for an introduction to covariant functorial constructions.

`sage.categories.with_realizations.WithRealizations(self)`

Return the category of parents in `self` endowed with multiple realizations.

INPUT:

- `self` – a category

See also:

- The documentation and code (`sage.categories.examples.with_realizations`) of `Sets().WithRealizations().example()` for more on how to use and implement a parent with several realizations.
- Various use cases:
 - `SymmetricFunctions`
 - `QuasiSymmetricFunctions`
 - `NonCommutativeSymmetricFunctions`
 - `SymmetricFunctionsNonCommutingVariables`
 - `DescentAlgebra`
 - `algebras.Moebius`
 - `IwahoriHeckeAlgebra`
 - `ExtendedAffineWeylGroup`
- The [Implementing Algebraic Structures](#) thematic tutorial.
- `sage.categories.realizations`

Note: this *function* is actually inserted as a *method* in the class `Category` (see `WithRealizations()`). It is defined here for code locality reasons.

EXAMPLES:

```
sage: Sets().WithRealizations()
Category of sets with realizations
```

Parent with realizations

Let us now explain the concept of realizations. A *parent with realizations* is a facade parent (see `Sets.Facade`) admitting multiple concrete realizations where its elements are represented. Consider for example an algebra A which admits several natural bases:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
```

For each such basis B one implements a parent P_B which realizes A with its elements represented by expanding them on the basis B :

```
sage: A.F()
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis
sage: A.Out()
The subset algebra of {1, 2, 3} over Rational Field in the Out basis
sage: A.In()
The subset algebra of {1, 2, 3} over Rational Field in the In basis

sage: A.an_element()
F[{}] + 2*F[{1}] + 3*F[{2}] + F[{1, 2}]
```

If B and B' are two bases, then the change of basis from B to B' is implemented by a canonical coercion between P_B and $P_{B'}$:

```
sage: F = A.F(); In = A.In(); Out = A.Out()
sage: i = In.an_element(); i
In[{}] + 2*In[{1}] + 3*In[{2}] + In[{1, 2}]
sage: F(i)
7*F[{}] + 3*F[{1}] + 4*F[{2}] + F[{1, 2}]
sage: F.coerce_map_from(Out)
Generic morphism:
  From: The subset algebra of {1, 2, 3} over Rational Field in the Out basis
  To:   The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis
```

allowing for mixed arithmetic:

```
sage: (1 + Out.from_set(1)) * In.from_set(2,3)
Out[{}] + 2*Out[{1}] + 2*Out[{2}] + 2*Out[{3}] + 2*Out[{1, 2}] + 2*Out[{1, 3}] +
↪ 4*Out[{2, 3}] + 4*Out[{1, 2, 3}]
```

In our example, there are three realizations:

```
sage: A.realizations()
[The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis,
The subset algebra of {1, 2, 3} over Rational Field in the In basis,
The subset algebra of {1, 2, 3} over Rational Field in the Out basis]
```

Instead of manually defining the shorthands `F`, `In`, and `Out`, as above one can just do:

```
sage: A.inject_shorthands()
Defining F as shorthand for The subset algebra of {1, 2, 3} over Rational Field in
↳the Fundamental basis
Defining In as shorthand for The subset algebra of {1, 2, 3} over Rational Field in
↳the In basis
Defining Out as shorthand for The subset algebra of {1, 2, 3} over Rational Field
↳in the Out basis
```

Rationale

Besides some goodies described below, the role of A is threefold:

- To provide, as illustrated above, a single entry point for the algebra as a whole: documentation, access to its properties and different realizations, etc.
- To provide a natural location for the initialization of the bases and the coercions between, and other methods that are common to all bases.
- To let other objects refer to A while allowing elements to be represented in any of the realizations.

We now illustrate this second point by defining the polynomial ring with coefficients in A :

```
sage: P = A['x']; P
Univariate Polynomial Ring in x over The subset algebra of {1, 2, 3} over Rational
↳Field
sage: x = P.gen()
```

In the following examples, the coefficients turn out to be all represented in the F basis:

```
sage: P.one()
F[{}]
sage: (P.an_element() + 1)^2
F[{}]*x^2 + 2*F[{}]*x + F[{}]
```

However we can create a polynomial with mixed coefficients, and compute with it:

```
sage: p = P([1, In[{1}], Out[{2}] ]); p
Out[{2}]*x^2 + In[{1}]*x + F[{}]
sage: p^2
Out[{2}]*x^4
+ (-8*In[{}] + 4*In[{1}] + 8*In[{2}] + 4*In[{3}] - 4*In[{1, 2}] - 2*In[{1, 3}] -
↳4*In[{2, 3}] + 2*In[{1, 2, 3}])*x^3
+ (F[{}] + 3*F[{1}] + 2*F[{2}] - 2*F[{1, 2}] - 2*F[{2, 3}] + 2*F[{1, 2, 3}])*x^2
+ (2*F[{}] + 2*F[{1}])*x
+ F[{}]
```

Note how each coefficient involves a single basis which need not be that of the other coefficients. Which basis is used depends on how coercion happened during mixed arithmetic and needs not be deterministic.

One can easily coerce all coefficient to a given basis with:

```
sage: p.map_coefficients(In)
(-4*In[{}] + 2*In[{1}] + 4*In[{2}] + 2*In[{3}] - 2*In[{1, 2}] - In[{1, 3}] - 2*In[
↪{2, 3}] + In[{1, 2, 3}])*x^2 + In[{1}]*x + In[{}]
```

Alas, the natural notation for constructing such polynomials does not yet work:

```
sage: In[{1}] * x
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *: 'The subset algebra of {1, 2, 3}
↪over Rational Field in the In basis' and 'Univariate Polynomial Ring in x over
↪The subset algebra of {1, 2, 3} over Rational Field'
```

The category of realizations of A

The set of all realizations of A , together with the coercion morphisms is a category (whose class inherits from `Category_realization_of_parent`):

```
sage: A.Realizations()
Category of realizations of The subset algebra of {1, 2, 3} over Rational Field
```

The various parent realizing A belong to this category:

```
sage: A.F() in A.Realizations()
True
```

A itself is in the category of algebras with realizations:

```
sage: A in Algebras(QQ).WithRealizations()
True
```

The (mostly technical) `WithRealizations` categories are the analogs of the `*WithSeveralBases` categories in MuPAD-Combinat. They provide support tools for handling the different realizations and the morphisms between them.

Typically, `VectorSpaces(QQ).FiniteDimensional().WithRealizations()` will eventually be in charge, whenever a coercion $\phi : A \mapsto B$ is registered, to register ϕ^{-1} as coercion $B \mapsto A$ if there is none defined yet. To achieve this, `FiniteDimensionalVectorSpaces` would provide a nested class `WithRealizations` implementing the appropriate logic.

`WithRealizations` is a *regressive covariant functorial construction*. On our example, this simply means that A is automatically in the category of rings with realizations (covariance):

```
sage: A in Rings().WithRealizations()
True
```

and in the category of algebras (regressiveness):

```
sage: A in Algebras(QQ)
True
```

Note: For C a category, `C.WithRealizations()` in fact calls `sage.categories.with_realizations.WithRealizations(C)`. The later is responsible for building the hierarchy of the categories with realizations in parallel to that of their base categories, optimizing away those categories that do not provide a `WithRealizations` nested class. See [sage.categories.covariant_functorial_construction](#) for the technical details.

Note: Design question: currently `WithRealizations` is a regressive construction. That is `self.WithRealizations()` is a subcategory of `self` by default:

sage: `Algebras(QQ).WithRealizations().super_categories()`
[Category of algebras over Rational Field,
Category of monoids with realizations,
Category of additive unital additive magmas with realizations]

Is this always desirable? For example, `AlgebrasWithBasis(QQ).WithRealizations()` should certainly be a subcategory of `Algebras(QQ)`, but not of `AlgebrasWithBasis(QQ)`. This is because `AlgebrasWithBasis(QQ)` is specifying something about the concrete realization.

class `sage.categories.with_realizations.WithRealizationsCategory`(*category*, **args*)

Bases: [sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory](#)

An abstract base class for all categories of parents with multiple realizations.

See also:

[Sets\(\).WithRealizations](#)

The role of this base class is to implement some technical goodies, such as the name for that category.

EXAMPLES OF PARENTS USING CATEGORIES

5.1 Examples of algebras with basis

`sage.categories.examples.algebras_with_basis.Example`
alias of `sage.categories.examples.algebras_with_basis.FreeAlgebra`

class `sage.categories.examples.algebras_with_basis.FreeAlgebra(R, alphabet=('a', 'b', 'c'))`
Bases: `sage.combinat.free_module.CombinatorialFreeModule`

An example of an algebra with basis: the free algebra

This class illustrates a minimal implementation of an algebra with basis.

algebra_generators()

Return the generators of this algebra, as per `algebra_generators()`.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example(); A
An example of an algebra with basis: the free algebra on the generators ('a', 'b
↩', 'c') over Rational Field
sage: A.algebra_generators()
Family (B[word: a], B[word: b], B[word: c])
```

one_basis()

Returns the empty word, which index the one of this algebra, as per `AlgebrasWithBasis.ParentMethods.one_basis()`.

EXAMPLES::r

```
sage: A = AlgebrasWithBasis(QQ).example() sage: A.one_basis() word: sage: A.one() B[word:
]
```

product_on_basis(w1, w2)

Product of basis elements, as per `AlgebrasWithBasis.ParentMethods.product_on_basis()`.

EXAMPLES:

```
sage: A = AlgebrasWithBasis(QQ).example()
sage: Words = A.basis().keys()
sage: A.product_on_basis(Words("acb"), Words("cba"))
B[word: acbcb]
sage: (a,b,c) = A.algebra_generators()
sage: a * (1-b)^2 * c
B[word: abbc] - 2*B[word: abc] + B[word: ac]
```

5.2 Examples of commutative additive monoids

`sage.categories.examples.commutative_additive_monoids.Example`

alias of `sage.categories.examples.commutative_additive_monoids.FreeCommutativeAdditiveMonoid`

```
class sage.categories.examples.commutative_additive_monoids.FreeCommutativeAdditiveMonoid(alphabet=('a',
                                                                                                     'b',
                                                                                                     'c',
                                                                                                     'd'))
```

Bases: `sage.categories.examples.commutative_additive_semigroups.FreeCommutativeAdditiveSemigroup`

An example of a commutative additive monoid: the free commutative monoid

This class illustrates a minimal implementation of a commutative monoid.

EXAMPLES:

```
sage: S = CommutativeAdditiveMonoids().example(); S
An example of a commutative monoid: the free commutative monoid generated by ('a',
↪ 'b', 'c', 'd')

sage: S.category()
Category of commutative additive monoids
```

This is the free semigroup generated by:

```
sage: S.additive_semigroup_generators()
Family (a, b, c, d)
```

with product rule given by $a \times b = a$ for all a, b :

```
sage: (a,b,c,d) = S.additive_semigroup_generators()
```

We conclude by running systematic tests on this commutative monoid:

```
sage: TestSuite(S).run(verbose = True)
running ._test_additive_associativity() . . . pass
running ._test_an_element() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_nonzero_equal() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
```

(continues on next page)

(continued from previous page)

```

running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass
running ._test_zero() . . . pass

```

class `Element`(*parent, iterable*)

Bases: `sage.categories.examples.commutative_additive_semigroups.FreeCommutativeAdditiveSemigroup.Element`

zero()

Returns the zero of this additive monoid, as per `CommutativeAdditiveMonoids.ParentMethods.zero()`.

EXAMPLES:

```

sage: M = CommutativeAdditiveMonoids().example(); M
An example of a commutative monoid: the free commutative monoid generated by ('a
→', 'b', 'c', 'd')
sage: M.zero()
0

```

5.3 Examples of commutative additive semigroups

`sage.categories.examples.commutative_additive_semigroups.Example`
 alias of `sage.categories.examples.commutative_additive_semigroups.FreeCommutativeAdditiveSemigroup`

class `sage.categories.examples.commutative_additive_semigroups.FreeCommutativeAdditiveSemigroup`(*alphabet=*
'b',
'c',
'd'))

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a commutative additive monoid: the free commutative monoid

This class illustrates a minimal implementation of a commutative additive monoid.

EXAMPLES:

```

sage: S = CommutativeAdditiveSemigroups().example(); S
An example of a commutative semigroup: the free commutative semigroup generated by (
→'a', 'b', 'c', 'd')
sage: S.category()
Category of commutative additive semigroups

```

This is the free semigroup generated by:

```

sage: S.additive_semigroup_generators()
Family (a, b, c, d)

```

with product rule given by $a \times b = a$ for all a, b :

```
sage: (a,b,c,d) = S.additive_semigroup_generators()
```

We conclude by running systematic tests on this commutative monoid:

```
sage: TestSuite(S).run(verbose = True)
running ._test_additive_associativity() . . . pass
running ._test_an_element() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass
```

class `Element`(*parent, iterable*)

Bases: `sage.structure.element_wrapper.ElementWrapper`

EXAMPLES:

```
sage: F = CommutativeAdditiveSemigroups().example()
sage: x = F.element_class(F, (('a',4), ('b', 0), ('a', 2), ('c', 1), ('d', 5)))
sage: x
2*a + c + 5*d
sage: x.value
{'a': 2, 'b': 0, 'c': 1, 'd': 5}
sage: x.parent()
An example of a commutative semigroup: the free commutative semigroup generated_
↳by ('a', 'b', 'c', 'd')
```

Internally, elements are represented as dense dictionaries which associate to each generator of the monoid its multiplicity. In order to get an element, we wrap the dictionary into an element via `ElementWrapper`:

```
sage: x.value
{'a': 2, 'b': 0, 'c': 1, 'd': 5}
```

additive_semigroup_generators()

Returns the generators of the semigroup.

EXAMPLES:

```
sage: F = CommutativeAdditiveSemigroups().example()
sage: F.additive_semigroup_generators()
Family (a, b, c, d)
```

an_element()

Returns an element of the semigroup.

EXAMPLES:

```
sage: F = CommutativeAdditiveSemigroups().example()
sage: F.an_element()
a + 2*b + 3*c + 4*d
```

summation(x, y)

Returns the product of x and y in the semigroup, as per `CommutativeAdditiveSemigroups.ParentMethods.summation()`.

EXAMPLES:

```
sage: F = CommutativeAdditiveSemigroups().example()
sage: (a,b,c,d) = F.additive_semigroup_generators()
sage: F.summation(a,b)
a + b
sage: (a+b) + (a+c)
2*a + b + c
```

5.4 Examples of Coxeter groups

5.5 Example of a crystal

class `sage.categories.examples.crystals.HighestWeightCrystalOfTypeA($n=3$)`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a crystal: the highest weight crystal of type A_n of highest weight ω_1 .

The purpose of this class is to provide a minimal template for implementing crystals. See `CrystalOfLetters` for a full featured and optimized implementation.

EXAMPLES:

```
sage: C = Crystals().example()
sage: C
Highest weight crystal of type A_3 of highest weight omega_1
sage: C.category()
Category of classical crystals
```

The elements of this crystal are in the set $\{1, \dots, n + 1\}$:

```
sage: C.list()
[1, 2, 3, 4]
sage: C.module_generators[0]
1
```

The crystal operators themselves correspond to the elementary transpositions:

```
sage: b = C.module_generators[0]
sage: b.f(1)
2
sage: b.f(1).e(1) == b
True
```

Only the following basic operations are implemented:

- `cartan_type()` or an attribute `_cartan_type`
- an attribute `module_generators`
- `Element.e()`
- `Element.f()`

All the other usual crystal operations are inherited from the categories; for example:

```
sage: C.cardinality()
4
```

class `Element`

Bases: `sage.structure.element_wrapper.ElementWrapper`

`e(i)`

Returns the action of e_i on self.

EXAMPLES:

```
sage: C = Crystals().example(4)
sage: [[c,i,c.e(i)] for i in C.index_set() for c in C if c.e(i) is not None]
[[2, 1, 1], [3, 2, 2], [4, 3, 3], [5, 4, 4]]
```

`f(i)`

Returns the action of f_i on self.

EXAMPLES:

```
sage: C = Crystals().example(4)
sage: [[c,i,c.f(i)] for i in C.index_set() for c in C if c.f(i) is not None]
[[1, 1, 2], [2, 2, 3], [3, 3, 4], [4, 4, 5]]
```

class `sage.categories.examples.crystals.NaiveCrystal`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

This is an example of a “crystal” which does not come from any kind of representation, designed primarily to test the Stembridge local rules with. The crystal has vertices labeled 0 through 5, with 0 the highest weight.

The code here could also possibly be generalized to create a class that automatically builds a crystal from an edge-colored digraph, if someone feels adventurous.

Currently, only the methods `highest_weight_vector()`, `e()`, and `f()` are guaranteed to work.

EXAMPLES:

```
sage: C = Crystals().example(choice='naive')
sage: C.highest_weight_vector()
0
```

class ElementBases: `sage.structure.element_wrapper.ElementWrapper`**e(i)**Returns the action of e_i on self.

EXAMPLES:

```
sage: C = Crystals().example(choicе='naive')
sage: [[c,i,c.e(i)] for i in C.index_set() for c in [C(j) for j in [0..5]]]
↳if c.e(i) is not None]
[[1, 1, 0], [2, 1, 1], [3, 1, 2], [5, 1, 3], [4, 2, 0], [5, 2, 4]]
```

f(i)Returns the action of f_i on self.

EXAMPLES:

```
sage: C = Crystals().example(choicе='naive')
sage: [[c,i,c.f(i)] for i in C.index_set() for c in [C(j) for j in [0..5]]]
↳if c.f(i) is not None]
[[0, 1, 1], [1, 1, 2], [2, 1, 3], [3, 1, 5], [0, 2, 4], [4, 2, 5]]
```

5.6 Examples of CW complexes

`sage.categories.examples.cw_complexes.Example`alias of `sage.categories.examples.cw_complexes.Surface`**class** `sage.categories.examples.cw_complexes.Surface`(*bdy*=(1, 2, 1, 2))Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a CW complex: a (2-dimensional) surface.

This class illustrates a minimal implementation of a CW complex.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: X = CWComplexes().example(); X
An example of a CW complex: the surface given by the boundary map (1, 2, 1, 2)

sage: X.category()
Category of finite finite dimensional CW complexes
```

We conclude by running systematic tests on this manifold:

```
sage: TestSuite(X).run()
```

class `Element`(*parent*, *dim*, *name*)Bases: `sage.structure.element.Element`

A cell in a CW complex.

dimension()

Return the dimension of self.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: X = CWComplexes().example()
sage: f = X.an_element()
sage: f.dimension()
2
```

an_element()

Return an element of the CW complex, as per *Sets.ParentMethods.an_element()*.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: X = CWComplexes().example()
sage: X.an_element()
2-cell f
```

cells()

Return the cells of self.

EXAMPLES:

```
sage: from sage.categories.cw_complexes import CWComplexes
sage: X = CWComplexes().example()
sage: C = X.cells()
sage: sorted((d, C[d]) for d in C.keys())
[(0, (0-cell v,)),
 (1, (0-cell e1, 0-cell e2)),
 (2, (2-cell f,))]
```

5.7 Example of facade set

class sage.categories.examples.facade_sets.IntegersCompletion

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a facade parent: the set of integers completed with $+\infty$

This class illustrates a minimal implementation of a facade parent that models the union of several other parents.

EXAMPLES:

```
sage: S = Sets().Facade().example("union"); S
An example of a facade set: the integers completed by +-infinity
```

class sage.categories.examples.facade_sets.PositiveIntegerMonoid

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a facade parent: the positive integers viewed as a multiplicative monoid

This class illustrates a minimal implementation of a facade parent which models a subset of a set.

EXAMPLES:

```
sage: S = Sets().Facade().example(); S
An example of facade set: the monoid of positive integers
```


5.8 Examples of finite Coxeter groups

class `sage.categories.examples.finite_coxeter_groups.DihedralGroup($n=5$)`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of finite Coxeter group: the n -th dihedral group of order $2n$.

The purpose of this class is to provide a minimal template for implementing finite Coxeter groups. See `DihedralGroup` for a full featured and optimized implementation.

EXAMPLES:

```
sage: G = FiniteCoxeterGroups().example()
```

This group is generated by two simple reflections s_1 and s_2 subject to the relation $(s_1 s_2)^n = 1$:

```
sage: G.simple_reflections()
Finite family {1: (1,), 2: (2,)}

sage: s1, s2 = G.simple_reflections()
sage: (s1*s2)^5 == G.one()
True
```

An element is represented by its reduced word (a tuple of elements of `self.index_set()`):

```
sage: G.an_element()
(1, 2)

sage: list(G)
[(),
 (1,),
 (2,),
 (1, 2),
 (2, 1),
 (1, 2, 1),
 (2, 1, 2),
 (1, 2, 1, 2),
 (2, 1, 2, 1),
 (1, 2, 1, 2, 1)]
```

This reduced word is unique, except for the longest element where the chosen reduced word is $(1, 2, 1, 2, \dots)$:

```
sage: G.long_element()
(1, 2, 1, 2, 1)
```

class `Element`

Bases: `sage.structure.element_wrapper.ElementWrapper`

apply_simple_reflection_right(i)

Implements `CoxeterGroups.ElementMethods.apply_simple_reflection()`.

EXAMPLES:

```
sage: D5 = FiniteCoxeterGroups().example(5)
sage: [i^2 for i in D5] # indirect doctest
```

(continues on next page)

(continued from previous page)

```
[(), (), (), (1, 2, 1, 2), (2, 1, 2, 1), (), (), (2, 1), (1, 2), ()]
sage: [i^5 for i in D5] # indirect doctest
[(), (1,), (2,), (), (), (1, 2, 1), (2, 1, 2), (), (), (1, 2, 1, 2, 1)]
```

has_right_descent(*i*, *positive=False*, *side='right'*)

Implements `SemiGroups.ElementMethods.has_right_descent()`.

EXAMPLES:

```
sage: D6 = FiniteCoxeterGroups().example(6)
sage: s = D6.simple_reflections()
sage: s[1].has_descent(1)
True
sage: s[1].has_descent(1)
True
sage: s[1].has_descent(2)
False
sage: D6.one().has_descent(1)
False
sage: D6.one().has_descent(2)
False
sage: D6.long_element().has_descent(1)
True
sage: D6.long_element().has_descent(2)
True
```

wrapped_class

alias of `builtins.tuple`

coxeter_matrix()

Return the Coxeter matrix of `self`.

EXAMPLES:

```
sage: FiniteCoxeterGroups().example(6).coxeter_matrix()
[1 6]
[6 1]
```

degrees()

Return the degrees of `self`.

EXAMPLES:

```
sage: FiniteCoxeterGroups().example(6).degrees()
(2, 6)
```

index_set()

Implements `CoxeterGroups.ParentMethods.index_set()`.

EXAMPLES:

```
sage: D4 = FiniteCoxeterGroups().example(4)
sage: D4.index_set()
(1, 2)
```

one()Implements `Monoids.ParentMethods.one()`.

EXAMPLES:

```
sage: D6 = FiniteCoxeterGroups().example(6)
sage: D6.one()
()
```

`sage.categories.examples.finite_coxeter_groups.Example`alias of `sage.categories.examples.finite_coxeter_groups.DihedralGroup`

5.9 Example of a finite dimensional algebra with basis

`sage.categories.examples.finite_dimensional_algebras_with_basis.Example`alias of `sage.categories.examples.finite_dimensional_algebras_with_basis.KroneckerQuiverPathAlgebra`**class** `sage.categories.examples.finite_dimensional_algebras_with_basis.KroneckerQuiverPathAlgebra`(*base_ring*)Bases: `sage.combinat.free_module.CombinatorialFreeModule`

An example of a finite dimensional algebra with basis: the path algebra of the Kronecker quiver.

This class illustrates a minimal implementation of a finite dimensional algebra with basis. See `sage.quivers.algebra.PathAlgebra` for a full-featured implementation of path algebras.**algebra_generators()**

Return algebra generators for this algebra.

See also:`Algebras.ParentMethods.algebra_generators()`.

EXAMPLES:

```
sage: A = FiniteDimensionalAlgebrasWithBasis(QQ).example(); A
An example of a finite dimensional algebra with basis:
the path algebra of the Kronecker quiver
(containing the arrows a:x->y and b:x->y) over Rational Field
sage: A.algebra_generators()
Finite family {'x': x, 'y': y, 'a': a, 'b': b}
```

one()

Return the unit of this algebra.

See also:`AlgebrasWithBasis.ParentMethods.one_basis()`

EXAMPLES:

```
sage: A = FiniteDimensionalAlgebrasWithBasis(QQ).example()
sage: A.one()
x + y
```

product_on_basis(*w1*, *w2*)Return the product of the two basis elements indexed by *w1* and *w2*.

See also:

`AlgebrasWithBasis.ParentMethods.product_on_basis()`.

EXAMPLES:

```
sage: A = FiniteDimensionalAlgebrasWithBasis(QQ).example()
```

Here is the multiplication table for the algebra:

```
sage: matrix([[p*q for q in A.basis()] for p in A.basis()])
[x 0 a b]
[0 y 0 0]
[0 a 0 0]
[0 b 0 0]
```

Here we take some products of linear combinations of basis elements:

```
sage: x, y, a, b = A.basis()
sage: a * (1-b)^2 * x
0
sage: x*a + b*y
a + b
sage: x*x
x
sage: x*y
0
sage: x*a*y
a
```

5.10 Examples of a finite dimensional Lie algebra with basis

```
class sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebra(R,
                                                                                          n=None,
                                                                                          M=None,
                                                                                          am-
                                                                                          bi-
                                                                                          ent=None)
```

Bases: `sage.structure.parent.Parent`, `sage.structure.unique_representation.UniqueRepresentation`

An example of a finite dimensional Lie algebra with basis: the abelian Lie algebra.

Let R be a commutative ring, and M an R -module. The *abelian Lie algebra* on M is the R -Lie algebra obtained by endowing M with the trivial Lie bracket ($[a, b] = 0$ for all $a, b \in M$).

This class illustrates a minimal implementation of a finite dimensional Lie algebra with basis.

INPUT:

- R – base ring
- n – (optional) a nonnegative integer (default: `None`)
- M – an R -module (default: the free R -module of rank n) to serve as the ground space for the Lie algebra

- `ambient` – (optional) a Lie algebra; if this is set, then the resulting Lie algebra is declared a Lie subalgebra of `ambient`

OUTPUT:

The abelian Lie algebra on M .

class `Element`

Bases: `sage.categories.examples.lie_algebras.LieAlgebraFromAssociative.Element`

lift()

Return the lift of `self` to the universal enveloping algebra.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: elt = 2*a + 2*b + 3*c
sage: elt.lift()
2*b0 + 2*b1 + 3*b2
```

monomial_coefficients(*copy=True*)

Return the monomial coefficients of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: elt = 2*a + 2*b + 3*c
sage: elt.monomial_coefficients()
{0: 2, 1: 2, 2: 3}
```

to_vector(*order=None*)

Return `self` as a vector in `self.parent().module()`.

See the docstring of the latter method for the meaning of this.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: elt = 2*a + 2*b + 3*c
sage: elt.to_vector()
(2, 2, 3)
```

ambient()

Return the ambient Lie algebra of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: S = L.subalgebra([2*a+b, b + c])
sage: S.ambient() == L
True
```

basis()

Return the basis of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.basis()
Finite family {0: (1, 0, 0), 1: (0, 1, 0), 2: (0, 0, 1)}
```

basis_matrix()

Return the basis matrix of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.basis_matrix()
[1 0 0]
[0 1 0]
[0 0 1]
```

from_vector(*v*, *order=None*)

Return the element of `self` corresponding to the vector `v` in `self.module()`.

Implement this if you implement `module()`; see the documentation of `sage.categories.lie_algebras.LieAlgebras.module()` for how this is to be done.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: u = L.from_vector(vector(QQ, (1, 0, 0))); u
(1, 0, 0)
sage: parent(u) is L
True
```

gens()

Return the generators of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.gens()
((1, 0, 0), (0, 1, 0), (0, 0, 1))
```

ideal(*gens*)

Return the Lie subalgebra of `self` generated by the elements of the iterable `gens`.

This currently requires the ground ring R to be a field.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: L.subalgebra([2*a+b, b + c])
An example of a finite dimensional Lie algebra with basis:
the 2-dimensional abelian Lie algebra over Rational Field with
basis matrix:
[ 1  0 -1/2]
[ 0  1  1]
```

is_ideal(A)

Return if `self` is an ideal of the ambient space `A`.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: L.is_ideal(L)
True
sage: S1 = L.subalgebra([2*a+b, b + c])
sage: S1.is_ideal(L)
True
sage: S2 = L.subalgebra([2*a+b])
sage: S2.is_ideal(S1)
True
sage: S1.is_ideal(S2)
False

```

lie_algebra_generators()

Return the basis of self.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.basis()
Finite family {0: (1, 0, 0), 1: (0, 1, 0), 2: (0, 0, 1)}

```

module()

Return an R -module which is isomorphic to the underlying R -module of self.

See `sage.categories.lie_algebras.LieAlgebras.module()` for an explanation.

In this particular example, this returns the module M that was used to construct self.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.module()
Vector space of dimension 3 over Rational Field

sage: a, b, c = L.lie_algebra_generators()
sage: S = L.subalgebra([2*a+b, b + c])
sage: S.module()
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1/2]
[ 0  1  1]

```

subalgebra(gens)

Return the Lie subalgebra of self generated by the elements of the iterable gens.

This currently requires the ground ring R to be a field.

EXAMPLES:

```

sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: a, b, c = L.lie_algebra_generators()
sage: L.subalgebra([2*a+b, b + c])
An example of a finite dimensional Lie algebra with basis:
the 2-dimensional abelian Lie algebra over Rational Field with
basis matrix:

```

(continues on next page)

(continued from previous page)

```
[ 1  0 -1/2]
[ 0  1  1]
```

zero()

Return the zero element.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).FiniteDimensional().WithBasis().example()
sage: L.zero()
(0, 0, 0)
```

sage.categories.examples.finite_dimensional_lie_algebras_with_basis.**Example**
 alias of [sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebra](#)

5.11 Examples of finite enumerated sets

class sage.categories.examples.finite_enumerated_sets.**Example**

Bases: [sage.structure.unique_representation.UniqueRepresentation](#), [sage.structure.parent.Parent](#)

An example of a finite enumerated set: {1, 2, 3}

This class provides a minimal implementation of a finite enumerated set.

See [FiniteEnumeratedSet](#) for a full featured implementation.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().example()
sage: C.cardinality()
3
sage: C.list()
[1, 2, 3]
sage: C.an_element()
1
```

This checks that the different methods of the enumerated set C return consistent results:

```
sage: TestSuite(C).run(verbose = True)
running ._test_an_element() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_nonzero_equal() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
```

(continues on next page)

(continued from previous page)

```

pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_enumerated_set_contains() . . . pass
running ._test_enumerated_set_iter_cardinality() . . . pass
running ._test_enumerated_set_iter_list() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass

```

class `sage.categories.examples.finite_enumerated_sets.IsomorphicObjectOfFiniteEnumeratedSet` (*ambient=An example of a finite enumerated set: {1, 2, 3}*)

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

ambient()

Returns the ambient space for `self`, as per `Sets.Subquotients.ParentMethods.ambient()`.

EXAMPLES:

```

sage: C = FiniteEnumeratedSets().IsomorphicObjects().example(); C
The image by some isomorphism of An example of a finite enumerated set: {1,2,3}
sage: C.ambient()
An example of a finite enumerated set: {1,2,3}

```

lift(x)

INPUT:

- `x` – an element of `self`

Lifts `x` to the ambient space for `self`, as per `Sets.Subquotients.ParentMethods.lift()`.

EXAMPLES:

```

sage: C = FiniteEnumeratedSets().IsomorphicObjects().example(); C
The image by some isomorphism of An example of a finite enumerated set: {1,2,3}

```

(continues on next page)

(continued from previous page)

```
sage: C.lift(9)
3
```

retract(x)**INPUT:**

- x – an element of the ambient space for `self`

Retracts x from the ambient space to `self`, as per `Sets.Subquotients.ParentMethods.retract()`.

EXAMPLES:

```
sage: C = FiniteEnumeratedSets().IsomorphicObjects().example(); C
The image by some isomorphism of An example of a finite enumerated set: {1,2,3}
sage: C.retract(3)
9
```

5.12 Examples of finite monoids

`sage.categories.examples.finite_monoids.Example`

alias of `sage.categories.examples.finite_monoids.IntegerModMonoid`

class `sage.categories.examples.finite_monoids.IntegerModMonoid($n=12$)`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a finite monoid: the integers mod n

This class illustrates a minimal implementation of a finite monoid.

EXAMPLES:

```
sage: S = FiniteMonoids().example(); S
An example of a finite multiplicative monoid: the integers modulo 12

sage: S.category()
Category of finitely generated finite enumerated monoids
```

We conclude by running systematic tests on this monoid:

```
sage: TestSuite(S).run(verbose = True)
running ._test_an_element() . . . pass
running ._test_associativity() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass
```

(continues on next page)

(continued from previous page)

```

running ._test_pickling() . . . pass
pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_enumerated_set_contains() . . . pass
running ._test_enumerated_set_iter_cardinality() . . . pass
running ._test_enumerated_set_iter_list() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_one() . . . pass
running ._test_pickling() . . . pass
running ._test_prod() . . . pass
running ._test_some_elements() . . . pass

```

class ElementBases: `sage.structure.element_wrapper.ElementWrapper`**wrapped_class**alias of `sage.rings.integer.Integer`**an_element()**Returns an element of the monoid, as per `Sets.ParentMethods.an_element()`.

EXAMPLES:

```

sage: M = FiniteMonoids().example()
sage: M.an_element()
6

```

one()Return the one of the monoid, as per `Monoids.ParentMethods.one()`.

EXAMPLES:

```

sage: M = FiniteMonoids().example()
sage: M.one()
1

```

product(x, y)Return the product of two elements x and y of the monoid, as per `Semigroups.ParentMethods.product()`.

EXAMPLES:

```

sage: M = FiniteMonoids().example()
sage: M.product(M(3), M(5))
3

```

semigroup_generators()Returns a set of generators for `self`, as per `Semigroups.ParentMethods.semigroup_generators()`. Currently this returns all integers mod n , which is of course far from optimal!

EXAMPLES:

```
sage: M = FiniteMonoids().example()
sage: M.semigroup_generators()
Family (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11)
```

5.13 Examples of finite semigroups

`sage.categories.examples.finite_semigroups.Example`

alias of `sage.categories.examples.finite_semigroups.LeftRegularBand`

class `sage.categories.examples.finite_semigroups.LeftRegularBand`(*alphabet=*('a', 'b', 'c', 'd'))

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a finite semigroup

This class provides a minimal implementation of a finite semigroup.

EXAMPLES:

```
sage: S = FiniteSemigroups().example(); S
An example of a finite semigroup: the left regular band generated by ('a', 'b', 'c',
↪ 'd')
```

This is the semigroup generated by:

```
sage: S.semigroup_generators()
Family ('a', 'b', 'c', 'd')
```

such that $x^2 = x$ and $xyx = xy$ for any x and y in S :

```
sage: S('dab')
'dab'
sage: S('dab') * S('acb')
'dabc'
```

It follows that the elements of S are strings without repetitions over the alphabet a, b, c, d :

```
sage: sorted(S.list())
['a', 'ab', 'abc', 'abcd', 'abd', 'abdc', 'ac', 'acb', 'acbd', 'acd',
'acdb', 'ad', 'adb', 'adbc', 'adc', 'adcb', 'b', 'ba', 'bac',
'bacd', 'bad', 'badc', 'bc', 'bca', 'bcad', 'bcd', 'bcda', 'bd',
'bda', 'bdac', 'bdc', 'bdca', 'c', 'ca', 'cab', 'cabd', 'cad',
'cadb', 'cb', 'cba', 'cbad', 'cbd', 'cbda', 'cd', 'cda', 'cdab',
'cdb', 'cdba', 'd', 'da', 'dab', 'dabc', 'dac', 'dacb', 'db',
'dba', 'dbac', 'dbc', 'dbca', 'dc', 'dca', 'dcab', 'dcb', 'dcba']
```

It also follows that there are finitely many of them:

```
sage: S.cardinality()
64
```

Indeed:

```
sage: 4 * ( 1 + 3 * (1 + 2 * (1 + 1)))
64
```

As expected, all the elements of S are idempotents:

```
sage: all( x.is_idempotent() for x in S )
True
```

Now, let us look at the structure of the semigroup:

```
sage: S = FiniteSemigroups().example(alphabet = ('a','b','c'))
sage: S.cayley_graph(side="left", simple=True).plot()
Graphics object consisting of 60 graphics primitives
sage: S.j_transversal_of_idempotents() # random (arbitrary choice)
['acb', 'ac', 'ab', 'bc', 'a', 'c', 'b']
```

We conclude by running systematic tests on this semigroup:

```
sage: TestSuite(S).run(verbose = True)
running ._test_an_element() . . . pass
running ._test_associativity() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_enumerated_set_contains() . . . pass
running ._test_enumerated_set_iter_cardinality() . . . pass
running ._test_enumerated_set_iter_list() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass
```

class Element

Bases: `sage.structure.element_wrapper.ElementWrapper`

wrapped_class

alias of `builtins.str`

an_element()

Returns an element of the semigroup.

EXAMPLES:

```

sage: S = FiniteSemigroups().example()
sage: S.an_element()
'cdab'

sage: S = FiniteSemigroups().example(("b"))
sage: S.an_element()
'b'

```

product(x, y)

Returns the product of two elements of the semigroup.

EXAMPLES:

```

sage: S = FiniteSemigroups().example()
sage: S('a') * S('b')
'ab'
sage: S('a') * S('b') * S('a')
'ab'
sage: S('a') * S('a')
'a'

```

semigroup_generators()

Returns the generators of the semigroup.

EXAMPLES:

```

sage: S = FiniteSemigroups().example(alphabet=('x', 'y'))
sage: S.semigroup_generators()
Family ('x', 'y')

```

5.14 Examples of finite Weyl groups

`sage.categories.examples.finite_weyl_groups.Example`

alias of `sage.categories.examples.finite_weyl_groups.SymmetricGroup`

class `sage.categories.examples.finite_weyl_groups.SymmetricGroup`($n=4$)

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of finite Weyl group: the symmetric group, with elements in list notation.

The purpose of this class is to provide a minimal template for implementing finite Weyl groups. See `SymmetricGroup` for a full featured and optimized implementation.

EXAMPLES:

```

sage: S = FiniteWeylGroups().example()
sage: S
The symmetric group on {0, ..., 3}
sage: S.category()
Category of finite irreducible weyl groups

```

The elements of this group are permutations of the set $\{0, \dots, 3\}$:

```
sage: S.one()
(0, 1, 2, 3)
sage: S.an_element()
(1, 2, 3, 0)
```

The group itself is generated by the elementary transpositions:

```
sage: S.simple_reflections()
Finite family {0: (1, 0, 2, 3), 1: (0, 2, 1, 3), 2: (0, 1, 3, 2)}
```

Only the following basic operations are implemented:

- `one()`
- `product()`
- `simple_reflection()`
- `cartan_type()`
- `Element.has_right_descent()`.

All the other usual Weyl group operations are inherited from the categories:

```
sage: S.cardinality()
24
sage: S.long_element()
(3, 2, 1, 0)
sage: S.cayley_graph(side = "left").plot()
Graphics object consisting of 120 graphics primitives
```

Alternatively, one could have implemented `sage.categories.coxeter_groups.CoxeterGroups.ElementMethods.apply_simple_reflection()` instead of `simple_reflection()` and `product()`. See `CoxeterGroups().example()`.

class Element

Bases: `sage.structure.element_wrapper.ElementWrapper`

`has_right_descent(i)`

Implements `CoxeterGroups.ElementMethods.has_right_descent()`.

EXAMPLES:

```
sage: S = FiniteWeylGroups().example()
sage: s = S.simple_reflections()
sage: (s[1] * s[2]).has_descent(2)
True
sage: S._test_has_descent()
```

`cartan_type()`

Return the Cartan type of self.

EXAMPLES:

```
sage: FiniteWeylGroups().example().cartan_type()
['A', 3] relabelled by {1: 0, 2: 1, 3: 2}
```

`degrees()`

Return the degrees of self.

EXAMPLES:

```
sage: W = FiniteWeylGroups().example()
sage: W.degrees()
(2, 3, 4)
```

index_set()

Implements *CoxeterGroups.ParentMethods.index_set()*.

EXAMPLES:

```
sage: FiniteWeylGroups().example().index_set()
[0, 1, 2]
```

one()

Implements *Monoids.ParentMethods.one()*.

EXAMPLES:

```
sage: FiniteWeylGroups().example().one()
(0, 1, 2, 3)
```

product(x, y)

Implements *Semigroups.ParentMethods.product()*.

EXAMPLES:

```
sage: s = FiniteWeylGroups().example().simple_reflections()
sage: s[1] * s[2]
(0, 2, 3, 1)
```

simple_reflection(i)

Implement *CoxeterGroups.ParentMethods.simple_reflection()* by returning the transposition $(i, i + 1)$.

EXAMPLES:

```
sage: FiniteWeylGroups().example().simple_reflection(2)
(0, 1, 3, 2)
```

5.15 Examples of graded connected Hopf algebras with basis

`sage.categories.examples.graded_connected_hopf_algebras_with_basis.Example`
 alias of `sage.categories.examples.graded_connected_hopf_algebras_with_basis.GradedConnectedCombinatorialHopfAlgebraWithPrimitiveGenerator`

class `sage.categories.examples.graded_connected_hopf_algebras_with_basis.GradedConnectedCombinatorialHopfAlgebraWithPrimitiveGenerator`
 Bases: `sage.combinat.free_module.CombinatorialFreeModule`

This class illustrates an implementation of a graded Hopf algebra with basis that has one primitive generator of degree 1 and basis elements indexed by non-negative integers.

This Hopf algebra example differs from what topologists refer to as a graded Hopf algebra because the twist operation in the tensor rule satisfies

$$(\mu \otimes \mu) \circ (id \otimes \tau \otimes id) \circ (\Delta \otimes \Delta) = \Delta \circ \mu$$

where $\tau(x \otimes y) = y \otimes x$.

coproduct_on_basis(*i*)

The coproduct of a basis element.

$$\Delta(P_i) = \sum_{j=0}^i P_{i-j} \otimes P_j$$

INPUT:

- *i* – a non-negative integer

OUTPUT:

- an element of the tensor square of `self`

degree_on_basis(*i*)

The degree of a non-negative integer is itself

INPUT:

- *i* – a non-negative integer

OUTPUT:

- a non-negative integer

one_basis()

Returns 0, which index the unit of the Hopf algebra.

OUTPUT:

- the non-negative integer 0

EXAMPLES:

```
sage: H = GradedHopfAlgebrasWithBasis(QQ).Connected().example()
sage: H.one_basis()
0
sage: H.one()
P0
```

product_on_basis(*i*, *j*)

The product of two basis elements.

The product of elements of degree *i* and *j* is an element of degree *i*+*j*.

INPUT:

- *i*, *j* – non-negative integers

OUTPUT:

- a basis element indexed by *i*+*j*

5.16 Examples of graded modules with basis

`sage.categories.examples.graded_modules_with_basis.Example`

alias of `sage.categories.examples.graded_modules_with_basis.GradedPartitionModule`

class `sage.categories.examples.graded_modules_with_basis.GradedPartitionModule`(*base_ring*)

Bases: `sage.combinat.free_module.CombinatorialFreeModule`

This class illustrates an implementation of a graded module with basis: the free module over partitions.

INPUT:

- R – base ring

The implementation involves the following:

- A choice of how to represent elements. In this case, the basis elements are partitions. The algebra is constructed as a `CombinatorialFreeModule` on the set of partitions, so it inherits all of the methods for such objects, and has operations like addition already defined.

```
sage: A = GradedModulesWithBasis(QQ).example()
```

- A basis function - this module is graded by the non-negative integers, so there is a function defined in this module, creatively called `basis()`, which takes an integer d as input and returns a family of partitions representing a basis for the algebra in degree d .

```
sage: A.basis(2)
Lazy family (Term map from Partitions to An example of a graded module with
↳basis: the free module on partitions over Rational Field(i))_{i in Partitions
↳of the integer 2}
sage: A.basis(6)[Partition([3,2,1])]
P[3, 2, 1]
```

- If the algebra is called A , then its basis function is stored as `A.basis`. Thus the function can be used to find a basis for the degree d piece: essentially, just call `A.basis(d)`. More precisely, call x for each x in `A.basis(d)`.

```
sage: [m for m in A.basis(4)]
[P[4], P[3, 1], P[2, 2], P[2, 1, 1], P[1, 1, 1, 1]]
```

- For dealing with basis elements: `degree_on_basis()`, and `_repr_term()`. The first of these defines the degree of any monomial, and then the `degree` method for elements – see the next item – uses it to compute the degree for a linear combination of monomials. The last of these determines the print representation for monomials, which automatically produces the print representation for general elements.

```
sage: A.degree_on_basis(Partition([4,3]))
7
sage: A._repr_term(Partition([4,3]))
'P[4, 3]'
```

- There is a class for elements, which inherits from `IndexedFreeModuleElement`. An element is determined by a dictionary whose keys are partitions and whose corresponding values are the coefficients. The class implements two things: an `is_homogeneous` method and a `degree` method.

```
sage: p = A.monomial(Partition([3,2,1])); p
P[3, 2, 1]
```

(continues on next page)

(continued from previous page)

```

sage: p.is_homogeneous()
True
sage: p.degree()
6

```

basis(*d=None*)

Return the basis for (the *d*-th homogeneous component of) *self*.

INPUT:

- *d* – (optional, default *None*) nonnegative integer or *None*

OUTPUT:

If *d* is *None*, returns the basis of the module. Otherwise, returns the basis of the homogeneous component of degree *d* (i.e., the subfamily of the basis of the whole module which consists only of the basis vectors lying in $F_d \setminus \bigcup_{i < d} F_i$).

The basis is always returned as a family.

EXAMPLES:

```

sage: A = ModulesWithBasis(ZZ).Filtered().example()
sage: A.basis(4)
Lazy family (Term map from Partitions to An example of a
  filtered module with basis: the free module on partitions
  over Integer Ring(i))_{i in Partitions of the integer 4}

```

Without arguments, the full basis is returned:

```

sage: A.basis()
Lazy family (Term map from Partitions to An example of a
  filtered module with basis: the free module on partitions
  over Integer Ring(i))_{i in Partitions}
sage: A.basis()
Lazy family (Term map from Partitions to An example of a
  filtered module with basis: the free module on partitions
  over Integer Ring(i))_{i in Partitions}

```

Checking this method on a filtered algebra. Note that this will typically raise a `NotImplementedError` when this feature is not implemented.

```

sage: A = AlgebrasWithBasis(ZZ).Filtered().example()
sage: A.basis(4)
Traceback (most recent call last):
...
NotImplementedError: infinite set

```

Without arguments, the full basis is returned:

```

sage: A.basis()
Lazy family (Term map from Free abelian monoid indexed by
  {'x', 'y', 'z'} to An example of a filtered algebra with
  basis: the universal enveloping algebra of Lie algebra
  of RR^3 with cross product over Integer Ring(i))_{i in
  Free abelian monoid indexed by {'x', 'y', 'z'}}

```

An example with a graded algebra:

```
sage: E.<x,y> = ExteriorAlgebra(QQ)
sage: E.basis()
Lazy family (Term map from Subsets of {0, 1} to
The exterior algebra of rank 2 over Rational Field(i))_{i in
Subsets of {0, 1}}
```

degree_on_basis(*t*)

The degree of the element determined by the partition *t* in this graded module.

INPUT:

- *t* – the index of an element of the basis of this module, i.e. a partition

OUTPUT: an integer, the degree of the corresponding basis element

EXAMPLES:

```
sage: A = GradedModulesWithBasis(QQ).example()
sage: A.degree_on_basis(Partition((2,1)))
3
sage: A.degree_on_basis(Partition((4,2,1,1,1)))
10
sage: type(A.degree_on_basis(Partition((1,1))))
<type 'sage.rings.integer.Integer'>
```

5.17 Examples of graphs

class `sage.categories.examples.graphs.Cycle`(*n=5*)

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a graph: the cycle of length *n*.

This class illustrates a minimal implementation of a graph.

EXAMPLES:

```
sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example(); C
An example of a graph: the 5-cycle

sage: C.category()
Category of graphs
```

We conclude by running systematic tests on this graph:

```
sage: TestSuite(C).run()
```

class `Element`

Bases: `sage.structure.element_wrapper.ElementWrapper`

dimension()

Return the dimension of `self`.

EXAMPLES:

```

sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: e = C.edges()[0]
sage: e.dimension()
2
sage: v = C.vertices()[0]
sage: v.dimension()
1

```

an_element()

Return an element of the graph, as per *Sets.ParentMethods.an_element()*.

EXAMPLES:

```

sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: C.an_element()
0

```

edges()

Return the edges of self.

EXAMPLES:

```

sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: C.edges()
[(0, 1), (1, 2), (2, 3), (3, 4), (4, 0)]

```

vertices()

Return the vertices of self.

EXAMPLES:

```

sage: from sage.categories.graphs import Graphs
sage: C = Graphs().example()
sage: C.vertices()
[0, 1, 2, 3, 4]

```

`sage.categories.examples.graphs.Example`

alias of `sage.categories.examples.graphs.Cycle`

5.18 Examples of Hopf algebras with basis

class `sage.categories.examples.hopf_algebras_with_basis.MyGroupAlgebra(R, G)`

Bases: `sage.combinat.free_module.CombinatorialFreeModule`

An example of a Hopf algebra with basis: the group algebra of a group

This class illustrates a minimal implementation of a Hopf algebra with basis.

algebra_generators()

Return the generators of this algebra, as per `algebra_generators()`.

They correspond to the generators of the group.

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example(); A
An example of Hopf algebra with basis: the group algebra of the Dihedral group
↳ of order 6 as a permutation group over Rational Field
sage: A.algebra_generators()
Finite family {(1,2,3): B[(1,2,3)], (1,3): B[(1,3)]}
```

antipode_on_basis(g)

Antipode, on basis elements, as per *HopfAlgebrasWithBasis.ParentMethods.antipode_on_basis()*.

It is given, on basis elements, by $\nu(g) = g^{-1}$

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example()
sage: (a, b) = A._group.gens()
sage: A.antipode_on_basis(a)
B[(1,3,2)]
```

coproduct_on_basis(g)

Coproduct, on basis elements, as per *HopfAlgebrasWithBasis.ParentMethods.coproduct_on_basis()*.

The basis elements are group like: $\Delta(g) = g \otimes g$.

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example()
sage: (a, b) = A._group.gens()
sage: A.coproduct_on_basis(a)
B[(1,2,3)] # B[(1,2,3)]
```

counit_on_basis(g)

Counit, on basis elements, as per *HopfAlgebrasWithBasis.ParentMethods.counit_on_basis()*.

The counit on the basis elements is 1.

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example()
sage: (a, b) = A._group.gens()
sage: A.counit_on_basis(a)
1
```

one_basis()

Returns the one of the group, which index the one of this algebra, as per *AlgebrasWithBasis.ParentMethods.one_basis()*.

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example()
sage: A.one_basis()
()
sage: A.one()
B[()]
```

product_on_basis($g1, g2$)

Product, on basis elements, as per `AlgebrasWithBasis.ParentMethods.product_on_basis()`.

The product of two basis elements is induced by the product of the corresponding elements of the group.

EXAMPLES:

```
sage: A = HopfAlgebrasWithBasis(QQ).example()
sage: (a, b) = A._group.gens()
sage: a*b
(1,2)
sage: A.product_on_basis(a, b)
B[(1,2)]
```

5.19 Examples of infinite enumerated sets

`sage.categories.examples.infinite_enumerated_sets.Example`

alias of `sage.categories.examples.infinite_enumerated_sets.NonNegativeIntegers`

class `sage.categories.examples.infinite_enumerated_sets.NonNegativeIntegers`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of infinite enumerated set: the non negative integers

This class provides a minimal implementation of an infinite enumerated set.

EXAMPLES:

```
sage: NN = InfiniteEnumeratedSets().example()
sage: NN
An example of an infinite enumerated set: the non negative integers
sage: NN.cardinality()
+Infinity
sage: NN.list()
Traceback (most recent call last):
...
NotImplementedError: cannot list an infinite set
sage: NN.element_class
<type 'sage.rings.integer.Integer'>
sage: it = iter(NN)
sage: [next(it), next(it), next(it), next(it), next(it)]
[0, 1, 2, 3, 4]
sage: x = next(it); type(x)
<type 'sage.rings.integer.Integer'>
sage: x.parent()
Integer Ring
sage: x+3
8
sage: NN(15)
15
sage: NN.first()
0
```

This checks that the different methods of `NN` return consistent results:

```

sage: TestSuite(NN).run(verbose = True)
running ._test_an_element() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_nonzero_equal() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_enumerated_set_contains() . . . pass
running ._test_enumerated_set_iter_cardinality() . . . pass
running ._test_enumerated_set_iter_list() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass

```

Element

alias of `sage.rings.integer.Integer`

an_element()

EXAMPLES:

```

sage: InfiniteEnumeratedSets().example().an_element()
42

```

next(*o*)

EXAMPLES:

```

sage: NN = InfiniteEnumeratedSets().example()
sage: NN.next(3)
4

```

5.20 Examples of a Lie algebra

`sage.categories.examples.lie_algebras.Example`

alias of `sage.categories.examples.lie_algebras.LieAlgebraFromAssociative`

class `sage.categories.examples.lie_algebras.LieAlgebraFromAssociative(gens)`

Bases: `sage.structure.parent.Parent`, `sage.structure.unique_representation.UniqueRepresentation`

An example of a Lie algebra: a Lie algebra generated by a set of elements of an associative algebra.

This class illustrates a minimal implementation of a Lie algebra.

Let R be a commutative ring, and A an associative R -algebra. The Lie algebra A (sometimes denoted A^-) is defined to be the R -module A with Lie bracket given by the commutator in A : that is, $[a, b] := ab - ba$ for all $a, b \in A$.

What this class implements is not precisely A^- , however; it is the Lie subalgebra of A^- generated by the elements of the iterable `gens`. This specific implementation does not provide a reasonable containment test (i.e., it does not allow you to check if a given element a of A^- belongs to this Lie subalgebra); it, however, allows computing inside it.

INPUT:

- `gens` – a nonempty iterable consisting of elements of an associative algebra A

OUTPUT:

The Lie subalgebra of A^- generated by the elements of `gens`

EXAMPLES:

We create a model of \mathfrak{sl}_2 using matrices:

```
sage: gens = [matrix([[0,1],[0,0]]), matrix([[0,0],[1,0]]), matrix([[1,0],[0,-1]])]
sage: for g in gens:
....:     g.set_immutable()
sage: L = LieAlgebras(QQ).example(gens)
sage: e,f,h = L.lie_algebra_generators()
sage: e.bracket(f) == h
True
sage: h.bracket(e) == 2*e
True
sage: h.bracket(f) == -2*f
True
```

class Element

Bases: `sage.structure.element_wrapper.ElementWrapper`

Wrap an element as a Lie algebra element.

lie_algebra_generators()

Return the generators of `self` as a Lie algebra.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).example()
sage: L.lie_algebra_generators()
Family ([2, 1, 3], [2, 3, 1])
```

zero()

Return the element 0.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).example()
sage: L.zero()
0
```

5.21 Examples of a Lie algebra with basis

class `sage.categories.examples.lie_algebras_with_basis.AbelianLieAlgebra(R, gens)`
 Bases: `sage.combinat.free_module.CombinatorialFreeModule`

An example of a Lie algebra: the abelian Lie algebra.

This class illustrates a minimal implementation of a Lie algebra with a distinguished basis.

class `Element`

Bases: `sage.modules.with_basis.indexed_element.IndexedFreeModuleElement`

lift()

Return the lift of `self` to the universal enveloping algebra.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).WithBasis().example()
sage: elt = L.an_element()
sage: elt.lift()
3*P[F[2]] + 2*P[F[1]] + 2*P[F[]]
```

bracket_on_basis(*x, y*)

Return the Lie bracket on basis elements indexed by `x` and `y`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).WithBasis().example()
sage: L.bracket_on_basis(Partition([4,1]), Partition([2,2,1]))
0
```

lie_algebra_generators()

Return the generators of `self` as a Lie algebra.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).WithBasis().example()
sage: L.lie_algebra_generators()
Lazy family (Term map from Partitions to
An example of a Lie algebra: the abelian Lie algebra on the
generators indexed by Partitions over Rational
Field(i))_{i in Partitions}
```

`sage.categories.examples.lie_algebras_with_basis.Example`
 alias of `sage.categories.examples.lie_algebras_with_basis.AbelianLieAlgebra`

class `sage.categories.examples.lie_algebras_with_basis.IndexedPolynomialRing(R, indices, **kwds)`

Bases: `sage.combinat.free_module.CombinatorialFreeModule`

Polynomial ring whose generators are indexed by an arbitrary set.

Todo: Currently this is just used as the universal enveloping algebra for the example of the abelian Lie algebra. This should be factored out into a more complete class.

algebra_generators()

Return the algebra generators of `self`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).WithBasis().example()
sage: UEA = L.universal_enveloping_algebra()
sage: UEA.algebra_generators()
Lazy family (algebra generator map(i))_{i in Partitions}
```

one_basis()

Return the index of element `l`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).WithBasis().example()
sage: UEA = L.universal_enveloping_algebra()
sage: UEA.one_basis()
1
sage: UEA.one_basis().parent()
Free abelian monoid indexed by Partitions
```

product_on_basis(x, y)

Return the product of the monomials indexed by `x` and `y`.

EXAMPLES:

```
sage: L = LieAlgebras(QQ).WithBasis().example()
sage: UEA = L.universal_enveloping_algebra()
sage: I = UEA._indices
sage: UEA.product_on_basis(I.an_element(), I.an_element())
P[F[]^4*F[1]^4*F[2]^6]
```

5.22 Examples of magmas

`sage.categories.examples.magmas.Example`

alias of `sage.categories.examples.magmas.FreeMagma`

class `sage.categories.examples.magmas.FreeMagma`(*alphabet=('a', 'b', 'c', 'd')*)

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of magma.

The purpose of this class is to provide a minimal template for implementing a magma.

EXAMPLES:

```
sage: M = Magmas().example(); M
An example of a magma: the free magma generated by ('a', 'b', 'c', 'd')
```

This is the free magma generated by:

```
sage: M.magma_generators()
Family ('a', 'b', 'c', 'd')
sage: a, b, c, d = M.magma_generators()
```

and with a non-associative product given by:

```
sage: a * (b * c) * (d * a * b)
'((a*(b*c))*((d*a)*b))'
sage: a * (b * c) == (a * b) * c
False
```

class Element

Bases: `sage.structure.element_wrapper.ElementWrapper`

The class for elements of the free magma.

wrapped_class

alias of `builtins.str`

an_element()

Return an element of the magma.

EXAMPLES:

```
sage: F = Magmas().example()
sage: F.an_element()
'(((a*b)*c)*d)'
```

magma_generators()

Return the generators of the magma.

EXAMPLES:

```
sage: F = Magmas().example()
sage: F.magma_generators()
Family ('a', 'b', 'c', 'd')
```

product(x, y)

Return the product of `x` and `y` in the magma, as per `Magmas.ParentMethods.product()`.

EXAMPLES:

```
sage: F = Magmas().example()
sage: F('a') * F.an_element()
'(a*(((a*b)*c)*d))'
```

5.23 Examples of manifolds

`sage.categories.examples.manifolds.Example`

alias of `sage.categories.examples.manifolds.Plane`

class `sage.categories.examples.manifolds.Plane`(*n=3, base_ring=None*)

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a manifold: the n -dimensional plane.

This class illustrates a minimal implementation of a manifold.

EXAMPLES:

```

sage: from sage.categories.manifolds import Manifolds
sage: M = Manifolds(QQ).example(); M
An example of a Rational Field manifold: the 3-dimensional plane

sage: M.category()
Category of manifolds over Rational Field

```

We conclude by running systematic tests on this manifold:

```

sage: TestSuite(M).run()

```

Element

alias of `sage.structure.element_wrapper.ElementWrapper`

an_element()

Return an element of the manifold, as per *Sets.ParentMethods.an_element()*.

EXAMPLES:

```

sage: from sage.categories.manifolds import Manifolds
sage: M = Manifolds(QQ).example()
sage: M.an_element()
(0, 0, 0)

```

dimension()

Return the dimension of self.

EXAMPLES:

```

sage: from sage.categories.manifolds import Manifolds
sage: M = Manifolds(QQ).example()
sage: M.dimension()
3

```

5.24 Examples of monoids

`sage.categories.examples.monoids.Example`

alias of `sage.categories.examples.monoids.FreeMonoid`

class `sage.categories.examples.monoids.FreeMonoid`(*alphabet*=('a', 'b', 'c', 'd'))

Bases: `sage.categories.examples.semigroups.FreeSemigroup`

An example of a monoid: the free monoid

This class illustrates a minimal implementation of a monoid. For a full featured implementation of free monoids, see `FreeMonoid()`.

EXAMPLES:

```

sage: S = Monoids().example(); S
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')

sage: S.category()
Category of monoids

```

This is the free semigroup generated by:

```
sage: S.semigroup_generators()
Family ('a', 'b', 'c', 'd')
```

with product rule given by concatenation of words:

```
sage: S('dab') * S('acb')
'dabacb'
```

and unit given by the empty word:

```
sage: S.one()
''
```

We conclude by running systematic tests on this monoid:

```
sage: TestSuite(S).run(verbose = True)
running ._test_an_element() . . . pass
running ._test_associativity() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_one() . . . pass
running ._test_pickling() . . . pass
running ._test_prod() . . . pass
running ._test_some_elements() . . . pass
```

class Element

Bases: `sage.structure.element_wrapper.ElementWrapper`

wrapped_class

alias of `builtins.str`

monoid_generators()

Return the generators of this monoid.

EXAMPLES:

```
sage: M = Monoids().example(); M
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
```

(continues on next page)

(continued from previous page)

```

sage: M.monoid_generators()
Finite family {'a': 'a', 'b': 'b', 'c': 'c', 'd': 'd'}
sage: a,b,c,d = M.monoid_generators()
sage: a*d*c*b
'adcb'

```

one()

Returns the one of the monoid, as per `Monoids.ParentMethods.one()`.

EXAMPLES:

```

sage: M = Monoids().example(); M
An example of a monoid: the free monoid generated by ('a', 'b', 'c', 'd')
sage: M.one()
''

```

5.25 Examples of posets

`class sage.categories.examples.posets.FiniteSetsOrderedByInclusion`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a poset: finite sets ordered by inclusion

This class provides a minimal implementation of a poset

EXAMPLES:

```

sage: P = Posets().example(); P
An example of a poset: sets ordered by inclusion

```

We conclude by running systematic tests on this poset:

```

sage: TestSuite(P).run(verbose = True)
running ._test_an_element() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass

```

(continues on next page)

(continued from previous page)

```

running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass

```

class ElementBases: `sage.structure.element_wrapper.ElementWrapper`**wrapped_class**alias of `sage.sets.set.Set_object_enumerated`**an_element()**

Returns an element of this poset

EXAMPLES:

```

sage: B = Posets().example()
sage: B.an_element()
{1, 4, 6}

```

le(x, y)Returns whether x is a subset of y

EXAMPLES:

```

sage: P = Posets().example()
sage: P.le( P(Set([1,3])), P(Set([1,2,3])) )
True
sage: P.le( P(Set([1,3])), P(Set([1,3])) )
True
sage: P.le( P(Set([1,2])), P(Set([1,3])) )
False

```

class sage.categories.examples.posets.PositiveIntegersOrderedByDivisibilityFacadeBases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a facade poset: the positive integers ordered by divisibility

This class provides a minimal implementation of a facade poset

EXAMPLES:

```

sage: P = Posets().example("facade"); P
An example of a facade poset: the positive integers ordered by divisibility

sage: P(5)
5
sage: P(0)
Traceback (most recent call last):
...
ValueError: Can't coerce `0` in any parent `An example of a facade poset: the
↳ positive integers ordered by divisibility` is a facade for

sage: 3 in P
True

```

(continues on next page)

(continued from previous page)

```
sage: 0 in P
False
```

class `element_class(X)`

Bases: `sage.sets.set.Set_object_enumerated`, `sage.categories.finite_sets.FiniteSets`.
`parent_class`

A finite enumerated set.

le(x, y)

Returns whether x is divisible by y

EXAMPLES:

```
sage: P = Posets().example("facade")
sage: P.le(3, 6)
True
sage: P.le(3, 3)
True
sage: P.le(3, 7)
False
```

5.26 Examples of semigroups

class `sage.categories.examples.semigroups.FreeSemigroup(alphabet=('a', 'b', 'c', 'd'))`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of semigroup.

The purpose of this class is to provide a minimal template for implementing of a semigroup.

EXAMPLES:

```
sage: S = Semigroups().example("free"); S
An example of a semigroup: the free semigroup generated by ('a', 'b', 'c', 'd')
```

This is the free semigroup generated by:

```
sage: S.semigroup_generators()
Family ('a', 'b', 'c', 'd')
```

and with product given by concatenation:

```
sage: S('dab') * S('acb')
'dabacb'
```

class `Element`

Bases: `sage.structure.element_wrapper.ElementWrapper`

The class for elements of the free semigroup.

wrapped_class

alias of `builtins.str`

an_element()

Returns an element of the semigroup.

EXAMPLES:

```
sage: F = Semigroups().example('free')
sage: F.an_element()
'abcd'
```

product(x, y)

Returns the product of x and y in the semigroup, as per `Semigroups.ParentMethods.product()`.

EXAMPLES:

```
sage: F = Semigroups().example('free')
sage: F.an_element() * F('a')^5
'abcdaaaa'
```

semigroup_generators()

Returns the generators of the semigroup.

EXAMPLES:

```
sage: F = Semigroups().example('free')
sage: F.semigroup_generators()
Family ('a', 'b', 'c', 'd')
```

class `sage.categories.examples.semigroups.IncompleteSubquotientSemigroup`(*category=None*)

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An incompletely implemented subquotient semigroup, for testing purposes

EXAMPLES:

```
sage: S = sage.categories.examples.semigroups.IncompleteSubquotientSemigroup()
sage: S
A subquotient of An example of a semigroup: the left zero semigroup
```

class `Element`

Bases: `sage.structure.element_wrapper.ElementWrapper`

ambient()

Returns the ambient semigroup.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: S.ambient()
An example of a semigroup: the left zero semigroup
```

class `sage.categories.examples.semigroups.LeftZeroSemigroup`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of a semigroup.

This class illustrates a minimal implementation of a semigroup.

EXAMPLES:

```
sage: S = Semigroups().example(); S
An example of a semigroup: the left zero semigroup
```

This is the semigroup that contains all sorts of objects:

```
sage: S.some_elements()
[3, 42, 'a', 3.4, 'raton laveur']
```

with product rule given by $a \times b = a$ for all a, b :

```
sage: S('hello') * S('world')
'hello'
sage: S(3)*S(1)*S(2)
3
sage: S(3)^12312321312321
3
```

class Element

Bases: `sage.structure.element_wrapper.ElementWrapper`

is_idempotent()

Trivial implementation of `Semigroups.Element.is_idempotent` since all elements of this semigroup are idempotent!

EXAMPLES:

```
sage: S = Semigroups().example()
sage: S.an_element().is_idempotent()
True
sage: S(17).is_idempotent()
True
```

an_element()

Returns an element of the semigroup.

EXAMPLES:

```
sage: Semigroups().example().an_element()
42
```

product(x, y)

Returns the product of x and y in the semigroup, as per `Semigroups.ParentMethods.product()`.

EXAMPLES:

```
sage: S = Semigroups().example()
sage: S('hello') * S('world')
'hello'
sage: S(3)*S(1)*S(2)
3
```

some_elements()

Returns a list of some elements of the semigroup.

EXAMPLES:

```
sage: Semigroups().example().some_elements()
[3, 42, 'a', 3.4, 'raton laveur']
```

class sage.categories.examples.semigroups.**QuotientOfLeftZeroSemigroup**(category=None)
 Bases: sage.structure.unique_representation.UniqueRepresentation, sage.structure.parent.Parent

Example of a quotient semigroup

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example(); S
An example of a (sub)quotient semigroup: a quotient of the left zero semigroup
```

This is the quotient of:

```
sage: S.ambient()
An example of a semigroup: the left zero semigroup
```

obtained by setting $x = 42$ for any $x \geq 42$:

```
sage: S(100)
42
sage: S(100) == S(42)
True
```

The product is inherited from the ambient semigroup:

```
sage: S(1)*S(2) == S(1)
True
```

class Element

Bases: sage.structure.element_wrapper.ElementWrapper

ambient()

Returns the ambient semigroup.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: S.ambient()
An example of a semigroup: the left zero semigroup
```

an_element()

Returns an element of the semigroup.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: S.an_element()
42
```

lift(x)

Lift the element x into the ambient semigroup.

INPUT:

- x – an element of self.

OUTPUT:

- an element of `self.ambient()`.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: x = S.an_element(); x
42
sage: S.lift(x)
42
sage: S.lift(x) in S.ambient()
True
sage: y = S.ambient()(100); y
100
sage: S.lift(S(y))
42
```

retract(*x*)

Returns the retract *x* onto an element of this semigroup.

INPUT:

- *x* – an element of the ambient semigroup (`self.ambient()`).

OUTPUT:

- an element of `self`.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: L = S.ambient()
sage: S.retract(L(17))
17
sage: S.retract(L(42))
42
sage: S.retract(L(171))
42
```

some_elements()

Returns a list of some elements of the semigroup.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: S.some_elements()
[1, 2, 3, 8, 42, 42]
```

the_answer()

Returns the Answer to Life, the Universe, and Everything as an element of this semigroup.

EXAMPLES:

```
sage: S = Semigroups().Subquotients().example()
sage: S.the_answer()
42
```

5.27 Examples of semigroups in cython

```
class sage.categories.examples.semigroups_cython.IdempotentSemigroups(s=None)
    Bases: sage.categories.category.Category
```

```
class ElementMethods
```

```
    Bases: object
```

```
    is_idempotent()
```

```
        EXAMPLES:
```

```
sage: from sage.categories.examples.semigroups_cython import L
      ↪ LeftZeroSemigroup
sage: S = LeftZeroSemigroup()
sage: S(2).is_idempotent()
True
```

```
super_categories()
```

```
    EXAMPLES:
```

```
sage: from sage.categories.examples.semigroups_cython import I
      ↪ IdempotentSemigroups
sage: IdempotentSemigroups().super_categories()
[Category of semigroups]
```

```
class sage.categories.examples.semigroups_cython.LeftZeroSemigroup
```

```
    Bases: sage.categories.examples.semigroups.LeftZeroSemigroup
```

An example of semigroup

This class illustrates a minimal implementation of a semi-group where the element class is an extension type, and still gets code from the category. The category itself must be a Python class though.

This is purely a proof of concept. The code obviously needs refactorisation!

Comments:

- one cannot play ugly class surgery tricks (as with `_mul_parent`). available operations should really be declared to the coercion model!

EXAMPLES:

```
sage: from sage.categories.examples.semigroups_cython import LeftZeroSemigroup
sage: S = LeftZeroSemigroup(); S
An example of a semigroup: the left zero semigroup
```

This is the semigroup which contains all sort of objects:

```
sage: S.some_elements()
[3, 42, 'a', 3.4, 'raton laveur']
```

with product rule is given by $a \times b = a$ for all a, b .

```
sage: S('hello') * S('world')
'hello'

sage: S(3)*S(1)*S(2)
```

(continues on next page)

(continued from previous page)

```

3
sage: S(3)^12312321312321
3
sage: TestSuite(S).run(verbose = True)
running ._test_an_element() . . . pass
running ._test_associativity() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass
  running ._test_pickling() . . . pass
  pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass

```

That's really the only method which is obtained from the category ...

```

sage: S(42).is_idempotent
<bound method IdempotentSemigroups.element_class.is_idempotent of 42>
sage: S(42).is_idempotent()
True

sage: S(42)._pow_int
<bound method IdempotentSemigroups.element_class._pow_int of 42>
sage: S(42)^10
42

sage: S(42).is_idempotent
<bound method IdempotentSemigroups.element_class.is_idempotent of 42>
sage: S(42).is_idempotent()
True

```

Element

alias of *LeftZeroSemigroupElement*

class sage.categories.examples.semigroups_cython.LeftZeroSemigroupElement

Bases: `sage.structure.element.Element`

EXAMPLES:

```
sage: from sage.categories.examples.semigroups_cython import LeftZeroSemigroup
sage: S = LeftZeroSemigroup()
sage: x = S(3)
sage: TestSuite(x).run()
```

5.28 Examples of sets

class sage.categories.examples.sets_cat.PrimeNumbers

Bases: sage.structure.unique_representation.UniqueRepresentation, sage.structure.parent.Parent

An example of parent in the category of sets: the set of prime numbers.

The elements are represented as plain integers in \mathbf{Z} (facade implementation).

This is a minimal implementations. For more advanced examples of implementations, see also:

```
sage: P = Sets().example("facade")
sage: P = Sets().example("inherits")
sage: P = Sets().example("wrapper")
```

EXAMPLES:

```
sage: P = Sets().example()
sage: P(12)
Traceback (most recent call last):
...
AssertionError: 12 is not a prime number
sage: a = P.an_element()
sage: a.parent()
Integer Ring
sage: x = P(13); x
13
sage: type(x)
<type 'sage.rings.integer.Integer'>
sage: x.parent()
Integer Ring
sage: 13 in P
True
sage: 12 in P
False
sage: y = x+1; y
14
sage: type(y)
<type 'sage.rings.integer.Integer'>

sage: TestSuite(P).run(verbose=True)
running ._test_an_element() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
```

(continues on next page)

(continued from previous page)

```

Running the test suite of self.an_element()
running ._test_category() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_nonzero_equal() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass

```

an_element()

Implements *Sets.ParentMethods.an_element()*.

element_class

alias of `sage.rings.integer.Integer`

class `sage.categories.examples.sets_cat.PrimeNumbers_Abstract`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

This class shows how to write a parent while keeping the choice of the datastructure for the children open. Different class with fixed datastructure will then be constructed by inheriting from *PrimeNumbers_Abstract*.

This is used by:

```

sage: P = Sets().example("facade") sage: P = Sets().example("inherits") sage: P =
Sets().example("wrapper")

```

class `Element`

Bases: `sage.structure.element.Element`

is_prime()

Return whether `self` is a prime number.

EXAMPLES:

```

sage: P = Sets().example("inherits")
sage: x = P.an_element()
sage: P.an_element().is_prime()
True

```

next()

Return the next prime number.

EXAMPLES:

```

sage: P = Sets().example("inherits")
sage: p = P.an_element(); p
47

```

(continues on next page)

(continued from previous page)

```
sage: p.next()
53
```

Note: This method is not meant to implement the protocol iterator, and thus not subject to Python 2 vs Python 3 incompatibilities.

an_element()

Implements *Sets.ParentMethods.an_element()*.

next(*i*)

Return the next prime number.

EXAMPLES:

```
sage: P = Sets().example("inherits")
sage: x = P.next(P.an_element()); x
53
sage: x.parent()
Set of prime numbers
```

some_elements()

Return some prime numbers.

EXAMPLES:

```
sage: P = Sets().example("inherits")
sage: P.some_elements()
[47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97]
```

class sage.categories.examples.sets_cat.**PrimeNumbers_Facade**

Bases: *sage.categories.examples.sets_cat.PrimeNumbers_Abstract*

An example of parent in the category of sets: the set of prime numbers.

In this alternative implementation, the elements are represented as plain integers in \mathbf{Z} (facade implementation).

EXAMPLES:

```
sage: P = Sets().example("facade")
sage: P(12)
Traceback (most recent call last):
...
ValueError: 12 is not a prime number
sage: a = P.an_element()
sage: a.parent()
Integer Ring
sage: x = P(13); x
13
sage: type(x)
<type 'sage.rings.integer.Integer'>
sage: x.parent()
Integer Ring
sage: 13 in P
True
```

(continues on next page)

(continued from previous page)

```

sage: 12 in P
False
sage: y = x+1; y
14
sage: type(y)
<type 'sage.rings.integer.Integer'>

sage: z = P.next(x); z
17
sage: type(z)
<type 'sage.rings.integer.Integer'>
sage: z.parent()
Integer Ring

```

The disadvantage of this implementation is that the elements do not know that they are prime, so that prime testing is slow:

```

sage: pf = Sets().example("facade").an_element()
sage: timeit("pf.is_prime()") # random
625 loops, best of 3: 4.1 us per loop

```

compared to the other implementations where prime testing is only done if needed during the construction of the element, and later on the elements “know” that they are prime:

```

sage: pw = Sets().example("wrapper").an_element()
sage: timeit("pw.is_prime()") # random
625 loops, best of 3: 859 ns per loop

sage: pi = Sets().example("inherits").an_element()
sage: timeit("pw.is_prime()") # random
625 loops, best of 3: 854 ns per loop

```

Note also that the next method for the elements does not exist:

```

sage: pf.next()
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'next'

```

unlike in the other implementations:

```

sage: pw.next()
53
sage: pi.next()
53

```

element_class

alias of `sage.rings.integer.Integer`

class `sage.categories.examples.sets_cat.PrimeNumbers_Inherits`

Bases: `sage.categories.examples.sets_cat.PrimeNumbers_Abstract`

An example of parent in the category of sets: the set of prime numbers. In this implementation, the element are stored as object of a new class which inherits from the class `Integer` (technically `IntegerWrapper`).

EXAMPLES:

```

sage: P = Sets().example("inherits")
sage: P
Set of prime numbers
sage: P(12)
Traceback (most recent call last):
...
ValueError: 12 is not a prime number
sage: a = P.an_element()
sage: a.parent()
Set of prime numbers
sage: x = P(13); x
13
sage: x.is_prime()
True
sage: type(x)
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Inherits_with_category.
->element_class'>
sage: x.parent()
Set of prime numbers
sage: P(13) in P
True
sage: y = x+1; y
14
sage: type(y)
<type 'sage.rings.integer.Integer'>
sage: y.parent()
Integer Ring
sage: type(P(13)+P(17))
<type 'sage.rings.integer.Integer'>
sage: type(P(2)+P(3))
<type 'sage.rings.integer.Integer'>

sage: z = P.next(x); z
17
sage: type(z)
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Inherits_with_category.
->element_class'>
sage: z.parent()
Set of prime numbers

sage: TestSuite(P).run(verbose=True)
running ._test_an_element() . . . pass
running ._test_cardinality() . . . pass
running ._test_category() . . . pass
running ._test_construction() . . . pass
running ._test_elements() . . .
  Running the test suite of self.an_element()
  running ._test_category() . . . pass
  running ._test_eq() . . . pass
  running ._test_new() . . . pass
  running ._test_not_implemented_methods() . . . pass

```

(continues on next page)

(continued from previous page)

```

running ._test_pickling() . . . pass
pass
running ._test_elements_eq_reflexive() . . . pass
running ._test_elements_eq_symmetric() . . . pass
running ._test_elements_eq_transitive() . . . pass
running ._test_elements_neq() . . . pass
running ._test_eq() . . . pass
running ._test_new() . . . pass
running ._test_not_implemented_methods() . . . pass
running ._test_pickling() . . . pass
running ._test_some_elements() . . . pass

```

See also:

```

sage: P = Sets().example("facade")
sage: P = Sets().example("inherits")
sage: P = Sets().example("wrapper")

```

class `Element`(*parent, p*)

Bases: `sage.rings.integer.IntegerWrapper`, `sage.categories.examples.sets_cat.PrimeNumbers_Abstract.Element`

class `sage.categories.examples.sets_cat.PrimeNumbers_Wrapper`

Bases: `sage.categories.examples.sets_cat.PrimeNumbers_Abstract`

An example of parent in the category of sets: the set of prime numbers.

In this second alternative implementation, the prime integer are stored as a attribute of a sage object by inheriting from `ElementWrapper`. In this case we need to ensure conversion and coercion from this parent and its element to `ZZ` and `Integer`.

EXAMPLES:

```

sage: P = Sets().example("wrapper")
sage: P(12)
Traceback (most recent call last):
...
ValueError: 12 is not a prime number
sage: a = P.an_element()
sage: a.parent()
Set of prime numbers (wrapper implementation)
sage: x = P(13); x
13
sage: type(x)
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Wrapper_with_category.
↪element_class'>
sage: x.parent()
Set of prime numbers (wrapper implementation)
sage: 13 in P
True
sage: 12 in P
False
sage: y = x+1; y
14

```

(continues on next page)

(continued from previous page)

```

sage: type(y)
<type 'sage.rings.integer.Integer'>

sage: z = P.next(x); z
17
sage: type(z)
<class 'sage.categories.examples.sets_cat.PrimeNumbers_Wrapper_with_category.
↪element_class'>
sage: z.parent()
Set of prime numbers (wrapper implementation)

```

class Element

Bases: `sage.structure.element_wrapper.ElementWrapper`, `sage.categories.examples.sets_cat.PrimeNumbers_Abstract.Element`

ElementWrapper

alias of `sage.structure.element_wrapper.ElementWrapper`

5.29 Example of a set with grading

`sage.categories.examples.sets_with_grading.Example`

alias of `sage.categories.examples.sets_with_grading.NonNegativeIntegers`

class `sage.categories.examples.sets_with_grading.NonNegativeIntegers`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

Non negative integers graded by themselves.

EXAMPLES:

```

sage: E = SetsWithGrading().example(); E
Non negative integers
sage: E in Sets().Infinite()
True
sage: E.graded_component(0)
{0}
sage: E.graded_component(100)
{100}

```

an_element()

Return 0.

EXAMPLES:

```

sage: SetsWithGrading().example().an_element()
0

```

generating_series(*var='z'*)

Return $1/(1 - z)$.

EXAMPLES:

```

sage: N = SetsWithGrading().example(); N
Non negative integers
sage: f = N.generating_series(); f
1/(-z + 1)
sage: LaurentSeriesRing(ZZ, 'z')(f)
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + z^7 + z^8 + z^9 + z^10 + z^11 + z^12 + z^
↪13 + z^14 + z^15 + z^16 + z^17 + z^18 + z^19 + 0(z^20)

```

graded_component(*grade*)

Return the component with grade *grade*.

EXAMPLES:

```

sage: N = SetsWithGrading().example()
sage: N.graded_component(65)
{65}

```

grading(*elt*)

Return the grade of *elt*.

EXAMPLES:

```

sage: N = SetsWithGrading().example()
sage: N.grading(10)
10

```

5.30 Examples of parents endowed with multiple realizations

class `sage.categories.examples.with_realizations.SubsetAlgebra(R, S)`

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.parent.Parent`

An example of parent endowed with several realizations

We consider an algebra $A(S)$ whose bases are indexed by the subsets s of a given set S . We consider three natural basis of this algebra: *F*, *In*, and *Out*. In the first basis, the product is given by the union of the indexing sets. That is, for any $s, t \subset S$

$$F_s F_t = F_{s \cup t}$$

The *In* basis and *Out* basis are defined respectively by:

$$In_s = \sum_{t \subset s} F_t \quad \text{and} \quad F_s = \sum_{t \supset s} Out_t$$

Each such basis gives a realization of A , where the elements are represented by their expansion in this basis.

This parent, and its code, demonstrate how to implement this algebra and its three realizations, with coercions and mixed arithmetic between them.

See also:

- [Sets\(\).WithRealizations](#)
- the [Implementing Algebraic Structures](#) thematic tutorial.

EXAMPLES:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.base_ring()
Rational Field
```

The three bases of A:

```
sage: F = A.F() ; F
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis
sage: In = A.In() ; In
The subset algebra of {1, 2, 3} over Rational Field in the In basis
sage: Out = A.Out(); Out
The subset algebra of {1, 2, 3} over Rational Field in the Out basis
```

One can quickly define all the bases using the following shortcut:

```
sage: A.inject_shorthands()
Defining F as shorthand for The subset algebra of {1, 2, 3} over Rational Field in
↳the Fundamental basis
Defining In as shorthand for The subset algebra of {1, 2, 3} over Rational Field in
↳the In basis
Defining Out as shorthand for The subset algebra of {1, 2, 3} over Rational Field
↳in the Out basis
```

Accessing the basis elements is done with `basis()` method:

```
sage: F.basis().list()
[F[{}], F[{1}], F[{2}], F[{3}], F[{1, 2}], F[{1, 3}], F[{2, 3}], F[{1, 2, 3}]]
```

To access a particular basis element, you can use the `from_set()` method:

```
sage: F.from_set(2,3)
F[{2, 3}]
sage: In.from_set(1,3)
In[{1, 3}]
```

or as a convenient shorthand, one can use the following notation:

```
sage: F[2,3]
F[{2, 3}]
sage: In[1,3]
In[{1, 3}]
```

Some conversions:

```
sage: F(In[2,3])
F[{}] + F[{2}] + F[{3}] + F[{2, 3}]
sage: In(F[2,3])
In[{}] - In[{2}] - In[{3}] + In[{2, 3}]

sage: Out(F[3])
Out[{3}] + Out[{1, 3}] + Out[{2, 3}] + Out[{1, 2, 3}]
sage: F(Out[3])
```

(continues on next page)

(continued from previous page)

```
F[{3}] - F[{1, 3}] - F[{2, 3}] + F[{1, 2, 3}]
```

```
sage: Out(In[2,3])
```

```
Out[{}] + Out[{1}] + 2*Out[{2}] + 2*Out[{3}] + 2*Out[{1, 2}] + 2*Out[{1, 3}] +
↳4*Out[{2, 3}] + 4*Out[{1, 2, 3}]
```

We can now mix expressions:

```
sage: (1 + Out[1]) * In[2,3]
```

```
Out[{}] + 2*Out[{1}] + 2*Out[{2}] + 2*Out[{3}] + 2*Out[{1, 2}] + 2*Out[{1, 3}] +
↳4*Out[{2, 3}] + 4*Out[{1, 2, 3}]
```

```
class Bases(parent_with_realization)
```

Bases: `sage.categories.realizations.Category_realization_of_parent`

The category of the realizations of the subset algebra

```
class ParentMethods
```

Bases: object

```
from_set(*args)
```

Construct the monomial indexed by the set containing the elements passed as arguments.

EXAMPLES:

```
sage: In = Sets().WithRealizations().example().In(); In
```

The subset algebra of {1, 2, 3} over Rational Field in the In basis

```
sage: In.from_set(2,3)
```

```
In[{2, 3}]
```

As a shorthand, one can construct elements using the following notation:

```
sage: In[2,3]
```

```
In[{2, 3}]
```

```
one()
```

Returns the unit of this algebra.

This default implementation takes the unit in the fundamental basis, and coerces it in `self`.

EXAMPLES:

```
sage: A = Sets().WithRealizations().example(); A
```

The subset algebra of {1, 2, 3} over Rational Field

```
sage: In = A.In(); Out = A.Out()
```

```
sage: In.one()
```

```
In[{}]
```

```
sage: Out.one()
```

```
Out[{}] + Out[{1}] + Out[{2}] + Out[{3}] + Out[{1, 2}] + Out[{1, 3}] +
↳Out[{2, 3}] + Out[{1, 2, 3}]
```

```
super_categories()
```

EXAMPLES:

```
sage: A = Sets().WithRealizations().example(); A
```

The subset algebra of {1, 2, 3} over Rational Field

(continues on next page)

(continued from previous page)

```

sage: C = A.Bases(); C
Category of bases of The subset algebra of {1, 2, 3} over Rational Field
sage: C.super_categories()
[Category of realizations of The subset algebra of {1, 2, 3} over Rational_
↪Field,
  Join of Category of algebras with basis over Rational Field and
  Category of commutative algebras over Rational Field and
  Category of realizations of unital magmas]

```

F

alias of *SubsetAlgebra.Fundamental*

class Fundamental(A)

Bases: `sage.combinat.free_module.CombinatorialFreeModule`, `sage.misc.bindable_class.BindableClass`

The Subset algebra, in the fundamental basis

INPUT:

- *A* – a parent with realization in *SubsetAlgebra*

EXAMPLES:

```

sage: A = Sets().WithRealizations().example()
sage: A.F()
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis
sage: A.Fundamental()
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis

```

one()

Return the multiplicative unit element.

EXAMPLES:

```

sage: A = AlgebrasWithBasis(QQ).example()
sage: A.one_basis()
word:
sage: A.one()
B[word: ]

```

one_basis()

Returns the index of the basis element which is equal to '1'.

EXAMPLES:

```

sage: F = Sets().WithRealizations().example().F(); F
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis
sage: F.one_basis()
{}
sage: F.one()
F[{}]

```

product_on_basis(left, right)

Product of basis elements, as per `AlgebrasWithBasis.ParentMethods.product_on_basis()`.

INPUT:

- `left`, `right` – sets indexing basis elements

EXAMPLES:

```
sage: F = Sets().WithRealizations().example().FC(); F
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis
sage: S = F.basis().keys(); S
Subsets of {1, 2, 3}
sage: F.product_on_basis(S([], []), S([], []))
F[{}]
sage: F.product_on_basis(S({1}), S({3}))
F[{1, 3}]
sage: F.product_on_basis(S({1,2}), S({2,3}))
F[{1, 2, 3}]
```

class `In(A)`

Bases: `sage.combinat.free_module.CombinatorialFreeModule`, `sage.misc.bindable_class.BindableClass`

The Subset Algebra, in the *In* basis

INPUT:

- `A` – a parent with realization in *SubsetAlgebra*

EXAMPLES:

```
sage: A = Sets().WithRealizations().example()
sage: A.In()
The subset algebra of {1, 2, 3} over Rational Field in the In basis
```

class `Out(A)`

Bases: `sage.combinat.free_module.CombinatorialFreeModule`, `sage.misc.bindable_class.BindableClass`

The Subset Algebra, in the *Out* basis

INPUT:

- `A` – a parent with realization in *SubsetAlgebra*

EXAMPLES:

```
sage: A = Sets().WithRealizations().example()
sage: A.Out()
The subset algebra of {1, 2, 3} over Rational Field in the Out basis
```

`a_realization()`

Returns the default realization of `self`

EXAMPLES:

```
sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.a_realization()
The subset algebra of {1, 2, 3} over Rational Field in the Fundamental basis
```

`base_set()`

EXAMPLES:

```

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.base_set()
{1, 2, 3}

```

indices()

The objects that index the basis elements of this algebra.

EXAMPLES:

```

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.indices()
Subsets of {1, 2, 3}

```

indices_key(x)

A key function on a set which gives a linear extension of the inclusion order.

INPUT:

- x – set

EXAMPLES:

```

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: sorted(A.indices(), key=A.indices_key)
[{}, {1}, {2}, {3}, {1, 2}, {1, 3}, {2, 3}, {1, 2, 3}]

```

supsets(set)

Returns all the subsets of S containing set

INPUT:

- set – a subset of the base set S of self

EXAMPLES:

```

sage: A = Sets().WithRealizations().example(); A
The subset algebra of {1, 2, 3} over Rational Field
sage: A.supsets(Set((2,)))
[{}1, 2, 3}, {2, 3}, {1, 2}, {2}]

```

INTERNALS

6.1 Specific category classes

This is placed in a separate file from `categories.py` to avoid circular imports (as morphisms must be very low in the hierarchy with the new coercion model).

class `sage.categories.category_types.AbelianCategory`(*s=None*)

Bases: `sage.categories.category.Category`

is_abelian()

Return True as self is an abelian category.

EXAMPLES:

```
sage: CommutativeAdditiveGroups().is_abelian()
True
```

class `sage.categories.category_types.Category_ideal`(*ambient, name=None*)

Bases: `sage.categories.category_types.Category_in_ambient`

classmethod `an_instance`()

Return an instance of this class.

EXAMPLES:

```
sage: AlgebraIdeals.an_instance()
Category of algebra ideals in Univariate Polynomial Ring in x over Rational_
↪Field
```

ring()

Return the ambient ring used to describe objects self.

EXAMPLES:

```
sage: C = Ideals(IntegerRing())
sage: C.ring()
Integer Ring
```

class `sage.categories.category_types.Category_in_ambient`(*ambient, name=None*)

Bases: `sage.categories.category.Category`

Initialize self.

EXAMPLES:

```
sage: C = Ideals(IntegerRing())
sage: TestSuite(C).run()
```

ambient()

Return the ambient object in which objects of this category are embedded.

EXAMPLES:

```
sage: C = Ideals(IntegerRing())
sage: C.ambient()
Integer Ring
```

class `sage.categories.category_types.Category_module`(*base, name=None*)

Bases: `sage.categories.category_types.AbelianCategory`, `sage.categories.category_types.Category_over_base_ring`

class `sage.categories.category_types.Category_over_base`(*base, name=None*)

Bases: `sage.categories.category.CategoryWithParameters`

A base class for categories over some base object

INPUT:

- *base* – a category C or an object of such a category

Assumption: the classes for the parents, elements, morphisms, of `self` should only depend on C . See [trac ticket #11935](#) for details.

EXAMPLES:

```
sage: Algebras(GF(2)).element_class is Algebras(GF(3)).element_class
True

sage: C = GF(2).category()
sage: Algebras(GF(2)).parent_class is Algebras(C).parent_class
True

sage: C = ZZ.category()
sage: Algebras(ZZ).element_class is Algebras(C).element_class
True
```

classmethod `an_instance()`

Returns an instance of this class

EXAMPLES:

```
sage: Algebras.an_instance()
Category of algebras over Rational Field
```

base()

Return the base over which elements of this category are defined.

EXAMPLES:

```
sage: C = Algebras(QQ)
sage: C.base()
Rational Field
```

class `sage.categories.category_types.Category_over_base_ring`(*base, name=None*)

Bases: `sage.categories.category_types.Category_over_base`

Initialize self.

EXAMPLES:

```
sage: C = Algebras(GF(2)); C
Category of algebras over Finite Field of size 2
sage: TestSuite(C).run()
```

base_ring()

Return the base ring over which elements of this category are defined.

EXAMPLES:

```
sage: C = Algebras(GF(2))
sage: C.base_ring()
Finite Field of size 2
```

class `sage.categories.category_types.Elements`(*object*)

Bases: `sage.categories.category.Category`

The category of all elements of a given parent.

EXAMPLES:

```
sage: a = IntegerRing()(5)
sage: C = a.category(); C
Category of elements of Integer Ring
sage: a in C
True
sage: 2/3 in C
False
sage: loads(C.dumps()) == C
True
```

classmethod `an_instance`()

Returns an instance of this class

EXAMPLES:

```
sage: Elements.an_instance()
Category of elements of Rational Field
```

object()

EXAMPLES:

```
sage: Elements(ZZ).object()
Integer Ring
```

super_categories()

EXAMPLES:

```
sage: Elements(ZZ).super_categories()
[Category of objects]
```

Todo: Check that this is what we want.

6.2 Singleton categories

class `sage.categories.category_singleton.Category_contains_method_by_parent_class`

Bases: `object`

Returns whether `x` is an object in this category.

More specifically, returns `True` if and only if `x` has a category which is a subcategory of this one.

EXAMPLES:

```
sage: ZZ in Sets()
True
```

class `sage.categories.category_singleton.Category_singleton(s=None)`

Bases: `sage.categories.category.Category`

A base class for implementing singleton category

A *singleton* category is a category whose class takes no parameters like `Fields()` or `Rings()`. See also the [Singleton design pattern](#).

This is a subclass of `Category`, with a couple optimizations for singleton categories.

The main purpose is to make the idioms:

```
sage: QQ in Fields()
True
sage: ZZ in Fields()
False
```

as fast as possible, and in particular competitive to calling a constant Python method, in order to foster its systematic use throughout the Sage library. Such tests are time critical, in particular when creating a lot of polynomial rings over small fields like in the elliptic curve code.

EXAMPLES:

```
sage: from sage.categories.category_singleton import Category_singleton
sage: class MyRings(Category):
....:     def super_categories(self): return Rings().super_categories()
sage: class MyRingsSingleton(Category_singleton):
....:     def super_categories(self): return Rings().super_categories()
```

We create three rings. One of them is contained in the usual category of rings, one in the category of “my rings” and the third in the category of “my rings singleton”:

```
sage: R = QQ['x,y']
sage: R1 = Parent(category = MyRings())
sage: R2 = Parent(category = MyRingsSingleton())
sage: R in MyRings()
False
sage: R1 in MyRings()
```

(continues on next page)

(continued from previous page)

```

True
sage: R1 in MyRingsSingleton()
False
sage: R2 in MyRings()
False
sage: R2 in MyRingsSingleton()
True

```

One sees that containment tests for the singleton class is a lot faster than for a usual class:

```

sage: timeit("R in MyRings()", number=10000)           # not tested
10000 loops, best of 3: 7.12  $\mu$ s per loop
sage: timeit("R1 in MyRings()", number=10000)         # not tested
10000 loops, best of 3: 6.98  $\mu$ s per loop
sage: timeit("R in MyRingsSingleton()", number=10000) # not tested
10000 loops, best of 3: 3.08  $\mu$ s per loop
sage: timeit("R2 in MyRingsSingleton()", number=10000) # not tested
10000 loops, best of 3: 2.99  $\mu$ s per loop

```

So this is an improvement, but not yet competitive with a pure Cython method:

```

sage: timeit("R.is_ring()", number=10000)           # not tested
10000 loops, best of 3: 383 ns per loop

```

However, it is competitive with a Python method. Actually it is faster, if one stores the category in a variable:

```

sage: _Rings = Rings()
sage: R3 = Parent(category = _Rings)
sage: R3.is_ring.__module__
'sage.categories.rings'
sage: timeit("R3.is_ring()", number=10000)           # not tested
10000 loops, best of 3: 2.64  $\mu$ s per loop
sage: timeit("R3 in Rings()", number=10000)         # not tested
10000 loops, best of 3: 3.01  $\mu$ s per loop
sage: timeit("R3 in _Rings", number=10000)           # not tested
10000 loops, best of 3: 652 ns per loop

```

This might not be easy to further optimize, since the time is consumed in many different spots:

```

sage: timeit("MyRingsSingleton.__classcall__()", number=10000) # not tested
10000 loops, best of 3: 306 ns per loop

sage: X = MyRingsSingleton()
sage: timeit("R in X ", number=10000)               # not tested
10000 loops, best of 3: 699 ns per loop

sage: c = MyRingsSingleton().__contains__
sage: timeit("c(R)", number = 10000)                 # not tested
10000 loops, best of 3: 661 ns per loop

```

Warning: A singleton concrete class A should not have a subclass B (necessarily concrete). Otherwise, creating an instance a of A and an instance b of B would break the singleton principle: A would have two

instances a and b .

With the current implementation only direct subclasses of `Category_singleton` are supported:

```
sage: class MyRingsSingleton(Category_singleton):
.....:     def super_categories(self): return Rings().super_categories()
sage: class Disaster(MyRingsSingleton): pass
sage: Disaster()
```

Traceback (most recent call last):

```
...
AssertionError: <class '__main__.Disaster'> is not a direct subclass of <class
->'sage.categories.category_singleton.Category_singleton'>
```

However, it is acceptable for a direct subclass R of `Category_singleton` to create its unique instance as an instance of a subclass of itself (in which case, it's the subclass of R which is concrete, not R itself). This is used for example to plug in extra category code via a dynamic subclass:

```
sage: from sage.categories.category_singleton import Category_singleton
sage: class R(Category_singleton):
.....:     def super_categories(self): return [Sets()]
sage: R()
Category of r
sage: R().__class__
<class '__main__.R_with_category'>
sage: R().__class__.mro()
[<class '__main__.R_with_category'>,
 <class '__main__.R'>,
 <class 'sage.categories.category_singleton.Category_singleton'>,
 <class 'sage.categories.category.Category'>,
 <class 'sage.structure.unique_representation.UniqueRepresentation'>,
 <class 'sage.structure.unique_representation.CachedRepresentation'>,
 <type 'sage.misc.fast_methods.WithEqualityById'>,
 <type 'sage.structure.sage_object.SageObject'>,
 <class '__main__.R.subcategory_class'>,
 <class 'sage.categories.sets_cat.Sets.subcategory_class'>,
 <class 'sage.categories.sets_with_partial_maps.SetsWithPartialMaps.subcategory_
->class'>,
 <class 'sage.categories.objects.Objects.subcategory_class'>,
 <... 'object'>]
sage: R() is R()
True
sage: R() is R().__class__()
True
```

In that case, R is an abstract class and has a single concrete subclass, so this does not break the Singleton design pattern.

See also:

`Category.__classcall__()`, `Category.__init__()`

Note: The `_test_category` test is failing because `MyRingsSingleton()` is not a subcategory of the join of its super categories:

```
sage: C = MyRingsSingleton()
```

(continues on next page)

(continued from previous page)

```

sage: C.super_categories()
[Category of rngs, Category of semirings]
sage: Rings() & Semirings()
Category of rings
sage: C.is_subcategory(Rings())
False

```

Oh well; it's not really relevant for those tests.

6.3 Fast functions for the category framework

AUTHOR:

- Simon King (initial version)

class sage.categories.category_cy_helper.AxiomContainer

Bases: dict

A fast container for axioms.

This is derived from dict. A key is the name of an axiom. The corresponding value is the “rank” of this axiom, that is used to order the axioms in `canonicalize_axioms()`.

EXAMPLES:

```

sage: all_axioms = sage.categories.category_with_axiom.all_axioms
sage: isinstance(all_axioms, sage.categories.category_with_axiom.AxiomContainer)
True

```

add(*axiom*)

Add a new axiom name, of the next rank.

EXAMPLES:

```

sage: all_axioms = sage.categories.category_with_axiom.all_axioms
sage: m = max(all_axioms.values())
sage: all_axioms.add('Awesome')
sage: all_axioms['Awesome'] == m + 1
True

```

To avoid side effects, we remove the added axiom:

```

sage: del all_axioms['Awesome']

```

sage.categories.category_cy_helper.canonicalize_axioms(*all_axioms*, *axioms*)

Canonicalize a set of axioms.

INPUT:

- *all_axioms* – all available axioms
- *axioms* – a set (or iterable) of axioms

Note: `AxiomContainer` provides a fast container for axioms, and the collection of axioms is stored in `sage.categories.category_with_axiom`. In order to avoid circular imports, we expect that the collection of all axioms is provided as an argument to this auxiliary function.

OUTPUT:

A set of axioms as a tuple sorted according to the order of the tuple `all_axioms` in `sage.categories.category_with_axiom`.

EXAMPLES:

```
sage: from sage.categories.category_with_axiom import canonicalize_axioms, all_
↪axioms
sage: canonicalize_axioms(all_axioms, ["Commutative", "Connected", "WithBasis",
↪"Finite"])
('Finite', 'Connected', 'WithBasis', 'Commutative')
sage: canonicalize_axioms(all_axioms, ["Commutative", "Connected", "Commutative",
↪"WithBasis", "Finite"])
('Finite', 'Connected', 'WithBasis', 'Commutative')
```

`sage.categories.category_cy_helper.category_sort_key(category)`

Return `category._cmp_key`.

This helper function is used for sorting lists of categories.

It is semantically equivalent to `operator.attrgetter()("_cmp_key")`, but currently faster.

EXAMPLES:

```
sage: from sage.categories.category_cy_helper import category_sort_key
sage: category_sort_key(Rings()) is Rings()._cmp_key
True
```

`sage.categories.category_cy_helper.get_axiom_index(all_axioms, axiom)`

Helper function: Return the rank of an axiom.

INPUT:

- `all_axioms` – the axiom collection
- `axiom` – string, name of an axiom

EXAMPLES:

```
sage: all_axioms = sage.categories.category_with_axiom.all_axioms
sage: from sage.categories.category_cy_helper import get_axiom_index
sage: get_axiom_index(all_axioms, 'AdditiveCommutative') == all_axioms[
↪'AdditiveCommutative']
True
```

`sage.categories.category_cy_helper.join_as_tuple(categories, axioms, ignore_axioms)`

Helper for `join()`.

INPUT:

- `categories` – tuple of categories to be joined,
- `axioms` – tuple of strings; the names of some supplementary axioms.

- `ignore_axioms` – tuple of pairs `(cat, axiom)`, such that `axiom` will not be applied to `cat`, should `cat` occur in the algorithm.

EXAMPLES:

```
sage: from sage.categories.category_helper import join_as_tuple
sage: T = (Coalgebras(QQ), Sets().Finite(), Algebras(ZZ), SimplicialComplexes())
sage: join_as_tuple(T,(),())
(Category of algebras over Integer Ring,
 Category of finite monoids,
 Category of finite additive groups,
 Category of coalgebras over Rational Field,
 Category of finite simplicial complexes)
sage: join_as_tuple(T,('WithBasis',),())
(Category of algebras with basis over Integer Ring,
 Category of finite monoids,
 Category of coalgebras with basis over Rational Field,
 Category of finite additive groups,
 Category of finite simplicial complexes)
sage: join_as_tuple(T,(),((Monoids(), 'Finite'),))
(Category of algebras over Integer Ring,
 Category of finite additive groups,
 Category of coalgebras over Rational Field,
 Category of finite simplicial complexes)
```

6.4 Coercion methods for categories

The purpose of this Cython module is to hold special coercion methods, which are inserted by their respective categories.

6.5 Poor Man's map

class `sage.categories.poor_man_map.PoorManMap`(*function*, *domain=None*, *codomain=None*, *name=None*)
 Bases: `sage.structure.sage_object.SageObject`

A class for maps between sets which are not (yet) modeled by parents

Could possibly disappear when all combinatorial classes / enumerated sets will be parents

INPUT:

- `function` – a callable or an iterable of callables. This represents the underlying function used to implement this map. If it is an iterable, then the callables will be composed to implement this map.
- `domain` – the domain of this map or `None` if the domain is not known or should remain unspecified
- `codomain` – the codomain of this map or `None` if the codomain is not known or should remain unspecified
- `name` – a name for this map or `None` if this map has no particular name

EXAMPLES:

```
sage: from sage.categories.poor_man_map import PoorManMap
sage: f = PoorManMap(factorial, domain = (1, 2, 3), codomain = (1, 2, 6))
```

(continues on next page)

(continued from previous page)

```
sage: f
A map from (1, 2, 3) to (1, 2, 6)
sage: f(3)
6
```

The composition of several functions can be created by passing in a tuple of functions:

```
sage: i = PoorManMap((factorial, sqrt), domain=(1, 4, 9), codomain=(1, 2, 6))
```

However, the same effect can also be achieved by just composing maps:

```
sage: g = PoorManMap(factorial, domain=(1, 2, 3), codomain=(1, 2, 6))
sage: h = PoorManMap(sqrt, domain=(1, 4, 9), codomain=(1, 2, 3))
sage: i == g*h
True
```

codomain()

Returns the codomain of self

EXAMPLES:

```
sage: from sage.categories.poor_man_map import PoorManMap
sage: PoorManMap(lambda x: x+1, domain=(1,2,3), codomain=(2,3,4)).codomain()
(2, 3, 4)
```

domain()

Returns the domain of self

EXAMPLES:

```
sage: from sage.categories.poor_man_map import PoorManMap
sage: PoorManMap(lambda x: x+1, domain=(1,2,3), codomain=(2,3,4)).domain()
(1, 2, 3)
```

INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

C

sage.categories.action, 155
sage.categories.additive_groups, 158
sage.categories.additive_magmas, 160
sage.categories.additive_monoids, 171
sage.categories.additive_semigroups, 172
sage.categories.affine_weyl_groups, 174
sage.categories.algebra_functor, 773
sage.categories.algebra_ideals, 177
sage.categories.algebra_modules, 178
sage.categories.algebras, 178
sage.categories.algebras_with_basis, 182
sage.categories.aperiodic_semigroups, 187
sage.categories.associative_algebras, 187
sage.categories.bialgebras, 187
sage.categories.bialgebras_with_basis, 189
sage.categories.bimodules, 193
sage.categories.cartesian_product, 769
sage.categories.category, 28
sage.categories.category_helper, 859
sage.categories.category_singleton, 856
sage.categories.category_types, 853
sage.categories.category_with_axiom, 64
sage.categories.classical_crystals, 194
sage.categories.coalgebras, 198
sage.categories.coalgebras_with_basis, 203
sage.categories.coercion_methods, 861
sage.categories.commutative_additive_groups, 205
sage.categories.commutative_additive_monoids, 207
sage.categories.commutative_additive_semigroups, 207
sage.categories.commutative_algebra_ideals, 208
sage.categories.commutative_algebras, 208
sage.categories.commutative_ring_ideals, 209
sage.categories.commutative_rings, 209
sage.categories.complete_discrete_valuation, 213
sage.categories.complex_reflection_groups, 217
sage.categories.complex_reflection_or_generalized_coxeter, 219
sage.categories.covariant_functorial_construction, 763
sage.categories.coxeter_group_algebras, 237
sage.categories.coxeter_groups, 240
sage.categories.crystals, 269
sage.categories.cw_complexes, 293
sage.categories.discrete_valuation, 296
sage.categories.distributive_magmas_and_additive_magmas, 298
sage.categories.division_rings, 299
sage.categories.domains, 300
sage.categories.dual, 773
sage.categories.enumerated_sets, 301
sage.categories.euclidean_domains, 307
sage.categories.examples.algebras_with_basis, 793
sage.categories.examples.commutative_additive_monoids, 794
sage.categories.examples.commutative_additive_semigroups, 795
sage.categories.examples.coxeter_groups, 797
sage.categories.examples.crystals, 797
sage.categories.examples.cw_complexes, 799
sage.categories.examples.facade_sets, 800
sage.categories.examples.finite_coxeter_groups, 801
sage.categories.examples.finite_dimensional_algebras_with, 803
sage.categories.examples.finite_dimensional_lie_algebras_w, 804
sage.categories.examples.finite_enumerated_sets, 808
sage.categories.examples.finite_monoids, 810
sage.categories.examples.finite_semigroups, 812
sage.categories.examples.finite_weyl_groups, 814
sage.categories.examples.graded_connected_hopf_algebras_wi, 816
sage.categories.examples.graded_modules_with_basis,

- 818
- sage.categories.examples.graphs, 820
- sage.categories.examples.hopf_algebras_with_basis, 821
- sage.categories.examples.infinite_enumerated_sets, 823
- sage.categories.examples.lie_algebras, 824
- sage.categories.examples.lie_algebras_with_basis, 826
- sage.categories.examples.magnas, 827
- sage.categories.examples.manifolds, 828
- sage.categories.examples.monoids, 829
- sage.categories.examples.posets, 831
- sage.categories.examples.semigroups, 833
- sage.categories.examples.semigroups_cython, 838
- sage.categories.examples.sets_cat, 840
- sage.categories.examples.sets_with_grading, 846
- sage.categories.examples.with_realizations, 847
- sage.categories.facade_sets, 760
- sage.categories.fields, 309
- sage.categories.filtered_algebras, 314
- sage.categories.filtered_algebras_with_basis, 315
- sage.categories.filtered_modules, 322
- sage.categories.filtered_modules_with_basis, 324
- sage.categories.finite_complex_reflection_groups, 338
- sage.categories.finite_coxeter_groups, 355
- sage.categories.finite_crystals, 367
- sage.categories.finite_dimensional_algebras_with_basis, 367
- sage.categories.finite_dimensional_bialgebras_with_basis, 386
- sage.categories.finite_dimensional_coalgebras_with_basis, 386
- sage.categories.finite_dimensional_graded_lie_algebras_with_basis, 387
- sage.categories.finite_dimensional_hopf_algebras_with_basis, 388
- sage.categories.finite_dimensional_lie_algebras_with_basis, 389
- sage.categories.finite_dimensional_modules_with_basis, 405
- sage.categories.finite_dimensional_nilpotent_lie_algebras_with_basis, 413
- sage.categories.finite_dimensional_semisimple_lie_algebras_with_basis, 414
- sage.categories.finite_enumerated_sets, 416
- sage.categories.finite_fields, 422
- sage.categories.finite_groups, 423
- sage.categories.finite_lattice_posets, 425
- sage.categories.finite_monoids, 428
- sage.categories.finite_permutation_groups, 432
- sage.categories.finite_posets, 436
- sage.categories.finite_semigroups, 457
- sage.categories.finite_sets, 459
- sage.categories.finite_weyl_groups, 460
- sage.categories.finitely_generated_lambda_bracket_algebras, 461
- sage.categories.finitely_generated_lie_conformal_algebras, 462
- sage.categories.finitely_generated_magnas, 463
- sage.categories.finitely_generated_semigroups, 464
- sage.categories.function_fields, 466
- sage.categories.functor, 98
- sage.categories.g_sets, 467
- sage.categories.gcd_domains, 467
- sage.categories.generalized_coxeter_groups, 468
- sage.categories.graded_algebras, 469
- sage.categories.graded_algebras_with_basis, 470
- sage.categories.graded_bialgebras, 472
- sage.categories.graded_bialgebras_with_basis, 472
- sage.categories.graded_coalgebras, 472
- sage.categories.graded_coalgebras_with_basis, 473
- sage.categories.graded_hopf_algebras, 474
- sage.categories.graded_hopf_algebras_with_basis, 474
- sage.categories.graded_lie_algebras, 475
- sage.categories.graded_lie_algebras_with_basis, 476
- sage.categories.graded_lie_conformal_algebras, 477
- sage.categories.graded_lie_modules, 478
- sage.categories.graded_modules_with_basis, 478
- sage.categories.graphs, 480
- sage.categories.group_algebras, 482
- sage.categories.groupoid, 487
- sage.categories.groups, 487
- sage.categories.h_trivial_semigroups, 510
- sage.categories.highest_weight_crystals, 497
- sage.categories.homset, 114
- sage.categories.homsets, 782
- sage.categories.hopf_algebras, 504
- sage.categories.hopf_algebras_with_basis, 506
- sage.categories.infinite_enumerated_sets, 511

sage.categories.integral_domains, 512
 sage.categories.isomorphic_objects, 781
 sage.categories.j_trivial_semigroups, 512
 sage.categories.kac_moody_algebras, 513
 sage.categories.l_trivial_semigroups, 550
 sage.categories.lambda_bracket_algebras, 514
 sage.categories.lambda_bracket_algebras_with_basis, 516
 sage.categories.lattice_posets, 517
 sage.categories.left_modules, 518
 sage.categories.lie_algebras, 519
 sage.categories.lie_algebras_with_basis, 529
 sage.categories.lie_conformal_algebras, 531
 sage.categories.lie_conformal_algebras_with_basis, 535
 sage.categories.lie_groups, 537
 sage.categories.loop_crystals, 537
 sage.categories.magmas, 551
 sage.categories.magmas_and_additive_magmas, 565
 sage.categories.magmatic_algebras, 567
 sage.categories.manifolds, 570
 sage.categories.map, 105
 sage.categories.matrix_algebras, 574
 sage.categories.metric_spaces, 575
 sage.categories.modular_abelian_varieties, 579
 sage.categories.modules, 580
 sage.categories.modules_with_basis, 590
 sage.categories.monoid_algebras, 616
 sage.categories.monoids, 616
 sage.categories.morphism, 122
 sage.categories.number_fields, 622
 sage.categories.objects, 624
 sage.categories.partially_ordered_monoids, 626
 sage.categories.permutation_groups, 626
 sage.categories.pointed_sets, 627
 sage.categories.polyhedra, 627
 sage.categories.poor_man_map, 861
 sage.categories.posets, 628
 sage.categories.primer, 1
 sage.categories.principal_ideal_domains, 637
 sage.categories.pushout, 126
 sage.categories.quantum_group_representations, 644
 sage.categories.quotient_fields, 638
 sage.categories.quotients, 780
 sage.categories.r_trivial_semigroups, 671
 sage.categories.realizations, 786
 sage.categories.regular_crystals, 650
 sage.categories.regular_supercrystals, 658
 sage.categories.right_modules, 660
 sage.categories.ring_ideals, 660
 sage.categories.rings, 661
 sage.categories.rngs, 670
 sage.categories.schemes, 671
 sage.categories.semigroups, 672
 sage.categories.semirings, 684
 sage.categories.semisimple_algebras, 684
 sage.categories.sets_cat, 686
 sage.categories.sets_with_grading, 712
 sage.categories.sets_with_partial_maps, 715
 sage.categories.shephard_groups, 715
 sage.categories.signed_tensor, 772
 sage.categories.simplicial_complexes, 716
 sage.categories.simplicial_sets, 717
 sage.categories.subobjects, 781
 sage.categories.subquotients, 780
 sage.categories.super_algebras, 724
 sage.categories.super_algebras_with_basis, 726
 sage.categories.super_hopf_algebras_with_basis, 727
 sage.categories.super_lie_conformal_algebras, 727
 sage.categories.super_modules, 729
 sage.categories.super_modules_with_basis, 731
 sage.categories.supercommutative_algebras, 733
 sage.categories.supercrystals, 734
 sage.categories.tensor, 771
 sage.categories.topological_spaces, 739
 sage.categories.triangular_kac_moody_algebras, 740
 sage.categories.tutorial, 102
 sage.categories.unique_factorization_domains, 742
 sage.categories.unital_algebras, 744
 sage.categories.vector_bundles, 746
 sage.categories.vector_spaces, 747
 sage.categories.weyl_groups, 751
 sage.categories.with_realizations, 788

Symbols

- `__classcall__()` (*sage.categories.category.Category* static method), 40
 - `__classcall__()` (*sage.categories.category_with_axiom.CategoryWithAxiom* static method), 90
 - `__classget__()` (*sage.categories.category_with_axiom.CategoryWithAxiom* static method), 90
 - `__init__()` (*sage.categories.category.Category* method), 41
 - `__init__()` (*sage.categories.category_with_axiom.CategoryWithAxiom* method), 91
 - `_all_super_categories()` (*sage.categories.category.Category* method), 34
 - `_all_super_categories_proper()` (*sage.categories.category.Category* method), 35
 - `_make_named_class()` (*sage.categories.category.Category* method), 36
 - `_make_named_class()` (*sage.categories.category.CategoryWithParameters.CategoryWithParameters* method), 60
 - `_repr_()` (*sage.categories.category.Category* method), 37
 - `_repr_()` (*sage.categories.category.JoinCategory.Category* method), 62
 - `_repr_object_names()` (*sage.categories.category.Category* method), 37
 - `_repr_object_names()` (*sage.categories.category.JoinCategory.Category* method), 62
 - `_repr_object_names()` (*sage.categories.category_with_axiom.CategoryWithAxiom* method), 91
 - `_repr_object_names_static()` (*sage.categories.category_with_axiom.CategoryWithAxiom* static method), 91
 - `_set_of_super_categories()` (*sage.categories.category.Category* method), 35
 - `_sort()` (*sage.categories.category.Category* static method), 39
 - `_sort_uniq()` (*sage.categories.category.Category* static method), 40
 - `_super_categories()` (*sage.categories.category.Category* method), 33
 - `_super_categories_for_classes()` (*sage.categories.category.Category* method), 34
 - `_test_category()` (*sage.categories.category.Category* method), 37
 - `_test_category_with_axiom()` (*sage.categories.category_with_axiom.CategoryWithAxiom* method), 92
 - `_with_axiom()` (*sage.categories.category.Category* method), 38
 - `_with_axiom_as_tuple()` (*sage.categories.category.Category* method), 38
 - `_without_axioms()` (*sage.categories.category.Category* method), 39
 - `_without_axioms()` (*sage.categories.category.JoinCategory.Category* method), 62
 - `_without_axioms()` (*sage.categories.category_with_axiom.CategoryWithAxiom* method), 92
- A**
- `a_realization()` (*sage.categories.examples.with_realizations.SubsetAlgebra* method), 851
 - `a_realization()` (*sage.categories.sets_cat.Sets.WithRealizations.ParentMorphism* method), 708
 - `AbelianCategory` (class in *sage.categories.category_types*), 853
 - `AbelianLieAlgebra` (class in *sage.categories.examples.finite_dimensional_lie_algebras_with_basis*), 804
 - `AbelianLieAlgebra` (class in *sage.categories.examples.lie_algebras_with_basis*), 826
 - `AbelianLieAlgebra.Element` (class in *sage.categories.examples.finite_dimensional_lie_algebras_with_basis*), 804

805 *method*), 218

AbelianLieAlgebra.Element (class in additional_structure()
sage.categories.examples.lie_algebras_with_basis), (sage.categories.covariant_functorial_construction.CovariantCon
 826 *method*), 763

abs() (sage.categories.metric_spaces.MetricSpaces.Element) additional_structure()
method), 576 (sage.categories.coxeter_groups.CoxeterGroups

absolute_covers() (sage.categories.coxeter_groups.CoxeterGroups.Element) Methods
method), 241 additional_structure()

absolute_le() (sage.categories.coxeter_groups.CoxeterGroups.Element) Methods
method), 241 (sage.categories.enumerated_sets.EnumeratedSets

absolute_length() (sage.categories.coxeter_groups.CoxeterGroups.Element) Methods
method), 242 additional_structure()
 (sage.categories.gcd_domains.GcdDomains

absolute_order_ideal() *method*), 467
 (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.Irreducible.ParentMethods
method), 340 (sage.categories.generalized_coxeter_groups.GeneralizedCoxeter

absolute_poset() (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.Irreducible.ParentMethods
method), 342 additional_structure()

act() (sage.categories.action.Action *method*), 156 (sage.categories.highest_weight_crystals.HighestWeightCrystals
 Action (class in sage.categories.action), 155 *method*), 503

ActionEndomorphism (class in sage.categories.action), additional_structure()
 156 (sage.categories.lie_groups.LieGroups

actor() (sage.categories.action.Action *method*), 156 *method*), 537

adams_operator() (sage.categories.bialgebras_with_basis.BialgebrasWithBasis.Element) Methods
method), 189 (sage.categories.magnas.Magnas.Unital

add() (sage.categories.category_helper.AxiomContainer *method*), 564
method), 859 additional_structure()

addition_table() (sage.categories.additive_magnas.AdditiveMagnas.ParentMethods) magnas_and_additive_magnas.MagnasAndAd
method), 166 *method*), 566

additional_structure() additional_structure()
 (sage.categories.additive_magnas.AdditiveMagnas.AdditiveMagnas) (sage.categories.magmatic_algebras.MagmaticAlgebras
method), 164 *method*), 569

additional_structure() additional_structure()
 (sage.categories.affine_weyl_groups.AffineWeylGroups (sage.categories.manifolds.Manifolds *method*),
method), 176 574

additional_structure() additional_structure()
 (sage.categories.bialgebras.Bialgebras (sage.categories.modules.Modules *method*),
method), 188 589

additional_structure() additional_structure()
 (sage.categories.bimodules.Bimodules (sage.categories.objects.Objects *method*),
method), 193 625

additional_structure() additional_structure()
 (sage.categories.category.Category *method*), (sage.categories.principal_ideal_domains.PrincipalIdealDomain
 46 *method*), 637

additional_structure() additional_structure()
 (sage.categories.category.JoinCategory (sage.categories.regular_crystals.RegularCrystals
method), 63 *method*), 658

additional_structure() additional_structure()
 (sage.categories.category_with_axiom.CategoryWithAxiom (sage.categories.unique_factorization_domains.UniqueFactorizat
method), 93 *method*), 743

additional_structure() additional_structure()
 (sage.categories.classical_crystals.ClassicalCrystals (sage.categories.vector_spaces.VectorSpaces
method), 197 *method*), 750

additional_structure() additional_structure()
 (sage.categories.complex_reflection_groups.ComplexReflectionGroups) (sage.categories.weyl_groups.WeylGroups

method), 760

additive_order() (sage.categories.commutative_additive_groups.CommutativeAdditiveGroups.ElementMethods method), 206

additive_semigroup_generators() (sage.categories.examples.commutative_additive_semigroups.ExampleCommutativeAdditiveSemigroupMagmas method), 796

AdditiveAssociative (sage.categories.additive_magmas.AdditiveMagmas attribute), 160

AdditiveAssociative() (sage.categories.additive_magmas.AdditiveMagmas.SubcategoryMethods method), 169

AdditiveCommutative (sage.categories.additive_groups.AdditiveGroups attribute), 158

AdditiveCommutative (sage.categories.additive_monoids.AdditiveMonoids attribute), 171

AdditiveCommutative (sage.categories.additive_semigroups.AdditiveSemigroups attribute), 172

AdditiveCommutative() (sage.categories.additive_magmas.AdditiveMagmas.SubcategoryMethods method), 170

AdditiveGroups (class in sage.categories.additive_groups), 158

AdditiveGroups.Algebras (class in sage.categories.additive_groups), 159

AdditiveGroups.Algebras.ParentMethods (class in sage.categories.additive_groups), 159

AdditiveGroups.Finite (class in sage.categories.additive_groups), 159

AdditiveGroups.Finite.Algebras (class in sage.categories.additive_groups), 159

AdditiveGroups.Finite.Algebras.ParentMethods (class in sage.categories.additive_groups), 159

AdditiveInverse (sage.categories.additive_monoids.AdditiveMonoids attribute), 171

AdditiveInverse (sage.categories.distributive_magmas_and_additive_magmas.DistributiveMagmasAndAdditiveMagmas attribute), 298

AdditiveInverse() (sage.categories.additive_magmas.AdditiveMagmas.SubcategoryMethods method), 164

AdditiveMagmas (class in sage.categories.additive_magmas), 160

AdditiveMagmas.AdditiveCommutative (class in sage.categories.additive_magmas), 160

AdditiveMagmas.AdditiveCommutative.Algebras (class in sage.categories.additive_magmas), 160

AdditiveMagmas.AdditiveCommutative.CartesianProducts (class in sage.categories.additive_magmas), 161

AdditiveMagmas.AdditiveUnital (class in sage.categories.additive_magmas), 161

AdditiveMagmas.AdditiveUnital.AdditiveInverse (class in sage.categories.additive_magmas), 161

AdditiveMagmas.AdditiveUnital.AdditiveInverse.CartesianProducts (class in sage.categories.additive_magmas), 161

AdditiveMagmas.AdditiveUnital.Algebras (class in sage.categories.additive_magmas), 161

AdditiveMagmas.AdditiveUnital.Algebras.ParentMethods (class in sage.categories.additive_magmas), 161

AdditiveMagmas.AdditiveUnital.CartesianProducts (class in sage.categories.additive_magmas), 162

AdditiveMagmas.AdditiveUnital.CartesianProducts.ParentMethods (class in sage.categories.additive_magmas), 162

AdditiveMagmas.AdditiveUnital.ElementMethods (class in sage.categories.additive_magmas), 162

AdditiveMagmas.AdditiveUnital.Homsets (class in sage.categories.additive_magmas), 162

AdditiveMagmas.AdditiveUnital.Homsets.ParentMethods (class in sage.categories.additive_magmas), 162

AdditiveMagmas.AdditiveUnital.ParentMethods (class in sage.categories.additive_magmas), 163

AdditiveMagmas.AdditiveUnital.SubcategoryMethods (class in sage.categories.additive_magmas), 163

AdditiveMagmas.AdditiveUnital.WithRealizations (class in sage.categories.additive_magmas), 164

AdditiveMagmas.AdditiveUnital.WithRealizations.ParentMethods (class in sage.categories.additive_magmas), 164

AdditiveMagmas.Algebras.ParentMethods (class in sage.categories.additive_magmas), 164

AdditiveMagmas.CartesianProducts (class in sage.categories.additive_magmas), 165

AdditiveMagmas.CartesianProducts.ElementMethods (class in sage.categories.additive_magmas), 165

AdditiveMagmas.ElementMethods (class in sage.categories.additive_magmas), 166

AdditiveMagmas.Homsets (class in sage.categories.additive_magmas), 166

AdditiveMagmas.ParentMethods (class in sage.categories.additive_magmas), 166

sage.categories.additive_magmas), 166
AdditiveMagmas.SubcategoryMethods (class in *algebra_generators*)
sage.categories.additive_magmas), 169
AdditiveMonoids (class in *algebra_generators*)
sage.categories.additive_monoids), 171
AdditiveMonoids.Homsets (class in *algebra_generators*)
sage.categories.additive_monoids), 171
AdditiveMonoids.ParentMethods (class in *algebra_generators*)
sage.categories.additive_monoids), 171
AdditiveSemigroups (class in *algebra_generators*)
sage.categories.additive_semigroups), 172
AdditiveSemigroups.Algebras (class in *algebra_generators*)
sage.categories.additive_semigroups), 172
AdditiveSemigroups.Algebras.ParentMethods (class in *algebra_generators*)
sage.categories.additive_semigroups), 173
AdditiveSemigroups.CartesianProducts (class in *algebra_generators*)
sage.categories.additive_semigroups), 173
AdditiveSemigroups.Homsets (class in *algebra_generators*)
sage.categories.additive_semigroups), 174
AdditiveSemigroups.ParentMethods (class in *algebra_generators*)
sage.categories.additive_semigroups), 174
AdditiveUnital (*sage.categories.additive_semigroups.AdditiveSemigroups* attribute), 172
AdditiveUnital() (*sage.categories.additive_magmas.AdditiveMagmas.SubcategoryMethods* method), 170
adjoint_matrix() (*sage.categories.finite_dimensional_lie_algebras_with_basis.finite_dimensional_lie_algebras_with_basis.ElementMethods* method), 389
affine_grading() (*sage.categories.loop_crystals.KirillovReinekeAlgebras.ParentMethods* method), 543
affine_grassmannian_elements_of_given_length() (*sage.categories.affine_weyl_groups.AffineWeylGroups.ParentMethods* method), 176
affine_grassmannian_to_core() (*sage.categories.affine_weyl_groups.AffineWeylGroups.ElementMethods* method), 175
affine_grassmannian_to_partition() (*sage.categories.affine_weyl_groups.AffineWeylGroups.ElementMethods* method), 175
AffineWeylGroups (class in *algebra_generators*)
sage.categories.affine_weyl_groups), 174
AffineWeylGroups.ElementMethods (class in *algebra_generators*)
sage.categories.affine_weyl_groups), 174
AffineWeylGroups.ParentMethods (class in *algebra_generators*)
sage.categories.affine_weyl_groups), 176
affinization() (*sage.categories.loop_crystals.KirillovReinekeAlgebras* attribute), 539
algebra() (*sage.categories.algebra_ideals.AlgebraIdeals* method), 177
algebra() (*sage.categories.algebra_modules.AlgebraModules* method), 178
algebra() (*sage.categories.commutative_algebra_ideals.CommutativeAlgebraIdeals* method), 208
algebra() (*sage.categories.sets_cat.Sets.ParentMethods* method), 694
algebra_generators)
(sage.categories.additive_magmas.AdditiveMagmas.Algebras.ParentMethods), 165
algebra_generators)
(sage.categories.additive_semigroups.AdditiveSemigroups.Algebras.ParentMethods), 173
algebra_generators)
(sage.categories.algebras.Algebras.Quotients.ParentMethods), 180
algebra_generators)
(sage.categories.examples.algebras_with_basis.FreeAlgebra) method), 793
algebra_generators)
(sage.categories.examples.finite_dimensional_algebras_with_basis.finite_dimensional_algebras_with_basis.ParentMethods), 803
algebra_generators)
(sage.categories.examples.hopf_algebras_with_basis.MyGroupAlgebras.ParentMethods), 821
algebra_generators)
(sage.categories.examples.lie_algebras_with_basis.IndexedPolynomialAlgebras.ParentMethods), 826
algebra_generators)
(sage.categories.magmatic_algebras.MagmaticAlgebras.ParentMethods), 670
algebra_generators)
(sage.categories.finite_dimensional_lie_algebras_with_basis.finite_dimensional_lie_algebras_with_basis.ElementMethods), 569
algebra_generators)
(sage.categories.monoids.Monoids.Algebras.ParentMethods), 617
algebra_generators)
(sage.categories.semigroups.Semigroups.Algebras.ParentMethods), 673
AlgebraFunctor (class in *algebra_functor*), 778
AlgebraicClosureFunctor (class in *algebra_functor*), 126
AlgebraicExtensionFunctor (class in *algebra_functor*), 126
AlgebraIdeals (class in *algebra_ideals*), 177
AlgebraModules (class in *algebra_modules*), 178
Algebras (class in *sage.categories.algebras*), 178
Algebras() (*sage.categories.groups.Groups* attribute), 487
Algebras() (*sage.categories.sets_cat.Sets.SubcategoryMethods* method), 697
Algebras.CartesianProducts (class in *algebras*), 179
Algebras.DualObjects (class in *algebras*), 179

Algebras.ElementMethods (class in method), 836
 sage.categories.algebras), 180
 Algebras.Quotients (class in method), 404
 sage.categories.algebras), 180
 Algebras.Quotients.ParentMethods (class in method), 707
 sage.categories.algebras), 180
 Algebras.SubcategoryMethods (class in method), 282
 sage.categories.algebras), 180
 Algebras.TensorProducts (class in method), 797
 sage.categories.algebras), 181
 Algebras.TensorProducts.ElementMethods (class in *sage.categories.algebras*), 181
 Algebras.TensorProducts.ParentMethods (class in *sage.categories.algebras*), 181
 AlgebrasCategory (class in method), 813
 sage.categories.algebra_functor), 778
 AlgebrasCategory.ParentMethods (class in method), 821
 sage.categories.algebra_functor), 779
 AlgebrasWithBasis (class in method), 824
 sage.categories.algebras_with_basis), 182
 AlgebrasWithBasis.CartesianProducts (class in method), 828
 sage.categories.algebras_with_basis), 183
 AlgebrasWithBasis.CartesianProducts.ParentMethods (class in *sage.categories.algebras_with_basis*), 183
 method), 829
 AlgebrasWithBasis.ElementMethods (class in method), 833
 sage.categories.algebras_with_basis), 184
 AlgebrasWithBasis.ParentMethods (class in method), 835
 sage.categories.algebras_with_basis), 184
 AlgebrasWithBasis.TensorProducts (class in method), 836
 sage.categories.algebras_with_basis), 185
 AlgebrasWithBasis.TensorProducts.ElementMethods (class in *sage.categories.algebras_with_basis*), 185
 method), 841
 AlgebrasWithBasis.TensorProducts.ParentMethods (class in *sage.categories.algebras_with_basis*), 185
 method), 842
 all_paths_to_highest_weight() (class in method), 846
 sage.categories.crystals.Crystals.ElementMethods
 method), 276
 all_super_categories() (class in method), 846
 sage.categories.category.Category method), 48
 AlmostComplex() (*sage.categories.manifolds.Manifolds.Submanifolds*) (class in method), 572
 method), 193
 ambient() (*sage.categories.category_types.Category_in_ambient*) (class in method), 854
 method), 49
 ambient() (*sage.categories.examples.finite_dimensional_lie_algebras_with_basis*) (class in method), 805
 method), 853
 ambient() (*sage.categories.examples.finite_enumerated_sets*) (class in method), 809
 method), 854
 ambient() (*sage.categories.examples.semigroups.IncompleteSemigroup*) (class in method), 834
 method), 855
 ambient() (*sage.categories.examples.semigroups.QuotientOfLinearGroup*) (class in method), 834
 method), 855
 ambient() (*sage.categories.finite_dimensional_lie_algebras_with_basis*) (class in method), 805
 method), 853
 ambient() (*sage.categories.sets_cat.Sets.Subquotients.ParentMethods*) (class in method), 707
 method), 797
 an_element() (*sage.categories.crystals.Crystals.ParentMethods*) (class in method), 282
 method), 797
 an_element() (*sage.categories.examples.commutative_additive_semigroups*) (class in method), 282
 method), 797
 an_element() (*sage.categories.examples.cw_complexes.Surface*) (class in method), 800
 method), 811
 an_element() (*sage.categories.examples.finite_monoids.IntegerModMonoids*) (class in method), 811
 method), 813
 an_element() (*sage.categories.examples.finite_semigroups.LeftRegularBases*) (class in method), 813
 method), 821
 an_element() (*sage.categories.examples.graphs.Cycle*) (class in method), 821
 method), 824
 an_element() (*sage.categories.examples.infinite_enumerated_sets.NonNegativeIntegers*) (class in method), 824
 method), 828
 an_element() (*sage.categories.examples.magnas.FreeMagma*) (class in method), 828
 method), 829
 an_element() (*sage.categories.examples.manifolds.Plane*) (class in method), 829
 method), 832
 an_element() (*sage.categories.examples.posets.FiniteSetsOrderedByInclusion*) (class in method), 832
 method), 833
 an_element() (*sage.categories.examples.semigroups.FreeSemigroup*) (class in method), 833
 method), 835
 an_element() (*sage.categories.examples.semigroups.LeftZeroSemigroup*) (class in method), 835
 method), 836
 an_element() (*sage.categories.examples.semigroups.QuotientOfLeftZeroSemigroup*) (class in method), 836
 method), 841
 an_element() (*sage.categories.examples.sets_cat.PrimeNumbers*) (class in method), 841
 method), 842
 an_element() (*sage.categories.examples.sets_cat.PrimeNumbers_Abstract*) (class in method), 842
 method), 846
 an_element() (*sage.categories.examples.sets_with_grading.NonNegativeIntegers*) (class in method), 846
 method), 846
 an_element() (*sage.categories.sets_cat.Sets.CartesianProducts.ParentMethods*) (class in method), 846
 method), 690
 an_element() (*sage.categories.sets_cat.Sets.ParentMethods*) (class in method), 695
 method), 695
 an_instance() (*sage.categories.algebra_modules.AlgebraModules*) (class in method), 178
 method), 178
 an_instance() (*sage.categories.bimodules.Bimodules*) (class in method), 193
 method), 193
 an_instance() (*sage.categories.category.Category*) (class in method), 49
 method), 49
 an_instance() (*sage.categories.category_types.Category_ideal*) (class in method), 853
 method), 853
 an_instance() (*sage.categories.category_types.FiniteEnumeratedSet*) (class in method), 854
 method), 854
 an_instance() (*sage.categories.category_types.Category_over_base*) (class in method), 854
 method), 855
 an_instance() (*sage.categories.category_types.Elements*) (class in method), 855
 method), 855
 an_instance() (*sage.categories.g_sets.GSets*) (class in method), 855
 method), 855

method), 467
 an_instance() (sage.categories.groupoid.Groupoid class method), 487
 Analytic() (sage.categories.manifolds.Manifolds.SubcategoryMethods method), 573
 annihilator() (sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis.ParentMethods method), 407
 annihilator_basis() (sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis.ParentMethods method), 408
 antichains() (sage.categories.finite_posets.FinitePosets.ParentMethods method), 436
 antipode() (sage.categories.hopf_algebras.HopfAlgebras.ElementMethods method), 504
 antipode() (sage.categories.hopf_algebras.HopfAlgebras.SubcategoryMethods method), 505
 antipode() (sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis.ParentMethods method), 508
 antipode() (sage.categories.super_hopf_algebras_with_basis.SuperHopfAlgebrasWithBasis.ParentMethods method), 727
 antipode_by_coercion() (sage.categories.hopf_algebras.HopfAlgebras.Realizations.ParentMethods method), 505
 antipode_on_basis() (sage.categories.examples.hopf_algebras_with_basis.ExampleHopfAlgebrasWithBasis.ParentMethods method), 822
 antipode_on_basis() (sage.categories.graded_hopf_algebras_with_basis.GradedHopfAlgebrasWithBasis.ParentMethods method), 474
 antipode_on_basis() (sage.categories.group_algebras.GroupAlgebras.ParentMethods method), 484
 antipode_on_basis() (sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis.ParentMethods method), 509
 Aperiodic (sage.categories.semigroups.Semigroups attribute), 674
 Aperiodic() (sage.categories.semigroups.Semigroups.SubcategoryMethods method), 680
 AperiodicSemigroups (class in sage.categories.aperiodic_semigroups), 187
 apply_conjugation_by_simple_reflection() (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods method), 220
 apply_demazure_product() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 242
 apply_multilinear_morphism() (sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods method), 614
 apply_reflections() (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods method), 220
 apply_simple_projection() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 242
 apply_simple_reflection() (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods method), 222
 apply_simple_reflection_left() (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods method), 223
 apply_simple_reflection_right() (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods method), 223
 apply_simple_reflections() (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods method), 801
 as_finite_dimensional_algebra() (sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis.ParentMethods method), 390
 Associative (sage.categories.magnas.Magnas attribute), 550
 Associative (sage.categories.magmatic_algebras.MagmaticAlgebras attribute), 567
 AssociativeAlgebras (class in sage.categories.magnas.Magnas.SubcategoryMethods method), 558
 AssociativeAlgebras (class in sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis.SubcategoryMethods method), 487
 axiom() (in module sage.categories.category_with_axiom), 96
 axiom() (in module sage.categories.category_with_axiom), 96
 AxiomContainer (class in sage.categories.category_with_axiom), 859
 axioms() (sage.categories.category.Category method), 49
 axioms() (sage.categories.category_with_axiom.CategoryWithAxiom method), 93

B

b_sharp() (sage.categories.loop_crystals.KirillovReshetikhinCrystals.ParentMethods method), 539
 baker_campbell_hausdorff() (sage.categories.lie_algebras.LieAlgebras.ParentMethods method), 522
 base() (sage.categories.category_with_axiom), 88
 base() (sage.categories.category_types.Category_over_base method), 854
 base() (sage.categories.tensor_products_element_methods_homsets_category_homsets_category method), 784
 base() (sage.categories.signed_tensor.SignedTensorProductsCategory method), 771
 base() (sage.categories.tensor.TensorProductsCategory method), 771

base_category() (*sage.categories.category_with_axiom.CategoryWithAxiom* (class in *sage.categories.bialgebras*), 188
method), 94
base_category() (*sage.categories.covariant_functorial_category.CovariantFunctorialCategory* (class in *sage.categories.bialgebras_with_basis*), 189
method), 767
base_category_class_and_axiom() (in module *BialgebrasWithBasis.ElementMethods* (class in *sage.categories.bialgebras_with_basis*), 189
sage.categories.category_with_axiom), 97
base_change_matrix() (*BialgebrasWithBasis.ParentMethods* (class in *sage.categories.bialgebras_with_basis*), 189
sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods), 191
method), 344
base_field() (*sage.categories.modular_abelian_varieties.ModularAbelianVarieties* (class in *sage.categories.bimodules*), 193
method), 579
base_field() (*sage.categories.vector_spaces.VectorSpaces* (class in *sage.categories.bimodules*), 193
method), 750
base_point() (*sage.categories.simplicial_sets.SimplicialSets* (class in *sage.categories.coxeter_groups.CoxeterGroups.ElementMethods*
method), 720
sage.categories.finite_posets.FinitePosets.ParentMethods)
base_point_map() (*sage.categories.simplicial_sets.SimplicialSets.ParentMethods* (class in *sage.categories.coxeter_groups.CoxeterGroups.ElementMethods*
method), 721
ParentMethods)
base_ring() (*sage.categories.algebra_functor.AlgebraFunctor* (class in *sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 778
method), 436
base_ring() (*sage.categories.cartesian_product.CartesianProduct* (class in *sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 770
method), 440
base_ring() (*sage.categories.category_types.Category_over_base_ring* (class in *sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 855
method), 440
base_ring() (*sage.categories.modules.Modules.Homsets* (class in *sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 583
method), 442
base_ring() (*sage.categories.modules.Modules.Homsets.ParentMethods* (class in *sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 582
method), 442
base_ring() (*sage.categories.modules.Modules.SubcategoryMethodMethods* (class in *sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 587
method), 444
base_scheme() (*sage.categories.schemes.Schemes_over_base* (class in *sage.categories.pushout*), 129
method), 672
base_set() (*sage.categories.examples.with_realizations.SubsetAlgebras* (class in *sage.categories.category_with_axiom*), 88
method), 851
base_space() (*sage.categories.vector_bundles.VectorBundles* (class in *sage.categories.category_with_axiom*), 89
method), 747
basis() (*sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebras* (class in *sage.categories.category_with_axiom*), 89
method), 805
basis() (*sage.categories.examples.graded_modules_with_basis.GradedPartitionModuleCategory* (class in *sage.categories.category_with_axiom*), 89
method), 819
basis() (*sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods* (class in *sage.categories.category_with_axiom*), 89
method), 331
basis() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods* (class in *sage.categories.category_with_axiom*), 89
method), 602
basis_matrix() (*sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebras* (class in *sage.categories.category_with_axiom*), 89
method), 806
basis_matrix() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.Subobjects* (class in *sage.categories.category_with_axiom*), 89
method), 404
bch() (*sage.categories.lie_algebras.LieAlgebras.ParentMethods* (class in *sage.categories.category_with_axiom*), 89
method), 523
bhz_poset() (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups* (class in *sage.categories.category_with_axiom*), 88
method), 358
Bialgebras (class in *sage.categories.bialgebras*), 187
Bialgebras.ElementMethods (class in *sage.categories.bialgebras*), 187
BlackBoxConstructionFunctor (class in *sage.categories.pushout*), 129
Blahs (class in *sage.categories.category_with_axiom*), 88
Blahs.Commutative (class in *sage.categories.category_with_axiom*), 89
Blahs.Connected (class in *sage.categories.category_with_axiom*), 89
Blahs.FiniteDimensional (class in *sage.categories.category_with_axiom*), 89
Blahs.Flying (class in *sage.categories.category_with_axiom*), 89
Blahs.ParentMethods (class in *sage.categories.category_with_axiom*), 89
Blahs.SubcategoryMethods (class in *sage.categories.category_with_axiom*), 89
Blahs.Unital (class in *sage.categories.category_with_axiom*), 89
Blahs.Unital.Blue (class in *sage.categories.category_with_axiom*), 89
Blue() (*sage.categories.category_with_axiom.Blahs.SubcategoryMethods* (class in *sage.categories.category_with_axiom*), 89
method), 88
Blue_extra_super_categories() (*sage.categories.category_with_axiom.Blahs.SubcategoryMethods* (class in *sage.categories.category_with_axiom*), 89
method), 88
bracket() (*sage.categories.lambda_bracket_algebras.LambdaBracketAlgebras* (class in *sage.categories.category_with_axiom*), 89
method), 514
bracket() (*sage.categories.lie_algebras.LieAlgebras.ElementMethods* (class in *sage.categories.category_with_axiom*), 89
method), 88

method), 692
 cartesian_product() (sage.categories.sets_cat.Sets.ParentMethods *method*), 695
 cartesian_projection() (sage.categories.sets_cat.Sets.CartesianProducts.ParentMethods *method*), 689
 cartesian_projection() (sage.categories.sets_cat.Sets.CartesianProducts.ParentMethods *method*), 690
 CartesianProduct (sage.categories.posets.Posets.ParentMethods *attribute*), 629
 CartesianProduct (sage.categories.sets_cat.Sets.ParentMethods *attribute*), 694
 CartesianProductFunctor (class in sage.categories.cartesian_product), 769
 CartesianProducts() (sage.categories.cartesian_product.CartesianProducts *method*), 770
 CartesianProducts() (sage.categories.sets_cat.Sets.SubcategoryMethods *method*), 698
 CartesianProductsCategory (class in sage.categories.cartesian_product), 770
 catalan_number() (sage.categories.finite_complex_reflection_groups.WellGenerated.Irreducible.ParabolicComplexReflectionGroups *method*), 349
 Category (class in sage.categories.category), 29
 category() (sage.categories.category.Category *method*), 49
 category() (sage.categories.morphism.Morphism *method*), 123
 Category_contains_method_by_parent_class (class in sage.categories.category_singleton), 856
 category_for() (sage.categories.map.Map *method*), 110
 category_from_categories() (sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction *method*), 766
 category_from_category() (sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction *method*), 766
 category_from_parents() (sage.categories.covariant_functorial_construction.CovariantFunctorialConstruction *method*), 767
 category_graph() (in module sage.categories.category), 63
 category_graph() (sage.categories.category.Category *method*), 49
 Category_ideal (class in sage.categories.category_types), 853
 Category_in_ambient (class in sage.categories.category_types), 853
 Category_module (class in sage.categories.category_types), 854
 category_of() (sage.categories.covariant_functorial_construction.FunctorialConstruction *class method*), 767
 Category_over_base (class in sage.categories.category_types), 854
 Category_over_base_ring (class in sage.categories.category_types), 854
 Category_realization_of_parent (class in sage.categories.realizations), 786
 category_sample() (in module sage.categories.category), 64
 Category_singleton (class in sage.categories.category_singleton), 856
 category_sort_key() (in module sage.categories.category_cy_helper), 860
 CategoryWithAxiom (class in sage.categories.category_with_axiom), 89
 CategoryWithAxiom_over_base_ring (class in sage.categories.category_with_axiom), 95
 CategoryWithAxiom_singleton (class in sage.categories.category_with_axiom), 95
 CategoryWithParameters (class in sage.categories.category), 60
 cayley_graph() (sage.categories.semigroups.Semigroups.ParentMethods *method*), 477
 cayley_graph_disabled() (sage.categories.finite_groups.FiniteGroups.ParentMethods *method*), 424
 cayley_table() (sage.categories.groups.Groups.ParentMethods *method*), 490
 cell_module() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 369
 cell_module_indices() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 369
 cell_module_indices() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 369
 cell_module_indices() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 369
 cell_poset() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 369
 cell_poset() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 370
 cells() (sage.categories.cw_complexes.CWComplexes.ParentMethods *method*), 764
 cells() (sage.categories.examples.cw_complexes.Surface *method*), 800
 cells() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 369
 Cellular() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 386
 cellular_basis() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 369
 cellular_involution() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis *method*), 369

method), 368
 cellular_involution() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods), 370
 cellular_involution() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods), 371
 center() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods), 375
 center() (sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods), 390
 center_basis() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods), 375
 center_basis() (sage.categories.group_algebras.GroupAlgebras.ParentMethods.TensorProducts.ParentMethods), 484
 central_form() (sage.categories.group_algebras.GroupAlgebras.ParentMethods.TensorProducts.ParentMethods), 483
 central_orthogonal_idempotents() (sage.categories.finite_dimensional_semisimple_algebras_with_basis.FiniteDimensionalSemisimpleAlgebrasWithBasis.CommunityMethods.TensorProducts.ParentMethods), 414
 central_orthogonal_idempotents() (sage.categories.finite_dimensional_semisimple_algebras_with_basis.FiniteDimensionalSemisimpleAlgebrasWithBasis.CommunityMethods.TensorProducts.ParentMethods), 415
 centralizer() (sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods), 390
 centralizer_basis() (sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods), 390
 character() (sage.categories.classical_crystals.ClassicalCrystals.ParentMethods.TensorProducts.ParentMethods), 195
 character() (sage.categories.supercrystals.SuperCrystals.FiniteParentMethods.TensorProducts.ParentMethods), 735
 character_value() (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ElementMethods.TensorProducts.ParentMethods), 339
 characteristic() (sage.categories.rings.Rings.ParentMethods.TensorProducts.ParentMethods), 665
 chevalley_eilenberg_complex() (sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods), 391
 classical_decomposition() (sage.categories.loop_crystals.KirillovReshetikhinCrystals.ParentMethods.TensorProducts.ParentMethods), 540
 classical_weight() (sage.categories.loop_crystals.RegularLoopCrystalsWithBasis.ParentMethods.TensorProducts.ParentMethods), 549
 ClassicalCrystals (class in sage.categories.classical_crystals), 194
 ClassicalCrystals.ElementMethods (class in sage.categories.classical_crystals), 194
 ClassicalCrystals.ParentMethods (class in sage.categories.classical_crystals), 195
 ClassicalCrystals.TensorProducts (class in sage.categories.classical_crystals), 197
 classically_highest_weight_vectors() (sage.categories.loop_crystals.KirillovReshetikhinCrystals.ParentMethods.TensorProducts.ParentMethods), 540
 classically_highest_weight_vectors() (sage.categories.loop_crystals.KirillovReshetikhinCrystals.ParentMethods.TensorProducts.ParentMethods), 546
 Coalgebras (class in sage.categories.coalgebras), 198
 Coalgebras.Cocommutative (class in sage.categories.coalgebras), 198
 Coalgebras.DualObjectAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods (class in sage.categories.coalgebras), 198
 Coalgebras.FiniteDimensionalAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods (class in sage.categories.coalgebras), 198
 Coalgebras.FiniteDimensionalAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods (class in sage.categories.coalgebras), 199
 Coalgebras.GroupAlgebras.ParentMethods.TensorProducts.ParentMethods (class in sage.categories.coalgebras), 199
 Coalgebras.Realizations (class in sage.categories.coalgebras), 200
 Coalgebras.Realizations.ParentMethods (class in sage.categories.coalgebras), 200
 Coalgebras.SemisimpleAlgebrasWithBasis.CommunityMethods.TensorProducts.ParentMethods (class in sage.categories.coalgebras), 201
 Coalgebras.SuperFiniteDimensionalSemisimpleAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods (class in sage.categories.coalgebras), 201
 Coalgebras.SuperFiniteDimensionalSemisimpleAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods (class in sage.categories.coalgebras), 201
 Coalgebras.SuperSubcategoryMethods (class in sage.categories.coalgebras), 201
 Coalgebras.SuperSupercocommutative (class in sage.categories.coalgebras), 202
 Coalgebras.TensorProducts (class in sage.categories.coalgebras), 202
 Coalgebras.TensorProducts.ElementMethods (class in sage.categories.coalgebras), 202
 Coalgebras.TensorProducts.ParentMethods (class in sage.categories.coalgebras), 202
 Coalgebras.WithRealizations (class in sage.categories.coalgebras), 202
 Coalgebras.WithRealizations.ParentMethods (class in sage.categories.coalgebras), 202
 Coalgebras.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods.TensorProducts.ParentMethods (class in sage.categories.coalgebras_with_basis), 203
 CoalgebrasWithBasis.ElementMethods (class in sage.categories.coalgebras_with_basis), 203
 CoalgebrasWithBasis.ParentMethods (class in sage.categories.coalgebras_with_basis), 204
 CoalgebrasWithBasis.Super (class in sage.categories.coalgebras_with_basis), 205
 Cocommutative() (sage.categories.coalgebras.Coalgebras.SubcategoryMethods.TensorProducts.ParentMethods), 201
 codegrees() (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ElementMethods.TensorProducts.ParentMethods), 339

codegrees() (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups* attribute), 110

codomain (*sage.categories.map.Map* attribute), 110

codomain() (*sage.categories.action.Action* method), 156

codomain() (*sage.categories.action.InverseAction* method), 157

codomain() (*sage.categories.action.PrecomposedAction* method), 158

codomain() (*sage.categories.functor.Functor* method), 101

codomain() (*sage.categories.homset.Homset* method), 119

codomain() (*sage.categories.poor_man_map.PoorManMap* method), 862

coefficient() (*sage.categories.modules_with_basis.ModulesWithBasis* method), 592

coefficients() (*sage.categories.modules_with_basis.ModulesWithBasis* method), 592

cohomology() (*sage.categories.finite_dimensional_lie_algebras.FiniteDimensionalLieAlgebras* method), 392

common_base() (*sage.categories.pushout.ConstructionFunctor* method), 133

common_base() (*sage.categories.pushout.MultivariateConstructionFunctor* method), 141

Commutative (*sage.categories.algebras.Algebras* attribute), 179

Commutative (*sage.categories.division_rings.DivisionRings* attribute), 299

Commutative (*sage.categories.domains.Domains* attribute), 300

Commutative (*sage.categories.rings.Rings* attribute), 661

Commutative() (*sage.categories.category_with_axiom.BladeCategory* method), 89

Commutative() (*sage.categories.magnas.Magnas.SubcategoryMethods* method), 559

Commutative_extra_super_categories() (*sage.categories.l_trivial_semigroups.LTrivialSemigroups* method), 550

Commutative_extra_super_categories() (*sage.categories.r_trivial_semigroups.RTrivialSemigroups* method), 671

CommutativeAdditiveGroups (class in *sage.categories.commutative_additive_groups*), 205

CommutativeAdditiveGroups.Algebras (class in *sage.categories.commutative_additive_groups*), 206

CommutativeAdditiveGroups.CartesianProducts (class in *sage.categories.commutative_additive_groups*), 206

CommutativeAdditiveGroups.CartesianProducts.ElementMethods (class in *sage.categories.commutative_additive_groups*), 206

CommutativeAdditiveMonoids (class in *sage.categories.commutative_additive_monoids*), 207

CommutativeAdditiveSemigroups (class in *sage.categories.commutative_additive_semigroups*), 207

CommutativeAlgebraIdeals (class in *sage.categories.commutative_algebra_ideals*), 208

CommutativeAlgebras (class in *sage.categories.commutative_algebras*), 208

CommutativeRingIdeals (class in *sage.categories.commutative_ring_ideals*), 209

CommutativeRings.ElementMethods (class in *sage.categories.commutative_rings*), 209

CommutativeRings.ElementMethodsAlgebrasWithBasis.ParentMethods (class in *sage.categories.commutative_rings*), 209

CommutativeRings.Finite (class in *sage.categories.commutative_rings*), 209

CommutativeRings.Finite.ParentMethods (class in *sage.categories.commutative_rings*), 210

CommutativeRings.ParentMethods (class in *sage.categories.commutative_rings*), 211

commutes() (*sage.categories.pushout.CompletionFunctor* method), 130

commutes() (*sage.categories.pushout.ConstructionFunctor* method), 133

Compact() (*sage.categories.topological_spaces.TopologicalSpaces.SubcategoryMethods* method), 740

ComplexManifolds (class in *sage.categories.manifolds*), 573

Complete() (*sage.categories.metric_spaces.MetricSpaces.SubcategoryMethods* method), 578

CompleteDiscreteValuationFields (class in *sage.categories.complete_discrete_valuation*), 213

CompleteDiscreteValuationFields.ElementMethods (class in *sage.categories.complete_discrete_valuation*), 214

CompleteDiscreteValuationRings (class in *sage.categories.complete_discrete_valuation*), 215

CompleteDiscreteValuationRings.ElementMethods (class in *sage.categories.complete_discrete_valuation*), 215

CompletionFunctor (class in *sage.categories.pushout*), 130

ComplexManifolds (class in *sage.categories.manifolds*), 573

570
 ComplexReflectionGroups (class in sage.categories.complex_reflection_groups), 217
 ComplexReflectionGroups.ParentMethods (class in sage.categories.complex_reflection_groups), 218
 ComplexReflectionOrGeneralizedCoxeterGroups (class in sage.categories.complex_reflection_or_generalized_coxeter_groups), 219
 ComplexReflectionOrGeneralizedCoxeterGroups.ElementMethods (class in sage.categories.complex_reflection_or_generalized_coxeter_groups), 220
 ComplexReflectionOrGeneralizedCoxeterGroups.IrreducibleElements (class in sage.categories.complex_reflection_or_generalized_coxeter_groups), 225
 ComplexReflectionOrGeneralizedCoxeterGroups.IrreducibleElementParentMethods (class in sage.categories.complex_reflection_or_generalized_coxeter_groups), 225
 ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods (class in sage.categories.complex_reflection_or_generalized_coxeter_groups), 226
 ComplexReflectionOrGeneralizedCoxeterGroups.SubcategoryMethods (class in sage.categories.complex_reflection_or_generalized_coxeter_groups), 236
 CompositeConstructionFunctor (class in sage.categories.pushout), 131
 conjugacy_class() (sage.categories.groups.Groups.ElementMethods), 489
 conjugacy_class() (sage.categories.groups.Groups.ParentMethods), 494
 conjugacy_classes() (sage.categories.finite_groups.FiniteGroups.ParentMethods), 424
 conjugacy_classes_representatives() (sage.categories.finite_groups.FiniteGroups.ParentMethods), 424
 Connected() (sage.categories.category_with_axiom.Blahs.SubcategoryMethods), 89
 Connected() (sage.categories.cw_complexes.CWComplexes.SubcategoryMethods), 295
 Connected() (sage.categories.filtered_modules.FilteredModules.SubcategoryMethods), 323
 Connected() (sage.categories.manifolds.Manifolds.SubcategoryMethods), 573
 Connected() (sage.categories.simplicial_complexes.SimplicialComplexes.SubcategoryMethods), 717
 Connected() (sage.categories.topological_spaces.TopologicalSpaces.SubcategoryMethods), 740
 connected_components() (sage.categories.crystals.Crystals.ParentMethods), 282
 connected_components() (sage.categories.supercrystals.SuperCrystals.Finite.ParentMethods), 735
 connected_components_generators() (sage.categories.crystals.Crystals.ParentMethods), 283
 connected_components_generators() (sage.categories.highest_weight_crystals.HighestWeightCrystals.ParentMethods), 499
 connected_components_generators() (sage.categories.supercrystals.SuperCrystals.Finite.ParentMethods), 735
 construction() (sage.categories.sets_cat.Sets.Algebras.ParentMethods), 688
 construction() (sage.categories.sets_cat.Sets.ParentMethods), 696
 construction() (sage.categories.pushout), 145
 ConstructionFunctor (class in sage.categories.pushout), 131
 convolution_product() (sage.categories.bialgebras_with_basis.BialgebrasWithBasis.ElementMethods), 90
 convolution_product() (sage.categories.bialgebras_with_basis.BialgebrasWithBasis.ParentMethods), 191
 coproduct() (sage.categories.coalgebras.Coalgebras.ElementMethods), 198
 coproduct() (sage.categories.coalgebras.Coalgebras.ParentMethods), 199
 coproduct() (sage.categories.coalgebras.Coalgebras.WithRealizations.ParentMethods), 202
 coproduct() (sage.categories.coalgebras_with_basis.CoalgebrasWithBasis.ParentMethods), 204
 coproduct_by_coercion() (sage.categories.coalgebras.Coalgebras.Realizations.ParentMethods), 200
 coproduct_on_basis() (sage.categories.coalgebras_with_basis.CoalgebrasWithBasis.ElementMethods), 203
 coproduct_on_basis() (sage.categories.algebra_functor.AlgebrasCategory.ParentMethods), 779
 coproduct_on_basis() (sage.categories.coalgebras_with_basis.CoalgebrasWithBasis.ParentMethods), 822
 coproduct_on_basis() (sage.categories.group_algebras.GroupAlgebras.ParentMethods), 822

method), 485
 coset_representative() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 246
 counit() (sage.categories.coalgebras.Coalgebras.ElementMethods method), 198
 counit() (sage.categories.coalgebras.Coalgebras.ParentMethods method), 199
 counit() (sage.categories.coalgebras.Coalgebras.WithRealizations.ParentMethods method), 202
 counit() (sage.categories.coalgebras_with_basis.CoalgebrasWithBasis.ParentMethods method), 204
 counit() (sage.categories.group_algebras.GroupAlgebras.ParentMethods method), 485
 counit_by_coercion() (sage.categories.coalgebras.Coalgebras.Realizations.ParentMethods method), 200
 counit_on_basis() (sage.categories.coalgebras_with_basis.CoalgebrasWithBasis.ParentMethods method), 205
 counit_on_basis() (sage.categories.examples.hopf_algebras.ExamplesHopfAlgebras.ParentMethods method), 822
 counit_on_basis() (sage.categories.graded_hopf_algebras.GradedHopfAlgebras.ParentMethods method), 475
 counit_on_basis() (sage.categories.group_algebras.GroupAlgebras.ParentMethods method), 485
 CovariantConstructionCategory (class in sage.categories.covariant_functorial_construction), 763
 CovariantFunctorialConstruction (class in sage.categories.covariant_functorial_construction), 765
 cover_reflections() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 247
 covered_reflections_subgroup() (sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods method), 356
 coxeter_diagram() (sage.categories.coxeter_groups.CoxeterGroups.ParentMethods method), 262
 coxeter_element() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 263
 coxeter_element() (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.WellGenerated.ParentMethods method), 352
 coxeter_elements() (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.WellGenerated.ParentMethods method), 353
 coxeter_knuth_graph() (sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods method), 356
 coxeter_knuth_neighbor() (sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods method), 357
 coxeter_matrix() (sage.categories.coxeter_groups.CoxeterGroups.ParentMethods method), 264
 coxeter_matrix() (sage.categories.examples.finite_coxeter_groups.ExamplesFiniteCoxeterGroups.ParentMethods method), 802
 coxeter_matrix() (sage.categories.weyl_groups.WeylGroups.ParentMethods method), 758
 coxeter_number() (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods method), 342
 coxeter_number() (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.WellGenerated.ParentMethods method), 350
 coxeter_sorting_word() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 247
 CoxeterGroupAlgebras (class in sage.categories.coxeter_group_algebras), 237
 CoxeterGroupAlgebras.ParentMethods (class in sage.categories.coxeter_group_algebras), 237
 CoxeterGroups (class in sage.categories.coxeter_groups), 240
 CoxeterGroups.ElementMethods (class in sage.categories.coxeter_groups), 241
 CoxeterGroups.ParentMethods (class in sage.categories.coxeter_groups), 241
 CoxeterGroupsWithBasis (class in sage.categories.coxeter_groups), 240
 CoxeterGroupsWithBasis.ParentMethods (class in sage.categories.coxeter_groups), 241
 CoxeterGroupsWithBasis.Connected.ParentMethods (class in sage.categories.coxeter_groups), 259
 CrystalHomset (class in sage.categories.crystals), 269
 CrystalMorphism (class in sage.categories.crystals), 272
 CrystalMorphismByGenerators (class in sage.categories.crystals), 273
 Crystals (class in sage.categories.crystals), 275
 Crystals.ElementMethods (class in sage.categories.crystals), 275
 Crystals.MorphismMethods (class in sage.categories.crystals), 281
 Crystals.ParentMethods (class in sage.categories.crystals), 282
 Crystals.Subalgebras (class in sage.categories.crystals), 292
 Crystals.RemoveProducts (class in sage.categories.crystals), 292
 CWComplexes (class in sage.categories.cw_complexes), 293
 CWComplexes.FiniteComplexReflectionGroups (class in sage.categories.cw_complexes), 294
 CWComplexes.FiniteComplexReflectionGroups.WellGenerated (class in sage.categories.cw_complexes), 294
 CWComplexes.FiniteComplexReflectionGroups.WellGenerated.ParentMethods (class in sage.categories.cw_complexes), 294
 CWComplexes.FiniteDimensional (class in sage.categories.cw_complexes), 294
 CWComplexes.ParentMethods (class in sage.categories.cw_complexes), 294

sage.categories.cw_complexes), 294
 CWComplexes.SubcategoryMethods (class in *sage.categories.cw_complexes*), 295
 Cycle (class in *sage.categories.examples.graphs*), 820
 Cycle.Element (class in *sage.categories.examples.graphs*), 820
 cycle_index() (*sage.categories.finite_permutation_groups.FinitePermutationGroups.FiniteMethods* method), 432
 cyclotomic_cosets() (*sage.categories.commutative_rings.CommutativeRings.FiniteMethods* method), 210

D

default_super_categories() (*sage.categories.covariant_functorial_construction.CovariantFunctorialConstructionCategory* class method), 764
 default_super_categories() (*sage.categories.covariant_functorial_construction.RegressiveCovariantConstructionCategory* class method), 768
 default_super_categories() (*sage.categories.graded_modules.GradedModulesCategory* class method), 478
 default_super_categories() (*sage.categories.homsets.HomsetsCategory* class method), 784
 default_super_categories() (*sage.categories.isomorphic_objects.IsomorphicObjectsCategory* class method), 781
 default_super_categories() (*sage.categories.metric_spaces.MetricSpacesCategory* class method), 578
 default_super_categories() (*sage.categories.quotients.QuotientsCategory* class method), 780
 default_super_categories() (*sage.categories.subobjects.SubobjectsCategory* class method), 781
 default_super_categories() (*sage.categories.super_modules.SuperModulesCategory* class method), 731
 degree() (*sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ElementMethods* method), 325
 degree_negation() (*sage.categories.graded_modules_with_basis.GradedModulesWithBasis.ElementMethods* method), 479
 degree_negation() (*sage.categories.graded_modules_with_basis.GradedModulesWithBasis.ParentMethods* method), 480
 degree_on_basis() (*sage.categories.examples.graded_connected_hopf_algebras_with_basis.GradedConnectedHopfAlgebrasWithBasis.ElementMethods* method), 817
 degree_on_basis() (*sage.categories.examples.graded_modules_with_basis.GradedModulesWithBasis.ElementMethods* method), 820
 degree_on_basis() (*sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ElementMethods* method), 326
 degree_on_basis() (*sage.categories.finite_dimensional_graded_lie_algebras_with_basis.FiniteDimensionalGradedLieAlgebrasWithBasis.ElementMethods* method), 388
 degree_on_basis() (*sage.categories.lambda_bracket_algebras_with_basis.LambdaBracketAlgebrasWithBasis.ElementMethods* method), 517
 degrees() (*sage.categories.examples.finite_coxeter_groups.DihedralGroups.ElementMethods* method), 802
 degrees() (*sage.categories.examples.finite_weyl_groups.SymmetricGroups.ElementMethods* method), 815
 degrees() (*sage.categories.finite_permutation_groups.FinitePermutationGroups.FiniteMethods* method), 346
 degrees() (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods* method), 196
 demazure_character() (*sage.categories.classical_crystals.ClassicalCrystals.ParentMethods* method), 196
 demazure_lusztig_eigenvectors() (*sage.categories.coxeter_group_algebras.CoxeterGroupAlgebras.ElementMethods* method), 237
 demazure_lusztig_operator_on_basis() (*sage.categories.coxeter_group_algebras.CoxeterGroupAlgebras.ElementMethods* method), 238
 demazure_lusztig_operators() (*sage.categories.coxeter_group_algebras.CoxeterGroupAlgebras.ElementMethods* method), 238
 demazure_operator() (*sage.categories.regular_crystals.RegularCrystals.ParentMethods* method), 655
 demazure_operator_simple() (*sage.categories.regular_crystals.RegularCrystals.ElementMethods* method), 651
 demazure_product() (*sage.categories.coxeter_groups.CoxeterGroups.ParentMethods* method), 264
 demazure_subcrystal() (*sage.categories.regular_crystals.RegularCrystals.ParentMethods* method), 656
 denominator() (*sage.categories.complete_discrete_valuation.CompleteDiscreteValuation.ElementMethods* method), 214
 denominator() (*sage.categories.complete_discrete_valuation.CompleteDiscreteValuation.ParentMethods* method), 215
 denominator() (*sage.categories.quotient_fields.QuotientFields.ElementMethods* method), 638
 dense_coefficient_list() (*sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis.ElementMethods* method), 405
 deodhar_factor_element() (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods* method), 248
 deodhar_lift_down() (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods* method), 248
 deodhar_lift_up() (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods* method), 249
 derivations_basis() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ElementMethods* method), 393
 derivations_basis() (*sage.categories.finite_dimensional_graded_lie_algebras_with_basis.FiniteDimensionalGradedLieAlgebrasWithBasis.ElementMethods* method), 393

(*sage.categories.magmatic_algebras.MagmaticAlgebras.WithBasis.FiniteDimensional.ParentMethods*
method), 568

directed_subset() (*sage.categories.posets.Posets.ParentMethods*
method), 629

derivative() (*sage.categories.quotient_fields.QuotientFields.ElementMethods*
method), 638

derived_series() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods*
method), 393

derived_subalgebra()
(*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods*
method), 394

descends() (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods*
method), 249

Differentiable() (*sage.categories.manifolds.Manifolds.DiscreteValuationRings.ElementMethods*
method), 573

Differentiable() (*sage.categories.vector_bundles.VectorBundles.DiscreteValuationRings.ElementMethods*
method), 746

digraph() (*sage.categories.crystals.Crystals.ParentMethods*
method), 286

digraph() (*sage.categories.highest_weight_crystals.HighestWeightCrystals.ParentMethods*
method), 499

digraph() (*sage.categories.loop_crystals.LoopCrystals.ParentMethods*
method), 548

digraph() (*sage.categories.supercrystals.SuperCrystals.ParentMethods*
method), 736

DihedralGroup (class in *sage.categories.examples.finite_coxeter_groups*),
801

DihedralGroup.Element (class in *sage.categories.examples.finite_coxeter_groups*),
801

dimension() (*sage.categories.cw_complexes.CWComplexes.ElementMethods*
method), 294

dimension() (*sage.categories.cw_complexes.CWComplexes.DistributiveMagmaAndAdditiveMagma.Attribute*), 566

dimension() (*sage.categories.cw_complexes.CWComplexes.DistributiveMagmaAndAdditiveMagma.Methods*
method), 295

dimension() (*sage.categories.examples.cw_complexes.SunFunctor*
method), 799

dimension() (*sage.categories.examples.graphs.Cycle.ElementMethods*
method), 820

dimension() (*sage.categories.examples.manifolds.Plane*
method), 829

dimension() (*sage.categories.graphs.Graphs.ParentMethods*
method), 481

dimension() (*sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis.ParentMethods*
method), 530

dimension() (*sage.categories.manifolds.Manifolds.ParentMethods*
method), 572

dimension() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods*
method), 603

dimension() (*sage.categories.simplicial_complexes.SimplicialComplexes.ParentMethods*
method), 716

dimension() (*sage.categories.vector_spaces.VectorSpaces.ParentMethods*
method), 748

direct_sum() (*sage.categories.crystals.Crystals.ParentMethods*
(class in *sage.categories.distributive_magmas_and_additive_magmas*),
method), 298

discrete_valuation_fields() (*sage.categories.discrete_valuation_fields.DiscreteValuationFields*
(class in *sage.categories.discrete_valuation_fields*),
296

discrete_valuation_rings() (*sage.categories.discrete_valuation_rings.DiscreteValuationRings*
(class in *sage.categories.discrete_valuation_rings*),
296

discrete_valuation_rings_element_methods() (*sage.categories.discrete_valuation_rings.DiscreteValuationRings.ElementMethods*
(class in *sage.categories.discrete_valuation_rings*),
297

discrete_valuation_rings_parent_methods() (*sage.categories.discrete_valuation_rings.DiscreteValuationRings.ParentMethods*
(class in *sage.categories.discrete_valuation_rings*),
297

dist() (*sage.categories.metric_spaces.MetricSpaces.WithRealizations.ParentMethods*
method), 578

distinguished_reflection()
(*sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods*
method), 226

distinguished_reflections()
(*sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods*
method), 226

distributive_magma_and_additive_magma_attribute() (*sage.categories.magmas_and_additive_magmas.MagmaAndAdditiveMagma.Attribute*), 566

distributive_magma_and_additive_magma_methods() (*sage.categories.magmas_and_additive_magmas.MagmaAndAdditiveMagma.Methods*
method), 559

distributive_magma_and_additive_magma_parent_methods() (*sage.categories.magmas_and_additive_magmas.MagmaAndAdditiveMagma.ParentMethods*
method), 566

DistributiveMagmaAndAdditiveMagma (class in *sage.categories.distributive_magmas_and_additive_magmas*),
298

DistributiveMagmaAndAdditiveMagma.AdditiveAssociative
(class in *sage.categories.distributive_magmas_and_additive_magmas*),
298

DistributiveMagmaAndAdditiveMagma.AdditiveAssociative.Attribute
(class in *sage.categories.distributive_magmas_and_additive_magmas*),
298

DistributiveMagmaAndAdditiveMagma.AdditiveAssociative.Methods
(class in *sage.categories.distributive_magmas_and_additive_magmas*),
298

DistributiveMagmaAndAdditiveMagma.AdditiveAssociative.ParentMethods
(class in *sage.categories.distributive_magmas_and_additive_magmas*),
298

DistributiveMagmaAndAdditiveMagma.CartesianProducts
(class in *sage.categories.distributive_magmas_and_additive_magmas*),
298

- 298
- DistributiveMagmasAndAdditiveMagmas.ParentMethods (class in *sage.categories.distributive_magmas_and_additive_magmas*), 299
- Division (*sage.categories.rings.Rings* attribute), 661
- Division() (*sage.categories.rings.Rings.SubcategoryMethods* method), 669
- DivisionRings (class in *sage.categories.division_rings*), 299
- DivisionRings.ElementMethods (class in *sage.categories.division_rings*), 299
- DivisionRings.ParentMethods (class in *sage.categories.division_rings*), 300
- domain (*sage.categories.map.Map* attribute), 110
- domain() (*sage.categories.action.Action* method), 156
- domain() (*sage.categories.action.PrecomposedAction* method), 158
- domain() (*sage.categories.functor.Functor* method), 101
- domain() (*sage.categories.homset.Homset* method), 119
- domain() (*sage.categories.poor_man_map.PoorManMap* method), 862
- Domains (class in *sage.categories.domains*), 300
- domains() (*sage.categories.map.FormalCompositeMap* method), 106
- domains() (*sage.categories.map.Map* method), 110
- Domains.ElementMethods (class in *sage.categories.domains*), 300
- Domains.ParentMethods (class in *sage.categories.domains*), 300
- dot_tex() (*sage.categories.crystals.Crystals.ParentMethods* method), 288
- dual() (*sage.categories.hopf_algebras.HopfAlgebras* method), 506
- dual() (*sage.categories.hopf_algebras.HopfAlgebras.Super* method), 505
- dual() (*sage.categories.modules.Modules.SubcategoryMethods* method), 588
- dual_equivalence_class() (*sage.categories.regular_crystals.RegularCrystals.ElementMethods* method), 651
- dual_equivalence_graph() (*sage.categories.regular_crystals.RegularCrystals.Elements* method), 656
- DualFunctor (class in *sage.categories.dual*), 773
- DualObjects() (*sage.categories.modules.Modules.SubcategoryMethods* method), 584
- DualObjectsCategory (class in *sage.categories.dual*), 773
- E**
- e() (*sage.categories.crystals.Crystals.ElementMethods* method), 276
- e() (*sage.categories.examples.crystals.HighestWeightCrystals* method), 798
- e() (*sage.categories.examples.crystals.NaiveCrystal.Element* method), 799
- e() (*sage.categories.quantum_group_representations.QuantumGroupRepresentations* method), 646
- e() (*sage.categories.triangular_kac_moody_algebras.TriangularKacMoodyAlgebras* method), 741
- e_on_basis() (*sage.categories.quantum_group_representations.QuantumGroupRepresentations* method), 648
- e_string() (*sage.categories.crystals.Crystals.ElementMethods* method), 277
- e_string_to_ground_state() (*sage.categories.loop_crystals.KirillovReshetikhinCrystals.Tensor* method), 544
- echelon_form() (*sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis* method), 410
- echelon_form() (*sage.categories.modules_with_basis.ModulesWithBasis* method), 603
- edges() (*sage.categories.examples.graphs.Cycle* method), 821
- edges() (*sage.categories.graphs.Graphs.ParentMethods* method), 481
- Element (*sage.categories.crystals.CrystalHomset* attribute), 272
- Element (*sage.categories.examples.infinite_enumerated_sets.NonNegativeIntegers* attribute), 824
- Element (*sage.categories.examples.manifolds.Plane* attribute), 829
- Element (*sage.categories.examples.semigroups_cython.LeftZeroSemigroup* attribute), 839
- Element (*sage.categories.highest_weight_crystals.HighestWeightCrystalHomset* attribute), 497
- element_class (*sage.categories.examples.sets_cat.PrimeNumbers* attribute), 841
- element_class (*sage.categories.examples.sets_cat.PrimeNumbers_Facade* attribute), 843
- element_class() (*sage.categories.category.Category* method), 50
- element_class_set_morphism() (*sage.categories.homset.Homset* method), 119
- Elements (class in *sage.categories.category_types*), 855
- ElementWrapper (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups* method), 342
- elements_of_length() (*sage.categories.coxeter_groups.CoxeterGroups.ParentMethods* method), 264
- ElementWrapper (*sage.categories.examples.sets_cat.PrimeNumbers_Wrap* attribute), 846
- EmptySetError, 686
- End() (in module *sage.categories.homset*), 115
- end() (in module *sage.categories.homset*), 121
- End() (*sage.categories.homsets.Homsets.SubcategoryMethods* method), 784

Endsets() (*sage.categories.objects.Objects.SubcategoryMethod* (in module *sage.categories.objects*), 624

Example (in module *sage.categories.examples.finite_dimensional_algebras*), 803

energy_function() (*sage.categories.loop_crystals.KirillovElementMethods* (in module *sage.categories.examples.finite_dimensional_lie_algebras*), 537

Example (in module *sage.categories.examples.finite_dimensional_lie_algebras*), 808

energy_function() (*sage.categories.loop_crystals.KirillovElementMethods* (in module *sage.categories.examples.finite_dimensional_lie_algebras*), 544

Example (in module *sage.categories.examples.finite_dimensional_lie_algebras*), 810

Enumerated (*sage.categories.sets_cat.Sets* attribute), 692

Example (in module *sage.categories.examples.finite_semigroups*), 812

Enumerated() (*sage.categories.sets_cat.Sets.SubcategoryMethod* (in module *sage.categories.examples.finite_weyl_groups*), 698

Example (in module *sage.categories.examples.finite_weyl_groups*), 814

EnumeratedSets (class in *sage.categories.enumerated_sets*), 301

Example (in module *sage.categories.examples.graded_connected_hopf_algebras*), 816

EnumeratedSets.CartesianProducts (class in *sage.categories.enumerated_sets*), 301

Example (in module *sage.categories.examples.graded_modules_with_basis*), 818

EnumeratedSets.CartesianProducts.ParentMethods (class in *sage.categories.enumerated_sets*), 301

Example (in module *sage.categories.examples.graphs*), 821

EnumeratedSets.ElementMethods (class in *sage.categories.enumerated_sets*), 302

Example (in module *sage.categories.examples.infinite_enumerated_sets*), 823

EnumeratedSets.ParentMethods (class in *sage.categories.enumerated_sets*), 302

Example (in module *sage.categories.examples.lie_algebras*), 824

Epsilon() (*sage.categories.crystals.Crystals.ElementMethods* (in module *sage.categories.examples.lie_algebras_with_basis*), 275

Example (in module *sage.categories.examples.lie_algebras_with_basis*), 826

epsilon() (*sage.categories.crystals.Crystals.ElementMethods* (in module *sage.categories.examples.magnas*), 277

Example (in module *sage.categories.examples.magnas*), 827

epsilon() (*sage.categories.regular_crystals.RegularCrystals.ElementMethods* (in module *sage.categories.examples.manifolds*), 652

Example (in module *sage.categories.examples.manifolds*), 828

epsilon() (*sage.categories.regular_supercrystals.RegularSuperCrystals.ElementMethods* (in module *sage.categories.examples.monoids*), 659

Example (in module *sage.categories.examples.monoids*), 829

euclidean_degree() (*sage.categories.discrete_valuation.DiscreteValuationElementMethods* (in module *sage.categories.examples.sets_with_grading*), 297

Example (in module *sage.categories.examples.sets_with_grading*), 846

euclidean_degree() (*sage.categories.euclidean_domains.EuclideanDomainsElementMethods* (in module *sage.categories.examples.sets_with_grading*), 307

Example (in module *sage.categories.examples.sets_with_grading*), 846

euclidean_degree() (*sage.categories.euclidean_domains.EuclideanDomainsElementMethods* (in module *sage.categories.examples.sets_with_grading*), 307

Example (in module *sage.categories.examples.sets_with_grading*), 846

euclidean_degree() (*sage.categories.fields.Fields.ElementMethods* (in module *sage.categories.examples.sets_with_grading*), 309

Example (in module *sage.categories.examples.sets_with_grading*), 846

EuclideanDomains (class in *sage.categories.euclidean_domains*), 307

Example (in module *sage.categories.examples.sets_with_grading*), 846

EuclideanDomains.ElementMethods (class in *sage.categories.euclidean_domains*), 307

Example (in module *sage.categories.examples.sets_with_grading*), 846

EuclideanDomains.ParentMethods (class in *sage.categories.euclidean_domains*), 308

Example (in module *sage.categories.examples.sets_with_grading*), 846

even_component() (*sage.categories.super_modules_with_basis.SuperModulesWithBasisElementMethods* (in module *sage.categories.examples.sets_with_grading*), 732

Example (in module *sage.categories.examples.sets_with_grading*), 846

Example (class in *sage.categories.examples.finite_enumerated_sets*), 808

Example (in module *sage.categories.examples.finite_enumerated_sets*), 808

Example (in module *sage.categories.examples.algebras_with_basis*), 793

Example (in module *sage.categories.examples.algebras_with_basis*), 793

Example (in module *sage.categories.examples.commutative_algebras*), 794

Example (in module *sage.categories.examples.commutative_algebras*), 794

Example (in module *sage.categories.examples.commutative_algebras*), 795

Example (in module *sage.categories.examples.commutative_algebras*), 795

Example (in module *sage.categories.examples.cw_complexes*), 799

Example (in module *sage.categories.examples.cw_complexes*), 799

Example (in module *sage.categories.examples.finite_coxeter_groups*), 803

Example (in module *sage.categories.examples.finite_coxeter_groups*), 803

`example()` (`sage.categories.finite_enumerated_sets.FiniteEnumeratedSets` `expand()` (`sage.categories.lie_algebras.LieAlgebras.ElementMethods` `method`), 419 `method`), 520
`example()` (`sage.categories.finite_groups.FiniteGroups` `expand()` (`sage.categories.pushout.AlgebraicExtensionFunctor` `method`), 425 `method`), 127
`example()` (`sage.categories.finite_permutation_groups.FinitePermutationGroups` `expand()` (`sage.categories.pushout.CompositeConstructionFunctor` `method`), 435 `method`), 131
`example()` (`sage.categories.finitely_generated_semigroups.FinitelyGeneratedSemigroups` `expand()` (`sage.categories.pushout.ConstructionFunctor` `method`), 466 `method`), 134
`example()` (`sage.categories.graded_hopf_algebras_with_basis.GradedHopfAlgebrasWithBasis` `expand()` (`sage.categories.pushout.InfinitePolynomialFunctor` `method`), 475 `method`), 137
`example()` (`sage.categories.graded_hopf_algebras_with_basis.GradedHopfAlgebrasWithBasis` `expand()` (`sage.categories.pushout.MultiPolynomialFunctor` `method`), 475 `method`), 140
`example()` (`sage.categories.group_algebras.GroupAlgebras` `expand_tower()` (`in module sage.categories.pushout`), `method`), 486 146
`example()` (`sage.categories.groups.Groups` `method`), `extend_codomain()` (`sage.categories.map.Map` `method`), 495 `method`), 110
`example()` (`sage.categories.highest_weight_crystals.HighestWeightCrystals` `extend_codomain()` (`sage.categories.map.Map` `method`), `method`), 503 111
`example()` (`sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis` `extend_codomain()` (`sage.categories.map.Map` `method`), `method`), 509 `method`), 111
`example()` (`sage.categories.kac_moody_algebras.KacMoodyAlgebras` `extend_codomain()` (`sage.categories.map.Map` `method`), `method`), 513 `method`), 663
`example()` (`sage.categories.lie_algebras.LieAlgebras` `extra_super_categories()` (`sage.categories.additive_groups.AdditiveGroups.Finite.Algebras` `method`), 528 `method`), 159
`example()` (`sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveCom` `method`), 531 `method`), 160
`example()` (`sage.categories.lie_conformal_algebras.LieConformalAlgebras` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveCom` `method`), 534 `method`), 161
`example()` (`sage.categories.loop_crystals.LoopCrystals` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveCom` `method`), 549 `method`), 161
`example()` (`sage.categories.magmas.Magmas.CartesianProducts` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveUnit` `method`), 552 `method`), 161
`example()` (`sage.categories.posets.Posets` `method`), 637 `method`), 161
`example()` (`sage.categories.quantum_group_representations.QuantumGroupRepresentations` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveUnit` `method`), 650 `method`), 162
`example()` (`sage.categories.regular_crystals.RegularCrystals` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveUnit` `method`), 658 `method`), 162
`example()` (`sage.categories.semigroups.Semigroups` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveUnit` `method`), 683 `method`), 162
`example()` (`sage.categories.semigroups.Semigroups.Quotients` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveUnit` `method`), 680 `method`), 163
`example()` (`sage.categories.semigroups.Semigroups.Subquotients` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.AdditiveUnit` `method`), 683 `method`), 163
`example()` (`sage.categories.sets_cat.Sets` `method`), 711 `method`), 165
`example()` (`sage.categories.sets_cat.Sets.CartesianProducts` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.Algebras` `method`), 692 `method`), 165
`example()` (`sage.categories.sets_cat.Sets.WithRealizations` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.CartesianPro` `method`), 711 `method`), 166
`example()` (`sage.categories.super_lie_conformal_algebras.SuperLieConformalAlgebras` `extra_super_categories()` (`sage.categories.additive_magmas.AdditiveMagmas.Homsets` `method`), 728 `method`), 166
`example()` (`sage.categories.vector_spaces.VectorSpaces.WithBasis.Finite` `extra_super_categories()` (`sage.categories.additive_monoids.AdditiveMonoids.Homsets` `method`), 749 `method`), 171
`example()` (`sage.categories.vector_spaces.VectorSpaces.WithBasis.Graded` `extra_super_categories()` (`sage.categories.additive_monoids.AdditiveMonoids.Homsets` `method`), 749 `method`), 171

`extra_super_categories()` (*sage.categories.additive_semigroups.AdditiveSemigroups.Algebras* method), 173
`extra_super_categories()` (*sage.categories.additive_semigroups.AdditiveSemigroups.CartesianProducts* method), 173
`extra_super_categories()` (*sage.categories.additive_semigroups.AdditiveSemigroups.Homomorphisms* method), 174
`extra_super_categories()` (*sage.categories.algebras.Algebras.CartesianProducts* method), 179
`extra_super_categories()` (*sage.categories.algebras.Algebras.DualObjects* method), 179
`extra_super_categories()` (*sage.categories.algebras.Algebras.TensorProducts* method), 181
`extra_super_categories()` (*sage.categories.algebras_with_basis.AlgebrasWithBasis.CartesianProducts* method), 184
`extra_super_categories()` (*sage.categories.algebras_with_basis.AlgebrasWithBasis.TensorProducts* method), 186
`extra_super_categories()` (*sage.categories.aperiodic_semigroups.AperiodicSemigroups* method), 187
`extra_super_categories()` (*sage.categories.category_with_axiom.Blahs.Flying* method), 89
`extra_super_categories()` (*sage.categories.category_with_axiom.CategoryWithAxiom* method), 94
`extra_super_categories()` (*sage.categories.classical_crystals.ClassicalCrystals.TensorProducts* method), 197
`extra_super_categories()` (*sage.categories.coalgebras.Coalgebras.DualObjects* method), 198
`extra_super_categories()` (*sage.categories.coalgebras.Coalgebras.Super* method), 201
`extra_super_categories()` (*sage.categories.coalgebras.Coalgebras.TensorProducts* method), 202
`extra_super_categories()` (*sage.categories.coalgebras_with_basis.CoalgebrasWithBasis.Super* method), 205
`extra_super_categories()` (*sage.categories.commutative_rings.CommutativeRings.CartesianProducts* method), 209
`extra_super_categories()` (*sage.categories.covariant_functorial_construction.FunctorialConstruction* method), 768
`extra_super_categories()` (*sage.categories.crystals.Crystals.TensorProducts* method), 292
`extra_super_categories()` (*sage.categories.cw_complexes.CWComplexes.Finite* method), 294
`extra_super_categories()` (*sage.categories.distributive_magmas_and_additive_magmas.DistributiveMagmasAndAdditiveMagmas* method), 298
`extra_super_categories()` (*sage.categories.division_rings.DivisionRings* method), 300
`extra_super_categories()` (*sage.categories.fields.Fields* method), 314
`extra_super_categories()` (*sage.categories.filtered_modules.FilteredModules* method), 323
`extra_super_categories()` (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups* method), 366
`extra_super_categories()` (*sage.categories.finite_crystals.FiniteCrystals* method), 367
`extra_super_categories()` (*sage.categories.finite_crystals.FiniteCrystals.TensorProducts* method), 367
`extra_super_categories()` (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis* method), 371
`extra_super_categories()` (*sage.categories.finite_enumerated_sets.FiniteEnumeratedSets* method), 419
`extra_super_categories()` (*sage.categories.finite_fields.FiniteFields* method), 422
`extra_super_categories()` (*sage.categories.finite_groups.FiniteGroups.Algebras* method), 423
`extra_super_categories()` (*sage.categories.finite_permutation_groups.FinitePermutationGroups* method), 435
`extra_super_categories()` (*sage.categories.finite_sets.FiniteSets.Algebras* method), 459
`extra_super_categories()` (*sage.categories.finite_sets.FiniteSets.Subquotients* method), 460
`extra_super_categories()` (*sage.categories.finitely_generated_semigroups.FinitelyGeneratedSemigroups* method), 460
`extra_super_categories()` (*sage.categories.generalized_coxeter_groups.GeneralizedCoxeterGroups* method), 460
`extra_super_categories()` (*sage.categories.generalized_coxeter_groups.GeneralizedCoxeterGroups* method), 460

(*sage.categories.graded_algebras.GradedAlgebras.SignedTensorProducts* method), 469

(*sage.categories.magnas.Magnas.CartesianProducts* method), 553

extra_super_categories() (*sage.categories.graded_algebras_with_basis.GradedAlgebrasWithBasis.SignedTensorProducts* method), 471

extra_super_categories() (*sage.categories.magnas.Magnas.Commutative.Algebras* method), 553

extra_super_categories() (*sage.categories.graded_coalgebras.GradedCoalgebras.SignedTensorProducts* method), 472

extra_super_categories() (*sage.categories.magnas.Magnas.Commutative.CartesianProducts* method), 553

extra_super_categories() (*sage.categories.graded_coalgebras_with_basis.GradedCoalgebrasWithBasis.SignedTensorProducts* method), 473

extra_super_categories() (*sage.categories.magnas.Magnas.Unital.Algebras* method), 562

extra_super_categories() (*sage.categories.graded_lie_algebras.GradedLieAlgebras.StratifiedFiniteDimensionalMagnas.Unital.CartesianProducts* method), 476

extra_super_categories() (*sage.categories.magnas.Magnas.Unital.Inverse.CartesianProducts* method), 563

extra_super_categories() (*sage.categories.graphs.Graphs.Connected* method), 481

extra_super_categories() (*sage.categories.magnas_and_additive_magnas.MagnasAndAdditiveMagnas* method), 566

extra_super_categories() (*sage.categories.group_algebras.GroupAlgebras* method), 486

extra_super_categories() (*sage.categories.manifolds.Manifolds.AlmostComplex* method), 571

extra_super_categories() (*sage.categories.groups.Groups.CartesianProducts* method), 488

extra_super_categories() (*sage.categories.manifolds.Manifolds.Analytic* method), 571

extra_super_categories() (*sage.categories.hecke_modules.HeckeModules.Homsets* method), 496

extra_super_categories() (*sage.categories.manifolds.Manifolds.Smooth* method), 572

extra_super_categories() (*sage.categories.highest_weight_crystals.HighestWeightCrystals.TensorProducts* method), 503

extra_super_categories() (*sage.categories.metric_spaces.MetricSpaces.CartesianProducts* method), 576

extra_super_categories() (*sage.categories.homsets.Homsets.Endset* method), 783

extra_super_categories() (*sage.categories.metric_spaces.MetricSpaces.Complete.CartesianProducts* method), 576

extra_super_categories() (*sage.categories.hopf_algebras.HopfAlgebras.TensorProducts* method), 506

extra_super_categories() (*sage.categories.manifolds.Manifolds.Riemannian* method), 579

extra_super_categories() (*sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis.TensorProducts* method), 509

extra_super_categories() (*sage.categories.modular_abelian_varieties.ModularAbelianVarieties* method), 579

extra_super_categories() (*sage.categories.j_trivial_semigroups.JTrivialSemigroups* method), 512

extra_super_categories() (*sage.categories.modules.Modules.CartesianProducts* method), 581

extra_super_categories() (*sage.categories.l_trivial_semigroups.LTrivialSemigroups* method), 550

extra_super_categories() (*sage.categories.modules.Modules.FiniteDimensional* method), 581

extra_super_categories() (*sage.categories.lie_algebras.LieAlgebras.FiniteDimensional* method), 521

extra_super_categories() (*sage.categories.modules.Modules.Homsets* method), 583

extra_super_categories() (*sage.categories.kirillov_reshetikhin_crystals.KirillovReshetikhinCrystals.TensorProducts* method), 547

extra_super_categories() (*sage.categories.modules.Modules.Homsets.Endset* method), 582

extra_super_categories() (*sage.categories.magnas.Magnas.Algebras* method), 551

extra_super_categories() (*sage.categories.modules.Modules.TensorProducts* method), 589

extra_super_categories() (*sage.categories.modules.Modules.TensorProducts* method), 589

extra_super_categories() (*sage.categories.modules.Modules.TensorProducts* method), 589

(*sage.categories.modules_with_basis.ModulesWithBasis.CartesianProducts*.*super_algebras_with_basis.SuperAlgebrasWithBasis*.*method*), 591

extra_super_categories() (*sage.categories.modules_with_basis.ModulesWithBasis.DualObjects*.*super_lie_conformal_algebras.SuperLieConformalAlgebras*.*method*), 591

extra_super_categories() (*sage.categories.modules_with_basis.ModulesWithBasis.TensorProducts*.*super_modules.SuperModules*.*method*), 615

extra_super_categories() (*sage.categories.monoids.Monoids.Algebras*.*method*), 618

extra_super_categories() (*sage.categories.monoids.Monoids.CartesianProducts*.*method*), 619

extra_super_categories() (*sage.categories.quantum_group_representations.QuantumGroupRepresentations*.*topological_spaces.TopologicalSpaces*.*CartesianProducts*.*method*), 645

extra_super_categories() (*sage.categories.quantum_group_representations.QuantumGroupRepresentations*.*topological_spaces.TopologicalSpaces*.*Compact*.*method*), 650

extra_super_categories() (*sage.categories.r_trivial_semigroups.RTrivialSemigroups*.*method*), 671

extra_super_categories() (*sage.categories.regular_crystals.RegularCrystals.TensorProducts*.*method*), 657

extra_super_categories() (*sage.categories.regular_supercrystals.RegularSuperCrystals.TensorProducts*.*method*), 659

extra_super_categories() (*sage.categories.semigroups.Semigroups.Algebras*.*method*), 674

extra_super_categories() (*sage.categories.semigroups.Semigroups.CartesianProducts*.*method*), 675

extra_super_categories() (*sage.categories.sets_cat.Sets.Algebras*.*method*), 688

extra_super_categories() (*sage.categories.sets_cat.Sets.CartesianProducts*.*method*), 692

extra_super_categories() (*sage.categories.sets_cat.Sets.WithRealizations*.*method*), 711

extra_super_categories() (*sage.categories.super_algebras.SuperAlgebras*.*method*), 725

extra_super_categories() (*sage.categories.super_algebras.SuperAlgebras*.*SignsTensorProducts*.*method*), 725

extra_super_categories() (*sage.categories.super_algebras_with_basis.SuperAlgebrasWithBasis*.*method*), 726

extra_super_categories()

(*sage.categories.super_algebras_with_basis.SuperAlgebrasWithBasis*.*method*), 726

extra_super_categories() (*sage.categories.super_lie_conformal_algebras.SuperLieConformalAlgebras*.*method*), 728

extra_super_categories() (*sage.categories.super_modules.SuperModules*.*method*), 730

extra_super_categories() (*sage.categories.supercommutative_algebras.SupercommutativeAlgebras*.*method*), 733

extra_super_categories() (*sage.categories.supercrystals.SuperCrystals.TensorProducts*.*method*), 738

extra_super_categories() (*sage.categories.supercrystals.SuperCrystals.TensorProducts*.*method*), 739

extra_super_categories() (*sage.categories.supercrystals.SuperCrystals.TensorProducts*.*method*), 739

extra_super_categories() (*sage.categories.topological_spaces.TopologicalSpaces*.*Connectivity*.*method*), 740

extra_super_categories() (*sage.categories.vector_spaces.VectorSpaces.CartesianProducts*.*method*), 747

extra_super_categories() (*sage.categories.vector_spaces.VectorSpaces.DualObjects*.*method*), 748

extra_super_categories() (*sage.categories.vector_spaces.VectorSpaces.TensorProducts*.*method*), 748

extra_super_categories() (*sage.categories.vector_spaces.VectorSpaces.WithBasis.CartesianProducts*.*method*), 749

extra_super_categories() (*sage.categories.vector_spaces.VectorSpaces.WithBasis.TensorProducts*.*method*), 749

F

F (*sage.categories.examples.with_realizations.SubsetAlgebra*.*attribute*), 850

f() (*sage.categories.crystals.Crystals.ElementMethods*.*method*), 277

f() (*sage.categories.examples.crystals.HighestWeightCrystalOfTypeA.ElementMethods*.*method*), 798

f() (*sage.categories.examples.crystals.NaiveCrystal.ElementMethods*.*method*), 799

f() (*sage.categories.quantum_group_representations.QuantumGroupRepresentations*.*method*), 646

f() (*sage.categories.triangular_kac_moody_algebras.TriangularKacMoodyAlgebras*.*method*), 741

f_on_basis() (*sage.categories.quantum_group_representations.QuantumGroupRepresentations*.*method*), 649

f_string() (*sage.categories.crystals.Crystals.ElementMethods* method), 277
FilteredAlgebras (class in *sage.categories.filtered_algebras*), 314
FilteredAlgebras.ParentMethods (class in *sage.categories.filtered_algebras*), 314
FilteredAlgebrasWithBasis (class in *sage.categories.filtered_algebras_with_basis*), 315
FilteredAlgebrasWithBasis.ElementMethods (class in *sage.categories.filtered_algebras_with_basis*), 315
FilteredAlgebrasWithBasis.ParentMethods (class in *sage.categories.filtered_algebras_with_basis*), 315
FilteredModules (class in *sage.categories.filtered_modules*), 323
FilteredModules.Connected (class in *sage.categories.filtered_modules*), 323
FilteredModules.SubcategoryMethods (class in *sage.categories.filtered_modules*), 323
FilteredModulesCategory (class in *sage.categories.filtered_modules*), 324
FilteredModulesWithBasis (class in *sage.categories.filtered_modules_with_basis*), 324
FilteredModulesWithBasis.ElementMethods (class in *sage.categories.filtered_modules_with_basis*), 325
FilteredModulesWithBasis.ParentMethods (class in *sage.categories.filtered_modules_with_basis*), 325
Finite (*sage.categories.complex_reflection_groups.ComplexReflectionGroups* attribute), 218
Finite (*sage.categories.coxeter_groups.CoxeterGroups* attribute), 259
Finite (*sage.categories.crystals.Crystals* attribute), 281
Finite (*sage.categories.enumerated_sets.EnumeratedSets* attribute), 302
Finite (*sage.categories.fields.Fields* attribute), 312
Finite (*sage.categories.groups.Groups* attribute), 490
Finite (*sage.categories.lattice_posets.LatticePosets* attribute), 517
Finite (*sage.categories.monoids.Monoids* attribute), 620
Finite (*sage.categories.permutation_groups.PermutationGroups* attribute), 627
Finite (*sage.categories.posets.Posets* attribute), 629
Finite (*sage.categories.semigroups.Semigroups* attribute), 675
Finite (*sage.categories.sets_cat.Sets* attribute), 692
Finite (*sage.categories.weyl_groups.WeylGroups* attribute), 758
Finite() (*sage.categories.sets_cat.Sets.SubcategoryMethods* method), 701
Finite_extra_super_categories() (*sage.categories.division_rings.DivisionRings* method), 299
Finite_extra_super_categories() (*sage.categories.h_trivial_semigroups.HTrivialSemigroups* method), 510
FiniteComplexReflectionGroups (class in *sage.categories.finite_complex_reflection_groups*), 338
FiniteComplexReflectionGroups.ElementMethods (class in *sage.categories.finite_complex_reflection_groups*), 339

FiniteComplexReflectionGroups.Irreducible (class in *sage.categories.finite_complex_reflection_groups*), 340
 FiniteComplexReflectionGroups.Irreducible.ParentMethods (class in *sage.categories.finite_complex_reflection_groups*), 340
 FiniteComplexReflectionGroups.ParentMethods (class in *sage.categories.finite_complex_reflection_groups*), 344
 FiniteComplexReflectionGroups.SubcategoryMethods (class in *sage.categories.finite_complex_reflection_groups*), 348
 FiniteComplexReflectionGroups.WellGenerated (class in *sage.categories.finite_complex_reflection_groups*), 349
 FiniteComplexReflectionGroups.WellGenerated.Irreducible (class in *sage.categories.finite_complex_reflection_groups*), 349
 FiniteComplexReflectionGroups.WellGenerated.Irreducible.ParentMethods (class in *sage.categories.finite_complex_reflection_groups*), 349
 FiniteComplexReflectionGroups.WellGenerated.ParentMethods (class in *sage.categories.finite_complex_reflection_groups*), 352
 FiniteCoxeterGroups (class in *sage.categories.finite_coxeter_groups*), 355
 FiniteCoxeterGroups.ElementMethods (class in *sage.categories.finite_coxeter_groups*), 355
 FiniteCoxeterGroups.ParentMethods (class in *sage.categories.finite_coxeter_groups*), 357
 FiniteCrystals (class in *sage.categories.finite_crystals*), 367
 FiniteCrystals.TensorProducts (class in *sage.categories.finite_crystals*), 367
 FiniteDimensional (*sage.categories.algebras_with_basis.AlgebrasWithBasis* attribute), 184
 FiniteDimensional (*sage.categories.graded_lie_algebras.FiniteDimensionalGradedLieAlgebrasWithBasis* attribute), 477
 FiniteDimensional (*sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis* attribute), 508
 FiniteDimensional (*sage.categories.modules_with_basis.ModulesWithBasis* attribute), 601
 FiniteDimensional() (*sage.categories.category_with_axiom.Blahs.SubcategoryMethods* method), 89
 FiniteDimensional() (*sage.categories.cw_complexes.CWComplexes.SubcategoryMethods* method), 295
 FiniteDimensional() (*sage.categories.manifolds.Manifolds.SubcategoryMethods* method), 573
 FiniteDimensional() (*sage.categories.modules.Modules.SubcategoryMethods* method), 586
 FiniteDimensionalAlgebrasWithBasis (class in *sage.categories.finite_dimensional_algebras_with_basis*), 367
 FiniteDimensionalAlgebrasWithBasis.Cellular (class in *sage.categories.finite_dimensional_algebras_with_basis*), 368
 FiniteDimensionalAlgebrasWithBasis.Cellular.ElementMethods (class in *sage.categories.finite_dimensional_algebras_with_basis*), 368
 FiniteDimensionalAlgebrasWithBasis.Cellular.ParentMethods (class in *sage.categories.finite_dimensional_algebras_with_basis*), 369
 FiniteDimensionalAlgebrasWithBasis.Cellular.TensorProducts (class in *sage.categories.finite_dimensional_algebras_with_basis*), 370
 FiniteDimensionalAlgebrasWithBasis.Cellular.TensorProducts.Irreducible (class in *sage.categories.finite_dimensional_algebras_with_basis*), 370
 FiniteDimensionalAlgebrasWithBasis.Cellular.TensorProducts.Irreducible.ParentMethods (class in *sage.categories.finite_dimensional_algebras_with_basis*), 372
 FiniteDimensionalAlgebrasWithBasis.ParentMethods (class in *sage.categories.finite_dimensional_algebras_with_basis*), 373
 FiniteDimensionalAlgebrasWithBasis.SubcategoryMethods (class in *sage.categories.finite_dimensional_algebras_with_basis*), 386
 FiniteDimensionalBialgebrasWithBasis() (in *module sage.categories.finite_dimensional_bialgebras_with_basis*), 386
 FiniteDimensionalCoalgebrasWithBasis() (in *module sage.categories.finite_dimensional_coalgebras_with_basis*), 386
 FiniteDimensionalGradedLieAlgebrasWithBasis (class in *sage.categories.finite_dimensional_graded_lie_algebras*), 387
 FiniteDimensionalGradedLieAlgebrasWithBasis.ParentMethods (class in *sage.categories.finite_dimensional_graded_lie_algebras*), 387
 FiniteDimensionalGradedLieAlgebrasWithBasis.Stratified (class in *sage.categories.finite_dimensional_graded_lie_algebras*), 388
 FiniteDimensionalGradedLieAlgebrasWithBasis.Stratified.ParentMethods (class in *sage.categories.finite_dimensional_graded_lie_algebras*), 388
 FiniteDimensionalHopfAlgebrasWithBasis (class in *sage.categories.finite_dimensional_hopf_algebras_with_basis*), 388
 FiniteDimensionalHopfAlgebrasWithBasis.ElementMethods (class in *sage.categories.finite_dimensional_hopf_algebras_with_basis*), 388
 FiniteDimensionalHopfAlgebrasWithBasis.ParentMethods (class in *sage.categories.finite_dimensional_hopf_algebras_with_basis*), 388

FiniteDimensionalLieAlgebrasWithBasis (class in *sage.categories.finite_enumerated_sets*), 419
sage.categories.finite_dimensional_lie_algebras_with_basis. **FiniteEnumeratedSets.IsomorphicObjects.ParentMethods**
 389 (class in *sage.categories.finite_enumerated_sets*),
FiniteDimensionalLieAlgebrasWithBasis.ElementMethods 419
 (class in *sage.categories.finite_dimensional_lie_algebras_with_basis*). **FiniteEnumeratedSets.ParentMethods** (class in
 389 *sage.categories.finite_enumerated_sets*), 420
FiniteDimensionalLieAlgebrasWithBasis.ParentMethods **FiniteFields** (class in *sage.categories.finite_fields*),
 (class in *sage.categories.finite_dimensional_lie_algebras_with_basis*),
 389 **FiniteFields.ElementMethods** (class in
FiniteDimensionalLieAlgebrasWithBasis.Subobjects *sage.categories.finite_fields*), 422
 (class in *sage.categories.finite_dimensional_lie_algebras_with_basis*). **FiniteFields.ParentMethods** (class in
 404 *sage.categories.finite_fields*), 422
FiniteDimensionalLieAlgebrasWithBasis.SubobjectIsomorphismMethods (class in *sage.categories.finite_groups*),
 (class in *sage.categories.finite_dimensional_lie_algebras_with_basis*),
 404 **FiniteGroups.Algebras** (class in
FiniteDimensionalModulesWithBasis (class in *sage.categories.finite_groups*), 423
sage.categories.finite_dimensional_modules_with_basis. **FiniteGroups.Algebras.ParentMethods** (class in
 405 *sage.categories.finite_groups*), 423
FiniteDimensionalModulesWithBasis.ElementMethods **FiniteGroups.ElementMethods** (class in
 (class in *sage.categories.finite_dimensional_modules_with_basis*), *sage.categories.finite_groups*), 423
 405 **FiniteGroups.ParentMethods** (class in
FiniteDimensionalModulesWithBasis.MorphismMethods *sage.categories.finite_groups*), 423
 (class in *sage.categories.finite_dimensional_modules_with_basis*). **FiniteLatticePosets** (class in
 405 *sage.categories.finite_lattice_posets*), 425
FiniteDimensionalModulesWithBasis.ParentMethods **FiniteLatticePosets.ParentMethods** (class in
 (class in *sage.categories.finite_dimensional_modules_with_basis*), *sage.categories.finite_lattice_posets*), 425
 407 **FinitelyGenerated()**
FiniteDimensionalNilpotentLieAlgebrasWithBasis (*sage.categories.lambda_bracket_algebras.LambdaBracketAlgebras*
 (class in *sage.categories.finite_dimensional_nilpotent_lie_algebras_with_basis*),
 413 **FinitelyGenerated()**
FiniteDimensionalNilpotentLieAlgebrasWithBasis.ParentMethods *sage.categories.magnas.Magnas.SubcategoryMethods*
 (class in *sage.categories.finite_dimensional_nilpotent_lie_algebras_with_basis*),
 413 **FinitelyGeneratedAsLambdaBracketAlgebra**
FiniteDimensionalSemisimpleAlgebrasWithBasis (*sage.categories.lambda_bracket_algebras.LambdaBracketAlgebras*
 (class in *sage.categories.finite_dimensional_semisimple_algebras_with_basis*),
 414 **FinitelyGeneratedAsLambdaBracketAlgebra**
FiniteDimensionalSemisimpleAlgebrasWithBasis.Commutative *sage.categories.lie_conformal_algebras.LieConformalAlgebras*
 (class in *sage.categories.finite_dimensional_semisimple_algebras_with_basis*),
 414 **FinitelyGeneratedAsLambdaBracketAlgebra()**
FiniteDimensionalSemisimpleAlgebrasWithBasis.Commutative.ParentMethods *sage.categories.lambda_bracket_algebras.LambdaBracketAlgebras*
 (class in *sage.categories.finite_dimensional_semisimple_algebras_with_basis*),
 414 **FinitelyGeneratedAsMagma**
FiniteDimensionalSemisimpleAlgebrasWithBasis.ParentMethods *sage.categories.magnas.Magnas* (attribute),
 (class in *sage.categories.finite_dimensional_semisimple_algebras_with_basis*),
 415 **FinitelyGeneratedAsMagma**
FiniteEnumeratedSets (class in *sage.categories.semigroups.Semigroups*
sage.categories.finite_enumerated_sets), (attribute), 675
 416 **FinitelyGeneratedAsMagma()**
FiniteEnumeratedSets.CartesianProducts (class *sage.categories.magnas.Magnas.SubcategoryMethods*
 in *sage.categories.finite_enumerated_sets*), 417 (method), 560
FiniteEnumeratedSets.CartesianProducts.ParentMethods **FinitelyGeneratedLambdaBracketAlgebras** (class
 (class in *sage.categories.finite_enumerated_sets*), in *sage.categories.finitely_generated_lambda_bracket_algebras*),
 417 461
FiniteEnumeratedSets.IsomorphicObjects (class **FinitelyGeneratedLambdaBracketAlgebras.Granted**

(class in sage.categories.finitely_generated_lambda_bracket_algebras),
461 FinitePosets.ParentMethods (class in
FinitelyGeneratedLambdaBracketAlgebras.ParentMethods sage.categories.finite_posets), 436
(class in sage.categories.finitely_generated_lambda_bracket_algebras),
461 FiniteSemigroups (class in
sage.categories.finite_semigroups), 457
FinitelyGeneratedLieConformalAlgebras (class in FiniteSemigroups.ParentMethods (class in
sage.categories.finitely_generated_lie_conformal_algebras)sage.categories.finite_semigroups), 458
462 FiniteSets (class in sage.categories.finite_sets), 459
FinitelyGeneratedLieConformalAlgebras.Graded FiniteSets.Algebras (class in
(class in sage.categories.finitely_generated_lie_conformal_algebras)sage.categories.finite_sets), 459
462 FiniteSets.ParentMethods (class in
FinitelyGeneratedLieConformalAlgebras.ParentMethods sage.categories.finite_sets), 460
(class in sage.categories.finitely_generated_lie_conformal_algebras)sage.categories.finite_sets), 460
462 FiniteSets.Subquotients (class in
sage.categories.finite_sets), 460
FinitelyGeneratedLieConformalAlgebras.Super FiniteSetsOrderedByInclusion (class in
(class in sage.categories.finitely_generated_lie_conformal_algebras)sage.categories.examples.posets), 831
462 FiniteSetsOrderedByInclusion.Element (class in
FinitelyGeneratedLieConformalAlgebras.Super.Graded sage.categories.examples.posets), 832
(class in sage.categories.finitely_generated_lie_conformal_algebras)sage.categories.finite_weyl_groups), 460
463 FiniteWeylGroups (class in
sage.categories.finite_weyl_groups), 460
FinitelyGeneratedMagmas (class in FiniteWeylGroups.ElementMethods (class in
sage.categories.finitely_generated_magmas), sage.categories.finite_weyl_groups), 460
463 FiniteWeylGroups.ParentMethods (class in
sage.categories.finite_weyl_groups), 460
FinitelyGeneratedMagmas.ParentMethods (class in sage.categories.finitely_generated_magmas), first() (sage.categories.enumerated_sets.EnumeratedSets.CartesianProduct
463 method), 302
FinitelyGeneratedSemigroups (class in first() (sage.categories.enumerated_sets.EnumeratedSets.ParentMethods
sage.categories.finitely_generated_semigroups), method), 302
464 first() (sage.categories.map.FormalCompositeMap
method), 106
FinitelyGeneratedSemigroups.Finite (class in first_descent() (sage.categories.coxeter_groups.CoxeterGroups.Element
sage.categories.finitely_generated_semigroups), method), 250
464
FinitelyGeneratedSemigroups.Finite.ParentMethods first_descent() (sage.categories.category_with_axiom.Blahs.SubcategoryMethod
(class in sage.categories.finitely_generated_semigroups), method), 89
464 ForgetfulFunctor() (in module
FinitelyGeneratedSemigroups.ParentMethods sage.categories.functor), 98
(class in sage.categories.finitely_generated_semigroups)sage.categories.functor), 98
464 ForgetfulFunctor_generic (class in
sage.categories.functor), 99
FiniteMonoids (class in FormalCoercionMorphism (class in
sage.categories.finite_monoids), 428 sage.categories.morphism), 122
FiniteMonoids.ElementMethods (class in FormalCompositeMap (class in sage.categories.map),
sage.categories.finite_monoids), 428 105
FiniteMonoids.ParentMethods (class in fraction_field() (sage.categories.fields.Fields.ParentMethods
sage.categories.finite_monoids), 429 method), 313
FinitePermutationGroups (class in FractionField (class in sage.categories.pushout), 134
sage.categories.finite_permutation_groups), free() (sage.categories.groups.Groups static method),
432 495
FinitePermutationGroups.ElementMethods (class free() (sage.categories.groups.Groups.Commutative
in sage.categories.finite_permutation_groups), static method), 489
432 free() (sage.categories.monoids.Monoids static
method), 622
FinitePermutationGroups.ParentMethods (class free() (sage.categories.monoids.Monoids.Commutative
in sage.categories.finite_permutation_groups), static method), 619
432
FinitePosets (class in sage.categories.finite_posets), free_module() (sage.categories.rings.Rings.ParentMethods

method), 665

FreeAlgebra (class in *sage.categories.examples.algebras_with_basis*), 793

FreeCommutativeAdditiveMonoid (class in *sage.categories.examples.commutative_additive_monoids*), 794

FreeCommutativeAdditiveMonoid.Element (class in *sage.categories.examples.commutative_additive_monoids*), 795

FreeCommutativeAdditiveSemigroup (class in *sage.categories.examples.commutative_additive_semigroups*), 795

FreeCommutativeAdditiveSemigroup.Element (class in *sage.categories.examples.commutative_additive_semigroups*), 796

FreeMagma (class in *sage.categories.examples.magnas*), 827

FreeMagma.Element (class in *sage.categories.examples.magnas*), 828

FreeMonoid (class in *sage.categories.examples.monoids*), 829

FreeMonoid.Element (class in *sage.categories.examples.monoids*), 830

FreeSemigroup (class in *sage.categories.examples.semigroups*), 833

FreeSemigroup.Element (class in *sage.categories.examples.semigroups*), 833

from_base_ring() (*sage.categories.unital_algebras.UnitalAlgebras.ParentMethods* method), 744

from_base_ring() (*sage.categories.unital_algebras.UnitalAlgebras.WithBasis.ParentMethods* method), 744

from_base_ring_from_one_basis() (*sage.categories.unital_algebras.UnitalAlgebras.WithBasis.ParentMethods* method), 745

from_graded_conversion() (*sage.categories.filtered_algebras_with_basis.FilteredAlgebrasWithBasis.ParentMethods* method), 315

from_graded_conversion() (*sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods* method), 332

from_reduced_word() (*sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods* method), 227

from_set() (*sage.categories.examples.with_realizations.SubsetAlgebraBases.ParentMethods* method), 849

from_vector() (*sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebra* method), 806

from_vector() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods* method), 394

from_vector() (*sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis.ParentMethods* method), 411

from_vector() (*sage.categories.lie_algebras.LieAlgebras.ParentMethods* method), 524

from_vector() (*sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis.ParentMethods* method), 530

full_super_categories() (*sage.categories.category.Category* method), 51

fully_commutative_elements() (*sage.categories.coxeter_groups.CoxeterGroups.ParentMethods* method), 265

FunctionFields (class in *sage.categories.function_fields*), 466

FunctionFields.ElementMethods (class in *sage.categories.function_fields*), 466

FunctionFields.ParentMethods (class in *sage.categories.function_fields*), 466

FunctorialConstructionCategory (class in *sage.categories.functor*), 99

FunctorialConstructionCategory (class in *sage.categories.covariant_functorial_construction*), 767

fundamental_group() (*sage.categories.simplicial_sets.SimplicialSets.Pointed.ParentMethods* method), 722

fuss_catalan_number() (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods* method), 350

G

G (*sage.categories.action.Action* attribute), 156

gcd() (*sage.categories.discrete_valuation.DiscreteValuationRings.ElementMethods* method), 310

gcd() (*sage.categories.euclidean_domains.EuclideanDomains.ElementMethods* method), 310

gcd() (*sage.categories.fields.Fields.ElementMethods* method), 310

gcd() (*sage.categories.quotient_fields.QuotientFields.ElementMethods* method), 639

gcd_free_basis() (*sage.categories.euclidean_domains.EuclideanDomains.ParentMethods* method), 310

GcdDomains (class in *sage.categories.gcd_domains*), 467

GcdDomains.ElementMethods (class in *sage.categories.gcd_domains*), 467

GcdDomains.ParentMethods (class in *sage.categories.gcd_domains*), 467

gen() (*sage.categories.posets.Posets.ParentMethods* method), 629

gen() (*sage.categories.finitely_generated_lambda_bracket_algebras.FinitelyGeneratedLambdaBracketAlgebras.ParentMethods* method), 461

gen() (*sage.categories.semigroups.Semigroups.ParentMethods* method), 673

generalized_noncrossing_partitions() (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods* method), 342

GeneralizedCoxeterGroups (class in *sage.categories.generalized_coxeter_groups*), 468

GeneralizedCoxeterGroups.Finite (class in graded_algebra() (sage.categories.graded_algebras_with_basis.GradedAlgebrasWithBasis), 468)

generating_series() (sage.categories.examples.sets_with_grading.NonGradedAlgebra() (sage.categories.super_algebras_with_basis.SuperAlgebrasWithBasis), 846)

generating_series() (sage.categories.sets_with_grading.SetsWithGrading.ParentMethods), 713

gens() (sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebra), 806

gens() (sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis.ParentMethods), 411

gens() (sage.categories.pushout.PermutationGroupFunctor), 141

gens() (sage.categories.semigroups.Semigroups.Algebras.ParentMethods), 673

genuine_highest_weight_vectors() (sage.categories.supercrystals.SuperCrystals.FiniteGradedAlgebras), 736

genuine_lowest_weight_vectors() (sage.categories.supercrystals.SuperCrystals.FiniteGradedAlgebrasWithBasis), 736

get_axiom_index() (in module sage.categories.category_cy_helper), 860

Graded (sage.categories.algebras.Algebras attribute), 180

Graded (sage.categories.algebras_with_basis.AlgebrasWithBasis attribute), 184

Graded (sage.categories.coalgebras.Coalgebras attribute), 199

Graded (sage.categories.coalgebras_with_basis.CoalgebrasWithBasis attribute), 204

Graded (sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis attribute), 508

Graded (sage.categories.lie_algebras.LieAlgebras attribute), 521

Graded (sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis attribute), 530

Graded (sage.categories.lie_conformal_algebras.LieConformalAlgebras attribute), 534

Graded (sage.categories.modules.Modules attribute), 582

Graded (sage.categories.modules_with_basis.ModulesWithBasis attribute), 602

Graded() (sage.categories.modules.Modules.SubcategoryMethods), 586

graded_algebra() (sage.categories.filtered_algebras.FilteredAlgebras), 314

graded_algebra() (sage.categories.filtered_algebras_with_basis.FilteredAlgebrasWithBasis), 316

graded_algebra() (sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods), 332

graded_algebra() (sage.categories.graded_algebras.GradedAlgebras), 469

graded_algebra() (sage.categories.graded_algebras_with_basis.GradedAlgebrasWithBasis), 470

graded_algebra() (sage.categories.super_algebras.SuperAlgebras.ParentMethods), 724

graded_algebra() (sage.categories.super_algebras_with_basis.SuperAlgebrasWithBasis), 726

graded_component() (sage.categories.examples.sets_with_grading.NonGradedAlgebra), 847

graded_component() (sage.categories.sets_with_grading.SetsWithGrading.ParentMethods), 713

graded_component() (sage.categories.sets_with_grading.SetsWithGrading.ParentMethods), 713

GradedAlgebras (class in sage.categories.graded_algebras), 469

GradedAlgebras.ElementMethods (class in sage.categories.graded_algebras), 469

GradedAlgebras.ParentMethods (class in sage.categories.graded_algebras), 469

GradedAlgebras.SignedTensorProducts (class in sage.categories.graded_algebras), 469

GradedAlgebras.SubcategoryMethods (class in sage.categories.graded_algebras), 470

GradedAlgebrasWithBasis (class in sage.categories.graded_algebras_with_basis), 470

GradedAlgebrasWithBasis.ElementMethods (class in sage.categories.graded_algebras_with_basis), 470

GradedAlgebrasWithBasis.ParentMethods (class in sage.categories.graded_algebras_with_basis), 470

GradedAlgebrasWithBasis.SignedTensorProducts (class in sage.categories.graded_algebras_with_basis), 471

GradedAlgebrasWithBasis.SignedTensorProducts.ParentMethods (class in sage.categories.graded_algebras_with_basis), 471

GradedBialgebras() (in module sage.categories.graded_bialgebras), 472

GradedBialgebrasWithBasis() (in module sage.categories.graded_bialgebras_with_basis), 472

GradedCoalgebras (class in sage.categories.graded_coalgebras), 472

GradedCoalgebras.SignedTensorProducts (class in sage.categories.graded_coalgebras), 472

GradedCoalgebras.SubcategoryMethods (class in sage.categories.graded_coalgebras), 473

GradedCoalgebrasWithBasis (class in sage.categories.graded_coalgebras_with_basis), 473

GradedCoalgebrasWithBasis.ParentMethods (class in sage.categories.graded_coalgebras_with_basis), 473

GradedCoalgebrasWithBasis.SignedTensorProducts (class in sage.categories.graded_coalgebras_with_basis), 473

GradedCombinatorialHopfAlgebraWithPrimitiveGenerators (class in sage.categories.examples.graded_connected_hopf_algebras), 473

816

GradedHopfAlgebras() (in module *sage.categories.graded_hopf_algebras*), 474

GradedHopfAlgebrasWithBasis (class in *sage.categories.graded_hopf_algebras_with_basis*), 474

GradedHopfAlgebrasWithBasis.Connected (class in *sage.categories.graded_hopf_algebras_with_basis*), 474

GradedHopfAlgebrasWithBasis.Connected.ElementMethods (class in *sage.categories.graded_hopf_algebras_with_basis*), 474

GradedHopfAlgebrasWithBasis.Connected.ParentMethods (class in *sage.categories.graded_hopf_algebras_with_basis*), 474

GradedHopfAlgebrasWithBasis.ElementMethods (class in *sage.categories.graded_hopf_algebras_with_basis*), 475

GradedHopfAlgebrasWithBasis.ParentMethods (class in *sage.categories.graded_hopf_algebras_with_basis*), 475

GradedHopfAlgebrasWithBasis.WithRealizations (class in *sage.categories.graded_hopf_algebras_with_basis*), 475

GradedLieAlgebras (class in *sage.categories.graded_lie_algebras*), 475

GradedLieAlgebras.Stratified (class in *sage.categories.graded_lie_algebras*), 475

GradedLieAlgebras.Stratified.FiniteDimensional (class in *sage.categories.graded_lie_algebras*), 476

GradedLieAlgebras.SubcategoryMethods (class in *sage.categories.graded_lie_algebras*), 476

GradedLieAlgebrasWithBasis (class in *sage.categories.graded_lie_algebras_with_basis*), 476

GradedLieConformalAlgebras (class in *sage.categories.graded_lie_conformal_algebras*), 477

GradedLieConformalAlgebrasCategory (class in *sage.categories.graded_lie_conformal_algebras*), 477

GradedModules (class in *sage.categories.graded_modules*), 478

GradedModules.ElementMethods (class in *sage.categories.graded_modules*), 478

GradedModules.ParentMethods (class in *sage.categories.graded_modules*), 478

GradedModulesCategory (class in *sage.categories.graded_modules*), 478

GradedModulesWithBasis (class in *sage.categories.graded_modules_with_basis*), 479

GradedModulesWithBasis.ElementMethods (class in *sage.categories.graded_modules_with_basis*), 479

GradedModulesWithBasis.ParentMethods (class in *sage.categories.graded_modules_with_basis*), 480

GradedPartitionModule (class in *sage.categories.examples.graded_modules_with_basis*), 818

grading() (*sage.categories.examples.sets_with_grading.NonNegativeIntegerSet*), 847

grading() (*sage.categories.sets_with_grading.SetsWithGrading.ParentMethods*), 714

grading_set() (*sage.categories.sets_with_grading.SetsWithGrading.ParentMethods*), 714

Graphs (class in *sage.categories.graphs*), 480

Graphs.Connected (class in *sage.categories.graphs*), 480

Graphs.ParentMethods (class in *sage.categories.graphs*), 481

ghasmanian_elements() (*sage.categories.coxeter_groups.CoxeterGroups.ParentMethods*), 265

group() (*sage.categories.additive_groups.AdditiveGroups.Algebras.ParentMethods*), 159

group() (*sage.categories.algebra_functor.GroupAlgebraFunctor*), 779

group() (*sage.categories.group_algebras.GroupAlgebras.ParentMethods*), 485

group_generators() (*sage.categories.complex_reflection_or_generalized_linear_groups.ParentMethods*), 229

group_generators() (*sage.categories.groups.Groups.CartesianProducts*), 488

group_generators() (*sage.categories.groups.Groups.ParentMethods*), 494

GroupAlgebraFunctor (class in *sage.categories.algebra_functor*), 779

GroupAlgebras (class in *sage.categories.group_algebras*), 482

GroupAlgebras.ElementMethods (class in *sage.categories.group_algebras*), 483

GroupAlgebras.ParentMethods (class in *sage.categories.group_algebras*), 484

Groupoid (class in *sage.categories.groupoid*), 487

Groups (class in *sage.categories.groups*), 487

Groups.CartesianProducts (class in *sage.categories.groups*), 487

Groups.CartesianProducts.ElementMethods (class in *sage.categories.groups*), 487

Groups.CartesianProducts.ParentMethods (class in *sage.categories.groups*), 488

Groups.Commutative (class in *sage.categories.groups*), 489

Groups.ElementMethods (class in *sage.categories.groups*), 489

Groups.ParentMethods (class in sage.categories.groups), 490

Groups.Topological (class in sage.categories.groups), 495

GSets (class in sage.categories.g_sets), 467

gt() (sage.categories.posets.Posets.ParentMethods method), 629

H

has_descent() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 250

has_full_support() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 250

has_left_descent() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 251

has_right_descent() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 251

has_right_descent() (sage.categories.examples.finite_coxeter_groups.DihedralGroup.ElementMethods method), 802

has_right_descent() (sage.categories.examples.finite_weyl_groups.SymmetricGroup.ElementMethods method), 815

HeckeModules (class in sage.categories.hecke_modules), 496

HeckeModules.Homsets (class in sage.categories.hecke_modules), 496

HeckeModules.Homsets.ParentMethods (class in sage.categories.hecke_modules), 496

HeckeModules.ParentMethods (class in sage.categories.hecke_modules), 496

highest_weight_vector() (sage.categories.highest_weight_crystals.HighestWeightCrystals.ParentMethods method), 500

highest_weight_vectors() (sage.categories.highest_weight_crystals.HighestWeightCrystals.ParentMethods method), 500

highest_weight_vectors() (sage.categories.highest_weight_crystals.HighestWeightCrystals.TensorProducts.ParentMethods method), 502

highest_weight_vectors() (sage.categories.supercrystals.SuperCrystals.Finite.ParentMethods method), 737

highest_weight_vectors_iterator() (sage.categories.highest_weight_crystals.HighestWeightCrystals.TensorProducts.ParentMethods method), 503

HighestWeightCrystalHomset (class in sage.categories.highest_weight_crystals), 497

HighestWeightCrystalMorphism (class in sage.categories.highest_weight_crystals), 497

HighestWeightCrystalOfTypeA (class in sage.categories.examples.crystals), 797

HighestWeightCrystalOfTypeA.Element (class in sage.categories.examples.crystals), 798

HighestWeightCrystals (class in sage.categories.highest_weight_crystals), 497

HighestWeightCrystals.ElementMethods (class in sage.categories.highest_weight_crystals), 498

HighestWeightCrystals.ParentMethods (class in sage.categories.highest_weight_crystals), 499

HighestWeightCrystals.TensorProducts (class in sage.categories.highest_weight_crystals), 502

HighestWeightCrystals.TensorProducts.ParentMethods (class in sage.categories.highest_weight_crystals), 502

hochschild_complex() (sage.categories.algebras_with_basis.AlgebrasWithBasis.ParentMethods method), 184

holomorph() (sage.categories.groups.Groups.ParentMethods method), 494

Hom() (in module sage.categories.homset), 116

hom() (in module sage.categories.homset), 121

homogeneous_component() (sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods method), 326

homogeneous_component() (sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods method), 333

homogeneous_component_as_submodule() (sage.categories.finite_dimensional_graded_lie_algebras_with_basis.ParentMethods method), 387

homogeneous_component_basis() (sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods method), 333

homogeneous_degree() (sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods method), 327

homology() (sage.categories.finite_dimensional_lie_algebras_with_basis.ParentMethods method), 395

Homset (class in sage.categories.homset), 118

homset_category() (sage.categories.homset.Homset method), 119

Homsets (class in sage.categories.homsets), 782

Homsets() (sage.categories.objects.Objects.SubcategoryMethods method), 624

Homsets.Endset (class in sage.categories.homsets), 783

Homsets.Endset.ParentMethods (class in sage.categories.homsets), 783

Homsets.ParentMethods (class in sage.categories.homsets), 783

Homsets.SubcategoryMethods (class in sage.categories.homsets), 784

HomsetsCategory (class in sage.categories.homsets), 784

- 784
- `HomsetsOf` (class in `sage.categories.homsets`), 786
- `HomsetWithBase` (class in `sage.categories.homset`), 121
- `HopfAlgebras` (class in `sage.categories.hopf_algebras`), 504
- `HopfAlgebras.DualCategory` (class in `sage.categories.hopf_algebras`), 504
- `HopfAlgebras.DualCategory.ParentMethods` (class in `sage.categories.hopf_algebras`), 504
- `HopfAlgebras.ElementMethods` (class in `sage.categories.hopf_algebras`), 504
- `HopfAlgebras.Morphism` (class in `sage.categories.hopf_algebras`), 504
- `HopfAlgebras.ParentMethods` (class in `sage.categories.hopf_algebras`), 504
- `HopfAlgebras.Realizations` (class in `sage.categories.hopf_algebras`), 505
- `HopfAlgebras.Realizations.ParentMethods` (class in `sage.categories.hopf_algebras`), 505
- `HopfAlgebras.Super` (class in `sage.categories.hopf_algebras`), 505
- `HopfAlgebras.Super.ElementMethods` (class in `sage.categories.hopf_algebras`), 505
- `HopfAlgebras.TensorProducts` (class in `sage.categories.hopf_algebras`), 505
- `HopfAlgebras.TensorProducts.ElementMethods` (class in `sage.categories.hopf_algebras`), 506
- `HopfAlgebras.TensorProducts.ParentMethods` (class in `sage.categories.hopf_algebras`), 506
- `HopfAlgebrasWithBasis` (class in `sage.categories.hopf_algebras_with_basis`), 506
- `HopfAlgebrasWithBasis.ElementMethods` (class in `sage.categories.hopf_algebras_with_basis`), 508
- `HopfAlgebrasWithBasis.ParentMethods` (class in `sage.categories.hopf_algebras_with_basis`), 508
- `HopfAlgebrasWithBasis.TensorProducts` (class in `sage.categories.hopf_algebras_with_basis`), 509
- `HopfAlgebrasWithBasis.TensorProducts.ElementMethods` (class in `sage.categories.hopf_algebras_with_basis`), 509
- `HopfAlgebrasWithBasis.TensorProducts.ParentMethods` (class in `sage.categories.hopf_algebras_with_basis`), 509
- `HTrivial` (`sage.categories.semigroups.Semigroups` attribute), 675
- `HTrivial()` (`sage.categories.semigroups.Semigroups.SubcategoryMethods` method), 680
- `HTrivialSemigroups` (class in `sage.categories.h_trivial_semigroups`), 510
- `hyperplane_index_set()` (`sage.categories.complex_reflection_or_generalized_coxeter_group` method), 229
- ## I
- `ideal()` (`sage.categories.examples.finite_dimensional_lie_algebras_with_basis` method), 806
- `ideal()` (`sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis` method), 395
- `ideal()` (`sage.categories.finitely_generated_semigroups.FinitelyGeneratedSemigroups` method), 464
- `ideal()` (`sage.categories.lambda_bracket_algebras.LambdaBracketAlgebras` method), 515
- `ideal()` (`sage.categories.lie_algebras.LieAlgebras.ParentMethods` method), 524
- `ideal()` (`sage.categories.rings.Rings.ParentMethods` method), 666
- `ideal_monoid()` (`sage.categories.rings.Rings.ParentMethods` method), 666
- `idempotent_lift()` (`sage.categories.finite_dimensional_algebras_with_basis` method), 376
- `idempotents()` (`sage.categories.finite_semigroups.FiniteSemigroups.ParentMethods` method), 458
- `IdempotentSemigroups` (class in `sage.categories.examples.semigroups_cython`), 838
- `IdempotentSemigroups.ElementMethods` (class in `sage.categories.examples.semigroups_cython`), 838
- `identity()` (`sage.categories.homset.Homset` method), 119
- `IdentityConstructionFunctor` (class in `sage.categories.pushout`), 135
- `IdentityFunctor()` (in `sage.categories.functor` module), 101
- `IdentityFunctor_generic` (class in `sage.categories.functor`), 101
- `IdentityMorphism` (class in `sage.categories.morphism`), 122
- `im_gens()` (`sage.categories.crystals.CrystalMorphismByGenerators` method), 274
- `image()` (`sage.categories.crystals.CrystalMorphismByGenerators` method), 274
- `image()` (`sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis` method), 405
- `image_basis()` (`sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis` method), 406
- `IncompleteSubquotientSemigroup` (class in `sage.categories.examples.semigroups`), 834
- `IncompleteSubquotientSemigroup.Element` (class in `sage.categories.examples.semigroups`), 834
- `index()` (`sage.categories.lambda_bracket_algebras_with_basis.LambdaBracketAlgebrasWithBasis` method), 516
- `index_set()` (`sage.categories.complex_reflection_or_generalized_coxeter_group` method), 230

index_set() (*sage.categories.coxeter_groups.CoxeterGroups.ParentMethods* (class in *sage.categories.integral_domains*), 265
sage.categories.integral_domains), 512
index_set() (*sage.categories.crystals.Crystals.ElementMethods* (class in *sage.categories.integral_domains*), 277
sage.categories.integral_domains), 512
index_set() (*sage.categories.crystals.Crystals.ParentMethods* (class in *sage.categories.integral_domains*), 288
sage.categories.integral_domains), 512
index_set() (*sage.categories.examples.finite_coxeter_groups.ParentMethods* (class in *sage.categories.integral_domains*), 802
sage.categories.integral_domains), 512
index_set() (*sage.categories.examples.finite_weyl_groups.ParentMethods* (class in *sage.categories.integral_domains*), 816
sage.categories.integral_domains), 512
index_set() (*sage.categories.quantum_group_representations.ParentMethods* (class in *sage.categories.integral_domains*), 644
sage.categories.integral_domains), 512
IndexedPolynomialRing (class in *sage.categories.examples.lie_algebras_with_basis*), 826
indices() (*sage.categories.examples.with_realizations.SubsetAlgebra* (class in *sage.categories.examples.with_realizations*), 852
sage.categories.examples.with_realizations), 852
indices_key() (*sage.categories.examples.with_realizations.SubsetAlgebra* (class in *sage.categories.examples.with_realizations*), 852
sage.categories.examples.with_realizations), 852
induced_graded_map() (*sage.categories.filtered_algebras_with_basis.FilteredAlgebraWithBasis.ParentMethods* (class in *sage.categories.filtered_algebras_with_basis*), 316
sage.categories.filtered_algebras_with_basis), 316
induced_graded_map() (*sage.categories.filtered_modules_with_basis.FilteredModuleWithBasis.ParentMethods* (class in *sage.categories.filtered_modules_with_basis*), 334
sage.categories.filtered_modules_with_basis), 334
Infinite (*sage.categories.enumerated_sets.EnumeratedSets* (class in *sage.categories.enumerated_sets*), 302
sage.categories.enumerated_sets), 302
Infinite() (*sage.categories.sets_cat.Sets.SubcategoryMethods* (class in *sage.categories.sets_cat*), 701
sage.categories.sets_cat), 701
InfiniteEnumeratedSets (class in *sage.categories.infinite_enumerated_sets*), 511
InfiniteEnumeratedSets.ParentMethods (class in *sage.categories.infinite_enumerated_sets*), 511
InfinitePolynomialFunctor (class in *sage.categories.pushout*), 135
inject_shorthands() (*sage.categories.sets_cat.Sets.WithRealizations.ParentMethods* (class in *sage.categories.sets_cat*), 709
sage.categories.sets_cat), 709
inner_derivations_basis() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods* (class in *sage.categories.finite_dimensional_lie_algebras_with_basis*), 396
sage.categories.finite_dimensional_lie_algebras_with_basis), 396
IntegerModMonoid (class in *sage.categories.examples.finite_monoids*), 810
IntegerModMonoid.Element (class in *sage.categories.examples.finite_monoids*), 811
IntegersCompletion (class in *sage.categories.examples.facade_sets*), 800
IntegralDomains (class in *sage.categories.integral_domains*), 512
IntegralDomains.ElementMethods (class in *sage.categories.integral_domains*), 512

`is_abelian()` (*sage.categories.vector_spaces.VectorSpaces.WithBasis*), 750
method), 750
`is_affine_grassmannian()` (*sage.categories.affine_weyl_groups.AffineWeylGroups.ElementMethods*), 175
method), 175
`is_antichain_of_poset()` (*sage.categories.posets.Posets.ParentMethods*), 630
method), 630
`is_Category()` (in module *sage.categories.category*), 64
`is_central()` (*sage.categories.monoids.Monoids.Algebras.ElementMethods*), 617
method), 617
`is_chain_of_poset()` (*sage.categories.posets.Posets.ParentMethods*), 631
method), 631
`is_commutative()` (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods*), 376
method), 376
`is_commutative()` (*sage.categories.lie_algebras.LieAlgebras.ParentMethods*), 525
method), 525
`is_commutative()` (*sage.categories.magmas.Magmas.CommutativeParentMethods*), 554
method), 554
`is_connected()` (*sage.categories.crystals.Crystals.ParentMethods*), 288
method), 288
`is_construction_defined_by_base()` (*sage.categories.covariant_functorial_construction.ParentMethods*), 765
method), 765
`is_coxeter_element()` (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ElementMethods*), 357
method), 357
`is_coxeter_sortable()` (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods*), 251
method), 251
`is_embedding()` (*sage.categories.crystals.Crystals.MorphismMethods*), 281
method), 281
`is_empty()` (*sage.categories.additive_magmas.AdditiveMagmas.AdditiveUnitalParentMethods*), 163
method), 163
`is_empty()` (*sage.categories.enumerated_sets.ParentMethods*), 302
method), 302
`is_empty()` (*sage.categories.magmas.Magmas.Unital.ParentMethods*), 563
method), 563
`is_empty()` (*sage.categories.sets_cat.Sets.CartesianProducts.ParentMethods*), 691
method), 691
`is_empty()` (*sage.categories.sets_cat.Sets.Infinite.ParentMethods*), 693
method), 693
`is_endomorphism()` (*sage.categories.morphism.Morphism*), 124
method), 124
`is_endomorphism_set()` (*sage.categories.homsets.Homsets.Endset.ParentMethods*), 783
method), 783
`is_endomorphism_set()` (*sage.categories.homsets.Homsets.ParentMethods*), 783
method), 783
`is_Endset()` (in module *sage.categories.homset*), 121
`is_euclidean_domain()` (*sage.categories.euclidean_domains.EuclideanDomains.ParentMethods*), 308
method), 308
`is_even()` (*sage.categories.super_modules.SuperModules.ElementMethods*), 729
method), 729
`is_even_odd()` (*sage.categories.lie_conformal_algebras.LieConformalAlgebras.ParentMethods*), 533
method), 533
`is_even_odd()` (*sage.categories.super_lie_conformal_algebras.SuperLieConformalAlgebras.ParentMethods*), 728
method), 728
`is_even_odd()` (*sage.categories.super_modules.SuperModules.ElementMethods*), 729
method), 729
`is_even_odd()` (*sage.categories.super_modules_with_basis.SuperModulesWithBasis.ParentMethods*), 732
method), 732
`is_field()` (*sage.categories.fields.Fields.ParentMethods*), 313
method), 313
`is_field()` (*sage.categories.magmas.Magmas.Algebras.ParentMethods*), 313
method), 313
`is_finite()` (*sage.categories.finite_sets.FiniteSets.ParentMethods*), 460
method), 460
`is_finite()` (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods*), 460
method), 460
`is_finite()` (*sage.categories.sets_cat.Sets.CartesianProducts.ParentMethods*), 691
method), 691
`is_finite()` (*sage.categories.sets_cat.Sets.Infinite.ParentMethods*), 693
method), 693
`is_finite()` (*sage.categories.simplicial_sets.SimplicialSets.ParentMethods*), 718
method), 718
`is_full_subcategory()` (*sage.categories.category.Category*), 52
method), 52
`is_Functor()` (in module *sage.categories.functor*), 102
`is_highest_weight()` (*sage.categories.supercrystals.SuperCrystals.Finite.ElementMethods*), 734
method), 734
`is_genuine_lowest_weight()` (*sage.categories.supercrystals.SuperCrystals.Finite.ElementMethods*), 734
method), 734
`is_grassmannian()` (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods*), 252
method), 252
`is_grouplike()` (*sage.categories.bialgebras.Bialgebras.ElementMethods*), 187
method), 187
`is_highest_weight()` (*sage.categories.crystals.Crystals.ElementMethods*), 278
method), 278
`is_homogeneous()` (*sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods*), 328
method), 328
`is_Homset()` (in module *sage.categories.homset*), 122
`is_ideal()` (*sage.categories.examples.finite_dimensional_lie_algebras_with_basis.ParentMethods*), 806
method), 806
`is_ideal()` (*sage.categories.finite_dimensional_lie_algebras_with_basis.ParentMethods*), 396
method), 396
`is_ideal()` (*sage.categories.lie_algebras.LieAlgebras.ParentMethods*), 525
method), 525
`is_idempotent()` (*sage.categories.examples.semigroups.LeftZeroSemigroups.ParentMethods*), 835
method), 835

is_idempotent() (*sage.categories.examples.semigroups_cython.Semigroups.ElementMethods*
method), 838
is_idempotent() (*sage.categories.magnas.Magnas.ElementMethods*
method), 554
is_identity() (*sage.categories.morphism.IdentityMorphism*
method), 122
is_identity() (*sage.categories.morphism.Morphism*
method), 124
is_identity_decomposition_into_orthogonal_idempotents()
(*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods*
method), 376
is_injective() (*sage.categories.crystals.CrystalMorphismMethods*
method), 272
is_injective() (*sage.categories.map.FormalCompositeMap*
method), 106
is_injective() (*sage.categories.morphism.IdentityMorphism*
method), 123
is_injective() (*sage.categories.rings.Rings.MorphismMethods*
method), 663
is_injective() (*sage.categories.sets_cat.Sets.MorphismMethods*
method), 693
is_integral_domain()
(*sage.categories.group_algebras.GroupAlgebras.ParentMethods*
method), 486
is_integral_domain()
(*sage.categories.integral_domains.IntegralDomains.ParentMethods*
method), 512
is_integrally_closed()
(*sage.categories.fields.Fields.ParentMethods*
method), 313
is_irreducible() (*sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups*
method), 231
is_isomorphism() (*sage.categories.crystals.Crystals.MorphismMethods*
method), 281
is_isomorphism() (*sage.categories.regular_crystals.RegularCrystals.MorphismMethods*
method), 654
is_lattice() (*sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 446
is_lattice_morphism()
(*sage.categories.finite_lattice_posets.FiniteLatticePosets.ParentMethods*
method), 426
is_left() (*sage.categories.action.Action* *method*), 156
is_lowest_weight() (*sage.categories.crystals.Crystals.ElementMethods*
method), 278
is_Map() (*in module sage.categories.map*), 114
is_Morphism() (*in module sage.categories.morphism*),
126
is_nilpotent() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods*
method), 397
is_nilpotent() (*sage.categories.finite_dimensional_nilpotent_lie_algebras_with_basis.FiniteDimensionalNilpotentLieAlgebrasWithBasis.ParentMethods*
method), 413
is_nilpotent() (*sage.categories.lie_algebras.LieAlgebras.NilpotentParentMethods*
method), 522
is_nilpotent() (*sage.categories.lie_algebras.LieAlgebras.ParentMethods*
method), 282
is_odd() (*sage.categories.super_modules.SuperModules.ElementMethods*
method), 730
is_one() (*sage.categories.monoids.Monoids.ElementMethods*
method), 620
is_order_filter() (*sage.categories.posets.Posets.ParentMethods*
method), 633
is_order_ideal() (*sage.categories.posets.Posets.ParentMethods*
method), 633
is_parent_of() (*sage.categories.sets_cat.Sets.ParentMethods*
method), 696
is_perfect() (*sage.categories.fields.Fields.ParentMethods*
method), 313
is_perfect() (*sage.categories.loop_crystals.KirillovReshetikhinCrystals*
method), 540
is_primitive_factor() (*sage.categories.weyl_groups.WeylGroups.ElementMethods*
method), 753
is_pointed() (*sage.categories.simplicial_sets.SimplicialSets.ParentMethods*
method), 718
is_poset_isomorphism()
(*sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 446
is_poset_morphism()
(*sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 447
is_prime() (*sage.categories.examples.sets_cat.PrimeNumbers_Abstract*
method), 841
is_primitive() (*sage.categories.bialgebras.Bialgebras.ElementMethods*
method), 288
is_real() (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups*
method), 346
is_real() (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods*
method), 231
is_reducible() (*sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups*
method), 231
is_reflection() (*sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups*
method), 225
is_ring() (*in module sage.categories.rings.Rings.ParentMethods*
method), 667
is_self_dual() (*sage.categories.finite_posets.FinitePosets.ParentMethods*
method), 448
is_semisimple() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods*
method), 397
is_simply_connected()
(*sage.categories.simplicial_sets.SimplicialSets.Pointed.ParentMethods*
method), 718
is_solvable() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods*
method), 397
is_solvable() (*sage.categories.lie_algebras.LieAlgebras.ParentMethods*
method), 282
is_strict() (*sage.categories.crystals.Crystals.MorphismMethods*
method), 282

is_subcategory() (*sage.categories.category.Category* method), 53

is_subcategory() (*sage.categories.category.JoinCategory_transversal_of_idempotents()* method), 63

is_super_homogeneous() (*sage.categories.super_modules_with_basis.SuperModulesWithBasisElementMethods* method), 732

is_surjective() (*sage.categories.crystals.CrystalMorphisms.ParentMethods* method), 272

is_surjective() (*sage.categories.map.FormalCompositionalJoin_as_tuple()* method), 107

is_surjective() (*sage.categories.map.Map* method), 111

is_surjective() (*sage.categories.morphism.IdentityMorphism* method), 123

is_unique_factorization_domain() (*sage.categories.unique_factorization_domains.UniqueFactorizationDomains.ParentMethods* method), 743

is_unit() (*sage.categories.discrete_valuation.DiscreteValuationRings.ElementMethods* method), 297

is_unit() (*sage.categories.fields.Fields.ElementMethods* method), 311

is_unit() (*sage.categories.rings.Rings.ElementMethods* method), 662

is_well_generated() (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods* method), 346

is_well_generated() (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.WellGeneratedParentMethods* method), 353

is_zero() (*sage.categories.modules_with_basis.ModulesWithBasisElementMethods* method), 593

is_zero() (*sage.categories.rings.Rings.ParentMethods* method), 667

IsomorphicObjectOfFiniteEnumeratedSet (class in *sage.categories.examples.finite_enumerated_sets*), 809

IsomorphicObjects() (*sage.categories.sets_cat.Sets.SubcategoryMethods* method), 701

IsomorphicObjectsCategory (class in *sage.categories.isomorphic_objects*), 781

isotypic_projective_modules() (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods* method), 378

iterator_range() (*sage.categories.enumerated_sets.EnumeratedSets.ParentMethods* method), 302

iterator_range() (*sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods* method), 420

J

j_classes() (*sage.categories.finite_semigroups.FiniteSemigroups.ParentMethods* method), 458

j_classes_of_idempotents() (*sage.categories.finite_semigroups.FiniteSemigroups.ParentMethods* method), 458

JoinCategory (*sage.categories.category*), 61

JoinCategory_transversal_of_idempotents() (*sage.categories.finite_semigroups.FiniteSemigroups.ParentMethods* method), 63

Join_as_tuple() (in module *sage.categories.category_cy_helper*), 860

join_irreducibles() (*sage.categories.finite_lattice_posets.FiniteLatticePosets.ParentMethods* method), 427

join_irreducibles_poset() (*sage.categories.finite_lattice_posets.FiniteLatticePosets.ParentMethods* method), 427

join_trivial() (*sage.categories.magmas.Magmas.SubcategoryMethods* method), 561

join_trivial() (*sage.categories.semigroups.Semigroups.SubcategoryMethods* method), 681

JoinTrivialSemigroups (class in *sage.categories.finite_semigroups.FiniteSemigroups*), 512

K

kernel() (*sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis.ParentMethods* method), 406

kernel_basis() (*sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis.ParentMethods* method), 406

killing_form() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods* method), 397

killing_form() (*sage.categories.lie_algebras.LieAlgebras.ElementMethods* method), 520

killing_form() (*sage.categories.lie_algebras.LieAlgebras.ParentMethods* method), 398

killing_form_matrix() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods* method), 398

killing_matrix() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods* method), 398

KernelParentMethodsInCrystals (class in *sage.categories.loop_crystals*), 537

- KirillovReshetikhinCrystals.ElementMethods (class in *sage.categories.loop_crystals*), 537
- KirillovReshetikhinCrystals.ParentMethods (class in *sage.categories.loop_crystals*), 538
- KirillovReshetikhinCrystals.TensorProducts (class in *sage.categories.loop_crystals*), 543
- KirillovReshetikhinCrystals.TensorProducts.ElementMethods (class in *sage.categories.loop_crystals*), 543
- KirillovReshetikhinCrystals.TensorProducts.ParentMethods (class in *sage.categories.loop_crystals*), 546
- KroneckerQuiverPathAlgebra (class in *sage.categories.examples.finite_dimensional_algebras_with_basis*), 803
- L**
- Lambda() (*sage.categories.crystals.Crystals.ParentMethods* method), 282
- LambdaBracketAlgebras (class in *sage.categories.lambda_bracket_algebras*), 514
- LambdaBracketAlgebras.ElementMethods (class in *sage.categories.lambda_bracket_algebras*), 514
- LambdaBracketAlgebras.ParentMethods (class in *sage.categories.lambda_bracket_algebras*), 515
- LambdaBracketAlgebras.SubcategoryMethods (class in *sage.categories.lambda_bracket_algebras*), 515
- LambdaBracketAlgebrasWithBasis (class in *sage.categories.lambda_bracket_algebras_with_basis*), 516
- LambdaBracketAlgebrasWithBasis.ElementMethods (class in *sage.categories.lambda_bracket_algebras_with_basis*), 516
- LambdaBracketAlgebrasWithBasis.FinitelyGeneratedAsLambdaBracketAlgebra (class in *sage.categories.lambda_bracket_algebras_with_basis*), 516
- LambdaBracketAlgebrasWithBasis.FinitelyGeneratedAsLambdaBracketAlgebra.Graded (class in *sage.categories.lambda_bracket_algebras_with_basis*), 517
- LambdaBracketAlgebrasWithBasis.FinitelyGeneratedAsLambdaBracketAlgebra.Graded.ParentMethods (class in *sage.categories.lambda_bracket_algebras_with_basis*), 517
- last() (*sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods* method), 417
- last() (*sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods* method), 420
- latex() (*sage.categories.crystals.Crystals.ParentMethods* method), 288
- latex_file() (*sage.categories.crystals.Crystals.ParentMethods* method), 288
- LatticePosets (class in *sage.categories.lattice_posets*), 517
- LatticePosets.ParentMethods (class in *sage.categories.lattice_posets*), 517
- LaurentPolynomialFunctor (class in *sage.categories.pushout*), 137
- lcm() (*sage.categories.discrete_valuation.DiscreteValuationRings.ElementMethods* method), 297
- lcm() (*sage.categories.fields.Fields.ElementMethods* method), 311
- lcm() (*sage.categories.quotient_fields.QuotientFields.ElementMethods* method), 640
- le() (*sage.categories.examples.posets.FiniteSetsOrderedByInclusion* method), 832
- le() (*sage.categories.examples.posets.PositiveIntegersOrderedByDivisibility* method), 833
- le() (*sage.categories.posets.Posets.ParentMethods* method), 634
- leading_coefficient() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods* method), 593
- leading_item() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods* method), 594
- leading_monomial() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods* method), 594
- leading_support() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods* method), 595
- leading_term() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods* method), 595
- left_base_ring() (*sage.categories.bimodules.Bimodules* method), 193
- left_domain() (*sage.categories.action.Action* method), 156
- left_inversions_as_reflections() (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods* method), 252
- left_pieri_factorizations() (*sage.categories.coxeter_groups.WeylGroups.ElementMethods* method), 753
- left_precomposition (*sage.categories.algebras.Graded* attribute), 158
- LeftModules (class in *sage.categories.left_modules*), 518
- LeftModules.ElementMethods (class in *sage.categories.left_modules*), 518
- LeftModules.ParentMethods (class in *sage.categories.left_modules*), 518
- LeftRegularBand (class in *sage.categories.examples.finite_semigroups*), 812
- LeftRegularBand.Element (class in *sage.categories.examples.finite_semigroups*), 813
- LeftZeroSemigroup (class in *sage.categories.examples.semigroups*), 834

LeftZeroSemigroup	(class in sage.categories.examples.semigroups_cython), 838	sage.categories.lie_conformal_algebras), 533
LeftZeroSemigroup.Element	(class in sage.categories.examples.semigroups), 835	LieConformalAlgebras.ElementMethods (class in sage.categories.lie_conformal_algebras), 533
LeftZeroSemigroupElement	(class in sage.categories.examples.semigroups_cython), 839	LieConformalAlgebras.ParentMethods (class in sage.categories.lie_conformal_algebras), 534
length()	(sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 253	LieConformalAlgebrasWithBasis (class in sage.categories.lie_conformal_algebras_with_basis), 535
length()	(sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods method), 595	LieConformalAlgebrasWithBasis.FinitelyGeneratedAsLambdaBranched (class in sage.categories.lie_conformal_algebras_with_basis), 535
level()	(sage.categories.loop_crystals.KirillovReshetikhinLieConformalAlgebrasWithBasis method), 541	LieConformalAlgebrasWithBasis.FinitelyGeneratedAsLambdaBranched (class in sage.categories.lie_conformal_algebras_with_basis), 535
Lie	(sage.categories.groups.Groups attribute), 490	LieConformalAlgebrasWithBasis.FinitelyGeneratedAsLambdaBranched (class in sage.categories.lie_conformal_algebras_with_basis), 535
lie_algebra_generators()	(sage.categories.examples.finite_dimensional_lie_algebras_with_basis.LieAlgebra method), 807	LieConformalAlgebrasWithBasis.FinitelyGeneratedAsLambdaBranched (class in sage.categories.lie_conformal_algebras_with_basis), 535
lie_algebra_generators()	(sage.categories.examples.lie_algebras.LieAlgebraFromAssociative method), 825	LieConformalAlgebrasWithBasis.FinitelyGeneratedAsLambdaBranched (class in sage.categories.lie_conformal_algebras_with_basis), 536
lie_algebra_generators()	(sage.categories.examples.lie_algebras_with_basis.AbelianLieAlgebra method), 826	LieConformalAlgebrasWithBasis.Graded (class in sage.categories.lie_conformal_algebras_with_basis), 536
lie_group()	(sage.categories.finite_dimensional_nilpotent_lie_algebras.LieAlgebrasWithBasis method), 413	LieConformalAlgebrasWithBasis.Super.Nilpotent (class in sage.categories.lie_conformal_algebras_with_basis), 536
lie_group()	(sage.categories.lie_algebras.LieAlgebras.ParentMethods method), 526	LieConformalAlgebrasWithBasis.Super.Graded (class in sage.categories.lie_conformal_algebras_with_basis), 536
LieAlgebraFromAssociative	(class in sage.categories.examples.lie_algebras), 824	LieConformalAlgebrasWithBasis.Super.ParentMethods (class in sage.categories.lie_conformal_algebras_with_basis), 536
LieAlgebraFromAssociative.Element	(class in sage.categories.examples.lie_algebras), 825	LieGroups (class in sage.categories.lie_groups), 537
LieAlgebras	(class in sage.categories.lie_algebras), 519	lift() (sage.categories.examples.finite_dimensional_lie_algebras_with_basis method), 805
LieAlgebras.ElementMethods	(class in sage.categories.lie_algebras), 519	lift() (sage.categories.examples.finite_enumerated_sets.IsomorphicObjects method), 809
LieAlgebras.FiniteDimensional	(class in sage.categories.lie_algebras), 521	lift() (sage.categories.examples.lie_algebras_with_basis.AbelianLieAlgebra method), 826
LieAlgebras.Nilpotent	(class in sage.categories.lie_algebras), 521	lift() (sage.categories.examples.semigroups.QuotientOfLeftZeroSemigroup method), 836
LieAlgebras.Nilpotent.ParentMethods	(class in sage.categories.lie_algebras), 521	lift() (sage.categories.lie_algebras.LieAlgebras.ElementMethods method), 520
LieAlgebras.ParentMethods	(class in sage.categories.lie_algebras), 522	lift() (sage.categories.lie_algebras.LieAlgebras.ParentMethods method), 526
LieAlgebras.SubcategoryMethods	(class in sage.categories.lie_algebras), 528	lift() (sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis.ElementMethods method), 529
LieAlgebrasWithBasis	(class in sage.categories.lie_algebras_with_basis), 529	lift() (sage.categories.sets_cat.Sets.Subquotients.ElementMethods method), 706
LieAlgebrasWithBasis.ElementMethods	(class in sage.categories.lie_algebras_with_basis), 529	lift() (sage.categories.sets_cat.Sets.Subquotients.ParentMethods method), 707
LieAlgebrasWithBasis.ParentMethods	(class in sage.categories.lie_algebras_with_basis), 530	lift_to_precision()
LieConformalAlgebras	(class in sage.categories.complete_discrete_valuation.CompleteDiscreteValuation), 533	

method), 216

LiftMorphism (class in *sage.categories.lie_algebras*), 529

linear_combination() (sage.categories.modules.Modules.ParentMethods method), 583

list() (sage.categories.enumerated_sets.EnumeratedSets.ParentMethods method), 303

list() (sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods method), 421

list() (sage.categories.infinite_enumerated_sets.InfiniteEnumeratedSets.ParentMethods method), 511

local_energy_function() (sage.categories.loop_crystals.KirillovReshetikhinCrystals.ParentMethods method), 542

LocalEnergyFunction (class in *sage.categories.loop_crystals*), 547

long_element() (sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods method), 361

LoopCrystals (class in *sage.categories.loop_crystals*), 548

LoopCrystals.ParentMethods (class in *sage.categories.loop_crystals*), 548

lower_central_series() (sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods method), 398

lower_cover_reflections() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 253

lower_covers() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 253

lower_covers() (sage.categories.posets.Posets.ParentMethods method), 634

lowest_weight_vectors() (sage.categories.highest_weight_crystals.HighestWeightCrystals.ParentMethods method), 500

lowest_weight_vectors() (sage.categories.supercrystals.SuperCrystals.Finite.ParentMethods method), 737

lt() (sage.categories.posets.Posets.ParentMethods method), 634

LTrivial (sage.categories.semigroups.Semigroups attribute), 675

LTrivial() (sage.categories.semigroups.Semigroups.SubcategoryMethods method), 681

LTrivialSemigroups (class in *sage.categories.l_trivial_semigroups*), 550

lusztig_involution() (sage.categories.classical_crystals.ClassicalCrystals.ElementMethods method), 194

lusztig_involution() (sage.categories.loop_crystals.KirillovReshetikhinCrystals.ElementMethods method), 538

M

m_cambrian_lattice() (sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods method), 361

magma_generators() (sage.categories.examples.magnas.FreeMagma method), 828

magma_generators() (sage.categories.finitely_generated_magnas.FinitelyGeneratedMagnas method), 463

magma_generators() (sage.categories.semigroups.Semigroups.ParentMethods method), 677

Magnas (class in *sage.categories.magnas*), 551

Magnas.Algebras (class in *sage.categories.magnas*), 551

Magnas.Algebras.ParentMethods (class in *sage.categories.magnas*), 551

Magnas.CartesianProducts (class in *sage.categories.magnas*), 552

Magnas.CartesianProducts.ParentMethods (class in *sage.categories.magnas*), 552

Magnas.Commutative (class in *sage.categories.magnas*), 553

Magnas.Commutative.Algebras (class in *sage.categories.magnas*), 553

Magnas.Commutative.CartesianProducts (class in *sage.categories.magnas*), 553

Magnas.Commutative.ParentMethods (class in *sage.categories.magnas*), 553

Magnas.ElementMethods (class in *sage.categories.magnas*), 554

Magnas.Frivial (class in *sage.categories.magnas*), 554

Magnas.ParentMethods (class in *sage.categories.magnas*), 554

Magnas.Realizations (class in *sage.categories.magnas*), 558

Magnas.Realizations.ParentMethods (class in *sage.categories.magnas*), 558

Magnas.SubcategoryMethods (class in *sage.categories.magnas*), 558

Magnas.Subquotients (class in *sage.categories.magnas*), 561

Magnas.Subquotients.ParentMethods (class in *sage.categories.magnas*), 562

Magnas.Unital (class in *sage.categories.magnas*), 562

Magnas.Unital.Algebras (class in *sage.categories.magnas*), 562

Magnas.Unital.CartesianProducts (class in *sage.categories.magnas*), 562

Magnas.Unital.CartesianProducts.ElementMethods (class in *sage.categories.magnas*), 563

Magnas.Unital.CartesianProducts.ParentMethods (class in *sage.categories.magnas*), 563

Magnas.Unital.ElementMethods (class in *sage.categories.magnas*), 563

Magma.Unital.Inverse (class in `map()` (*sage.categories.enumerated_sets.EnumeratedSets.ParentMethods* method), 304
*sage.categories.magma*s), 563
Magma.Unital.Inverse.CartesianProducts (class in `map_coefficients()` (*sage.categories.modules_with_basis.ModulesWithBasis.Element* method), 596
*sage.categories.magma*s), 563
Magma.Unital.ParentMethods (class in `map_item()` (*sage.categories.modules_with_basis.ModulesWithBasis.Element* method), 596
*sage.categories.magma*s), 563
Magma.Unital.Realizations (class in `map_support()` (*sage.categories.modules_with_basis.ModulesWithBasis.Element* method), 597
*sage.categories.magma*s), 564
Magma.Unital.Realizations.ParentMethods (class in `map_support_skip_none()` (*sage.categories.modules_with_basis.ModulesWithBasis.Element* method), 597
*sage.categories.magma*s), 564
Magma.Unital.SubcategoryMethods (class in `matrix()` (*sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalModulesWithBasis.Element* method), 406
*sage.categories.magma*s), 564
MagmasAndAdditiveMagma (class in `MatrixAlgebras` (class in *sage.categories.matrix_algebras*), 574
*sage.categories.magma*s_and_additive_magma), 565
MagmasAndAdditiveMagma.CartesianProducts (class in `MatrixFunctor` (*sage.categories.pushout*), 138
*sage.categories.magma*s_and_additive_magma), 566
MagmasAndAdditiveMagma.SubcategoryMethods (class in `maximal_degree()` (*sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.Element* method), 329
*sage.categories.magma*s_and_additive_magma), 566
MagmamaticAlgebras (class in `maximal_vector()` (*sage.categories.loop_crystals.KirillovReshetikhinCrystal* method), 546
*sage.categories.magma*matic_algebras), 567
MagmamaticAlgebras.ParentMethods (class in `meet()` (*sage.categories.category.Category* static method), 56
*sage.categories.magma*matic_algebras), 567
MagmamaticAlgebras.WithBasis (class in `meet()` (*sage.categories.lattice_posets.LatticePosets.ParentMethods* method), 518
*sage.categories.magma*matic_algebras), 568
MagmamaticAlgebras.WithBasis.FiniteDimensional (class in `meet_irreducibles()` (*sage.categories.finite_lattice_posets.FiniteLatticePosets.ParentMethods* method), 427
*sage.categories.magma*matic_algebras), 568
MagmamaticAlgebras.WithBasis.FiniteDimensional.ParentMethods (class in `meet_irreducibles_poset()` (*sage.categories.finite_lattice_posets.FiniteLatticePosets.ParentMethods* method), 428
*sage.categories.magma*matic_algebras), 568
MagmamaticAlgebras.WithBasis.ParentMethods (class in `merge()` (*sage.categories.pushout.AlgebraicClosureFunctor* method), 126
*sage.categories.magma*matic_algebras), 569
Manifolds (class in `merge()` (*sage.categories.pushout.AlgebraicExtensionFunctor* method), 128
sage.categories.manifolds), 570
Manifolds.AlmostComplex (class in `merge()` (*sage.categories.pushout.CompletionFunctor* method), 130
sage.categories.manifolds), 571
Manifolds.Analytic (class in `merge()` (*sage.categories.pushout.ConstructionFunctor* method), 134
sage.categories.manifolds), 571
Manifolds.Connected (class in `merge()` (*sage.categories.pushout.InfinitePolynomialFunctor* method), 137
sage.categories.manifolds), 571
Manifolds.Differentiable (class in `merge()` (*sage.categories.pushout.LaurentPolynomialFunctor* method), 138
sage.categories.manifolds), 571
Manifolds.FiniteDimensional (class in `merge()` (*sage.categories.pushout.MatrixFunctor* method), 139
sage.categories.manifolds), 572
Manifolds.ParentMethods (class in `merge()` (*sage.categories.pushout.MultiPolynomialFunctor* method), 140
sage.categories.manifolds), 572
Manifolds.Smooth (class in `merge()` (*sage.categories.pushout.PermutationGroupFunctor* method), 141
sage.categories.manifolds), 572
Manifolds.SubcategoryMethods (class in `merge()` (*sage.categories.pushout.PolynomialFunctor* method), 142
sage.categories.manifolds), 572
Map (class in `merge()` (*sage.categories.pushout.QuotientFunctor* method), 143
sage.categories.map), 109

- merge() (*sage.categories.pushout.SubspaceFunctor* method), 144
- merge() (*sage.categories.pushout.VectorFunctor* method), 144
- metapost() (*sage.categories.crystals.Crystals.ParentMethods* method), 289
- Metric (*sage.categories.sets_cat.Sets* attribute), 693
- metric() (*sage.categories.metric_spaces.MetricSpaces.ParentMethods* method), 577
- Metric() (*sage.categories.sets_cat.Sets.SubcategoryMethods* method), 702
- metric_function() (*sage.categories.metric_spaces.MetricSpaces.ParentMethods* method), 577
- MetricSpaces (class in *sage.categories.metric_spaces*), 575
- MetricSpaces.CartesianProducts (class in *sage.categories.metric_spaces*), 575
- MetricSpaces.CartesianProducts.ParentMethods (class in *sage.categories.metric_spaces*), 575
- MetricSpaces.Complete (class in *sage.categories.metric_spaces*), 576
- MetricSpaces.Complete.CartesianProducts (class in *sage.categories.metric_spaces*), 576
- MetricSpaces.ElementMethods (class in *sage.categories.metric_spaces*), 576
- MetricSpaces.Homsets (class in *sage.categories.metric_spaces*), 577
- MetricSpaces.Homsets.ElementMethods (class in *sage.categories.metric_spaces*), 577
- MetricSpaces.ParentMethods (class in *sage.categories.metric_spaces*), 577
- MetricSpaces.SubcategoryMethods (class in *sage.categories.metric_spaces*), 578
- MetricSpaces.WithRealizations (class in *sage.categories.metric_spaces*), 578
- MetricSpaces.WithRealizations.ParentMethods (class in *sage.categories.metric_spaces*), 578
- MetricSpacesCategory (class in *sage.categories.metric_spaces*), 578
- min_demazure_product_greater() (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods* method), 254
- ModularAbelianVarieties (class in *sage.categories.modular_abelian_varieties*), 579
- ModularAbelianVarieties.Homsets (class in *sage.categories.modular_abelian_varieties*), 579
- ModularAbelianVarieties.Homsets.Endset (class in *sage.categories.modular_abelian_varieties*), 579
- module
- sage.categories.action, 155
 - sage.categories.additive_groups, 158
 - sage.categories.additive_magmas, 160
 - sage.categories.additive_monoids, 171
 - sage.categories.additive_semigroups, 172
 - sage.categories.affine_weyl_groups, 174
 - sage.categories.algebra_functor, 773
 - sage.categories.algebra_ideals, 177
 - sage.categories.algebra_modules, 178
 - sage.categories.algebras, 178
 - sage.categories.algebras_with_basis, 182
 - sage.categories.aperiodic_semigroups, 187
 - sage.categories.associative_algebras, 187
 - sage.categories.bialgebras, 187
 - sage.categories.bialgebras_with_basis, 189
 - sage.categories.bimodules, 193
 - sage.categories.cartesian_product, 769
 - sage.categories.category, 28
 - sage.categories.category_cy_helper, 859
 - sage.categories.category_singleton, 856
 - sage.categories.category_types, 853
 - sage.categories.category_with_axiom, 64
 - sage.categories.classical_crystals, 194
 - sage.categories.coalgebras, 198
 - sage.categories.coalgebras_with_basis, 203
 - sage.categories.coercion_methods, 861
 - sage.categories.commutative_additive_groups, 205
 - sage.categories.commutative_additive_monoids, 207
 - sage.categories.commutative_additive_semigroups, 207
 - sage.categories.commutative_algebra_ideals, 208
 - sage.categories.commutative_algebras, 208
 - sage.categories.commutative_ring_ideals, 209
 - sage.categories.commutative_rings, 209
 - sage.categories.complete_discrete_valuation, 213
 - sage.categories.complex_reflection_groups, 217
 - sage.categories.complex_reflection_or_generalized_coxeter_groups, 219
 - sage.categories.covariant_functorial_construction, 763
 - sage.categories.coxeter_group_algebras, 237
 - sage.categories.coxeter_groups, 240
 - sage.categories.crystals, 269
 - sage.categories.cw_complexes, 293
 - sage.categories.discrete_valuation, 296
 - sage.categories.distributive_magmas_and_additive_magma, 298

sage.categories.division_rings, 299
 sage.categories.domains, 300
 sage.categories.dual, 773
 sage.categories.enumerated_sets, 301
 sage.categories.euclidean_domains, 307
 sage.categories.examples.algebras_with_basis, 793
 sage.categories.examples.commutative_additive_monoids, 794
 sage.categories.examples.commutative_additive_semigroups, 795
 sage.categories.examples.coxeter_groups, 797
 sage.categories.examples.crystals, 797
 sage.categories.examples.cw_complexes, 799
 sage.categories.examples.facade_sets, 800
 sage.categories.examples.finite_coxeter_groups, 801
 sage.categories.examples.finite_dimensional_algebras_with_basis, 803
 sage.categories.examples.finite_dimensional_lie_algebras_with_basis, 804
 sage.categories.examples.finite_enumerated_sets, 808
 sage.categories.examples.finite_monoids, 810
 sage.categories.examples.finite_semigroups, 812
 sage.categories.examples.finite_weyl_groups, 814
 sage.categories.examples.graded_connected_hopf_algebras_with_basis, 816
 sage.categories.examples.graded_modules_with_basis, 818
 sage.categories.examples.graphs, 820
 sage.categories.examples.hopf_algebras_with_basis, 821
 sage.categories.examples.infinite_enumerated_sets, 823
 sage.categories.examples.lie_algebras, 824
 sage.categories.examples.lie_algebras_with_basis, 826
 sage.categories.examples.magnas, 827
 sage.categories.examples.manifolds, 828
 sage.categories.examples.monoids, 829
 sage.categories.examples.posets, 831
 sage.categories.examples.semigroups, 833
 sage.categories.examples.semigroups_cython, 838
 sage.categories.examples.sets_cat, 840
 sage.categories.examples.sets_with_grading, 846
 sage.categories.examples.with_realizations, 847
 sage.categories.facade_sets, 760
 sage.categories.fields, 309
 sage.categories.filtered_algebras, 314
 sage.categories.filtered_algebras_with_basis, 315
 sage.categories.filtered_modules, 322
 sage.categories.filtered_modules_with_basis, 324
 sage.categories.finite_complex_reflection_groups, 338
 sage.categories.finite_coxeter_groups, 355
 sage.categories.finite_crystals, 367
 sage.categories.finite_dimensional_algebras_with_basis, 367
 sage.categories.finite_dimensional_bialgebras_with_basis, 386
 sage.categories.finite_dimensional_coalgebras_with_basis, 386
 sage.categories.finite_dimensional_graded_lie_algebras, 387
 sage.categories.finite_dimensional_hopf_algebras_with_basis, 388
 sage.categories.finite_dimensional_lie_algebras_with_basis, 389
 sage.categories.finite_dimensional_modules_with_basis, 405
 sage.categories.finite_dimensional_nilpotent_lie_algebras, 413
 sage.categories.finite_dimensional_semisimple_algebras, 414
 sage.categories.finite_enumerated_sets, 416
 sage.categories.finite_fields, 422
 sage.categories.finite_groups, 423
 sage.categories.finite_lattice_posets, 425
 sage.categories.finite_monoids, 428
 sage.categories.finite_permutation_groups, 432
 sage.categories.finite_posets, 436
 sage.categories.finite_semigroups, 457
 sage.categories.finite_sets, 459
 sage.categories.finite_weyl_groups, 460
 sage.categories.finitely_generated_lambda_bracket_algebras, 461
 sage.categories.finitely_generated_lie_conformal_algebras, 462
 sage.categories.finitely_generated_magnas, 463
 sage.categories.finitely_generated_semigroups, 464

- sage.categories.function_fields, 466
- sage.categories.functor, 98
- sage.categories.g_sets, 467
- sage.categories.gcd_domains, 467
- sage.categories.generalized_coxeter_groups, 468
- sage.categories.graded_algebras, 469
- sage.categories.graded_algebras_with_basis, 470
- sage.categories.graded_bialgebras, 472
- sage.categories.graded_bialgebras_with_basis, 472
- sage.categories.graded_coalgebras, 472
- sage.categories.graded_coalgebras_with_basis, 473
- sage.categories.graded_hopf_algebras, 474
- sage.categories.graded_hopf_algebras_with_basis, 474
- sage.categories.graded_lie_algebras, 475
- sage.categories.graded_lie_algebras_with_basis, 476
- sage.categories.graded_lie_conformal_algebras, 477
- sage.categories.graded_modules, 478
- sage.categories.graded_modules_with_basis, 479
- sage.categories.graphs, 480
- sage.categories.group_algebras, 482
- sage.categories.grouppoid, 487
- sage.categories.groups, 487
- sage.categories.h_trivial_semigroups, 510
- sage.categories.hecke_modules, 496
- sage.categories.highest_weight_crystals, 497
- sage.categories.homset, 114
- sage.categories.homsets, 782
- sage.categories.hopf_algebras, 504
- sage.categories.hopf_algebras_with_basis, 506
- sage.categories.infinite_enumerated_sets, 511
- sage.categories.integral_domains, 512
- sage.categories.isomorphic_objects, 781
- sage.categories.j_trivial_semigroups, 512
- sage.categories.kac_moody_algebras, 513
- sage.categories.l_trivial_semigroups, 550
- sage.categories.lambda_bracket_algebras, 514
- sage.categories.lambda_bracket_algebras_with_basis, 516
- sage.categories.lattice_posets, 517
- sage.categories.left_modules, 518
- sage.categories.lie_algebras, 519
- sage.categories.lie_algebras_with_basis, 529
- sage.categories.lie_conformal_algebras, 531
- sage.categories.lie_conformal_algebras_with_basis, 535
- sage.categories.lie_groups, 537
- sage.categories.loop_crystals, 537
- sage.categories.magmas, 551
- sage.categories.magmas_and_additive_magmas, 565
- sage.categories.magmatic_algebras, 567
- sage.categories.manifolds, 570
- sage.categories.map, 105
- sage.categories.matrix_algebras, 574
- sage.categories.metric_spaces, 575
- sage.categories.modular_abelian_varieties, 579
- sage.categories.modules, 580
- sage.categories.modules_with_basis, 590
- sage.categories.monoid_algebras, 616
- sage.categories.monoids, 616
- sage.categories.morphism, 122
- sage.categories.number_fields, 622
- sage.categories.objects, 624
- sage.categories.partially_ordered_monoids, 626
- sage.categories.permutation_groups, 626
- sage.categories.pointed_sets, 627
- sage.categories.polyhedra, 627
- sage.categories.poor_man_map, 861
- sage.categories.posets, 628
- sage.categories.primers, 1
- sage.categories.principal_ideal_domains, 637
- sage.categories.pushout, 126
- sage.categories.quantum_group_representations, 644
- sage.categories.quotient_fields, 638
- sage.categories.quotients, 780
- sage.categories.r_trivial_semigroups, 671
- sage.categories.realizations, 786
- sage.categories.regular_crystals, 650
- sage.categories.regular_supercrystals, 658
- sage.categories.right_modules, 660
- sage.categories.ring_ideals, 660
- sage.categories.rings, 661
- sage.categories.rngs, 670
- sage.categories.schemes, 671
- sage.categories.semigroups, 672
- sage.categories.semiring, 684
- sage.categories.semisimple_algebras, 684
- sage.categories.sets_cat, 686

sage.categories.sets_with_grading, 712
 sage.categories.sets_with_partial_maps, 715
 sage.categories.shephard_groups, 715
 sage.categories.signed_tensor, 772
 sage.categories.simplicial_complexes, 716
 sage.categories.simplicial_sets, 717
 sage.categories.subobjects, 781
 sage.categories.subquotients, 780
 sage.categories.super_algebras, 724
 sage.categories.super_algebras_with_basis, 726
 sage.categories.super_hopf_algebras_with_basis, 727
 sage.categories.super_lie_conformal_algebras, 727
 sage.categories.super_modules, 729
 sage.categories.super_modules_with_basis, 731
 sage.categories.supercommutative_algebras, 733
 sage.categories.supercrystals, 734
 sage.categories.tensor, 771
 sage.categories.topological_spaces, 739
 sage.categories.triangular_kac_moody_algebras, 740
 sage.categories.tutorial, 102
 sage.categories.unique_factorization_domains, 742
 sage.categories.unital_algebras, 744
 sage.categories.vector_bundles, 746
 sage.categories.vector_spaces, 747
 sage.categories.weyl_groups, 751
 sage.categories.with_realizations, 788
 module() (sage.categories.examples.finite_dimensional_lie_algebras.ParentMethods method), 807
 module() (sage.categories.finite_dimensional_lie_algebras.ModulesWithBasis.ParentMethods method), 399
 module() (sage.categories.lie_algebras.LieAlgebras.ParentMethods method), 527
 module() (sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis.ParentMethods method), 530
 module_generator() (sage.categories.loop_crystals.KirillovReshetikhinCrystals.ParentMethods method), 542
 module_morphism() (sage.categories.modules.Modules.ParentMethods method), 584
 module_morphism() (sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods method), 604
 Modules (class in sage.categories.modules), 580
 Modules.CartesianProducts (class in sage.categories.modules), 581
 Modules.CartesianProducts.ElementMethods (class in sage.categories.modules), 581
 Modules.CartesianProducts.ParentMethods (class in sage.categories.modules), 581
 Modules.ElementMethods (class in sage.categories.modules), 581
 Modules.FiniteDimensional (class in sage.categories.modules), 581
 Modules.Homsets (class in sage.categories.modules), 582
 Modules.Homsets.Endset (class in sage.categories.modules), 582
 Modules.Homsets.ParentMethods (class in sage.categories.modules), 582
 Modules.ParentMethods (class in sage.categories.modules), 583
 Modules.SubcategoryMethods (class in sage.categories.modules), 584
 Modules.TensorProducts (class in sage.categories.modules), 589
 ModulesWithBasis (class in sage.categories.modules_with_basis), 590
 ModulesWithBasis.CartesianProducts (class in sage.categories.modules_with_basis), 591
 ModulesWithBasis.CartesianProducts.ParentMethods (class in sage.categories.modules_with_basis), 591
 ModulesWithBasis.DualObjects (class in sage.categories.modules_with_basis), 591
 ModulesWithBasis.ElementMethods (class in sage.categories.modules_with_basis), 592
 ModulesWithBasis.Homsets (class in sage.categories.modules_with_basis), 602
 ModulesWithBasis.Homsets.ParentMethods (class in sage.categories.modules_with_basis), 602
 ModulesWithBasis.MorphismMethods (class in sage.categories.modules_with_basis), 602
 ModulesWithBasis.ParentMethods (class in sage.categories.modules_with_basis), 602
 ModulesWithBasis.TensorProducts (class in sage.categories.modules_with_basis), 613
 ModulesWithBasis.TensorProducts.ElementMethods (class in sage.categories.modules_with_basis), 615
 monoid_generators() (sage.categories.examples.monoids.FreeMonoid monoid_generators()), 424
 monoid_generators() (sage.categories.finite_groups.FiniteGroups.ParentMethods method), 424
 monoid_generators() (sage.categories.groups.Groups.ParentMethods method), 494
 monoid_generators()

(*sage.categories.monoids.Monoids.CartesianProducts.ParentMethods*, 139
method), 619

MonoidAlgebras() (in module *sage.categories.monoid_algebras*), 616

Monoids (class in *sage.categories.monoids*), 616

Monoids.Algebras (class in *sage.categories.monoids*), 617

Monoids.Algebras.ElementMethods (class in *sage.categories.monoids*), 617

Monoids.Algebras.ParentMethods (class in *sage.categories.monoids*), 617

Monoids.CartesianProducts (class in *sage.categories.monoids*), 618

Monoids.CartesianProducts.ParentMethods (class in *sage.categories.monoids*), 619

Monoids.Commutative (class in *sage.categories.monoids*), 619

Monoids.ElementMethods (class in *sage.categories.monoids*), 620

Monoids.ParentMethods (class in *sage.categories.monoids*), 620

Monoids.Subquotients (class in *sage.categories.monoids*), 621

Monoids.Subquotients.ParentMethods (class in *sage.categories.monoids*), 621

Monoids.WithRealizations (class in *sage.categories.monoids*), 621

Monoids.WithRealizations.ParentMethods (class in *sage.categories.monoids*), 621

monomial() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods*
method), 608

monomial_coefficients() (*sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebra*
method), 805

monomial_coefficients() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods*
method), 597

monomial_or_zero_if_none() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods*
method), 608

monomials() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods*
method), 598

Morphism (class in *sage.categories.morphism*), 123

morphism() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebraWithBasis.ParentMethods*
method), 399

morphism_class() (*sage.categories.category.Category*
method), 56

multiplication_table() (*sage.categories.magnas.Magnas.ParentMethods*
method), 554

multiplicative_order() (*sage.categories.groups.Groups.CartesianProducts.ElementMethods*
method), 488

MultiPolynomialFunctor (class in *sage.categories.pushout*), 140

MultivariateConstructionFunctor (class in *sage.categories.pushout*), 140

MyGroupAlgebra (class in *sage.categories.examples.hopf_algebras_with_basis*), 821

N

NaiveCrystal (class in *sage.categories.examples.crystals*), 798

NaiveCrystal.Element (class in *sage.categories.examples.crystals*), 798

natural_map() (*sage.categories.homset.Homset*
method), 120

nerve() (*sage.categories.finite_monoids.FiniteMonoids.ParentMethods*
method), 429

next() (*sage.categories.enumerated_sets.EnumeratedSets.ParentMethods*
method), 304

next() (*sage.categories.examples.infinite_enumerated_sets.NonNegativeIntegers.ParentMethods*
method), 824

next() (*sage.categories.examples.sets_cat.PrimeNumbers_Abstract*
method), 842

next() (*sage.categories.examples.sets_cat.PrimeNumbers_Abstract.ElementMethods*
method), 841

ngens() (*sage.categories.finitely_generated_lambda_bracket_algebras.FinitelyGeneratedLambdaBracketAlgebra.ParentMethods*
method), 461

ngens() (*sage.categories.semigroups.Semigroups.Algebras.ParentMethods*
method), 673

Nilpotent (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebraWithBasis.ParentMethods*
method), 460

Nilpotent() (*sage.categories.lie_algebras.LieAlgebras.SubcategoryMethods*
method), 528

nilpotent_with_basis_AbelianLieAlgebra() (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroupWithBasis.ParentMethods*
method), 343

NonNegativeIntegers (class in *sage.categories.examples.infinite_enumerated_sets*), 823

NonNegativeIntegers (class in *sage.categories.examples.sets_with_grading*), 845

NoZeroDivisors (*sage.categories.rings.Rings*
tribute), 664

NoZeroDivisors.FiniteDimensionalLieAlgebraWithBasis.ParentMethods
method), 670

nproduct() (*sage.categories.lambda_bracket_algebras.LambdaBracketAlgebra.ParentMethods*
method), 515

number_of_connected_components() (*sage.categories.crystals.Crystals.ParentMethods*
method), 289

number_of_irreducible_components() (*sage.categories.complex_reflection_or_generalized_coxeter_group.ComplexReflectionOrGeneralizedCoxeterGroup.ParentMethods*
method), 231

number_of_reflection_hyperplanes()

(sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods.SubsetAlgebra.FundamentalMethod), 347
 (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods.CartesianProducts.ParentMethod), 347
 number_of_reflections() one() (sage.categories.homset.Homset method), 120
 (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods), 347
 number_of_reflections_of_full_support() one() (sage.categories.magnas.Magnas.Unital.ParentMethods method), 351
 (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.WellGenerated.Irreducible.ParentMethods), 351
 number_of_simple_reflections() one() (sage.categories.magnas.Magnas.Unital.Realizations.ParentMethods method), 232
 (sage.categories.complex_reflection_or_generalization.ComplexReflectionOrGeneralization.ParentMethods), 232
 NumberFields (class in sage.categories.number_fields), 622
 NumberFields.ElementMethods (class in sage.categories.number_fields), 623
 NumberFields.ParentMethods (class in sage.categories.number_fields), 623
 numerator() (sage.categories.complete_discrete_valuation_domains.CompleteDiscreteValuationDomains.ElementMethods.AdditiveMagmas.AdditiveMethod), 214
 numerator() (sage.categories.complete_discrete_valuation_domains.CompleteDiscreteValuationDomains.ElementMethods.AlgebrasWithBasis.TensorAlgebrasWithBasis.TensorAlgebrasWithBasis.ElementMethods), 216
 numerator() (sage.categories.quotient_fields.QuotientFields.ElementMethods), 640
 one_basis() (sage.categories.examples.algebras_with_basis.FreeAlgebraWithBasis.FreeAlgebraWithBasis.ElementMethods), 793
 one_basis() (sage.categories.examples.graded_connected_hopf_algebras.GradedConnectedHopfAlgebras.ParentMethods), 817
 one_basis() (sage.categories.examples.hopf_algebras_with_basis.MyGroupHopfAlgebrasWithBasis.ParentMethods), 822
 one_basis() (sage.categories.examples.lie_algebras_with_basis.IndexedLieAlgebrasWithBasis.ParentMethods), 827
 one_basis() (sage.categories.examples.with_realizations.SubsetAlgebra.FundamentalMethod), 850
 one_basis() (sage.categories.graded_algebras_with_basis.GradedAlgebrasWithBasis.ParentMethods), 871
 odd_component() (sage.categories.super_modules_with_basis.SuperModulesWithBasis.ElementMethods method), 733
 one_basis() (sage.categories.monoids.Monoids.Algebras.ParentMethods method), 618
 on_basis() (sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods method), 602
 one_basis() (sage.categories.unital_algebras.UnitalAlgebras.WithBasis.ParentMethods), 745
 on_left_matrix() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ElementMethods method), 372
 one_dimensional_configuration_sum() (sage.categories.lorentz_crystals.KirillovReshetikhinCrystals.TensorAlgebrasWithBasis.ParentMethods method), 547
 one() (sage.categories.algebras_with_basis.AlgebrasWithBasis.CartesianProducts.ParentMethods method), 183
 one_from_cartesian_product_of_one_basis() (sage.categories.algebras_with_basis.AlgebrasWithBasis.CartesianProducts.ParentMethods method), 183
 one() (sage.categories.examples.finite_coxeter_groups.DihedralGroupParentMethods method), 802
 one_from_one_basis() (sage.categories.unital_algebras.UnitalAlgebras.WithBasis.ParentMethods method), 745
 one() (sage.categories.examples.finite_dimensional_algebras_with_basis.KroneckerQuiverParentMethods method), 803
 one() (sage.categories.action.Action attribute), 156
 operation() (sage.categories.action.Action method), 156
 one() (sage.categories.examples.finite_weyl_groups.SymmetricGroupParentMethods method), 816
 or_subcategory() (sage.categories.category.Category method), 56
 one() (sage.categories.examples.monoids.FreeMonoidParentMethods method), 831
 order() (sage.categories.groups.Groups.CartesianProducts.ParentMethods method), 488
 one() (sage.categories.examples.with_realizations.SubsetAlgebra.Basis.ParentMethods method), 849
 order_filter() (sage.categories.posets.Posets.ParentMethods method)

- method), 634
- `order_filter_generators()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 448
- `order_ideal()` (*sage.categories.posets.Posets.ParentMethods* method), 635
- `order_ideal_complement_generators()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 448
- `order_ideal_generators()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 449
- `order_ideal_toggle()` (*sage.categories.posets.Posets.ParentMethods* method), 635
- `order_ideal_toggles()` (*sage.categories.posets.Posets.ParentMethods* method), 635
- `order_ideals_lattice()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 450
- `orthogonal_idempotents_central_mod_radical()` (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ElementMethods* method), 379
- `over()` (*sage.categories.commutative_rings.CommutativeRings.ParentMethods* method), 211
- P**
- `panyushev_complement()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 450
- `panyushev_orbit_iter()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 451
- `panyushev_orbits()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 452
- `parent()` (*sage.categories.map.Map* method), 111
- `parent_class()` (*sage.categories.category.Category* method), 57
- `part()` (*sage.categories.triangular_kac_moody_algebras.TriangularKacMoodyAlgebras.ElementMethods* method), 741
- `partial_fraction_decomposition()` (*sage.categories.quotient_fields.QuotientFields.ElementMethods* method), 641
- `PartiallyOrderedMonoids` (class in *sage.categories.partially_ordered_monoids*), 626
- `PartiallyOrderedMonoids.ElementMethods` (class in *sage.categories.partially_ordered_monoids*), 626
- `PartiallyOrderedMonoids.ParentMethods` (class in *sage.categories.partially_ordered_monoids*), 626
- `pbw_basis()` (*sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis.ElementMethods* method), 531
- `partial_decomposition()` (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ElementMethods* method), 380
- `peirce_summand()` (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ElementMethods* method), 381
- `PermutationCubehedron()` (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ElementMethods* method), 362
- `PermutationGroupFunctor` (class in *sage.categories.pushout*), 141
- `PermutationGroups` (class in *sage.categories.permutation_groups*), 626
- `Phi()` (*sage.categories.crystals.Crystals.ElementMethods* method), 276
- `phi()` (*sage.categories.crystals.Crystals.ElementMethods* method), 278
- `phi()` (*sage.categories.regular_crystals.RegularCrystals.ElementMethods* method), 652
- `phi()` (*sage.categories.regular_supercrystals.RegularSuperCrystals.ElementMethods* method), 659
- `phi_minus_epsilon()` (*sage.categories.regular_crystals.RegularCrystals.ElementMethods* method), 278
- `Plane` (class in *sage.categories.examples.manifolds*), 828
- `plot()` (*sage.categories.crystals.Crystals.ParentMethods* method), 289
- `plot3d()` (*sage.categories.crystals.Crystals.ParentMethods* method), 290
- `poincare_birkhoff_witt_basis()` (*sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis.ElementMethods* method), 531
- `Pointed()` (*sage.categories.simplicial_sets.SimplicialSets.SubcategoryMethods* method), 724
- `PointedSets` (class in *sage.categories.pointed_sets*), 627
- `PolyhedralSets` (class in *sage.categories.polyhedra*), 627
- `PolynomialFunctor` (class in *sage.categories.pushout*), 141
- `PoorManMap` (class in *sage.categories.poor_man_map*), 861
- `Posets` (class in *sage.categories.posets*), 628
- `Posets.ElementMethods` (class in *sage.categories.posets*), 629
- `Posets.ParentMethods` (class in *sage.categories.posets*), 629
- `PositiveIntegerMonoid` (class in *sage.categories.examples.facade_sets*), 800
- `PositiveIntegersOrderedByDivisibilityFacade` (class in *sage.categories.examples.posets*), 832
- `PositiveIntegersOrderedByDivisibilityFacade.element_class`

(class in *sage.categories.examples.posets*), 833

post_compose() (*sage.categories.map.Map* method), 112

powers() (*sage.categories.monoids.Monoids.ElementMethods* method), 620

pre_compose() (*sage.categories.map.Map* method), 113

PrecomposedAction (class in *sage.categories.action*), 157

PrimeNumbers (class in *sage.categories.examples.sets_cat*), 840

PrimeNumbers_Abstract (class in *sage.categories.examples.sets_cat*), 841

PrimeNumbers_Abstract.Element (class in *sage.categories.examples.sets_cat*), 841

PrimeNumbers_Facade (class in *sage.categories.examples.sets_cat*), 842

PrimeNumbers_Inherits (class in *sage.categories.examples.sets_cat*), 843

PrimeNumbers_Inherits.Element (class in *sage.categories.examples.sets_cat*), 845

PrimeNumbers_Wrapper (class in *sage.categories.examples.sets_cat*), 845

PrimeNumbers_Wrapper.Element (class in *sage.categories.examples.sets_cat*), 846

principal_ideal() (*sage.categories.finite_dimensional_algebras_with_basis* method), 382

principal_lower_set() (*sage.categories.posets.Posets.ParentMethods* method), 636

principal_order_filter() (*sage.categories.posets.Posets.ParentMethods* method), 636

principal_order_ideal() (*sage.categories.posets.Posets.ParentMethods* method), 636

principal_upper_set() (*sage.categories.posets.Posets.ParentMethods* method), 636

PrincipalIdealDomains (class in *sage.categories.principal_ideal_domains*), 637

PrincipalIdealDomains.ElementMethods (class in *sage.categories.principal_ideal_domains*), 637

PrincipalIdealDomains.ParentMethods (class in *sage.categories.principal_ideal_domains*), 637

print_compare() (in module *sage.categories.sets_cat*), 712

prod() (*sage.categories.monoids.Monoids.ParentMethods* method), 620

prod() (*sage.categories.semigroups.Semigroups.ParentMethods* method), 677

product() (*sage.categories.examples.finite_monoids.IntegralMonoids* method), 811

product() (*sage.categories.examples.finite_semigroups.LeftRegularBand* method), 814

product() (*sage.categories.examples.finite_weyl_groups.SymmetricGroup* method), 816

product() (*sage.categories.examples.magnas.FreeMagma* method), 828

product() (*sage.categories.examples.semigroups.FreeSemigroup* method), 834

product() (*sage.categories.examples.semigroups.LeftZeroSemigroup* method), 835

product() (*sage.categories.magnas.Magnas.CartesianProducts.ParentMethods* method), 552

product() (*sage.categories.magnas.Magnas.ParentMethods* method), 556

product() (*sage.categories.magnas.Magnas.Subquotients.ParentMethods* method), 562

product() (*sage.categories.magmatic_algebras.MagmaticAlgebras.WithBasis* method), 569

product_by_coercion() (*sage.categories.magnas.Magnas.Realizations.ParentMethods* method), 558

product_from_element_class_mul() (*sage.categories.magnas.Magnas.ParentMethods* method), 557

product_on_basis() (*sage.categories.additive_magnas.AdditiveMagnas* method), 561

product_on_basis() (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods* method), 173

product_on_basis() (*sage.categories.additive_semigroups.AdditiveSemigroups* method), 173

product_on_basis() (*sage.categories.algebras_with_basis.AlgebrasWithBasis* method), 185

product_on_basis() (*sage.categories.examples.algebras_with_basis.FreeAlgebrasWithBasis* method), 793

product_on_basis() (*sage.categories.examples.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis* method), 803

product_on_basis() (*sage.categories.examples.graded_connected_hopf_algebras_with_basis.GradedConnectedHopfAlgebrasWithBasis* method), 817

product_on_basis() (*sage.categories.examples.hopf_algebras_with_basis.HopfAlgebrasWithBasis* method), 822

product_on_basis() (*sage.categories.examples.lie_algebras_with_basis.LieAlgebrasWithBasis* method), 827

product_on_basis() (*sage.categories.examples.with_realizations.Subsets* method), 850

product_on_basis() (*sage.categories.graded_algebras_with_basis.GradedAlgebrasWithBasis* method), 471

product_on_basis() (*sage.categories.magmatic_algebras.MagmaticAlgebras* method), 569

product_on_basis() (*sage.categories.semigroups.Semigroups.Algebras* method), 673

product_space() (*sage.categories.finite_dimensional_lie_algebras_with_basis* method), 400

read_file() (*sage.categories.finite_permutation_groups.FinitePermutationGroups* method), 434

read_polynomial() (*sage.categories.finite_permutation_groups.FinitePermutationGroups* method), 434

profile_series() (*sage.categories.finite_permutation_groups.FinitePermutationGroups.ParentMethods*), 435
 projection() (*sage.categories.filtered_algebras_with_basis.FilteredAlgebrasWithBasis.ParentMethods*), 321
 projection() (*sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis.ParentMethods*), 337
 pseudo_order() (*sage.categories.finite_monoids.FiniteMonoids.ElementMethods*), 428
 pushforward() (*sage.categories.morphism.Morphism*), 124
 pushout() (*in module sage.categories.pushout*), 146
 pushout() (*sage.categories.pushout.ConstructionFunctor*), 134
 pushout_lattice() (*in module sage.categories.pushout*), 153
Q
 q() (*sage.categories.quantum_group_representations.QuantumGroupRepresentations.ParentMethods*), 644
 q_dimension() (*sage.categories.highest_weight_crystals.HighestWeightCrystals.ParentMethods*), 500
 q_dimension() (*sage.categories.loop_crystals.KirillovReshetikhinCrystals.ParentMethods*), 542
 quantum_bruhat_graph() (*sage.categories.weyl_groups.WeylGroups.ParentMethods*), 759
 quantum_bruhat_successors() (*sage.categories.weyl_groups.WeylGroups.ElementMethods*), 754
 QuantumGroupRepresentations (class in *sage.categories.quantum_group_representations*), 644
 QuantumGroupRepresentations.ParentMethods (class in *sage.categories.quantum_group_representations*), 644
 QuantumGroupRepresentations.TensorProducts (class in *sage.categories.quantum_group_representations*), 645
 QuantumGroupRepresentations.TensorProducts.ParentMethods (class in *sage.categories.quantum_group_representations*), 645
 QuantumGroupRepresentations.WithBasis (class in *sage.categories.quantum_group_representations*), 645
 QuantumGroupRepresentations.WithBasis.ElementMethods (class in *sage.categories.quantum_group_representations*), 645
 QuantumGroupRepresentations.WithBasis.ParentMethods (class in *sage.categories.quantum_group_representations*), 647
 QuantumGroupRepresentations.WithBasis.TensorProducts (class in *sage.categories.quantum_group_representations*), 647
 QuantumGroupRepresentations.WithBasis.TensorProducts.ParentMethods (class in *sage.categories.quantum_group_representations*), 647
 quo_rem() (*sage.categories.fields.Fields.ElementMethods*), 312
 quotient() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods*), 401
 quotient() (*sage.categories.rings.Rings.ParentMethods*), 668
 quotient_module() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods*), 608
 quotient_ring() (*sage.categories.rings.Rings.ParentMethods*), 669
 QuotientFields (class in *sage.categories.quotient_fields*), 638
 QuotientFields.ElementMethods (class in *sage.categories.quotient_fields*), 638
 QuotientFields.ParentMethods (class in *sage.categories.quotient_fields*), 644
 QuotientFunctor (class in *sage.categories.pushout*), 142
 QuotientOfLeftZeroSemigroup (class in *sage.categories.examples.semigroups*), 836
 QuotientOfLeftZeroSemigroup.Element (class in *sage.categories.examples.semigroups*), 836
 Quotients() (*sage.categories.sets_cat.Sets.SubcategoryMethods*), 702
 QuotientsCategory (class in *sage.categories.quotients*), 780
R
 radical() (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods*), 383
 radical() (*sage.categories.unique_factorization_domains.UniqueFactorizationDomains.ParentMethods*), 742
 radical_basis() (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods*), 384
 radical_basis() (*sage.categories.finite_dimensional_semisimple_algebras.FiniteDimensionalSemisimpleAlgebras.ParentMethods*), 416
 radical_basis() (*sage.categories.semisimple_algebras.SemisimpleAlgebras.ParentMethods*), 685
 random_element() (*sage.categories.enumerated_sets.EnumeratedSets.ParentMethods*), 305
 random_element() (*sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods*), 417

`random_element()` (*sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods*
method), 421 `reflection_length()`
`random_element()` (*sage.categories.infinite_enumerated_sets.InfiniteEnumeratedSets.ParentMethods*
method), 511 `reflection_groups.FiniteComplex`
method), 339
`random_element()` (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods*
method), 609 (*sage.categories.weyl_groups.WeylGroups.ElementMethods*
method), 691
`random_element()` (*sage.categories.sets_cat.Sets.CartesianProducts.ParentMethods*
method), 691 `reflection_to_root()`
method), 691 (*sage.categories.weyl_groups.WeylGroups.ElementMethods*
method), 755
`random_element_of_length()` (*sage.categories.coxeter_groups.CoxeterGroups.ParentMethods*
method), 266 `reflections()` (*sage.categories.complex_reflection_or_generalized_coxeter*
method), 218 `reflections_from_w0()`
method), 302
`rank()` (*sage.categories.enumerated_sets.EnumeratedSets.ElementMethods*
method), 302 (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.Parent*
method), 305 `register_as_coercion()`
method), 305 (*sage.categories.morphism.Morphism* *method*),
method), 348 `register_as_conversion()`
method), 418 (*sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods*
method), 418 125
`rational_catalan_number()` `RegressiveCovariantConstructionCategory` (*class*
method), 352 (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.WellGeneratedInvariants*
method), 768
`realization_of()` (*sage.categories.sets_cat.Sets.Realizations.ParentMethods*
method), 697 `regular_representation()`
method), 674
`Realizations()` (*in module sage.categories.realizations*), 787 `regular_representation()`
method), 678
`Realizations()` (*sage.categories.category.Category* *method*), 41 (*sage.categories.semigroups.Semigroups.ParentMethods*
method), 678
`realizations()` (*sage.categories.sets_cat.Sets.WithRealizations.ParentMethods* (*class in*
method), 710 *sage.categories.regular_crystals*), 650
`RealizationsCategory` (*class in RegularCrystals.ElementMethods* (*class in*
sage.categories.realizations), 788 *sage.categories.regular_crystals*), 651
`reduced_word()` (*sage.categories.coxeter_groups.CoxeterGroups.RegularCrystals.MorphismMethods* (*class in*
method), 254 *sage.categories.regular_crystals*), 654
`reduced_word_graph()` `RegularCrystals.ParentMethods` (*class in*
sage.categories.coxeter_groups.CoxeterGroups.ElementMethods *sage.categories.regular_crystals*), 655
method), 255 `RegularCrystals.TensorProducts` (*class in*
sage.categories.regular_crystals), 657
`reduced_word_reverse_iterator()` (*sage.categories.coxeter_groups.CoxeterGroups.RegularCrystals* (*class in*
method), 255 *sage.categories.loop_crystals*), 549
`reduced_words()` (*sage.categories.coxeter_groups.CoxeterGroups.RegularCrystals.ElementMethods* (*class in*
method), 256 *sage.categories.loop_crystals*), 549
`reflection()` (*sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups*
method), 232 *sage.categories.regular_supercrystals*), 658
`reflection_index_set()` `RegularSuperCrystals.ElementMethods` (*class in*
sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.Parent
method), 232 *RegularSuperCrystals.TensorProducts* (*class in*
sage.categories.regular_supercrystals), 659
`reflection_length()` (*sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups*
method), 225 `required_method()` (*sage.categories.coxeter_groups.CoxeterGroups.Element*
method), 58
`reflection_length()` `residue_field()` (*sage.categories.discrete_valuation.DiscreteValuationF*
method), 296

`residue_field()` (*sage.categories.discrete_valuation.DiscreteValuation.RingElementMethods*, 297)
`residue_field()` (*sage.categories.discrete_valuation.DiscreteValuation.RingElementMethods*, 297)
`retract()` (*sage.categories.examples.finite_enumerated_sets.RTrivialSemigroupOfFiniteEnumeratedSet* in *sage.categories.r_trivial_semigroups*), 671
`retract()` (*sage.categories.examples.semigroups.QuotientOfLeftZeroSemigroup* method), 837
`retract()` (*sage.categories.sets_cat.Sets.Subquotients.ParentMethods* method), 707
`reversed()` (*sage.categories.homset.Homset* method), 121
`rhodes_radical_congruence()` (*sage.categories.finite_monoids.FiniteMonoids.ParentMethods* method), 431
`right_base_ring()` (*sage.categories.bimodules.Bimodules* method), 193
`right_domain()` (*sage.categories.action.Action* method), 156
`right_precomposition` (*sage.categories.action.PrecomposedAction* attribute), 158
`RightModules` (class in *sage.categories.right_modules*), 660
`RightModules.ElementMethods` (class in *sage.categories.right_modules*), 660
`RightModules.ParentMethods` (class in *sage.categories.right_modules*), 660
`ring()` (*sage.categories.category_types.Category_ideal* method), 853
`RingIdeals` (class in *sage.categories.ring_ideals*), 660
`Rings` (class in *sage.categories.rings*), 661
`Rings.ElementMethods` (class in *sage.categories.rings*), 662
`Rings.MorphismMethods` (class in *sage.categories.rings*), 663
`Rings.ParentMethods` (class in *sage.categories.rings*), 665
`Rings.SubcategoryMethods` (class in *sage.categories.rings*), 669
`Rngs` (class in *sage.categories.rngs*), 670
`rowmotion()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 453
`rowmotion_orbit_iter()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 453
`rowmotion_orbits()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 454
`rowmotion_orbits_plots()` (*sage.categories.finite_posets.FinitePosets.ParentMethods* method), 455
`RTrivial` (*sage.categories.semigroups.Semigroups* attribute), 680
`RTrivial()` (*sage.categories.semigroups.Semigroups.SubcategoryMethods* method), 682
`RTrivial_extra_super_categories()` (*sage.categories.semigroups.Semigroups.SubcategoryMethods* method), 550
`s()` (*sage.categories.loop_crystals.KirillovReshetikhinCrystals.ParentMethods* method), 543
sage.categories.action module, 155
sage.categories.additive_groups module, 158
sage.categories.additive_magmas module, 160
sage.categories.additive_monoids module, 171
sage.categories.additive_semigroups module, 172
sage.categories.affine_weyl_groups module, 174
sage.categories.algebra_functor module, 773
sage.categories.algebra_ideals module, 177
sage.categories.algebra_modules module, 178
sage.categories.algebras module, 178
sage.categories.algebras_with_basis module, 182
sage.categories.aperiodic_semigroups module, 187
sage.categories.associative_algebras module, 187
sage.categories.bialgebras module, 187
sage.categories.bialgebras_with_basis module, 189
sage.categories.bimodules module, 193
sage.categories.cartesian_product module, 769
sage.categories.category module, 28
sage.categories.category_cy_helper module, 859
sage.categories.category_singleton module, 856
sage.categories.category_types module, 853
sage.categories.category_with_axiom module, 64

sage.categories.classical_crystals
 module, 194
 sage.categories.coalgebras
 module, 198
 sage.categories.coalgebras_with_basis
 module, 203
 sage.categories.coercion_methods
 module, 861
 sage.categories.commutative_additive_groups
 module, 205
 sage.categories.commutative_additive_monoids
 module, 207
 sage.categories.commutative_additive_semigroups
 module, 207
 sage.categories.commutative_algebra_ideals
 module, 208
 sage.categories.commutative_algebras
 module, 208
 sage.categories.commutative_ring_ideals
 module, 209
 sage.categories.commutative_rings
 module, 209
 sage.categories.complete_discrete_valuation
 module, 213
 sage.categories.complex_reflection_groups
 module, 217
 sage.categories.complex_reflection_or_generalization_coxeter_groups
 module, 219
 sage.categories.covariant_functorial_constructions
 module, 763
 sage.categories.coxeter_group_algebras
 module, 237
 sage.categories.coxeter_groups
 module, 240
 sage.categories.crystals
 module, 269
 sage.categories.cw_complexes
 module, 293
 sage.categories.discrete_valuation
 module, 296
 sage.categories.distributive_magmas_and_additive_magmas
 module, 298
 sage.categories.division_rings
 module, 299
 sage.categories.domains
 module, 300
 sage.categories.dual
 module, 773
 sage.categories.enumerated_sets
 module, 301
 sage.categories.euclidean_domains
 module, 307
 sage.categories.examples.algebras_with_basis
 module, 793
 sage.categories.examples.commutative_additive_monoids
 module, 794
 sage.categories.examples.commutative_additive_semigroups
 module, 795
 sage.categories.examples.coxeter_groups
 module, 797
 sage.categories.examples.crystals
 module, 797
 sage.categories.examples.cw_complexes
 module, 799
 sage.categories.examples.facade_sets
 module, 800
 sage.categories.examples.finite_coxeter_groups
 module, 801
 sage.categories.examples.finite_dimensional_algebras_with_basis
 module, 803
 sage.categories.examples.finite_dimensional_lie_algebras_with_basis
 module, 804
 sage.categories.examples.finite_enumerated_sets
 module, 808
 sage.categories.examples.finite_monoids
 module, 810
 sage.categories.examples.finite_semigroups
 module, 812
 sage.categories.examples.finite_weyl_groups
 module, 814
 sage.categories.examples.graduated_coxeter_groups
 module, 816
 sage.categories.examples.graduated_modules_with_basis
 module, 818
 sage.categories.examples.graphs
 module, 820
 sage.categories.examples.hopf_algebras_with_basis
 module, 821
 sage.categories.examples.infinite_enumerated_sets
 module, 823
 sage.categories.examples.lie_algebras
 module, 824
 sage.categories.examples.lie_algebras_with_basis
 module, 826
 sage.categories.examples.magmas
 module, 827
 sage.categories.examples.manifolds
 module, 828
 sage.categories.examples.monoids
 module, 829
 sage.categories.examples.posets
 module, 831
 sage.categories.examples.semigroups
 module, 833
 sage.categories.examples.semigroups_cython
 module, 838
 sage.categories.examples.sets_cat
 module, 840

[sage.categories.examples.sets_with_grading](#)
 module, 846
[sage.categories.examples.with_realizations](#)
 module, 847
[sage.categories.facade_sets](#)
 module, 760
[sage.categories.fields](#)
 module, 309
[sage.categories.filtered_algebras](#)
 module, 314
[sage.categories.filtered_algebras_with_basis](#)
 module, 315
[sage.categories.filtered_modules](#)
 module, 322
[sage.categories.filtered_modules_with_basis](#)
 module, 324
[sage.categories.finite_complex_reflection_groups](#)
 module, 338
[sage.categories.finite_coxeter_groups](#)
 module, 355
[sage.categories.finite_crystals](#)
 module, 367
[sage.categories.finite_dimensional_algebras_with_basis](#)
 module, 367
[sage.categories.finite_dimensional_bialgebras_with_basis](#)
 module, 386
[sage.categories.finite_dimensional_coalgebras_with_basis](#)
 module, 386
[sage.categories.finite_dimensional_graded_lie_algebras_with_basis](#)
 module, 387
[sage.categories.finite_dimensional_hopf_algebras_with_basis](#)
 module, 388
[sage.categories.finite_dimensional_lie_algebras_with_basis](#)
 module, 389
[sage.categories.finite_dimensional_modules_with_basis](#)
 module, 405
[sage.categories.finite_dimensional_nilpotent_lie_algebras_with_basis](#)
 module, 413
[sage.categories.finite_dimensional_semisimple_lie_algebras_with_basis](#)
 module, 414
[sage.categories.finite_enumerated_sets](#)
 module, 416
[sage.categories.finite_fields](#)
 module, 422
[sage.categories.finite_groups](#)
 module, 423
[sage.categories.finite_lattice_posets](#)
 module, 425
[sage.categories.finite_monoids](#)
 module, 428
[sage.categories.finite_permutation_groups](#)
 module, 432
[sage.categories.finite_posets](#)
 module, 436
[sage.categories.finite_semigroups](#)
 module, 457
[sage.categories.finite_sets](#)
 module, 459
[sage.categories.finite_weyl_groups](#)
 module, 460
[sage.categories.finitely_generated_lambda_bracket_algebras](#)
 module, 461
[sage.categories.finitely_generated_lie_conformal_algebras](#)
 module, 462
[sage.categories.finitely_generated_magmas](#)
 module, 463
[sage.categories.finitely_generated_semigroups](#)
 module, 464
[sage.categories.function_fields](#)
 module, 466
[sage.categories.functor](#)
 module, 98
[sage.categories.g_sets](#)
 module, 467
[sage.categories.gcd_domains](#)
 module, 467
[sage.categories.generalized_coxeter_groups](#)
 module, 468
[sage.categories.graded_algebras](#)
 module, 469
[sage.categories.graded_algebras_with_basis](#)
 module, 470
[sage.categories.graded_bialgebras](#)
 module, 472
[sage.categories.graded_bialgebras_with_basis](#)
 module, 472
[sage.categories.graded_coalgebras](#)
 module, 472
[sage.categories.graded_coalgebras_with_basis](#)
 module, 473
[sage.categories.graded_hopf_algebras](#)
 module, 474
[sage.categories.graded_hopf_algebras_with_basis](#)
 module, 474
[sage.categories.graded_lie_algebras](#)
 module, 475
[sage.categories.graded_lie_algebras_with_basis](#)
 module, 476
[sage.categories.graded_lie_conformal_algebras](#)
 module, 477
[sage.categories.graded_modules](#)
 module, 478
[sage.categories.graded_modules_with_basis](#)
 module, 479
[sage.categories.graphs](#)
 module, 480
[sage.categories.group_algebras](#)
 module, 482

`sage.categories.groupoid`
module, 487

`sage.categories.groups`
module, 487

`sage.categories.h_trivial_semigroups`
module, 510

`sage.categories.hecke_modules`
module, 496

`sage.categories.highest_weight_crystals`
module, 497

`sage.categories.homset`
module, 114

`sage.categories.homsets`
module, 782

`sage.categories.hopf_algebras`
module, 504

`sage.categories.hopf_algebras_with_basis`
module, 506

`sage.categories.infinite_enumerated_sets`
module, 511

`sage.categories.integral_domains`
module, 512

`sage.categories.isomorphic_objects`
module, 781

`sage.categories.j_trivial_semigroups`
module, 512

`sage.categories.kac_moody_algebras`
module, 513

`sage.categories.l_trivial_semigroups`
module, 550

`sage.categories.lambda_bracket_algebras`
module, 514

`sage.categories.lambda_bracket_algebras_with_basis`
module, 516

`sage.categories.lattice_posets`
module, 517

`sage.categories.left_modules`
module, 518

`sage.categories.lie_algebras`
module, 519

`sage.categories.lie_algebras_with_basis`
module, 529

`sage.categories.lie_conformal_algebras`
module, 531

`sage.categories.lie_conformal_algebras_with_basis`
module, 535

`sage.categories.lie_groups`
module, 537

`sage.categories.loop_crystals`
module, 537

`sage.categories.magmas`
module, 551

`sage.categories.magmas_and_additive_magmas`
module, 565

`sage.categories.magmatic_algebras`
module, 567

`sage.categories.manifolds`
module, 570

`sage.categories.map`
module, 105

`sage.categories.matrix_algebras`
module, 574

`sage.categories.metric_spaces`
module, 575

`sage.categories.modular_abelian_varieties`
module, 579

`sage.categories.modules`
module, 580

`sage.categories.modules_with_basis`
module, 590

`sage.categories.monoid_algebras`
module, 616

`sage.categories.monoids`
module, 616

`sage.categories.morphism`
module, 122

`sage.categories.number_fields`
module, 622

`sage.categories.objects`
module, 624

`sage.categories.partially_ordered_monoids`
module, 626

`sage.categories.permutation_groups`
module, 626

`sage.categories.pointed_sets`
module, 627

`sage.categories.polyhedra`
module, 627

`sage.categories.poor_man_map`
module, 861

`sage.categories.posets`
module, 628

`sage.categories.primers`
module, 1

`sage.categories.principal_ideal_domains`
module, 637

`sage.categories.pushout`
module, 126

`sage.categories.quantum_group_representations`
module, 644

`sage.categories.quotient_fields`
module, 638

`sage.categories.quotients`
module, 780

`sage.categories.r_trivial_semigroups`
module, 671

`sage.categories.realizations`
module, 786

- sage.categories.regular_crystals
module, 650
- sage.categories.regular_supercrystals
module, 658
- sage.categories.right_modules
module, 660
- sage.categories.ring_ideals
module, 660
- sage.categories.rings
module, 661
- sage.categories.rngs
module, 670
- sage.categories.schemes
module, 671
- sage.categories.semigroups
module, 672
- sage.categories.semirings
module, 684
- sage.categories.semisimple_algebras
module, 684
- sage.categories.sets_cat
module, 686
- sage.categories.sets_with_grading
module, 712
- sage.categories.sets_with_partial_maps
module, 715
- sage.categories.shephard_groups
module, 715
- sage.categories.signed_tensor
module, 772
- sage.categories.simplicial_complexes
module, 716
- sage.categories.simplicial_sets
module, 717
- sage.categories.subobjects
module, 781
- sage.categories.subquotients
module, 780
- sage.categories.super_algebras
module, 724
- sage.categories.super_algebras_with_basis
module, 726
- sage.categories.super_hopf_algebras_with_basis
module, 727
- sage.categories.super_lie_conformal_algebras
module, 727
- sage.categories.super_modules
module, 729
- sage.categories.super_modules_with_basis
module, 731
- sage.categories.supercommutative_algebras
module, 733
- sage.categories.supercrystals
module, 734
- sage.categories.tensor
module, 771
- sage.categories.topological_spaces
module, 739
- sage.categories.triangular_kac_moody_algebras
module, 740
- sage.categories.tutorial
module, 102
- sage.categories.unique_factorization_domains
module, 742
- sage.categories.unital_algebras
module, 744
- sage.categories.vector_bundles
module, 746
- sage.categories.vector_spaces
module, 747
- sage.categories.weyl_groups
module, 751
- sage.categories.with_realizations
module, 788
- scaling_factors() (*sage.categories.crystals.CrystalMorphism*
method), 273
- Schemes (*class in sage.categories.schemes*), 671
- Schemes_over_base (*class in sage.categories.schemes*),
672
- Section (*class in sage.categories.map*), 114
- section() (*sage.categories.map.FormalCompositeMap*
method), 108
- section() (*sage.categories.map.Map* method), 113
- section() (*sage.categories.morphism.IdentityMorphism*
method), 123
- semidirect_product()
(*sage.categories.groups.Groups.ParentMethods*
method), 494
- semigroup_generators()
(*sage.categories.complex_reflection_or_generalized_coxeter_group*
method), 234
- semigroup_generators()
(*sage.categories.examples.finite_monoids.IntegerModMonoid*
method), 811
- semigroup_generators()
(*sage.categories.examples.finite_semigroups.LeftRegularBand*
method), 814
- semigroup_generators()
(*sage.categories.examples.semigroups.FreeSemigroup*
method), 834
- semigroup_generators()
(*sage.categories.finite_groups.FiniteGroups.ParentMethods*
method), 424
- semigroup_generators()
(*sage.categories.finitely_generated_semigroups.FinitelyGenerated*
method), 465
- semigroup_generators()
(*sage.categories.monoids.Monoids.ParentMethods*

method), 620

semigroup_generators() (sage.categories.semigroups.Semigroups.ParentMethods method), 678

semigroup_generators() (sage.categories.semigroups.Semigroups.Quotients.ParentMethods method), 680

Semigroups (class in sage.categories.semigroups), 672

Semigroups.Algebras (class in sage.categories.semigroups), 672

Semigroups.Algebras.ParentMethods (class in sage.categories.semigroups), 672

Semigroups.CartesianProducts (class in sage.categories.semigroups), 674

Semigroups.ElementMethods (class in sage.categories.semigroups), 675

Semigroups.ParentMethods (class in sage.categories.semigroups), 675

Semigroups.Quotients (class in sage.categories.semigroups), 679

Semigroups.Quotients.ParentMethods (class in sage.categories.semigroups), 679

Semigroups.SubcategoryMethods (class in sage.categories.semigroups), 680

Semigroups.Subquotients (class in sage.categories.semigroups), 682

Semirings (class in sage.categories.semirings), 684

Semisimple (sage.categories.algebras.Algebras attribute), 180

Semisimple() (sage.categories.algebras.Algebras.SubcategoryMethods method), 180

semisimple_quotient() (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.ParentMethods method), 385

SemisimpleAlgebras (class in sage.categories.semisimple_algebras), 684

SemisimpleAlgebras.FiniteDimensional (class in sage.categories.semisimple_algebras), 685

SemisimpleAlgebras.ParentMethods (class in sage.categories.semisimple_algebras), 685

set_base_point() (sage.categories.simplicial_sets.SimplicialSets.ParentMethods method), 719

SetMorphism (class in sage.categories.morphism), 125

Sets (class in sage.categories.sets_cat), 686

Sets.Algebras (class in sage.categories.sets_cat), 688

Sets.Algebras.ParentMethods (class in sage.categories.sets_cat), 688

Sets.CartesianProducts (class in sage.categories.sets_cat), 689

Sets.CartesianProducts.ElementMethods (class in sage.categories.sets_cat), 689

Sets.CartesianProducts.ParentMethods (class in sage.categories.sets_cat), 690

Sets.ElementMethods (class in sage.categories.sets_cat), 692

Sets.Infinite (class in sage.categories.sets_cat), 692

Sets.Infinite.ParentMethods (class in sage.categories.sets_cat), 692

Sets.IsomorphicObjects (class in sage.categories.sets_cat), 693

Sets.IsomorphicObjects.ParentMethods (class in sage.categories.sets_cat), 693

Sets.MorphismMethods (class in sage.categories.sets_cat), 693

Sets.ParentMethods (class in sage.categories.sets_cat), 694

Sets.Quotients (class in sage.categories.sets_cat), 697

Sets.Quotients.ParentMethods (class in sage.categories.sets_cat), 697

Sets.Realizations (class in sage.categories.sets_cat), 697

Sets.Realizations.ParentMethods (class in sage.categories.sets_cat), 697

Sets.SubcategoryMethods (class in sage.categories.sets_cat), 697

Sets.Subobjects (class in sage.categories.sets_cat), 706

Sets.Subobjects.ParentMethods (class in sage.categories.sets_cat), 706

Sets.Subquotients (class in sage.categories.sets_cat), 706

Sets.Subquotients.ElementMethods (class in sage.categories.sets_cat), 706

Sets.Subquotients.ParentMethods (class in sage.categories.sets_cat), 707

Sets.WithRealizations (class in sage.categories.sets_cat), 708

Sets.WithRealizations.ParentMethods (class in sage.categories.sets_cat), 708

Sets.WithRealizations.ParentMethods.Realizations (class in sage.categories.sets_cat), 708

SetsWithGrading (class in sage.categories.sets_with_grading), 712

SetsWithGrading.ParentMethods (class in sage.categories.sets_with_grading), 713

SetsWithPartialMaps (class in sage.categories.sets_with_partial_maps), 715

shard_poset() (sage.categories.finite_coxeter_groups.FiniteCoxeterGroups method), 363

ShephardGroups (class in sage.categories.shephard_groups), 715

sign_representation() (sage.categories.coxeter_groups.CoxeterGroups.ParentMethods method), 266

SignedTensorProductFunctor (class in sage.categories.signed_tensor), 772

SignedTensorProducts()

<code>(sage.categories.graded_algebras.GradedAlgebras.SimplicialSets.ParentMethods</code> (class in <code>sage.categories.graded_algebras.GradedAlgebras.SimplicialSets</code>), 470	<code>smash_product()</code> (sage.categories.simplicial_sets.SimplicialSets.Pointed.Finite.ParentMethods (class in sage.categories.simplicial_sets), 719
<code>SignedTensorProducts()</code> (sage.categories.graded_coalgebras.GradedCoalgebras.SubcategoryMethods (class in sage.categories.graded_coalgebras.GradedCoalgebras.SubcategoryMethods), 473	<code>smooth()</code> (sage.categories.manifolds.Manifolds.SubcategoryMethods (class in sage.categories.manifolds.Manifolds.SubcategoryMethods), 573
<code>SignedTensorProducts()</code> (sage.categories.signed_tensor.SignedTensorProducts.SimplicialSets.Pointed.Finite.ParentMethods (class in sage.categories.signed_tensor.SignedTensorProducts.SimplicialSets.Pointed.Finite.ParentMethods), 772	<code>Smooth()</code> (sage.categories.vector_bundles.VectorBundles.SubcategoryMethods (class in sage.categories.vector_bundles.VectorBundles.SubcategoryMethods), 746
<code>SignedTensorProductsCategory</code> (class in <code>sage.categories.signed_tensor</code>), 772	<code>some_elements()</code> (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods (class in sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods), 305
<code>simple_module_parameterization()</code> (sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.Cellular.ParentMethods (class in sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis.Cellular.ParentMethods), 370	<code>some_elements()</code> (sage.categories.examples.semigroups.LeftZeroSemigroups.ParentMethods (class in sage.categories.examples.semigroups.LeftZeroSemigroups.ParentMethods), 835
<code>simple_projection()</code> (sage.categories.coxeter_groups.CoxeterGroups.ParentMethods (class in sage.categories.coxeter_groups.CoxeterGroups.ParentMethods), 266	<code>some_elements()</code> (sage.categories.examples.semigroups.QuotientOfLeftZeroSemigroups.ParentMethods (class in sage.categories.examples.semigroups.QuotientOfLeftZeroSemigroups.ParentMethods), 837
<code>simple_projections()</code> (sage.categories.coxeter_groups.CoxeterGroups.ParentMethods (class in sage.categories.coxeter_groups.CoxeterGroups.ParentMethods), 267	<code>some_elements()</code> (sage.categories.examples.semigroups.QuotientOfLeftZeroSemigroups.ParentMethods (class in sage.categories.examples.semigroups.QuotientOfLeftZeroSemigroups.ParentMethods), 842
<code>simple_reflection()</code> (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods (class in sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods), 234	<code>some_elements()</code> (sage.categories.finite_groups.FiniteGroups.ParentMethods (class in sage.categories.finite_groups.FiniteGroups.ParentMethods), 462
<code>simple_reflection()</code> (sage.categories.examples.finite_weyl_groups.SymmetricGroups.ParentMethods (class in sage.categories.examples.finite_weyl_groups.SymmetricGroups.ParentMethods), 816	<code>some_elements()</code> (sage.categories.finitely_generated_lambda_bracket_algebras.FinitelyGeneratedLambdaBracketAlgebras.ParentMethods (class in sage.categories.finitely_generated_lambda_bracket_algebras.FinitelyGeneratedLambdaBracketAlgebras.ParentMethods), 462
<code>simple_reflection_orders()</code> (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods (class in sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods), 235	<code>some_elements()</code> (sage.categories.finitely_generated_lie_conformal_algebras.FinitelyGeneratedLieConformalAlgebras.ParentMethods (class in sage.categories.finitely_generated_lie_conformal_algebras.FinitelyGeneratedLieConformalAlgebras.ParentMethods), 462
<code>simple_reflections()</code> (sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods (class in sage.categories.complex_reflection_or_generalized_coxeter_groups.ComplexReflectionOrGeneralizedCoxeterGroups.ParentMethods), 235	<code>some_elements()</code> (sage.categories.finitely_generated_semigroups.FinitelyGeneratedSemigroups.ParentMethods (class in sage.categories.finitely_generated_semigroups.FinitelyGeneratedSemigroups.ParentMethods), 464
<code>SimplicialComplexes</code> (class in <code>sage.categories.simplicial_complexes</code>), 716	<code>some_elements()</code> (sage.categories.sets_cat.Sets.ParentMethods (class in sage.categories.sets_cat.Sets.ParentMethods), 696
<code>SimplicialComplexes.Connected</code> (class in <code>sage.categories.simplicial_complexes</code>), 716	<code>special_node()</code> (sage.categories.affine_weyl_groups.AffineWeylGroups.ParentMethods (class in sage.categories.affine_weyl_groups.AffineWeylGroups.ParentMethods), 176
<code>SimplicialComplexes.Finite</code> (class in <code>sage.categories.simplicial_complexes</code>), 716	<code>squarefree_part()</code> (sage.categories.unique_factorization_domains.UniqueFactorizationDomains.ParentMethods (class in sage.categories.unique_factorization_domains.UniqueFactorizationDomains.ParentMethods), 743
<code>SimplicialComplexes.Finite.ParentMethods</code> (class in <code>sage.categories.simplicial_complexes</code>), 716	<code>standard_coxeter_elements()</code> (sage.categories.coxeter_groups.CoxeterGroups.ParentMethods (class in sage.categories.coxeter_groups.CoxeterGroups.ParentMethods), 268
<code>SimplicialComplexes.ParentMethods</code> (class in <code>sage.categories.simplicial_complexes</code>), 716	<code>standard_coxeter_elements()</code> (sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods (class in sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods), 354
<code>SimplicialComplexes.SubcategoryMethods</code> (class in <code>sage.categories.simplicial_complexes</code>), 717	<code>stanley_symmetric_function()</code> (sage.categories.weyl_groups.WeylGroups.ElementMethods (class in sage.categories.weyl_groups.WeylGroups.ElementMethods), 756
<code>SimplicialSets</code> (class in <code>sage.categories.simplicial_sets</code>), 717	<code>stanley_symmetric_function_as_polynomial()</code> (sage.categories.weyl_groups.WeylGroups.ElementMethods (class in sage.categories.weyl_groups.WeylGroups.ElementMethods), 757
<code>SimplicialSets.Finite</code> (class in <code>sage.categories.simplicial_sets</code>), 718	
<code>SimplicialSets.Homsets</code> (class in <code>sage.categories.simplicial_sets</code>), 718	
<code>SimplicialSets.Homsets.Endset</code> (class in <code>sage.categories.simplicial_sets</code>), 718	
<code>SimplicialSets.Homsets.Endset.ParentMethods</code> (class in <code>sage.categories.simplicial_sets</code>), 718	

stembridgeDel_depth() (sage.categories.regular_crystals.RegularCrystals.ElementMethods method), 678
 (sage.categories.regular_crystals.RegularCrystals.SubsetMethods method), 652
 (sage.categories.sets_with_grading.SetsWithGrading.ParentMethods method), 714

stembridgeDel_rise() SubsetAlgebra (class in (sage.categories.regular_crystals.RegularCrystals.ElementMethods method), 653
 (sage.categories.regular_crystals.RegularCrystals.ElementMethods method), 847

stembridgeDelta_depth() SubsetAlgebra.Bases (class in (sage.categories.regular_crystals.RegularCrystals.ElementMethods method), 653
 (sage.categories.regular_crystals.RegularCrystals.ElementMethods method), 849

stembridgeDelta_rise() SubsetAlgebra.Bases.ParentMethods (class in (sage.categories.regular_crystals.RegularCrystals.ElementMethods method), 653
 (sage.categories.regular_crystals.RegularCrystals.ElementMethods method), 849

stembridgeTriple() (sage.categories.regular_crystals.RegularCrystals.ElementMethods method), 654
 (sage.categories.regular_crystals.RegularCrystals.SubsetAlgebra.Fundamental method), 870

step() (sage.categories.finite_dimensional_nilpotent_lie_algebras_with_basis.FiniteDimensionalNilpotentLieAlgebrasWithBasis.ParentMethods method), 414
 (sage.categories.lie_algebras.LieAlgebras.Nilpotent.ParentMethods method), 851

step() (sage.categories.lie_algebras.LieAlgebras.Nilpotent.ParentMethods method), 522
 (sage.categories.sets_with_grading.SetsWithGrading.ParentMethods method), 851

Stratified() (sage.categories.graded_lie_algebras.GradedLieAlgebrasSubcategoryMethods (class in (sage.categories.graded_lie_algebras.GradedLieAlgebrasSubcategoryMethods (class in (sage.categories.sets_with_grading.SetsWithGrading.ParentMethods method), 476
 (sage.categories.sets_with_grading.SetsWithGrading.ParentMethods method), 851

string_parameters() (sage.categories.highest_weight_crystals.HighestWeightCrystals.ParentMethods method), 498
 (sage.categories.pushout.PushoutMethod method), 143

structure() (sage.categories.category.Category method), 58
 succ_generators() (sage.categories.finitely_generated_semigroups.FinitelyGeneratedSemigroups.ParentMethods method), 465

structure_coefficients() (sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods method), 402
 sum() (sage.categories.additive_monoids.AdditiveMonoids.ParentMethods method), 514

subalgebra() (sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebra method), 807
 sum_of_monomials() (sage.categories.modules_with_basis.ModulesWithBasis method), 514

subalgebra() (sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods method), 402
 sum_of_terms() (sage.categories.modules_with_basis.ModulesWithBasis method), 514

subalgebra() (sage.categories.lie_algebras.LieAlgebras.ParentMethods method), 527
 summation() (sage.categories.additive_magmas.AdditiveMagmas.ParentMethods method), 168

subcategory_class() (sage.categories.category.Category method), 59
 summation() (sage.categories.examples.commutative_additive_semigroups.CommutativeAdditiveSemigroups.ParentMethods method), 797

subcrystal() (sage.categories.crystals.Crystals.ElementMethods method), 279
 summation_from_element_class_add() (sage.categories.additive_magmas.AdditiveMagmas.ParentMethods method), 169

subcrystal() (sage.categories.crystals.Crystals.ParentMethods method), 290
 Super (sage.categories.algebras.Algebras attribute), 181

submodule() (sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods method), 610
 Super (sage.categories.algebras_with_basis.AlgebrasWithBasis attribute), 185

submonoid() (sage.categories.monoids.Monoids.ParentMethods method), 621
 Super (sage.categories.hopf_algebras_with_basis.HopfAlgebrasWithBasis attribute), 509

Subobjects() (sage.categories.sets_cat.Sets.SubcategoryMethods method), 703
 Super (sage.categories.lie_conformal_algebras.LieConformalAlgebras attribute), 534

SubobjectsCategory (class in (sage.categories.sets_cat.Sets.SubcategoryMethods method), 703
 Super (sage.categories.modules.Modules attribute), 589

Subquotients() (sage.categories.sets_cat.Sets.SubcategoryMethods method), 704
 Super (sage.categories.modules_with_basis.ModulesWithBasis attribute), 613

SubquotientsCategory (class in (sage.categories.sets_cat.Sets.SubcategoryMethods method), 704
 Super () (sage.categories.graded_lie_conformal_algebras.GradedLieConformalAlgebras attribute), 534

SubquotientsCategory (class in (sage.categories.subquotients), 780
 Super () (sage.categories.modules.Modules.SubcategoryMethods method), 586

subsemigroup() (sage.categories.semigroups.Semigroups.ParentMethods method), 170
 super_categories() (sage.categories.additive_magmas.AdditiveMagmas attribute), 534

`super_categories()` (*sage.categories.magnas.Magnas* `super_categories()` (*sage.categories.sets_with_grading.SetsWithGrading*
method), 565 *method*), 714
`super_categories()` (*sage.categories.magnas_and_additive_magnas.AdditiveMagnas* `super_categories()` (*sage.categories.sets_with_partial_maps.SetsWithP*
method), 567 *method*), 715
`super_categories()` (*sage.categories.magmatic_algebras.MagmaticAlgebras* `super_categories()` (*sage.categories.shephard_groups.ShephardGroups*
method), 570 *method*), 715
`super_categories()` (*sage.categories.manifolds.ComplexManifolds* `super_categories()` (*sage.categories.simplicial_complexes.SimplicialCo*
method), 570 *method*), 717
`super_categories()` (*sage.categories.manifolds.Manifolds* `super_categories()` (*sage.categories.simplicial_sets.SimplicialSets*
method), 574 *method*), 724
`super_categories()` (*sage.categories.matrix_algebras.MatrixAlgebras* `super_categories()` (*sage.categories.super_modules.SuperModules*
method), 574 *method*), 730
`super_categories()` (*sage.categories.modular_abelian_superalgebras.ModularAbelianSuperAlgebras* `super_categories()` (*sage.categories.supercrystals.SuperCrystals*
method), 579 *method*), 738
`super_categories()` (*sage.categories.modules.Modules* `super_categories()` (*sage.categories.triangular_kac_moody_algebras.T*
method), 589 *method*), 742
`super_categories()` (*sage.categories.number_fields.NumberFields* `super_categories()` (*sage.categories.unique_factorization_domains.Uni*
method), 624 *method*), 744
`super_categories()` (*sage.categories.objects.Objects* `super_categories()` (*sage.categories.vector_bundles.VectorBundles*
method), 625 *method*), 747
`super_categories()` (*sage.categories.partially_ordered_superalgebras.PartiallyOrderedSuperAlgebras* `super_categories()` (*sage.categories.vector_spaces.VectorSpaces*
method), 626 *method*), 750
`super_categories()` (*sage.categories.permutation_groups.PermutationGroups* `super_categories()` (*sage.categories.weyl_groups.WeylGroups*
method), 627 *method*), 760
`super_categories()` (*sage.categories.pointed_sets.PointedSets* `SuperAlgebras` (class in
method), 627 *sage.categories.super_algebras*), 724
`super_categories()` (*sage.categories.polyhedra.Polyhedra* `SuperAlgebras.ParentMethods` (class in
method), 627 *sage.categories.super_algebras*), 724
`super_categories()` (*sage.categories.posets.Posets* `SuperAlgebras.SignedTensorProducts` (class in
method), 637 *sage.categories.super_algebras*), 725
`super_categories()` (*sage.categories.principal_ideal_domains.PrincipalIdealDomains* `SuperAlgebras.SubcategoryMethods` (class in
method), 638 *sage.categories.super_algebras*), 725
`super_categories()` (*sage.categories.quantum_group_representations.QuantumGroupRepresentations* `SuperAlgebrasWithBasis` (class in
method), 650 *sage.categories.super_algebras_with_basis*),
`super_categories()` (*sage.categories.quotient_fields.QuotientFields* `SuperAlgebrasWithBasis.ParentMethods` (class in
method), 644 *sage.categories.super_algebras_with_basis*),
`super_categories()` (*sage.categories.regular_crystals.RegularCrystals* `SuperAlgebrasWithBasis.SignedTensorProducts`
method), 658 *(class in sage.categories.super_algebras_with_basis)*,
`super_categories()` (*sage.categories.regular_supercrystals.RegularSupercrystals* `SuperAlgebrasWithBasis.SignedTensorProducts`
method), 659 *726*
`super_categories()` (*sage.categories.right_modules.RightModules* `Supercocommutative()`
method), 660 *(sage.categories.coalgebras.Coalgebras.Super.SubcategoryMethod*
`super_categories()` (*sage.categories.ring_ideals.RingIdeals* *method*), 201
`super_categories()` (*sage.categories.schemes.Schemes* `Supercommutative(sage.categories.super_algebras.SuperAlgebras`
method), 671 *attribute)*, 725
`super_categories()` (*sage.categories.schemes.Schemes_Supercommutative* `Supercommutative()` (*sage.categories.algebras.Algebras.SubcategoryMe*
method), 672 *method*), 181
`super_categories()` (*sage.categories.semisimple_algebras.SemisimpleAlgebras* `SupercommutativeAlgebras()` (*sage.categories.super_algebras.SuperAlgebras.Sub*
method), 685 *method*), 725
`super_categories()` (*sage.categories.sets_cat.Sets* `SupercommutativeAlgebras` (class in
method), 711 *sage.categories.supercommutative_algebras*),
`super_categories()` (*sage.categories.sets_cat.Sets.WithRealizations* `SupercommutativeAlgebras.ParentMethods.Realizations`
method), 708 *SupercommutativeAlgebras.SignedTensorProducts*

(class in *sage.categories.supercommutative_algebras*), 733

733

SupercommutativeAlgebras.WithBasis (class in *sage.categories.supercommutative_algebras*), 734

SupercommutativeAlgebras.WithBasis.ParentMethods (class in *sage.categories.supercommutative_algebras*), 734

SuperCrystals (class in *sage.categories.supercrystals*), 734

SuperCrystals.Finite (class in *sage.categories.supercrystals*), 734

SuperCrystals.Finite.ElementMethods (class in *sage.categories.supercrystals*), 734

SuperCrystals.Finite.ParentMethods (class in *sage.categories.supercrystals*), 735

SuperCrystals.ParentMethods (class in *sage.categories.supercrystals*), 738

SuperCrystals.TensorProducts (class in *sage.categories.supercrystals*), 738

SuperHopfAlgebrasWithBasis (class in *sage.categories.super_hopf_algebras_with_basis*), 727

SuperHopfAlgebrasWithBasis.ParentMethods (class in *sage.categories.super_hopf_algebras_with_basis*), 727

SuperLieConformalAlgebras (class in *sage.categories.super_lie_conformal_algebras*), 727

SuperLieConformalAlgebras.ElementMethods (class in *sage.categories.super_lie_conformal_algebras*), 728

SuperLieConformalAlgebras.Graded (class in *sage.categories.super_lie_conformal_algebras*), 728

SuperLieConformalAlgebras.ParentMethods (class in *sage.categories.super_lie_conformal_algebras*), 728

SuperModules (class in *sage.categories.super_modules*), 729

SuperModules.ElementMethods (class in *sage.categories.super_modules*), 729

SuperModules.ParentMethods (class in *sage.categories.super_modules*), 730

SuperModulesCategory (class in *sage.categories.super_modules*), 730

SuperModulesWithBasis (class in *sage.categories.super_modules_with_basis*), 731

SuperModulesWithBasis.ElementMethods (class in *sage.categories.super_modules_with_basis*), 732

SuperModulesWithBasis.ParentMethods (class in *sage.categories.super_modules_with_basis*), 733

support() (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods* method), 257

support() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods* method), 598

support_of_term() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods* method), 598

supsets() (*sage.categories.examples.with_realizations.SubsetAlgebra* method), 852

Surface (class in *sage.categories.examples.cw_complexes*), 799

Surface.Element (class in *sage.categories.examples.cw_complexes*), 799

SymmetricGroup (class in *sage.categories.examples.finite_weyl_groups*), 814

SymmetricGroup.Element (class in *sage.categories.examples.finite_weyl_groups*), 815

T

T() (*sage.categories.lambda_bracket_algebras.LambdaBracketAlgebras.ElementMethods* method), 514

tensor() (in module *sage.categories.tensor*), 771

tensor() (*sage.categories.crystals.Crystals.ElementMethods* method), 279

tensor() (*sage.categories.crystals.Crystals.ParentMethods* method), 291

tensor() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods* method), 599

tensor() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethods* method), 613

tensor() (*sage.categories.quantum_group_representations.QuantumGroupRepresentations* method), 647

tensor() (*sage.categories.super_algebras.SuperAlgebras.ParentMethods* method), 724

tensor() (*sage.categories.supercrystals.SuperCrystals.ParentMethods* method), 738

tensor_signed (in module *sage.categories.signed_tensor*), 772

tensor_square() (*sage.categories.modules.Modules.ParentMethods* method), 584

TensorProductFunctor (class in *sage.categories.tensor*), 771

TensorProducts() (*sage.categories.crystals.Crystals.SubcategoryMethods* method), 292

TensorProducts() (*sage.categories.modules.Modules.SubcategoryMethods* method), 587

TensorProducts() (*sage.categories.tensor.TensorProductsCategory* method), 771

TensorProductsCategory (class in *sage.categories.tensor*), 771

term() (*sage.categories.modules_with_basis.ModulesWithBasis.ParentMethod*), 613

terms() (*sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods*), 599

TestObjects (class in *sage.categories.category_with_axiom*), 95

TestObjects.Commutative (class in *sage.categories.category_with_axiom*), 95

TestObjects.Commutative.Facade (class in *sage.categories.category_with_axiom*), 95

TestObjects.Commutative.Finite (class in *sage.categories.category_with_axiom*), 95

TestObjects.Commutative.FiniteDimensional (class in *sage.categories.category_with_axiom*), 95

TestObjects.FiniteDimensional (class in *sage.categories.category_with_axiom*), 95

TestObjects.FiniteDimensional.Finite (class in *sage.categories.category_with_axiom*), 95

TestObjects.FiniteDimensional.Unital (class in *sage.categories.category_with_axiom*), 95

TestObjects.FiniteDimensional.Unital.Commutative (class in *sage.categories.category_with_axiom*), 95

TestObjects.Unital (class in *sage.categories.category_with_axiom*), 95

TestObjectsOverBaseRing (class in *sage.categories.category_with_axiom*), 95

TestObjectsOverBaseRing.Commutative (class in *sage.categories.category_with_axiom*), 95

TestObjectsOverBaseRing.Commutative.Facade (class in *sage.categories.category_with_axiom*), 95

TestObjectsOverBaseRing.Commutative.Finite (class in *sage.categories.category_with_axiom*), 95

TestObjectsOverBaseRing.Commutative.FiniteDimensional (class in *sage.categories.category_with_axiom*), 95

TestObjectsOverBaseRing.FiniteDimensional (class in *sage.categories.category_with_axiom*), 96

TestObjectsOverBaseRing.FiniteDimensional.Finite (class in *sage.categories.category_with_axiom*), 96

TestObjectsOverBaseRing.FiniteDimensional.Unital (class in *sage.categories.category_with_axiom*), 96

TestObjectsOverBaseRing.FiniteDimensional.Unital.Commutative (class in *sage.categories.category_with_axiom*), 96

TestObjectsOverBaseRing.Unital (class in *sage.categories.category_with_axiom*), 96

the_answer() (*sage.categories.examples.semigroups.QuotientOfLeftClassSemigroup*), 837

then() (*sage.categories.map.FormalCompositeMap*), 613

to_graded_conversion() (*sage.categories.filtered_algebras_with_basis.FilteredAlgebrasWithBasis*), 322

to_graded_conversion() (*sage.categories.filtered_modules_with_basis.FilteredModulesWithBasis*), 338

to_highest_weight() (*sage.categories.crystals.Crystals.ElementMethods*), 280

to_lowest_weight() (*sage.categories.crystals.Crystals.ElementMethods*), 280

to_matrix() (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups*), 340

to_matrix() (*sage.categories.finite_dimensional_algebras_with_basis.FiniteDimensionalAlgebrasWithBasis*), 372

to_module_generator() (*sage.categories.crystals.CrystalMorphismByGenerators*), 274

to_vector() (*sage.categories.examples.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis*), 805

to_vector() (*sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis*), 389

to_vector() (*sage.categories.lie_algebras.LieAlgebras.ElementMethods*), 521

to_vector() (*sage.categories.lie_algebras_with_basis.LieAlgebrasWithBasis*), 529

toggling_orbit_iter() (*sage.categories.finite_posets.FinitePosets.ParentMethods*), 455

toggling_orbits() (*sage.categories.finite_posets.FinitePosets.ParentMethods*), 456

toggling_orbits_plots() (*sage.categories.finite_posets.FinitePosets.ParentMethods*), 457

Topological (*sage.categories.sets_cat.Sets* attribute), 708

Topological() (*sage.categories.sets_cat.Sets.SubcategoryMethods*), 706

TopologicalSpaces (class in *sage.categories.topological_spaces*), 739

TopologicalSpaces.CartesianProducts (class in *sage.categories.topological_spaces*), 739

TopologicalSpaces.Compact (class in *sage.categories.topological_spaces*), 739

TopologicalSpaces.Compact.CartesianProducts (class in *sage.categories.topological_spaces*), 739

TopologicalSpaces.Connected (class in *sage.categories.topological_spaces*), 739

TopologicalSpaces.Connected.CartesianProducts (class in *sage.categories.topological_spaces*), 739

740
 TopologicalSpaces.SubcategoryMethods (class in sage.categories.topological_spaces), 740
 TopologicalSpacesCategory (class in sage.categories.topological_spaces), 740
 trailing_coefficient() (sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods method), 599
 trailing_item() (sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods method), 600
 trailing_monomial() (sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods method), 600
 trailing_support() (sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods method), 601
 trailing_term() (sage.categories.modules_with_basis.ModulesWithBasis.ElementMethods method), 601
 TriangularKacMoodyAlgebras (class in sage.categories.triangular_kac_moody_algebras), 740
 TriangularKacMoodyAlgebras.ElementMethods (class in sage.categories.triangular_kac_moody_algebras), 740
 TriangularKacMoodyAlgebras.ParentMethods (class in sage.categories.triangular_kac_moody_algebras), 741
 trivial_representation() (sage.categories.semigroups.Semigroups.Algebras.ParentMethods method), 674
 trivial_representation() (sage.categories.semigroups.Semigroups.ParentMethods method), 679
 truncate() (sage.categories.filtered_modules_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ElementMethods method), 330
 twisted_invariant_module() (sage.categories.finite_dimensional_modules_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ParentMethods method), 412
 type_to_parent() (in module sage.categories.pushout), 153

U
 uncamelcase() (in module sage.categories.category_with_axiom), 98
 uniformizer() (sage.categories.discrete_valuation.DiscreteValuationFields.ParentMethods method), 296
 uniformizer() (sage.categories.discrete_valuation.DiscreteValuationRings.ParentMethods method), 297
 UniqueFactorizationDomains (class in sage.categories.unique_factorization_domains), 742
 UniqueFactorizationDomains.ElementMethods (class in sage.categories.unique_factorization_domains), 742
 UniqueFactorizationDomains.ParentMethods (class in sage.categories.unique_factorization_domains), 743
 Unital (sage.categories.associative_algebras.AssociativeAlgebras attribute), 187
 Unital (sage.categories.distributive_magmas_and_additive_magmas.DistributiveMagmas attribute), 298
 Unital (sage.categories.magma_magmatic_algebras.MagmaticAlgebras attribute), 567
 Unital (sage.categories.semigroups.Semigroups attribute), 683
 UnitalAlgebras (class in sage.categories.unital_algebras), 744
 UnitalAlgebras.ParentMethods (class in sage.categories.unital_algebras), 744
 UnitalAlgebras.WithBasis (class in sage.categories.unital_algebras), 744
 UnitalAlgebras.WithBasis.ParentMethods (class in sage.categories.unital_algebras), 744
 universal_commutative_algebra() (sage.categories.finite_dimensional_lie_algebras_with_basis.FiniteDimensionalLieAlgebrasWithBasis.ElementMethods method), 403
 universal_enveloping_algebra() (sage.categories.lie_algebras.LieAlgebras.ParentMethods method), 528
 UniversalEnvelopingAlgebra (class in sage.categories.universal_enveloping_algebras), 403
 unrank() (sage.categories.enumerated_sets.EnumeratedSets.ParentMethods method), 305
 unrank() (sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods method), 418
 unrank_range() (sage.categories.enumerated_sets.EnumeratedSets.ParentMethods method), 306
 unrank_range() (sage.categories.finite_enumerated_sets.FiniteEnumeratedSets.ParentMethods method), 421
 unset_base_point() (sage.categories.simplicial_sets.SimplicialSets.ParentMethods method), 720
 upper_covers() (sage.categories.coxeter_groups.CoxeterGroups.ElementMethods method), 257
 upper_covers() (sage.categories.posets.Posets.ParentMethods method), 636

V
 valuation() (sage.categories.complete_discrete_valuation.CompleteDiscreteValuationFields.ParentMethods method), 215

- `valuation()` (*sage.categories.complete_discrete_valuation.CompleteDiscreteValuationRings.ElementMethods* method), 217
`valuation()` (*sage.categories.discrete_valuation.DiscreteValuationFields.ElementMethods* method), 296
`valuation()` (*sage.categories.discrete_valuation.DiscreteValuationRings.ElementMethods* method), 297
`vector_space()` (*sage.categories.fields.Fields.ParentMethods* method), 313
VectorBundles (class in *sage.categories.vector_bundles*), 746
VectorBundles.Differentiable (class in *sage.categories.vector_bundles*), 746
VectorBundles.Smooth (class in *sage.categories.vector_bundles*), 746
VectorBundles.SubcategoryMethods (class in *sage.categories.vector_bundles*), 746
VectorFunctor (class in *sage.categories.pushout*), 144
VectorSpaces (class in *sage.categories.vector_spaces*), 747
VectorSpaces.CartesianProducts (class in *sage.categories.vector_spaces*), 747
VectorSpaces.DualObjects (class in *sage.categories.vector_spaces*), 748
VectorSpaces.ElementMethods (class in *sage.categories.vector_spaces*), 748
VectorSpaces.Filtered (class in *sage.categories.vector_spaces*), 748
VectorSpaces.Graded (class in *sage.categories.vector_spaces*), 748
VectorSpaces.ParentMethods (class in *sage.categories.vector_spaces*), 748
VectorSpaces.TensorProducts (class in *sage.categories.vector_spaces*), 748
VectorSpaces.WithBasis (class in *sage.categories.vector_spaces*), 749
VectorSpaces.WithBasis.CartesianProducts (class in *sage.categories.vector_spaces*), 749
VectorSpaces.WithBasis.Filtered (class in *sage.categories.vector_spaces*), 749
VectorSpaces.WithBasis.Graded (class in *sage.categories.vector_spaces*), 749
VectorSpaces.WithBasis.TensorProducts (class in *sage.categories.vector_spaces*), 749
`verma_module()` (*sage.categories.triangular_kac_moody_algebras.TriangularKacMoodyAlgebras.ParentMethods* method), 741
`vertices()` (*sage.categories.examples.graphs.Cycle* method), 821
`vertices()` (*sage.categories.graphs.Graphs.ParentMethods* method), 482
`virtualization()` (*sage.categories.crystals.CrystalMorphism* attribute), 273
W
`w0()` (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods* method), 788
`weak_covers()` (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods* method), 258
`weak_lattice()` (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods* method), 264
`weak_le()` (*sage.categories.coxeter_groups.CoxeterGroups.ElementMethods* method), 258
`weak_order_ideal()` (*sage.categories.coxeter_groups.CoxeterGroups.ParentMethods* method), 268
`weak_poset()` (*sage.categories.finite_coxeter_groups.FiniteCoxeterGroups.ParentMethods* method), 365
`weight()` (*sage.categories.crystals.Crystals.ElementMethods* method), 281
`weight()` (*sage.categories.regular_crystals.RegularCrystals.ElementMethods* method), 654
`weight_lattice_realization()` (*sage.categories.crystals.Crystals.ParentMethods* method), 292
`weight_lattice_realization()` (*sage.categories.loop_crystals.LoopCrystals.ParentMethods* method), 549
`WellGenerated()` (*sage.categories.finite_complex_reflection_groups.FiniteComplexReflectionGroups.ParentMethods* method), 348
`weyl_group()` (*sage.categories.kac_moody_algebras.KacMoodyAlgebras.ParentMethods* method), 513
WeylGroups (class in *sage.categories.weyl_groups*), 751
WeylGroups.ElementMethods (class in *sage.categories.weyl_groups*), 751
WeylGroups.ParentMethods (class in *sage.categories.weyl_groups*), 758
WithBasis (*sage.categories.algebras.Algebras* attribute), 181
WithBasis (*sage.categories.bialgebras.Bialgebras* attribute), 188
WithBasis (*sage.categories.coalgebras.Coalgebras* attribute), 202
WithBasis (*sage.categories.hopf_algebras.HopfAlgebras* attribute), 506
WithBasis (*sage.categories.lambda_bracket_algebras.LambdaBracketAlgebras* attribute), 516
WithBasis (*sage.categories.lie_algebras.LieAlgebras* attribute), 528
WithBasis (*sage.categories.lie_algebras.LieAlgebras.FiniteDimensional* attribute), 534
WithBasis (*sage.categories.lie_conformal_algebras.LieConformalAlgebras* attribute), 534
WithBasis (*sage.categories.modules.Modules* attribute), 589
WithBasis (*sage.categories.semisimple_algebras.SemisimpleAlgebras.FiniteDimensional* attribute), 685
WithBasis() (*sage.categories.modules.Modules.SubcategoryMethods* method), 587
WithRealizations() (in *sage.categories.with_realizations*), 788

WithRealizations() (*sage.categories.category.Category*
 method), 42
 WithRealizationsCategory (class in
 sage.categories.with_realizations), 792
 wrapped_class (*sage.categories.examples.finite_coxeter_groups.DihedralGroup.Element*
 attribute), 802
 wrapped_class (*sage.categories.examples.finite_monoids.IntegerModMonoid.Element*
 attribute), 811
 wrapped_class (*sage.categories.examples.finite_semigroups.LeftRegularBand.Element*
 attribute), 813
 wrapped_class (*sage.categories.examples.magnas.FreeMagma.Element*
 attribute), 828
 wrapped_class (*sage.categories.examples.monoids.FreeMonoid.Element*
 attribute), 830
 wrapped_class (*sage.categories.examples.posets.FiniteSetsOrderedByInclusion.Element*
 attribute), 832
 wrapped_class (*sage.categories.examples.semigroups.FreeSemigroup.Element*
 attribute), 833

X

xgcd() (*sage.categories.fields.Fields.ElementMethods*
 method), 312
 xgcd() (*sage.categories.quotient_fields.QuotientFields.ElementMethods*
 method), 643

Z

zero() (*sage.categories.additive_magnas.AdditiveMagnas.AdditiveUnital.CartesianProducts.ParentMethods*
 method), 162
 zero() (*sage.categories.additive_magnas.AdditiveMagnas.AdditiveUnital.Homsets.ParentMethods*
 method), 162
 zero() (*sage.categories.additive_magnas.AdditiveMagnas.AdditiveUnital.ParentMethods*
 method), 163
 zero() (*sage.categories.additive_magnas.AdditiveMagnas.AdditiveUnital.WithRealizations.ParentMethods*
 method), 164
 zero() (*sage.categories.examples.commutative_additive_monoids.FreeCommutativeAdditiveMonoid*
 method), 795
 zero() (*sage.categories.examples.finite_dimensional_lie_algebras_with_basis.AbelianLieAlgebra*
 method), 808
 zero() (*sage.categories.examples.lie_algebras.LieAlgebraFromAssociative*
 method), 825
 zero() (*sage.categories.modules.Modules.Homsets.ParentMethods*
 method), 583
 zeta_function() (*sage.categories.number_fields.NumberFields.ParentMethods*
 method), 623